Contents

- FOE
- manipulating bode diagram
- getting data from the bode function
- Modifying the script for approximating for a new tf:
- Problem 1):
- Aproximating the magnitude

```
% Introduction to Bode diagrams
```

FOE


```
k = 1;
T = 5;
H = tf(k, [T, 1]);
bode(H);
grid;
shg;
```

Bode Diagram (gg -10 -20 -40 -90 10⁻² 10⁻¹ Frequency (rad/s)

```
wu = 2;
Tu = 2*pi/wu;
t = 0:Tu/50:12*Tu;
lsim(H,sin(t.*wu),t);
hold;
```


```
yline(10^(-1),'r');
hold;
yline(-10^(-1),'r');
```

Current plot held
Current plot released




manipulating bode diagram

```
w = logspace(-3,2,1000);
bode(H,w);
grid;
shg;
```



getting data from the bode function


```
[m,ph] = bode(H,w);
mv = squeeze(m);
phv = squeeze(ph);
%ploting the bode diagram using {\tt mv} and {\tt phv} vectors:
%magnitude:
figure;
subplot(2,1,1);
semilogx(w,20*log10(mv));
% drawing an approximation
hold on;
semilogx([1e-3 1/5 2 20 100],[0 0 -20 -40 -54],'r*-',LineWidth=2);
hold off;
title("Magnitude characteristic");
xlabel('Frequencies \omega (lg)[rad/sec]');
ylabel('|H(j\omega)|^{dB}', 'FontSize', 14);
grid;
%phase:
subplot(2,1,2);
semilogx(w,phv,'b-');
hold on;
semilogx([1e-3 0.02 0.2 2 100],[0 0 -45 -90 -90],'r*-',LineWidth=2);
hold off
title("Phase characteristic");
xlabel('Frequencies \omega (lg)[rad/sec]');
```



Modifying the script for approximating for a new tf:


```
k = 2;
T = 5;
H = tf(k, [T 1]);
w = logspace(-3,3,1000);
[m,ph] = bode(H,w);
mv = squeeze(m);
phv = squeeze(ph);
% ploting the bode diagram using mv and phv vectors:
%magnitude:
figure;
subplot(2,1,1);
semilogx(w,20*log10(mv));
\% drawing an approximation
hold on;
semilogx([1e-3 1/5 2 20 100],[0 0 -20 -40 -54]+20*log10(k),'r*-',LineWidth=2);
hold off;
title("Magnitude characteristic");
xlabel('Frequencies \omega (lg)[rad/sec]');
ylabel('|H(j\omega)|^{dB}', 'FontSize', 14);
grid;
%phase:
```

```
subplot(2,1,2);
semilogx(w,phv,'b-');
hold on;
semilogx([1e-3 0.02 0.2 2 1000],[0 0 -45 -90 -90],'r*-',LineWidth=2);
hold off
title("Phase characteristic");
xlabel('Frequencies \omega (lg)[rad/sec]');
ylabel('\angle H(j\omega) [deg]', 'FontSize', 14);
grid;
```



Problem 1):


```
wn = 10;
df = 0.5;
H =tf(1,[1/wn^2 2*df/wn 1]);
figure;
bode(H);
grid;
shg;
% Proble: approximate the magnitude using the cheatsheet
%for smalle freq.<< wn the magnitude approx. 0 dB and
% for high freq.>> wn the magnitude is along an asymptote with
% a slope of -40 dB
```



Aproximating the magnitude

```
w = logspace(-3,3,1000);
[m, ph] = bode(H,w);
mv = squeeze(m);
phv = squeeze(ph);

figure;
semilogx(w,20*log10(mv));
hold on;
semilogx([1e-3 wn 100 1000],[0 0 -40 -80],'r*-', LineWidth=2);
title("Magnitude characteristic for second order tf");
xlabel('Frequencies \omega (lg)[rad/sec]');
ylabel('|H(j\omega)|^{dB}', 'FontSize', 14);
hold off;
grid
```



Published with MATLAB® R2022b