



PesaPal API Reference

<http://developer.pesapal.com>

Contents

PostPesapalDirectOrderV4	3
URL.....	3
Parameters:.....	3
Return Query Parameters	7
QueryPaymentStatus.....	7
URL.....	7
Parameters:.....	8
Return Value:.....	8
QueryPaymentStatusByMerchantRef	8
URL.....	8
Parameters:.....	8
Return Value:.....	9
QueryPaymentDetails.....	9
URL.....	9
Parameters:.....	9
Return Value:.....	10

PesaPal exposes the following API methods:

1. ***PostPesapalDirectOrderV4***

Use this to post a transaction to PesaPal. PesaPal will present the user with a page which contains the available payment options and will redirect to your site once the user has completed the payment process.

A tracking id will be returned as a query parameter – this can be used subsequently to track the payment status on pesapal for this transaction.

2. ***QueryPaymentStatus***

Use this to query the status of the transaction. When a transaction is posted to PesaPal, it may be in a PENDING, COMPLETED or FAILED state. If the transaction is PENDING, the payment may complete or fail at a later stage.

Both the unique order id generated by your system and the pesapal tracking id are required as input parameters.

3. *QueryPaymentStatus*

Same as *QueryPaymentStatus*, but only the unique order id generated by your system is required as the input parameter.

4. *QueryPaymentDetails*

Same as *QueryPaymentStatus*, but additional information is returned.

PostPesapalDirectOrderV4

URL:

<https://www.pesapal.com/API/PostPesapalDirectOrderV4>

Parameters:

oauth_callback = <url to the redirect page>

This is the page on your site the users will be redirected to, after they have made the payment on PesaPal. Example: <http://www.mysite.com/processingorder>

oauth_consumer_key = <your consumer key>

When you register as a merchant on PesaPal, you will receive your consumer key and secret via email.

Please Note: it is very important that you store the consumer secret safely.

oauth_nonce = <a unique id>

This must be unique for each PesaPal API request you make. Tip: a date-time based value may ensure uniqueness across all your requests.

oauth_signature = <OAuth signatue>

PesaPal uses the OAuth protocol to authenticate API requests. The request is signed using the Consumer Secret you received at registration.

You may download OAuth libraries for PHP and .Net from our downloads section. For a list of other OAuth libraries, please visit: <http://oauth.net/code/>

More information on OAuth can be found at oauth.net or in the [Beginner's Guide to OAuth](#) from Hueniverse.

oauth_signature_method = HMAC-SHA1

oauth_timestamp = <number of seconds since January 1, 1970 00:00:00 GMT, also known as Unix Time>

oauth_version = 1.0

pesapal_request_data = <XML formatted order data >

Schema:

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  attributeFormDefault="unqualified"
  elementFormDefault="qualified"
  targetNamespace="http://www.pesapal.com">
  <xsd:element name="PesapalDirectOrderInfo">
    <xsd:complexType>
      <xsd:sequence>
        <xsd:element name="LineItems" minOccurs="0" maxOccurs="1">
          <xsd:complexType>
            <xsd:sequence>
              <xsd:element minOccurs="1" maxOccurs="unbounded" name="LineItem">
                <xsd:complexType>
                  <xsd:attribute name="UniqueId" type="xsd:string" use="required" />
                  <xsd:attribute name="Particulars" type="xsd:string" use="required" />
                  <xsd:attribute name="Quantity" type="xsd:unsignedInt" use="required" />
                  <xsd:attribute name="UnitCost" type="xsd:decimal" use="required" />
                  <xsd:attribute name="SubTotal" type="xsd:decimal" use="required" />
                </xsd:complexType>
              </xsd:element>
            </xsd:sequence>
          </xsd:complexType>
        </xsd:element>
      </xsd:sequence>
      <xsd:attribute name="Amount" type="xsd:decimal" use="required" />
      <xsd:attribute name="Currency" use="optional" >
        <xsd:simpleType>
          <xsd:restriction base="xs:string">
            <xsd:pattern value="[A-Za-z][A-Za-z][A-Za-z]"/>
          </xsd:restriction>
        </xsd:simpleType>
      </xsd:attribute>
      <xsd:attribute name="Description" type="xsd:string" use="required" />
      <xsd:attribute name="Type" use="required" >
        <xsd:simpleType>
          <xsd:restriction base="xsd:string">
            <xsd:enumeration value="MERCHANT"/>
            <xsd:enumeration value="ORDER"/>
          </xsd:restriction>
        </xsd:simpleType>
      </xsd:attribute>
      <xsd:attribute name="Reference" type="xsd:string" use="required" />
      <xsd:attribute name="FirstName" type="xsd:string" use="optional" />
      <xsd:attribute name="LastName" type="xsd:string" use="optional" />
      <xsd:attribute name="Email" type="xsd:string" use="required" />
      <xsd:attribute name="PhoneNumber" type="xsd:string" use="optional" />
    </xsd:complexType>
  </xsd:element>
</xs:schema>
```

When testing integration with PesaPal, you may use this schema to validate the XML you generate.

Required XML Attributes:

Amount = <the total amount of the order>

Description = <the description of the order>

Type = <MERCHANT|ORDER>

MERCHANT: use this by default.

ORDER: use this if your order meets the following requirements:

1. The order needs to be shipped
2. The customer has the option to verify the delivery as satisfactory
3. The payment is held in escrow until the completion of the delivery and acceptance process.

Please Note: if you use ORDER, it requires you to mark the order as SHIPPED and DELIVERED via your PesaPal merchant console.

Reference = <a unique order id>

Please Note: this reference MUST be unique for each transaction that is posted to PesaPal. You will use this reference to query the status of the transaction later on, so this value must be stored on your system.

Email = <the email of the customer>

OR

PhoneNumber = <the phone number of the customer>

ONE of Email or PhoneNumber is required.

Optional XML Attributes

Currency = <ISO code for the currency>

By default, this is set to your country's currency. For example, if you registered as a merchant in Kenya, it would be KES (UGX for Uganda, TZA for Tanzania, and so on).

However, if you wish to transact in a different currency (such as USD), you may specify the three letter ISO code for that currency.

Please Note: PesaPal will request payment from the customer in the currency you specified where possible. If the payment option the customer selects does not support that currency, PesaPal will convert the amount using the day's exchange rate and present the amount in the local currency to the user.

FirstName = <first name of the customer>

LastName = <last name of the customer>

Email = <the email of the customer>

OR

PhoneNumber = <the phone number of the customer>

ONE of Email or PhoneNumber is required. The other can be set optionally.

Optional XML Element

LineItems = <a list of items purchased by the customer>

MUST have one or more child elements. Example:

```
<LineItem UniqueId="1" Particulars="Item 1" Quantity="6" UnitCost="10.00"
SubTotal="60.00" />
```

Required Attributes

UniqueId = <unique id of the purchased item>

Particulars = <description of the item>

Quantity = <quantity purchased>

UnitCost = <cost per unit of the purchased item>

SubTotal = <Quantity x UnitCost>

Sample 1:

```
<?xml version="1.0" encoding="utf-8"?>
<PesapalDirectOrderInfo
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  Amount="100.00"
  Description="Order payment"
  Type="MERCHANT"
  Reference="12"
  FirstName="Foo"
  LastName="Bar"
  Email="foo@bar.com"
  xmlns="http://www.pesapal.com" />
```

Sample 2:

```
<?xml version="1.0" encoding="utf-8"?>
<PesapalDirectOrderInfo
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
```

```

Amount="125.00"
Currency="USD"
Description="Order payment for order ACD09"
Type="MERCHANT"
Reference="ACD09"
FirstName="Foo"
LastName="Bar"
Email="foo@bar.com"
PhoneNumber="254722111111"
xmlns="http://www.pesapal.com">
<LineItems>
  <LineItem UniqueId="1" Particulars="Item 1" Quantity="6" UnitCost="10.00"
SubTotal="60.00" />
  <LineItem UniqueId="2" Particulars="Item 2" Quantity="1" UnitCost="5.00"
SubTotal="5.00" />
  <LineItem UniqueId="3" Particulars="Item 3" Quantity="2" UnitCost="30.00"
SubTotal="60.00" />
</LineItems>
</PesapalDirectOrderInfo>

```

Return Query Parameters

Once the payment process has been completed by the user, PesaPal will redirect to your site using the url you specified in the **oauth_callback** parameter. The following two values are returned in the query string:

pesapal_merchant_reference: this is the reference (a unique order id), that you passed to PesaPal when posting the transaction.

pesapal_transaction_tracking_id: this is the unique tracking id for this transaction on PesaPal.

You will need to send PesaPal both these values when subsequently querying for payment status or details. So, store *the pesapal_merchant_reference* against your order in your database.

Example:

Let's say that the **oauth_callback** parameter you specified is: *http://www.mysite.com/processingorder* and the **reference** you specified is *12345*.

PesaPal will redirect to a url with the following format once the payment is completed:

http://www.mysite.com/processingorder? pesapal_transaction_tracking_id=195035be-56bb-48ba-8439-7e12196cb87e&pesapal_merchant_reference=12345

QueryPaymentStatus

Once the transaction has been posted to PesaPal, you may use *QueryPaymentStatus* to query the status of the payment.

URL:

<https://www.pesapal.com/API/QueryPaymentStatus>

Parameters:

oauth_consumer_key = <your consumer key>

oauth_nonce = <a unique id>

oauth_signature = <OAuth signature>

oauth_signature_method = HMAC-SHA1

oauth_timestamp = <number of seconds since January 1, 1970 00:00:00 GMT (also known as Unix Time)>

oauth_version = 1.0

pesapal_merchant_reference = <the *Reference* you sent to PesaPal when posting the transaction>

This is the a unique order id that you sent as *Reference* in the *pesapal_request_data* XML when posting the transaction.

pesapal_transaction_tracking_id = <the id returned to you by PesaPal (as a query parameter) when redirecting to your website>

Return Value:

The status of the payment is returned as follows:

pesapal_response_data =<PENDING|COMPLETED|FAILED|INVALID>

A return value of INVALID indicates that the transaction with the *Reference* you provided could not be found.

If you receive a return value of PENDING, you will have to query PesaPal again, until you receive COMPLETED or FAILED as the response.

QueryPaymentStatusByMerchantRef

Same as *QueryPaymentStatus* above, but *pesapal_transaction_tracking_id* is not required.

URL:

<https://www.pesapal.com/API/QueryPaymentStatusByMerchantRef>

Parameters:

oauth_consumer_key = <your consumer key>

oauth_nonce = <a unique id>

oauth_signature = <OAuth signature>

oauth_signature_method = HMAC-SHA1

oauth_timestamp = <number of seconds since January 1, 1970 00:00:00 GMT (also known as Unix Time)>

oauth_version = 1.0

pesapal_merchant_reference = <the *Reference* you sent to PesaPal when posting the transaction>

This is the a unique order id that you sent as *Reference* in the *pesapal_request_data* XML when posting the transaction.

Please note: if you don't ensure that the *Reference* is unique for each order on your system, you may get INVALID as the response. Because of this, it is recommended that you use *QueryPaymentStatus* instead.

Return Value:

The status of the payment is returned as follows:

pesapal_response_data = <PENDING|COMPLETED|FAILED|INVALID>

A return value of INVALID indicates that the transaction with the *Reference* you provided could not be found.

If you receive a return value of PENDING, you will have to query PesaPal again, until you receive COMPLETED or FAILED as the response.

QueryPaymentDetails

Same as *QueryPaymentStatus* above, but the return value contains more information.

URL:

<https://www.pesapal.com/API/QueryPaymentDetails>

Parameters:

oauth_consumer_key = <your consumer key>

oauth_nonce = <a unique id>

oauth_signature = <OAuth signatue>

oauth_signature_method = HMAC-SHA1

oauth_timestamp = <number of seconds since January 1, 1970 00:00:00 GMT (also known as Unix Time)>

oauth_version = 1.0

pesapal_merchant_reference = <the *Reference* you sent to PesaPal when posting the transaction>

This is the a unique order id that you sent as *Reference* in the *pesapal_request_data* XML when posting the transaction.

pesapal_transaction_tracking_id = <the id returned to you by PesaPal (as a query parameter) when redirecting to your website>

Return Value:

Four values are returned as a comma separated string, as follows:

pesapal_response_data =
pesapal_transaction_tracking_id,payment_method,payment_status,pesapal_merchant_reference

pesapal_transaction_tracking_id: this is the same as the parameter you sent when making the query

payment_method: the payment method used by the user to make the payment

payment_status: one of <PENDING|COMPLETED|FAILED|INVALID>

pesapal_merchant_reference: this is the same as the parameter you sent when making the query

Example

pesapal_response_data=195035be-56bb-48ba-8439-7e12196cb87e,MPESA,PENDING,12345

If you receive a return value of PENDING for payment_status, you will have to query PesaPal again, until you receive COMPLETED or FAILED as the response.