
CONCEPTUAL ARCHITECTURE / FORMAL SPECIFICATION

The Multiplex
Y-Switch Paradigm

Seed, father / mother inversion, complex representations,
palindrome, repetition and bounded acknowledgment.

> Preserve the origin. Define the transformation.
> Route explicitly. Commit once. Record the acknowledgment.



`dooh hood / ACK_PREPARED / ACK_COMMITTED`

Concept and source vocabulary

Tom Klootwijk
Author-supplied reference: **NL200678942**
Author-supplied date: **10-07-1990** (DD-MM-YYYY).

Version 1.0 | 23 October 2026 | English with original Dutch source terms.
Formalization prepared with AI assistance from two attached transcripts and the accompanying message.

Status: a proposed, source-traceable conceptual specification. Formal definitions added in this edition are identified as proposals; source metaphors and measured claims retain distinct evidence status.

What this paradigm specifies

The Multiplex Y-Switch Paradigm organizes a heterogeneous set of ideas around a shared information pattern: an originating seed produces two labeled representations; explicit transformations act on them; a routing policy selects or combines their results; a guarded transition records one accepted outcome. Repetition preserves traceability rather than silently multiplying effects.

```
Architecture = provenance + typed transformations + explicit routing
+ guarded state transitions + bounded receipts
```

The words **father** and **mother** name peer branches in this edition. They do not prescribe gendered functions. The seed denotes a source snapshot. A child or descendant denotes a derived record. These meanings are editorial definitions offered to make the supplied vocabulary usable and testable. [S0; S1.24-S1.26]

The six commitments

Commitment	Resulting behavior
Preserve origin	Keep raw source text, source spans, model version and parent references.
Define the inverse	Name the operator: branch exchange, reflection, conjugation, reciprocal or string reversal.
Type every interface	Record representation, units, reference frame, clock domain and evidence status where applicable.
Declare the Y mode	Selection, demultiplexing, copying and merging have separate contracts.
Separate ready from done	Checkpoint 9 records preparation; checkpoint 10 records the committed result.
Bound repetition	Retries reuse an operation identity; feedback creates an explicitly new revision.

Reading route

Pages 4-10 define the architecture. Pages 11-17 translate and audit the technical and symbolic source material. Pages 18-19 provide a worked example and acceptance criteria. Pages 20-25 preserve source coverage, open definitions and references.

Nederlandse kern: bewaar de bron; benoem de spiegeling; scheid de twee takken; kies een expliciete schakel- of samenvoegregel; bevestig voorbereiding en vastlegging afzonderlijk.

Source corpus and interpretation

This edition synthesizes all three supplied source groups. It does not treat every earlier AI response as a statement made or endorsed by the author. Short user prompts, longer AI expansions, calculations and source links are recorded separately.

Source	Contents and status
S0 Current message	Physical SIM/eSIM; Assad, Syria, Peshmerga and push/merge wordplay; viper/ader/adelaarlijk/kraaienpoot; Abraham and Leviathan; the final seed/father/mother/nine/ten/dooh/hood/ACK request.
S1 First attachment	Pasted text(20261023-051705).txt 1,755 lines; 130,399 bytes. Long conversational chain from whistle and clocks to Y routing, lineage and a one-time clover exit.
S2 Second attachment	Pasted text (2).txt 249 lines; 18,356 bytes. Copying, geometry, biomechanical analogies, structural tables, compass, optics, OBS and biological tables.

Evidence labels used throughout


Label	Meaning
SOURCE	A phrase or assertion occurs in the supplied material. This establishes its provenance, not its truth.
PROPOSAL	A new definition or rule chosen in this formalization. It remains editable by the author.
DERIVED	A mathematical consequence under stated definitions or assumptions, checked in this edition.
VERIFIED	A limited background claim supported by an identified primary source [R1-R9].
UNRESOLVED	Meaning, evidence, parameter, or implementation is missing. It is retained without an invented explanation.

Editorial boundary. Mother, seed, nine/ten, dooh/hood and ACK ACK do not receive formal definitions in the attachments. Their operational meanings in this document are proposals derived from the latest request. The father/grandfather/son motifs occur in S1.24-S1.26.

Attachment line references are one-based and refer to the supplied copies. Byte counts and SHA-256 fingerprints appear on page 25. The pasted message is referenced by topic because it has no supplied line numbering.

A shared pattern with typed boundaries

The diagram describes a proposed information architecture. Every edge carries a declared type. A physical or biological interpretation requires its own adapter, evidence and measurements; the common shape alone does not supply those mechanisms.



Layer	Responsibility
Origin	Freeze the source snapshot and preserve the author vocabulary.
Transformation	Produce F and M with named functions. Log parameters and assumptions.
Routing	Choose MUX, DEMUX, COPY or JOIN; resolve conflicts under an explicit policy.
Decision	Check compatibility and record the exact candidate at checkpoint 9.
Commit	Record the accepted result at checkpoint 10 and return a terminal receipt.

A feedback edge, when enabled, returns a result as the input to a new revision. It does not rewrite the frozen seed or pretend that the previous event did not occur. A rejected candidate retains its reason and source lineage.

The seed and the provenance record

PROPOSAL. A seed is the immutable input snapshot for a run: selected source bytes, a schema version, model version and declared parameters. A pseudorandom generator seed, if needed later, is a separate field named `rng_seed`. The two uses of the word seed are not interchangeable.

```
A = (S, D, G, O, Q, delta, L)
S: source manifest D: types G: directed graph
O: operators Q: control states
delta: guarded transitions L: append-only ledger
```

Record field	Required meaning
id / seed_id	Stable identity for the record and its originating snapshot.
source / span / raw	The attachment or message topic, exact span, and retained original text.
normalized	Optional edited representation, stored alongside the raw text.
type / unit / frame	Payload schema; units and coordinate frame when they apply. Use explicit not-applicable values.
clock / event_seq	Timestamp with clock domain, plus causal or sequence information.
operator / parameters	Named transformation, version and inputs needed to reproduce it.
parents / version	Earlier records used in the derivation, plus a monotonically advancing revision.
status / evidence	SOURCE, PROPOSAL, DERIVED, VERIFIED or UNRESOLVED, with references.

Three invariants

Immutability: editing a seed produces a new seed identity. **Traceability:** every derived record points to its inputs. **Meaning preservation:** changing representation does not silently upgrade an unresolved claim to a verified one.

Parentage for derivation is acyclic: a record can depend on earlier versions, never on its own future result. A hash detects changed bytes under the chosen encoding; it does not authenticate a person or establish ownership. [DERIVED / PROPOSAL]

What “inverse” can mean

The source uses mirror, inverse, reversal and rotation across several domains. This edition gives each operation its own symbol and domain. Calling M the mother branch does not imply that its function is the mathematical inverse of F.

Operator	Definition	Restoration property
Branch exchange J	J(a,b) = (b,a)	J(J(a,b)) = (a,b)
Plane reflection R	R(x,y) = (x,-y)	R(R(x,y)) = (x,y)
Complex conjugation C	C(a+bi) = a-bi	C(C(z)) = z
Reciprocal K	K(z) = 1/z, z != 0	K(K(z)) = z
String reversal rev	Reverse a declared sequence of characters or tokens.	rev(rev(w)) = w
Quarter-turn Q	Q(x,y) = (-y,x)	Q^4 = I; Q^2 != I in general

A concrete complex example

```
z = 3 + 4i
C(z) = 3 - 4i
K(z) = (3 - 4i)/25 = 0.12 - 0.16i
```

Conjugation is reflection across the real axis after identifying z with the point (x,y). Reciprocal also changes magnitude unless |z| = 1. A true inverse f^{-1} requires a one-to-one mapping on the declared domain. Averaging two values generally loses information and cannot recover both values without retained data. [DERIVED]

Reflection and physical transport

For a consistent coordinate reflection, set x' = Rx, u' = Ru and grad' = R grad. Orthogonality gives (Ru) dot (R grad) = u dot grad. The advective operator keeps its form. Turning a real device relative to gravity is a different physical experiment. Convection/advection terminology depends on context; reflection does not exchange the mechanisms. [R7; S1.03, S1.06-S1.07]

The multiplex Y-switch

PROPOSAL. A Y is a junction with three incident arms: one common path and two branches. Geometry does not determine which operation happens there. The mode must be part of the state.

Mode	Contract	Information behavior
MUX / select	mux_0(a,b)=a mux_1(a,b)=b	One branch is selected. Keep provenance for the unselected candidate.
DEMUX / route	demux_0(x)=(x,empty) demux_1(x)=(empty,x)	One payload goes to one selected destination. Empty is an explicit absence marker.
COPY / fan-out	copy(x)=(x,x)	Two digital representations share a source identity. This is not a physical power claim.
JOIN / retain pair	join(a,b)=<a,b>	Both contributions remain recoverable when boundaries and types are stored.
RESOLVE / combine	resolve(a,b,policy)=c	A policy determines the result. Loss, conflict handling and assumptions must be declared.

Father/mother exchange preserves a selected payload

```
mux_(1-u)(b,a) = mux_u(a,b), u in {0,1}
```

Swapping the two branch labels and complementing the selector preserves the chosen value. Swapping labels alone usually changes the result. This is a precise, testable interpretation of father/mother inversion. [DERIVED]

Physical and semantic boundaries

A documented physical example is TI's SN74LVC1G3157: a common terminal connects to one selected branch, with signaling permitted in either direction and specified break-before-make behavior. These are properties of that device. They do not imply that every Y diagram is optical, reversible or instantaneous. [R4]

MIDI messages, acoustic measurements, optical power and personal narratives need different encoders and payload schemas. They cannot be added as raw interchangeable quantities. An optical split requires its own power balance; a digital COPY does not duplicate optical energy. [S1.17; S2.05-S2.06]

Nine preparation stages; tenth commit

PROPOSAL. “Nine ten” names a transition from checkpoint 9, PREPARED, to checkpoint 10, COMMITTED. The ten stages below are a design convention, not an interpretation forced by the source or a numerical law. Data, counters and the ledger make this an extended finite-state machine.

Stage	State	Condition before advancing
1	CAPTURE	Source snapshot and identity exist.
2	TYPE	Payload schema and evidence status are declared.
3	FRAME	Normalization, units, frame and clock are fixed or explicitly not applicable.
4	F_BRANCH	The father-labeled candidate is evaluated and recorded.
5	M_BRANCH	The mother-labeled candidate is evaluated and recorded.
6	ROUTE	Mode and selector are declared; the selected path is recorded.
7	RESOLVE	JOIN/merge policy produces a candidate, or selection is retained unchanged.
8	VALIDATE	Type, provenance, policy and domain-specific checks pass.
9	PREPARED	Exact candidate, digest, base version and preparation expiry are recorded.
10	COMMITTED	Atomic commit succeeds; result version and terminal receipt are durable.


```
9 -- [matching digest + current version + valid policy] --> 10
any failed guard --> REJECTED, with a recorded reason
```

Stages 4 and 5 may be evaluated concurrently if they are independent; their logical records still exist separately. PREPARED is a readiness claim about an identified candidate. COMMITTED is a claim about the specified durable result boundary.

If delivery of the final receipt is uncertain, the caller enters UNKNOWN_PENDING_RECONCILIATION. That caller state does not change an already committed receiver state. A status query resolves the uncertainty when connectivity returns.

ACK ACK, without an endless loop

PROPOSAL. The two acknowledgments have distinct meanings: **ACK_PREPARED** identifies a candidate accepted for commit; **ACK_COMMITTED** identifies its durable result. They carry the same operation ID and candidate digest. A receipt is terminal at its declared stage.



Case	Required behavior
Same ID, same digest	Return the recorded status or result; do not repeat the committed effect.
Same ID, different digest	Reject the identity conflict. A changed request needs a new operation ID.
Stale base version or expiry	For a first commit, reject or re-prepare under an explicit new request.
Lost final receipt	Query/retry the same operation within a finite retry budget and deadline.
Retry budget exhausted	Report uncertainty and retain reconciliation data; do not invent success or failure.

Retry precedence. If an operation is already COMMITTED and its digest matches, return the stored result before checking preparation expiry or the original base version. Those guards apply only to a first commit.

Atomic boundary. Atomically check the expected version, apply the result and record deduplication state. Retain that state for the permitted retry horizon. External effects need an idempotent adapter or recovery protocol. Two receipts alone do not establish distributed exactly-once execution.

This application protocol is separate from TCP. RFC 9293 describes cumulative byte acknowledgments and explains that a pure ACK consumes no sequence space, avoiding an endless acknowledgment chain. TCP receipt does not certify application completion. [R5]

Dooh / hood; palindrome and repeat

These literal observations are derived directly from the supplied text. The counting unit here is an ASCII character, including spaces; token-level and character-level symmetry are different tests. [S0]

Expression	Exact result	Classification
rev("dooh")	"hood"	Reversal pair
rev("hood")	"dooh"	Reversal pair
"doohhood"	8 characters; equals its reversal	Character palindrome
"dooh hood"	9 characters, including one central space; equals its reversal	Character palindrome
"ack ack"	Reverses to "kca kca"	Repetition, not a character palindrome
["ack", "ack"]	Same token sequence after reversing token order	Token palindrome

```
P(w) = w + rev(w)
P_c(w) = w + c + rev(w), where c is one character
rev(P(w)) = P(w); rev(P_c(w)) = P_c(w)
```

Setting w = "dooh" and c = a space constructs the nine-character phrase. This literal nine is independent of stage 9 in the protocol. The proposed tenth stage records completion; it does not add a tenth character or reveal a hidden rule.

Repetition has two different identities

Retry: the same operation ID asks about the same intended effect. **Iteration:** a new revision applies a transition to a prior result, with a new operation ID and a parent link. A palindrome says something about representation; it does not prove that a real-world operation is reversible.

```
x_(k+1) = T(x_k; parameters_k)
stop if k reaches K_max, a terminal state is reached,
or a declared convergence condition is satisfied.
```

Convergence is not automatic. An enforced finite step or retry cap bounds execution. Other stopping conditions require a separate termination argument; a guard that may never become true is not enough. [DERIVED / PROPOSAL]

Clocks, cadence and sampling

Whistle, football, chemical clock, atomic clock, tau/mu, conductor, MIDI, VR and OBS appear as timing motifs. Their useful architectural connection is a separation between event order, measured time and periodic signal phase. [S1.01-S1.05, S1.14-S1.16; S2.01]

Quantity	Meaning in this architecture
Wall-clock time	A timestamp for reporting, with timezone and clock source.
Monotonic elapsed time	A duration source for deadlines and timeouts.
Logical sequence	Order or causal dependency between records.
Sample clock	The declared interval between observations in one stream.
Signal phase	Position within a periodic model; not a timestamp by itself.

Lamport's happens-before relation gives a partial order. If a precedes b causally, a consistent logical clock has C(a) < C(b); the inequality alone does not prove causation. [R6]

What 240 to 120 actually says

```
Input interval: 1/240 s = 4.1667 ms
Output interval: 1/120 s = 8.3333 ms
Simple paired average: y[n] = (x[2n] + x[2n+1])/2
```

The paired average is a lossy filter followed by decimation. Pairs (0,2) and (1,1) both yield 1. The inverse cannot recover the pair from that output alone. Two alternating channels can each have 120 observations per second, but they are offset in time and are not automatically interchangeable samples of one signal. [DERIVED; S1.23]

A chosen anti-alias filter, sample alignment and compatible quantities are needed for a defensible resampling design. Pairwise averaging does not guarantee arbitrary noise cancellation. Multiplying a signal and its noise by the same factor does not by itself improve their ratio. The source's hardware rates and zero-latency claims are not adopted as specifications.

Frames, sensing and uncertainty

The source connects acoustic ITD/IPD, infrared, radio, cell towers, Doppler, RSSI, compass orientation and a world frame. These can share a record interface while retaining distinct observation models. A single index lookup does not make all sensor measurements equivalent. [S1.18-S1.21; S2.04]

```
observation_j = (value, unit, frame, timestamp,
clock_domain, uncertainty, source_id)
y_j = h_j(x, parameters_j) + error_j
```

Source motif	Formal treatment
Time of flight	Declare one-way or round-trip timing, propagation speed, clock offsets and processing delay.
ITD / IPD	Keep inter-channel delay and phase as distinct observations. A phase needs a frequency and an ambiguity model.
Triangulation / ranges	Angle-based and range-based localization have different models. Two ranges in a plane may leave two intersections.
Doppler	Treat frequency shift as an observation of relative radial motion; it is not a unique position correction.
RSSI / parabolic array	Record signal strength and calibration. Selection also needs freshness, validity and uncertainty.
Marine compass	Represent orientation and calibration in a named reference frame. Do not infer a standard meaning for the token "Z A".

A minimal timing distinction

```
Ideal one-way range: R = c * t_oneway
Ideal round-trip range: R = c * (t_roundtrip - delay)/2
```

These expressions assume the chosen propagation model and known delay. Mixing one-way and round-trip definitions introduces a factor-of-two error before any fusion algorithm runs. A coordinate conversion must transform the data, axes and uncertainty consistently. [DERIVED]

No device-specific accuracy, global position guarantee, haptic safety claim or physical controller tuning is implied by this conceptual interface. The source does not supply a calibrated instrument or plant model.

Domain warp, WFC and a bounded LUT

A domain warp is represented here as a declared coordinate map phi(x) = x + g(x), followed by composition f(phi(x)). If invertibility is required, it must be established for that map and domain. A warped drawing alone does not satisfy fluid equations or change physical boundaries. [S1.07-S1.10]

Correcting the log-polar index

```
rho = log((r + epsilon) / r_ref)
rho_min = log(epsilon / r_ref)
rho_max = log((r_max + epsilon) / r_ref)
i = clip(floor((rho-rho_min)/(rho_max-rho_min)
* (N_r-1)), 0, N_r-1)
```

Require r >= 0, epsilon > 0 and r_ref > 0 in the same length unit, with r_max > 0. The normalization subtracts the minimum log radius used when building the table. The source code omits that offset. A dimensionless log argument and explicit out-of-domain behavior make the lookup contract reproducible. [DERIVED; S1.08]

Operation	Defensible cost / condition
One indexed fetch	O(1) under a fixed representation and random-access model.
N sample queries	O(N) work, even if the implementation uses vectorized array operations.
H by W grid minimum	O(HW) inspected cells for a full grid scan.
Table construction	Time and storage scale with table resolution and the model used to fill it.
Approximation quality	Requires interpolation policy, domain limits, error measurement and versioned parameters.

WFC-style tile compatibility is a procedural constraint. Physical continuity, conservation and stability require additional equations and boundary checks. Precomputation can reuse a model efficiently; it cannot establish that model's physical accuracy.

For a hypothetical scalar numerical function only, a bounded nearest-grid error can be derived when the function has a known Lipschitz bound. The source provides no such bound for its proposed material or signal fields.

Migration, merge and runtime change

Physical SIM to eSIM: an activation boundary

Apple documents conversion/transfer methods subject to carrier support; activating the replacement plan deactivates the preceding SIM. The useful analogy is a stateful reassignment of a subscription to a new profile. The paradigm records the old profile, candidate profile, activation result and effective version. It makes no universal promise about timing, downtime or reversing that carrier action. [R1; S0]

Git: reconciliation and remote publication

Git merge integrates changes into the current branch; git push updates remote references and transfers needed objects. They are separate operations. A repository adapter should track candidate history, conflict resolution, project checks, the chosen commit and the remote update result. A successful local merge does not establish that a push happened or that project policy passed. [R2-R3; S0]

Paradigm concept	Concrete software interpretation
Seed / parents	An input snapshot plus explicitly recorded source history.
F and M	Two candidate branches or representations, with no implied priority.
Resolver	A merge policy, including a conflict outcome.
Checkpoint 9	Checks passed for a particular candidate and expected base version.
Checkpoint 10	The selected durable change is recorded. Remote publication has its own result.

“J.I.T. comply”: a declared guard

PROPOSAL. Translate this phrase into a policy check at an activation boundary. “Comply” needs a named rule set, evidence and a decision owner. JIT compilation is not automatically an inverse of decompilation, a permissions system or proof of compliance. [S0; S1.22]

For a benign software prototype, validate a candidate version, prepare it, activate it under a version check and retain the prior version for an explicitly supported recovery. The source's label-lookup example does not demonstrate a real compiler, hard real-time behavior or zero-cost hot patching.

Lineage, branching and narrative

The following mappings preserve the source vocabulary as a design language. Each mapping is a proposal. It does not assert a hidden causal connection between the people, stories, products or physical systems named in the source.

Source motif	Usable symbolic role	Boundary
Father, mother, grandfather, son; Allfather / Bloodhound	Peer branches, ancestor records and derived outputs.	The lineage is record provenance. It makes no assertion about reincarnation or a person's mental state.
63 / 36 / 99 / 96	Digit reversal and explicitly chosen arithmetic labels.	rev("63")="36" and 63+36=99; no unique grandfather value follows.
Clover / quarter-turn / one-time exit	A four-state cycle plus a consumable authorization token.	Q^4=I is geometry. Exit permission is a separate rule, not a consequence of family identity or waveform.
Triple fang; viper; ader; adelaarlijk; kraaienpoot	Three-arm branching imagery and names for views.	Ader and adder are distinct words. The phrase does not establish an anatomical device or biological relation.
Abraham; seed; substitution; Leviathan	Origin, continuation, substitution and shared-name imagery.	Narrative interpretation is distinct from a documented connection to a modern vessel or owner.
Peshmerga / push merge; Syria	Mnemonic for organizational combination and staged transition.	Wordplay is not etymology; a political event does not validate software mathematics.

Finite cycles and explicit permission

The source's father-only clover exit can be represented as a fictional role policy: an allowed role may consume one unused exit token. The token, role policy and state transition must be declared independently. The original code does not establish that a sine wave cannot turn or that rotating sigma produces a knot. [S1.26]

For the numeric motif, the decimal digit sums of 63 and 36 are both 9; 99 reduces to 9 and 96 to 6 under repeated digit sum. Those are arithmetic operations. Any symbolic meaning is a separate author choice. Nine is the largest single decimal digit, not a largest number. [DERIVED; S1.25]

Arithmetic and assumptions

S2's first tube table supplies eccentricity e=10 mm and the formula sigma=F/A+Fe/Z. Recomputing that stated ideal model gives different numbers from the source. This check validates arithmetic under assumptions, not the applicability of the model to a component or body. [S2.03]

```
Inner diameter d = D - 2t
A = pi*(D^2-d^2)/4
I = pi*(D^4-d^4)/64; Z = I/(D/2)
sigma = F/A + F*e/Z [N/mm^2 = MPa]
```

D mm	t mm	F N	Source MPa	Recomputed MPa
20	2	1,000	85.06	30.41
20	2	3,000	255.19	91.22
30	3	3,000	92.51	30.96
40	2	5,000	69.83	44.08
50	5	5,000	36.32	13.97

Assumptions: circular, uniform, idealized tube; axial force with eccentric bending; consistent units; elementary linear stress expression. Material grade, anisotropy, buckling, fatigue, geometry details and dynamic loading are absent. The source's “Safe”/“Failure” labels and assumed bone strength are not adopted.

The biological chart does not reproduce its table

Domain	Table: normal / failure	Chart: normal / failure
Cell membrane	2.89 / 0.90	2.10 / 0.45
Spinal fluid	3.33 / 0.78	1.75 / 0.85
Skull vault	3.00 / 0.87	3.40 / 0.60

These are quoted source values for an internal-consistency comparison, not validated biological thresholds. The supplied material gives no adequate basis for the associated clinical outcomes. Likewise, the laser tables omit the absorption, cooling, geometry and material model needed to derive their stresses. [S2.05-S2.08]

Source claims and corrections

Source claim or shortcut	Treatment in the formalization
Reflection exchanges advection and convection.	Corrected: distinguish coordinate relabeling from physically reorienting a device. [S1.03, .06; R7]
Domain warp creates turbulence, channels or quantum-like spins.	Unestablished: retain a coordinate-map operation; require separate physics and measurements. [S1.07]
All vectorized/LUT operations are O(1), with no latency.	Corrected: cost depends on query count, grid size, build work and hardware. [S1.08, .18-.23]
The inverse-log expression proves lipid/carbohydrate freezing.	Unestablished: printed expression and code differ; domain, units and material evidence are missing. [S1.09-.10]
A Y-prism directly merges MIDI, acoustics and optics.	Require typed encoders, transducers, channel framing and separate routing/combining semantics. [S1.17]
Averaging eliminates interference; high RSSI guarantees a valid path.	Unestablished: preserve uncertainty, loss and freshness; require a measured quality model. [S1.20-.23]
JIT labels prove instant recompilation or physical control safety.	Unestablished: define versioned software transitions and a separately validated implementation. [S1.21-.22]
Numbers and lineage establish time reversal or reincarnation.	Retained as symbolic language; use string/arithmetic operations and provenance edges. [S1.24-.25]
Rotated sigma is a clover/knot; one waveform cannot turn.	Corrected: glyph resemblance is not topological proof; rotation and permission are separate. [S1.26]
Structural, optical and biological tables are validated limits.	Corrected arithmetic where assumptions permit; otherwise retain unverified source status. [S2.03-.08]

Source-history boundary: S1.11-S1.13 and related passages introduce speculative launcher, ablation and shock narratives. This edition records their release, gate and propagation motifs at an abstract level. Operational weapon construction, blast and damage calculations are not carried into the architecture.

Earlier source code is not treated as a verified implementation. For example, S1.26 contains an incomplete membership condition, and several other examples are array transformations presented as physical hardware.

One seed, two branches, one commit

This benign text example instantiates the complete proposed workflow. Its payload is a word, its inversion is character reversal, and its merge policy is concatenation with a declared central separator. No physical model is required.

Stage	Recorded value / decision
1 / CAPTURE	seed_id="example-001"; raw text="dooh"; model="Y-1.0".
2 / TYPE	Type: ASCII string. Evidence: SOURCE for the token, PROPOSAL for this workflow.
3 / FRAME	Preserve case and spaces. Unit, spatial frame and sample clock: not applicable.
4 / F_BRANCH	F(seed)="dooh". Record identity operator and parent seed.
5 / M_BRANCH	M(seed)=rev("dooh")="hood". Record reversal operator.
6 / ROUTE	Mode=RESOLVE. Both branch records are inputs; no MUX selection is implied.
7 / RESOLVE	Policy="concat-with-space-v1"; candidate="dooh hood".
8 / VALIDATE	String length=9; palindrome test passes; both parent references exist.
9 / PREPARED	Bind operation="demo-001", candidate digest, policy version, base version=0 and expiry. Emit ACK_PREPARED.
10 / COMMITTED	Atomically compare base version, store result and deduplication record, set version=1. Emit ACK_COMMITTED.

Repeat, reverse and conflict

A second delivery of demo-001 with the same candidate returns the version-1 result. It does not create version 2. Reusing demo-001 for a different candidate is rejected. An intentional new transformation uses a new operation ID and records version 1 as its parent.

The stored result reads the same when its characters are reversed. That representational symmetry is independent of committing the record: reversing the text does not remove it from the ledger. This keeps “palindrome,” “inverse” and “repeat” distinct. [DERIVED / PROPOSAL]

Invariants and acceptance criteria

The specification can be assessed at two levels: exact mathematical examples, which can be checked now, and implementation obligations, which need an actual system. A coherent notation does not certify an unbuilt physical or distributed system.

Check	Expected result	Status in this edition
J applied twice	Original branch ordering is restored.	Verified by direct examples and definition.
MUX exchange identity	Swapped inputs plus complemented selector preserve the selected payload.	Both selector values checked.
Palindrome construction	dooh hood equals its reverse and has 9 ASCII characters.	Directly checked.
Conjugate vs reciprocal	3-4i differs from 0.12-0.16i.	Directly checked.
Paired-average inversion	Different input pairs can share an output.	Counterexample checked.
Tube arithmetic	Recomputed values match page 16 to two decimals.	Independently recomputed.
Atomic commit and retry	Duplicate request never repeats the committed effect within the declared boundary.	Implementation requirement; no deployed system tested.
Physical/clinical performance	Model agrees with calibrated observations and relevant failure criteria.	Not established by the source material.

Required properties of a future implementation

Preserve raw sources; validate types and units; reject unsupported operators; retain parent links; prevent reuse of an operation ID for a different candidate; check expected versions; persist commit and deduplication state atomically; bound retries; and expose an explicit uncertainty outcome after communication failure.

If an external effect cannot participate in that atomic boundary, its adapter must define recovery and duplication behavior. A consumable exit token must be consumed in the same transaction as its effect. A finite retry limit guarantees stopping attempts, not eventual success.

```
Acceptance means: the declared contract is satisfied
under its stated assumptions, with evidence attached.
It does not upgrade the entire source corpus to fact.
```

S1: clocks through propagation

Inventory covers every major source segment. Later transcript prompts are apparent user seeds where the explicit “You said” marker is absent. “Use” indicates this edition's treatment, not an empirical conclusion.

ID / lines	Seed or motif	Use in this edition
S1.01 5-40	fluitje; voetbal; biomechanisch/biochemisch; tau/mu; chemical/atomic clocks	Clock domains and symbol discipline.
S1.02 42-70	mechanika van fluitje	Input, channel, edge and output as an interface motif.
S1.03 72-98	werveling; convection/advection; perspective	Separate reference frame from transport mechanism.
S1.04 100-133	symbol resembling a whistle	Glyph resemblance retained; sigma identification is earlier AI interpretation.
S1.05 135-153	sigma sigma boy; simple sinusoidal curve	Periodicity, phase and repetition; animation claim unverified.
S1.06 155-192	mirror on the X axis	Explicit plane-reflection operator.
S1.07 194-230	domain warp	Function composition with declared domain.
S1.08 232-321	WFC; vector fields; log-encoded polar LUT	Procedural constraints and corrected lookup cost/indexing.
S1.09 323-404	aquaplaning; two preparations; inverse flash freeze	Unverified material-transition motif.
S1.10 406-502	acoustic FMCW chirp	Probe/echo and delay as typed observations.
S1.11 504-581	ultrasonic fracture; launcher/pneumatic terms	Abstract release/transition motif only.
S1.12 583-671	ablation as enabling	Abstract gate; speculative device claims not adopted.
S1.13 673-765	shockwave	Abstract propagating disturbance; no operational damage model.

The earlier responses often supply specific mechanisms that the brief user seeds do not establish. The provenance record therefore retains speaker role and evidence status wherever those can be determined.

S1: cadence through lineage

ID / lines	Seed or motif	Use in this edition
S1.14 767-797	2e Hansie Runge-Kutta; Gretle; death of sin-wave; neck key	Narrative mnemonic for iteration and discretization.
S1.15 799-810	crescendo; conductor Zorlda; DJ; VR; timing windows	Coordination interface; response is incomplete.
S1.16 812-901	cadence	Multiple clocks, buffers and deadlines.
S1.17 903-983	MIDI; FMCW; bidirectional Y-prism multiplex	Typed channels and separate routing modes.
S1.18 985-1075	ITD/IPD; TOF; infrared; 5G; Wi-Fi; towers	Observation model, range/angle distinction and uncertainty.
S1.19 1077-1170	Doppler; world coordinates; SS	Relative-motion observation; SS remains an unresolved token.
S1.20 1172-1268	signal strength; parabolic arrays; LUT; Y-switch	Quality-aware routing with explicit validity rules.
S1.21 1270-1357	RSSI and VR zords	Feedback and degraded-state motif; no control-safety assurance.
S1.22 1359-1454	graceful J.I.T. decompile and compile	Versioned adaptation, validation and activation.
S1.23 1456-1546	240 to 120; sawtooth/sine mean; SSRI	Lossy resampling audit; acronym expansion unestablished.
S1.24 1548-1635	Allfather; Bloodhound; grandfather; father through son	Symbolic record lineage and derived results.
S1.25 1637-1671	father 63; son 36; grandfather numerology	Digit reversal and arithmetic; no inferred biography.
S1.26 1673-1755	sigma quarter-turn; clover pad; father-only exit	Fourfold cycle and separate one-use role policy.

Terms such as “God complex,” “reincarnation” and “escape” are preserved as source narrative labels. They are not diagnoses, statements about the author's family, or demonstrated physical events.

S2 and the accompanying message

ID / lines	Source cluster	Treatment
S2.01 1-33	CC/copy; tracing; etching; Escher; comet; OBS; multiplex; foods; tubes; school/playground; swarm; DT	Vocabulary inventory; copying, representation and geometry motifs.
S2.02 35-60	Biochemical and biomechanical mappings	Analogies need separate physical models; no automatic equivalence.
S2.03 62-86	Structural failure LUT	Arithmetic recomputed under a declared ideal tube model.
S2.04 88-123	Z A; marine compass; second-hand; balldodge; bracket LUT	Orientation/calibration motif; missing bracket geometry retained.
S2.05 125-147	Prism; Y-switch; illumination; laser cylinder	Separate optical split, switch, scanner and digital routing.
S2.06 149-176	Physical system plus OBS telemetry	A requested model/display interface; supplied numerical calibration unverified.
S2.07 178-199	Egg/CSF; Phobos; skull; osmosis; biological FoS	Source themes preserved; clinical thresholds not adopted.
S2.08 201-249	Chart code	Internal mismatch with preceding table documented.

S0: current-message coverage

Topic	Location in this document
SIM swap / hot swap / eSIM	Migration adapter on page 14; source [R1].
Assad / Syria / Peshmerga / Git / JIT	Page 14 for software; page 15 for wordplay; dated statement check on page 25.
Triple fang / viper / ader / adelaarlijk / kraaienpoot	Symbolic branching treatment on page 15; unresolved terms on page 23.
Abraham / Leviathan / Gabe Newell	Source narrative/name association on page 15; no vessel specifications adopted.
Seed / father / mother / complex / nine ten / dooh hood / repeat / ack ack	Core definitions on pages 5-10 and worked example on page 18.

Glossary and open definitions

The completed model is usable as a conceptual specification while the following author choices remain explicit. A future revision can change these conventions without claiming that an earlier interpretation was the only possible meaning.

Term	Meaning used here / remaining choice
Seed / zaad / oorsprong	Immutable source snapshot. Any biological or cosmological sense remains a separate narrative interpretation.
Father / vader; mother / moeder	Peer branch names F and M. The author can define distinct functions; none is assigned by gender.
Child / son / descendant	A derived record with parent references. Older ancestry is a path in the provenance graph.
Inverse / complex	A named operator on a declared domain. Complex numbers are optional; the general architecture also accepts strings.
Multiplex / Y / prism	MUX is selection; a Y is a junction; prism is source imagery unless a specific optical device is separately modeled. “Multiplex” as plywood is a different material meaning.
Nine / ten	Literal nine-character phrase plus a separate proposed 9-to-10 commit boundary. Ten has no independently supplied operational definition.
dooh / hood / palindome	Exact strings preserved. “Palindrome” is the standard term used for the defined reversal test.
ACK ACK	Two named application receipts, with bounded retries and an explicit commit boundary.
SS / SSRI / eigenvot / acis / key phobos / balldodge	Unresolved source tokens. Earlier AI expansions are not accepted as established definitions.
Egg incubation of spinal fluid	An undefined source phrase retained without an invented biological mechanism.

Revision choices to settle next

Choose the intended application domain; specify the independent F and M functions; choose the default routing/merge mode; define what a committed result means; select permitted retry duration and record retention; and state whether any metaphor should remain purely narrative. These choices refine the model rather than prevent this edition from being read or assessed.

Version 1.0 establishes terminology, source coverage, exact examples and evidence boundaries. It does not claim an experimental discovery, a validated physical device or a tested deployment.

Primary references used for verification

Sources were consulted on 23 October 2026. Each reference supports only the nearby background claim for which it is cited. The proposed architecture and mathematical examples are defined in this document.

R1

Apple Support. Set up eSIM on iPhone.
Carrier-dependent provisioning and deactivation of the preceding SIM on replacement-plan activation.
https://support.apple.com/en-us/118669

R2

Git Project. git-merge Documentation.
Integration of changes into the current branch; conflict handling.
https://git-scm.com/docs/git-merge

R3

Git Project. git-push Documentation.
Remote reference updates and transfer of required objects.
https://git-scm.com/docs/git-push

R4

Texas Instruments. SN74LVC1G3157 Single-Pole Double-Throw Analog Switch, Rev. O, June 2025.
Selected connection between one common terminal and two branches; either-direction signaling; device-specific break-before-make behavior.
https://www.ti.com/lit/ds/symlink/sn74lvc1g3157.pdf

R5

IETF / RFC Editor. RFC 9293: Transmission Control Protocol (TCP), August 2022, sections 3.4-3.5.
Cumulative byte acknowledgments and why pure ACKs do not consume sequence space.
https://www.rfc-editor.org/rfc/rfc9293.html

R6

Leslie Lamport. Time, Clocks, and the Ordering of Events in a Distributed System. Communications of the ACM 21(7), 1978, pp. 558-565.
Happens-before partial order and consistent logical clocks.
https://lamport.azurewebsites.net/pubs/time-clocks.pdf

R7

COMSOL. What Is Convection? Multiphysics Cyclopedia.
Context-dependent usage of convection/advection; distinction between bulk transport and thermal mechanisms.
https://www.comsol.com/multiphysics/what-is-convection

Context check and source fingerprints

The geopolitical passage was checked as a dated statement claim. KRG's Ministry of Peshmerga Affairs announced completion of unification/reorganization in September 2026. Qatar's Ministry of Foreign Affairs welcomed SDF integration in Syrian military institutions in August 2026. These sources establish official statements; this review does not independently verify every operational detail. [R8-R9]

R8

Kurdistan Regional Government, Ministry of Peshmerga Affairs. MoPA Announces Completion of Peshmerga Unification and Reorganisation. September 2026.
Open the primary statement

R9

Qatar Ministry of Foreign Affairs. Qatar Welcomes SDF's Integration in Syrian Military Institutions. August 2026.
Open the primary statement

The model therefore distinguishes agreement, announcement, formal change and verified completion. The Peshmerga/push-merge resemblance remains a wordplay motif; it contributes no proof to the architecture.

Attachment identity

S1: Pasted text(20261023-051705).txt
130,399 bytes; 1,755 lines. SHA-256:

```
9b5fed68bc3914f127138d0d7765e852
d02ea3f2618e455c3709a8e823de25c7
```

S2: Pasted text (2).txt
18,356 bytes; 249 lines. SHA-256:

```
b42bb3b40426aa8369ec71eff7051c90
030010b115ac0ba9ca75d0c47085ec66
```

Fingerprints identify the attachment bytes used in this edition. The complete original inputs remain separate from this synthesized report. Potentially hazardous operational passages are represented only by their high-level source-history entries.

Attribution and version

Concept and source vocabulary: Tom Klootwijk. Formalization, editorial definitions, source verification and document production: prepared with AI assistance. Author-supplied reference and date are reproduced on the cover without assigning an unstated identifier type. Version 1.0, 23 October 2026.