UNIVERSAL

log net D

Automorphic coordinates · 1-bit integer storage
Exact symbolic π · Deterministic LUT operations

Physical, analog and digital records for CCD sensing, polar motion, biochemical preparation and biomechanical interpretation.

PERSONAL IDENTIFIERS - AS SUPPLIED

Tom Klootwijk

Identifier supplied: NL200678942
Date supplied: 10-07-1990

Current numeric contract

The canonical payload uses one-bit cells, binary integer words, exact rational units and symbolic constants. The earlier hexagonal Q16 LUT is preserved in binary form. A separate integer logarithmic table supplies exact power-of-two levels. Wrapped orientation, unwrapped phase and geodetic coordinates have distinct fields.

Included	Format
Automorphic coordinate addendum	Definitions, binary domains, D6 actions, height and phase conventions.
CODEX / LLM machine packet	Canonical JSON, packed .bin data, Python reference code, verification records.
Crossdomain reference and sources	Revised core report, full earlier scientific report and original conversation.

Edition 2 | 30 October 2026
Heading: UNIVERSAL | Current runtime profile: integer_bits_v1

Document and processing map

The machine packet defines the numerical interface; page sections explain the same fields.

Pages	Section
3-4	Symbols, one-bit cells, fixed-width words and canonical domains
5-7	Geodetic model, elevation, θ / φ / Φ, D6 automorphisms
8-10	Preserved hexagonal LUT, exact log-level table and integer interval decoder
11-14	Transport, CODEX processing, verification fields and new references
15-32	Crossdomain reference: logarithms, motion, CCD, analog, chemistry, mechanics, graphics
33-47	Appendix A: the complete 15-page earlier scientific report
48-50	Appendix B: the complete supplied conversation

Profile selection

Profile	Operation
integer_bits_v1	Coordinate words, symbolic π coefficients, phase, D6, swizzle and multiplex.
LND_HEX_Q16_BITS_V1	The original 17 × 72 stored irradiance codes and validity mask.
exact_log2_levels_64	An additional 64-level integer logarithmic table.
Q16 integer interval decoder	Certified rational intervals for the original log-encoded values.

Automatic processing

Extract log_net_D_bits_bundle.zip from the PDF attachments. Select the named profile, validate its binary fields, and process its declared operations. Data-origin, datum, calibration and uncertainty fields describe the measurement record; ordinary integer operations use their numerical domain checks.

UNIVERSAL is the common document heading and schema organization. Each operation declares its input type and range. Source appendices retain their original wording. Page references 1-15 inside Appendix A correspond to master pages 33-47: add 32.

Symbol registry

Letter case, mathematical constants, prime integers and prime marks occupy distinct namespaces.

Symbol	Machine meaning
φ	latitude_phi_word: geodetic latitude, the ellipsoid-normal angle.
λ	longitude_lambda_word: east-positive longitude in its canonical interval.
h / H	Ellipsoidal height / orthometric height, with explicit height-kind metadata.
θ	theta_word: local planar angle, counterclockwise from local +x.
Φ	Phi_unwrapped_word: accumulated local phase with its winding count.
φc / θc	Geocentric latitude / geocentric colatitude; separate derived coordinates.
π	Exact symbolic circle constant; no finite numeric approximation is stored.
p	Prime integer: an integer greater than one with exactly two positive divisors.
π(n)	Prime-counting function; a different object from the circle constant. [U08]
φ′ or Φ′	An explicitly named transformed value or derivative, according to operator metadata.

Symbolic π without floating-point storage

$$\alpha(j) = \pi \frac{j}{180\,000\,000\,000}$$

The packet stores a symbolic basis named pi and an exact rational coefficient. The numerator and denominator are integer bit strings. For example, 60° has coefficient 1/3 and 5° has coefficient 1/36. Symbolic Pi and numerical evaluation are separate representations. [U09]

Prime integers are not the circle constant π. The prime-counting function happens to use the letter π, while a prime mark qualifies an operation. The registry keeps these meanings explicit so a parser does not infer one from another.

Angle-unit marks are also typed: one arcminute is π/10800 radians; one arcsecond is π/648000 radians. A mark used as an angular unit is not a derivative operator.

One-bit cells and integer words

A bit has the value 0 or 1. A word assembles multiple bits into a larger exact integer.

$$n = \sum_{i=0}^{w-1} b_i 2^{w-1-i}, \qquad b_i \in \{0, 1\}$$

The active JSON profiles contain only 0 or 1 as numeric literals. Wider quantities are binary strings or rational records with binary numerator and denominator. Packed .bin files store the bit cells directly. Word order is most-significant bit first; signed words use two’s complement.

Field	Bits	Range / unit
Latitude φ	40 signed	-90,000,000,000 to +90,000,000,000 nanodegrees
Longitude λ	40 signed	[-180,000,000,000, +180,000,000,000) nanodegrees
Local θ	39 unsigned	0 through 359,999,999,999 nanodegrees
Height	64 signed	Integer millimetres; height kind and datum in metadata
Winding w	32 signed	-2^{31} through $2^{31}-1$ complete turns
Derived Φ ticks	71 signed	U = wN + j; reconstructed from winding and θ
Validity / longitude defined	1 each	Independent boolean bit fields

$$N = 360\,000\,000\,000, \quad 1 \text{ degree} = 10^9 \text{ ticks}, \quad 1 \text{ mm} = \frac{1}{1000} \text{ m}$$

Canonical ingestion

Parse decimal-degree text with at most nine fractional digits using integer arithmetic. Thus the text "52.123456789" becomes the integer 52,123,456,789 ticks. A rational multiple of π is accepted when its exact coefficient lands on this lattice. The default policy returns a domain error for off-grid inputs; it does not round silently.

```
turn = 360000000000
theta = raw_theta % turn
longitude = (raw_lon + turn//2) % turn - turn//2
winding, theta = divmod(unwrapped_ticks, turn)
```

The unsigned 39-bit word has unused codes at and above N. Those codes are rejected. Signed overflow is also rejected; wraparound is used only for explicitly periodic angle operations.

Latitude, longitude and elevation

Use the declared reference ellipsoid, coordinate frame and height type.

$$a = 6\,378\,137\ \text{m}, \quad f = \frac{10^9}{298\,257\,223\,563}, \quad b = a(1-f), \quad e^2 = 2f - f^2$$

These exact rational definitions encode the WGS 84 reference ellipsoid’s semi-major axis and flattening. Datum realization, coordinate epoch and observation time are separate record fields. [U01,U05]

$$\nu(\phi) = \frac{a}{\sqrt{1 - e^2 \sin^2 \phi}}$$

$$X = (\nu + h)\cos\phi\cos\lambda, \quad Y = (\nu + h)\cos\phi\sin\lambda$$

$$Z = [\nu(1 - e^2) + h]\sin\phi$$

ECEF X points through the equator at longitude zero, Y through longitude 90° east, and Z toward the North Pole. The formulas remain exact symbolic expressions in this contract. The supplied numerical kernels implement integer records and LUT operations; a Cartesian evaluator must declare its rational output interval and scale. [U02]

Height field	Meaning
h: ellipsoidal	Height along the ellipsoid normal. This is the demonstration-record convention.
H: orthometric	Height tied to the named vertical datum and geoid convention.
Ng: geoid height	Model value used in h = H + Ng; model identity/version accompany it.

$$h = H + N_g, \qquad H = h - N_g$$

Use compatible reference systems for this height conversion. Record vertical_datum_id, geoid_model_id and the model/interpolation uncertainty. A free-text “elevation” input must first be assigned a height kind. [U04]

Exact anchor coordinates

At zero ellipsoidal height: (φ, λ) = (0, 0) maps to (a, 0, 0); (0, π/2) maps to (0, a, 0); the North Pole maps to (0, 0, b). At a pole, canonical longitude is zero and longitude_defined_bit is 0. Preserve the supplied longitude separately when source reconstruction requires it.

θ, φ and Φ across frames

Geographic latitude, local orientation and accumulated phase remain distinct.

$$\phi_c = \operatorname{atan2}\left(Z, \sqrt{X^2 + Y^2}\right), \qquad \theta_c = \pi/2 - \phi_c$$

Geodetic φ measures the ellipsoid normal; geocentric φc measures the Earth-center position vector. They coincide at the equator and poles. The surface relation tan φc = (1-e²) tan φ applies at h = 0; use the full ECEF vector for other heights. [U03]

Local east-north convention

$$E = -\sin\lambda_0\,\Delta X + \cos\lambda_0\,\Delta Y$$

$$N_{\text{local}} = -\sin\phi_0\cos\lambda_0\,\Delta X - \sin\phi_0\sin\lambda_0\,\Delta Y + \cos\phi_0\,\Delta Z$$

$$\theta = \operatorname{atan2}(N_{\text{local}}, E), \qquad j_\theta = (N/4 - j_{\text{heading}}) \bmod N$$

Here φ₀ and λ₀ belong to the local origin; ΔX, ΔY and ΔZ are point-minus-origin ECEF differences. The heading formula converts a clockwise bearing from north to the counterclockwise angle from east. Record the origin, axes and CRS. At zero planar radius, orientation has an independent undefined flag. A polar local frame needs an explicit reference direction. [U06]

Unwrapped uppercase Φ

$$U = wN + j, \quad \Phi = \frac{2\pi U}{N}, \quad w = \lfloor U/N \rfloor, \quad j = U - wN$$

Euclidean division gives 0 ≤ j < N even for negative U. The packet transmits the 32-bit winding and 39-bit wrapped angle, from which the 71-bit signed phase is recovered. Adding one full turn changes U by N and w by one, while leaving wrapped θ unchanged.

Two operation names

orientation_symmetry(k, reflection_bit) acts on wrapped θ. phase_advance(delta_ticks) changes the unwrapped phase and retains turns. Six 60° orientation rotations are the identity; six 60° phase advances add one full turn.

Automorphic hexagonal operations

D6, order twelve: six rotations and six reflections on a declared structure. [U07]

$$g_{k,s}(j) = (sj + kT) \bmod N, \quad T = N/6, \quad k \in \{0, \ldots, 5\}, \quad s = 1 - 2b$$

The reflection bit b is 0 or 1. The turn count N is divisible by six, so T = 60,000,000,000 ticks exactly. The action is a bijection of the wrapped angular lattice. Its composition and inverse use only integer arithmetic:

$$g_{k,s} \circ g_{\ell,t} = g_{(k+s\ell) \bmod 6,\ st}, \qquad g_{k,s}^{-1} = g_{(-sk) \bmod 6,\ s}$$

$$R^6 = I, \qquad S^2 = I, \qquad SRS = R^{-1}$$

An integer hexagonal lattice

$$R(q, r) = (-r, q + r), \qquad S(q, r) = (q + r, -r)$$

$$\max(|q|, |r|, |q + r|) \le M, \qquad q^2 + qr + r^2 \text{ is preserved}$$

Axial indices (q, r) transform by additions and sign changes. A symbolic Cartesian embedding is x = d(q+r/2), y = d√3 r/2. Record its orientation; the earlier LUT's face-normal convention is aligned by a π/6 basis rotation.

Structure / field	Declared action
Regular hexagon or axial domain	Exact D6 permutations preserve the boundary and lattice.
Original 72-angle Q16 array	Index j′ = (sj + 12k) mod 72 preserves all stored words and validity bits.
Reference ellipsoid	Longitude rotations and meridian reflection preserve its rotationally symmetric equation.
General measured scalar/vector field	Transform positions and the field's components according to their declared representation; test field invariance separately.

An automorphism preserves a specified structure. Latitude/longitude/ECEF conversion is a change of representation with domain and branch rules; unrestricted interior heights and pole equivalence require their own inverse handling.

The original LUT, as bitplanes

Profile: LND_HEX_Q16_BITS_V1. Stored codes and the source validity mask are preserved exactly.

Object	Exact stored form
Grid	17 radial rows × 72 angular columns = 1,224 positions
Signal	16 MSB-first intensity bitplanes: 19,584 bits = 2,448 packed bytes
Validity	1,224 independent bits = 153 packed bytes; 1,158 valid and 66 outside
Angles	j × 5,000,000,000 nanodegrees; exact radians jπ/36
Source radii / log-radii	Exact rational copies of the source’s serialized decimal tokens
Center	Separate center record, retained with its signal word

$$q_{ij} = \sum_{b=0}^{15} B_{b,i,j}\, 2^{15-b}, \qquad B_{b,i,j} \in \{0,1\}$$

The validity bit is checked before the signal word is interpreted. An invalid position has a zero payload with validity 0. A valid zero has validity 1. This distinction is preserved under packing, swizzling and multiplexing.

Exact array symmetry

$$j' = (sj + 12k) \bmod 72$$

All 14,688 node transformations and 235,008 bitplane transformations were checked over the twelve D6 operations. Stored values, masks and bits match exactly. This is a verified property of the retained array.

Coordinate provenance

The source’s decimal radius tokens are preserved as exact rational values. They record the source’s numerical output. The original boundary mask and its tolerance of 1/500,000,000,000 mm are retained as mask_basis = preserved_source_mask. Recomputing a zero-tolerance ideal boundary from rounded source coordinates would define a different dataset.

Lookup contract

Use exact row/column addressing for the preserved table. The metadata records the separate center and inner interval. A different interpolation, radial resampling or geometric mask is a named operation with its own error record; it does not silently alter the stored source.

Exact logarithmic integer levels

Profile: exact_log2_levels_64. This additional table has exact integer outputs at all declared levels.

$$v_k = 2^k - 1, \quad s = s_0 v_k, \quad u = \frac{k}{63}, \quad k = 0, \ldots, 63$$

A six-bit code selects one of 64 levels. Each value has 64 bits; s_0 is a positive rational unit scale. On these levels, $\log_2(1+s/s_0) = k$ exactly. Decode with a shift and subtraction.

k	Code	Integer v_k
0	000000	0
1	000001	1
2	000010	3
3	000011	7
4	000100	15
5	000101	31
8	001000	255
16	010000	65535
32	100000	4294967295
63	111111	9223372036854775807

```
def decode_level(k):
    if not 0 <= k < 64:
        raise ValueError("code_out_of_range")
    return (1 << k) - 1
```

One-bit matrix and level selection

The complete 64 × 64 matrix contains 4,096 literal bit cells and packs into 512 bytes. Every row reconstructs its value word exactly. All 64 decode/encode round trips passed.

The default encoder accepts the declared levels. Explicit alternatives are floor, ceil and nearest_ties_up. These alternatives quantize an off-level input; the selected policy travels with the result. All three were checked against independent level searches for every nonnegative 16-bit input.

> **Separate profiles, explicit units**
>
> This integer-level table supplements the retained Q16 table. It does not reinterpret an existing Q16 code as a six-bit exponent. The demonstration scale is dimensionless; a calibrated channel supplies the physical unit and scale.

Q16 inverse with integer bounds

The original logarithmic inverse can be carried symbolically or evaluated into a certified rational interval.

$$\frac{\hat{s}}{s_0} = 16^{q/65535} - 1, \qquad 0 \le q \le 65535$$

The exact expression is stored as a typed syntax tree. For a numerical result without floating-point arithmetic, choose a positive integer output scale S and reduce q/65535 to p/d using the greatest common divisor.

$$A = S^d 2^{4p}, \qquad n^d \le A < (n+1)^d$$

$$\frac{n - S}{S} \le \frac{\hat{s}}{s_0} < \frac{n + 1 - S}{S}$$

If $n^d = A$, both endpoints collapse to the exact rational value. Otherwise the interval width is 1/S. The guarantee follows from monotonicity of the positive d-th power; every comparison is between integers.

```
g = gcd(q, 65535)
p, d = q//g, 65535//g
A = (S ** d) << (4*p)
lo, hi = S, 16*S + 1
while hi - lo > 1:
    mid = (lo + hi)//2
    if mid**d <= A: lo = mid
    else: hi = mid
lower = (lo-S, S)  # exact numerator/denominator
```

Code	Exact normalized result
0	0
21,845	16^(1/3) - 1
43,690	16^(2/3) - 1
65,535	15

The bundle includes q16_integer_interval.py and its checks. Larger S narrows the output interval and increases integer computation. The interval describes evaluation of the stored code; acquisition uncertainty and the original code quantization remain separate quantities.

Binary swizzle and multiplex

Whole fields retain their widths, type labels and units through reversible transport.

$$(a, b, c, d) \longmapsto (b, d, a, c) \longmapsto (a, b, c, d)$$

The forward component order is .ywxz and the inverse is .zxwy. Apply this to tagged bit strings. Fields can have different widths because transport boundaries are declared rather than inferred from visual position.

Coordinate frame field	Bits
latitude_phi_word	40
longitude_lambda_word	40
height_mm_word	64
theta_word	39
winding_word	32
valid_bit	1
longitude_defined_bit	1
Total transmitted frame	217

Phi_unwrapped_word is derived and excluded from the transmitted frame. Each stored frame occupies 28 bytes: 217 field bits followed by seven zero padding bits. The bundle includes five complete demonstration records, totaling 140 bytes.

$$F[kM + c] = x_c[k], \qquad c = 0, \ldots, M - 1$$

Multiplex complete records in frame-major, then channel-major order. Demultiplex with the same channel count and declared field widths. Partial frames return an error. The source acquisition timestamps and exposure intervals accompany the record; interleaving does not change them.

Packed bit ordering

Within a word and byte, the most-significant bit appears first. The Q16 binary file is plane-major, then radial-row-major, then angular-column-major. The validity file follows radial row and angular column. Padding rules are explicit and checked.

CODEX and LLM processing interface

The embedded bundle contains the complete data contract, packed arrays and executable integer reference.

Bundle component	Purpose
log_net_D_universal_bits.json	Coordinate, phase, symmetry, transport and exact-level profiles
legacy_hex_binary.json	Original Q16 codes, bitplanes, validity, source coordinates and symbolic inverse
Four .bin files	Packed intensity bits, validity bits, integer-level matrix and coordinate frames
Python reference and decoder	Integer operations, Q16 interval evaluation and reproducible checks
Manifest, QA and README	File identities, layouts, hashes, test outcomes and usage

Extract the machine bundle from this PDF

```
from pathlib import Path
from pypdf import PdfReader
reader = PdfReader("log_net_D_master.pdf")
name = "log_net_D_bits_bundle.zip"
Path(name).write_bytes(reader.attachments[name][0])
```

Unpack the ZIP into a working folder, then run verify_bundle.py. Run log_net_D_integer_reference.py to regenerate the coordinate/log-level packet and its arithmetic checks. The Q16 decoder accepts a stored integer code and a positive integer scale.

Operation contract

1. Select the named profile and decode its bit widths.
2. Verify the file identity and numeric-token rule.
3. Validate domain, mask and record boundaries.
4. Run the declared integer or symbolic operation.
5. Return the result with its profile, units and evaluation interval.

A JSON null in calibration or uncertainty metadata denotes an absent value. It is not a numeric zero. Integer lookup, symmetry, swizzle and transport remain available for generated data. Physical-unit interpretation uses the channel’s calibration and measurement fields.

The source archive also retains the original decimal-token JSON as source_polar_log_irradiance_lut_demo.json. The migrator reads its decimal tokens as text and exact rational values; active processing uses the binary profiles above.

Verification and measurement fields

Exactness is specified per operation and per dataset, with reproducible checks.

Property	Result
Integer profile	46 checks passed; no floating literals, float conversions or true-division operators in its numerical reference.
Canonical JSON	Every numeric literal is 0 or 1. Wider numbers use binary strings or exact rational records.
Original LUT preservation	All 1,224 positions, 1,158 valid signal words and 66 invalid positions preserved.
Automorphic array checks	14,688 node actions and 235,008 bitplane actions; zero mismatches.
Exact log levels	All 64 levels round-trip; 4,096 bit cells reconstruct their integer words.
Optional quantizers	All 65,536 nonnegative 16-bit inputs checked against independent level searches.
Coordinates and phase	Boundaries, poles, seams, negative phase, winding limits and frame recovery checked.
Q16 evaluation	Integer-power brackets give rational bounds at the requested scale.

Physical measurement binding

Field	Current representation
source_kind	Generated arithmetic fixtures and the retained source LUT
wgs84_defining_constants	WGS 84 ellipsoid definitions with rational constants
calibration	Null until a measured channel calibration is assigned
physical_uncertainty	Null until an uncertainty value/model is assigned
numeric_processing_enabled	1

The exact angular grid spacing is π/180,000,000,000 radians. On the model equator, the corresponding arc is 6,378,137π/180,000,000,000 metres. These are numerical resolution expressions. Physical accuracy is determined from the observation, calibration, datum/epoch and uncertainty record.

The preserved LUT is bit-for-bit exact relative to its source codes. Its physical-error field remains separate from code preservation and integer reproducibility. This gives automated processing a precise computation domain and a precise measurement record.

References for the addendum

Official model definitions, primary software documentation and mathematical reference material.

[U01] NGA. WGS 84 defining parameters.
Reference ellipsoid, axes and constants.
earth-info.nga.mil/?action=wgs84&dir=wgs84

[U02] OGC. CDB Spatial Reference System Guidance, section 7.2.
Geodetic-to-ECEF equations and axis conventions.
docs.ogc.org/bp/16-011r5.html

[U03] PROJ. Geocentric Latitude.
Geodetic normal latitude and geocentric radial latitude.
proj.org/en/stable/operations/conversions/geoc.html

[U04] NOAA NGS. Converting GPS Height into NAVD88 Elevation.
Height definitions and h = H + Ng; used for the relationship, not as a current geoid-model selection.
geodesy.noaa.gov/PUBS_LIB/gislis96.html

[U05] OGC. Abstract Specification Topic 2: Referencing by coordinates.
Coordinate systems, datums, reference-frame epochs and coordinate metadata.
docs.ogc.org/as/18-005r4/18-005r4.html

[U06] PROJ. FAQ: coordinate axis order.
Authority-defined axis ordering and explicit CRS conventions.
proj.org/en/stable/faq.html

[U07] University of Lethbridge. Symmetry Group of a Regular Hexagon.
Dihedral group of order twelve and its generators.
www.cs.uleth.ca/~holzmann/notes/dihedral/dihedral1.html

[U08] NIST DLMF. Section 27.2: Functions of Number Theory.
Prime integers, prime factorization and prime-counting function π(x).
dlmf.nist.gov/27.2

[U09] Wolfram Language Documentation. Pi.
Exact symbolic constant and its distinct numerical evaluation.
reference.wolfram.com/language/ref/Pi.html

Sources consulted 30 October 2026. The nanodegree bit widths, transport layout, integer-level table and machine profile identifiers are definitions of this edition. The archived report retains its original bibliography.

Inverse logarithmic scaling

Use a unit-consistent encoder and its exact analytic inverse.

Let s be a nonnegative physical scalar. Choose a reference $s_0 > 0$ and an upper design value $s_{max} > 0$ in the same units as s. Logarithm arguments are dimensionless. The selected map sends 0 to 0 and s_{max} to 1.

$$L = \ln(1 + s_{max}/s_0), \qquad u = \frac{\ln(1 + s/s_0)}{L}$$

$$s = s_0 \operatorname{expm1}(Lu) = s_0[\exp(Lu) - 1]$$

The second equation is the requested **inverse logarithmic** operation. The reciprocal $1/\ln(1+s/s_0)$ is a different function and is singular at s = 0. A log map alone does not place an unbounded input inside a bounded coordinate interval.

Quantized storage and recovery

$$Q = 2^b - 1, \quad q = \lfloor Qu + 1/2 \rfloor, \quad \hat{s} = s_0 \operatorname{expm1}(Lq/Q)$$

s / s_0	u	q, 16 bits
0	0	0
1	0.25	16,384
3	0.50	32,768
7	0.75	49,151
15	1	65,535

Fixture: $s_{max} = 15 s_0$ and round half upward. With s in mW/cm² and s_0 = 1 mW/cm², these codes encode irradiance. They are numerical examples, not lamp measurements.

$$|\hat{s} - s| \le (s_{max} + s_0)\left[\exp\left(\frac{L}{2Q}\right) - 1\right]$$

For that fixture, the conservative absolute error bound is 0.00033846 mW/cm², excluding acquisition error, clipping and interpolation. Store saturation, invalidity and clipping flags independently. An inverse cannot recover information already discarded.

Decode before physical calculations

Use $H \approx \Sigma \hat{I}_n \Delta t_n$ for exposure. Averaging log codes generally does not produce the arithmetic mean of the physical signal. The UNIVERSAL profile stores this inverse as an exact symbolic expression and carries its code as integer bits.

Polar calculus and the hexagon

The scalar signal encoder and the spatial coordinate transform have separate definitions.

$$\rho = \ln(r/r_{\mathrm{ref}}), \qquad r = r_{\mathrm{ref}} e^{\rho}, \qquad r > 0$$

$$\mathbf{v} = r\dot{\rho}\,\mathbf{e}_r + r\dot{\theta}\,\mathbf{e}_\theta$$

$$\mathbf{a} = r(\ddot{\rho} + \dot{\rho}^2 - \dot{\theta}^2)\mathbf{e}_r + r(\ddot{\theta} + 2\dot{\rho}\dot{\theta})\mathbf{e}_\theta$$

These expressions follow by substituting r = r_{ref} exp(ρ) into ordinary polar kinematics. Angles are in radians. Unwrap θ before differentiation and wrap it for periodic LUT addressing. The r = 0 point needs a separate representation. [M16]

Physical area requires the coordinate Jacobian

$$dA = r\,dr\,d\theta = r^2\,d\rho\,d\theta$$

Equal steps in (ρ, θ) cover unequal physical areas. For an integral over a specimen, include the Jacobian and valid-domain mask. Convert mm² to cm² by dividing by 100 when combining areas with mW/cm².

$$\eta = \ln(1 + r/r_0) \quad \Rightarrow \quad dA = r\,r_0 e^{\eta}\,d\eta\,d\theta$$

This alternative log1p radial coordinate includes the origin but has a different area weight. It cannot reuse the strict log-polar r² weight unchanged.

Hexagonal domain

$$r_{\mathrm{hex}}(\theta) = \frac{a_h}{\max\limits_{k=0,\ldots,5} \cos(\theta - \theta_0 - k\pi/3)}$$

Here a_h is the apothem and θ_0 is an outward face-normal direction. Keep samples only when r ≤ $r_{hex}(\theta)$. The boundary radius ranges from a_h to $2a_h/\sqrt{3}$. A physical path that traverses a sharp vertex at nonzero speed requires an instantaneous direction change; round the path or stop to keep acceleration finite.


> **Checked circular fixture**
>
> At r = 5 mm and θ = 0.2 rad/s: speed = 1 mm/s, radial acceleration = -0.2 mm/s² and period = 31.41593 s. Appendix A contains the detailed polar LUT construction and moving-frame exposure model.

Bounded geometry and Escher motifs

Choose the map and metric explicitly before interpreting a visual pattern.

$$R = R_{\max}\frac{r}{r + a_d}, \qquad r = \frac{a_d R}{R_{\max} - R}$$

This proposed radial display map uses a scale a_d > 0 in physical length units. Every finite r ≥ 0 maps to 0 ≤ R < Rmax. The graphic below uses a_d = 10 mm and Rmax = 1 display unit.



$$\frac{dr}{dR} = \frac{a_d R_{\max}}{(R_{\max} - R)^2}$$

Reconstruction becomes sensitive near the boundary. Clipping R to Rmax removes the finite inverse. A finite raster or buffer therefore does not retain unlimited spatial precision merely because a mathematical map has a bounded range.

A Poincaré disk needs its hyperbolic metric

$$d\ell^2 = \frac{4(dx_d^2 + dy_d^2)}{(1 - x_d^2 - y_d^2)^2}, \quad d = 2\operatorname{artanh}(s)$$

For the unit disk of curvature -1, s = √(x_d²+y_d²) < 1 and s = tanh(d/2), where d is hyperbolic distance from the origin. Applying a similar radial formula to laboratory positions is a display choice; a physical specimen acquires no hyperbolic metric from that rendering. Escher-like motifs may be drawn within either display convention. [M13]

Displayed motion can accelerate without physical acceleration

$$\dot{\mathbf{y}} = J_G \dot{\mathbf{x}}, \qquad \ddot{\mathbf{y}} = J_G \ddot{\mathbf{x}} + \mathcal{H}_G[\dot{\mathbf{x}}, \dot{\mathbf{x}}]$$

For the rational map at r = 5 mm, ṙ = 1 mm/s, r̈ = 0 and a_d = 10 mm: Ṙ = 0.044444 display units/s and R̈ = -0.005926 display units/s². Estimate biomechanical motion in calibrated physical coordinates.


Swizzle: reorder, then invert

A reversible permutation preserves values when field labels and units travel with them.

HLSL uses component selectors such as .xyzw or .rgba. Here **swizzle** means vector-component ordering; tiled-memory addressing would need a separate mapping specification. A full permutation has an inverse. Selecting repeated components can lose a field. [M04]

$$\mathbf{c} = (r, \theta, z, t) \quad \longmapsto \quad P\mathbf{c} = (\theta, t, r, z), \qquad P^{-1} = P^{T}$$

```
original = (r_word, theta_word, z_word, time_word)
packed = (original[1],original[3],original[0],original[2])
restored = (packed[2],packed[0],packed[3],packed[1])
```



Operation	Recovery condition
.ywxz followed by .zxwy	Exact field-order recovery in the same number representation.
.xxzw	The second original component is discarded; output alone cannot recover it.
Angle wrapping	Recover orientation modulo 2π; preserve a winding count if complete rotations matter.
Grid snapping or finite quantization	Many inputs can share a result. Retain originals if exact recovery is needed.

A packed (r, θ, z, t) record contains mixed units and is not automatically a physical four-vector. Do not log-transform each component with the irradiance encoder: θ is circular, z can be signed, and time needs a declared clock and epoch.

Rendering payload used in this master

The active packet stores integer words and one-bit flags. Swizzle whole tagged fields and inverse-swizzle before interpretation. The UNIVERSAL transport contract defines field widths; acquisition timestamps, calibration identifiers and units remain in the record metadata.

Multiplex: share a path

Channel order, timing and the separation model make multiplexing interpretable.

Method	What is shared	What recovery needs
Digital interleaving	Storage or transport slots	Known indexing, channel identity and complete records.
Analog time scan	One input path or ADC	Settling, per-channel filtering and actual acquisition times. [M03]
Frequency division	Carrier-frequency bands	Bandwidth allocation, filters, demodulation and sufficient SNR.
Wavelength division	One optical path	Wavelength separation, calibrated channel response and crosstalk control. [M14]

Digital interleave and its inverse

$$F[kM_c + c] = x_c[k], \qquad x_c[k] = F[kM_c + c], \quad c = 0, \ldots, M_c - 1$$



The slots above show two frames with four channels each. This digital layout does not imply that the four measurements were made simultaneously.

A sequential analog scanner has time offsets

$$t_{k,\,c} = t_0 + \frac{kM_c + c}{f_s}, \qquad f_{\text{channel}} = \frac{f_s}{M_c}$$

Example: 1,000 conversions/s shared uniformly by four channels gives 250 samples/s per channel and offsets of 0, 1, 2 and 3 ms within a frame. The nominal per-channel Nyquist frequency is 125 Hz; practical filtering and settling need margin. Preserve exposure intervals as well as sample timestamps. [M03]

Physical mixing is a different inverse problem

$$\mathbf{y} = A\mathbf{s} + \mathbf{n}$$

Separating mixed measurements requires sufficient independent channels, a calibrated matrix A and acceptable conditioning. Nonlinear log encoding generally does not commute with mixing: each logarithm needs its declared positive, dimensionless argument. A broadband CCD count integrates spectral contributions; an RGB swizzle cannot recover arbitrary unmeasured wavelengths. Follow the actual acquisition order when demixing, calibrating and encoding. [M01,M14]

CCD: photons to measured records

Specify the actual sensor, its spectral path and its timing architecture.

A CCD collects photo-generated charge and transfers charge packets toward an output node. The readout converts charge to voltage; conditioning and an ADC then produce digital counts. Correlated double sampling can reduce reset-related noise. Sensor saturation, dark signal, read noise and nonuniform response constrain interpretation. [M01]

$$\bar{N}_e = A_p \int_{t_0}^{t_1} \int QE(\lambda)\, E_\lambda(t)\, \frac{\lambda}{hc}\, d\lambda\, dt$$

The integral gives the expected collected signal-electron count, excluding dark signal and readout effects. Eλ is sensor-plane irradiance in $W \cdot m^{-2} \cdot m^{-1}$, λ is in metres, pixel area A_p is in m^2, and QE is electrons per incident photon. Photon energy is hc/λ. Relating specimen illumination to sensor-plane Eλ needs optical throughput; noise, spatial averaging and transfer losses require additional terms.

An explicit calibration model

$$S_{\mathrm{DN}}(x,y) = \frac{\mathrm{DN}(x,y) - B(x,y) - t_e D(x,y)}{F(x,y)}$$

Symbol	Declared meaning
DN	Raw digital number for the relevant pixel/exposure.
B	Bias/offset map in counts.
D	Dark-signal rate in counts per second.
t_e	Exposure duration in seconds.
F	Dimensionless normalized flat-field response.

This proposed model yields corrected counts. If a measured dark frame already includes bias, do not subtract the bias twice. Irradiance or photon-flux units additionally need calibrated gain, spectral response, optical geometry and exposure time. Match dark and flat measurements to the operating conditions. [M01]

> **Three measurement boundaries**
>
> A pixel count alone does not identify lipid chemistry, UV conversion or mechanical stiffness. Sequential readout alone does not establish rolling exposure. Label the device CCD only if its specified architecture is CCD; use the camera’s documented shutter and storage timing.

Design proposal: use a calibrated monitoring path to sample the relevant illumination plane, record spectral filtering and avoid inferring dose from a display-brightness control. Preserve raw counts alongside calibration and status metadata.

Analog logarithm and digital code

Each logarithmic stage needs its own reference, scale, domain and inverse.

$$V = A + B\log_{10}(I/I_{\mathrm{ref}}), \qquad I = I_{\mathrm{ref}}10^{(V-A)/B}$$

In this illustrative calibrated analog model, I is a positive current, I_{ref} is a positive reference current, A is an offset voltage, and B is volts per decade. Hardware bandwidth, temperature response, noise and clipping limits remain part of the measurement.

A concrete component example

$$V_{\mathrm{LOGOUT}} = 0.375\,\mathrm{V}\log_{10}(I_1/I_2)$$

Texas Instruments specifies this scale for the LOG114 log-ratio amplifier, with an input-current range of 100 pA to 10 mA under its stated conditions. Scaling/offset circuitry can match the output to an ADC. This is an example for a compatible current-monitor channel; it does not establish direct compatibility with a particular CCD camera output. [M02]

Analog log ratio	Digital log1p encoder
Transfer occurs before the ADC.	Transfer occurs after a physical scalar has been estimated.
Positive input/reference current and circuit limits.	Chosen nonnegative scalar range, including zero.
Inverse uses 10 to a calibrated exponent.	Inverse uses expm1 with the recorded normalization.
Voltage offsets and scale drift affect recovery.	Bit depth, rounding and clipping affect recovery.

Avoid an accidental second logarithm

If an analog log stage precedes digitization, first invert its calibrated transfer when estimating the physical signal. Apply the optional digital encoder only after that interpretation. Recording both transfers makes a deliberate two-stage encoding reproducible.

Zeros, signed residuals and uncertainty

Bias-corrected estimates can be negative near the noise floor. Keep them for unbiased measurement analysis, or define a separate signed representation. Silently clipping every negative estimate to zero changes the estimated mean. A proposed signed display encoder is:

$$u_s = \mathrm{sgn}(s)\frac{\ln(1+|s|/s_0)}{L}, \quad s = \mathrm{sgn}(u_s)s_0\mathrm{expm1}(L|u_s|)$$

Its signed integer storage, full scale and rounding rule must be specified separately. For the positive encoder, small code uncertainty propagates approximately as $\sigma_s \approx L(s+s_0)\sigma_u$; this is only the encoding contribution to total uncertainty.

Light, motion and UV exposure

The supplied Fresnel/parabolic diagram concerns collimation; exposure also needs spatial calibration.

The optics illustration is retained in Appendix A. Parallel output rays describe direction, while curing depends on the irradiance distribution, wavelength, transmission and time at the specimen. A collimated beam can still have a nonuniform intensity profile. Appendix A gives the supporting optics references and source credit.

$$\mathbf{x}_{\mathrm{lab}}(t; X) = \mathbf{c}(t) + R(\phi(t))X$$

$$I(X, t) = g(t)p(t)B(\mathbf{x}_{\mathrm{lab}}(t; X) - \mathbf{b}(t)), \quad H(X) = \int I(X, t)dt$$

X labels a material point; c and φ describe specimen translation and rotation; b is beam position; g is a temporal gate. In this convention p has irradiance units and B is a dimensionless measured profile. The integral H has radiant-exposure units. Decode logged irradiance before integration.

Planning an exposure field

$$H_j = \sum_k A_{jk}\tau_k, \qquad \tau_k \geq 0$$

A proposed dwell-time controller uses A_{jk} as calibrated irradiance at target j from exposure position k. Solve for nonnegative dwell times τ_k under travel, time and uniformity constraints. The point formula t = H/I is sufficient only for a constant local irradiance with the relevant overlap and motion already accounted for.

A cure working curve is a fitted material model

$$C_d = D_p \ln(H/H_c), \qquad H \geq H_c$$

The Jacobs working-curve form relates cure depth C_d to exposure using fitted penetration depth D_p and threshold H_c. NIST's interlaboratory work documents the measurement dependence of these parameters. Use the fit only within the tested resin, spectrum, geometry and exposure regime. Equal nominal H need not guarantee equal reaction histories. [M15; Appendix A, A3]

Observable	What it supports
Calibrated irradiance + time	Radiant exposure at the specified plane.
Reactive-group spectroscopy	Chemical conversion under a defined analysis. [M24]
Mechanical test after conditioning	Mechanical response for that specimen and loading mode.
Structural scattering/diffraction	Assessment of molecular or mesophase order. [M18,M21]

Preparaat 1 + preparaat 2

Select the chemical roles before choosing the optical or digital control settings.

Preparaat 1: a defined lipid preparation

Specify lipid identity, purity, concentration, hydration and domain structure. Native lipid droplets may be entrapped within a polymer network; entrapment does not establish covalent bonding to the carbohydrate. Reactive lipid-derived materials are another route: photocurable acrylated epoxidized soybean oil is a documented example, not evidence that any oil will UV-harden. [M20]

Preparaat 2: a compatible carbohydrate-derived network

A functionalized polysaccharide can provide reactive groups for network formation. Methacrylated hyaluronic acid is a published example of a photocrosslinked hydrogel system whose formulation affects swelling and mechanics. The master does not select a formulation, initiator or dose without the missing material and wavelength specifications. [M19]

Architecture	Question to resolve
Lipid domains in a continuous network	Do domains remain stable during mixing and curing, and remain retained after swelling?
Sequential lipid/carbohydrate layers	Does the interface adhere under wet conditions and differential swelling?
Reactive lipid + reactive carbohydrate	Do the selected chemistries actually couple, and what independent controls demonstrate this?

Three meanings of “hexagon”

Meaning	Required evidence
Macroscopic hexagonal shape	Dimensions, imaging and boundary geometry.
Hexagonal liquid-crystalline lipid phase	Phase-sensitive scattering with indexed peaks and composition/temperature context.
Molecular crystalline order	Appropriate diffraction and/or thermal/structural characterization.

Hexagonal mesophase peak-position ratios can be consistent with $1 : \sqrt{3} : 2 : \sqrt{7}$, but the indexing, number of reflections and competing phases matter. A hexagonal outline or a single image is insufficient. Photocuring describes chemical network formation; crystallization describes structural ordering. [M17,M18,M21]

> **Connection to log net D**
>
> Record preparation, exposure, conversion, structure and mechanics under shared specimen IDs. Encoding organizes data; chemical bonding and structural order must be established by material measurements.

Biomechanics in physical coordinates

Geometry can influence response, but mechanical claims need their own measurements.

$$\mathbf{x}(X,t) = X + \mathbf{u}(X,t), \quad F = \frac{\partial \mathbf{x}}{\partial X}, \quad E_G = \frac{1}{2}(F^T F - I)$$

These continuum definitions relate displacement u, deformation gradient F and Green-Lagrange strain E_G. For small deformations, ε ≈ ½(∇u + ∇uᵀ). The coordinate scale, camera projection and displacement registration must be calibrated before a CCD image can support strain estimates.

Quantity	Example definition or test	Interpretation limit
Stiffness	Force/displacement slope for a defined geometry.	Depends on specimen shape and supports.
Modulus	Stress/strain response under a stated model.	Depends on loading regime and material state.
Strength	Failure stress in a specified test.	Does not follow from stiffness alone.
Toughness	Work to failure per volume, or an appropriate fracture measure.	State the definition and loading geometry.
Hardness	Resistance in a specified indentation method.	Not a general synonym for cured or stiff.

Suggested measurement sequence

Record specimen dimensions, hydration, temperature and conditioning time. Measure a mechanical response before and after the selected cure/conditioning sequence. Include the carbohydrate network alone, the lipid-containing material and any relevant interface control. Report replicates, variability and failure location.

For dynamic loading, retain force/displacement timing and the acquisition phase between channels. An analog multiplexer can introduce offsets that resemble phase lag; use actual sample times or suitable simultaneous acquisition when the inference requires it. [M03]

Display deformation is not specimen deformation

$$\mathbf{y} = G(\mathbf{x}) \quad \Rightarrow \quad \frac{\partial \mathbf{y}}{\partial X} = J_G(\mathbf{x})F$$

A bounded radial map changes the apparent deformation gradient. Compute physical strain before applying that display map, or reconstruct calibrated physical coordinates first. Swizzling a displacement tuple also requires its component labels to follow the values.

Photopolymerization can involve oxygen inhibition and shrinkage. Their effects must be characterized for the selected composition and geometry. Neither a lipid addition nor a honeycomb appearance guarantees improved strength, toughness or biocompatibility. [M22,M23; Appendix A]

LUT and record specification

The supplied synthetic LUT remains a reproducible demonstration, with its limits preserved.

Item	Demonstration definition
Grid	17 geometric radial nodes × 72 angles; 1,224 nodes total.
Domain	Hexagon apothem 10 mm; circumradius 11.547005 mm.
Mask	1,158 valid nodes; 66 outside-domain nodes stored as null.
Center	Separate I = 12 mW/cm² record; q = 60,627.
Inner gap	0 < r < 0.5 mm is unrepresented; do not invent samples there.
Encoding	s_0 = 1 and s_{max} = 15 mW/cm²; natural log; uint16.
Interpolation	Decode values, then bilinear interpolation in (ρ, θ). Reject a stencil with an invalid nonzero-weight node.

The demonstration is preserved by the UNIVERSAL binary migration. Its source_kind is synthetic; calibration and material-response fields retain their original values. The largest observed node quantization error is 0.00022832 mW/cm², below the 0.00033846 bound. This measures encoding error in generated data, not instrument accuracy.

Proposed authoritative record fields

```
specimen_id, acquisition_id, frame_id, sequence
channel_id, sensor_id, clock_id, sample_time
exposure_start, exposure_end, coordinate_frame
units, calibration_id, encoding_id, swizzle_id
raw_code, encoded_value, status_flags
```

Define channel labels and units in a schema before transport. Status distinguishes invalid, saturated, clipped, uncalibrated, dropped and interpolated samples. A valid zero and an unknown sample must remain distinguishable. Keep the supplied personal identifiers in document attribution; specimen and acquisition identifiers describe the measured objects.

A defensible round trip

Read a valid physical value → encode within its declared range → permute the payload → interleave complete records → demultiplex → inverse-permute → decode → compare against the physical value within the stated quantization tolerance. Preserve raw records so later calibration changes can be applied.

> **Metadata is part of the value**
>
> A stored integer without its units, reference scale, channel, timing, validity and calibration cannot establish the intended physical measurement. Finite precision, saturation and missing samples remain visible limitations after decoding.

GPU buffers and bilateral imagery

Carry integer payloads to an explicitly defined display adapter.


Unity VFX Graph supports Structured GraphicsBuffer inputs with matching stride and supported blittable types, including uint. SetGraphicsBuffer binds the buffer at runtime; the reference must be restored with the appropriate lifecycle. The UNIVERSAL data contract uses integer words, bitplanes and separate metadata. [M05,M06]

```
// Integer payload operations; indices are validated.
uint word = words[recordOffset + limbIndex];
uint bit = (word >> bitIndex) & 1u;
uint mirroredX = width - 1u - xIndex;
// Grid width, origin and axis direction are metadata.
```

A display adapter declares its coordinate conversion and pixel rounding. Keep this adapter separate from the integer LUT decoder and the physical-unit record. Render the center at its declared coordinate and exclude invalid records before reconstruction. A complete GPU scene can have a different numeric execution model from the canonical data packet.

Creator examples: Keijiro’s GeoVfx uses GeoTIFF-derived .geodata textures. VfxGraphGraphicsBufferTest separately demonstrates GraphicsBuffer operators receiving compute-shader data. Profile upload, synchronization and rendering work for the chosen environment. [M07,M08]

Reflection, folding and duplication



$$F(x,y) = (|x|, y), \quad R(x,y) = (-x, y), \quad S_{\text{bilateral}} = S \cup R(S)$$

abs(x) folds points onto one half-plane and loses the sign. Reflection is invertible; bilateral rendering explicitly draws the original and reflected set. Handle axis points once where duplicate brightness matters. Inkblot resemblance is a visual motif; interpretation belongs to the named measurement or visualization method.

Geospatial data and source labels

Relative coordinates are a representation choice; the source text does not establish anonymity.

$$\mathbf{q}_i = \mathbf{p}_i - \mathbf{p}_0, \qquad \Delta\mathbf{p}_i = \mathbf{p}_i - \mathbf{p}_{i-1}$$

$$\mathbf{p}_i = \mathbf{p}_0 + \sum_{j=1}^{i} \Delta\mathbf{p}_j$$

Origin removal and successive displacement encoding are different operations. With the initial position, displacement records reconstruct the path. Without it, timestamps and movement shape can still be linkable. The attachment's claim of complete masking is unsupported; pseudonymisation and anonymisation are distinct concepts. [M11]

For a proposed geospatial input, record the coordinate reference system, datum, units, spatial transform and time standard. Convert coordinates into a declared metric frame before applying laboratory-distance formulas. Reordering longitude and latitude is a field-layout operation, not a projection.

Supplied wording	Treatment in this master
JITSKE; SK	Preserved as undefined source labels. No acronym, identity or operating role is inferred.
J.I.T.	Where used technically, compilation or just-in-time processing needs a specified implementation; it provides no anonymity guarantee.
prismatic gol ned log	Preserved as a literal project/source phrase. No established multispectral ledger is implied.
antagonist; collaborators	Recorded in the source appendix. They do not establish a technical mechanism, relationship or action involving a person.
identity tracking logs	No such dataset was supplied. The personal identifiers serve the requested attribution block.

Mass-energy and encoding have different definitions

$$E_0 = mc^2, \qquad m = E_0/c^2$$

With m defined as rest mass, this is mass-energy equivalence. Its inverse algebraic rearrangement is division by c^2. Choosing a logarithmic display of energy after dividing by a reference energy is a separate encoding decision. It is not a new relativistic compression law. [M12]

Source interpretation rule

The main specification uses defined quantities and neutral data operations. It does not adopt the earlier assistant's invented expansions or its unsupported physical, psychological, privacy and performance claims.

Historical context and corrections

The source conversation is preserved in Appendix B; this page identifies key factual boundaries.

Nuremberg: verified historical context

The International Military Tribunal indicted 24 defendants and tried 22. It convicted 19 and acquitted three. Judgments on 30 September and 1 October 1946 imposed 12 death sentences, three life sentences and four fixed prison terms. The attachment conflates the number indicted with the number tried. [M09]

The University of Bern's Rorschach archive inventory documents protocols, Gilbert retests and correspondence with Douglas M. Kelley. The inventory supports the occurrence of historical testing; it does not support the attachment's claim that every prisoner received daily visits, or supply a psychological interpretation for this project's graphics. [M10]

Claim in the supplied conversation	Correction or scope
abs(x) duplicates the point set	It folds the x coordinate. Generate original and reflected instances to display both halves.
Relative coordinates fully anonymize	They remove an origin or encode displacement. Identifiability needs a separate contextual assessment. [M11]
GraphicsBuffer eliminates all CPU work	Measure CPU uploads/submission and synchronization as well as GPU work. No benchmark was supplied.
Inverse $E = mc^2$ is logarithmic	$m = E_0/c^2$ is algebraic. Logarithmic scaling is independently defined. [M12]
Bounded geometry holds arbitrary recoverable detail	Finite storage and near-boundary conditioning limit reconstruction.
Grid snapping guarantees mechanical stability	Quantization changes coordinates. Mechanical stability needs a physical model and evidence.
Metaballs establish fluid simulation	A density-rendering technique is not evidence that governing fluid equations were solved.

The source's film/news references and other historical details remain quoted as source material rather than adopted as verified findings. Historical legal proceedings, psychological testing and modern graphics are separate contexts; their appearance in one conversation does not establish a causal or technical connection.

> **Status of Appendix B**
>
> It reproduces the supplied conversation, including prior assistant assertions. Read it as provenance. The definitions, evidence qualifications and corrections in the main synthesis govern the proposed technical specification.

Verification and data requirements

Numerical checks validate this specification’s examples; experiments must validate the proposed system.

Check performed	Result / interpretation
Log encoder fixtures	0, 1, 3, 7, 15 map to 0, 16,384, 32,768, 49,151, 65,535.
Permutation inverse	(r, θ, z, t) → .ywxz → .zxwy restores component order.
Digital interleave/demux	Four synthetic channels are recovered without reordering their samples.
Circular kinematics	r = 5 mm, ω = 0.2 rad/s gives speed 1 mm/s and radial acceleration -0.2 mm/s².
Display derivative fixture	Ṙ = 0.044444 and R̈ = -0.005926 for the declared uniform radial motion.
LUT mask and node count	1,224 nodes = 1,158 valid + 66 null; periodic angle handling and domain checks retained.
Quantization error	Observed node error 0.00022832 < 0.00033846 mW/cm² bound.

Measurements needed to turn the proposal into a system

Domain	Required evidence
Optics and CCD	Spectrum, irradiance map, sensor response, dark/flat calibration, timing, saturation limits.
Analog and transport	Transfer curve, uncertainty, channel settling, bandwidth, crosstalk and timestamp recovery.
Chemistry	Exact compositions, reactive groups, initiator, conversion measurements, phase stability and cure regime.
Structure and mechanics	Structural characterization, dimensions, hydration, mechanical loading protocol and controls.
Digital and visualization	Schema and unit checks, masks, error policy, round-trip limits and measured platform performance.

Record classes: mathematical definition, generated numerical fixture, published measurement, and attached source. The instrument calibration, formulation, conversion, structure and mechanical-response fields identify the available evidence for each operation.

The source records and current integer data bundle are embedded as file attachments. Standard PDF readers may expose them through an attachment panel; all substantive source text is also readable in the page appendices.

Primary references 1/3

New synthesis references M01-M24. Appendix A retains its original numbered bibliography.

[M01] Hamamatsu Photonics. Technical note: CCD image sensors.
Charge transfer, conversion, noise, response and calibration; sections 1-2, 1-3, 2 and 3-7.
www.hamamatsu.com/content/dam/hamamatsu-photonics/sites/documents/99_SALES_LIBRARY/ss...

[M02] Texas Instruments. LOG114 datasheet, revision C.
Log-ratio transfer, 0.375 V/decade output scale and stated input-current range.
www.ti.com/lit/ds/symlink/log114.pdf

[M03] Kester W, Freeman W. Practical Analog Design Techniques, Section 6. Analog Devices.
Multichannel acquisition, filtering, settling and simultaneous-sampling considerations.
www.analog.com/media/en/training-seminars/design-handbooks/Practical-Analog-Design-Te...

[M04] Microsoft. HLSL specification, section 5.5: Swizzle expressions.
Component selection/order, xyzw/rgba names and repeated-component rules.
microsoft.github.io/hlsl-specs/specs/5-Expr.html

[M05] Unity. Sample Graphics Buffer Operator. Visual Effect Graph 17.0.4.
Structured target, matching stride, blittable data and supported payload types.
docs.unity3d.com/Packages/com.unity.visualeffectgraph@17.0/manual/Operator-SampleBuff...

[M06] Unity. VisualEffect.SetGraphicsBuffer. Unity 6.0 API documentation.
Runtime binding and the non-serialized buffer-reference behavior.
docs.unity3d.com/6000.0/Documentation/ScriptReference/VFX.VisualEffect.SetGraphicsBuf...

[M07] Keijiro Takahashi. GeoVfx. Creator repository.
Geographical VFX examples using GeoTIFF-derived .geodata texture files.
github.com/keijiro/GeoVfx

[M08] Keijiro Takahashi. VfxGraphGraphicsBufferTest. Creator repository.
VFX Graph GraphicsBuffer operators receiving compute-shader data.
github.com/keijiro/VfxGraphGraphicsBufferTest

Primary references 2/3

New synthesis references M01-M24. Appendix A retains its original numbered bibliography.

[M09] US National Archives. Record Group 238: World War II War Crimes Records.

IMT administrative history, defendant counts and judgments.
www.archives.gov/research/guide-fed-records/groups/238.html

[M10] University of Bern. Inventory Fonds Marguerite Loosli-Usteri (2013).

Hermann Rorschach Archives, page 9, entries Rorsch LU 1:1:16 and 1:1:17.
www.img.unibe.ch/e40446/e617165/e617200/e617212/Ror-LU-Inv_ger.pdf

[M11] UK Information Commissioner’s Office. Pseudonymisation.

Distinguishes transformed/pseudonymised records from anonymised information; used here for context, not a jurisdiction-specific compliance assessment.
ico.org.uk/for-organisations/uk-gdpr-guidance-and-resources/data-sharing/anonymisatio...

[M12] Einstein Online. Special relativity: E=mc².

Institutional background on mass-energy equivalence; this report defines m as rest mass.
www.einstein-online.info/en/emc/

[M13] University of Kentucky mathematics notes. Poincaré’s Disk Model for Hyperbolic Geometry, chapter 9.

Disk metric and radial hyperbolic-distance relation.
www.ms.uky.edu/~droyster/courses/spring08/math6118/classnotes/chapter09.pdf

[M14] Cisco. DWDM Engineering and Planning Guide, chapter 1.

Optical multiplexing/demultiplexing and wavelength-separated transport.
www.cisco.com/c/en/us/td/docs/optical/15000r7_0/dwdm/planning/guide/70epg/d7ovw.html

[M15] Kolibaba TJ et al. Results of an Interlaboratory Study on the Working Curve in Vat Photopolymerization (2024).

NIST publication; Additive Manufacturing. DOI: 10.1016/j.addma.2024.104082.
www.nist.gov/publications/results-interlaboratory-study-working-curve-vat-photopolyme...

[M16] MIT OpenCourseWare. 16.07 Dynamics, Lecture L5: Other Coordinate Systems (2009).

Polar velocity and acceleration expressions; log-polar forms in this master are derived by substitution.
ocw.mit.edu/courses/16-07-dynamics-fall-2009/57081b546fff23e6b88dbac0ab859c7d_MIT16_0...

Primary references 3/3

New synthesis references M01-M24. Appendix A retains its original numbered bibliography.

[M17] IUPAC Gold Book. Curing.

Terminology for conversion into a polymer network; source definition.
goldbook.iupac.org/terms/view/CT07137

[M18] IUPAC Gold Book. Crystalline state.

Terminology for crystalline order; distinct from a macroscopic shape.
goldbook.iupac.org/terms/view/12754

[M19] Burdick JA et al. Controlled degradation and mechanical behavior of photopolymerized hyaluronic acid networks (2005).

Biomacromolecules. DOI: 10.1021/bm049508a. Material precedent, not the formulation of this project.
doi.org/10.1021/bm049508a

[M20] Kousaalya AB, Ayalew B, Pilla S. Photopolymerization of Acrylated Epoxidized Soybean Oil: A Photocalorimetry-Based Kinetic Study (2019).

ACS Omega 4:21799-21808. DOI: 10.1021/acsomega.9b02680. Reactive lipid-derived formulation precedent.
doi.org/10.1021/acsomega.9b02680

[M21] Pan D et al. Chain Packing in the Inverted Hexagonal Phase of Phospholipids: A Study by X-ray Anomalous Diffraction on Bromine-labeled Chains (2006).

JACS 128:3800-3807. DOI: 10.1021/ja058045t. Structural characterization.
doi.org/10.1021/ja058045t

[M22] O’Brien AK, Bowman CN. Impact of Oxygen on Photopolymerization Kinetics and Polymer Structure (2006).

Macromolecules 39:2501-2506. DOI: 10.1021/ma051863l. Oxygen-dependent reaction effects.
doi.org/10.1021/ma051863l

[M23] Sun G, Wu X, Liu R. A comprehensive investigation of acrylates photopolymerization shrinkage stress from micro and macro perspectives by real time MIR-photo-rheology (2021).

Progress in Organic Coatings 155:106229. DOI: 10.1016/j.porgcoat.2021.106229.
doi.org/10.1016/j.porgcoat.2021.106229

[M24] Hofstetter C et al. Combining cure depth and cure degree, a new way to fully characterize novel photopolymers (2018).

Additive Manufacturing 24:166-172. DOI: 10.1016/j.addma.2018.09.025.
doi.org/10.1016/j.addma.2018.09.025


Web sources consulted 30 October 2026. Equations and numerical fixtures marked as definitions or calculations are the report’s own specification. User-supplied sources are preserved for provenance and are not treated as external scientific evidence.

BIOCHEMISTRY + BIOMECHANICS

Two-stage lipid-carbohydrate preparation

Preparaat 1: lipids | Preparaat 2: carbohydrates
UV curing, hexagonal architecture and crystalline order

A plausible concept is to prepare defined lipid domains, incorporate them into a photocurable carbohydrate-polymer formulation, and use light to fix a designed shape. Any claim of internal hexagonal or crystalline order requires separate evidence. [1,2]



Schematic only. Colors identify phases; no size, dose or mechanical property is implied.

Central distinction

UV curing forms chemical bonds in a reactive formulation. A hexagonal mold defines geometry. Crystallization requires evidence of ordered structure. None of these observations substitutes for the others. [1,2]

Interpretation used in this report

Here, **preparaat** means a material preparation, and the two stages produce one composite. The main proposal is a carbohydrate-derived network containing lipid domains. A separate lipid coating plus carbohydrate coating is discussed as an alternative with its own adhesion problem.

No lipid identity, carbohydrate identity, resin, wavelength, specimen dimensions or intended application was specified. The examples below explain possible chemistry; they do not constitute a validated formulation or a prediction of performance.

Mathematical extension added

Polar kinematics, log-polar LUT and exposure integration: pages 10-15.

What each preparation contributes

Define the molecular role before choosing the curing system.

Preparaat 1 - lipids

Lipids are a broad family. Neutral oils can provide hydrophobic domains; amphiphilic lipids, with polar and nonpolar regions, can form organized structures in water. The selected lipid, hydration and environment determine the phase. A droplet dispersion and an inverse hexagonal lipid phase are different starting materials. [6,7]

For the main proposed architecture, Stage 1 establishes the lipid identity, amount, domain size and stability over the intended processing interval. Its role could be compartmentalization or a change in mechanical response. These are design aims to test; lipid addition does not establish reinforcement.

Preparaat 2 - carbohydrates

Choose a specific carbohydrate polymer and a defined reactive derivative. Methacrylated hyaluronic acid (MeHA), for example, is a polysaccharide modified with polymerizable groups. Published studies formed photocrosslinked HA networks and showed that polymer concentration and degree of modification influence swelling and mechanical properties. [3,4]

In an aqueous formulation, light-induced network formation can produce a **hydrogel**: a polymer network containing substantial water. A gel can retain its shape while remaining soft. Native sugar, an unmodified polysaccharide and a photocurable derivative are therefore different formulation choices. [1,3,4]

Material choice	Role and chemical limitation
Native lipid domains	May be physically trapped in the carbohydrate network. Covalent attachment is not established by entrapment.
Reactive lipid-derived resin	Acrylated epoxidized soybean oil (AESO) is a documented photocurable example. Its chemical modification is essential to that example. It is not evidence that arbitrary oil will UV-harden. [5]
Functionalized polysaccharide	Can supply the continuous photocrosslinked phase when its reactive groups, initiator and illumination are compatible. MeHA is an example, not a selected recipe. [3,4]

The interface is part of the design


The proposed mixture must remain sufficiently uniform while it is shaped and cured. Test wetting, coalescence, phase separation and lipid retention. Mixing may change hydration, ionic conditions or the internal lipid phase; repeat structural measurements after incorporation and after curing. A stable-looking specimen does not prove that the original nanostructure survived.

Alternative laminate: depositing a carbohydrate layer on a lipid layer requires a separately evaluated interface. Adhesion and differential swelling become central. Simply combining the preparations neither creates a glycolipid nor guarantees chemical bonds between the phases.

What does “hexagonal” mean?


Geometry, liquid-crystalline order and molecular crystals require different evidence.

EXTERNAL SHAPE




A molded hexagonal object
or a cellular honeycomb

LIPID MESOPHASE



Cylindrical water channels
seen in cross-section

MOLECULAR ORDER



Illustrative hexagonal cell
Actual lattice must be indexed

All drawings are conceptual and have independent scales. No measured crystal structure is shown.

1. A six-sided object or a honeycomb

A mold, mask, projector or printing path can impose a macroscopic or microscopic hexagonal shape. A solid hexagonal prism is different from a honeycomb with open cells. Verify dimensions and cell walls by calibrated imaging. The external outline alone says nothing about molecular crystallinity. [2]

2. A hexagonal liquid-crystalline lipid phase

In an inverse hexagonal phase, H_{II}, water channels are surrounded by lipid monolayers and arranged on a two-dimensional hexagonal lattice. This is mesophase order. It does not by itself establish a three-dimensional molecular crystal. Appropriate lipid chemistry and environmental conditions are required. [2,6,7]

Small-angle X-ray scattering (SAXS) can support phase identification through an indexed reflection sequence. For an ideal two-dimensional hexagonal lattice, characteristic q-position ratios include **1 : √3 : 2 : √7**. Several consistent peaks and a structural model are more informative than one peak or optical texture. Compare before mixing, after mixing and after curing. [7]

3. A molecular crystal

A claim of crystalline phase identity needs suitable diffraction evidence, commonly wide-angle X-ray scattering or X-ray diffraction (WAXS/XRD), with thermal analysis as support where appropriate. A six-sided face does not identify the crystal system. [2]

A real precedent, with a specific limitation

Engineered reactive lipids have been crosslinked while retaining H_{II} order. The cited study used redox initiation. It supports the possibility of fixing an appropriately designed mesophase, but does not validate a generic UV resin mixed with lipids and carbohydrates. [6]

What the light diagram establishes

A Fresnel lens and a parabolic reflector are alternative collimating approaches.




Figure 1. User-supplied reference image, reproduced with its original credit: © Parabolix Lighting LLC, www.parabolixlight.com. The illustration concerns ray direction; it provides no measured UV spectrum or irradiance.

Collimation controls direction

For an ideal point source at the relevant focal position, a Fresnel lens refracts light into a near-parallel beam; a paraboloidal reflector performs the corresponding operation by reflection. Real source size and alignment limit collimation. Lens transmission and mirror reflectance must suit the actual curing wavelength. [8,10]

Uniform exposure is a separate requirement

Parallel rays do not guarantee equal irradiance over the specimen. Newport’s flood-exposure design, for example, combines a homogenizer with a collimating lens. For this concept, measure the illumination across the specimen plane with the actual window, optic and patterning arrangement installed. [9]

How this relates to a hexagon

Use a defined mold or a validated exposure pattern to establish the external shape. The collimator itself supplies neither a hexagonal mold nor evidence of hexagonal molecular order. Select the source by spectral overlap with the photoinitiating chemistry, then calibrate the delivered exposure. [8-11]

How UV hardening would work

Network formation, cure depth and final mechanical properties are separate measurements.

A representative reaction mechanism

For a free-radical (meth)acrylate formulation, an appropriate photoinitiating system absorbs light and generates reactive radicals. These react with polymerizable groups; sufficient intermolecular linking produces a network. The carbohydrate backbone supplies the polymer scaffold in the MeHA example. Other UV-resin chemistries can use different mechanisms. [1,3,5]

Conceptual sequence

Light absorption → reactive species → polymerization / crosslinking → network formation
For the proposed aqueous carbohydrate route, the product may remain a hydrated gel. Hardness, stiffness and crystallinity must each be established separately.

Quantify the exposure at the specimen

Quantity	Expression and interpretation
Radiant exposure H	$\mathbf{H(x,y) = \int I(x,y,t)\, dt}$ For constant irradiance, H = I × t. With I in mW/cm² and t in seconds, H is in mJ/cm². Record the spectrum as well as the energy. [11]
Calibrated cure-depth model	$\mathbf{C_d = D_p \ln(H / H_c)}$, for $H > H_c$ C_d: gelled depth; D_p: fitted optical penetration parameter; H_c: fitted gelation threshold. This is an empirical working-curve approximation within its validated range. [11]
Conversion α	$\mathbf{\alpha = 1 - R_{after} / R_{before}}$ R can be a reactive-group spectral signal normalized to a stable reference. The chosen band, baseline and depth sampling must be appropriate to the chemistry. [5,12,13]

Illustrative arithmetic only: 5 mW/cm² for 20 s gives 100 mJ/cm² at the measured plane. This is not a recommended curing dose. Equal total exposure at different irradiances need not give equal conversion, and none of these numbers specifies the energy reaching the specimen interior. [11]

Why a solid-looking surface is insufficient

Cure depth identifies a gelled layer; it does not alone determine conversion or stiffness. Oxygen can inhibit free-radical polymerization near an exposed surface, while reaction kinetics and optical attenuation can produce depth-dependent curing. Lipid domains may change scattering or phase partitioning, so the complete mixture needs its own measurements. [11-13]

Record dimensional change and temperature as well as conversion. Acrylate polymerization can generate shrinkage stress; in this composite, the resulting interfacial or shape changes are hypotheses to examine. A rigid dry object requires a specifically designed formulation and drying or post-processing assessment. [14]

How the composite may carry load

The following effects are testable hypotheses, not measured performance claims.

Biomechanics here concerns how the bio-derived composite deforms, relaxes and fails under controlled loading. Hydration and test conditions are part of the material description.

Property	Meaning for this material
Stiffness / modulus	Resistance to deformation at a stated strain range. Greater stiffness does not automatically mean greater strength or toughness.
Strength	Stress associated with a defined failure or yielding criterion. Report the failure mode, not only the maximum force.
Toughness / energy absorption	Energy needed for fracture, or energy absorbed during a defined loading path. These require a specified test and are not interchangeable.
Hardness	Resistance to localized indentation under a stated method. A shape-stable gel need not be hard.

Constituents, interfaces and architecture

Carbohydrate network. Polymer identity, concentration, reactive-group density, conversion and hydration help determine mechanical response. HA studies demonstrate that formulation changes alter swelling and moduli, but their numerical results cannot be transferred to this unspecified composite. [3,4]

Lipid domains. Soft inclusions could lower an effective modulus or alter energy dissipation. Solid lipid domains could behave differently. Poorly coupled domains could act as defects. Domain size, lipid state and interfacial bonding determine which explanation is consistent with the measurements; lipid content alone is insufficient.

Hexagonal architecture. For a honeycomb, wall thickness, cell size, relative density, vertices, defects and loading direction matter. A published polymer-honeycomb study found that changing vertex architecture changed deformation and mechanical performance. This supports testing the actual geometry; it does not supply a strength prediction for the proposed chemistry. [15]

Report mechanics in the state of intended use

Specify hydration medium, conditioning time, temperature, specimen dimensions and loading rate. Include relaxation or cyclic loading if time dependence matters. Test after conditioning as well as after fabrication, so swelling or lipid loss is not hidden by a dry-only result.

Minimal compression quantities

$\sigma = F / A_0 \quad \varepsilon = \Delta h / h_0 \quad E_{app} = \Delta\sigma / \Delta\varepsilon$

Use a stated compression-positive convention and strain interval. F is force, A_0 the chosen initial area, h_0 initial height and Δh shortening. Gross-area stress for a honeycomb yields an effective structural modulus. It is not the intrinsic modulus of its solid walls.

A two-stage validation sequence

Move from an explicitly defined formulation to claims supported by measurements.

Stage 1 - establish Preparaat 1

Specify the lipid and its role; prepare a reproducible dispersion or selected self-assembled phase. Record composition, domain size, hydration and temperature. For an H_{II} claim, collect phase evidence before incorporation. Retain this material as a reference.

Stage 2 - combine, shape and cure Preparaat 2

Specify the carbohydrate derivative and photoinitiating system. Establish compatibility with Preparaat 1, impose the chosen geometry, calibrate exposure on small specimens of known thickness, and measure conversion and properties after curing. Repeat phase and dimensional checks after the intended conditioning step.

Question	Measurement to plan	Claim it supports
Did a network form?	Reaction-specific FTIR/NIR, rheology and an appropriate gel / extractables assessment.	Chemical conversion and network development, separately from appearance. [5,12,13]
Is cure adequate throughout?	Irradiance map, thickness series, and accessible surface / interior conversion checks.	A process window for the actual resin, optics and specimen. [11,12]
Are lipids retained?	Domain imaging and a validated lipid-retention or mass-balance measurement.	Distribution and retention; not automatically chemical bonding.
Is hexagonal order present?	Dimensional imaging for shape; SAXS for mesophase; WAXS/XRD for crystal phase.	The specific scale and kind of order measured. [2,7]
Is the structure useful?	Compression or tension, relaxation / cycles as relevant, and failure imaging.	Mechanical behavior under the reported test conditions.

Controls that separate the possible causes

Use the carbohydrate network without lipid; the combined formulation without exposure; Preparaat 1 before incorporation; and a geometry comparison under an explicit mass or dimension constraint. Compare independent preparation batches. Match non-lipid ingredients where possible and measure conversion, rather than assuming it is equal.

Information needed for an executable protocol

Exact lipid and carbohydrate identities; chemical modification; water or solvent content; resin and initiator; intended lipid fraction; specimen thickness and hexagon scale; source spectrum; delivered irradiance; target mechanical behavior; and wet or dry use conditions.

Defensible description at this stage: “A proposed two-stage lipid-carbohydrate composite with photocured hexagonal architecture.” Add “hexagonal liquid-crystalline lipid phase” or “crystalline” only when the relevant structural evidence supports that additional statement.

Sources and evidence

Primary studies and official technical references. Links are clickable.

[1] IUPAC. Curing. *Compendium of Chemical Terminology (Gold Book)*, online edition.
https://doi.org/10.1351/goldbook.CT07137
Terminology: chemical curing is distinct from crystallization and physical aging.

[2] IUPAC. Crystalline state. *Gold Book*, online edition.
https://doi.org/10.1351/goldbook.12754
Terminology: three-dimensional long-range atomic order; mesophase distinction.

[3] Burdick JA, Chung C, Jia X, Randolph MA, Langer R. Controlled Degradation and Mechanical Behavior of Photopolymerized Hyaluronic Acid Networks. *Biomacromolecules*. 2005;6:386-391.
https://doi.org/10.1021/bm049508a
Primary research: modified HA photogels, swelling, mechanics and degradation.

[4] Bencherif SA et al. Influence of the degree of methacrylation on hyaluronic acid hydrogels properties. *Biomaterials*. 2008;29:1739-1749.
https://doi.org/10.1016/j.biomaterials.2007.11.047
Primary research: degree of modification and concentration affect hydrogel properties.

[5] Kousaalya AB, Ayalew B, Pilla S. Photopolymerization of Acrylated Epoxidized Soybean Oil: A Photocalorimetry-Based Kinetic Study. *ACS Omega*. 2019;4:21799-21808.
https://doi.org/10.1021/acsomega.9b02680
Primary research: a reactive oil-derived formulation; cure kinetics and incomplete conversion.

[6] Srisiri W, Sisson TM, O'Brien DF, McGrath KM, Han Y, Gruner SM. Polymerization of the Inverted Hexagonal Phase. *Journal of the American Chemical Society*. 1997;119:4866-4873.
https://doi.org/10.1021/ja970052x
Primary research: reactive lipid mesophase fixation using redox initiation.

[7] Pan D, Wang W, Liu W, Yang L, Huang HW. Chain Packing in the Inverted Hexagonal Phase of Phospholipids: A Study by X-ray Anomalous Diffraction on Bromine-labeled Chains. *Journal of the American Chemical Society*. 2006;128:3800-3807.
https://doi.org/10.1021/ja058045t
Primary research: HII structure, indexed reflections and lipid-chain packing.

The published examples support individual mechanisms. They do not establish a combined lipid-carbohydrate formulation for the proposed specimen. Experimental choices, controls and the two-stage architecture in this report are proposed reasoning, clearly separated from reported results.

Optics, cure and mechanics

Technical sources accessed 30 October 2026; publication dates are shown below.

[8] Edmund Optics. Advantages of Fresnel Lenses. Manufacturer technical reference.
Technical note
Focal placement, collimation and wavelength-dependent substrate choice.

[9] Newport / Oriel. Flood Exposure Sources. Manufacturer technical documentation.
Technical documentation
Separate functions of beam homogenization and collimation.

[10] Newport. Light Collection and Optical System Throughput. Manufacturer technical reference.
Technical note
Finite-source effects, optical transmission and paraboloidal reflectors.

[11] Kolibaba TJ et al. Results of an interlaboratory study on the working curve in vat photopolymerization. *Additive Manufacturing*. 2024;84:104082.
https://doi.org/10.1016/j.addma.2024.104082
Primary research: calibration variability and working-curve model limitations.

[12] Hofstetter C, Orman S, Baudis S, Stampfl J. Combining cure depth and cure degree, a new way to fully characterize novel photopolymers. *Additive Manufacturing*. 2018;24:166-172.
https://doi.org/10.1016/j.addma.2018.09.025
Primary research: cure depth alone does not determine cured-layer mechanics.

[13] O'Brien AK, Bowman CN. Impact of Oxygen on Photopolymerization Kinetics and Polymer Structure. *Macromolecules*. 2006;39:2501-2506.
https://doi.org/10.1021/ma051863l
Primary research: oxygen inhibition and spatial conversion differences.

[14] Sun G, Wu X, Liu R. A comprehensive investigation of acrylates photopolymerization shrinkage stress from micro and macro perspectives by real time MIR-photo-rheology. *Progress in Organic Coatings*. 2021;155:106229.
https://doi.org/10.1016/j.porgcoat.2021.106229
Primary research: conversion, modulus development and shrinkage stress.

[15] Tao Y, Chen X, Lu S. Out-of-Plane Mechanical Behavior of 3D-Printed Polymeric Circular-Vertex-Based Hierarchical Hexagonal Honeycombs. *Polymers*. 2025;17:862.
https://doi.org/10.3390/polym17070862
Primary research: architecture-dependent honeycomb deformation and mechanics.

Image credit: the supplied collimation figure retains the Parabolix Lighting LLC credit. All other diagrams were drawn specifically for this conceptual report and represent no experimental data.

Kinematic calculus in polar coordinates

Interpretation: polar means spatial coordinates; LUT means lookup table.

The extension describes the motion of a light spot, stage or tracked material point. A log-polar grid addresses positions; a separate logarithmic encoding stores a physical field. These mathematical operations do not establish chemical conversion, stiffness or crystalline order.

Position, velocity and acceleration

For a fixed inertial origin, r is radius and θ is angle in radians. The radial and circumferential unit vectors rotate with θ. A dot denotes a derivative with respect to time. [A1]

$$x = r\cos\theta, \qquad y = r\sin\theta$$

$$\mathbf{v} = \dot{r}\,\mathbf{e}_r + r\dot{\theta}\,\mathbf{e}_\theta$$

$$\mathbf{a} = (\ddot{r} - r\dot{\theta}^2)\mathbf{e}_r + (r\ddot{\theta} + 2\dot{r}\dot{\theta})\mathbf{e}_\theta$$

Change the radial coordinate to a logarithm

$$\rho = \ln(r/r_{\mathrm{ref}}), \qquad r = r_{\mathrm{ref}}e^{\rho}, \qquad r > 0$$

The positive reference length r_{ref} makes the logarithm dimensionless. Direct differentiation gives dr/dt = r dρ/dt and $d^2r/dt^2 = r[d^2\rho/dt^2 + (d\rho/dt)^2]$. Substitution produces:

$$\mathbf{v} = r\dot{\rho}\,\mathbf{e}_r + r\dot{\theta}\,\mathbf{e}_\theta$$

$$\mathbf{a} = r(\ddot{\rho} + \dot{\rho}^2 - \dot{\theta}^2)\mathbf{e}_r + r(\ddot{\theta} + 2\dot{\rho}\dot{\theta})\mathbf{e}_\theta$$

$$|\mathbf{v}| = r\sqrt{\dot{\rho}^2 + \dot{\theta}^2}$$

Two implementation rules

Use an **unwrapped angle** when differentiating a trajectory, so crossing 2π does not create an artificial jump. Use a wrapped angle only for periodic LUT addressing. Constant dρ/dt produces exponential radial motion, not constant radial speed.

The radius zero is outside the logarithmic coordinate domain. The supplied example tabulates r ≥ 0.5 mm, records the center point separately, and treats the remaining central disk as unrepresented. It does not silently replace that disk with zero.

A hexagon on a log-polar grid

The boundary describes the specimen outline; it is not a crystal-lattice model.


Let a be the apothem: the distance from the origin to a face. The six outward face-normal angles are $\varphi_k = \theta_0 + k\pi/3$, for k = 0,…,5. Intersecting the six half-planes gives the radial boundary:

$$r_{\mathrm{hex}}(\theta) = \frac{a}{\max\limits_{k=0,\ldots,5} \cos(\theta - \phi_k)}, \qquad a \le r_{\mathrm{hex}} \le \frac{2a}{\sqrt{3}}$$

A point is inside the specimen when $0 \le r \le r_{\mathrm{hex}}(\theta)$. The synthetic LUT uses a = 10 mm, $\theta_0 = 0$, and outer radius $R = 2a/\sqrt{3} = 11.547005$ mm.

Log-polar grid inside a regular hexagon

17 radial nodes × 72 angles; every sixth angular ray shown
Face-normal angle θ₀ = 0; geometric radius 0.5 to 11.547 mm



Synthetic geometry; no measured optical data

Area and derivatives need geometric factors

$$dA = r\,dr\,d\theta = r^2\,d\rho\,d\theta$$

Equal log-polar cells have unequal physical areas. For an unclipped annular sector, its area is $\tfrac{1}{2}(r_{\mathrm{outer}}^2 - r_{\mathrm{inner}}^2)\Delta\theta$. Clip boundary cells to the hexagon when computing area integrals. Convert mm² to cm² by dividing by 100 when combining area with values per cm².

Away from the center, $\partial/\partial r = (1/r)\partial/\partial\rho$. Likewise, gradients and Laplacians in physical space need the coordinate metric; ordinary index differences are not already physical derivatives.

Geometry limits: a hexagonal boundary has sharp vertices, so a finite-acceleration path needs rounded corners or stops if it follows the perimeter. A hexagonal mask does not require perimeter scanning. Sixfold geometry also does not guarantee sixfold illumination symmetry.

Log-encoded LUT values

A zero-preserving encoding for nonnegative irradiance, independent of grid coordinates.

Let I be irradiance, I_0 a positive encoding scale, and I_{max} the declared upper limit. All three use the same units. I_0 is a storage parameter; it is not a curing threshold. The proposed encoding uses natural logarithms:

$$L = \ln(1 + I_{max}/I_0), \qquad u = \frac{\ln(1 + I/I_0)}{L}$$

$$q = \left\lfloor 65535u + \tfrac{1}{2} \right\rfloor, \qquad 0 \le I \le I_{max}$$

$$\hat{I} = I_0\left[\exp\left(\frac{qL}{65535}\right) - 1\right]$$

The integer q uses 16 unsigned bits. The formula rounds half values upward. A separate validity status distinguishes a genuine zero, an absent value and an out-of-range value.

Calculated encoding example

Choose I_0 = 1 mW/cm² and I_{max} = 15 mW/cm², so L = ln(16). These are synthetic numerical choices, not curing recommendations.

I (mW/cm²)	u	q (uint16)	Decoded I (mW/cm²)
0	0	0	0
1	0.25	16384	1.000021154
3	0.50	32768	3.000084615
7	0.75	49151	6.999915386
15	1	65535	15

Quantization has a calculable bound

$$\delta = \frac{L}{2 \cdot 65535}, \qquad |\hat{I} - I| \le (I + I_0)(e^{\delta} - 1)$$

Across this declared range, the bound is 0.000338460 mW/cm². It covers encoding quantization only. It says nothing about optical measurement error, interpolation error, alignment or material-model uncertainty.

Do physical arithmetic on decoded values

Decode irradiance before additive interpolation or integration over time. Interpolating u first produces a shifted geometric mean of I + I_0, which is a different model from arithmetic interpolation of I. Signed velocity or acceleration components need their own signed representation.

The supplied example LUT

Reusable JSON with explicit coordinates, encoding, validity and provenance.

The companion JSON is an **illustrative incident-irradiance field** on a specimen plane. Its values are analytically generated. It is not a measured map of your light source, a machine trajectory, or a prediction of either preparation's response.

Specification	Value / convention
Coordinate frame	Right-handed Cartesian plane; θ measured counterclockwise from +x; radii in mm and angles in radians.
Radial sampling	17 point nodes, geometrically spaced from 0.5 mm to 11.547005 mm; ρ = ln(r / 1 mm).
Angular sampling	72 point nodes at 5° intervals; 0° is included and 360° is excluded. Angular interpolation wraps.
Geometry	Regular hexagon, apothem 10 mm, outward face normal $\theta_0 = 0$. Outside-domain entries are null, not zero irradiance.
Stored value	16-bit log-encoded irradiance; $I_0 = 1$ and $I_{max} = 15$ mW/cm²; separate geometry / validity information.
Central region	The center point has synthetic I = 12 mW/cm². The open region 0 < r < 0.5 mm is not tabulated.
Calibration status	Synthetic. Spectrum, optical calibration and material-response parameters are unspecified.

The illustrative field

$$I(r,\theta) = 12e^{-(r/8)^2}\left[1 + 0.15(r/R)^6\cos(6\theta)\right]$$

Here r and R are numerical lengths in mm, R = 11.547005 mm, and I is in mW/cm². The angular term tends to zero smoothly at the center. The formula has sixfold symmetry by design; a real optical map must demonstrate that symmetry before any angular data reduction.

Retrieval contract

1. Transform the query into the declared frame and check the geometry.
2. Compute ρ, bracket the radius, and wrap the angular index.
3. Require a valid interpolation stencil; flag a missing or boundary-crossing stencil.
4. Decode q to irradiance, then apply bilinear weights in (ρ, θ).
5. Return irradiance and validity. Never silently extrapolate or fill unknowns with zero.

Interpolation weights are explicitly linear in ρ here. Linear weights in physical radius r would be another legitimate choice with different numerical behavior. The stored samples are point values, not equal-area averages.

From motion to radiant exposure

Integrate the illumination seen by each material point, in a consistent coordinate frame.

A moving specimen and a moving beam

Let X identify a specimen point. For planar rigid motion, c(t) is translation, R(φ) is a rotation matrix, and b(t) is the beam-center trajectory in laboratory coordinates:

$$\mathbf{x}_{\text{lab}}(t;\mathbf{X}) = \mathbf{c}(t) + R(\phi(t))\mathbf{X}$$

$$I(\mathbf{X},t) = g(t)p(t)B(\mathbf{x}_{\text{lab}}(t;\mathbf{X}) - \mathbf{b}(t))$$

B is a calibrated beam irradiance profile at a reference setting; g is a shutter fraction; p is a relative source multiplier whose scaling must be calibrated. This expression assumes a fixed-height planar geometry and a translated beam profile. Other optical arrangements need an appropriate forward model.

$$H(\mathbf{X}) = \int_0^T I(\mathbf{X},t)\,dt$$

With I in mW/cm² and time in seconds, H is in mJ/cm². A numerical implementation sums decoded irradiance multiplied by time increments, using a documented quadrature rule. H = It applies only when irradiance at that material point is constant.

An inverse controller is a separate calculation

$$H_j = \sum_k A_{jk}\tau_k, \qquad \tau_k \geq 0$$

A_{jk} describes the calibrated irradiance reaching target j from exposure position k, and τ_k is dwell time. Solving for a target exposure requires overlap and motion constraints. A pointwise rule $\tau = H_{target}/I$ cannot generally replace this spatial model.

Connection to the two preparations

Preparaat 1 contributes the characterized lipid domains. During Stage 2, the carbohydrate formulation and lipid-containing specimen can alter transmission, scattering or cure behavior. A surface irradiance LUT therefore does not automatically describe absorbed energy or conversion inside the composite.

Kinematics, reaction kinetics and mechanics

Kinematics specifies motion or deformation. Reaction kinetics describes conversion over time. Mechanical response requires a constitutive relationship and boundary conditions. A measured relation between formulation, illumination history, conversion and properties is needed to connect these parts. [A2,A3]

A calibrated working curve may use $C_d = D_p \ln(H/H_c)$ within a validated range. Its logarithm of H/H_c is not the same variable as the log1p storage code u. Equal total exposure also need not yield equal conversion under different intensity histories. [A2,A3]

Calculated example and implementation checks

All numerical values in this supplement are synthetic or directly calculated.

Circular trajectory inside the hexagon

$$r = 5\ \text{mm}, \qquad \theta(t) = 0.2t, \qquad r_{\text{ref}} = 1\ \text{mm}$$

Quantity	Calculated value
Log radius ρ	ln(5) = 1.609438
Radial / circumferential speed	$v_r = 0$; $v_\theta = 1$ mm/s
Radial / circumferential acceleration	$a_r = -0.2$ mm/s²; $a_\theta = 0$
One revolution	T = 2π / 0.2 = 31.415927 s

This calculation specifies a trajectory, not the exposure of the specimen. The beam footprint and the relative motion in the previous section are still needed. The path lies inside the example hexagon because its radius is below the 10 mm apothem.

Checks applied to the example

The supplied generator checks grid dimensions and monotonic radial nodes, angular periodicity, the hexagonal mask, integer ranges, the five encoding examples, the analytical quantization bound, and the circular-motion identities. These numerical checks validate the demonstration’s arithmetic; they do not calibrate a real curing process.

References for this extension

[A1] Widnall S, Peraire J. Lecture L5: Other Coordinate Systems. MIT 16.07 Dynamics, Fall 2009.

Open source - Standard polar-coordinate velocity and acceleration. Log-coordinate expressions above follow by substitution.

[A2] Kolibaba TJ et al. Results of an interlaboratory study on the working curve in vat photopolymerization. Additive Manufacturing. 2024;84:104082.

https://doi.org/10.1016/j.addma.2024.104082 - Primary research on calibration and limitations of cure-depth working curves.

[A3] The reciprocity law concerning light dose relationships applied to BisGMA/TEGDMA photopolymers: theoretical analysis and experimental characterization. Dental Materials. 2014. PubMed record 24674341.

Open source - Primary research showing that exposure alone need not determine conversion and shrinkage stress.

Model status: the hexagon equations, encoding choice, synthetic field and LUT contract are mathematical design choices developed for this report. No new experimental material data or crystal-structure evidence is supplied.

Appendix B | Supplied conversation

This appendix reproduces the supplied conversation in its original order. Its wording, identifiers, examples, source snippets, and diagrams are retained. The earlier responses are retained as quoted source records. The current technical definitions, operation domains and data classes are specified in the UNIVERSAL sections and embedded machine packet. Line wrapping and pagination have been adjusted for readability, while the original text and the sequence of its contents have been preserved here.

SOURCE CONVERSATION - ORIGINAL WORDING

wat wordt er met mensen tijdens het neurenberg bilder gedaan

Tijdens het Proces van Neurenberg (de rechtszaken tegen nazi-kopstukken na de Tweede Wereldoorlog) werden de verdachten officieel aangeklaagd, psychologisch onderzocht en uiteindelijk berecht door een internationaal tribunaal.
Omdat er recent ook een Hollywood-speelfilm genaamd Nuremberg is uitgebracht, kan het zijn dat je doelt op wat er met de mensen (de gevangenen) gebeurde tijdens hun detentie en de rechtszaak zelf. Dit is wat er destijds concreet met de gevangenen werd gedaan:

1. Ze werden onderworpen aan intensief psychologisch onderzoek

Alle gevangenen in Neurenberg werden dagelijks bezocht door Amerikaanse psychiaters en psychologen (zoals dr. Douglas Kelley en Gustave Gilbert). Ze kregen IQ-tests en rorschachtests. Het doel hiervan was om te begrijpen hoe deze ogenschijnlijk 'normale' of hoogopgeleide mannen in staat waren geweest tot zulke ongekende gruweldaden.

2. Ze werden geconfronteerd met filmbeelden van de concentratiekampen

Tijdens het proces kregen de nazi-kopstukken in de rechtszaal schokkende filmopnamen en foto's te zien die de geallieerden hadden gemaakt tijdens de bevrijding van de kampen. De aanklagers gebruikten deze beelden als onomstotelijk bewijsmateriaal. De reacties van de gevangenen op deze beelden (variërend van shock en huilbuien tot onverschilligheid) werden nauwkeurig vastgelegd door de aanwezige psychologen.

3. Ze kregen een officiële verdediging

In tegenstelling tot wat sommigen wilden (zoals Churchill, die nazi-leiders in eerste instantie zonder proces wilde executeren), kregen de gevangenen een formele rechtszaak. Ze kregen Duitse advocaten toegewezen, mochten getuigen oproepen en mochten zichzelf verdedigen. Hun belangrijkste verweer — dat zij "slechts bevelen opvolgden" (Befehl ist Befehl) — werd door de rechtbank resoluut verworpen.

4. Het vonnis en de executies

Op 1 oktober 1946 deed de rechtbank uitspraak over de eerste groep van 24 hoofdverdachten:
• 12 nazi-leiders kregen de doodstraf door ophanging (onder wie Joachim von Ribbentrop en Wilhelm Keitel).
• Hermann Göring, de belangrijkste overlevende nazi, ontsnapte enkele uren voor zijn executie aan de strop door in zijn cel zelfmoord te plegen met een cyaankalicapsule.
• 3 verdachten werden vrijgesproken.
• De overigen kregen lange gevangenisstraffen (variërend van 10 jaar tot levenslang, zoals Rudolf Hess).
Na dit eerste grote proces volgden er nog twaalf opeenvolgende processen waarin ook nazi-artsen, juristen en industriëlen werden berecht voor hun aandeel in de oorlogsmisdaden.
Bedoelde je specifiek de historische gebeurtenissen uit de rechtszaak van 1945-1946, of zocht je informatie over de recente speelfilm en hoe de acteurs deze gebeurtenissen uitbeelden? Laat het me weten, dan help ik je gericht verder!
•
Wikipedia
Proces van Neurenberg
van rechtvaardigheid is. Op 1 oktober 1946 werden de vonnissen voorgelezen.
•
Historiek
Proces van Neurenberg: berechting van het naziregime
Neurenberg, de vonnissen (1946), met commentaar van. Hoofdverdachten en vonnissen in Neurenberg

•
De Telegraaf
De erfenis van Neurenberg - De Telegraaf
Oct 13, 2026 — Churchill verzette zich tegen zo'n massale afrekening, maar voelde er wel voor de belangrijkste nazikopstukken zonder proces te ex...
Show all

rorschachtests keijiro vfx graph unity engine anonymizer J.I.T. SK plot test geospatial temporally

To bridge these seemingly disconnected concepts, you are describing a high-performance data pipeline that visualizes anonymized, spatiotemporal geospatial coordinate test plots as symmetrical, abstract structures (resembling Rorschach inkblots) inside the Unity Engine utilizing the Unity VFX Graph and Just-In-Time (J.I.T.) compilation.
Prominent Unity graphics evangelist Keijiro Takahashi has historically authored open-source repositories matching these domains, such as GeoVfx, which demonstrates how to feed raw geographic spatial coordinate data arrays into the Visual Effect Graph for GPU-accelerated mass rendering.

The Conceptual Technical Pipeline

```
[Raw Geospatial Time-Series Log]
               |
               ▼
   [Anonymizer & J.I.T. Script]  --> Strips PII / Strips spatial variance (Keeps delta steps)
               |
               ▼
[GraphicsBuffer / Compute Buffer] --> Passes raw float coordinates directly to GPU
               |
               ▼
   [Unity VFX Graph (Keijiro)]   --> Absolute X mirroring & custom Math node modifier
               |
               ▼
   [Symmetrical "Rorschach" Plot]
```

1. Geospatial & Temporal Anonymization

To map geospatial paths (X longitude, Y latitude, Z altitude) over time (T) without revealing actual locations, an anonymizer function strips identifying attributes. Instead of absolute global positioning, the data is J.I.T.-compiled or streamed as relative spatial vectors or delta movements (Δx, Δy, Δz). This preserves the temporal movement signatures (the speed, frequency, and curvature of a test plot) while completely masking the physical map coordinates.

2. Achieving the "Rorschach Test" Look in VFX Graph

To transform simple coordinate dots into organic, inkblot-like patterns, specific operations are computed directly on the GPU within the VFX Graph:
• Mirrored Symmetry (Symmetric X): The particle coordinates are duplicated along a central axis. In the VFX Graph, this is done by taking the absolute value abs(x) of the local position or using a reflection matrix, forcing any asymmetrical spatial trajectory to instantly mirror itself.
• Density & Blending (Fluid Simulation / Metaballs): Rather than rendering crisp points, particles use custom shaders with high overdraw, soft alpha blending, or signed distance fields (SDF). When thousands of temporal data points cluster together over time, they form smooth, bleed-like shapes resembling an ink blot on paper.
• GPU Buffer Injection: Keijiro’s technical approach frequently skips standard CPU overhead. Using a C# script, raw structured float arrays are written directly into a GraphicsBuffer. The VFX Graph reads this buffer dynamically, enabling millions of points to update at runtime with virtually zero CPU performance penalties.

3. Dynamic Demonstration

The mathematical visualization below models how raw asymmetrical spatiotemporal data paths are transformed when mapped through an absolute mirroring symmetry filter to create a unified Rorschach topology:
Are you attempting to implement a specific script or repository from Keijiro (like GeoVfx or VfxGraphGraphicsBufferTest), or do you need help writing the C# ComputeBuffer bridge to feed your temporal test coordinates directly into the VFX Graph? Let me know how you want to build this!

I Tom Klootwijk NL200678942 10-07-1990 antagonist JITSKE operate on collaborators against the prismatic gol ned log (e=mc^2 inverse logarithmic scaled etsching (escher impose able geo meet rij)

This technical framework translates into a specialized visual computing system: an inverse logarithmic geometric projection pipeline designed to map high-dimensional spatiotemporal data into self-contained, Escher-like recursive coordinate lattices.
By processing data against a "prismatic gol ned log" (a multi-spectral, non-linear geometric ledger), this architecture uses inverse relativistic formulas ($e=mc^2$ scaled inversely) to compress vast geographic data footprints into nested topological frameworks.

The Geometric & Algorithmic Matrix

```
[Raw Relativistic Spatiotemporal Ledger]
                    |
                    ▼
     [Inverse Logarithmic Scaling Layer]
                    |
                    ▼
     [M.C. Escher Spatial Transformation]
 (Hyperbolic Poincaré Disk / Isometric Tesselation)
                    |
                    ▼
       [Keijiro VFX Graph Render Matrix]
```

1. Inverse Logarithmic Scaling ($e=mc^2$ Inverse)

Standard relativistic mechanics expand infinitely at scale limits. By applying an inverse logarithmic scaling factor, the spatial metrics are inverted. Extremely large geospatial variables (macroscopic distances, cosmic intervals, or vast network coordinates) are compressed into highly manageable, dense localized nodes. The math ensures that as data complexity approaches infinity, its structural footprint is mathematically bound within a controlled, finite coordinate sphere.

2. M.C. Escher Geometry Imposition

To achieve an "Etching / Escher" structural composition (Escher-inpasbare geometrie), the pipeline applies hyperbolic non-Euclidean projections. The most efficient way to achieve this programmatically is via Poincaré Disk Transformations or complex Aperiodic Tesselation matrices:
• Recursive Scaling: Points moving outward from the origin are scaled progressively smaller using logarithmic decay functions, creating the illusion of infinite regression toward a perimeter boundary.
• Isometric Interlocking: Vertices are bound to an interlocking triangular or hexagonal grid constraint, forcing random temporal data paths to snap into structurally sound, repeatable geometric patterns.

3. Implementation in Unity VFX Graph

To visualize this system smoothly at runtime:
• The Antagonist Injection Vector (JITSKE Buffer): Operating as a custom J.I.T. Data Stream (Just-In-Time Scripted Kernel Engine), a specialized GraphicsBuffer is populated via C# using native array memory addresses.
• Custom Custom HLSL Expression Nodes: The inverse logarithmic equations and symmetry modifiers are computed inside custom HLSL sub-graphs within the Unity VFX Graph, removing calculations completely from the CPU and utilizing parallel processing threads.

Geometric Scaling Mapping

The function below visualizes how the inverse logarithmic mapping transforms an expanding data field into a bounded, highly organized geometric structure:
Are we optimizing the HLSL math block for the inverse logarithmic scaling formulas within your shader graph, or do you need the C# memory pointer configuration to safely stream the NL200678942 identity tracking logs into the graphics pipeline? Let me know which component you would like to construct next.