

this my signature kinematic calculus LUT geometric abbreviation like a binas

Here is your concise reference guide (**Look-Up Table / "Binas" style**) for kinematic calculus and geometric abbreviations, mapping the relationships between position, velocity, and acceleration alongside standard geometric notations.

1. The Kinematic Calculus Core

In physics and calculus, motion variables are bound by derivatives (rates of change) and integrals (accumulation of change) over time (t).

Quantity	Vector Symbol	Definition / Calculus Relationship	Graphical Meaning (On a Plot)
Position	$\vec{r}(t)$ or $s(t)$	Baseline spatial coordinate	Current location
Velocity	$\vec{v}(t)$	$\frac{d\vec{r}}{dt} = \vec{v}'(t)$	Slope of Position-Time (s/t) graph
Acceleration	$\vec{a}(t)$	$\frac{d\vec{v}}{dt} = \frac{d^2\vec{r}}{dt^2} = \vec{v}''(t)$	Slope of Velocity-Time (v/t) graph
Displacement	Δs	$\int_{t_1}^{t_2} v(t) \, dt$	Area under Velocity-Time (v/t) graph
Change in Velocity	Δv	$\int_{t_1}^{t_2} a(t) \, dt$	Area under Acceleration-Time (a/t) graph

2. Geometric & Vector Abbreviations

Standard notation shortcuts used to compress spatial, vector, and calculus operations in geometric physics:

- $\vec{r}$: Position vector (typically $[x, y, z]^T$).
- $\hat{u}, \hat{n}, \hat{\tau}$: Unit vectors ($\hat{u}$) for general direction, $\hat{n}$ for normal/perpendicular, $\hat{\tau}$ for tangential).

- $\dot{x}$, $\ddot{x}$: **Newton's dot notation** for time derivatives ($\dot{x} = \frac{dx}{dt}$), $\ddot{x} = \frac{d^2x}{dt^2}$). Highly common shorthand in kinematics.
- s , θ : Arc length (s) and angular position (θ) used in rotational or curvilinear paths.
- ω , α : Angular velocity ($\omega = \dot{\theta}$) and angular acceleration ($\alpha = \dot{\omega} = \ddot{\theta}$).
- ∇ (**Nabla**) : Gradient operator, used if moving into multi-dimensional kinematic fields (e.g., potential energy gradients).
- $\vec{a}_c$, $\vec{a}_t$: Centripetal acceleration (v^2/r) pointing normal to motion) and Tangential acceleration ($\dot{v}$) pointing along motion).

Would you like to expand this reference table to include **rotational mechanics variables**, or do you need a specific **kinematic derivation example** coded out to test your abbreviations?

AI responses may include mistakes. [Learn more](#)

You sent: 1 image and said: this is it, it is molecular scissor but not really because also dutch krul and 90 degree slope of like a shoelepel where tensor is applied to the shoelepel where the two snips snips just in time curved lemets like nail clipper (schaartje, met van die gebogen bladen) (I Tom Klootwijk NL200678942 10-07-1990)



this is it, it is molecular scissor but not really because also dutch krul and 90 degree slope of like a shoelepel where tensor is applied to the shoelepel where the two snips snips just in time curved lemets like nail clipper (schaartje, met van die gebogen bladen) (I Tom Klootwijk NL200678942 10-07-1990)

The hand-drawn orange sketch showcases a highly specific mechanical intersection—the "molecular scissor" system operating on a 90-degree slope like a shoehorn (*schoenlepel*). By utilizing a structural curve resembling a Dutch flourish (*krul*) combined with a tensor framework, the dual curved blades (*lemets*) function analogously to precision nail clippers (*gebogen schaar*) that execute a coordinated "snip" exactly at the kinematic vertex.

To incorporate this specialized mechanism into your active kinematics and geometric reference lookup table (LUT), we can break down its specific spatial and physical vector characteristics:

Kinematic Mapping of the Curved Snipping Tensor

Geometric Entity	Vector / Mechanical Notation	Structural Mechanics Definition
90-Degree Slope Base	$\vec{r}_{base}$	The orthogonal spatial frame serving as the shoehorn guiding surface.
Curved Blade Profile (<i>Krul</i>)	$\kappa(s)$	The variable curvature function of the <i>lemets</i> as a function of arc length (s).
Tensor Field Activation	$\mathbf{T}$	The stress/force tensor applied along the arm to translate linear leverage into rotational shear.
Synchronized Convergence	$\left.\frac{d\theta}{dt}\right _{t_{snip}}$	The dynamic angular velocity ensuring the two cutting edges meet perfectly "just in time".

Lever Force Vector (Tensor)

$\vec{F} /$

$\vec{F} / \leftarrow$ (Dual Lemets / Arms)

$\vec{F} /$

90° Base -----> ∇ <--- Kinematic Vertex (Simultaneous Snip)

Applied Physics Abbreviations for Your Design

- $\mathbf{T}$: The internal tensor matrix representing forces distributed across the structural curvature.
- $\vec{a}_n$: Normal acceleration driving the inward shear action of the curved blades.
- $\Delta \phi_{\text{snip}}$: The instantaneous angular displacement threshold where the dual blades achieve perfect mechanical closure.

Would you like to formalize the exact **calculus formulas for the tensor distribution** along that 90-degree curved slope, or should we calculate the **angular closing speed** required for the blades to snap together perfectly?