

To implement a mechanics system like the **HVT (High Value Target) Mark / Laser Designation** system using raycasting in a game engine like Unity or Unreal Engine, you need to cast a ray from the player's targeting device, identify if the hit object is a valid target, and then "paint" or mark that target for the team.

Below is a conceptual breakdown and a production-ready C# example (Unity) demonstrating how to achieve this.

Core Logic Workflow

1. **The Origin & Direction:** Cast a ray starting from the camera or the designator gadget's muzzle forward into the world.
2. **The Masking:** Use a `LayerMask` to ensure the ray only checks for colliders that can actually be targeted (e.g., enemy vehicles, infantry, HVTs).
3. **The Lock-On/Painting Phase:** Instead of instantly marking a target, check if the raycast continuously hits the target over a short duration (e.g., 1.5 seconds) to simulate "painting" the target.
4. **The Broadcast:** Once successfully designated, add a component or trigger an event that exposes the target's position globally (even through walls) to friendly engineering units or lock-on weapons.

C# Implementation Example (Unity)

Here is a script you can attach to your Laser Designator gadget or camera:

```
csharp

using UnityEngine;
using System.Collections;

public class LaserDesignator : MonoBehaviour
{
    [Header("Raycast Settings")]
    public Transform cameraTransform;
    public float maxDesignationDistance = 500f;
    public LayerMask targetableLayers;

    [Header("Designation Mechanics")]
    public float timeToPaint = 1.5f; // Time required to hold lock
    private float currentPaintTimer = 0f;
    private GameObject currentPotentialTarget;
    private bool isDesignating = false;
```

```

void Update()
{
    // Require the player to hold down the designation key (e.g., Left Click or Right
    Trigger)
    if (Input.GetButton("Fire1"))
    {
        PerformDesignationRaycast();
    }
    else
    {
        ResetDesignationProgress();
    }
}

void PerformDesignationRaycast()
{
    RaycastHit hit;
    Vector3 rayOrigin = cameraTransform.position;
    Vector3 rayDirection = cameraTransform.forward;

    // Perform the raycast
    if (Physics.Raycast(rayOrigin, rayDirection, out hit, maxDesignationDistance,
    targetableLayers))
    {
        GameObject hitObject = hit.collider.gameObject;

        // Check if the object can be an HVT/Target
        if (hitObject.CompareTag("Vehicle") || hitObject.CompareTag("HVT"))
        {
            // If it's a new target, reset the timer
            if (hitObject != currentPotentialTarget)
            {
                currentPotentialTarget = hitObject;
                currentPaintTimer = 0f;
                isDesignating = false;
                Debug.Log("Locking onto: " + currentPotentialTarget.name);
            }

            // Progress the painting timer while maintaining line-of-sight
            if (!isDesignating)
            {
                currentPaintTimer += Time.deltaTime;

                // UI progress bars can be updated here using (currentPaintTimer /
                timeToPaint)

                if (currentPaintTimer >= timeToPaint)
                {

```

```

        SuccessfullyPaintTarget(currentPotentialTarget);
    }
}
else
{
    // Ray hit something else (like terrain or a wall)
    ResetDesignationProgress();
}
}
else
{
    // Ray hit nothing
    ResetDesignationProgress();
}
}

void SuccessfullyPaintTarget(GameObject target)
{
    isDesignating = true;

    // Add or trigger your custom Target Marker component
    TargetMarker marker = target.GetComponent<TargetMarker>();
    if (marker != null)
    {
        marker.MarkTarget(duration: 10f); // Keep painted for 10 seconds
        Debug.Log(target.name + " SUCCESSFULLY DESIGNATED!");
    }
}

void ResetDesignationProgress()
{
    currentPotentialTarget = null;
    currentPaintTimer = 0f;
    isDesignating = false;
}
}

```

Use code with caution.

Accompanying Target Component

Attach a script like this to your targetable objects (Tanks, Helicopters, HVTs) to handle being spotted:

csharp

```

using UnityEngine;

public class TargetMarker : MonoBehaviour
{

```

```

private bool isMarked = false;
private float markerExpireTime = 0f;

// reference to a UI canvas or element that shows through walls
public GameObject 3dMarkerUI;

public void MarkTarget(float duration)
{
    isMarked = true;
    markerExpireTime = Time.time + duration;

    if (3dMarkerUI != null)
        3dMarkerUI.SetActive(true); // Expose to team UI

    // Change object layer or tags if your friendly homing missiles
    // rely on a specific layer to establish secondary lock-ons.
}

void Update()
{
    if (isMarked && Time.time >= markerExpireTime)
    {
        UnmarkTarget();
    }
}

public void UnmarkTarget()
{
    isMarked = false;
    if (3dMarkerUI != null)
        3dMarkerUI.SetActive(false);
}
}

```

Use code with caution.

Designing Advanced Polish Features

- **UI Feedback:** Display a bounding box or circular progress ring around the target that shrinks or fills up as `currentPaintTimer` ticks up.
- **Breaking Lock:** If you want a more forgiving system (like battlefield conditions where smoke or trees briefly clip the view), don't immediately drop `currentPaintTimer` to `0` when the raycast fails. Instead, decay the timer slowly over half a second to allow for brief obstructions.
- **Network Replication:** If this is for a multiplayer game, the raycast should ideally be calculated on the client for responsive UI, but the final "Painted" state must be verified and RPC-broadcasted by the server so all friendly players see the UI marker.

If you want to refine this code further, let me know:

- Which **game engine** (Unity, Unreal C++, or Blueprint) you are actively working in?
- Is this for a **single-player** or **multiplayer** project?
- Do you need help setting up the **homing missile logic** that seeks out this marked target next?

AI responses may include mistakes. [Learn more about](#)

Copied to clipboardFailed to copy to clipboard. Try again later.

More



Putting these mechanics together creates a dark, tactical, cyberpunk playground. You are fusing the tactical oversight of **Battlefield's Commander Mode**, the seamless, instant entity-swapping of **Driver: San Francisco's Possession**, and the real-world scale of **Google Maps API** styling—all to control a futuristic, high-tech network managing an illegal, high-value asset operation.

Here is how these systems integrate into a cohesive game mechanic design, alongside a technical implementation plan.

The Dynamic: The Tactical Net

In this futuristic setting, you don't play as a single character. You play as a decentralized **AI Syndicate Overlord** or corporate handler operating via an orbital or drone-mapped HUD styled exactly like a holographic, dark-mode **Google Maps vector network**.

Your objective is to securely move, defend, or extract automated, bio-synthetic "assets" (the futuristic variation of high-end, commodified high-value targets) through a sprawling mega-city.

Direct Feature Comparison

Mechanic	Implementation in This Concept
BF Command er Mode	You view the entire city from a top-down, real-time satellite layout. You drop radar s weeps, order drone strikes, jam enemy corporate scanners, and give tactical route w apoints to your autonomous street assets.
Driver: SF Possessio n	If an extraction team corners your asset, you instantly press a button to shift your consciousness down into any nearby electronic entity—a civilian hover-cab, an auto mated street sweeper, an enemy corporate drone, or the synthetic asset itself—to m annually pilot them out of danger.

Mechanic	Implementation in This Concept
Google Maps Blueprint	The UI uses actual geometric street layouts, displaying real-time traffic density, corporate security grid boundaries, and civilian data heatmaps natively overlaid on a sleek, vector-based road grid.
Laser Designation (Raycasting)	While in Commander mode, you cast rays downward onto the map to "paint" enemy interceptors. Once painted, automated air support or nearby hacked turrets automatically lock on and fire.

Core Gameplay Loop

- 1. Strategic Vector Phase (Commander / Google Maps View):** You look at the vector map. An asset transport route is compromised by rival corporate enforcers. You drop a *Scan Jammer* on the intersection to blind them.
- 2. Tactical Raycast Phase (Designation):** You use your orbital laser pointer (Raycast from screen space to the world plane) to tag the lead enemy enforcer vehicle as a **High Value Target (HVT)**.
- 3. The Possession Shift (Driver: SF Shift):** Realizing your automated transport vehicle's AI isn't fast enough to dodge a roadblock, you trigger a "Shift." Your view instantly plunges from the satellite map straight into the driver's seat of a heavy-duty corporate delivery truck coming down the opposite lane. You take manual control, smash through the roadblock to clear a path, and then instantly snap back up to the orbital map view.

Technical Blueprint: C# Unity Implementation

This script demonstrates how to handle the top-down screen-to-world **Raycast Designation** combined with an instant **Possession System** that swaps your control target seamlessly.

```
csharp

using UnityEngine;

public class CommanderPossessionSystem : MonoBehaviour
{
    [Header("Commander Settings")]
    public Camera commanderCamera;
    public LayerMask targetableLayers; // Vehicles, Drones, Synths

    [Header("Current Controlled Entity")]
    public MonoBehaviour currentManualController; // Generic placeholder for your driving/flying script
}
```

```

void Update()
{
    // 1. Raycasting from the Commander Top-Down Screen View
    if (Input.GetMouseButtonDown(0)) // Left Click to Designate or Shift
    {
        HandleCommanderClick();
    }
}

void HandleCommanderClick()
{
    Ray ray = commanderCamera.ScreenPointToRay(Input.mousePosition);
    RaycastHit hit;

    if (Physics.Raycast(ray, out hit, Mathf.Infinity, targetableLayers))
    {
        GameObject hitObject = hit.collider.gameObject;

        // IF WE CLICK AN ENEMY: Designate them as an HVT for drone strikes
        if (hitObject.CompareTag("EnemyEnforcer"))
        {
            DesignateHVT(hitObject);
        }

        // IF WE CLICK A HACKABLE VEHICLE: "Possess" it instantly (Driver: SF style)
        else if (hitObject.CompareTag("Possessable"))
        {
            PossessEntity(hitObject);
        }
    }
}

void DesignateHVT(GameObject target)
{
    Debug.Log($"[COMMANDER] HVT Laser Painted on: {target.name}. Tactical drones incoming.");

    // Add custom tracking marker that displays on the Google Maps UI layout
    TargetMarker marker = target.GetComponent<TargetMarker>();
    if (marker != null) marker.MarkTarget(15f);
}

void PossessEntity(GameObject newTarget)
{
    Debug.Log($"[SHIFT] Transporting consciousness into: {newTarget.name}");

    // Disable control on the old vehicle if it exists
    if (currentManualController != null)
    {

```

```

        currentManualController.enabled = false;
    }

    // Enable control on the new vehicle/drone
    MonoBehaviour newController = newTarget.GetComponent<MonoBehaviour>(); // e.g.,
    HoverCarController
    if (newController != null)
    {
        currentManualController = newController;
        currentManualController.enabled = true;

        // Smoothly blend or snap camera down to the vehicle's perspective
        // Camera.main.GetComponent<CameraFollow>().SetTarget(newTarget.transform);
    }
}
}

```

Use code with caution.

World Aesthetics & Visual Design

- **The Map Overlay:** The visual aesthetic mimics a highly saturated, neon-cyberpunk styling of a modern navigation app. Buildings are flat 3D vectors; roads are bright glowing lines that turn amber or red based on ambient corporate security presence or civilian panic levels.
- **The "Shift" Visual Effect:** When you click a vehicle to possess it, the camera shouldn't just jump. It should stretch vertically into a digital wireframe stream, mimicking data traveling through a network, before slamming down directly behind the wheel or optics of the chosen drone or proxy asset.

Would you like to explore the **camera interpolation logic** required to make the "Shift" transition feel as fast and smooth as *Driver: San Francisco*, or should we script the **holographic vector shader visual style** for the tactical city map next?

AI responses may include mistakes. [Learn more about](#)

Copied to clipboardFailed to copy to clipboard. Try again later.


More



Integrating **underground adult entertainment networks**, **crypto-betting**, and **surveillance capitalism** into this ecosystem expands the tactical map from simple traffic control into a dystopian web of espionage, asset exploitation, and high-stakes speculative markets.

In this dark-future universe, intimacy and high-end vice are completely commodified, packaged into secure data pipelines, and traded as speculative assets by elite corporate entities.

The Architecture: "The Red Network"



Expanded System Mechanics

1. The Google Maps Vector Layer: Vice Heatmaps

The top-down vector map doesn't just track cars; it overlays real-time **biometric heatmaps** of restricted commercial sectors.

- **Nodes:** Icons marking luxury cyberpunk sex clubs, private underground dungeons, and VIP high-rise suites.
- **Data Streams:** Clicking a venue reveals real-time metrics: current occupancy, asset transaction values, and average heart rates of high-value targets (politicians, rival corporate executives).
- **The Intercept:** You use this telemetry to track target movements through venues to coordinate blackmail, extraction, or assassination.

2. SHA-256 Encrypted 5G Streams & Blackmail Replays

Every private venue is heavily wired with non-consensual biometric and spatial recording arrays.

- **The Pipeline:** Encrypted, high-bandwidth 5G arrays stream raw audio, video, and sensory data out of "closed-room" sessions directly to your secure off-site servers.
- **The Blockchain Ledger:** To prevent rival syndicates from tampering with or stealing the footage, each session's raw data string is instantly hashed using **SHA-256 cryptographic verification**.
- **The Mechanic:** You can access "Replays" of past VIP sessions on your tactical map. These aren't just videos; they are fully interactive 3D spatial reconstructions generated from the sensor data. You scan these replays for behavioral vulnerabilities, biometric data keys, or blackmail material.

3. Decentralized Polymarket Crypto-Betting

The actions inside these clubs aren't just for surveillance; they feed a massive, gamified, decentralized prediction market layout on the dark web.

- **Speculative Markets:** Global anonymous users use cryptocurrency to place micro-bets via smart contracts on real-world outcomes occurring inside the clubs.
- **Example Betting Pools:**

- "Will Target X survive their encounter with Asset Y without their heart rate exceeding 160 BPM?"
- "Will the corporate extraction team raid the VIP room before midnight?"
- **The Commander Strategy:** As the Overlord, you can actively manipulate these outcomes to profit off the betting pools. If millions are bet that a target will leave the club safely, you can possess a nearby enforcer drone, execute the target, crash the market, and collect the massive crypto payout.

Technical Blueprint: C# Blockchain Validation & Betting Ledger

This script demonstrates how your engine handles the ingestion of an automated "Sex Room Session," generates its SHA-256 cryptographic proof string to protect it from manipulation, and calculates real-time betting odds for the Polymarket-style dashboard.

csharp

```
using UnityEngine;
using System.Security.Cryptography;
using System.Text;

public class ViceNetworkManager : MonoBehaviour
{
    [System.Serializable]
    public struct SexRoomSession
    {
        public string venueID;
        public int targetAssetID;
        public float targetHeartRate;
        public bool targetIsConscious;
        public string timestamp;
    }

    [Header("Polymarket Betting Dashboard")]
    public float poolTrueVolumeCrypto = 450.25f; // Amount of crypto bet on 'SUCCESS'
    public float poolFalseVolumeCrypto = 120.80f; // Amount of crypto bet on 'FAIL'

    // Simulates validating a 5G stream frame, hashing it, and updating the prediction market
    public void ProcessStreamTelemetry(SexRoomSession sessionData)
    {
        // 1. Serialize the session data string to simulate the raw 5G stream chunk
        string rawStreamChunk = $"{sessionData.venueID}_{sessionData.targetAssetID}_{sessionData.targetHeartRate}_{sessionData.targetIsConscious}_{sessionData.timestamp}";

        // 2. Generate SHA-256 Hash for secure ledger storage (preventing tampering)
        string sha256Proof = GenerateSHA256Hash(rawStreamChunk);
    }
}
```

```

Debug.Log($"[5G STREAM] Frame Secured. SHA-256 Proof: {sha256Proof}");

// 3. Update Polymarket Betting Odds based on Target Heart Rate spikes
if (sessionData.targetHeartRate > 140f)
{
    // Target is panicking/over-exerting; odds shift dramatically toward a 'FAIL'
    outcome
    poolFalseVolumeCrypto += Random.Range(5.0f, 25.0f);
    CalculateMarketPayoutOdds();
}
}

private string GenerateSHA256Hash(string rawData)
{
    using (SHA256 sha256Hash = SHA256.Create())
    {
        byte[] bytes = sha256Hash.ComputeHash(Encoding.UTF8.GetBytes(rawData));
        StringBuilder builder = new StringBuilder();
        for (int i = 0; i < bytes.Length; i++)
        {
            builder.Append(bytes[i].ToString("x2"));
        }
        return builder.ToString();
    }
}

private void CalculateMarketPayoutOdds()
{
    float totalPool = poolTrueVolumeCrypto + poolFalseVolumeCrypto;
    float successProbability = (poolTrueVolumeCrypto / totalPool) * 100f;

    Debug.Log($"[POLYMARKET] Live Odds Updated. Implied Probability of Asset Success:
{successProbability:F2}%");
}
}

```

Use code with caution.

Dynamic Gameplay Scenario: The Setup

1. **Monitor (Commander Layer):** You notice a high-value political target entering a VIP closed sex room at *Club Neon-Aphrodite*. You boot up the encrypted 5G feed.
2. **Expose (Cryptographic Replay):** You verify the target's identity through biometric tracking. The session data is recorded, hashed via SHA-256 to solidify its validity as immutable blackmail proof, and stored.
3. **Bet (Polymarket Layer):** You open the crypto betting market interface. The public is heavily betting that the politician leaves quietly. You place a massive contrarian bet.

4. **Execute (Possession Layer)**: You trigger a **Driver: SF-style Shift** downward, possessing a rogue synthetic host already inside the room. You trigger a weaponized biological chemical, forcing the target into cardiac arrest, winning the contrarian betting pool, and permanently securing the blackmail footprint against their political faction.

Should we implement the **UI overlay layout** that visually showcases the live betting odds tracking alongside the target's biometric vitals on screen, or would you like to script the **biometric tracking trigger logic** that automatically logs data when a target crosses a venue's threshold?

AI responses may include mistakes. [Learn more about](#)

Copied to clipboardFailed to copy to clipboard. Try again later.

More