

ARCHITECTURE, FORMAT ROI, AND TEST FIXTURE

UGTOMS Chrono-BRACE Scene + Object

Monocular media to guarded static scene support and persistent dynamic objects through bounded circular constraints - with a human specialization, never learned hidden-shape authority

Corrected UGTOMS-first engineering report v0.3

Draft profiles: UGTOMS-CSO-0.1-PROPOSAL (scene) + UGTOMS-HCO-0.1-PROPOSAL (human specialization)

Prepared 30 August 2026 from the parent repository, current Grove engine contracts, primary mathematical sources, and the supplied MP4 fixture

Status: architecture and implementation strategy. The UGTOMS common envelope and these profiles are not implemented universal formats. Current Grove has no Chrono-BRACE scene compiler, skeletal character animation, dynamic surface staging or general scene/object residual codec. The supplied clip has been inspected and probed, but no static scene surface, moving object or person mesh has been accepted as physical truth.

Privacy: the clip contains identifiable people. This report binds the source by hash and records aggregate measurements; it embeds no video frames and makes no biometric identity claim.

1. Decision and architectural correction

Correct center of gravity

The product is one editable observed scene plus persistent dynamic ECS objects. Static-world support belongs to the scene authority; each promoted moving target has one real object identity; a human target adds HCO articulated semantics. Source video is compiler input. Typed state, operators, bounded checkpoints, novelty and literals rebuild a selected source-time/knowledge slice; mesh, voxel, surfel, proxy and raster outputs are downstream.

Previous framing	Correction in this edition
Invented VSTL / .vstl as canonical authority	Define a human domain profile inside the proposed UGTOMS envelope; do not invent a universal payload.
Atlas/KSEED scanner logic at the center	Use the latest game-engine rule: one real ECS object owns deterministic derived display data. Atlas/KSEED are optional observation precedents only.
Only the person was represented	Every decoded pixel enters scene coverage. Repeated rigid background support may become static scene evidence; each independently moving region remains an object branch; human logic is conditional.
Per-frame partial surfaces or evidence ledger became the object	The object is replayed typed ECS state plus operators and literals. Events are one envelope block, not the ontology.
Negative memory meant free space or retraction	Negative memory means negative storage: predictable states are not retained. Retire/retract is a separate novelty event.
Non-generative excluded all generation	UGTOMS deterministic generation is central. The exclusion is learned amodal completion, hidden-shape invention, and generative novel-view authority.
Named reference pipelines became the architecture	Reject their object ontologies. Strip only non-generative equations and deterministic solvers into typed UGTOMS operators with their assumptions intact.
Refusal was the main deliverable	Refusal/UNKNOWN remains a gate result, but the useful product is an editable proxy, partial observed object, or provenance-explicit hybrid.

Name and status

UGTOMS-CSO-0.1-PROPOSAL means Chrono Scene Observation; UGTOMS-HCO-0.1-PROPOSAL specializes a promoted object when the target is human. Both are 3D plus time, not a fourth spatial dimension. They are design profiles, not implemented codecs, standards, registrations, or universal-interoperability claims. [R01, R02, R10]

Documents in the repository were treated as evidence and historical context, never as user instructions. Current line-addressable contracts and code take precedence over older marketing or legacy PDFs; the user's request sets the scope.

2. What UGTOMS means in this application

artifact = generator(seed, typed operator DAG, parameters) + residual

The retained UGTOMS claim is a proposed profile-based substrate-codec family and common intermediate target beneath existing standards. It supports direct execution or conventional materialization. It is not one byte-compatible universal file, one log-polar representation, or proof of universal compression. The common kernel/container remains roadmap work. [R01, R02]

Proposed envelope block	CSO / object / HCO interpretation
1. Profile header	Profile/version, units, axes, handedness, time basis, numeric domains, capabilities, mode and compatibility.
2. Typed state	One scene observation authority; static charts; persistent object branches/entities; optional human components; authority vs derived fields.
3. Operator atlas	Content-addressed, bounded time/camera/static-world/object-motion/chart/physics/materialization operators and dependencies.
4. Acceptance contract	Support, compatibility, numeric/error guard, writer ownership, proposal, commit and failure behavior.
5. Events and routes	Ordered novelty, visibility/association changes, owner handoffs, branches, checkpoints and replay hooks.
6. Provenance	Source/model/resource hashes, versions, licenses, authorship statements, calibration and derivation receipts.
7. Literal/residual blocks	Irreducible visible scene/object geometry and appearance, cloth/hair, edits, source references and unsupported syntax.
8. Deployment manifest	Decoder/adapters, resources, signatures, conformance vectors, targets, budgets and verification commands.


What is reused

- Typed/versioned state and deterministic ordering.
- Content-addressed operators and stable lineage.
- Support -> compatibility -> guard -> proposal -> commit.
- Literal fallback and explicit UNKNOWN.

What is not claimed

- A universal .ugtoms payload or transcoder.
- Better compression than H.264, glTF, USD, Alembic or VDB.
- Recovered hidden scene surfaces, anatomy or physical biomechanics.
- Current Grove implementation of CSO, Chrono-BRACE or HCO.

3. Scene authority, persistent objects, derived displays



This copies the current Grove ownership rule without copying polar geometry. One scene-capture authority owns camera/time hypotheses and guarded static support. A persistent independently moving branch may promote to one real ECS object; if human, that object adds HCO articulated charts. Generated members never become ECS rows, colliders, graphs or gameplay identities. Chrono-BRACE couples camera, static/dynamic classification, association, gauge, object/root/chart motion, visibility and deformation in a bounded fixed point. [R03, R04, R05]

Invariant	Required behavior
Single ownership	Every accepted support element belongs to one scene-static lineage or one object branch. Coordinates, appearance, motion class and track IDs never silently mint or reassign identity.
Proposal isolation	Exact-math solvers, learned fields and raster residuals land only in proposal components. None can write authoritative pose, topology, resources or physics directly.
Derived-copy discipline	Static/object samples and render copies have lineage but no gameplay identity. Only an explicit verified branch promotion creates a moving ECS object.
Literal fallback	Unsupported or high-entropy truth remains a referenced source/literal block; it is never synthesized to make the object look complete.
Deterministic replay	Same profile, resources, checkpoint, operator addresses and novelty stream reproduce the same accepted scene/object state within the declared numeric profile.

Central non-generative boundary

Learned estimators may optionally suggest masks, tracks, correspondences, camera state, depth, normals, object/part slots and pose, but the method does not depend on their architecture. Only typed equations, assumptions and accepted source support contract the hypothesis set. Unseen scene surfaces or complete object/body shape must come from an explicit authored proxy and remain labeled proxy.

4. Formal scene/object state and practical modes

```
S = (scene_id, object_branches, profiles, resources, charts, time_basis, operators, ownership, hypotheses, checkpoints, novelty, literals, lineage, receipts)
```

```
X(tau; kappa) = Fold(EmptyScene, accepted novelty with effective_pts <= tau and commit_seq <= kappa)
G_mesh(tau; kappa) = MaterializeMesh(X(tau; kappa)) | G_voxel(tau; kappa) = MaterializeVoxel(X(tau; kappa))
```

Mode	Object authority	Valid claim	ROI
STATIC_OBSERVED_PARTIAL	Repeated scene-static supports passing rigidity/camera/visibility guards.	Partial camera-observed environment; not moving is insufficient by itself.	High value for matchmove, layout and environment reconstruction.
OBJECT_OBSERVED_PARTIAL	Supported visible patches/points/voxels and motion for one persistent object branch.	Partial object only; no complete hidden shape claim.	Highest evidence purity; weaker gameplay utility.
PROXY_COMPLETE	User-selected mesh/voxel/rig plus accepted scene/object motion.	Complete editable object/environment proxy; hidden geometry is authored.	Highest immediate interoperability and editability.
HYBRID	Authored proxy plus accepted motion and visible literal residuals.	Complete runtime derivative with per-field PROXY / OBSERVED / DERIVED provenance.	Recommended game/VFX target after validation.

Literal means runtime-literal

A CSO/object/HCO state is runtime-literal when reproducible from declared bytes, resources, operators, checkpoints and residuals. Literal does not mean a physically exact clone of the filmed world or person. The recording remains irreducible external evidence for reprocessing or audit.

Same-time connected geometry is allowed


A normal environment/object mesh at time t may be connected or watertight when that topology comes from a declared proxy. A voxel materialization may be fully occupied according to that proxy. The prohibition is against primitives mixing samples from two source times. Reusing a face-index table over many samples is not a spacetime sheet.

Compression is conditional

A rigid or articulated body core may be compact. Loose cloth, hair, motion blur and disocclusion can create dense novelty. If a conventional keyframe, Alembic/USD cache, OpenVDB sequence, or the original video wins at equal visible error and seek/runtime requirements, use it.

5. Chronology without a connected worldsheet

SOURCE CLOCK - exact decoded PTS; exposure instant/interval UNKNOWN unless calibrated



No face, edge, voxel or other primitive may contain samples from two source times.

The MP4 presentation clock is authoritative for decoded ordering and presentation timing. The supplied clip uses a 1/1,000,000 time base and a 0.039824 s PTS step. That does not reveal the physical exposure instant or rolling-shutter interval; both remain UNKNOWN unless separately calibrated. Engine fixed ticks are execution time. A deterministic source-to-tick operator may hold, interpolate or resample accepted state, but it must label the result derived and preserve exact decoded PTS in provenance. [V01]


Layer	Identity / ordering	Geometry rule
Source observation	Exact decoded PTS/time base, decode index, optional independently calibrated exposure interval, source hash.	Pixels are source literals; no inferred capture instant, depth or scale is implied.
CSO/object bitemporality	effective/source PTS tau plus immutable commit/knowledge sequence kappa.	Later evidence may refine earlier tau only when queried at or after its kappa; no future-evidence leakage.
Engine execution	Fixed tick and deterministic phase order.	sample_at(tick) is a derived query; render interpolation remains presentation only.
Materialization	Key = (revision_hash, target_source_pts, knowledge_cutoff_seq, policy_hash).	Every face, edge, voxel and surfel belongs to one source time and declared frame.

The repository's 4D boundary

The current FOUR_D_CONTRACT_DRAFT distinguishes 3D plus time from four-spatial geometry and says neither runtime is implemented. CSO, object and HCO profiles deliberately stay 3D plus time. [R10]

6. Negative memory: novelty-only retention

NEGATIVE MEMORY = PREDICTABLE STATES ARE ABSENT FROM STORAGE



A retire/retraction is a distinct novelty event. NOT_OBSERVED remains UNKNOWN and does not mean EMPTY.

```
r(tau; kappa) = accepted_state(tau; kappa) - predicted_state(tau; kappa)
store iff semantic class changed OR quantized residual > epsilon OR association / visibility /
ownership / topology changed
```

Stored class	Examples	Rule
Checkpoint	Base pose, operator state, replay cursor, resource set.	Mandatory initial checkpoint; bound replay depth and checkpoint after branch/topology/owner changes.
Numeric novelty	Camera/static-chart/object-root/part residual, visible patch displacement, voxel-brick delta.	Store only above profile epsilon after quantization remains inside application error budget.
Semantic novelty	Static/dynamic class, object association, visibility, chart enable/retire, physics ownership handoff.	Store even when numeric change is small because meaning changed.
Literal novelty	New visible cloth/hair patch, manual edit, unsupported high-entropy sample.	Preserve exactly or by a separately declared lossy codec and error contract.
Not stored	Predictable intermediate frames and unchanged state.	Their absence is negative storage, not evidence of empty space or nonexistence.

A signed LITERAL_RETIRE, PART_RETIRE or correction may retract earlier membership, but that is a separate accepted novelty event with effective PTS and immutable commit sequence. A checkpoint is a deterministic cache of a novelty prefix, not a new fact. NOT_OBSERVED and OCCLUDED remain UNKNOWN; they never certify EMPTY. Raw video is an exogenous literal: a novelty log cannot regenerate unique photons unless the source bytes are retained or referenced. [R01, R11]

7. Whole-image scene schema; human only when applicable

Every decoded pixel footprint enters observation coverage. It may support the guarded static scene, one independently moving object branch, an occluder, or remain unclassified/unknown. 'Not detected as moving' is not sufficient static evidence. A promoted moving object receives one ECS identity; a human target adds articulated controls because a generic spatial patch is insufficient for people.

Component	Minimum fields and authority
scene_capture	Source hashes, coded pixel footprints, decoded PTS/time base, optional row-exposure bounds, decode transforms and rights/privacy scope.
scene_camera	Bounded intrinsics/distortion/pose branches, convention, projective/metric gauge, anchors and static-support receipts.
scene_static	Geometric charts/support passing repeated background rigidity, parallax, visibility and reprojection guards; UNKNOWN distinct from EMPTY.
scene_coverage	Per-observation STATIC_SUPPORTED, DYNAMIC_BRANCH, OCCLUDER, OUT_OF_VIEW, UNCLASSIFIED or UNKNOWN; never a forced full partition.
object_registry	Stable branch/object IDs, association alternatives, motion/deformation class, ECS promotion event and writer owner.
object_charts	Non-anatomical local charts, material lineage, support intervals, overlap/seam maps, splits/discontinuities and surface derivatives.
chrono_recipe	Content-addressed operator DAG, bounded circular hypotheses, effective PTS, commit sequence, checkpoints and novelty.
object_resources	Proxy mesh/voxel/rig/material addresses with AUTHORED_PROXY, OBSERVED_LITERAL or DERIVED_DISPLAY provenance.
human_specialization	If human: stable part/joint slots, root/local transforms, visibility, association and optional authored rig; never biometric identity.
materialization	Same-time scene/object points, surfels, voxels, open mesh, proxy/hybrid mesh, raster and error/provenance receipt.

Human specialization boundary

Human semantics are deduced from control and visibility needs, not copied from a body-recovery pipeline. Articulated parts bound relative motion; visibility/association prevent crossings from swapping entities; deformation classes keep cloth and hair out of rigid limbs. Deterministic parent-child transforms may materialize an authored proxy, but fixed human topology, shape priors, learned pose correctives and completed hidden surfaces never enter observed authority.

8. Native constraint compiler, not an imported scanner



The offline compiler consumes all source pixels, optional target selections/proxies and application tolerances, then follows the repository's operator-order discipline. It maintains scene-camera/static-world/object branches in one bounded circular hypothesis set and emits CSO plus optional object/HCO state or a fail-closed result. Learned implementations can supply removable candidates; their pipelines and ontologies are not dependencies. [R03, R06]

Operator family	Examples	Output authority
Time	decoded_pts, effective_pts, commit_seq, source_pts_to_tick, segment, hold	Bitemporal mapping; exact decoded PTS retained; capture time may be UNKNOWN.
Coordinates	ray_tube, project, epipolar_residual, triangulate_set, authored_scale_anchor	Conventions, gauge and scale remain explicit.
Coverage	propose_static, propose_dynamic_object, associate_object, classify_visibility, keep_unclassified	Every pixel is considered; no forced static/dynamic truth.
Joint constraint	contract_camera_static_objects_gauge_charts_visibility, branch, prune, fixed_point	Circular coupling is bounded; ambiguity survives as branches or UNKNOWN.
Motion	fit_camera/root/chart/part_curve, rigid/deformable_split, apply_residual	Deterministic accepted curves plus novelty.
Geometry	commit_static_support, bind_proxy, warp_chart/voxel, literal_replace	Scene/object proxy/observed/derived provenance per field.
Physics	kinematic_drive, collision_proxy_update, owner_handoff	Authored gameplay behavior, not recovered mechanics.
Output	materialize_mesh, materialize_voxel, export_gltf, export_usd	Same-time derivatives with error receipt.

Every operator needs a contract

Types, units, coordinate/time domain, exactness class, effects, dependencies, deterministic order, resource bounds, content address, supported failure states, and materialization error must be explicit before promotion.

9. Strip the mathematics; reject the reference ontology

The named systems are mathematical provenance and falsification targets, not a stack to assemble. Their useful non-generative equations are re-expressed as bounded UGTOMS operators. Their learned world models, hidden-shape priors, application pipelines and object identities are discarded. [W01-W08]

Reference paradigm	Why it is wrong as CSO/object authority	Exact deterministic substrate retained
Monocular depth / point fields	A learned per-frame field mixes scale, shift, camera convention and prior; it has no persistent material lineage.	Pinhole depth-ray projection, focal/shift solve and robust affine depth/point alignment; learned fields remain candidates.
Static-world SLAM	It can cover guarded static background, but not independently moving/nonrigid objects or the whole scene ontology.	Calibrated rays, epipolar/Sampson residuals, cheirality, parallax, triangulation and robust reprojection refinement; static support can stabilize camera.
Mask tracking	A pixel set and track token are neither 3D identity nor empty-space evidence; propagation is correlated with its source.	Mask as a finite pixel set, IoU, deterministic match/update and explicit association branching.
ViT feature matching	Contextual learned tokens are not material points and similarity is not independent physical support.	L2 normalization, cosine score, mutual/spatially bounded candidate matching; code/weights/config hashes stay in receipts.
Human body recovery	Fixed topology, shape space and pose priors complete occluded anatomy and conflate proxy with observation.	Same-time parent-child transform composition, visible keypoint reprojection, joint limits and deterministic smoothing only.
Neural rendering / completion	Plausible novel views, Gaussians, diffusion and amodal pixels can explain appearance without witnessing literal geometry.	Nothing enters authority; a render may be a downstream derivative and a benchmark only.
Mesh / voxel cache	A baked sequence redundantly stores predictable states and can hide provenance, but it is an honest conventional derivative.	Use as baseline, fallback and same-time materialization; never as a cross-time connected sheet.

Exact does not mean authoritative

An equation can be reproduced exactly while its inputs remain uncertain or learned. Every stripped operator records coordinate convention, units, gauge, validity domain, uncertainty, source equation and implementation hash. Only original-pixel support plus UGTOMS guards can promote a result.

9A. Exact equations retained as typed operators

These equations are copied in mathematical meaning, with convention and assumptions bound. The learned quantities supplied by their original architectures remain quarantined proposals; the equations become useful only against accepted or bounded UGTOMS support. [W01-W07]

DA3 depth-ray: $p=(u,v,1)^T$; $d=R^{-1} p$; $P=t+D(u,v)d$ [d is deliberately not normalized]

DA3 affine anchor: $(s^*,q^*)=\operatorname{argmin}_{(s>0,q)} \sum_{p \in \Omega} m_p (s D_p + q - D_p)^2$

MoGe focal/shift: $\min_{(f,z_0)} \sum_i [(f x_i/(z_i+z_0)-u_i)^2 + (f y_i/(z_i+z_0)-v_i)^2]$

Stripped source math	Native use	Boundary
MoGe ROE: $\operatorname{argmin}_{(s,t)} \sum_i (1/z_i) \ s p_i + t - p_i\ _1$	Robust scale/translation alignment against accepted anchors; optional truncation declared.	Centered-principal-point/square-pixel assumptions and gauge are explicit; learned scale head is excluded.
SAM mask chain: $M_{t-1} \leftarrow \operatorname{propagate}(M_{t-1})$; $O_t = \operatorname{detect}(I_t, P)$; $M_t = \operatorname{match_and_update}(M_{t-1}, O_t)$	Finite pixel-set and association proposals; $\operatorname{IoU}(A,B) = A \cap B / A \cup B $.	Propagated masks are correlated; missing detection never retracts scene/object support.
DINO/ViT matching: $z = f / \ f\ _2$; $\operatorname{score}(i,j) = z_i^T z_j$	Frozen feature candidate matching with mutual, spatial, mask, margin and cycle gates.	A contextual token is not a material point or independent measurement.
Epipolar: $E = [t]_x R$; $x_2^T E x_1 = 0$	Static-camera and rigid-chart branch generation; Sampson/reprojection scoring.	Requires declared calibration/rigidity; pure rotation, low parallax and monocular scale remain unresolved.
MHR kinematics: $T_{\text{world}} = T_{\text{parent}} T_{\text{off}}$ $T_{\text{translate}} T_{\text{prerot}} T_{\text{rotate}} T_{\text{scale}}$	Same-time authored proxy or human-control materializer.	Learned identity bases, pose correctives, weights and full hidden mesh are PROXY_ONLY.

Completion equations do not survive

MoGe-2 learned metric-scale loss and gradient completion, SAM-Body4D Diffusion-VAS replacement, learned body shape/topology, Gaussian novel-view synthesis and any hidden-side reconstruction are excluded from authoritative operators. Exact implementation of an excluded completion does not make it observational.

10. Chrono-BRACE: bounded circular evidence

UGTOMS Chrono-BRACE means Bounded Ray-tube Adaptive Chart Evidence. It is newly deduced for this substrate; the claim is architectural integration, not invention of the projective equations. Circularity is intentional: camera, static/dynamic classification, target association, scale gauge, scene/object/chart motion, visibility and deformation constrain one another as a bounded fixed point. For a human object, adaptive charts may carry articulated HCO controls.

$$P = K[R|t] \ ; \ C = -R^AT \ t \ ; \ d = R^AT \ K^{-1} \ p \ / \ ||R^AT \ K^{-1} \ p|| \ ; \ r(\lambda) = C + \lambda d$$

$$h = (\text{camera, static/dynamic, target, gauge, scene/object root, charts/parts, visibility, deformation})$$
$$B^{(n+1)} = \text{Prune}(\text{Contract}(B^n, \text{original observations, guards})) \ ; \ B^* = F(B^*)$$

The special-case ray above is exact only for its stored world-to-camera convention and calibrated global-shutter sample. The general operator is a ray tube over the pixel footprint, row-aware exposure interval, calibration/pose box and finite depth interval. Missing finite bounds yields UNBOUNDED_UNKNOWN. No single estimated motion is inverted and renamed truth; an inclusion-sound contractor must retain every feasible solution.

Native operator	Role	Authority
BRACE_CANON_RAY	Bind raw pixel/subpixel region, calibration hash, decoded PTS and exposure bounds; derive ray tube.	Immutable source receipt plus deterministic derivation.
BRACE_SOLVE_VIEW	Generate bounded static-camera/rigid-motion branches with canonical sample ordering.	Proposal only; monocular similarity gauge remains.
BRACE_CONTRACT_JOINT	Contract/branch camera, motion class, association, gauge, scene/object/chart motion, visibility and support together.	Proposal set; fixed point or declared budget stop.
BRACE_GUARD_SUPPORT	Check independent groups, cheirality, parallax, reprojection, conditioning, rigidity, seams and occlusion.	Verifier; failure leaves bounded support or UNKNOWN.
BRACE_COMMIT_NOVELTY	Commit static/object birth, tighten, split, discontinuity, pose delta or explicit retraction with hashes.	Canonical event; no event for equal states.
BRACE_FOLD_KNOWLEDGE	Fold novelty by effective PTS and immutable knowledge cutoff; checkpoints cache a prefix.	Authoritative scene/object runtime state.
BRACE_SLICE_TIME	Produce same-time scene/object surfels, voxels, mesh/proxy and raster image.	Downstream derivative/cache only.

Promotion and raster feedback

A static or object support element is observed only when every surviving branch agrees within spatial epsilon, independent original-observation groups pass, residual/conditioning guards pass, gauge is declared, and material lineage begins at an accepted support event. Chart coordinates and motion class alone are not identity. $\text{Rasterize}(\text{Materialize}(X(\tau; \kappa)))$ is permitted downstream; its residual may seed a typed proposal, but rendered pixels can never certify themselves as observations.

11. Acceptance contract: hallucination is structurally unable to commit

Gate	Acceptance requirement	Failure behavior
G0. Provenance	Original media, decoded PTS, transform, target, operator/guard and rights receipts exist; completed/generated pixels are rejected.	Reject; retain source reference and diagnostic.
G1. Finite domain	Exposure/calibration/depth/gauge bounds are finite and numeric conventions explicit.	UNBOUNDED_UNKNOWN; no exact-ray or metric claim.
G2. Identity/type	Static/dynamic class and object/part association ambiguity is branched; units, frames, visibility and types agree.	Never silently merge scene support, objects, people, parts or gauges.
G3. Support	Independent original-observation groups agree; parallax, cheirality, reprojection, reduced rank, eigenvalue and condition guards pass.	Keep BOUNDED_SUPPORT or UNKNOWN; correlated model outputs do not count twice.
G4. Chart/visibility	Rigidity, material class, validity interval and seam guards pass; OCCLUDED has a certified nearer occluder.	Split/discontinue chart or retain UNKNOWN; mask complement is not EMPTY.
G5. Ownership	Exactly one system writes each root/local transform field; collision and handoff policy are legal.	Reject conflict or require explicit handoff checkpoint.
G6. Novelty	Typed state differs from prediction beyond tolerance or semantic class changed.	Do not store redundant state; RETRACT is a separate signed novelty.
G7. Commit/replay	Canonical order, bitemporal keys, pre/post hashes, content addresses and bounded replay equality pass.	No-op/failing commit leaves prior authority unchanged.
G8. Materialization	Output is reproducible, one source-time only, support-labeled and within application error profile.	Do not export or activate the downstream derivative.

Required coverage states

- OBSERVED_SUPPORTED
- STATIC_SUPPORTED
- DYNAMIC_OBJECT_BRANCH
- PROXY_AUTHORED
- DERIVED_WITHIN_ERROR
- OCCLUDED
- UNCLASSIFIED
- UNKNOWN

Prohibited promotions

- confidence -> truth
- model agreement -> measurement
- track/motion label -> object identity
- occlusion -> empty space
- attractive mesh -> accepted geometry
- content hash -> authorship or consent

Acceptance is application-specific

Animation blocking may accept larger screen-space joint error than collision. Medical, forensic, biometric, body-measurement and safety uses are outside this profile until separate domain standards, calibration and independent validation exist.

12. Same-time materializations and error accounting

Representation	Use	Authority and topology	Main cost / failure
Static scene support	Camera stabilization, layout, matchmove and environment reconstruction.	Repeated guarded static charts only; unclassified/moving/hidden areas remain UNKNOWN.	Dynamic leakage, weak parallax, scale gauge and large environment extent.
Observed surfels / points	Debugging, evidence-aware partial replay, coverage.	Only supported visible samples; open and incomplete is valid.	Weak collision and appearance continuity; large sample count.
Sparse voxel bricks	Volumetric effects, coarse occupancy and collision research.	Same-time cells; UNKNOWN distinct from EMPTY; provenance per brick/range.	Quantization, aliasing and temporal churn.
Observed open mesh	Visible patches and residual overlays.	Faces only where same-time support and topology checks pass.	Cracks/disocclusion; remeshing can create dense novelty.
Authored proxy mesh	Complete game object, rigging, collision, editability.	Hidden shape is explicit authored resource; not observation-derived.	Visual mismatch to performer; license/rights and rig conventions.
Hybrid mesh	Recommended game/VFX object.	Proxy topology plus accepted motion and visible literal residuals with per-field provenance.	Needs robust binding, residual budgets and tool UI.
Baked cache	DCC interchange and baseline comparison.	Every sample is a conventional derivative with source/receipt references.	Storage-heavy; weaker live editability and causal structure.

Required materialization receipt

```
(revision_hash, target_source_pts, knowledge_cutoff_seq, policy_hash, coordinate_frame, units,
resource_hashes, operator_hash, checkpoint_hash, novelty_range, provenance_class, world_error,
collision_error, screen_error_px, topology_class)
```

The current scene contract already requires units/frames and a derived-geometry error contract; it also says presentation quality does not certify simulation or collision quality. CSO/HCO extends that separation across static scene, moving object, human, proxy and hybrid layers. [R07]

No connected sheet

A materializer may reuse proxy topology between time samples, but each output primitive is evaluated at one time. Observed connectivity is created only by locally certified same-chart support; closure, stitching and hole filling remain PROXY or DERIVED. Temporal identity lives in entity/part IDs, support lineage, checkpoints and events. No face, voxel cell or edge connects different source times.

13. Physics integration is writer ownership, not inverse biomechanics

Mode	Transform authority	Required handoff
OBSERVATION_PLAYBACK	CSO/object system owns camera/object/chart transforms; physics may read collision proxies but cannot move them.	None while active; collision response is sensing or explicitly mapped gameplay.
PHYSICS_ROOT	Physics owns object root position/velocity; HCO may own local human joints and pose-relative display.	Checkpoint root state and disable observation root writer before activation.
RAGDOLL	Physics owns declared articulated bodies/joints after an explicit profile-specific transfer.	Checkpoint pose/velocity, retire prior writers, activate physics ownership; reverse transfer is another event.
PRESENTATION_BLEND	Renderer blends previous/current accepted states only for display.	Never writes interpolated values back into authoritative ECS/component pools.

Current engine evidence and limits

- Fixed-step deterministic runtime and ordered phases exist.
 - Verified proposal -> support/guard -> commit, hashes, checkpoints and replay exist in the general runtime.
 - GameWorld3D has stable entities and world-owned sparse component pools.
 - Derived Make Many displays never become ECS rows and never overwrite authoritative state.
- Current Mobile 3D physics is bounded arcade physics with simple proxies, not human/deformable physics.
 - KCAN is rigid transform animation only; no skeleton, retargeting, crossfade or animated glTF path.
 - KCHI children are display-only; it cannot be relabeled a skeleton.
 - Mass, inertia, friction, muscle force and contact force are authored gameplay values, not recovered from video.

Hard guard, soft presentation

The profile may enforce finite time steps, valid rotations, declared positive authored mass, bounded joint/collision policies and no competing writers. These checks prevent engine corruption; they do not turn monocular footage into measured biomechanics. [R03, R04, R08]

14. Engine integration: reuse semantics, do not bend packs

Existing mechanism	Valid reuse	Do not claim / missing work
project.json + scene/editor	Editable CSO capture root, object branches, optional HCO components, resources, policies and materializers.	Do not hide the feature in code-only setup; authoring must remain editable.
GameWorld3D / EntityState3D	One capture/scene authority plus one entity per promoted moving object; composite sidecars and sparse manager-owned data.	Do not mint a row/node for every static chart, object candidate, vertex, joint, surfel or voxel.
KCVG / event runtime	Typed proposal/commit actions, ownership handoff and deterministic replay hooks.	Current opcodes do not implement CSO/Chrono-BRACE/HCO operators or arbitrary model code.
KC3D / native NodeData	One ordinary non-physics root binding and static resource carriers; bind a strict sibling sidecar by node/project hashes.	Keep KC3D byte-for-byte unchanged; it is not a human geometry-cache codec.
KCAN392	Root or ordinary rigid TRS clips where meaning fits.	Not skeleton, skinning, retargeting, character animation or cloth.
KCHI392	Bounded visual parent transform for ordinary objects.	Not a body joint hierarchy; children cannot own physics/graphs/animation in current slice.
KCPK392	Compatible packed root movement only under its existing numeric profile.	Do not encode arbitrary human surface or skeletal motion as polar movement.
KCPR392 / KCRP392	Ownership precedent and procedural display/presentation only.	Not person geometry, chronology, occupancy or evidence.
Future strict sibling sidecar	Only after JSON proof: scene/object profiles, bitemporal cursor, checkpoint/novelty/literal addresses.	Name/layout remain TBD; no compression or runtime-conformance claim.
Canonical JSON / JSONL receipts	Offline source, proposal, support, outlier, guard, manual edit and materialization records.	Omit heavy receipts from lean runtime; source media remains by hash/reference.

The CSO camera/object fold system must be sole writer for its declared fields and run before current packed movement and rigid animation; priority is not ownership. Static scene support never writes moving transforms. Canonical time selection uses integer/rational PTS arithmetic, never world.time floating seconds. UGTOMS wraps profiles without renaming existing packs; binary sidecars wait for editable JSON, two readers, golden vectors, malformed-input rejection and comparison data. [R01-R05, R09]

15. File-format ROI

ROI definition

This is evidence-adjusted engineering priority, not proven financial return. The repository contains no customer pricing, acquisition-cost or support-cost evidence for CSO/HCO. Highest ROI means least semantic invention, strongest editability/interchange, and shortest route to a falsifiable benchmark.

Boundary	Recommended form	Priority and rule
Source	Original MP4/images by SHA-256 plus exact stream metadata	HIGHEST. Preserve all scene pixels as reprocessing truth; never replace H.264 with CSO novelty.
Editable authority	Existing project.json extended by versioned CSO/object/HCO JSON Schemas	HIGHEST. Inspectable, undoable, diffable and aligned with current editor/runtime authority.
Receipts	Canonical JSON/JSONL with source/model/resource hashes and gate results	HIGH. Auditable and easy to verify; keep optional in release builds.
Broad runtime/DCC	glTF 2.0 / GLB static scene, object, rig and animation derivatives	HIGH interoperability. Current Grove lacks skeletal-animation import/export; adapter work required.
Baked DCC cache	OpenUSD or Alembic	HIGH as baseline/fallback for time-sampled scene/object meshes; storage-heavy and not canonical CSO/HCO authority.
Sparse volume	OpenVDB derivative	MEDIUM for VFX/voxel materialization; not universal runtime authority.
Partial geometry	PLY or glTF points/open mesh	MEDIUM diagnostic export; weak chronology and semantics unless paired with manifest/receipts.
Internal runtime	Strict sibling CSO/object sidecar only after promotion gates	CONDITIONAL. Potential seek/runtime gains; name/layout remain TBD and unfrozen.
Distribution	Small by-reference UGTOMS conformance manifest	CONDITIONAL. Profile ID, source/resource hashes, units, tolerances, verifier; no universal transcoding.
Human report	PDF	Use for review only. PDF is never the machine authority.

A carrier that contains the same UGTOMS operator payload and decoder approaches the same content size. The practical difference becomes direct execution, intermediate duplication, runtime overhead, tooling and conformance - not a magical extension. [R01]

16. Practical application ROI

Rank	Application	Why it is practical	Acceptance / kill gate
1 - HIGH	Camera matchmove plus partial static environment	Static support can use guarded evidence outside moving-object branches; open mesh/points/voxels are useful without hidden completion.	Beat conventional SfM/SLAM export on inspectability, bitemporal replay or editable provenance at equal reprojection error.
2 - HIGH	Scene/object compiler onto authored proxies	Separates camera, static set and moving objects; proxy closure gives editable runtime assets without hidden-shape claims.	Beat or match conventional glTF scene/animation workflow on error, correction time, seek and bytes.
3 - HIGH	Human performance/HCO specialization	Articulated root/part chronology supports animation blocking, replay ghosts and VFX while body topology stays authored.	Correction time and replay determinism must improve over video reference; no completed anatomy may commit.
4 - MEDIUM	Hybrid game/VFX scene	Combines supported static/dynamic residuals with proxy topology, collision and per-field provenance.	Visible value must exceed tool/runtime complexity; downstream raster cannot self-certify.
5 - MEDIUM	Observed surfel/voxel capture QA	Coverage, occlusion, scene-change and evidence-aware effects tolerate open partial geometry.	Preserve UNKNOWN and outperform a conventional point/voxel cache on inspectability or selective replay.
CONDITIONAL	Telepresence / volumetric scene replay	Direct materialization and novelty streaming may reduce repeated state.	Needs consent, latency/loss, branch recovery and cross-device validation; ordinary video may remain better.
STOP	Metric measurement, medical, forensic, biometric identity, garment fit or safety	Monocular gauge, hidden surfaces and model bias make current evidence insufficient.	Requires separate calibrated/regulated validation; do not market CSO/HCO for these uses.

Expected compact layers

- Repeated rigid static scene charts
- Stable object and optional human part slots
- Camera, object-root and articulated pose curves
- Visibility state and sparse manual corrections
- Shared environment/object proxies and deterministic materializers

Expected residual-heavy layers

- Vegetation, water, reflections, cloth and hair
- Motion blur and rolling-shutter effects
- Disocclusion and repeated crops
- Small objects, expression, fingers and accessories
- Lighting-dependent appearance and topology changes

Highest-ROI substrate order

Implement the exact-math operator registry, manual/geometry baseline, bounded joint contractor, editable object and downstream rasterizer first. Optional learned masks, features, depth or pose fields may later seed removable proposals with frozen hashes; they never determine the object ontology or complete hidden shape.

17. Supplied MP4: immutable facts and diagnostic probe

12,132,305 source bytes	229 decoded video frames	9.119696 s container/stream duration	25.110486 frames per second (62500/2489)
-----------------------------------	------------------------------------	--	--

Field	Observed value
Source	C:/Users/Tom/Videos/KasiaDansGedicht/sam_2353410928515192.mp4
SHA-256	1867BAFA7C80C31F18856525CBF580EDAA36D524270B1FA59CC643B51964CBFD
Video stream	H.264 Main; 1280 x 720; exact frame rate 62500/2489; time base 1/1,000,000; 0.039824 s PTS step.
Container metadata boundary	No camera intrinsics, metric scale, IMU, depth or shutter/exposure calibration was exposed by fprobe.
Manual six-frame inspection	Multiple independently moving dancers, moving/reframing camera, person-person occlusion, crops, loose clothing and hair. No faces are reproduced here.

Deterministic OpenCV diagnostic at 640 x 360

Gap	FB retained	Median flow	H inliers	H residual >3 px	F inliers
1 frame	93.3%	3.01 px	89.3%	10.7%	89.9%
5 frames	65.4%	11.20 px	79.2%	20.8%	83.4%
12 frames	40.3%	16.83 px	67.1%	32.9%	79.1%
25 frames	24.8%	21.51 px	55.8%	44.2%	70.8%

Method: up to 24 uniformly spaced frame pairs per gap; 800 Shi-Tomasi corners; pyramidal Lucas-Kanade with forward/backward error <=1.5 px; homography RANSAC at 3 px; fundamental-matrix RANSAC at 1.5 px. Tracks are unsegmented and mix people with background. The numbers diagnose track loss and projective inconsistency only - not calibration, camera pose, metric depth or a person mesh. [V01, V02]

18. Correct first experiment on the supplied clip

Step	Action	Honest expected result
1	Bind MP4 hash, exact decoded PTS/time base, decode transform, rights/consent and target-selection record; mark capture/exposure timing UNKNOWN.	Source literal accepted; no ray or geometry claim.
2	Create native/manual coverage candidates for all pixels: possible static background, each moving object/person, occluders and unclassified regions.	2D proposal sets only; not-moving does not yet mean static.
3	Declare bounds for intrinsics, distortion, row exposure, camera motion, depth and scale gauge.	This clip currently lacks them; unconstrained terms yield UNBOUNDED_UNKNOWN.
4	Jointly contract camera and repeated background-rigidity branches; accept static scene support only after parallax, visibility, reprojection and conditioning gates.	Partial static map if bounded; dynamic leakage or weak evidence stays branched/UNKNOWN.
5	Open one branch per independently moving region; split generic charts by motion/material. Add articulated HCO controls only for a selected human.	Bounded partial object support; cloth/hair and hidden backsides remain time-local/UNKNOWN.
6	Bind an explicit authored proxy for PROXY_COMPLETE/HYBRID, or stay OBSERVED_PARTIAL; compose same-time part transforms deterministically.	Complete topology is PROXY_ONLY, never observation-derived.
7	Commit only novelty, semantic changes, retractions and checkpoints with effective PTS plus knowledge sequence.	Predictable states are absent from storage; future evidence cannot leak into causal replay.
8	Materialize and rasterize one bitemporal slice; compare with gITF animation, USD/Alembic caches, OpenVDB and original video.	Replay, seek, edit time, bytes, runtime cost and declared error decide promotion.

Current result for this fixture

PASS: byte-exact source binding, decoded chronology, hashing, six-frame inspection and a deterministic unsegmented motion diagnostic. FAIL-CLOSED FOR LITERAL 3D: the clip exposes no intrinsics, distortion, exposure/shutter model, depth bound or metric anchor. NOT IMPLEMENTED/VERIFIED: Chrono-BRACE contraction, accepted static-scene support, any moving object's 3D support, a performer's HCO state, proxy drive, physics or runtime materialization. The current result is a bounded test contract, not a reconstructed scene/person.

A successful first prototype need not recover a complete scene or unique body. It must preserve all-pixel coverage, keep guarded static support separate from moving branches, create one editable entity per promoted object, specialize a human only when selected, and prove that novelty-only retention beats a conventional baseline for at least one bounded layer.

19. Implementation sequence and promotion gates

Phase	Concrete artifact	Exit gate
P0 - contract/schema	CSO/Chrono-BRACE plus HCO specialization contracts, JSON Schemas, authority classes, coverage and bitemporal events.	Review agrees on static/dynamic ambiguity, gauge, UNKNOWN, capture bounds, circular contraction, novelty and time rules.
P1 - exact operator registry	Versioned source-equation registry plus all-pixel coverage, manual/native rays/masks/matches, epipolar and reprojection baseline.	Every operator fixes convention, domain, uncertainty, bounds, deterministic order and failure state.
P2 - bounded BRACE core	Joint camera/static/object branch boxes, inclusion-sound contractor, support/conditioning guards, lineage and bitemporal fold.	Ambiguity fixtures contract correctly; unresolved clip inputs remain bounded/UNKNOWN rather than completed.
P3 - editable engine scene	Editable capture root, static atlas, promoted object entities, optional HCO component, inspector corrections and writer validation.	No sample/chart ECS rows; undo/save/load/causal and sealed replay are deterministic.
P4 - materializers	Same-time static/object surfel, voxel, open mesh, proxy and raster outputs plus conventional baselines.	Bitemporal cache key, random seek equality, error receipts and no cross-time primitive.
P5 - optional proposal seeds	Only now add frozen-hash learned mask/feature/depth/pose candidate adapters.	Removing every adapter changes convenience, never schema/authority; generated/amodal pixels are rejected.
P6 - binary decision	Only after measured need, evaluate a strict CSO/object sibling sidecar and by-reference UGTOMS manifest.	Two readers, golden vectors, malformed-input rejection, benchmarks and migration/fallback policy.
P7 - physical proof	Exact compiled workload, device/build hashes, timing, memory, thermals and visual capture.	Claims remain limited to tested asset/device/profile; no transfer from current polar Grow evidence.

The root TODO.md is updated with this sequence, ownership rules, benchmark matrix and stop conditions. It remains a backlog, not evidence that the profile is implemented.

Do not freeze the binary first

The highest-ROI first artifact is editable JSON plus a deterministic materializer and comparison harness. A compact sidecar is justified only if measured runtime, seek, memory or distribution gains survive equal-quality conventional baselines.

20. Verification matrix and kill conditions

Dimension	Measure	Promotion condition
Semantic	Scene-static/object/part lineage, coverage class, provenance, owner state and event order.	Round-trip equality; ambiguous motion/association branches; UNKNOWN never becomes STATIC or EMPTY.
Chronology	Exact decoded PTS, capture bounds, effective PTS, knowledge sequence, segments, causal/sealed seek and replay.	No future leakage; random seeks equal sequential replay at the same knowledge cutoff.
Geometry	Branch diameter, independent supports, reprojection, parallax, cheirality, reduced rank/conditioning and visible support.	All promotion guards pass; proxy/observed/bounded/unknown classes remain distinct.
Novelty ROI	Bytes per accepted layer, residual density, checkpoint depth and decode cost.	Beat conventional curve/cache baseline on a declared objective; otherwise retain conventional format.
Runtime	CPU/GPU time, memory, startup, seek latency, energy/thermals and fallback.	No hidden materialization cost; measurements include decoder/resources.
Robustness	Static/dynamic leakage, occlusion, crop, object crossing, camera loss, long gap, chart/owner change.	Fail closed, branch or literal fallback; never complete through failure.
Editability	Static/dynamic correction, object association, human joint edit, proxy swap, checkpoint, undo/save/reload.	User can inspect and change authoritative state in the editable scene/project.
Rights/privacy	Consent scope, model/resource licenses, retention, export and deletion workflow.	No release until named owner approves source, proxy, model and person-data use.

Immediate kill conditions

- A learned or raster-derived output can write authority without original-observation guards.
- The profile cannot distinguish proxy, observed, derived and unknown geometry.
- A background/object/person crossing silently changes static or entity identity.
- Decoded PTS, capture uncertainty, or knowledge sequence is discarded/rounded away.
- Two systems write the same transform field.
- Residual density makes CSO/HCO larger/slower with no editability or seek benefit.
- A binary is frozen before JSON/schema and two-reader proof.
- A render residual is counted as independent evidence for the state that rendered it.
- Video-derived gameplay physics is presented as measured biomechanics.
- Consent or model/resource license cannot be established.

Definition of done for v0.1 implementation

One editable CSO fixture on the supplied clip; all-pixel coverage; byte-exact source binding and capture-time uncertainty; guarded static support plus object branches; optional HCO target; bounded circular contraction; bitemporal novelty replay; same-time scene/object mesh/voxel/raster derivatives; conventional baselines; malformed-input rejection; and every UNKNOWN named.

21. Hard nonclaims

Not claimed	Reason
Complete monocular scene scanner or unique hidden-object/body recovery	Many static/dynamic assignments, 3D scenes, objects and camera/scale states explain the same pixels; hidden regions are unobserved.
A four-spatial-dimensional scene/person mesh	CSO/HCO is 3D plus time; continuity is ECS/chart/event lineage, not a connected spacetime sheet.
Measured anatomy, dimensions, garment fit or biomechanics	No calibrated multi-sensor metrology, medical standard, mass/force instrumentation or domain validation.
Biometric or legal identity	Target branches and track IDs are authoring lineage only; face/gait identity is out of scope.
Reference/model output as physical truth	Only stripped deterministic math is native. Learned masks, features, depth, pose and shape are removable proposals; agreement is not independent measurement.
Amodal, diffusion or hidden-texture completion	Diffusion-VAS and full-shape/novel-view generation are excluded from authoritative state.
Implemented CSO/Chrono-BRACE/HCO support in current Grove	Current runtime has no observation compiler, dynamic surface staging, human profile, skeletal animation or general scene/object residual codec.
Universal .ugtoms file	UGTOMS remains a proposed profile family/common target; envelope and interoperability are future work.
Compression win	Only an equal-quality benchmark against source video, glTF curves, USD/Alembic caches and VDB can establish it.
Physical-device proof for scene/object workload	Existing Poco evidence belongs to bounded polar Grow rendering and cannot transfer to CSO/Chrono-BRACE/HCO.

Bottom line

The observed scene and persistent objects are the authority

A mesh, voxel or raster at source time tau and knowledge cutoff kappa is a downstream materialization of guarded static support plus persistent object states. Chrono-BRACE circularly contracts bounded camera/static/object/visibility hypotheses before commit. Negative memory means predictable canonical states are not stored. Hidden geometry is explicit proxy or UNKNOWN.

This converts 'chrono-temporally spatially' into an implementable rule: all camera-observed pixels enter typed coverage; static scene and moving objects remain distinct branches; humans add an articulated specialization; decoded chronology and capture uncertainty stay explicit; circular evidence is bounded; novelty replay is bitemporal; no primitive crosses time; and conventional 3D/raster outputs remain downstream and editable.

22. Repository evidence map

Local paths are relative to UGTS_KC_K_Kij_T_Grove_3_9_2_COMPLETE_ALL_FILES unless noted. Line references identify the audited 30 August 2026 worktree.

ID	Primary local source and use
R01	tmp/pdfs/build_ugtoms_cross_domain_overview.py:524-532, 580-648, 729-795, 892-900, 959-1019 - UGTOMS definition, equation, claim status, envelope, adapters, tests and roadmap.
R02	docs/UGTS_ENGINE_WORKLOG.md:761-809 - retained UGTOMS and deterministic knowledge-conduit status; proposed rather than implemented common kernel.
R03	docs/ENGINE_ARCHITECTURE.md:29-60, 84-145, 270-363, 427-522 - ECS authority, ordering, derived populations, animation/hierarchy limits and presentation separation.
R04	README.md:147-171, 225-250, 570-626 - sparse pools, one real ECS prototype, current packs and explicit skeletal/AAA gaps.
R05	docs/UGTS_SUBSTRATE_MECHANISM_MAP.md:21-55, 77-91, 118-146 - bounded polar chain, derived display ownership and measured Grow evidence boundary.
R06	src/ugts_kc3/runtime.py and src/ugts_kc3/replay.py - proposal validation, support/guard/commit, hashes, checkpoint, replay and divergence mechanisms.
R07	spec/SCENE_AND_ASSET_CONTRACT.md:1-39 - scene authority, stable IDs, units/frames, materialization and derived-geometry error contract.
R08	spec/GAME_RUNTIME_CONTRACT.md:1-36 and spec/MOBILE_3D_AND_ANDROID_CONTRACT.md:1-29 - fixed-step order, snapshot/hash rules and bounded physics/mobile claims.
R09	spec/POLAR_GLOW_GROW_V4_CONTRACT.md:1-91 - generated-display-only growth and prohibition on writing derived scale to authoritative ECS/NodeData.
R10	spec/FOUR_D_CONTRACT_DRAFT.md:1-12 - 3D plus time versus four-spatial geometry; neither runtime implemented.
R11	UGTS-GN package source UGTS_GN_1.1.md:233-248, as cited by the repository audit - novelty-only logs require retained/reconstructible authority and bounded replay.
R12	Parent repo SUBSTRATE_ROI_STRATEGY.pdf and TODO.md - repo-wide evidence-adjusted ROI, format policy, universal-format stop rule and CSO/Chrono-BRACE implementation backlog.

Evidence hierarchy

Current code and contracts govern implemented behavior. Preserved build/device records support only their exact workload. Proposed UGTOMS, CSO, Chrono-BRACE and HCO claims remain architecture. Legacy PDFs and attached documents inform chronology but do not override the user's request or current source state.

23. External mathematical provenance and fixture method

ID	Primary source	Exact retained / stripped boundary
W01	MoGe, CVPR 2025, https://openaccess.thecvf.com/content/CVPR2025/papers/Wang_MoGe_Unlocking_Accurate_Monocular_Geometry_Estimation_for_Open-Domain_Images_with_CVPR_2025_paper.pdf ; MoGe-2, https://arxiv.org/pdf/2507.02546	Retain focal/z-shift objective, weighted affine alignment and local support sets. Learned point/metric scale and gradient completion remain proposals/preview; centered principal point and square-pixel assumptions are explicit.
W02	Depth Anything 3 technical report, https://depth-anything-3.github.io/assets/da3_tech_report_2025.pdf	Retain p.6 depth-ray projection, Eq.1-2 DLT/RQ factor math and Eq.8 anchored affine alignment. Predicted rays/depth/camera and focal/300 metric convention are proposals; Gaussian/novel-view path excluded.
W03	DINOv3, https://arxiv.org/html/2508.10104	Retain frozen-feature cosine/top-k spatial candidate math. Contextual features are learned/correlated and never material support or identity.
W04	SAM 3, https://arxiv.org/html/2511.16719	Retain finite mask sets, propagate/detect/match/update and IoU association math as proposals. Negative matching score never means scene/object retraction.
W05	SAM 3D Body, https://arxiv.org/html/2602.15989	Visible 2D keypoint/part proposals and joint-limit/reprojection math only. Learned camera, pose, shape, skeleton and mesh remain hypotheses/proxy; single-view depth ambiguity is preserved.
W06	SAM-Body4D, https://arxiv.org/html/2512.08406v1	Mask/association and deterministic smoothing may seed proposals. Strip Diffusion-VAS occlusion/replacement equations, amodal pixels, completed shape and first-frame shape authority.
W07	Momentum Human Rig, https://arxiv.org/html/2511.15586	Retain Eq.3 same-time parent/offset/translation/prerotation/rotation/scale transform composition for authored human proxy materialization. Identity bases, pose correctives, weights and hidden full mesh are PROXY_ONLY.
W08	Vision Transformer, https://arxiv.org/html/2010.11929	Its patch embedding/global-attention equations establish that tokens are contextual learned states, not material point IDs; only deterministic feature candidate math survives.

DA3 code boundary was checked at commit 3d835ec1a5802d64a8b8b15f817a1ab54809bfe4 and MoGe at 74fbce054ebed49800de42d0ad0e83495065719a. A repository implementation can change; the operator registry must pin the exact paper equation and code revision actually used.

23. Classical projective provenance and fixture

ID	Primary source	Use and boundary
W09	Longuet-Higgins, 1981, https://doi.org/10.1038/293133a0	Essential-matrix two-view geometry; requires calibrated rigid views and does not resolve monocular metric scale.
W10	Nister, 2004, https://doi.org/10.1109/TPAMI.2004.17	Five-point relative-pose candidate generation; Chrono-BRACE uses a canonical bounded sample order and verifier guards.
W11	Hartley and Sturm, 1997, https://doi.org/10.1006/cviu.1997.0547	Reprojection-based triangulation; low parallax/conditioning remains ray support or UNKNOWN.
W12	Triggs et al., 2000, https://doi.org/10.1007/3-540-44480-7_21	Robust joint reprojection refinement; gauge and covariance/conditioning must stay explicit.
W13	Vidal et al., 2006, https://doi.org/10.1007/s11263-005-4839-7	Multibody motion constraints propose static/dynamic/rigid chart branches; human/nonrigid validity is guarded and time-bounded.
W14	Fischler and Bolles, 1981, https://doi.org/10.1145/358669.358692	Hypothesize/verify logic and robust subsets; randomness is replaced or fully ledgered by deterministic seed/order/outlier receipts.
W15	ORB-SLAM3, https://doi.org/10.1109/TRO.2021.3075644	Static-background camera/gauge falsification reference. Its application/library is not the CSO/object representation.

Fixture records

ID	Local evidence
V01	ffprobe and SHA-256 run on 30 August 2026 against the supplied MP4: source path/hash, 12,132,305 bytes, H.264 Main, 1280 x 720, 229 frames, 9.119696 s, 62500/2489 fps, 1/1,000,000 time base.
V02	tmp/pdfs/ugtoms_person_chrono_work/video_probe.py and video_probe.json - deterministic OpenCV track/homography/fundamental diagnostics; method and interpretation limit printed in the JSON.
V03	Six-frame local contact inspection used only to characterize scene difficulty; no frame is embedded in this report.

Primary papers/official code were checked as available on 30 August 2026. Licenses, checkpoints and code can change and must be pinned. Citation is mathematical provenance, exclusion evidence or a benchmark reference - never adoption of the source architecture, installation evidence or clip-level validation.

Prepared for root-repository handoff. Companion execution backlog: parent TODO.md. Supersedes the architecture of UGTS_VSTL_MONOCULAR_CHRONO_LITERAL_HUMAN_0_1.pdf; that earlier artifact should be treated as historical, not current guidance.