





NEW





NEMA 1, 2, 4, 4X, 12 & 13, UL508 POLYCARBONATE AND ABS ENCLOSURES

Polycarbonate & high-impact ABS molded enclosures that meet NEMA 4X specifications, are ideal for PCB enclosures, junction boxes, & other applications in the electrical & electronic industry



Style 1

- Light Gray polycarbonate body and cover
 Body/Cover UV stabilized, UL94-2 flammability rating
- Suggested service temperature: -40°C to 120°C



For quantities greater than listed, call for quote

Γ	Dimensions: in.			MOUSER	Bud	Price	
ſ	D			Fig.	STOCK NO.	Part No.	Each
Γ	2.56	2.28	1.38	Α	563-PN-1320	PN-1320	7.40
	4.53	2.56	1.57	Α	563-PN-1321	PN-1321	10.80
-	4.53	2.56	2.17	Α	563-PN-1322	PN-1322	11.70
	4.53	3.54	2.17	Α	563-PN-1323	PN-1323	13.40
	6.73	4.76	2.17	Α	563-PN-1324	PN-1324	18.80
	8.74	5.75	2.17	Α	563-PN-1325	PN-1325	24.90
	7.68	3.15	2.17	Α	563-PN-1326	PN-1326	18.80
	6.73	4.76	3.15	Α	563-PN-1327	PN-1327	21.30
	4.53	3.54	3.15	Α	563-PN-1328	PN-1328	16.40
	8.74	5.75	2.95	Α	563-PN-1329	PN-1329	28.60
	2.05	1.97	1.38	Α	563-PN-1330	PN-1330	5.90
- [3.23	3.15	2.17	Α	563-PN-1331	PN-1331	11.30
	6.30	3.15	2.17	Α	563-PN-1332	PN-1332	15.40
-	6.30	3.15	3.35	Α	563-PN-1333	PN-1333	16.50
	7.87	4.72	2.95	Α	563-PN1334	PN-1334	23.40
-	10.43	7.28	3.74	Α	563-PN-1335	PN-1335	38.40
-	4.72	4.72	2.36	Α	563-PN1336	PN-1336	16.80
-	4.72	4.72	3.54	Α	563-PN1337	PN-1337	18.20
-	6.30	6.30	2.36	Α	563-PN-1338	PN-1338	23.30
-	6.30	6.30	3.54	Α	563-PN-1339	PN-1339	25.00
	9.45	6.30	3.54	Α	563-PN1340	PN-1340	29.80
-	9.45	6.30	4.72	Α	563-PN-1341	PN-1341	37.00
	11.81	9.06	3.39	Α	563-PN-1342	PN-1342	69.20
-	11.81	9.06	4.37	Α	563-PN-1343	PN-1343	77.60
Ļ	14.17	7.87	5.91	Α	563-PN-1344	PN-1344	93.60
Ľ			Brack			DN 4000 MD	7.40
	2.56 4.53	2.28 2.56	1.38 1.57	A	563-PN-1320-MB 563-PN-1321-MB		7.40 10.70
	4.53	2.56	2.17	A	563-PN-1321-MB		11.20
	4.53	3.54	2.17	A	563-PN-1322-MB		12.60
	6.73	4.76	2.17	A	563-PN-1324-MB		20.70
	8.74	5.75	2.17	A	563-PN-1325-MB		27.00
	7.68	3.15	3.15	A	563-PN-1327-MB	PN-1327-MB	22.30
	6.73	4.76	3.15	A	563-PN-1328-MB	PN-1328-MB	14.50
	4.53	3.54	2.95	A	563-PN-1329-MB		29.20
L	4.33	5.54	2.95	_ ^	303-F IV- 1329-IVID	1 14-1029-IVID	25.20

Style 2

- · Light Gray polycarbonate body
- and clear polycarbonate cover Body/Cover UV stabilized,
- UL94-2 flammability rating
- Suggested service temperature: -40°C to 120°C

For quantities greater than listed, call for quot-

For quantities greater than listed, call for o						
MOUSER	Bud	Price				
STOCK NO.	Part No.	Each				
563-PN1320-C	PN-1320-C	7.70				
563-PN1321C	PN-1321-C	11.10				
563-PN-1322-C	PN-1322-C	12.00				
563-PN1323-C	PN-1323-C	13.90				
563-PN1324-C	PN-1324-C	19.40				
563-PN-1325-C	PN-1325-C	25.50				
563-PN-1326-C	PN-1326-C	18.80				
563-PN-1327-C	PN-1327-C	21.98				
563-PN-1328-C	PN-1328-C	16.40				
563-PN-1329-C	PN-1329-C	28.60				
563-PN-1330-C	PN-1330-C	6.10				
563-PN-1331-C	PN-1331-C	11.50				
563-PN-1332-C	PN-1332-C	15.70				
563-PN-1333-C	PN-1333-C	16.80				
563-PN-1334-C	PN-1334-C	23.70				
563-PN-1335-C	PN-1335-C	38.40				
563-PN-1336-C	PN-1336-C	16.80				
563-PN-1337-C	PN-1337-C	18.20				
563-PN1338C	PN-1338-C	23.30				
563-PN-1339-C	PN-1339-C	25.00				
563-PN-1340-C	PN-1340-C	29.80				
563-PN-1341-C	PN-1341-C	37.00				
563-PN-1342-C	PN-1342-C	69.20				
563-PN-1343-C	PN-1343-C	77.60				
563-PN-1344-C	PN-1344-C	93.60				
With Mounting Brackets *						
563-PN-1320-CMB	PN-1320-CMB	7.40				
563-PN-1321-CMB	PN-1321-CMB	10.70				
563-PN-1322-CMB	PN-1322-CMB	11.20				
563-PN-1323-CMB	PN-1323-CMB	12.60				
563-PN-1324-CMB	PN-1324-CMB	20.70				
563-PN-1325-CMB	PN-1325-CMB	27.00				
563-PN-1327-CMB	PN-1327-CMB	22.30				

- Dark Grav ABS body and cover
- Body/Cover UL94-HB flammability rating
 Suggested service temperature: 40°C to 80°C

For quantities greater than listed, call for que					
MOUSER	Bud	Price			
STOCK NO.	Part No.	Each			
563-PN1320-DG	PN-1320-DG	5.90			
563-PN1321DG	PN-1321-DG	7.60			
563-PN-1322-DG	PN-1322-DG	8.50			
563-PN1323-DG	PN-1323-DG	10.30			
563-PN1324-DG	PN-1324-DG	14.90			
563-PN1325-DG	PN-1325-DG	20.20			
563-PN-1326-DG	PN-1326-DG	12.30			
563-PN1327-DG	PN-1327-DG	14.70			
563-PN-1328-DG	PN-1328-DG	11.10			
563-PN1329DG	PN-1329-DG	18.00			
563-PN-1330-DG	PN-1330-DG	5.20			
563-PN-1331-DG	PN-1331-DG	8.51			
563-PN-1332-DG	PN-1332-DG	11.80			
563-PN-1333-DG	PN-1333-DG	13.00			
563-PN-1334-DG	PN-1334-DG	17.30			
563-PN-1335-DG	PN-1335-DG	29.10			
563-PN-1336-DG	PN-1336-DG	12.20			
563-PN1337-DG	PN-1337-DG	13.00			
563-PN-1338-DG	PN-1338-DG	17.60			
563-PN-1339-DG	PN-1339-DG	18.80			
563-PN-1340-DG	PN-1340-DG	23.90			
563-PN1341-DG	PN-1341-DG	27.40			
563-PN-1342-DG	PN-1342-DG	44.40			
563-PN1343DG	PN-1343-DG	47.00			
563-PN-1344-DG	PN-1344-DG	55.30			
With Mounting Brackets:					
563-PN-1320-DGMB	PN-1320-DGMB	6.00			
563-PN-1321-DGMB	PN-1321-DGMB	8.00			
563-PN-1322-DGMB	PN-1322-DGMB	8.50			
563-PN-1323-DGMB	PN-1323-DGMB	9.50			
563-PN-1324-DGMB	PN-1324-DGMB	14.40			
563-PN-1325-DGMB	PN-1325-DGMB	18.30			
563-PN-1327-DGMB	PN-1327-DGMB	15.60			
563-PN-1328-DGMB	PN-1328-DGMB	11.40			
563-PN-1329-DGMB	PN-1329-DGMB	19.40			

* Dimensions exclude brackets



Style A:

Bud

Boxes

Plastic

- Has squared corners, provisions for mounting horizontal and vertical PCBs, and four non-skid feet UL94-HB flammability rating
- Temperature rating: -40°C to +60°C Available in Black or Gray

2 piece, screw together desktop enclosure with sloping cover Durable, self-extinguishing, ABS plastic material with UL94-H flammability rating Mark-resistant textured surface Internal PCB mounting bossesAvailable in Bone Gray

Style I:

- Unique, contemporary styling with rounded corners and edges
- Durable, self-extinguishing, ABS plastic material with UL94-5VA flammability rating
- Mar resistant textured surface
- Internal PCB mounting bosses
- Base is securely attached to the cover
- with four color matched screws
 PT-11754-DW features a display window
- Color: Black

PN-1328-CMB

PN-1329-CMB

Style J:
Designed to meet NEMA 4X and IP65 Specifications

29.20

- Easily removable cover screws into threaded brass inserts in base
- Molded in flanges allow easy wall or panel mounting without having to
- open enclosure
- 8 PCB mounting bosses in base
 PT-11801 has an additional 6 inside elevated cover
- Color: Textured Matte Black

Style K:

- Time saving, hinged, snap closed cover
- that is easily opened by hand

 Rubber inserts are easily cut to allow cable entry ports
- Durable, self-extinguishing, ABS plastic material with UL94-HB flammability rating
 Mark-resistant textured surface

- Internal PCB mounting bossesAvailable in Black or Gray

	For quantities greater than listed, can for quote				
MOUSER STOCK NO. Mrf. Mrf. Part No.	Fig.	Color	Style	Outside Dimensions: in. H x W x D	Price Each
563-PT-11308-B	В	Black	Α	3.62 x 2.25 x 1.50	7.00
563-PT-11308-G	В	Gray	Α	3.62 x 2.25 x 1.50	7.00
563—PBS-11327-B	В	Black	Α	5.62 x 3.25 x 1.50	12.20
563—PBS-11327-G	В	Gray	Α	5.62 x 3.25 x 1.50	12.80
563-PT-11372-B	В	Black	Α	3.62 x 2.25 x 2.50	8.50
563—PT-11372-G	В	Gray	Α	3.62 x 2.25 x 2.50	7.36
563—PT-11388-B	В	Black	Α	5.62 x 3.25 x 2.48	10.40
563—PT-11388-G	В	Gray	Α	5.62 x 3.25 x 2.48	9.88
563—PT-11820	С	Gray	L	7.40 x 5.24 x 2.22	12.50
563—PT-11743	D	Black	- 1	3.00 x 4.00 x 1.38	7.50
563—PT-11754	D	Black	- 1	4.00 x 5.50 x 1.38	9.90
563—PT-11754-DW*	D	Black	- 1	4.00 x 5.50 x 1.38	9.90
563—PT-11785	D	Black	- 1	5.00 x 7.50 x 1.75	13.20
563—PT-11785-MP*	D	Black	1	5.00 x 7.50 x 1.75	12.70
563—PT-11800	E	Black	J	8.25 x 5.00 x 3.00	21.30
563—PT-11801	E	Black	J	8.25 x 5.00 x 4.33	23.50

* DW: Display Window MP: Wall Mount

Style L:

Available in two types of finishes and with or without battery compartments, refer to the following prefix description to insure proper ordering.

PS: Textured body with smooth insert

PT: Textured body with textured top
PBS: Textured body with smooth top insert and 9V battery compartment

PSS: Textured body with smooth top and end panels PSP: Textured body with smooth top and sloped panels

PBSP: Textured body with smooth top, and sloped panel, and battery compartment

Contact a Mouser Service Representative



© Copyright 2013 Mouser Electronics