

technical data type WKX

Base: Batten fitting made of white stove enamelled steel.

- optional :


- white steel reflectors.
- high polished aluminium reflector.
- high polished alum. assymetrical reflector.

Suitable for a wide range of applications where many low cost lighting points are requested.



Electrical specifications:

- The metal case contains all switchstart (other versions on request) control gear components, lampholders and terminal connector for fluorescent lamps.
- Electrical wiring with first quality components according to European norms and standards.



WKX T8 with aluminium reflector (optional)

WKX T8 with white coated reflector (optional)



WKX T8 with aluminium assymetrical reflector (optional)

WKX T5

Lamps:

- fluorescent T8 lamps in 18w 36w 58w
- fluorescent T5 lamps in 14w-24w-28w-35w-49w-54w-80w



3p. troughwiring with connector (optional)






IP20





technical data type WKX



| T8 | 200 |
|----|-----|
| T5 | 200 |

| Model T8 | | L | Lf |
|-------------|-------------|------|------|
| 1x18W | 2x18W | 615 | 450 |
| 1x36W | 2x36W | 1225 | 900 |
| 1x58W | 2x58W | 1525 | 1200 |
| | | | |
| Model T5 | | | |
| 1x14/24W | 2x14/24W | 584 | 400 |
| 1x28/54W | 2x28/54W | 1184 | 900 |
| 1x35/49/80W | 2x35/49/80W | 1484 | 1200 |





Tel + 32 11 88 09 00

