

LEARNING HASKELL WITH NETWORK PROGRAMMING

CONTENTS

Foreword	v
1 Getting Everything Installed	1
1.0.1 GHC	2
1.0.2 Cabal and Stack	2
1.1 Getting Your Environment Set Up	3
1.1.1 Getting Set Up with Cabal	3
1.1.2 Getting Started with Stack	5
1.1.3 Using Stack	5
2 Functions	7

FOREWORD

Haskell, as a language, has a bit of a loaded reputation.

A lot of programmers assume that Haskell is that “mathey language”, and once they hear mention of functors, monoids, monads, and arrows, they end up with the conclusion that it is a tool that might have some interesting ideas, but is too academic to be suitable for any kind of practical use.

This is an easy viewpoint to have. There is a steep, non-trivial learning curve to the minutia of functional programming, and Haskell is among the most dogmatic of the functional languages; to understand Haskell is to understand the basics of algebra, Category Theory, Type Theory, and Set Theory. Consequently, a lot of people assume that people learn Haskell so that they can look smart.

While this is certainly true (and is why I picked up the language initially), functional programming has started to become fairly popular in the last couple years, and many people have started to appreciate the benefits of concepts like immutability, a clear type system, and the mathematical safety that programming in a functional style provides. The rise in popularity in languages like Scala, Rust, and F#, as well as the newer functional features being added to Java 8, C++, and C# has shown us that there is a clear market for functional programming in the field of computer science.

Learning Haskell is about more than just the language. Haskell has become the poster-child for the testing ground of the cutting edge features of computer science.

New methods of parallelism, thread safety, parsing, and nearly every other new programming theory comes over to Haskell first.

But what you get with Haskell isn't just access to functional features. Indeed, if you wanted an excuse to play with functional programming, the barrier of entry to do so is much lower with JavaScript.

What you get from Haskell is a purely devoted, unambiguous entry to a functional way of structuring your programs, with all the benefits and annoyances that come with that. You get all the frustration of having to avoid state, but also all the benefits of guarantees that your functions will work exactly the same after being run a trillion times. You get all the frustration of having to use recursion instead of loops, but all the benefit of knowing that you'll never be forced to deal with a `null` reference error.

What you get with Haskell is something you do not get with many other languages: guarantees. Mathematics is one of the very few things in life that boasts in its proofs and correctness and by taking a purely mathematical approach allows you to reap all the benefits of all that scary topics that I mentioned before. And with those guarantees, you find that Haskell is a language *especially* well-suited for production systems that need to *keep working*.

Upon learning Haskell, it's not uncommon for a person to re-evaluate and change their entire coding process to use a more functional style, or to start utilizing the functional features of their favorite language.

Being forced to view things from a different, strange angle can be a godsend in how you approach problems; sometimes approaching certain problems from a functional perspective can greatly simplify the problem. Recursion is a useful, often-underutilized tool that becomes easier to understand once confronted with a world without loops. Optional types give compile-time checks to that completely infamous `null` reference exception. Higher-order functions give a level of modularity that is nearly impossible to replicate with more "traditional" imperative coding styles.

There are plenty of reasons to learn functional style, and many of them will be described in this book, but if you are to take anything out of this book, it should be that there is value in the extravagant and theoretical. I hope you enjoy it, and find that something like Haskell can open the door to the other interesting new paradigms in this whacky field we call "Computer Science".

CHAPTER 1

GETTING EVERYTHING INSTALLED

It can be incredibly difficult to know where to even start when doing Haskell. The documentation on the Haskell Wiki, while very good, is designed for a more academic audience than most of the more mainstream languages. Challenges tend to arise when even knowing *which* compiler to install, let alone how to go about structuring things or installing libraries.

This probably why often the biggest hurdle to cross when getting started with a new programming language is simply getting the compiler, platform tools, and editor set up for beginning your development, if for no other reason than the fact that the territory is still entirely new and it can be difficult to know when you did something incorrectly.

Until very recently, Haskell has been an especially difficult platform to work because of its ambiguous ways of setting everything up, especially on Windows. Different versions of different point releases of Haskell compilers crowd their way through the package managers, making code more challenging to port between systems than it had any right to be.

Before getting too far into how to go about installing things, we should define some key terms that will be used frequently throughout the book.

1.0.1 GHC

The Glorious Haskell Compiler, or GHC for short, is the *de facto* standard compiler for doing Haskell work. It has been in development since the late eighties, and is usually what people mean when they say "Haskell". It survives out of user contributions and from funding from Microsoft Research, and is generally the first Haskell compiler to get new features (although they tend to be hidden away in compiler extensions)

1.0.1.1 Some Notes About GHC There is an old saying about Haskell by Simon Peyton Jones: "Avoid Success At All Cost". The meaning of this statement was to imply that Haskell should remain free as a platform for new ideas and doing things the "right" way, and not cave to the pressures of industry demands.

This is all well and good, but it also means that the developers of GHC can and will often introduce new features and rules for the language as often as they want, which can lead to breaking changes between differing versions of GHC, sometimes even for point-releases.

Several tools, such as Stack, have done a lot of great work to minimize the damage that these changes can cause, and it should be noted that the later versions of GHC have been doing much better at avoiding huge breaking changes, but it is something you have to be aware of.

1.0.2 Cabal and Stack

While GHC does a good job at compiling your Haskell programs, it doesn't dictate how to structure the project or handle library dependencies. GHC is exactly what its name states: a compiler.

Like many modern languages, most Haskell developers eschew the use of Make-files and build scripts, instead utilizing a folder structure and config file.

Cabal was the first major system to allow such a style for Haskell, and remains a popular tool today for such reasons. Cabal gives you a structure for building your projects, gives you simple commands like `cabal build` and `cabal repl`, giving you a simple-to-read project file for handling dependencies from Hackage (the standard repository for Haskell libraries), basic sandboxing, compiler extensions, and build parameters.

However, Cabal does nothing to address the fragmentation of GHC that was mentioned earlier. Cabal's installation is predicated on the notion that you already have a functioning GHC installed, and even installing Cabal itself can lead to some incompatibility between versions. This, compounded with the almost complete lack of management of transitive dependencies has lead to something people in the Haskell trade have labeled "Cabal Hell", and has been the bane of nearly every veteran the language has. It was not and still is not difficult to find people on Hacker News and Reddit complain about how they gave up on Haskell due to problems with getting Cabal to work.

In 2015, the people at FP Complete addressed this problem with their new build platform: Stack. Stack still used Cabal for things like dependency management behind the scenes, but gave Haskell a feature it had never had before: reproducible builds.

Stack allows the user declare which version of GHC they want to use for their project, on a per-project basis, and even allows them to declare it in the "shebang"

at the beginning of scripts. Like Cabal, it gives a structure to your project, gives you access to commands like `stack build` and `stack ghci`, which will generally “just work” on your machine.

They also built an alternative repository called “Stackage”, which, while similar to Hackage, audits packages to greatly reduce the likelihood of a transitive dependency conflicts, almost (but not completely) eliminating the potential for Cabal Hell.

1.0.2.1 A note about operating-system package managers I should also make this point abundantly and overwhelmingly clear: do *not* install GHC through your operating system’s package manager like `apt`, `pacman` or `brew`. The versions of GHC included in these repositories tend to be incredibly out of date, and are installed system-wide, thus making it difficult to install differing versions of GHC or Cabal for different project.

It is best to ignore your system package manager when working with Haskell, and utilize a tool like Stack instead. This will save you a lot of time avoiding arguments with Cabal.

1.1 Getting Your Environment Set Up

While Stack has largely supplanted any previous systems that were used for Haskell development, there is still a chance that if you’re reading this, you will be looking at an older, legacy project that hasn’t adapted to it yet.

So, although we will be using Stack throughout most of this book, I feel obliged to at least mention how to get started with the older, Cabal-only approach; I implore you to explore Stack unless you’re under explicit order to do it with Cabal.

With that being said, let us take a look at using Cabal.

1.1.1 Getting Set Up with Cabal

The first thing you will want to do when using Cabal is to make sure that you have downloaded the latest version of the Haskell Platform from <https://www.haskell.org/platform/>. This should guarantee an up-to-date version of Cabal is installed on your system, thus ensuring the best compatibility possible.

Once the Haskell Platform is installed, you should have `ghc` installed on your system, so let us begin the process of setting up a new project:

```
mkdir my_new_project
cd my_new_project
cabal sandbox init
```

The first two lines should be fairly self explanatory, but `cabal sandbox init` might be a bit confusing.

While it’s not *strictly* required, sandboxing will greatly simplify your time using Cabal. If you do not use a sandbox, dependencies get installed into the global space of your machine, instead of being contained to your project. This might not be an issue if you only have one project, or your projects are each contained separate virtual machines or containers, but it can be a tremendous nuisance when working with multiple projects on the same machine, which may be required depending on your workflow.

Once your sandbox is created, you will want to run `cabal init`

```
tombert@hostname:~/my_new_project# cabal sandbox init

Config file path source is default config file.
Config file /root/.cabal/config not found.
Writing default configuration to /root/.cabal/config
Writing a default package environment file to
/root/my_new_project/cabal.sandbox.config
Creating a new sandbox at /root/my_new_project/.cabal-sandbox
root@6a2da51caa38:~/my_new_project# cabal init
Package name? [default: my-new-project] my_new_project
Couldn't parse my_new_project, please try again!
Package name? [default: my-new-project]
Package version? [default: 0.1.0.0]
Please choose a license:
* 1) (none)
  2) GPL-2
  3) GPL-3
  4) LGPL-2.1
  5) LGPL-3
  6) AGPL-3
  7) BSD2
  8) BSD3
  9) MIT
 10) ISC
 11) MPL-2.0
 12) Apache-2.0
 13) PublicDomain
 14) AllRightsReserved
 15) Other (specify)
Your choice? [default: (none)]
Author name? Thomas Gebert
Maintainer email? thomas@gebert.sexy
Project homepage URL?
Project synopsis? A test project for everyone to enjoy
```

Generally, the defaults are fine for most projects, though you should pay special attention to the Haskell version (2010 or 98), as this can greatly influence what the language allows you to do. You also should pay attention to the location where the code exists (`src` in this case) and the name of the “`main.hs`” file.

As previously stated, there is not much reason now to run vanilla Cabal. It’s not useless or horrible, and it’s possible that if you need to work with an older project you will be forced to use it.

For new projects though, we will want to use Stack.

1.1.2 Getting Started with Stack

FPCComplete’s Stack is relatively easy to install. If you’re on a Unix or Linux machine, installation is a fairly straightforward process of pasting a command into your terminal:

```
curl -sSL https://get.haskellstack.org/ | sh
```

1.1.2.1 Installation on Windows If you’re on Windows, then first consider using a Linux installation in a free virtual machine or in a separate Linux server first. GHC tends to be a little out of date on Windows, and is usually at least one version behind. However, if your plan is to build a Windows program, you will be forced to use the Windows version of Stack.

The installation on Windows isn’t terribly hard, and involves a standard “next-next-next-finish” style of installer.

It should be noted that this book is going to assume that the user is using a Unix or Unix-Like environment, since the theme of this book is about network programming.

1.1.3 Using Stack

Stack com

CHAPTER 2

FUNCTIONS

We should start Haskell with most obvious thing in Functional Programming but arguably the most different from traditional programming: functions.

Functions, in the mathematical sense, are predictable units of work.