

Introduction

Machine Learning and Security

Fabio De Gaspari
Dorjan Hitaj

General Information

Google Classroom of the course:

- https://classroom.google.com/c/MTYyNzMyNTQ2MTMx?cjc=tftag4vd
- Code: tftag4vd

About the Course

Two lecturers:

- Fabio De Gaspari
- Dorjan Hitaj

Goal:

- Understand some applications of Machine Learning to cybersecurity and the vulnerabilities of Machine Learning in adversarial contexts
- Practical labs on select topic

About the Professor

Fabio De Gaspari

- Assistant Professor at the Department of Computer Science
- Research focus:
  - systems security
  - machine learning security and privacy
  - network security

Personal homepage (contact info, research topics, office hours, etc.):

https://sites.google.com/di.uniroma1.it/degaspari/home

About the Professor

Dorjan Hitaj

- Assistant Professor at the Department of Computer Science
- Research focus:
  - machine learning and cybersecurity

Personal homepage (contact info, research topics, office hours, etc.):
https://sites.google.com/view/dorjanhitaj/

Logistics

Lectures on Tuesday and Wednesday

- Tuesday: 12-14 Aula 101, Palazzina D, Viale Regina Elena 295
- Wednesday: 10-13 Aula 4 De Lollis, Via Tiburtina 205

Course Material:

- Available in the Classroom
- Mix of slides and papers - no textbook

Logistics

Exceptions:

- 29/09/2026
- 20/10/2026
- 10/11/2026

These lectures will be held in aula 2L, Castro Laurenziano.

About the Exam


- Focus on practical understanding -> Course Project
  - implement some techniques on one of the topics covered in class
  - Confirm with us (by mail/in person) if your project idea is ok before starting working on it
  - Handed in at least **2 weeks** before the planned day of the exam
- Class presentation on select topic
  - TBC - depending on number of students and timing
- Oral Exam
  - discussing the project and related topics

Tentative Syllabus


- Intro to Machine Learning and Deep Neural Networks
- Evasion attacks and defenses
- Poisoning and Trojaning attacks and defenses
- Certifiable Robustness
- Generative models and Large Language Models
- Inference attacks and Federated Learning
- Explainable AI

Why Do We Care?

Why Do We Care




Why Do We Care






Why Do We Care




Who Would Win?




VS



+



Who Would Win?







Stop Sign



Speed 30








Stop Yield Speed Limit

(a) Normal (b) Attack

Who Would Win?




VS



https://adversarial-attacks.net/


Who Would Win?




VS




Who Would Win?





(a) Example jailbreak via competing objectives.



(b) Example jailbreak via mismatched generalization.

Who Would Win?



AGENT GRIFT

OpenAI's New AI Browser Is Already Falling Victim to Prompt Injection Attacks

"Trust no AI."

By Victor Tangermann / Published Oct 24, 2025 12:06 PM EDT



BLOG > AI NEWS & FEATURES

Unseeable prompt injections in screenshots: more vulnerabilities in Comet and other AI browsers

PUBLISHED OCT 21, 2025



Cybersecurity experts warn OpenAI's ChatGPT Atlas is vulnerable to attacks that could turn it against a user—revealing sensitive data, downloading malware, or worse


BY BEATRICE NOLAN
TECH REPORTER

October 23, 2025 at 6:16 AM EDT




The glaring security risks with AI browser agents

Maxwell Zeff — 5:00 AM PDT · October 25, 2025


Search or enter address
Set Fellou as default browser
Set as default
Fellou
Search or ask me to do something
Search
Action
Think
Try these tasks:
Inspiration
Productivity
Daily Life
Data Analytics
Marketing
Career&Study
Deep search the latest updates about Fellou and summarize findings
Automate browser to follow Fellou's social media accounts
Generate 2 creative logo concepts for Fellou and save as images and SVGs
Create a simple portfolio website to showcase Fellou info and logos
Compose an ambient music track inspired by Fellou and integrate it on the website
To get started, you can try asking one of these:
Find and follow FellouAI on X.com
Open Google Calendar and summarize my schedule for the week.
Search for Fellou info, create 2 new logos (image + SVG) and a value-based music piece, build a website to showcase all of this, and post on X.com.

Ok, But Why?

Are we just burning hundreds of billions?



=




?


How You Model Your World Matters

Based on slides from Battista Biggio

The Classical World View of Machine Learning




The Classical World View of Machine Learning





The Classical World View of Machine Learning

Can you read this?
It's a legitimate question
you might or might not
recognize it as an
example of coursive writing




Training





x_1

Key Assumptions:
- Source of data does not depend on model
- Noise is stochastic in nature (typically assumed gaussian)




Data Source / Generator

Data Acquisition

Acquired Data


Feature Vector

Inference



Stochastic Noise

The Classical World View of Machine Learning



A Motivating Example: Spam

From: spammer@definitelynotsmap.com

You should buy some bitcoins here!



Keywords Weights:
buy: 2.0
bitcoins: 4.0


Threshold: 5.0

Score: 6.0 > 5.0 -> SPAM

A Motivating Example: Spam

From: spammer@definitelynotsmap.com

You should buy some bitcoins here!



A Motivating Example: Spam

From: spammer@definitelynotsmap.com

Hey, it's your uncle! You should buy some bitcoins here!
The Uncle

Keywords Weights:
buy: 2.0
bitcoins: 4.0
Uncle: -2.0



Threshold: 5.0


Score: 4.0 < 5.0 -> NOT SPAM

A Motivating Example: Spam

From: spammer@definitelynotsmap.com

Hey, it's your uncle! You should buy some bitcoins here!
The Uncle

Keywords Weights:
buy: 2.0
bitcoins: 4.0
Uncle: -2.0



A Motivating Example: Spam


From: spammer@definitelynotsmap.com

Hey, it's your uncle! You should buy some bitcoins here!
The Uncle

Keywo
buy: 2.
bitcoin
Uncle:


Key Assumptions:

- Source of data does not depend on model
  - **The adversary can craft data (attack) based on model**
- Noise is stochastic in nature (typically assumed gaussian)
  - **Adversarial data is not random**



An Adversarial World Model

Cybersecurity Arms Race



Key Rules

- Know your adversary
- Be proactive
- Protect your model

Know Your Adversary: The Threat Model

1. Knowledge




3. Capability


2. Goal

Threat Model: Adversary's Goal






Integrity



Availability




Confidentiality


Compromise model's intended operations


- Getting the model to misclassify samples

Threat Model: Adversary's Goal










Integrity **Availability** Confidentiality

Compromising access to the model


- Errors that compromise normal system operations (e.g., DoS)

Threat Model: Adversary's Goal






Integrity



Availability




Confidentiality

Extracting private information from the model


- Revealing confidential information of the model or its users

Threat Model: Adversary's Knowledge





Training Data




Model's Details



Output Feedback

Threat Model: Adversary's Knowledge




Training Data | Model's Details | Output Feedback

Whitebox Attacks: perfect knowledge, adversary knows everything

- worst-case scenario for the defender. Upper bound on performance degradation under attack

Threat Model: Adversary's Knowledge



Training Data | Model's Details | Output Feedback


Graybox Attacks: partial knowledge

- Typical realistic setting.
- Adversarial knowledge of what depends on use-case

Threat Model: Adversary's Knowledge



Training Data



Model's Details



Output Feedback

Blackbox Attacks: no knowledge. Adversary doesn't know anything.

- Very weak adversarial model. Best-case for defender
- Typically not very realistic

Threat Model: Kerckhoffs' Principle


"The enemy knows the system"

- A system should be secure even if everything about it is public knowledge
  - No security through obscurity
- Make minimal assumptions about what can be really kept secret
  - E.g., for ML, an adversary is likely aware of algorithms used, at least partial training data information, rough model architecture


Regardless, an ML model should always be tested under varying levels of adversary's knowledge and model access

Threat Model: Adversary's Capability






Data during Training




Data at Inference Time

Threat Model: Adversary's Capability





Data during Training



Data at Inference Time

Can modify training data, influencing the model at training time

- Resulting in errors/vulnerabilities at inference time
- Poisoning, backdoors, payload injection, ...


Threat Model: Adversary's Capability



"Unfortunately, in the first 24 hours of coming online, a coordinated attack by a subset of people exploited a vulnerability in Tay. Although we had prepared for many types of abuses of the system, we had made a critical oversight for this specific attack. As a result, Tay tweeted wildly inappropriate and reprehensible words and images. [...] We are hard at work addressing the specific vulnerability that was exposed by the attack on Tay."


- Microsoft

Threat Model: Adversary's Capability




Threat Model: Adversary's Capability





Data during Training



Data at Inference Time

Can manipulate samples sent for classification at inference time (e.g., spam mail text)

- Cause misclassifications, infer private data, …
- Evasion attacks, adversarial examples, membership inference, …

Threat Model: Adversary's Capability - Limits

Luckily, the adversary is typically *constrained* in what they can do

- Phishing emails still need to be emails, and they need to be readable and understandable by humans
- Images (e.g., phishing websites) still need to resemble the original to be credible
- Malware binaries must still execute correctly on a computer
  - They must also correctly perform their malicious activity (e.g., ransomware)
- The adversary does not have full control over the full model pipeline

Threat Model: Adversary's Capability - Limits




Data during Training

Only has limited control over training data manipulation

- Maximum number of samples that can be altered in the training data
  - Datasets are very large, adversaries typically control only small fractions
- Limited in how training data can be modified
  - Can only add/remove/modify points


Threat Model: Adversary's Capability - Limits



Data at Inference Time

Limited to the feasible domain

- Only limited modification on query samples
- application-specific constraints in input space (e.g., binary executable structure)



Threat Model: Adversary's Capability - Limits

- Systems should be designed avoiding unreasonable assumptions on the adversary's capabilities
  - Who is my adversary? who realistically do I need to defend against? NSA or Bob?
  - Assuming infinitely strong adversaries gives little information on real-world system robustness
  - Still, one should not choose unreasonably weak adversaries
- Testing systems under several levels of adversary's capability is key