

Bazy Danych: Projekt**Raport****Zespół 5: Furgała Tomasz, Łukasz Kluza, Mateusz Sacha****1. Administrator**

- Usuwanie webinaru, administrator może usunąć dostępne nagranie webinaru gdy uzna to za stosowne.
- Zarządzanie użytkownikami, administrator ma możliwość edycji kont innych użytkowników.
- Generowanie raportów, administrator generuje raporty zawierające aktualne statystyki.

2. Gość

- Założenie konta, użytkownik może założyć konto, które umożliwia mu korzystanie z systemu
- Przeglądanie kursów, użytkownik ma możliwość zapoznania się z aktualną ofertą kursów i szkoleń.

3. Zalogowany użytkownik

- Zapis na webinar, kurs lub studia, użytkownik może zapisać się na wybraną przez siebie usługę.
- Płatność za usługi, dokonuje opłaty by móc wziąć udział w webinarze, kursie lub studiach oraz wykupuje późniejszy dostęp do materiałów.
- Przeglądanie listy, możliwość przeglądania listy usług, na które dany użytkownik jest zapisany.
- Odbiera dyplom, użytkownik może odebrać dyplom, gdy zostanie on wystawiony przez administratora.

4. Koordynator

- Odrzucanie płatności, dyrektor szkoły ma możliwość odroczenia płatności na określony czas.
- Wgląd do kursów oraz webinarów, dyrektor ma możliwość wglądu do danych o kursach i webinarach prowadzonych przez jego pracowników
- Zatwierdzanie programu studiów, dyrektor ma dostęp do ułożonych przez pracowników sylabusów przed opublikowaniem ich oraz możliwość zatwierdzania i wprowadzania poprawek do nich
- Zatwierdzanie nowych kursów i webinarów, dyrektor zatwierdza bądź odrzuca każdy nowy kurs, webinar, stworzony przez jego pracowników

5. Menadżer

- Zarządzaniem limitem miejsc, menadżer ustala maksymalną liczbę osób która może uczestniczyć w danym webinarze, szkoleniu
- Wystawianie dyplomów, menadżer wystawia dyplom użytkownikowi, który spełnił wszystkie regulaminowe przesłanki co to do tego.
- Zarządzanie ofertą, menadżer ma możliwość edycji obecnej oferty jak i możliwość dodawania nowych kursów, szkoleń.

6. Prowadzący/Wykładowca

- Dostęp do swoich webinarów, każdy prowadzący ma nielimitowany czasowo dostęp do nagrań wszystkich swoich webinarów
- Możliwość edycji modułów kursu, prowadzący mają możliwość wprowadzania poprawek oraz modyfikacji materiałów znajdujących się na prowadzonych przez siebie kursach
- Dostęp do systemu ocen i obecności, prowadzący ma dostęp do systemu, w którym może swobodnie zapisywać oraz zmieniać oceny i obecności uczestników jego kursów
- Ułożenie sylabusu, prowadzący musi ułożyć sylabus do każdego z prowadzonych przez siebie przedmiotów w określonym terminie przed rozpoczęciem studiów

7. System

- Generowanie linków do płatności, system sam, automatycznie generuje link do płatności, gdy użytkownik chce opłacić zamówienie.
- Wysyłanie powiadomień, uczestnik spotkania dostaje powiadomienia, gdy rozpoczyna się spotkanie, w którym ma uczestniczyć.
- Powiadomienie o zapłacie, użytkownik dostaje przypomnienie o konieczności zapłaty tydzień przed ostatecznym terminem dokonania płatności, dotyczy to także zaliczek.

Diagram bazy danych:



```

CREATE TABLE [dbo].[Webinar](
    [WebinarID] [int] NOT NULL,
    [WebinarName] [nchar](50) NOT NULL,
    [Date] [datetime] NOT NULL,
    [TeacherID] [int] NOT NULL,
    [MeetingLink] [nchar](30) NULL,
    CONSTRAINT [PK_Webinar] PRIMARY KEY CLUSTERED
(
    [WebinarID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Webinar] WITH CHECK ADD CONSTRAINT [FK_Webinar_Offers] FOREIGN KEY([WebinarID])
REFERENCES [dbo].[Offers] ([OfferID])

ALTER TABLE [dbo].[Webinar] CHECK CONSTRAINT [FK_Webinar_Offers]

ALTER TABLE [dbo].[Webinar] WITH CHECK ADD CONSTRAINT [FK_Webinar_TeachingStaff] FOREIGN KEY([TeacherID])
REFERENCES [dbo].[TeachingStaff] ([TeacherID])

ALTER TABLE [dbo].[Webinar] CHECK CONSTRAINT [FK_Webinar_TeachingStaff]

ALTER TABLE [dbo].[Webinar] WITH CHECK ADD CONSTRAINT [CHK_Webinar_WebinarName_Length] CHECK
((len([WebinarName])>(5)))

ALTER TABLE [dbo].[Webinar] CHECK CONSTRAINT [CHK_Webinar_WebinarName_Length]

```

3. Studies:

Tabela zawiera informacje o studiach, zawiera klucz główny (StudiesID), kierunku studiów oraz opłacie za nie (Name, Fee), koorynatorze, maksymalnej ilości studentów na danym studium (MEnagerID, StudentCapacity).

```

CREATE TABLE [dbo].[Studies](
    [StudiesID] [int] NOT NULL,
    [Name] [nchar](50) NOT NULL,
    [Fee] [money] NOT NULL,
    [MenagerID] [int] NOT NULL,
    [StudentCapacity] [int] NOT NULL,
    CONSTRAINT [PK_Studies_1] PRIMARY KEY CLUSTERED
(
    [StudiesID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]S

ALTER TABLE [dbo].[Studies] WITH CHECK ADD CONSTRAINT [FK_Studies_Employees] FOREIGN KEY([MenagerID])
REFERENCES [dbo].[Employees] ([EmployeeID])

ALTER TABLE [dbo].[Studies] CHECK CONSTRAINT [FK_Studies_Employees]

ALTER TABLE [dbo].[Studies] WITH CHECK ADD CONSTRAINT [FK_Studies_Offers] FOREIGN KEY([StudiesID])
REFERENCES [dbo].[Offers] ([OfferID])

ALTER TABLE [dbo].[Studies] CHECK CONSTRAINT [FK_Studies_Offers]

ALTER TABLE [dbo].[Studies] WITH CHECK ADD CONSTRAINT [CHK_Fee_NonNegative] CHECK (([Fee]>=(0)))

ALTER TABLE [dbo].[Studies] CHECK CONSTRAINT [CHK_Fee_NonNegative]

ALTER TABLE [dbo].[Studies] WITH CHECK ADD CONSTRAINT [CHK_StudentCapacity_Minimum] CHECK
(([StudentCapacity]>=(10)))

ALTER TABLE [dbo].[Studies] CHECK CONSTRAINT [CHK_StudentCapacity_Minimum]

ALTER TABLE [dbo].[Studies] WITH CHECK ADD CONSTRAINT [CHK_Studies_Name_Length] CHECK ((len([Name])>(5)))

```

```
ALTER TABLE [dbo].[Studies] CHECK CONSTRAINT [CHK_Studies_Name_Length]
```

4. Courses:

Tabela zawiera spis wszystkich kursów z kluczem głównym (CourseID), posiada informację o temacie kursu oraz jego nazwie (TopicID, CourseName), a także dacie rozpoczęcia, ilości modułów z których kurs się składa i dacie zapłaty (StartDate, ModulesNo, PaymentDay), całkowitej kwocie jaką należy za kurs zapłacić, kwocie zaliczki oraz zniżce (FullPrice, Deposit, Discount).

```
CREATE TABLE [dbo].[Courses](
    [CourseID] [int] NOT NULL,
    [TopicID] [int] NOT NULL,
    [CourseName] [nchar](30) NOT NULL,
    [StartDate] [datetime] NOT NULL,
    [ModulesNo] [int] NOT NULL,
    [PaymentDay] [datetime] NOT NULL,
    [FullPrice] [money] NOT NULL,
    [Deposit] [money] NOT NULL,
    [Discount] [float] NOT NULL,
    CONSTRAINT [PK_Courses] PRIMARY KEY CLUSTERED
(
    [CourseID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [FK_Courses_Offers] FOREIGN KEY([CourseID])
REFERENCES [dbo].[Offers] ([OfferID])

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [FK_Courses_Offers]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [FK_Courses_Topics] FOREIGN KEY([TopicID])
REFERENCES [dbo].[Topics] ([TopicID])

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [FK_Courses_Topics]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [CHK_Courses_CourseName_Length] CHECK
((len([CourseName])>(5)))

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [CHK_Courses_CourseName_Length]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [CHK_Deposit_Range] CHECK ((([Deposit]>=(0) AND
[Deposit]<=[FullPrice]))

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [CHK_Deposit_Range]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [CHK_Discount_Range] CHECK ((([Discount]>=(0) AND
[Discount]<=(1)))

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [CHK_Discount_Range]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [CHK_FullPrice_NonNegative] CHECK ((([FullPrice]>=
(0)))

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [CHK_FullPrice_NonNegative]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [CHK_ModulesNo_Positive] CHECK ((([ModulesNo]>(0)))

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [CHK_ModulesNo_Positive]

ALTER TABLE [dbo].[Courses] WITH CHECK ADD CONSTRAINT [CHK_PaymentDay_BeforeStart] CHECK ((([PaymentDay]
<=dateadd(day,-3,[StartDate])))

ALTER TABLE [dbo].[Courses] CHECK CONSTRAINT [CHK_PaymentDay_BeforeStart]
```

5. Gatherings:

Tabela zawiera informacje o zjazdach, posiada klucz główny (GatheringID) i semestr, w ramach którego odbywa się dany zjazd oraz datę w której zjazd się odbywa (SemesterID, Date).

```
CREATE TABLE [dbo].[Gatherings](
    [GatheringID] [int] NOT NULL,
    [Semester] [int] NOT NULL,
    [Date] [datetime] NOT NULL,
    CONSTRAINT [PK_Gatherings] PRIMARY KEY CLUSTERED
(
    [GatheringID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Gatherings] WITH CHECK ADD CONSTRAINT [FK_Gatherings_Offers] FOREIGN KEY([GatheringID])
REFERENCES [dbo].[Offers] ([OfferID])

ALTER TABLE [dbo].[Gatherings] CHECK CONSTRAINT [FK_Gatherings_Offers]

ALTER TABLE [dbo].[Gatherings] WITH CHECK ADD CONSTRAINT [FK_Gatherings_Semesters] FOREIGN KEY([Semester])
REFERENCES [dbo].[Semesters] ([SemesterID])

ALTER TABLE [dbo].[Gatherings] CHECK CONSTRAINT [FK_Gatherings_Semesters]
```

6. Semesters:

W tabeli znajdują się informacje o wszystkich semestrach na wszystkich kierunkach studiów, klucz główny to (SemesterID), zawiera też informacje o kierunku studiów na którym semestr się znajduje, numerze semestru (StudiesID, Semester_no).

```
CREATE TABLE [dbo].[Semesters](
    [SemesterID] [int] NOT NULL,
    [StudiesID] [int] NOT NULL,
    [Semester_no] [int] NOT NULL,
    CONSTRAINT [PK_Semesters] PRIMARY KEY CLUSTERED
(
    [SemesterID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Semesters] WITH CHECK ADD CONSTRAINT [FK_Semesters_Studies] FOREIGN KEY([StudiesID])
REFERENCES [dbo].[Studies] ([StudiesID])

ALTER TABLE [dbo].[Semesters] CHECK CONSTRAINT [FK_Semesters_Studies]

ALTER TABLE [dbo].[Semesters] WITH CHECK ADD CONSTRAINT [CHK_Semester_no_Positive] CHECK ((([Semester_no]>
(0))))

ALTER TABLE [dbo].[Semesters] CHECK CONSTRAINT [CHK_Semester_no_Positive]
```

7. Practices:

Tabela zawiera dane o praktykach, posiada klucz główny (PractiseID), semestrze na którym się odbywają i pracownikowi, który je prowadzi (SemesterID, EmployeeID), posiada informacje o miejscu, w którym praktyki się odbywają, dacie rozpoczęcia, ilości spotkań oraz potrzebnym wyposażeniu (Address, StartDate, MeetingsCount, RequiredEquipment).

```
CREATE TABLE [dbo].[Practices](
    [PractiseID] [int] NOT NULL,
    [SemesterID] [int] NOT NULL,
    [EmployeeID] [int] NOT NULL,
    [Address] [nvarchar](40) NOT NULL,
```

```

[StartDate] [datetime] NOT NULL,
[MeetingsCount] [int] NOT NULL,
[RequiredEquipment] [nchar](20) NULL,
CONSTRAINT [PK_Practices] PRIMARY KEY CLUSTERED
(
    [PractiseID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Practices] WITH CHECK ADD CONSTRAINT [FK_Practices_Semesters] FOREIGN KEY([SemesterID])
REFERENCES [dbo].[Semesters] ([SemesterID])

ALTER TABLE [dbo].[Practices] CHECK CONSTRAINT [FK_Practices_Semesters]

ALTER TABLE [dbo].[Practices] WITH CHECK ADD CONSTRAINT [FK_Practices_TeachingStaff] FOREIGN
KEY([EmployeeID])
REFERENCES [dbo].[TeachingStaff] ([TeacherID])

ALTER TABLE [dbo].[Practices] CHECK CONSTRAINT [FK_Practices_TeachingStaff]

ALTER TABLE [dbo].[Practices] WITH CHECK ADD CONSTRAINT [CHK_MeetingsCount_Positive] CHECK
([MeetingsCount]>(0))

ALTER TABLE [dbo].[Practices] CHECK CONSTRAINT [CHK_MeetingsCount_Positive]

```

8. PractiseAttendance:

Tabela posiada informacje o obecności studentów na praktykach, posiada klucz główny (PractiseAttendanceID), dla każdego studenta przypisuje czy był obecny na danych praktykach, na które jest zapisany (PractiseID, StudentID, Attendance).

```

CREATE TABLE [dbo].[PractiseAttendance](
    [PractiseAttendanceID] [int] NOT NULL,
    [PractiseID] [int] NOT NULL,
    [StudentID] [int] NOT NULL,
    [Attendance] [bit] NOT NULL,
    CONSTRAINT [PK_PractiseAttendance] PRIMARY KEY CLUSTERED
(
    [PractiseAttendanceID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[PractiseAttendance] WITH CHECK ADD CONSTRAINT [FK_PractiseAttendance_Lessons] FOREIGN
KEY([StudentID])
REFERENCES [dbo].[Lessons] ([LessonID])

ALTER TABLE [dbo].[PractiseAttendance] CHECK CONSTRAINT [FK_PractiseAttendance_Lessons]

ALTER TABLE [dbo].[PractiseAttendance] WITH CHECK ADD CONSTRAINT [FK_PractiseAttendance_Practices] FOREIGN
KEY([PractiseID])
REFERENCES [dbo].[Practices] ([PractiseID])

ALTER TABLE [dbo].[PractiseAttendance] CHECK CONSTRAINT [FK_PractiseAttendance_Practices]

ALTER TABLE [dbo].[PractiseAttendance] WITH CHECK ADD CONSTRAINT [FK_PractiseAttendance_Students] FOREIGN
KEY([StudentID])
REFERENCES [dbo].[Students] ([StudentID])

ALTER TABLE [dbo].[PractiseAttendance] CHECK CONSTRAINT [FK_PractiseAttendance_Students]

```

9. Subjects:

Tabela zawiera informacje o przedmiotach występujących w semestrach z kluczem głównym (SubjectID), przypisuje przedmiot do określonego semestru, posiada nazwę przedmiotu oraz jego opis (SemesterID, SubjectName, Description).

```

CREATE TABLE [dbo].[Subjects](
    [SubjectID] [int] NOT NULL,
    [SemesterID] [int] NOT NULL,
    [SubjectName] [nchar](50) NOT NULL,
    [Description] [nchar](70) NULL,
    CONSTRAINT [PK_Subjects] PRIMARY KEY CLUSTERED
(
    [SubjectID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Subjects] WITH CHECK ADD CONSTRAINT [FK_Subjects_Semesters] FOREIGN KEY([SemesterID])
REFERENCES [dbo].[Semesters] ([SemesterID])

ALTER TABLE [dbo].[Subjects] CHECK CONSTRAINT [FK_Subjects_Semesters]

ALTER TABLE [dbo].[Subjects] WITH CHECK ADD CONSTRAINT [CHK_Subjects_SubjectName_Length] CHECK
((len([SubjectName])>(5)))

ALTER TABLE [dbo].[Subjects] CHECK CONSTRAINT [CHK_Subjects_SubjectName_Length]

```

10. Lessons:

Tabela zawiera informacje o lekcjach zarówno tych na studiach, oraz tych możliwych do kupienia pojedynczo, posiada klucz główny (LessonID), przedmiot i zjazd do którego jest przypisana dana lekcja, oraz nauczyciela który ją prowadzi (SubjectID, GatheringID, TeacherID) zawiera temat, datę, typ, język prowadzenia, cenę i czas trwania (TopicID, Date, Type, Language, Price, Duration).

```

CREATE TABLE [dbo].[Lessons](
    [LessonID] [int] NOT NULL,
    [SubjectID] [int] NOT NULL,
    [GatheringID] [int] NOT NULL,
    [TeacherID] [int] NOT NULL,
    [TopicID] [int] NOT NULL,
    [Date] [datetime] NOT NULL,
    [Type] [nchar](10) NOT NULL,
    [Language] [nchar](10) NOT NULL,
    [Price] [int] NOT NULL,
    [Duration] [time](7) NULL,
    CONSTRAINT [PK_Lessons] PRIMARY KEY CLUSTERED
(
    [LessonID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Lessons] WITH CHECK ADD CONSTRAINT [FK_Lessons_Gatherings] FOREIGN KEY([GatheringID])
REFERENCES [dbo].[Gatherings] ([GatheringID])

ALTER TABLE [dbo].[Lessons] CHECK CONSTRAINT [FK_Lessons_Gatherings]

ALTER TABLE [dbo].[Lessons] WITH CHECK ADD CONSTRAINT [FK_Lessons_Subjects] FOREIGN KEY([SubjectID])
REFERENCES [dbo].[Subjects] ([SubjectID])

ALTER TABLE [dbo].[Lessons] CHECK CONSTRAINT [FK_Lessons_Subjects]

ALTER TABLE [dbo].[Lessons] WITH CHECK ADD CONSTRAINT [FK_Lessons_TeachingStaff] FOREIGN KEY([TeacherID])
REFERENCES [dbo].[TeachingStaff] ([TeacherID])

ALTER TABLE [dbo].[Lessons] CHECK CONSTRAINT [FK_Lessons_TeachingStaff]

ALTER TABLE [dbo].[Lessons] WITH CHECK ADD CONSTRAINT [FK_Lessons_Topics] FOREIGN KEY([TopicID])
REFERENCES [dbo].[Topics] ([TopicID])

ALTER TABLE [dbo].[Lessons] CHECK CONSTRAINT [FK_Lessons_Topics]

```

```
ALTER TABLE [dbo].[Lessons] WITH CHECK ADD CONSTRAINT [CHK_Lessons_Type] CHECK (([Type]='online' OR [Type]='hybrid' OR [Type]='stationary'))

ALTER TABLE [dbo].[Lessons] CHECK CONSTRAINT [CHK_Lessons_Type]
```

11. LessonsAttendance:

Tabela posiada informacje o obecności studentów na lekcjach, posiada klucz główny (LessonsAttendenseID), dla każdego studenta przypisuje czy był obecny na danej lekcji, na którą jest zapisany (LessonID, StudentID, Attendance).

```
CREATE TABLE [dbo].[LessonsAttendance](
    [LessonsAttendenseID] [int] NOT NULL,
    [LessonID] [int] NOT NULL,
    [StudentID] [int] NOT NULL,
    [Attendance] [bit] NOT NULL,
    CONSTRAINT [PK_LessonsAttendance] PRIMARY KEY CLUSTERED
(
    [LessonsAttendenseID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON, ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[LessonsAttendance] WITH CHECK ADD CONSTRAINT [FK_LessonsAttendance_Lessons] FOREIGN KEY([LessonID])
REFERENCES [dbo].[Lessons] ([LessonID])

ALTER TABLE [dbo].[LessonsAttendance] CHECK CONSTRAINT [FK_LessonsAttendance_Lessons]

ALTER TABLE [dbo].[LessonsAttendance] WITH CHECK ADD CONSTRAINT [FK_LessonsAttendance_Students] FOREIGN KEY([StudentID])
REFERENCES [dbo].[Students] ([StudentID])

ALTER TABLE [dbo].[LessonsAttendance] CHECK CONSTRAINT [FK_LessonsAttendance_Students]

ALTER TABLE [dbo].[LessonsAttendance] WITH CHECK ADD CONSTRAINT [FK_LessonsAttendance_Students1] FOREIGN KEY([StudentID])
REFERENCES [dbo].[Students] ([StudentID])

ALTER TABLE [dbo].[LessonsAttendance] CHECK CONSTRAINT [FK_LessonsAttendance_Students1]
```

12. Topics:

Tabela posiada dane o tematach kursów, bądź lekcji, posiada klucz główny (TopicID) oraz nazwę tematu i jego opis (TopicName, Description).

```
CREATE TABLE [dbo].[Topics](
    [TopicID] [int] NOT NULL,
    [TopicName] [nchar](50) NOT NULL,
    [Description] [nchar](70) NULL,
    CONSTRAINT [PK_Topics] PRIMARY KEY CLUSTERED
(
    [TopicID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON, ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Topics] WITH CHECK ADD CONSTRAINT [CHK_Topics_TopicName_Length] CHECK ((len([TopicName])>(5)))

ALTER TABLE [dbo].[Topics] CHECK CONSTRAINT [CHK_Topics_TopicName_Length]
```

13. Modules:

Tabela zawiera wszystkie moduły, znajdujące się kursach, posiada klucz główny (ModuleID), informacje o kursie, do którego moduł należy oraz jego tytuł i typie (CourseID, Title, Type), a także dacie zakończenia i rozpoczęcia oraz klasie, w której się odbywa (EndDate, StartDate, Classroom).

```
CREATE TABLE [dbo].[Modules](
    [ModuleID] [int] IDENTITY(1,1) NOT NULL,
    [CourseID] [int] NOT NULL,
    [Title] [nchar](50) NOT NULL,
    [Type] [nchar](10) NOT NULL,
    [EndDate] [datetime] NULL,
    [StartDate] [datetime] NULL,
    [Classroom] [nchar](10) NULL,
    CONSTRAINT [PK_Modules] PRIMARY KEY CLUSTERED
(
    [ModuleID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Modules] WITH CHECK ADD CONSTRAINT [FK_Modules_Courses] FOREIGN KEY([CourseID])
REFERENCES [dbo].[Courses] ([CourseID])

ALTER TABLE [dbo].[Modules] CHECK CONSTRAINT [FK_Modules_Courses]

ALTER TABLE [dbo].[Modules] WITH CHECK ADD CONSTRAINT [CHK_Modules_Date_Order] CHECK (([EndDate]>
[StartDate]))

ALTER TABLE [dbo].[Modules] CHECK CONSTRAINT [CHK_Modules_Date_Order]

ALTER TABLE [dbo].[Modules] WITH CHECK ADD CONSTRAINT [CHK_Modules_Title_Length] CHECK ((len([Title])>
(5)))

ALTER TABLE [dbo].[Modules] CHECK CONSTRAINT [CHK_Modules_Title_Length]

ALTER TABLE [dbo].[Modules] WITH CHECK ADD CONSTRAINT [CHK_Modules_Type_Values] CHECK (([Type]='online'
OR [Type]='hybrid' OR [Type]='stationary'))

ALTER TABLE [dbo].[Modules] CHECK CONSTRAINT [CHK_Modules_Type_Values]
```

14. Meetings:

Tabela zawiera dane o spotkaniach odbywających się w ramach konkretnego modułu, posiada klucz główny (MeetingID), przypisuje spotkanie do modułu, zawiera datę odbycia się i język prowadzenia oraz typ (ModuleID, Date, LanguageID, Type), miejsce odbywania się modułu, link do ewentualnego spotkania online, nauczyciela prowadzącego i tłumacza (Place, Link, TeacherID, TranslatorID).

```
CREATE TABLE [dbo].[Meetings](
    [MeetingID] [int] IDENTITY(1,1) NOT NULL,
    [ModuleID] [int] NOT NULL,
    [LanguageID] [int] NOT NULL,
    [Date] [date] NOT NULL,
    [Type] [nchar](10) NOT NULL,
    [Place] [nchar](10) NULL,
    [Link] [nchar](30) NULL,
    [TeacherID] [int] NOT NULL,
    [TranslatorID] [int] NULL,
    CONSTRAINT [PK_Meetings] PRIMARY KEY CLUSTERED
(
    [MeetingID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Meetings] WITH CHECK ADD CONSTRAINT [FK_Meetings_Modules] FOREIGN KEY([ModuleID])
REFERENCES [dbo].[Modules] ([ModuleID])
```

```

ALTER TABLE [dbo].[Meetings] CHECK CONSTRAINT [FK_Meetings_Modules]

ALTER TABLE [dbo].[Meetings] WITH CHECK ADD CONSTRAINT [FK_Meetings_TeachingStaff] FOREIGN
KEY([TeacherID])
REFERENCES [dbo].[TeachingStaff] ([TeacherID])

ALTER TABLE [dbo].[Meetings] CHECK CONSTRAINT [FK_Meetings_TeachingStaff]

ALTER TABLE [dbo].[Meetings] WITH CHECK ADD CONSTRAINT [FK_Meetings_Translators] FOREIGN
KEY([TranslatorID])
REFERENCES [dbo].[Translators] ([TranslatorID])

ALTER TABLE [dbo].[Meetings] CHECK CONSTRAINT [FK_Meetings_Translators]

ALTER TABLE [dbo].[Meetings] WITH CHECK ADD CONSTRAINT [CHK_Meetings_Type_Values] CHECK (([Type]='online'
OR [Type]='hybrid' OR [Type]='stationary'))

ALTER TABLE [dbo].[Meetings] CHECK CONSTRAINT [CHK_Meetings_Type_Values]

```

15. CourseAttendance:

Tabela posiada informacje o obecności studentów na spotkaniach w danym module kursu, posiada klucz główny (AttendanceID), dla każdego studenta przypisuje czy był obecny na danym spotkaniu, na które jest zapisany (MeetingID, StudentID, Attendance).

```

CREATE TABLE [dbo].[CourseAttendance](
    [AttendanceID] [int] NOT NULL,
    [MeetingID] [int] NOT NULL,
    [StudentID] [int] NOT NULL,
    [Attendance] [bit] NOT NULL,
    CONSTRAINT [PK_Attendance] PRIMARY KEY CLUSTERED
(
    [AttendanceID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[CourseAttendance] WITH CHECK ADD CONSTRAINT [FK_Attendance_Meetings] FOREIGN
KEY([MeetingID])
REFERENCES [dbo].[Meetings] ([MeetingID])

ALTER TABLE [dbo].[CourseAttendance] CHECK CONSTRAINT [FK_Attendance_Meetings]

ALTER TABLE [dbo].[CourseAttendance] WITH CHECK ADD CONSTRAINT [FK_Attendance_Students] FOREIGN
KEY([StudentID])
REFERENCES [dbo].[Students] ([StudentID])

ALTER TABLE [dbo].[CourseAttendance] CHECK CONSTRAINT [FK_Attendance_Students]

```

16. Orders:

Tabela przypisuje zamówienie do określonego studenta, posiada klucz główny (OrderID), studenta, do którego należy zamówienie, datę jego złożenia (StudentID, OrderDate).

```

CREATE TABLE [dbo].[Orders](
    [OrderID] [int] NOT NULL,
    [StudentID] [int] NOT NULL,
    [OrderDate] [datetime] NOT NULL,
    CONSTRAINT [PK_Cart] PRIMARY KEY CLUSTERED
(
    [OrderID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

```

```
ALTER TABLE [dbo].[Orders] WITH CHECK ADD CONSTRAINT [FK_Orders_Students] FOREIGN KEY([StudentID])
REFERENCES [dbo].[Students] ([StudentID])
```

```
ALTER TABLE [dbo].[Orders] CHECK CONSTRAINT [FK_Orders_Students]
```

17. Order_Details:

Tabela zawiera szczegółowe informacje o konkretnym zamówieniu, posiada klucz główny (OrderDetailsID), przypisuje zamówienie do złożonego zamówienia, który się w nim znajduje (OrderID, EnrollmentID), wartość produktu i zniżke(Value, Discount), zniżka jest wartoscia typu float z zakresu od 0 do 1.

```
CREATE TABLE [dbo].[Order_details](
    [OrderDetailsID] [int] NOT NULL,
    [OrderID] [int] NOT NULL,
    [OfferID] [int] NOT NULL,
    [Value] [money] NOT NULL,
    [Discount] [float] NOT NULL,
    CONSTRAINT [PK_Cart_details] PRIMARY KEY CLUSTERED
(
    [OrderDetailsID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Order_details] WITH CHECK ADD CONSTRAINT [FK_Cart_details_Cart] FOREIGN KEY([OrderID])
REFERENCES [dbo].[Orders] ([OrderID])

ALTER TABLE [dbo].[Order_details] CHECK CONSTRAINT [FK_Cart_details_Cart]

ALTER TABLE [dbo].[Order_details] WITH CHECK ADD CONSTRAINT [FK_Order_details_Offers] FOREIGN
KEY([OfferID])
REFERENCES [dbo].[Offers] ([OfferID])

ALTER TABLE [dbo].[Order_details] CHECK CONSTRAINT [FK_Order_details_Offers]

ALTER TABLE [dbo].[Order_details] WITH CHECK ADD CONSTRAINT [CHK_OrderDetails_Discount_Range] CHECK
(((Discount]>=(0) AND [Discount]<=(1)))

ALTER TABLE [dbo].[Order_details] CHECK CONSTRAINT [CHK_OrderDetails_Discount_Range]

ALTER TABLE [dbo].[Order_details] WITH CHECK ADD CONSTRAINT [CHK_OrderDetails_Value_NonNegative] CHECK
(((Value]>=(0)))

ALTER TABLE [dbo].[Order_details] CHECK CONSTRAINT [CHK_OrderDetails_Value_NonNegative]
```

18. Payments:

Tabela zawiera dane o płatnościach, posiada klucz główny (PaymentID), łączy płatność z określonym zamówieniem(OrderID), zawiera datę, wartość oraz status płatności (Date, Value, IsCancelled), status jest typu bit.

```
CREATE TABLE [dbo].[Payments](
    [PaymentID] [int] NOT NULL,
    [OrderID] [int] NOT NULL,
    [Date] [datetime] NOT NULL,
    [Value] [money] NOT NULL,
    [IsCancelled] [bit] NOT NULL,
    CONSTRAINT [PK_Payments] PRIMARY KEY CLUSTERED
(
    [PaymentID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Payments] WITH CHECK ADD CONSTRAINT [FK_Payments_Cart] FOREIGN KEY([OrderID])
```

```
REFERENCES [dbo].[Orders] ([OrderID])

ALTER TABLE [dbo].[Payments] CHECK CONSTRAINT [FK_Payments_Cart]

ALTER TABLE [dbo].[Payments] WITH CHECK ADD CONSTRAINT [CHK_Payments_Value_Positive] CHECK (([Value]>
(0)))

ALTER TABLE [dbo].[Payments] CHECK CONSTRAINT [CHK_Payments_Value_Positive]
```

19. Users:

Tabela zawiera wszystkich użytkowników z całej bazy danych, posiada klucz główny (UserID), do tego dla każdego użytkownika przypisuje login i hasło (Login, Password).

```
CREATE TABLE [dbo].[Users](
    [UserID] [int] NOT NULL,
    [Login] [nvarchar](20) NOT NULL,
    [Password] [nvarchar](20) NOT NULL,
    CONSTRAINT [PK_Users] PRIMARY KEY CLUSTERED
(
    [UserID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY],
    CONSTRAINT [UQ_Users_Login] UNIQUE NONCLUSTERED
(
    [Login] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Users] WITH CHECK ADD CONSTRAINT [CHK_Users_Login_Length] CHECK ((len([Login])>=(5)))

ALTER TABLE [dbo].[Users] CHECK CONSTRAINT [CHK_Users_Login_Length]

ALTER TABLE [dbo].[Users] WITH CHECK ADD CONSTRAINT [CHK_Users_Password_Digit] CHECK ((patindex('%[0-
9]%', [Password])>(0)))

ALTER TABLE [dbo].[Users] CHECK CONSTRAINT [CHK_Users_Password_Digit]

ALTER TABLE [dbo].[Users] WITH CHECK ADD CONSTRAINT [CHK_Users_Password_Length] CHECK ((len([Password])>=
(8)))

ALTER TABLE [dbo].[Users] CHECK CONSTRAINT [CHK_Users_Password_Length]
```

20. Students:

Tabela posiada wszystkich zarejestrowanych studentów, zawiera klucz główny (StudentID). Przechowuje informacje o studentach takie jak: imię, nazwisko, datę urodzenia (FirstName, LastName, BirthDate), z jakiego kraju pochodzi i dane adresowe (CountryID, Country, Region, City, ZipCode, Street), numer prywatnego i domowego telefonu (Phone, HomeNumber).

```
CREATE TABLE [dbo].[Students](
    [StudentID] [int] NOT NULL,
    [FirstName] [nvarchar](20) NOT NULL,
    [LastName] [nvarchar](20) NOT NULL,
    [BirthDate] [date] NOT NULL,
    [CountryID] [int] NOT NULL,
    [Region] [nvarchar](20) NOT NULL,
    [City] [nvarchar](20) NOT NULL,
    [ZipCode] [nvarchar](10) NOT NULL,
    [Street] [nvarchar](20) NOT NULL,
    [Phone] [nvarchar](20) NOT NULL,
    [HomeNumber] [nvarchar](15) NULL,
    CONSTRAINT [PK_Students] PRIMARY KEY CLUSTERED
(
```

```

        [StudentID] ASC
    )WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
    ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
    ) ON [PRIMARY]

ALTER TABLE [dbo].[Students] WITH CHECK ADD CONSTRAINT [FK_Students_Countries] FOREIGN KEY([CountryID])
REFERENCES [dbo].[Countries] ([CountryID])

ALTER TABLE [dbo].[Students] CHECK CONSTRAINT [FK_Students_Countries]

ALTER TABLE [dbo].[Students] WITH CHECK ADD CONSTRAINT [FK_Students_Users] FOREIGN KEY([StudentID])
REFERENCES [dbo].[Users] ([UserID])

ALTER TABLE [dbo].[Students] CHECK CONSTRAINT [FK_Students_Users]

ALTER TABLE [dbo].[Students] WITH CHECK ADD CONSTRAINT [CHK_Students_BirthDate] CHECK (([BirthDate]
<=getdate()))

ALTER TABLE [dbo].[Students] CHECK CONSTRAINT [CHK_Students_BirthDate]

```

21. Employees:

Tabela zawiera o wszystkich pracownikach, posiada klucz główny (EmployeeID) oraz informacje o pracowniku takie jak: pozycję, imię, nazwisko (PositionID, FirstName, LastName), datę zatrudnienia, pensję, email, numer telefonu oraz miasto (HireDate, Salary, Email, Phone, City), dodatkowo informację czy dany pracownik wciąż dla nas pracuje(IsActive).

```

CREATE TABLE [dbo].[Employees](
    [EmployeeID] [int] NOT NULL,
    [PositionID] [int] NOT NULL,
    [FirstName] [nvarchar](20) NOT NULL,
    [LastName] [nvarchar](20) NOT NULL,
    [HireDate] [date] NOT NULL,
    [Salary] [money] NOT NULL,
    [Email] [nvarchar](30) NOT NULL,
    [Phone] [nvarchar](15) NOT NULL,
    [City] [nvarchar](20) NOT NULL,
    [IsActive] [bit] NOT NULL,
    CONSTRAINT [PK_Employees] PRIMARY KEY CLUSTERED
(
    [EmployeeID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY],
    CONSTRAINT [UQ_Employees_Email] UNIQUE NONCLUSTERED
(
    [Email] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Employees] WITH CHECK ADD CONSTRAINT [FK_Employees_Position] FOREIGN KEY([PositionID])
REFERENCES [dbo].[Positions] ([PositionID])

ALTER TABLE [dbo].[Employees] CHECK CONSTRAINT [FK_Employees_Position]

ALTER TABLE [dbo].[Employees] WITH CHECK ADD CONSTRAINT [FK_Employees_Users] FOREIGN KEY([EmployeeID])
REFERENCES [dbo].[Users] ([UserID])

ALTER TABLE [dbo].[Employees] CHECK CONSTRAINT [FK_Employees_Users]

ALTER TABLE [dbo].[Employees] WITH CHECK ADD CONSTRAINT [CHK_Employees_Email_Format] CHECK
((charindex('@',[Email])>(0)))

ALTER TABLE [dbo].[Employees] CHECK CONSTRAINT [CHK_Employees_Email_Format]

ALTER TABLE [dbo].[Employees] WITH CHECK ADD CONSTRAINT [CHK_Employees_Salary] CHECK (([Salary]>(0)))

```

```
ALTER TABLE [dbo].[Employees] CHECK CONSTRAINT [CHK_Employees_Salary]
```

22. TeachingStaff:

Tabela zawiera informacje o kadrze nauczycielskiej, posiada klucz główny (TeacherID) oraz informacje o tym w jakim języku prowadzi zajęcia i jego stopień naukowy (LanguageID, Degree).

```
CREATE TABLE [dbo].[TeachingStaff](
    [TeacherID] [int] NOT NULL,
    [LanguageID] [int] NOT NULL,
    [Degree] [nchar](30) NOT NULL,
    CONSTRAINT [PK_TeachingStaff] PRIMARY KEY CLUSTERED
    (
        [TeacherID] ASC
    )
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[TeachingStaff] WITH CHECK ADD CONSTRAINT [FK_TeachingStaff_Employees] FOREIGN
KEY([TeacherID])
REFERENCES [dbo].[Employees] ([EmployeeID])

ALTER TABLE [dbo].[TeachingStaff] CHECK CONSTRAINT [FK_TeachingStaff_Employees]

ALTER TABLE [dbo].[TeachingStaff] WITH CHECK ADD CONSTRAINT [CK_TeachingStaff_Degree] CHECK
((([Degree]='professor' OR [Degree]='doctor' OR [Degree]='master' OR [Degree]='bachelor' OR [Degree]='none'))

ALTER TABLE [dbo].[TeachingStaff] CHECK CONSTRAINT [CK_TeachingStaff_Degree]
```

23. Translators:

Tabela zawiera informacje o tłumaczach, posiada klucz główny (TranslatorID) oraz informacje o języku z którego tłumaczy (LanguageID).

```
CREATE TABLE [dbo].[Translators](
    [TranslatorID] [int] NOT NULL,
    [LanguageID] [int] NOT NULL,
    CONSTRAINT [PK_Translators] PRIMARY KEY CLUSTERED
    (
        [TranslatorID] ASC
    )
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Translators] WITH CHECK ADD CONSTRAINT [FK_Translators_Employees] FOREIGN
KEY([TranslatorID])
REFERENCES [dbo].[Employees] ([EmployeeID])

ALTER TABLE [dbo].[Translators] CHECK CONSTRAINT [FK_Translators_Employees]

ALTER TABLE [dbo].[Translators] WITH CHECK ADD CONSTRAINT [FK_Translators_Languages] FOREIGN
KEY([LanguageID])
REFERENCES [dbo].[Languages] ([LanguageID])

ALTER TABLE [dbo].[Translators] CHECK CONSTRAINT [FK_Translators_Languages]
```

24. Administrators:

Tabela zawiera informacja o admnistratach zawiera klucz główny (AdminID) oraz data otrzymania uprawnień (Add_date).

```
CREATE TABLE [dbo].[Administrators](
    [AdminID] [int] NOT NULL,
    [Add_date] [datetime] NOT NULL,
```

```

CONSTRAINT [PK_Administrators_1] PRIMARY KEY CLUSTERED
(
    [AdminID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Administrators] WITH CHECK ADD CONSTRAINT [FK_Administrators_Employees] FOREIGN
KEY([AdminID])
REFERENCES [dbo].[Employees] ([EmployeeID])

ALTER TABLE [dbo].[Administrators] CHECK CONSTRAINT [FK_Administrators_Employees]

```

25. Countries:

Tabela zawiera informacje o krajach, posiada klucz główny (CountryID), nazwę kraju i język (CountryName, LanguageID).

```

CREATE TABLE [dbo].[Countries](
    [CountryID] [int] NOT NULL,
    [CountryName] [nchar](20) NOT NULL,
    [LanguageID] [int] NOT NULL,
    CONSTRAINT [PK_Countries2] PRIMARY KEY CLUSTERED
(
    [CountryID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Countries] WITH CHECK ADD CONSTRAINT [FK_Countries_Languages] FOREIGN KEY([LanguageID])
REFERENCES [dbo].[Languages] ([LanguageID])

ALTER TABLE [dbo].[Countries] CHECK CONSTRAINT [FK_Countries_Languages]

ALTER TABLE [dbo].[Countries] WITH CHECK ADD CONSTRAINT [CHK_Countries_CountryName_Length] CHECK
((len([CountryName])>=(3)))

ALTER TABLE [dbo].[Countries] CHECK CONSTRAINT [CHK_Countries_CountryName_Length]

```

26. Languages:

Tabela zawiera informacje o językach, posiada klucz główny (LanguageID) oraz nazwę języka (LanguageName).

```

CREATE TABLE [dbo].[Languages](
    [LanguageID] [int] NOT NULL,
    [LanguageName] [nchar](20) NOT NULL,
    CONSTRAINT [PK_Languages] PRIMARY KEY CLUSTERED
(
    [LanguageID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Languages] WITH CHECK ADD CONSTRAINT [CHK_Languages_LanguageName_Length] CHECK
((len([LanguageName])>=(3)))

ALTER TABLE [dbo].[Languages] CHECK CONSTRAINT [CHK_Languages_LanguageName_Length]

```

27. Position

Tabela zawiera informacje o stanowiskach, posiada klucz główny (PositionID) oraz nazwę stanowiska w postaci znakowej (PositionName).

```

CREATE TABLE [dbo].[Positions](
    [PositionID] [int] NOT NULL,

```

```
[PositionName] [nvarchar](15) NOT NULL,
CONSTRAINT [PK_Position] PRIMARY KEY CLUSTERED
(
    [PositionID] ASC
)WITH (PAD_INDEX = OFF, STATISTICS_NORECOMPUTE = OFF, IGNORE_DUP_KEY = OFF, ALLOW_ROW_LOCKS = ON,
ALLOW_PAGE_LOCKS = ON, OPTIMIZE_FOR_SEQUENTIAL_KEY = OFF) ON [PRIMARY]
) ON [PRIMARY]

ALTER TABLE [dbo].[Positions] WITH CHECK ADD CONSTRAINT [CHK_Positions_PositionName] CHECK
(((PositionName]='director' OR [PositionName]='administrator' OR [PositionName]='educator' OR
[PositionName]='menager'))

ALTER TABLE [dbo].[Positions] CHECK CONSTRAINT [CHK_Positions_PositionName]
```

Widoki:

1. AttendanceMeetingView

Widok przedstawiający obecność studentów na spotkaniach. Dla każdego kursu podaje sumę obecności, łączną liczbę spotkań oraz procentową obecność. Umożliwia analizę uczestnictwa studentów w ramach konkretnych kursów i modułów.

```
CREATE VIEW [dbo].[AttendanceMeetingView] AS
SELECT
    c.CourseID,
    c.CourseName,
    a.StudentID,
    s.FirstName,
    s.LastName,
    m.ModuleID,
    m.Title,
    SUM(CAST(a.Attendance AS INT)) AS Attendance,
    COUNT(CAST(a.Attendance AS INT) * 100) AS AllMeeting,
    AVG(CAST(a.Attendance AS INT) * 100) AS AttendancePercentage
FROM dbo.Courses AS c
    INNER JOIN dbo.Modules AS m ON m.CourseID = c.CourseID
    INNER JOIN dbo.Meetings AS me ON me.ModuleID = m.ModuleID
    INNER JOIN dbo.CourseAttendance AS a ON a.MeetingID = me.MeetingID INNER JOIN dbo.Students AS s ON
a.StudentID = s.StudentID
GROUP BY c.CourseID, c.CourseName, a.StudentID, s.FirstName, s.LastName, m.ModuleID, m.Title
```

	CourseID	CourseName	StudentID	FirstName	LastName	ModuleID	Title	Attendance	AllMeeting	Att...
1	13	Java Programming Course	20	Sakura	Tanaka	1	Module 1: Introduction to Java	1	1	100
2	13	Java Programming Course	21	Sophie	Dupont	1	Module 1: Introduction to Java	1	1	100
3	13	Java Programming Course	22	Marco	Rossi	1	Module 1: Introduction to Java	1	1	100
4	13	Java Programming Course	20	Sakura	Tanaka	2	Module 2: Data Types and Control Structures	0	1	0
5	13	Java Programming Course	21	Sophie	Dupont	2	Module 2: Data Types and Control Structures	1	1	100
6	13	Java Programming Course	22	Marco	Rossi	2	Module 2: Data Types and Control Structures	0	1	0
7	13	Java Programming Course	20	Sakura	Tanaka	3	Module 3: Object-Oriented Programming	1	1	100
8	13	Java Programming Course	21	Sophie	Dupont	3	Module 3: Object-Oriented Programming	1	1	100
9	13	Java Programming Course	22	Marco	Rossi	3	Module 3: Object-Oriented Programming	0	1	0

2. CoursesPass

Widok ten identyfikuje, czy studenci zaliczyli kurs na podstawie procentowej obecności w poszczególnych modułach. Dla każdego kursu podaje procentową obecność, łączną liczbę modułów oraz status "Pass" lub "Fail" w zależności od spełnienia warunku procentowej obecności (80% lub więcej). Umożliwia monitorowanie postępów studentów i ocenę ich osiągnięć w kontekście kursów.

```
CREATE VIEW [dbo].[CoursesPass] As
SELECT
    amv.CourseID,
    amv.CourseName,
    amv.StudentID,
    s.FirstName,
    s.LastName,
    COUNT(amv.ModuleID) * 100 / c.ModulesNo AS AttendancePercentage,
    c.ModulesNo,
    CASE WHEN ((COUNT(amv.ModuleID) * 100) / c.odulesNo) >= 80 THEN 'Pass' ELSE 'Fail' END AS Result
```



```
FROM dbo.AttendanceMeetingView AS amv
    INNER JOIN dbo.Courses AS c ON amv.CourseID = c.CourseID
    INNER JOIN dbo.Students AS s ON amv.StudentID = s.StudentID
WHERE amv.AttendancePercentage = 100
GROUP BY amv.CourseID, amv.CourseName, amv.StudentID, s.FirstName, s.LastName, c.ModulesNo
```

	CourseID	CourseName	StudentID	FirstName	LastName	AttendancePercentage	ModulesNo	Result
1	13	Java Programming Course	20	Sakura	Tanaka	50	4	Fail
2	13	Java Programming Course	21	Sophie	Dupont	75	4	Fail
3	13	Java Programming Course	22	Marco	Rossi	25	4	Fail

3. ConflictingTranslatorMeetings

Widok [ConflictingTranslatorMeetings] identyfikuje konfliktowe spotkania tłumaczy, prezentując informacje o dwóch spotkaniach o różnych identyfikatorach (ModuleID1 i ModuleID2), które mają tę samą datę (MeetingDate) oraz dotyczą tego samego tłumacza (PersonID). Dodatkowo, widok dostarcza imię (FirstName) i nazwisko (LastName) tłumacza za pomocą danych pobranych z tabeli pracowników (Employees).

```
CREATE VIEW [dbo].[ConflictingTranslatorMeetings] AS
SELECT
    M1.ModuleID AS ModuleID1,
    M2.ModuleID AS ModuleID2,
    M1.Date AS MeetingDate,
    M1.TranslatorID AS PersonID,
    T.FirstName,
    T.LastName
FROM
    Meetings M1
JOIN
    Meetings M2 ON M1.TranslatorID = M2.TranslatorID
JOIN
    Employees T ON M1.TranslatorID = T.EmployeeID
WHERE
    M1.MeetingID <> M2.MeetingID
    AND M1.Date = M2.Date
    AND M1.MeetingID < M2.MeetingID
```

	ModuleID1	ModuleID2	MeetingDate	PersonID	FirstName	LastName
1	6	7	2023-04-21	20	Olivia	Williams

4. CourseProfitView

Widok ten zawiera informacje o studentach zapisanych na kursy, prezentując identyfikator studenta (StudentID), imię (FirstName) i nazwisko (LastName) studenta, identyfikator kursu (CourseID), nazwę kursu (CourseName), opis kursu (CourseDescription), miejsce kursu (CoursePlace), oraz datę rozpoczęcia kursu (StartDate).

```
CREATE VIEW [dbo].[CourseProfitView] AS
SELECT
    c.CourseID,
    c.CourseName,
    ISNULL(
        SELECT COUNT(od.OrderDetailsID)
        FROM Order_details od
        WHERE od.OfferID = c.CourseID
    ), 0) AS Students_number,
    ISNULL(
        SELECT SUM(od.Value)
        FROM Order_details od
        WHERE od.OrderID IN (SELECT p.OrderID FROM Payments p)
        AND od.OfferID = c.CourseID
    ), 0) AS Profit,
    c.ModulesNo,
    FORMAT(C.StartDate, 'dd-MM-yyyy') AS StartDate
```

```
FROM
Courses c
```

	CourseID	CourseName	Students_number	Profit	ModulesNo	StartDate
1	13	Java Programming Course	2	399.98	4	10-01-2023
2	14	Data Science Course	1	399.99	3	15-02-2023
3	15	Digital Marketing Course	1	249.99	5	20-03-2023
4	16	Web Development Bootcamp	1	499.99	3	25-04-2023

5. EnrolledStudentsToCourses

Widok przedstawia informacje o studentach zapisanych na kursy. Zawiera identyfikator studenta (StudentID), imię (FirstName) i nazwisko (LastName) studenta, identyfikator kursu (CourseID), nazwę kursu (CourseName), opis kursu (CourseDescription), miejsce kursu (CoursePlace), oraz datę rozpoczęcia kursu (StartDate).

```
CREATE VIEW [dbo].[EnrolledStudentsToCourses] AS
SELECT
    S.StudentID,
    S.FirstName,
    S.LastName,
    O.OfferID AS CourseID,
    O.Name AS CourseName,
    O.Description AS CourseDescription,
    O.Place AS CoursePlace,
    FORMAT(C.StartDate, 'dd-MM-yyyy') AS StartDate
FROM dbo.Students AS S
    INNER JOIN dbo.Orders AS Ord ON S.StudentID = Ord.StudentID
    INNER JOIN dbo.Order_details AS Od ON Ord.OrderID = Od.OrderID
    INNER JOIN dbo.Offers AS O ON Od.OfferID = O.OfferID
    INNER JOIN dbo.Courses AS C ON O.OfferID = C.CourseID
WHERE (O.Type = 'Courses')
```

	StudentID	FirstName	LastName	CourseID	CourseName	CourseDescription	CoursePlace	StartDate
1	17	John	Smith	13	Java Programming Course	Comprehensive Java programming course	CityM, Boulevard 123	10-01-2023
2	20	Sakura	Tanaka	15	Digital Marketing Course	Strategies and techniques in digital marketing	CityO, Lane 789	20-03-2023
3	21	Sophie	Dupont	16	Web Development Bootcamp	Intensive web development training program	CityP, Square 012	25-04-2023
4	21	Sophie	Dupont	14	Data Science Fundamentals Course	Fundamental concepts of Data Science	CityN, Avenue 456	15-02-2023
5	33	Carlos	Fernandez	13	Java Programming Course	Comprehensive Java programming course	CityM, Boulevard 123	10-01-2023

6. EnrolledStudentsToGatherings

Widok [EnrolledStudentsToGatherings] dostarcza informacje o studentach zapisanych na spotkania. Prezentuje identyfikator studenta (StudentID), imię (FirstName) i nazwisko (LastName) studenta, identyfikator spotkania (GatheringID), nazwę spotkania (GatheringName), opis spotkania (GatheringDescription), miejsce spotkania (GatheringPlace), oraz datę spotkania (Date).

```
CREATE VIEW [dbo].[EnrolledStudentsToGatherings] AS
SELECT
    S.StudentID,
    S.FirstName,
    S.LastName,
    O.OfferID AS GatheringID,
    O.Name AS GatheringName,
    O.Description AS GatheringDescription,
    O.Place AS GatheringPlace,
    FORMAT(G.Date, 'dd-MM-yyyy') AS Date
FROM
    dbo.Students S
    INNER JOIN dbo.Orders Ord ON S.StudentID = Ord.StudentID
    INNER JOIN dbo.Order_details Od ON Ord.OrderID = Od.OrderID
    INNER JOIN dbo.Offers O ON Od.OfferID = O.OfferID
    INNER JOIN dbo.Gatherings G ON O.OfferID = G.GatheringID
WHERE
    O.Type = 'Gathering';
```

	StudentID	FirstName	LastName	GatheringID	GatheringName	GatheringDescription	GatheringPlace	Date
1	22	Marco	Rossi	19	Science Fiction Fans Meetup	Discussion and presentations on sci-fi	CityS, Lane 789	25-05-2023
2	23	Mei	Wong	17	Tech Enthusiasts Gathering	Various tech-related sessions	CityQ, Street 123	15-03-2023
3	19	James	Brown	11	English for Business Communication	Improving English communication skills	CityK, Lane 789	28-05-2023
4	22	Marco	Rossi	9	Introduction to Programming	Basic programming concepts	CityI, Street 123	18-03-2023
5	23	Mei	Wong	12	Introduction to Machine Learning	Basic concepts of machine learning	CityL, Square 012	01-07-2023
6	17	John	Smith	20	Art and Creativity Symposium	Artistic workshops and discussions	CityT, Square 012	30-06-2023
7	30	Juan	Lopez	18	Health and Wellness Expo	Wellness sessions and workshops	CityR, Avenue 456	20-04-2023
8	21	Sophie	Dupont	10	Advanced Data Structures	In-depth study of data structures	CityJ, Avenue 456	21-04-2023
9	21	Sophie	Dupont	11	English for Business Communication	Improving English communication skills	CityK, Lane 789	28-05-2023
10	29	Sophie	Müller	19	Science Fiction Fans Meetup	Discussion and presentations on sci-fi	CityS, Lane 789	25-05-2023

7. EnrolledStudentsToStudies

Widok dostarcza informacje o studentach zapisanych na studia. Prezentuje identyfikator studenta (StudentID), imię (FirstName) i nazwisko (LastName) studenta, identyfikator studiów (StudiesID), nazwę oferty studiów (OfferName), opis oferty studiów (OfferDescription), miejsce oferty studiów (OfferPlace), oraz datę rozpoczęcia studiów (StartDate).

```
CREATE VIEW [dbo].[EnrolledStudentsToStudies] AS
SELECT
    S.StudentID,
    S.FirstName,
    S.LastName,
    St.StudiesID,
    O.Name AS OfferName,
    O.Description AS OfferDescription,
    O.Place AS OfferPlace,
    MIN(G.[Date]) AS StartDate
FROM
    dbo.Students S
    LEFT JOIN dbo.Orders Ord ON S.StudentID = Ord.StudentID
    LEFT JOIN dbo.Order_details Od ON Ord.OrderID = Od.OrderID
    LEFT JOIN dbo.Offers O ON Od.OfferID = O.OfferID
    LEFT JOIN dbo.Studies St ON O.OfferID = St.StudiesID
    LEFT JOIN dbo.Semesters Sem ON St.StudiesID = Sem.StudiesID
    LEFT JOIN dbo.Gatherings G ON Sem.SemesterID = G.SemesterID
WHERE
    O.Type = 'Studies'
GROUP BY S.StudentID, S.FirstName, S.LastName, St.StudiesID, O.OfferID, O.Name, O.Description, O.Place;
```

Studen_	FirstName	LastName	StudiesID	OfferName	OfferDescription	OfferPlace	StartDate
1	19	James	5	Computer Science Bachelor Program	Bachelor studies in Computer Science	CityE, Boulevard 123	2023-03-15 00:00:00.000
2	20	Sakura	6	Data Analytics Master Program	Master studies in Data Analytics	CityF, Square 456	NULL
3	20	Sakura	7	Business Administration PhD Program	PhD studies in Business Administration	CityG, Avenue 789	NULL
4	21	Sophie	8	Artificial Intelligence Certificate Program	Certificate program in AI	CityH, Lane 012	NULL
5	22	Marco	5	Computer Science Bachelor Program	Bachelor studies in Computer Science	CityE, Boulevard 123	2023-03-15 00:00:00.000
6	28	Hiroshi	5	Computer Science Bachelor Program	Bachelor studies in Computer Science	CityE, Boulevard 123	2023-03-15 00:00:00.000

8. EnrolledStudentsToWebinars

Widok dostarcza informacje o studentach zapisanych na webinar. Prezentuje identyfikator studenta (StudentID), imię (FirstName) i nazwisko (LastName) studenta, identyfikator webinaru (WebinarID), nazwę spotkania (GatheringName), opis spotkania (GatheringDescription), miejsce spotkania (GatheringPlace), oraz datę webinaru (Date). Zastosowanie tego widoku ułatwia monitorowanie uczestnictwa studentów w webinarach, umożliwiając identyfikację zapisanych osób oraz szczegółowe informacje o danym wydarzeniu edukacyjnym.

```
CREATE VIEW [dbo].[EnrolledStudentsToWebinars] AS
SELECT
    S.StudentID,
    S.FirstName,
    S.LastName,
    O.OfferID AS WebinarID,
    O.Name AS GatheringName,
    O.Description AS GatheringDescription,
    O.Place AS GatheringPlace,
    W.[Date]
FROM
    dbo.Students S
    INNER JOIN dbo.Orders Ord ON S.StudentID = Ord.StudentID
```

```
INNER JOIN dbo.Order_details Od ON Ord.OrderID = Od.OrderID
INNER JOIN dbo.Offers O ON Od.OfferID = O.OfferID
INNER JOIN dbo.Webinar W ON O.OfferID = W.WebinarID
WHERE
    O.Type = 'Webinar';
```

	StudentID	FirstName	LastName	WebinarID	GatheringName	GatheringDescription	GatheringPlace	Date
1	17	John	Smith	1	Webinar on Data Science Basics	Introduction to Data Science	CityA, Street 123	2023-01-15 00:00:00.000
2	18	Maria	Rodriguez	2	Webinar: Mastering Python	Explore Python programming	CityB, Avenue 456	2023-02-20 00:00:00.000
3	18	Maria	Rodriguez	3	Webinar: Machine Learning Fundamentals	Understanding basics of Machine Learning	CityC, Lane 789	2023-03-25 00:00:00.000
4	29	Sophie	Müller	4	Webinar: Cybersecurity Essentials	Essential tips for Cybersecurity	CityD, Square 012	2023-04-30 00:00:00.000
5	23	Mei	Wong	1	Webinar on Data Science Basics	Introduction to Data Science	CityA, Street 123	2023-01-15 00:00:00.000
6	30	Juan	Lopez	2	Webinar: Mastering Python	Explore Python programming	CityB, Avenue 456	2023-02-20 00:00:00.000

9. ListOfDebtors

Widok [ListOfDebtors] przedstawia szczegółowe informacje o osobach, które wzięły udział w różnych wydarzeniach, ale jeszcze nie uregulowały swoich płatności, pozostając w stanie zadłużenia. Zidentyfikowani dłużnicy są grupowani według identyfikatora studenta (StudentID) oraz oferty (OfferID), a informacje obejmują imię i nazwisko studenta (Student_name), identyfikator oferty (OfferID), nazwę oferty (Name) oraz kwotę zadłużenia (Debt). Widok uwzględnia różne rodzaje wydarzeń, takie jak spotkania (Gatherings), kursy (Courses), webinary (Webinar) oraz studia (Studies).

```
WITH t AS (
    SELECT
        o.OrderID,
        CASE
            WHEN EXISTS (SELECT 1 FROM Payments as p WHERE o.OrderID = p.OrderID AND p.CancelDate IS NULL)
        THEN 1
            ELSE 0
        END AS OrderStatus
    FROM
        Orders as o
)

SELECT
    s.StudentID,
    TRIM(s.FirstName) + ' ' + TRIM(s.LastName) AS Student_name,
    o.OfferID,
    o.Name,
    FORMAT((d.Value*(1-d.Discount)-P.Value), '0.00') AS Debt
FROM
    Gatherings as g
INNER JOIN
    Offers as o ON g.GatheringID = o.OfferID
INNER JOIN
    Order_details as d ON d.OfferID = o.OfferID
INNER JOIN
    t ON t.OrderID = d.OrderID
INNER JOIN
    Orders as r ON r.OrderID = d.OrderID
INNER JOIN
    Students as s ON s.StudentID = r.StudentID
INNER JOIN
    Payments AS P ON r.OrderID = P.OrderID
WHERE
    t.OrderStatus = 0 AND g.Date < GETDATE()

GROUP BY
    s.StudentID, s.FirstName, s.LastName, o.OfferID, o.Name, P.Value, d.Value, d.Discount

UNION

SELECT
    s.StudentID,
    TRIM(s.FirstName) + ' ' + TRIM(s.LastName) AS Student_name,
    o.OfferID,
    o.Name,
    FORMAT((d.Value*(1-d.Discount)-P.Value), '0.00') AS Debt
```

```

FROM
    Courses as c
INNER JOIN
    Offers as o ON c.CourseID = o.OfferID
INNER JOIN
    Order_details as d ON d.OfferID = o.OfferID
INNER JOIN
    t ON t.OrderID = d.OrderID
INNER JOIN
    Orders as r ON r.OrderID = d.OrderID
INNER JOIN
    Students as s ON s.StudentID = r.StudentID
INNER JOIN
    Payments AS P ON r.OrderID = P.OrderID
WHERE
    t.OrderStatus = 0 AND c.StartDate < GETDATE()
GROUP BY
    s.StudentID, s.FirstName, s.LastName, o.OfferID, o.Name, P.Value, d.Value, d.Discount

UNION

SELECT
    s.StudentID,
    TRIM(s.FirstName) + ' ' + TRIM(s.LastName) AS Student_name,
    o.OfferID,
    o.Name,
    FORMAT((d.Value*(1-d.Discount)-P.Value), '0.00') AS Debt
FROM
    Webinar as w
INNER JOIN
    Offers as o ON w.WebinarID = o.OfferID
INNER JOIN
    Order_details as d ON d.OfferID = o.OfferID
INNER JOIN
    t ON t.OrderID = d.OrderID
INNER JOIN
    Orders as r ON r.OrderID = d.OrderID
INNER JOIN
    Students as s ON s.StudentID = r.StudentID
INNER JOIN
    Payments AS P ON r.OrderID = P.OrderID
WHERE
    t.OrderStatus = 0 AND w.Date < GETDATE()
GROUP BY
    s.StudentID, s.FirstName, s.LastName, o.OfferID, o.Name, P.Value, d.Value, d.Discount

UNION

SELECT
    s.StudentID,
    TRIM(s.FirstName) + ' ' + TRIM(s.LastName) AS Student_name,
    o.OfferID,
    o.Name,
    FORMAT((d.Value*(1-d.Discount)-P.Value), '0.00') AS Debt
FROM
    Studies as sd
INNER JOIN
    Offers as o ON sd.StudiesID = o.OfferID
INNER JOIN
    Semesters as se ON se.StudiesID=sd.StudiesID
INNER JOIN
    Gatherings as g ON g.SemesterID = se.SemesterID
INNER JOIN
    Order_details as d ON d.OfferID = o.OfferID
INNER JOIN
    t ON t.OrderID = d.OrderID
INNER JOIN
    Orders as r ON r.OrderID = d.OrderID
INNER JOIN

```

```
Students as s ON s.StudentID = r.StudentID
INNER JOIN
Payments AS P ON r.OrderID = P.OrderID
GROUP BY
s.StudentID, s.FirstName, s.LastName, o.OfferID, o.Name, P.Value, t.OrderStatus, d.Value, d.Discount
HAVING min(g.Date) < GETDATE() AND t.OrderStatus = 0;
```

	StudentID	Student_name	OfferID	Name	Debt
1	28	Hiroshi Yamamoto	5	Computer Science Bachelor Program	3955.00

10. OrdersPaymentsView

Widok [OrdersPaymentsView] dostarcza kompleksowych informacji na temat płatności związanych z zamówieniami. Prezentuje identyfikator zamówienia (OrderID), łączną wartość zamówienia (Value), opłaconą kwotę (Paid), kwotę do zapłaty (ToPay), datę anulowania płatności (CancelDate), datę zamówienia (OrderDate), identyfikator studenta (StudentID), oraz imię i nazwisko osoby składającej zamówienie (Orderer_name).

```
CREATE VIEW [dbo].[OrdersPaymentsView] AS
SELECT
    Ord.OrderID,
    FORMAT(SUM(OD.Value*(1-OD.Discount)), '0.00') AS Value,
    FORMAT(P.Value, '0.00') AS Paid,
    FORMAT(
        IIF(P.CancelDate IS NOT NULL, 0.00, SUM(OD.Value*(1-OD.Discount))-P.Value), '0.00'
    ) AS ToPay,
    P.CancelDate,
    FORMAT(OrderDate, 'dd-MM-yyyy') AS OrderDate,
    ord.StudentID,
    TRIM(FirstName) + ' ' + TRIM(LastName) AS Orderer_name
FROM
    Orders AS Ord
INNER JOIN
    Order_details AS OD ON Ord.OrderID = OD.OrderID
INNER JOIN
    Payments AS P ON Ord.OrderID = P.OrderID
INNER JOIN
    Students AS s ON s.StudentID = ord.StudentID
GROUP BY
    Ord.OrderID, P.CancelDate, P.Value, OrderDate, ord.StudentID, FirstName, LastName
```

	OrderID	Value	Paid	ToPay	CancelDate	OrderDate	StudentID	Orderer_name
1	1	350.72	350.72	0.00	NULL	01-12-2022	17	John Smith
2	2	75.98	75.98	0.00	NULL	02-12-2022	18	Maria Rodriguez
3	3	4283.99	4283.99	0.00	NULL	03-12-2022	19	James Brown
4	4	16174.99	16174.99	0.00	NULL	04-12-2022	20	Sakura Tanaka
5	5	2331.98	2331.98	0.00	NULL	05-12-2022	21	Sophie Dupont
6	6	5056.98	5056.98	0.00	NULL	06-12-2022	22	Marco Rossi
7	7	102.47	102.47	0.00	NULL	06-11-2022	23	Mei Wong
8	8	331.98	331.98	0.00	NULL	07-11-2022	21	Sophie Dupont
9	9	99.99	12.00	87.99	NULL	09-07-2022	33	Carlos Fernandez
10	9	99.99	12.00	0.00	2022-07-16	09-07-2022	33	Carlos Fernandez
11	10	4000.00	45.00	0.00	2022-11-13	07-11-2022	28	Hiroshi Yamamoto
12	11	65.58	65.58	0.00	NULL	05-12-2022	30	Juan Lopez
13	12	48.48	48.48	0.00	NULL	07-01-2022	29	Sophie Müller

11. ProfitInfo

Widok analizuje zamówienia dla ofert, grupując je według identyfikatora oferty (OfferID), typu oferty (Type), daty zamówienia (OrderDate), identyfikatora studenta (StudentID), oraz imienia i nazwiska zamawiającego (Orderer_name). Dla każdej grupy prezentuje liczbę wszystkich zamówień (AllOrders) oraz całkowity zysk (Profit). Dodatkowo pokazuje datę dokonania zamówienia i dane osoby je składającej.

```
CREATE VIEW [dbo].[ProfitInfo] AS
SELECT
    Order_details.OfferID,
    Type,
    COUNT(Order_details.OrderID) AS AllOrders,
    SUM(Value) AS Profit,
    FORMAT(OrderDate, 'dd-MM-yyyy') AS OrderDate,
    Orders.StudentID,
    TRIM(FirstName) + ' ' + TRIM(LastName) AS Orderer_name
FROM dbo.Order_details
JOIN Offers ON Offers.OfferID = Order_details.OfferID
JOIN Orders ON Orders.OrderID = Order_details.OrderID
JOIN Students ON Students.StudentID = Orders.StudentID
GROUP BY Order_details.OfferID, Type, OrderDate, Orders.StudentID, FirstName, LastName
```

	OfferID	Type	AllOrders	Profit	OrderDate	StudentID	Orderer_name
1	1	Webinar	1	29.99	06-11-2022	23	Mei Wong
2	1	Webinar	1	29.99	01-12-2022	17	John Smith
3	2	Webinar	1	39.99	02-12-2022	18	Maria Rodriguez
4	2	Webinar	1	39.99	05-12-2022	30	Juan Lopez
5	3	Webinar	1	49.99	02-12-2022	18	Maria Rodriguez
6	4	Webinar	1	34.99	07-01-2022	29	Sophie Müller
7	5	Studies	1	5000.00	07-11-2022	28	Hiroshi Yamamoto
8	5	Studies	1	5000.00	03-12-2022	19	James Brown
9	5	Studies	1	5000.00	06-12-2022	22	Marco Rossi
10	6	Studies	1	7000.00	04-12-2022	20	Sakura Tanaka
11	7	Studies	1	10000.00	04-12-2022	20	Sakura Tanaka
12	8	Studies	1	2500.00	05-12-2022	21	Sophie Dupont
13	9	Gathering	1	49.99	06-12-2022	22	Marco Rossi
14	10	Gathering	1	59.99	05-12-2022	21	Sophie Dupont
15	11	Gathering	1	39.99	07-11-2022	21	Sophie Dupont
16	11	Gathering	1	39.99	03-12-2022	19	James Brown
17	12	Gathering	1	69.99	06-11-2022	23	Mei Wong
18	13	Courses	1	99.99	09-07-2022	33	Carlos Fernandez
19	13	Courses	1	299.99	01-12-2022	17	John Smith
20	14	Courses	1	399.99	07-11-2022	21	Sophie Dupont
21	15	Courses	1	249.99	04-12-2022	20	Sakura Tanaka
22	16	Courses	1	499.99	05-12-2022	21	Sophie Dupont
23	17	Gathering	1	19.99	06-11-2022	23	Mei Wong
24	18	Gathering	1	29.99	05-12-2022	30	Juan Lopez
25	19	Gathering	1	14.99	07-01-2022	29	Sophie Müller
26	19	Gathering	1	14.99	06-12-2022	22	Marco Rossi
27	20	Gathering	1	24.99	01-12-2022	17	John Smith

12. StudentPracticesCompletionStatus

Widok analizuje podsumowanie praktyk studenckich, korzystając z tymczasowej tabeli (PracticeCounts), aby określić liczbę wszystkich praktyk dla każdego studenta. Główne zapytanie prezentuje identyfikator studenta, imię, nazwisko, liczbę ukończonych praktyk, łączną liczbę praktyk, wynik (Pass/Fail) w zależności od tego, czy student ukończył wszystkie praktyki, oraz średnią frekwencję.

```
CREATE VIEW [dbo].[StudentPracticesCompletionStatus] AS
WITH PracticeCounts AS (
    SELECT
        in_t.StudentID,
        COUNT(in_t.PractiseID) AS TotalPracticesCount
    FROM
        StudentPracticesSummaryByPractiseID in_t
    GROUP BY
        in_t.StudentID
)

SELECT
    out_t.StudentID,
    out_t.FirstName,
    out_t.LastName,
    COUNT(out_t.PractiseID) AS CompletedPracticesCount,
    PracticeCounts.TotalPracticesCount,
    CASE
        WHEN COUNT(out_t.PractiseID) = PracticeCounts.TotalPracticesCount
            THEN 'Pass'
        ELSE 'Fail'
    END AS Result,
    FORMAT(SUM(CAST(out_t.Attendance AS FLOAT)) / PracticeCounts.TotalPracticesCount, '0.00') AS Attendance
FROM
    StudentPracticesSummaryByPractiseID out_t
JOIN
    PracticeCounts ON out_t.StudentID = PracticeCounts.StudentID
WHERE
    CompletedAllPractices = 'True'
GROUP BY
    out_t.StudentID, out_t.FirstName, out_t.LastName, PracticeCounts.TotalPracticesCount;
```

	StudentID	FirstName	LastName	CompletedPracticesCount	TotalPracticesCount	Result	Attendance
1	19	James	Brown	4	4	Pass	1.00
2	22	Marco	Rossi	1	4	Fail	0.25
3	28	Hiroshi	Yamamoto	3	4	Fail	0.75

13. StudentPracticesSummaryByPractiseID

Zapytanie to generuje raport na temat uczestnictwa studentów w praktykach zawodowych. Dla każdego studenta i praktyki, prezentuje identyfikator studenta, imię, nazwisko, identyfikator praktyki, informację czy student ukończył wszystkie zajęcia praktyczne ('True' lub 'False'), oraz procentowe obliczenie frekwencji studenta w praktyce.

```
CREATE VIEW [dbo].[StudentPracticesSummaryByPractiseID] AS
SELECT
    PA.StudentID,
    S.FirstName,
    S.LastName,
    PA.PractiseID,
    CASE WHEN SUM(CAST(PA.Attendance AS INT)) = COUNT(PA.Attendance)
        THEN 'True'
        ELSE 'False'
    END AS CompletedAllPractices,
    FORMAT(SUM(CAST(PA.Attendance AS FLOAT)) / COUNT(PA.Attendance), '0.00') AS Attendance
FROM
    PractiseAttendance PA
JOIN
    Students S ON PA.StudentID = S.StudentID
GROUP BY
    PA.StudentID, PA.PractiseID, S.FirstName, S.LastName;
```


	StudentID	FirstName	LastName	PractiseID	CompletedAllPractices	Attendance
1	19	James	Brown	1	True	1.00
2	22	Marco	Rossi	1	True	1.00
3	28	Hiroshi	Yamamoto	1	False	0.40
4	19	James	Brown	2	True	1.00
5	22	Marco	Rossi	2	False	0.00
6	28	Hiroshi	Yamamoto	2	True	1.00
7	19	James	Brown	3	True	1.00
8	22	Marco	Rossi	3	False	0.00
9	28	Hiroshi	Yamamoto	3	True	1.00
10	19	James	Brown	4	True	1.00
11	22	Marco	Rossi	4	False	0.00
12	28	Hiroshi	Yamamoto	4	True	1.00

14. StudentsEnrolmentInfo

Widok przedstawia informacje o zapisach studentów, uwzględniając identyfikator studenta, imię, nazwisko, liczbę unikalnych wydarzeń, do których się zapisali, oraz numer telefonu.

```
CREATE VIEW [dbo].[StudentsEnrolmentInfo] AS
SELECT
    dbo.Students.StudentID,
    dbo.Students.FirstName,
    dbo.Students.LastName,
    COUNT(DISTINCT dbo.Order_details.OfferID) AS Num_of_events,
    dbo.Students.Phone
FROM
    dbo.Users
INNER JOIN
    dbo.Students ON dbo.Users.UserID = dbo.Students.StudentID
INNER JOIN
    dbo.Orders ON dbo.Orders.StudentID = dbo.Students.StudentID
INNER JOIN
    dbo.Order_details ON dbo.Order_details.OrderID = dbo.Orders.OrderID
GROUP BY
    dbo.Students.StudentID,
    dbo.Students.FirstName,
    dbo.Students.LastName,
    dbo.Students.Phone
```

	StudentID	FirstName	LastName	Num_of_events	Phone
1	17	John	Smith	3	+1 555-123-4567
2	18	Maria	Rodriguez	2	+52 55-7890-1234
3	19	James	Brown	2	+1 416-555-7890
4	20	Sakura	Tanaka	3	+81 90-1234-5678
5	21	Sophie	Dupont	5	+33 1 23 45 67 89
6	22	Marco	Rossi	3	+39 06 1234 5678
7	23	Mei	Wong	3	+86 10 1234 5678
8	28	Hiroshi	Yamamoto	1	+81 90-9876-5432
9	29	Sophie	Müller	2	+49 89 1234 5678
10	30	Juan	Lopez	2	+34 91 987 65 43
11	33	Carlos	Fernandez	1	+34 93 987 65 43

15. StudiesProfitView

Widok prezentuje kompleksowe informacje o dochodach i zapisanych studentach dla różnych studiów. Obejmuje identyfikator studium, nazwę, liczbę studentów, całkowity dochód, ilość semestrów oraz imię i nazwisko menedżera studium.

```
SELECT
    s.StudiesID,
    s.Name,
    ISNULL((
        SELECT COUNT(od.OrderDetailsID)
        FROM Order_details od
        WHERE od.OfferID = s.StudiesID
    ), 0) AS Students_number,
    ISNULL((
        SELECT SUM(od.Value)
        FROM Order_details od
        WHERE od.OrderID IN (SELECT p.OrderID FROM Payments p)
        AND od.OfferID = s.StudiesID
    ), 0) AS Profit,
    ISNULL((
        SELECT COUNT(sem.SemesterID)
        FROM Semesters sem
        WHERE sem.StudiesID = s.StudiesID
    ), 0) AS Semesters_number,
    TRIM(e.FirstName) + ' ' + TRIM(e.LastName) AS Menager_name
FROM
    Studies s
LEFT JOIN TeachingStaff t ON t.TeacherID = s.MenagerID
LEFT JOIN Employees e ON e.EmployeeID = t.TeacherID;
```

	StudiesID	Name	Students_number	Profit	Semesters_number	Menager_name
1	5	Computer Science	3	15000.00	4	Michael Taylor
2	6	Data Analytics	1	7000.00	0	Emma Miller
3	7	Business Administration (PhD)	1	10000.00	0	Christopher Anderson
4	8	Artificial Intelligence Certificate	1	2500.00	0	Olivia Moore

16. WebinarProfitView

Widok prezentuje szczegółowe informacje o poszczególnych webinarach, uwzględniając identyfikator, nazwę, liczbę uczestników, całkowity dochód oraz datę wydarzenia. Dodatkowo, dostarcza imię i nazwisko prowadzącego.

```
CREATE VIEW [dbo].[WebinarProfitView] AS
SELECT
    w.WebinarID,
    w.WebinarName,
    ISNULL((
        SELECT COUNT(od.OrderDetailsID)
        FROM Order_details od
        WHERE od.OfferID = w.WebinarID
    ), 0) AS Students_number,
    ISNULL((
        SELECT SUM(od.Value)
        FROM Order_details od
        WHERE od.OrderID IN (SELECT p.OrderID FROM Payments p)
        AND od.OfferID = w.WebinarID
    ), 0) AS Profit,
    FORMAT(w.Date, 'dd-MM-yyyy') AS Event_date,
    TRIM(e.FirstName) + ' ' + TRIM(e.LastName) AS Teacher_name
FROM
    Webinar w
JOIN TeachingStaff t ON t.TeacherID = w.TeacherID
JOIN Employees e ON e.EmployeeID = t.TeacherID
```

	WebinarID	WebinarName	Students_number	Profit	Event_date	Teacher_name
1	1	Webinar on Data Science Basics	2	59.98	15-01-2023	Alice Johnson
2	2	Mastering Python	2	79.98	20-02-2023	Alice Johnson
3	3	Machine Learning Fundamentals	1	49.99	25-03-2023	David Brown
4	4	Cybersecurity Essentials	1	34.99	30-04-2023	Sophia Williams

Procedury:

1. AddLessonAttendance

Procedura ta pozwala na dodanie konkretnemu użytkownikowi obecności na danej lekcji, przed wykonaniem polecenia dodawania sprawdza także czy lekcja o podanym ID istnieje oraz czy uczeń o podanym ID istnieje.

```
CREATE PROCEDURE [dbo].[AddLessonAttendance]
    @LessonID INT,
    @StudentID INT,
    @IsPresent BIT
AS
BEGIN
    IF EXISTS (SELECT 1 FROM Lessons WHERE LessonID = @LessonID) AND EXISTS (SELECT 1 FROM Students WHERE StudentID = @StudentID)
    BEGIN
        INSERT INTO LessonsAttendance(LessonID, StudentID, Attendance)
        VALUES (@LessonID, @StudentID, @IsPresent);
    END
END;
```

2. AddMeetingAttendance

Procedura ta pozwala na dodanie konkretnemu użytkownikowi obecności na danym spotkaniu, przed wykonaniem polecenia dodawania sprawdza także czy spotkanie o podanym ID istnieje oraz czy uczeń o podanym ID istnieje.

```
CREATE PROCEDURE [dbo].[AddMeetingAttendance]
    @MeetingID INT,
    @StudentID INT,
    @IsPresent BIT
AS
BEGIN
    IF EXISTS (SELECT 1 FROM Meetings WHERE MeetingID = @MeetingID) AND EXISTS (SELECT 1 FROM Students WHERE StudentID = @StudentID)
    BEGIN
        INSERT INTO CourseAttendance (MeetingID, StudentID, Attendance)
        VALUES (@MeetingID, @StudentID, @IsPresent);
    END
END;
```

3. AddPractiseAttendance

Procedura ta pozwala na dodanie konkretnemu użytkownikowi obecności na danych praktykach, przed wykonaniem polecenia dodawania sprawdza także czy praktyki o podanym ID istnieją oraz czy uczeń o podanym ID istnieje.

```
CREATE PROCEDURE [dbo].[AddPractiseAttendance]
    @PractiseID INT,
    @StudentID INT,
    @IsPresent BIT
AS
BEGIN
    IF EXISTS (SELECT 1 FROM Practices WHERE PractiseID = @PractiseID) AND EXISTS (SELECT 1 FROM Students WHERE StudentID = @StudentID)
    BEGIN
        INSERT INTO PractiseAttendance(PractiseID, StudentID, Attendance)
        VALUES (@PractiseID, @StudentID, @IsPresent);
    END
END;
```

```
END  
END;
```

4. AddNewOrder

Procedura ta umożliwia dodanie do tabeli Orders nowego zamówienia dla studenta o podanym ID, jako datę zamówienia wstawia aktualną datę.

```
CREATE PROCEDURE [dbo].[AddNewOrder]  
    @StudentID INT  
AS  
BEGIN  
    INSERT INTO Orders (StudentID, OrderDate)  
    VALUES (@StudentID, GETDATE());  
  
END;
```

5. AddOrderDetails

Procedura ta pozwala na dodanie szczegółów do konkretnego zamówienia, przyjmuje argumenty takie jak: numer zamówienia, numer oferty zamówionego produktu, koszt tego produktu i ewentualną zniżkę, przed dodaniem do tabeli upewnia się czy suma wartości pozostałych kupionych produktów oraz tego wstawianego nie przekracza przypadkiem kwoty która została zapłacona za zamówienia.

```
CREATE PROCEDURE [dbo].[AddOrderDetails]  
    @OrderID INT,  
    @OfferID INT,  
    @Value MONEY,  
    @Discount FLOAT  
AS  
BEGIN  
    DECLARE @OrderTotalMoney MONEY;  
    DECLARE @PaymentTotalMoney MONEY;  
  
    IF EXISTS (SELECT 1 FROM Orders WHERE OrderID = @OrderID)  
    BEGIN  
        SELECT @OrderTotalMoney = SUM(Value * (1 - Discount))  
        FROM Order_details  
        WHERE OrderID = @OrderID;  
  
        SET @OrderTotalMoney = @OrderTotalMoney + (@Value * (1 - @Discount));  
  
        SELECT @PaymentTotalMoney = Value  
        FROM Payments  
        WHERE OrderID = @OrderID;  
  
        IF @OrderTotalMoney <= @PaymentTotalMoney  
        BEGIN  
            INSERT INTO Order_details (OrderID, OfferID, Value, Discount)  
            VALUES (@OrderID, @OfferID, @Value, @Discount);  
        END  
    END  
END;
```

6. AddPayment

Procedura ta pozwala na dodanie nowego rekordu w tabeli Payments, dla konkretnego zamówienia daty oraz kwoty oraz dla ewentualnej daty odroczenia płatności. Procedura sprawdza także czy podane ID zamówienia istnieje w tabeli z zamówieniami.

```
CREATE PROCEDURE [dbo].[AddPayment]  
    @OrderID INT,  
    @Date DATETIME,
```

```

    @Value MONEY,
    @CancelDate DATETIME
AS
BEGIN

    IF EXISTS (SELECT 1 FROM Orders WHERE OrderID = @OrderID)
    BEGIN

        INSERT INTO Payments (OrderID, Date, Value, CancelDate)
        VALUES (@OrderID, @Date, @Value, @CancelDate);

    END
END;

```

7. GetOrdersPaymentsByStudentID

```

CREATE PROCEDURE [dbo].[GetOrdersPaymentsByStudentID]
    @StudentID INT
AS
BEGIN
    SELECT
        Ord.OrderID,
        SUM(ROUND(OD.Value*(1-OD.Discount),2)) AS Value,
        P.Value AS Paid,
        ROUND(SUM(ROUND(ROUND(OD.Value*(1-OD.Discount),2),2))-P.Value,2) AS ToPay,
        P.CancelDate
    FROM
        Orders AS Ord
    INNER JOIN
        Order_details AS OD ON Ord.OrderID = OD.OrderID
    INNER JOIN
        Payments AS P ON Ord.OrderID = P.OrderID
    WHERE
        Ord.StudentID = @StudentID
    GROUP BY
        Ord.OrderID, P.CancelDate, P.Value;
END;

```

8. GetStudentPracticeCompletionStatus

```

CREATE PROCEDURE [dbo].[GetStudentPracticeCompletionStatus]
    @StudentID INT
AS
BEGIN
    SELECT *
    FROM StudentPracticesCompletionStatus
    WHERE StudentID = @StudentID;
END;

```

9. GetStudentPracticeSummary

```

CREATE PROCEDURE [dbo].[GetStudentPracticeSummary]
    @StudentID INT
AS
BEGIN
    SELECT
        PA.StudentID,
        S.FirstName,
        S.LastName,
        PA.PractiseID,
        CASE WHEN SUM(CAST(PA.Attendance AS INT)) = COUNT(PA.Attendance)
            THEN 'True'

```

```

        ELSE 'False'
    END AS CompletedAllPractices
FROM
    PractiseAttendance PA
JOIN
    Students S ON PA.StudentID = S.StudentID
WHERE
    PA.StudentID = @StudentID
GROUP BY
    PA.StudentID, PA.PractiseID, S.FirstName, S.LastName;
END;

```

10. MeetingsByTeacher

```

CREATE Procedure [dbo].[MeetingsByTeacher]
    @TeacherID INT
AS
Begin
select * from Meetings as m
where m.TeacherID=@TeacherID
End

```

11. OrdersByStudentID

```

CREATE PROCEDURE [dbo].[OrdersByStudentID]
    @StudentID int
AS
BEGIN
    SELECT O.OfferID, O.Name, O.Type, O.Place, OD.Value*(1-OD.Discount) AS Value, P.Value AS Paid, OD.Value-
    P.Value AS ToPay, P.CancelDate FROM Orders AS Ord
    INNER JOIN Order_details AS OD ON Ord.OrderID = OD.OrderID
    INNER JOIN Offers AS O on O.OfferID = OD.OfferID
    INNER JOIN Payments AS P on Ord.OrderID =P.PaymentID
    WHERE Ord.StudentID = @StudentID
END;

```

12. UpdateLessonAttendance

Procedura ta umożliwia zmianę statusu obecności danego ucznia na danej lekcji, przed wykonaniem polecenia sprawdza czy modyfikowany rekord obecności faktycznie istnieje.

```

CREATE PROCEDURE [dbo].[UpdateLessonAttendance]
    @LessonID INT,
    @StudentID INT,
    @NewAttendance BIT
AS
BEGIN
    IF EXISTS (SELECT 1 FROM LessonsAttendance WHERE LessonID = @LessonID AND StudentID = @StudentID)
    BEGIN
        UPDATE LessonsAttendance
        SET Attendance = @NewAttendance
        WHERE LessonID = @LessonID AND StudentID = @StudentID;
    END
END;

```

13. UpdateMeetingAttendance

Procedura ta umożliwia zmianę statusu obecności danego ucznia na danym spotkaniu, przed wykonaniem polecenia sprawdza czy modyfikowany rekord obecności faktycznie istnieje.

```
CREATE PROCEDURE [dbo].[UpdateMeetingAttendance]
    @MeetingID INT,
    @StudentID INT,
    @NewAttendance BIT
AS
BEGIN
    IF EXISTS (SELECT 1 FROM CourseAttendance WHERE MeetingID = @MeetingID AND StudentID = @StudentID)
    BEGIN
        UPDATE CourseAttendance
        SET Attendance = @NewAttendance
        WHERE MeetingID = @MeetingID AND StudentID = @StudentID;
    END
END;
```

14. UpdatePractiseAttendance

Procedura ta umożliwia zmianę statusu obecności danego ucznia na danych praktykach, przed wykonaniem polecenia sprawdza czy modyfikowany rekord obecności faktycznie istnieje.

```
CREATE PROCEDURE [dbo].[UpdatePractiseAttendance]
    @PractiseID INT,
    @StudentID INT,
    @NewAttendance BIT
AS
BEGIN
    IF EXISTS (SELECT 1 FROM PractiseAttendance WHERE PractiseID = @PractiseID AND StudentID = @StudentID)
    BEGIN
        UPDATE PractiseAttendance
        SET Attendance = @NewAttendance
        WHERE PractiseID = @PractiseID AND StudentID = @StudentID;
    END
END;
```

14. GetProfitInTimeRange

Procedura przedstawia dochód z poszczególnych kursów w zadanym przedziale czasowym.

```
CREATE PROCEDURE GetProfitInTimeRange
    @From DATE,
    @To DATE
AS
BEGIN
    SELECT
        c.CourseName,
        ISNULL((
            SELECT SUM(od.Value)
            FROM Order_details od
            INNER JOIN Payments p ON od.OrderID = p.OrderID
            WHERE od.OfferID = c.CourseID AND p.[Date] BETWEEN @From AND @To
        ), 0) AS Profit
    FROM Courses c;
END;
```

15. EnrolledStudentsToCoursesInTimeRange

Procedura przedstawia studentów zapisanych na poszczególne kursy w zadanym przedziale czasowym.

```
CREATE PROCEDURE EnrolledStudentsToCoursesInTimeRange
    @From DATE,
    @To DATE
AS
BEGIN
```

```
SELECT *
FROM StudentCourseDetailsView
WHERE StartDate BETWEEN @From AND @To;
END;
```

16.EnrolledStudentsToGatheringsInTimeRange

Procedura przedstawia studentów zapisanych na poszczególne zjazdy w zadanym przedziale czasowym.

```
CREATE PROCEDURE EnrolledStudentsToGatheringsInTimeRange
    @From DATE,
    @To DATE
AS
BEGIN
    SELECT *
    FROM EnrolledStudentsToGatherings
    WHERE [Date] BETWEEN @From AND @To;
END;
```

17.EnrolledStudentsToStudiesInDateRange

Procedura przedstawia studentów zapisanych na poszczególne studia w zadanym przedziale czasowym.

```
CREATE PROCEDURE EnrolledStudentsToStudiesInDateRange
    @From DATE,
    @To DATE
AS
BEGIN
    SELECT *
    FROM dbo.EnrolledStudentsToStudies
    WHERE StartDate BETWEEN @From AND @To;
END;
```

18.EnrolledStudentsToWebinarsInDateRange

Procedura przedstawia studentów zapisanych na poszczególne webinary w zadanym przedziale czasowym.

```
CREATE PROCEDURE EnrolledStudentsToWebinarsInDateRange
    @From DATE,
    @To DATE
AS
BEGIN
    SELECT *
    FROM dbo.EnrolledStudentsToWebinars
    WHERE [Date] BETWEEN @From AND @To;
END;
```

19. UpdateMeetingDate

Procedura UpdateMeetingDate umożliwia aktualizację daty spotkania o określonym MeetingID na nową datę @NewMeetingDate. Natomiast procedura AddNewOffer pozwala na dodanie nowej oferty do bazy danych, sprawdzając wcześniej, czy oferta o podanej nazwie już istnieje, aby uniknąć konfliktów. Jeśli oferta istnieje, procedura zwraca błąd, w przeciwnym razie dodaje nową ofertę z określonymi parametrami, takimi jak Name, Type, Description, Place, Price i DiscountToStudents.

```
CREATE PROCEDURE [dbo].[UpdateMeetingDate]
    @MeetingID INT,
    @NewMeetingDate DATE
AS
```



```
BEGIN
    SET NOCOUNT ON;

    UPDATE Meetings
    SET Date = @NewMeetingDate
    WHERE MeetingID = @MeetingID;
END;
```

20. AddNewOffer

```
CREATE PROCEDURE [dbo].[AddNewOffer]
    @Name NVARCHAR(50),
    @Type NVARCHAR(15),
    @Description NVARCHAR(50),
    @Place NVARCHAR(20),
    @Price money,
    @DiscountToStudents DECIMAL(5, 2)
AS
BEGIN
    SET NOCOUNT ON;

    IF EXISTS (SELECT 1 FROM Offers WHERE Name = @Name)
    BEGIN
        THROW 50000, 'Oferta o podanej nazwie już istnieje.', 1;
        RETURN;
    END

    INSERT INTO Offers (Name, Type, Description, Place, Price, DiscountToStudents)
    VALUES (@Name, @Type, @Description, @Place, @Price, @DiscountToStudents);
END;
```

21. AddNewCourse

Procedura AddNewCourse służy do dodawania nowego kursu do bazy danych. Najpierw wywołuje procedurę AddNewOffer, aby dodać nową ofertę typu 'Courses', a następnie pobiera identyfikator nowo dodanej oferty. Następnie dodaje kurs z odpowiednimi parametrami, takimi jak TopicID, CourseName, StartDate, ModulesNo, PaymentDay, FullPrice, Deposit i Discount.

```
CREATE PROCEDURE [dbo].[AddNewCourse]
    @CourseName NVARCHAR(30),
    @TopicID Int,
    @CourseDescription NVARCHAR(50),
    @CoursePlace NVARCHAR(20),
    @Price MONEY,
    @DiscountToStudents DECIMAL(5, 2),
    @StartDate DATE,
    @EndDate DATE,
    @Deposit Money,
    @PaymentDay Date
AS
BEGIN
    SET NOCOUNT ON;

    EXEC AddNewOffer @CourseName, 'Courses', @CourseDescription, @CoursePlace, @Price, @DiscountToStudents;

    DECLARE @NewOfferID INT;
    SET @NewOfferID = (SELECT SCOPE_IDENTITY());

    INSERT INTO Courses (CourseID, TopicID, CourseName, StartDate, ModulesNo, PaymentDay, FullPrice,
    Deposit, Discount)
    VALUES (@NewOfferID, @TopicID, @CourseName, @StartDate, 0, @PaymentDay, @Price, @Deposit,
    @DiscountToStudents);
END;
```

22. AddNewModule

Procedura AddNewModule służy do dodawania nowego modułu związanego z określonym kursem. Przed dodaniem modułu sprawdza istnienie kursu o podanym CourseID, a następnie pobiera datę rozpoczęcia kursu i dodaje nowy moduł z odpowiednimi parametrami, takimi jak Title, Type, EndDate i Classroom.

```
CREATE PROCEDURE [dbo].[AddNewModule]
    @CourseID INT,
    @Title NVARCHAR(50),
    @Type NVARCHAR(10),
    @EndDate DATE,
    @Classroom NVARCHAR(10)
AS
BEGIN
    SET NOCOUNT ON;

    IF NOT EXISTS (SELECT 1 FROM Courses WHERE CourseID = @CourseID)
    BEGIN
        THROW 50000, 'Podane CourseID nie istnieje w Courses.', 1;
        RETURN;
    END

    DECLARE @StartDate DATE;
    SET @StartDate = (SELECT StartDate FROM Courses WHERE CourseID = @CourseID);

    INSERT INTO Modules (CourseID, Title, Type, StartDate, EndDate, Classroom)
    VALUES (@CourseID, @Title, @Type, @StartDate, @EndDate, @Classroom);
END;
```

23. AddNewMeeting

Ta procedura przechowuje informacje o nowym spotkaniu w bazie danych. Przyjmuje różne parametry, takie jak ModuleID, LanguageID, Date, Type, Place, Link, Title, TeacherID i TranslatorID. Przed dodaniem spotkania sprawdza istnienie modułu, nauczyciela i tłumacza (jeśli podano TranslatorID), a w przypadku braku zapisuje wartość NULL w TranslatorID.

```
CREATE PROCEDURE [dbo].[AddNewMeeting]
    @ModuleID INT,
    @LanguageID INT,
    @Date date,
    @Type NVARCHAR(10),
    @Place NVARCHAR(10),
    @Link NVARCHAR(30),
    @Title NVARCHAR(50),
    @TeacherID INT,
    @TranslatorID INT
AS
BEGIN
    SET NOCOUNT ON;

    IF NOT EXISTS (SELECT 1 FROM Modules WHERE ModuleID = @ModuleID)
    BEGIN
        THROW 50000, 'Moduł o podanym ModuleID nie istnieje.', 1;
        RETURN;
    END

    IF NOT EXISTS (SELECT 1 FROM TeachingStaff WHERE TeacherID = @TeacherID)
    BEGIN
        THROW 50000, 'Nauczyciel o podanym TeacherID nie istnieje.', 1;
        RETURN;
    END

    IF NOT EXISTS (SELECT 1 FROM Translators WHERE TranslatorID = @TranslatorID)
    BEGIN
        SET @TranslatorID = NULL;
    END
END
```

```
INSERT INTO Meetings (ModuleID, LanguageID, Date, Type, Place, Link, TeacherID, TranslatorID)
VALUES (@ModuleID, @LanguageID, @Date, @Type, @Place, @Link, @TeacherID, @TranslatorID);

END;
```

Funkcje:

1. CourseEnrolmentsNumber

Ta funkcja zwraca ilość użytkowników aktualnie zapisanych na określony kurs o identyfikatorze (CourseID). Wykorzystuje informacje o zapisach, płatnościach i szczegółach zamówienia, filtrując rezultaty dla konkretnego kursu, a także sprawdzając, czy zamówienie nie zostało anulowane.

```
Create FUNCTION [dbo].[CourseEnrolmentsNumber](@CourseID INT)
RETURNS INT
AS
BEGIN

    DECLARE @Enrolments INT;

    select @Enrolments = count(o.StudentID) from Orders as o
    inner join Payments as p on p.OrderID=o.OrderID
    inner join Order_details as d on d.OrderID=p.OrderID
    inner join Offers as f on f.OfferID=d.OfferID
    inner join Courses as c on c.CourseID=f.OfferID
    group by c.CourseID,p.CancelDate
    having p.CancelDate is Null and c.CourseID=@CourseID

    RETURN @Enrolments;
END;
```

2. IsStudyEnrollmentPossible

Ta funkcja sprawdza, czy istnieje możliwość zapisania się na studium o określonym identyfikatorze (StudyID), porównując aktualną liczbę zapisanych studentów (wykorzystując funkcję dbo.StudyEnrollmentsNumber) do pojemności studium. Jeżeli istnieje dostępna przestrzeń, zwraca wartość 1, w przeciwnym razie 0.

```
CREATE FUNCTION [dbo].[IsStudyEnrollmentPossible] (@StudyID INT)
RETURNS BIT
AS
BEGIN
    DECLARE @Capacity INT;

    SELECT @Capacity = s.StudentCapacity
    FROM Studies as s
    WHERE s.StudiesID = @StudyID;

    IF (dbo.StudyEnrollmentsNumber(@StudyID) < @Capacity)
        RETURN 1;
    RETURN 0;
END;
```

3. StudyEnrollmentsNumber

Ta funkcja zwraca ilość obecnie zapisanych studentów na studium o określonym identyfikatorze (StudyID). Wykorzystuje do tego liczbę zamówień (Orders), płatności (Payments), szczegóły zamówienia (Order_details), oferty (Offers) i samego studium (Studies). Funkcja uwzględnia tylko te zapisy, które nie zostały anulowane (CancelDate is Null) i dotyczą danego studium.

```
CREATE FUNCTION [dbo].[StudyEnrollmentsNumber] (@StudyID INT)
RETURNS INT
AS
BEGIN
```

```

DECLARE @Enrollments INT;

select @Enrollments = count(o.StudentID) from Orders as o
inner join Payments as p on p.OrderID=o.OrderID
inner join Order_details as d on d.OrderID=p.OrderID
inner join Offers as f on f.OfferID=d.OfferID
inner join Studies as s on s.StudiesID=f.OfferID
group by p.CancelDate, s.StudiesID
having p.CancelDate is Null and s.StudiesID=@StudyID

RETURN @Enrollments;
END;

```

4. WebinarEnrolmentsNumber

Ta funkcja zwraca liczbę zapisanych studentów na webinar o określonym identyfikatorze (WebinarID). Wykorzystuje do tego liczbę zamówień (Orders), płatności (Payments), szczegóły zamówienia (Order_details), oferty (Offers) i samego webinaru (Webinar). Funkcja uwzględnia tylko te zapisy, które nie zostały anulowane (CancelDate is Null) i dotyczą danego webinaru.

```

CREATE FUNCTION [dbo].[WebinarEnrolmentsNumber](@WebinarID INT)
RETURNS INT
AS
BEGIN

    DECLARE @Enrolments INT;

    select @Enrolments = count(o.StudentID) from Orders as o
    inner join Payments as p on p.OrderID=o.OrderID
    inner join Order_details as d on d.OrderID=p.OrderID
    inner join Offers as f on f.OfferID=d.OfferID
    inner join Webinar as w on w.WebinarID=f.OfferID
    group by w.WebinarID,p.CancelDate
    having p.CancelDate is Null and w.WebinarID=@WebinarID

    RETURN @Enrolments;
END

```

Triggery:

1. CheckStudentCountOnStudies

Ten trigger sprawdza, czy liczba studentów zapisanych na studium przekracza maksymalną pojemność studium po dodaniu lub aktualizacji zamówienia. Jeśli liczba przekracza pojemność, wyświetla komunikat o błędzie i wykonuje rollback transakcji, uniemożliwiając przekroczenie limitu pojemności studium.

```

CREATE TRIGGER [dbo].[CheckStudentCountOnStudies]
ON [dbo].[Order_details]
AFTER INSERT, UPDATE
AS
BEGIN
    DECLARE @StudiesID INT,
            @NewStudentCount INT,
            @MaxStudentCapacity INT;

    SELECT @StudiesID = o.OfferID
    FROM inserted i
    INNER JOIN Offers o ON i.OfferID = o.OfferID;

    SELECT @NewStudentCount = COUNT(*)
    FROM Order_details od
    WHERE od.OfferID = @StudiesID;

    SELECT @MaxStudentCapacity = s.StudentCapacity
    FROM Studies s

```

```

WHERE s.StudiesID = @StudiesID;

IF (@NewStudentCount > @MaxStudentCapacity)
BEGIN
    RAISERROR('Liczba studentów przekracza maksymalną pojemność studium!', 16, 1);
    ROLLBACK;
END
END;

```

2. UpdateModulesNumber

Ten trigger automatycznie aktualizuje liczbę modułów (ModulesNo) w tabeli Courses po dodaniu nowego modułu. Działa na zasadzie zliczania liczby modułów przypisanych do danego kursu i aktualizuje odpowiedni rekord w tabeli Courses.

```

CREATE TRIGGER [dbo].[UpdateModulesNumber]
ON [dbo].[Modules]
AFTER INSERT
AS
BEGIN
    SET NOCOUNT ON;

    DECLARE @CourseID INT;

    SELECT @CourseID = CourseID
    FROM inserted;

    UPDATE Courses
    SET ModulesNo = (
        SELECT ISNULL(COUNT(ModuleID), 0)
        FROM Modules
        WHERE CourseID = @CourseID
    )
    WHERE CourseID = @CourseID;
END;

ALTER TABLE [dbo].[Modules] ENABLE TRIGGER [UpdateModulesNumber]

```

3. CheckAndUpdateModuleDates

Ten trigger sprawdza i aktualizuje daty modułów (StartDate i EndDate) w tabeli Modules po zmianie daty spotkania (MeetingDate) w tabeli Meetings. Jeśli spotkanie już się odbyło, trigger zwraca błąd i blokuje transakcję, w przeciwnym razie aktualizuje odpowiednie daty modułów.

```

CREATE TRIGGER [dbo].[CheckAndUpdateModuleDates]
ON [dbo].[Meetings]
AFTER UPDATE
AS
BEGIN
    SET NOCOUNT ON;

    DECLARE @ModuleID INT;
    DECLARE @NewMeetingDate DATE;
    DECLARE @StartDate DATE;
    DECLARE @EndDate DATE;
    DECLARE @OldMeetingDate DATE;

    SELECT
        @ModuleID = m.ModuleID,
        @NewMeetingDate = i.Date,
        @OldMeetingDate = m.Date,
        @StartDate = mo.StartDate,
        @EndDate = mo.EndDate
    FROM
        inserted i
        INNER JOIN Modules mo ON i.ModuleID = mo.ModuleID

```

```
INNER JOIN Meetings m ON i.ModuleID = m.ModuleID;

IF @OldMeetingDate > GETDATE()
BEGIN
    THROW 50000, 'Nie można zmienić daty spotkania, ponieważ wydarzenie się już odbyło.', 1;
    ROLLBACK;
END
ELSE
BEGIN
    IF @NewMeetingDate < @StartDate
    BEGIN
        UPDATE Modules
        SET StartDate = @NewMeetingDate
        WHERE ModuleID = @ModuleID;
    END;

    IF @NewMeetingDate > @EndDate
    BEGIN
        UPDATE Modules
        SET EndDate = @NewMeetingDate
        WHERE ModuleID = @ModuleID;
    END;
END;

END;

ALTER TABLE [dbo].[Meetings] ENABLE TRIGGER [CheckAndUpdateModuleDates]
```

4. UpdateCourseStartDate

Trigger sprawdza i aktualizuje datę rozpoczęcia kursu (StartDate) w tabeli Courses po zmianie daty rozpoczęcia modułu (NewStartDate) w tabeli Modules. Jeśli nowa data rozpoczęcia modułu jest późniejsza niż data zakończenia kursu, trigger zwraca błąd i blokuje transakcję, w przeciwnym razie aktualizuje datę rozpoczęcia kursu.

```
CREATE TRIGGER [dbo].[UpdateCourseStartDate]
ON [dbo].[Modules]
AFTER UPDATE
AS
BEGIN
    SET NOCOUNT ON;

    DECLARE @CourseID INT;
    DECLARE @NewStartDate DATE;
    DECLARE @EndDate DATE;

    SELECT
        @CourseID = i.CourseID,
        @NewStartDate = i.StartDate,
        @EndDate = i.EndDate
    FROM
        inserted i

    IF @NewStartDate > @EndDate
    BEGIN
        THROW 50000, 'Nowa data rozpoczęcia modułu nie może być późniejsza niż data zakończenia kursu.', 1;
        ROLLBACK;
    END
    ELSE
    BEGIN
        UPDATE Courses
        SET StartDate = @NewStartDate
        WHERE CourseID = @CourseID;
    END;
END;

ALTER TABLE [dbo].[Modules] ENABLE TRIGGER [UpdateCourseStartDate]
```

