

HTML5LAYOUT — FULL WORKBOOK EDITION

Professional HTML5 & CSS Learner Guide

Project Name: HTML5LAYOUT

Technologies Used:

- HTML5
- CSS3

Difficulty Level: Beginner → Intermediate

Learning Type: Practical Workbook

PART 1 — INTRODUCTION TO HTML5 & CSS

1.1 What is HTML?

HTML stands for:

HyperText Markup Language

HTML is used to create the **structure of webpages**.

Think of HTML as the **skeleton of a website**.

HTML defines:

- headings
- paragraphs
- images
- navigation menus
- sections

- links
- layouts

Example:

```
<h1>Welcome to HTML</h1>
```

Output:

Welcome to HTML

1.2 What is CSS?

CSS stands for:

Cascading Style Sheets

CSS controls the **appearance** of HTML.

CSS controls:

- colours
- fonts
- spacing
- layout
- positioning
- borders
- backgrounds

Without CSS:

Websites look plain.

Example:

```
h1{  
color:red;  
}
```

1.3 What Will You Build?

In this project learners will build a **semantic HTML5 webpage layout** containing:

- ✓ Header
 - ✓ Logo Image
 - ✓ Navigation Menu
 - ✓ Aside Panels
 - ✓ Sections
 - ✓ Footer
 - ✓ External CSS Styling
-

1.4 Learning Outcomes

By the end of this workbook learners should be able to:

- ✓ Create an HTML5 project.
 - ✓ Build semantic webpage layouts.
 - ✓ Use HTML5 layout elements.
 - ✓ Connect external CSS files.
 - ✓ Style webpages using CSS selectors.
 - ✓ Create navigation menus.
 - ✓ Apply typography styling.
 - ✓ Create reusable CSS classes.
 - ✓ Debug common HTML/CSS errors.
-

2. PROJECT SETUP

Create the following folder structure.

```
html5layout/
├── index.html
├── css/
│   └── styles.css
├── img/
│   └── dna_square_100x100.png
└── images/
    └── small_arrow.png
```

Folder Explanation

Folder	Purpose
index.html	Main webpage
css	Stores stylesheets
styles.css	CSS rules
img	Website images
images	Icons & list graphics

3. BUILDING THE HTML5 SKELETON

Create:

index.html

Write:

```
<!DOCTYPE html>
<html lang="en">
```

```
<head>
```

```
<meta charset="UTF-8">

<title>Simple Weblayout</title>

<meta name="description"
content="Testing style sheets">

<link rel="stylesheet"
href="css/styles.css">

</head>

<body>

</body>

</html>
```

Explanation

<!DOCTYPE html>

Defines:

HTML5 document type

<html>

Root container.

All webpage code goes inside.

<head>

Stores:

- metadata
- title
- CSS connections

<body>

Contains visible webpage content.

PART 2 — HEADER & NAVIGATION TUTORIAL

Building Semantic HTML5 Layout Components

In this chapter learners will create:

- ✓ Header Section
 - ✓ Logo Image
 - ✓ Website Title
 - ✓ Navigation Menu
 - ✓ Navigation Links
 - ✓ Horizontal Menu Styling Preparation
-

4. Understanding HTML5 Semantic Elements

Before writing code, it is important to understand **semantic HTML5 tags**.

Semantic elements give meaning to webpage structure.

Examples:

Element	Purpose
---------	---------

<header>	Top page section
-----------------------	------------------

- `<nav>` Navigation links
- `<section>` Main content grouping
- `<aside>` Sidebar / extra content
- `<footer>` Bottom page information

Using semantic HTML improves:

- ✓ readability
 - ✓ accessibility
 - ✓ SEO
 - ✓ code organisation
-

5. Creating the Header Section

The **header** normally contains:

- logo
- website title
- navigation

We will now build the webpage header.

Step 1 — Add the Header

Inside `<body>` add:

```
<header>

</header>
```

Explanation

`<header>` defines the **top section** of a webpage.

It usually stores:

- branding
 - menus
 - logos
 - titles
-

Step 2 — Add Website Logo

Inside `<header>` write:

```

```

Explanation of Attributes

Attribute	Purpose
src	image file location
alt	accessibility description
class	CSS styling identifier

Understanding `src`

```
src="img/dna_square_100x100.png"
```

This tells HTML:

Find the image inside the **img folder**.

Understanding `alt`

```
alt="dna square"
```

If image loading fails:

screen readers and browsers display:

dna square

Understanding **class**

`class="top-image"`

This connects HTML to CSS.

Later:

CSS will style:

- image size
 - image alignment
 - spacing
-

Step 3 — Add Page Title

Below the image:

```
<h1 class="toptitle">
```

Basic HTML with CSS

```
</h1>
```

Explanation

<h1>

Defines:

Main webpage heading

HTML heading hierarchy:

Tag	Importance
-----	------------

h1	Highest
----	---------

h2	Section heading
----	-----------------

h3	Subheading
----	------------

Using Classes

Notice:

```
class="toptitle"
```

This creates a **custom styling hook**.

Later CSS will style:

```
h1.toptitle
```

Current Header Code

Your code should now look like:

```
<header>
```

```

```

```
<h1 class="toptitle">
```

Basic HTML with CSS

```
</h1>
```

```
</header>
```

Expected Result

The webpage now contains:

- ✓ logo image
- ✓ large heading

No styling yet.

Layout still looks plain.

That is normal.

CSS comes later.

6. Building the Navigation Menu

Websites need navigation.

Navigation helps users move between pages.

HTML5 provides:

```
<nav>
```

Step 1 — Create Navigation Container

Inside `<header>` add:

```
<nav>
```

```
</nav>
```

Explanation

`<nav>` defines:

website navigation area

Best practice:

menus belong inside:

header → nav

Step 2 — Add Horizontal Lines

Add:

`<hr>`

before and after menu content.

Example:

`<nav>`

`<hr>`

`<hr>`

`</nav>`

What Does `<hr>` Mean?

HR = **H**orizontal **R**ule

Creates a visual separator line.

Example output:

Step 3 — Add Navigation Heading

Inside nav:

`<h1>`

Navigation Menu

`</h1>`

Why Use This Heading?

Navigation sections should have headings.

However:

later CSS hides it.

Why?

Accessibility.

Screen readers can still identify:

Navigation Menu

Step 4 — Create Navigation List

Menus are commonly built using:

Add:

Understanding Lists

ul means:

unordered list

Bullet-style container.

Step 5 — Create Menu Items

Inside `<ul>` write:

```
<li>
```

```
<a href="page1.html">
```

Backend

```
</a>
```

```
</li>
```

Understanding `<li>`

`li` = list item

Every menu item requires one.

Understanding `<a>`

Anchor tag.

Creates hyperlinks.

Syntax:

```
<a href="URL">
```

Link Text

```
</a>
```

Step 6 — Add Full Menu

Complete code:

```
<ul>
```

```
<li>
```

`<a href="page1.html">`

Backend

`</a>`

-

`</li>`

`<li>`

`<a href="page2.html">`

Frontend

`</a>`

-

`</li>`

`<li>`

`<a href="page3.html">`

Agile

`</a>`

`</li>`

`</ul>`

Full Navigation Block

Your navigation should now be:

`<nav>`

`<hr>`

`<h1>`

Navigation Menu

```
</h1>
```

```
<ul>
```

```
<li>
```

```
<a href="page1.html">
```

Backend

```
</a>
```

```
-
```

```
</li>
```

```
<li>
```

```
<a href="page2.html">
```

Frontend

```
</a>
```

```
-
```

```
</li>
```

```
<li>
```

```
<a href="page3.html">
```

Agile

```
</a>
```

```
</li>
```

```
</ul>
```

```
<hr>
```

```
</nav>
```

7. Complete Header Code

Your complete header becomes:

<header>

<h1 class="toptitle">

Basic HTML with CSS

</h1>

<nav>

<hr>

<h1>

Navigation Menu

</h1>

Backend -

Frontend -

Agile

<hr>

</nav>

</header>

Knowledge Check

Question 1

What semantic HTML5 tag creates a navigation area?

- A. `<section>`
 - B. `<nav>`
 - C. `<aside>`
 - D. `<footer>`
-

Question 2

Which tag creates hyperlinks?

- A. `<h1>`
 - B. `<img>`
 - C. `<a>`
 - D. `<li>`
-

Question 3

What does `<ul>` represent?

- A. ordered list
 - B. heading
 - C. unordered list
 - D. footer
-

Practical Activity

Modify your navigation menu.

Add:

Contact

Create:

`<a href="page4.html">`

Contact

`</a>`

Troubleshooting

Problem

Menu links do not work.

Cause

Incorrect file name.

Example:

`href="pagee1.html"`

Solution

Correct:

`href="page1.html"`

End of **PART 2**

PART 2 — HEADER & NAVIGATION TUTORIAL

Building Semantic HTML5 Layout Components

In this chapter learners will create:

- ✓ Header Section
 - ✓ Logo Image
 - ✓ Website Title
 - ✓ Navigation Menu
 - ✓ Navigation Links
 - ✓ Horizontal Menu Styling Preparation
-

4. Understanding HTML5 Semantic Elements

Before writing code, it is important to understand **semantic HTML5 tags**.

Semantic elements give meaning to webpage structure.

Examples:

Element	Purpose
<code><header></code>	Top page section
<code><nav></code>	Navigation links
<code><section></code> >	Main content grouping
<code><aside></code>	Sidebar / extra content

`<footer>` Bottom page information

Using semantic HTML improves:

- ✓ readability
 - ✓ accessibility
 - ✓ SEO
 - ✓ code organisation
-

5. Creating the Header Section

The **header** normally contains:

- logo
- website title
- navigation

We will now build the webpage header.

Step 1 — Add the Header

Inside `<body>` add:

```
<header>
```

```
</header>
```

Explanation

`<header>` defines the **top section** of a webpage.

It usually stores:

- branding
 - menus
 - logos
 - titles
-

Step 2 — Add Website Logo

Inside `<header>` write:

```

```

Explanation of Attributes

Attribute	Purpose
src	image file location
alt	accessibility description
class	CSS styling identifier

Understanding `src`

```
src="img/dna_square_100x100.png"
```

This tells HTML:

Find the image inside the **img** folder.

Understanding **alt**

`alt="dna square"`

If image loading fails:

screen readers and browsers display:

dna square

Understanding **class**

`class="top-image"`

This connects HTML to CSS.

Later:

CSS will style:

- image size
 - image alignment
 - spacing
-

Step 3 — Add Page Title

Below the image:

`<h1 class="toptitle">`

Basic HTML with CSS

</h1>

Explanation

<h1>

Defines:

Main webpage heading

HTML heading hierarchy:

Tag	Importance
-----	------------

h1	Highest
----	---------

h2	Section heading
----	-----------------

h3	Subheading
----	------------

Using Classes

Notice:

class="toptitle"

This creates a **custom styling hook**.

Later CSS will style:

h1.toptitle

Current Header Code

Your code should now look like:

```
<header>



<h1 class="toptitle">

Basic HTML with CSS

</h1>

</header>
```

Expected Result

The webpage now contains:

- ✓ logo image
- ✓ large heading

No styling yet.

Layout still looks plain.

That is normal.

CSS comes later.

6. Building the Navigation Menu

Websites need navigation.

Navigation helps users move between pages.

HTML5 provides:

```
<nav>
```

Step 1 — Create Navigation Container

Inside `<header>` add:

```
<nav>
```

```
</nav>
```

Explanation

`<nav>` defines:

website navigation area

Best practice:

menus belong inside:

header → nav

Step 2 — Add Horizontal Lines

Add:

```
<hr>
```

before and after menu content.

Example:

```
<nav>
```

```
<hr>
```

```
<hr>
```

```
</nav>
```

What Does `<hr>` Mean?

HR = **H**orizontal **R**ule

Creates a visual separator line.

Example output:

Step 3 — Add Navigation Heading

Inside nav:

```
<h1>
```

Navigation Menu

</h1>

Why Use This Heading?

Navigation sections should have headings.

However:

later CSS hides it.

Why?

Accessibility.

Screen readers can still identify:

Navigation Menu

Step 4 — Create Navigation List

Menus are commonly built using:

Add:

Understanding Lists

ul means:

unordered list

Bullet-style container.

Step 5 — Create Menu Items

Inside `<ul>` write:

```
<li>
```

```
<a href="page1.html">
```

Backend

```
</a>
```

```
</li>
```

Understanding `<li>`

`li` = list item

Every menu item requires one.

Understanding `<a>`

Anchor tag.

Creates hyperlinks.

Syntax:

```
<a href="URL">
```

Link Text

Step 6 — Add Full Menu

Complete code:

Backend

-

Frontend

-

Agile

Full Navigation Block

Your navigation should now be:

<nav>

<hr>

<h1>

Navigation Menu

</h1>

Backend

-

Frontend

-

Agile

<hr>

</nav>

7. Complete Header Code

Your complete header becomes:

<header>

<h1 class="toptitle">

Basic HTML with CSS

</h1>

<nav>

<hr>

<h1>

Navigation Menu

</h1>

Backend -

Frontend -

Agile

<hr>

</nav>

</header>

Knowledge Check

Question 1

What semantic HTML5 tag creates a navigation area?

A. <section>

B. <nav>

C. <aside>

D. <footer>

Question 2

Which tag creates hyperlinks?

A. <h1>

B. `<img>`

C. `<a>`

D. `<li>`

Question 3

What does `<ul>` represent?

A. ordered list

B. heading

C. unordered list

D. footer

Practical Activity

Modify your navigation menu.

Add:

Contact

Create:

```
<a href="page4.html">
```

Contact

```
</a>
```

Troubleshooting

Problem

Menu links do not work.

Cause

Incorrect file name.

Example:

```
href="pagee1.html"
```

Solution

Correct:

```
href="page1.html"
```

End of **PART 2**

Next:

PART 3 — ASIDE PANELS + CONTENT SECTIONS + FOOTER + Progressive Layout Construction

Part 3

PART 3 — ASIDE PANELS, CONTENT SECTIONS & FOOTER

Building Layout Structure in HTML5

In this chapter learners will create:

- ✓ Right Sidebar Panel
 - ✓ Left Sidebar Panel
 - ✓ Content Sections
 - ✓ Subsections
 - ✓ Lists
 - ✓ Paragraph Formatting
 - ✓ Footer
 - ✓ Multi-column page layout preparation
-

8. Understanding `<aside>`

HTML5 provides:

`<aside>`

The **aside element** represents:

secondary content related to the main page.

Examples:

- sidebars
 - notifications
 - advertisements
 - quotes
 - news panels
 - recommendations
-

Real-World Example

Websites often use asides for:

TRENDING NEWS

RECENT ARTICLES

NOTIFICATIONS

POPULAR POSTS

DAILY QUOTES

Your project uses:

✓ Trending News Panel

✓ Notifications Panel

9. Creating the First Aside Panel

We will build:

TRENDING NEWS

Step 1 — Create Aside Container

Below your `<header>` add:

```
<aside class="side-panel">
```

```
</aside>
```

Explanation

Notice:

```
class="side-panel"
```

This connects the HTML to CSS styling.

Later CSS will control:

- width
 - floating
 - background
 - borders
 - spacing
-

Step 2 — Add Aside Heading

Inside:

`<aside>`

write:

`<h1>`

TRENDING NEWS

`</h1>`

Explanation

`<h1>` creates the panel title.

Step 3 — Create Information Box

Add:

`<div>`

`</div>`

Why Use `<div>`?

Divisions organise content blocks.

Think of a `<div>` as:

a content container.

Step 4 — Add Subheading

Inside `<div>`:

`<h2>`

Fullstack Development

`</h2>`

Heading Hierarchy Review

Heading	Purpose
---------	---------

h1	Main title
----	------------

h2	Section title
----	---------------

h3	Subsection
----	------------

Step 5 — Add Resource List

Create:

```
<ul>
```

```
<li></li>
```

```
</ul>
```

Add content:

```
<ul>
```

```
<li>
```

```
<a href="http://www.w3schools.com">
```

W3 Schools

```
</a>
```

```
</li>
```

```
<li>
```

```
<a href="https://expressjs.com/">
```

NodeJS Express

Angular

Current Aside Panel

You should now have:

<aside class="side-panel">

<h1>

TRENDING NEWS

</h1>

<div>

<h2>

Fullstack Development

</h2>

W3 Schools

NodeJS Express

Angular

</div>

</aside>

10. Creating Quote Section

Inside the same aside:

Add:

<div class="quote">

</div>

Why Create a Class?

Using:

`class="quote"`

allows CSS to style only quote content.

Inside it:

`<h2>`

Daily Quote

`</h2>`

`<p>`

"Talk Less, Code More, Life is Short"

`</p>`

Completed Right Panel

`<aside class="side-panel">`

`<h1>TRENDING NEWS</h1>`

`<div>`

<h2>Fullstack Development</h2>

W3 Schools

NodeJS Express

Angular

</div>

<div class="quote">

<h2>Daily Quote</h2>

<p>

"Talk Less, Code More, Life is Short"

</p>

</div>

</aside>

11. Creating Second Aside Panel

Now build:

NOTIFICATIONS

Create:

<aside class="side-panel2">

</aside>

Why Use Another Class?

Your project uses:

side-panel

side-panel2

because the two panels use different layout positioning.

Later CSS will apply:

float:right;

and

float:left;

Add:

<h1>

Notifications

</h1>

Create:

<div>

with:

<h2>

Backend

</h2>

Add list:

Javascript

NodeJS Express

SQL / NoSQL

Add second quote block.

Completed Left Panel

<aside class="side-panel2">

<h1>

Notifications

</h1>

<div>

<h2>

Backend

</h2>

Javascript

NodeJS Express

SQL / NoSQL

</div>

<div class="quote">

<h2>

Daily Quote

</h2>

<p>

"It is a scientific fact that your body will not absorb cholesterol if you take it from another person's plate."

</p>

</div>

</aside>

12. Creating Main Content Paragraph

Below the asides:

Create:

<p>

</p>

Add:

<p>

This page has the purpose of demonstrating CSS.

</p>

Using **
**

HTML line breaks:

Example:

This page demonstrates CSS.

What follows is a list.

13. Creating Custom Lists

Your project uses:

`class="body-list"`

Create:

```
<ul class="body-list">
```

```
<li>First list element</li>
```

```
<li>Second list element</li>
```

```
<li>Third list element</li>
```

```
</ul>
```

Why Use a Class?

Later CSS will apply:

`ul.body-list`

to create:

- ✓ custom bullets
- ✓ spacing

✓ image icons

14. Building Content Sections

HTML5 uses:

`<section>`

to group related content.

Section 1

Create:

`<section>`

`</section>`

Add:

`<h2>`

Section 1: Web Applications

`</h2>`

Add paragraph:

`<p>`

This section discusses web applications.

</p>

Creating Subsections

Add:

<h3>

Input

</h3>

Then:

<p>

Input focuses on obtaining data from users.

</p>

Create second subsection:

<h3>

Output

</h3>

Add paragraph.

Completed Section 1

<section>

<h2>

Section 1: Web Applications

</h2>

<p>

This is the first section of the page.

</p>

<h3>

Input

</h3>

<p>

This subsection focuses on collecting user data.

</p>

<h3>

Output

</h3>

<p>

This subsection focuses on displaying results.

</p>

</section>

15. Creating Section 2

Add:

<section>

Create:

Section 2: Web Files

Include:

✓ paragraph

✓ subsection

✓ hyperlink

Example:

<section>

<h2>

Section 2: Web Files

</h2>

<p>

This section explains web files.

</p>

<h3>

Editing Files

</h3>

<p>

This subsection contains a

link

to another webpage.

</p>

</section>

16. Creating Footer

At the bottom:

Create:

<footer>

</footer>

Add:

The material on this website is © Dig.Academy

Understanding Copyright

HTML entity:

©

renders:

©

Example:

<footer>

The material on this website is

©

Dig.Academy

</footer>

17. Full HTML Structure So Far

You now have:

- ✓ Header
- ✓ Navigation
- ✓ Two Aside Panels
- ✓ Main Paragraph
- ✓ Lists
- ✓ Two Sections
- ✓ Footer

Your HTML layout structure is complete.

CSS styling comes next.

Practical Activity

Modify your webpage.

Add:

New Aside Resource

ReactJS

Add:

New Navigation Item

Contact

Create:

Third Section

Section 3 — Databases

Knowledge Check

Question 1

Which HTML5 element creates sidebar content?

- A. nav
 - B. footer
 - C. aside
 - D. img
-

Question 2

What does `<section>` represent?

- A. Image
 - B. Grouped content
 - C. CSS rule
 - D. Hyperlink
-

Question 3

Which HTML tag creates hyperlinks?

A. div

B. ul

C. a

D. section

Troubleshooting

Problem

Sidebar styling not appearing.

Cause

Incorrect class name.

Wrong:

```
class="sidepanel"
```

Correct:

```
class="side-panel"
```

Problem

List bullets missing.

Cause:

Wrong class spelling.

Correct:

```
class="body-list"
```

END OF **PART 3**

PART 4 — COMPLETE CSS WORKBOOK

Building & Understanding `styles.css`

In this chapter learners will:

- ✓ Create an external stylesheet
 - ✓ Style webpage layout
 - ✓ Style typography
 - ✓ Style navigation
 - ✓ Style side panels
 - ✓ Style lists, links & images
 - ✓ Learn CSS selectors
 - ✓ Understand floats, padding, margins & alignment
-

18. Understanding CSS

CSS stands for:

Cascading Style Sheets

CSS controls the **presentation** of HTML.

HTML creates structure.

CSS creates appearance.

HTML Without CSS

Example:

```
<h1>Basic HTML</h1>
```

Result:

Plain browser styling.

HTML With CSS

Example:

```
h1{  
  color:red;  
  font-size:3em;  
}
```

Result:

Styled heading.

19. Creating External Stylesheet

Create:

```
css/
```

```
  styles.css
```

Linking CSS to HTML

Inside `<head>`:

```
<link
```

```
rel="stylesheet"
href="css/styles.css">
```

Explanation

Attribute	Purpose
-----------	---------

rel	relationship
-----	--------------

stylesheet	stylesheet type
------------	-----------------

href	file location
------	---------------

20. Styling the HTML Background

Open:

styles.css

Add:

```
html{
```

```
background-color:#ff8500;
```

```
}
```

Line-by-Line Explanation

Selector

html

Targets:

entire HTML document

Property

background-color

Changes webpage background colour.

Value

#ff8500

Hexadecimal colour value.

Understanding Hex Colours

CSS colours can use:

Colour Names

red

blue

green

RGB

rgb(255,0,0)

Hexadecimal

#ff8500

Your project uses:

Orange

Expected Result

Browser background becomes:

orange

21. Styling the Body Container

Add:

```
body{
```

```
width:980px;
```

```
margin-left:auto;
```

```
margin-right:auto;
```

```
font-family:Gill Sans,sans-serif;
```

```
font-size:1.2em;
```

```
color:#404040;
```

```
background-color:gray;
```

```
padding:10px;
```

```
padding-top:0px;
```

```
}
```

Breaking Down the Body Rule

Width

```
width:980px;
```

Controls:

page container size.

What is PX?

PX means:

pixels

Example:

980 pixels wide

Margin Auto-Centering

CSS:

```
margin-left:auto;
```

```
margin-right:auto;
```

Purpose

Centers webpage container.

Visual Example

Without margins:

LEFT ALIGNED

With margins:

CENTERED PAGE

Font Family

```
font-family:Gill Sans,sans-serif;
```

What Does This Mean?

Preferred font:

Gill Sans

Fallback:

sans-serif

Why Use Fallback Fonts?

If a user's computer lacks:

Gill Sans

browser uses:

sans-serif

Font Size

font-size:1.2em;

Understanding EM Units

EM = scalable sizing.

Example:

1em = default size

1.2em = slightly larger

2em = double size

Text Colour

color:#404040;

Controls:

body text colour.

Background Colour

background-color:gray;

Creates:

gray content container.

Padding

padding:10px;

Creates:

internal spacing.

Margin vs Padding

Margin	Padding
outside spacing	inside spacing

Visual comparison:

MARGIN

[element]

PADDING

[content]

22. Styling Hyperlinks

Add:

```
a{
```

```
color:#3aa6d0;
```

```
text-decoration:none;
```

```
}
```

Understanding Anchor Styling

Selector:

```
a
```

targets:

all hyperlinks.

Link Colour

```
color:#3aa6d0;
```

Creates:

blue hyperlink colour.

Removing Underlines

CSS:

```
text-decoration:none;
```

Default browser links:

underlined

Your stylesheet:

clean links

23. Styling Headings

Your project styles:

✓ h1

✓ h2

✓ h3

H1 Styling

Add:

```
h1{
```

```
font-size:3em;
```

```
color:#FF2C00;
```

```
text-align:center;
```

```
}
```

NOTE

Original code:

```
align:center;
```

Professional CSS correction:

```
text-align:center;
```

Why?

`align` is invalid CSS.

Correct property:

```
text-align
```

Explanation

Font Size

```
font-size:3em;
```

Creates large headings.

Colour

```
color:#FF2C00;
```

Bright orange-red.

Text Alignment

`text-align:center;`

Centers heading.

Styling **.toptitle**

Add:

```
h1.toptitle{
```

```
margin-bottom:10px;
```

```
}
```

Understanding Combined Selectors

`h1.toptitle`

means:

style only h1 elements using class **toptitle**

Margin Bottom

Creates:

spacing below title.

H2 Styling

Add:

```
h2{
```

```
font-size:1.5em;
```

```
color:#ff8500;
```

```
}
```

H3 Styling

Add:

```
h3{
```

```
font-size:1.2em;
```

```
color:#00b945;
```

```
}
```

24. Styling Side Panels

Your project contains:

side-panel

side-panel2

Styling Right Panel

Add:

```
.side-panel{
```

```
float:right;
```

```
width:320px;
```

```
margin-right:20px;
```

```
margin-bottom:15px;
```

```
background-color:#d0d0d0;
```

```
padding:5px;
```

```
border:1px solid #a8a8a8;
```

```
color:#00b945;
```

```
}
```

Line-by-Line Explanation

Float

```
float:right;
```

Moves element:
to the right side.

Width

```
width:320px;
```

Panel width.

Margin Right

```
margin-right:20px;
```

Adds spacing.

Border

```
border:1px solid #a8a8a8;
```

Creates panel outline.

Background

```
background-color:#d0d0d0;
```

Light gray container.

Styling Left Panel

Add:

```
.side-panel2{
```

```
float:left;
```

```
width:320px;
```

```
margin-right:20px;
```

```
margin-bottom:15px;
```

```
background-color:#d0d0d0;
```

```
padding:5px;
```

```
border:1px solid #a8a8a8;
```

```
}
```

Difference Between Panels

Class	Position
side-panel	right
side-panel	left

2

25. Styling Aside Elements

Add:

```
aside h1{  
  
font-size:1.2em;  
  
margin-top:0px;  
  
}
```

Descendant Selectors

aside h1

means:

style **h1 inside aside only**

Add:

aside h2{

font-size:1em;

}

Add:

aside div{

padding:5px;

background-color:#f0f0f0;

margin-bottom:15px;

}

Add:

aside ul{

```
line-height:1.8em;
```

```
list-style-type:square;
```

```
color:#ff8500;
```

```
}
```

26. Styling Navigation

Add:

```
nav{
```

```
text-align:center;
```

```
margin-top:0;
```

```
}
```

Hide navigation heading:

```
nav h1{
```

```
display:none;
```

```
}
```

Understanding Display None

```
display:none;
```

Completely removes element from display.

Style Navigation Lists

Add:

```
nav ul{
```

```
list-style-type:none;
```

```
margin:0;
```

```
padding:0;
```

```
}
```

Why Remove List Bullets?

Navigation menus do not usually show:

- ✓ bullets

- ✓ numbering

Add:

```
nav li{
```

```
display:inline;
```

```
}
```

Inline Display

Creates:

horizontal menu.

Add:

```
nav a{
```

```
font-weight:bold;
```

```
color:#0776a0;
```

```
}
```

27. Styling Navigation Line

Add:

```
nav hr{

width:300px;

margin-right:auto;

margin-left:auto;

background-color:#63dc90;

height:3px;

border:3px;

}
```

28. Styling Footer

Add:

```
footer{

text-align:center;

font-size:0.8em;
```

```
font-style:italic;
```

```
}
```

29. Styling Images

Add:

```
img.top-image{
```

```
height:50px;
```

```
float:right;
```

```
margin-top:10px;
```

```
margin-right:30px;
```

```
}
```

30. Styling Quotes

Add:

```
.quote p{
```

```
font-style:italic;
```

```
}
```

31. Styling Custom Lists

Add:

```
ul.body-list{
```

```
list-style-position:inside;
```

```
list-style-image:
```

```
url("../images/small_arrow.png");
```

```
line-height:1.8em;
```

```
}
```

Understanding Image Bullets

Instead of normal bullets:

CSS uses:

small_arrow.png

as custom bullet icons.

Practical Activity

Modify your CSS.

Change:

- ✓ body background
 - ✓ panel colour
 - ✓ heading colours
 - ✓ navigation width
-

Knowledge Check

1. What property centers text?
 2. What property removes underlines?
 3. What selector targets classes?
 4. Difference between margin and padding?
-

END OF **PART 4**

Next:

PART 5 — PRACTICAL ACTIVITIES + TROUBLESHOOTING + KNOWLEDGE CHECKS + FINAL COMPLETE CODE PROJECT

