

Status report #30

- ToF: new setup
- Tuning amp circuit for MPPC

2020. 06. 05 (Fri)

Tohoku Univ. M1

Tomomasa FUJIWARA

- Checked again.
- Setup:
 - ToFR(upstream): $5 \times 11 \times 300$ [mm³], mppcx1s
 - ToFL(downstream): $5 \times 22 \times 300$ [mm³], mppcx4s
 - ※ Both of them used new board (designed Fujiwara)
- $V_b - V_{op}$ [V/mppc]: +9.0(Lside), +3.0(Rside)
- Taking 3-runs (~1run/day)
- Analysis: assuming Rside has the same resolution with Mar. data (~ 115 ps)

Run num.	σ_{detector} [psec]
177	146.21 \pm 2.44
178	147.33 \pm 2.95
179	141.29 \pm 2.94
Ave.	~145


The run that has problem

⇒ σ of TOF(not intrinsic) = 151.6 ps

- Using only these 3 points

⇒ Intrinsic resolution ~ 44 psec @ 44.7 V

- aaaaa




Run num.	σ_{detector} [psec]
177	146.21 ± 2.44
178	147.33 ± 2.95
179	141.29 ± 2.94
Ave.	~145

For higher bias run (+9.0 V/MPPC)

⇒ σ of TOF(not intrinsic) = 147.6 ps

- ギリギリ計算できるかどうかの値
- 改めて $5 \times 11 \times 300$ [mm³], MPPCx1s
での測定を行う必要有と判断した




Run num.	σ_{detector} [psec]
177	146.21 ± 2.44
178	147.33 ± 2.95
179	141.29 ± 2.94
Ave.	~145

- Conventional setup: 2-scintillators \Rightarrow analysis: assuming that we know already resolution one of them.
- New setup: 3-scintillators \Rightarrow calculation mathematical.
- Combination: Target of test + reference $\times 2$
reference: $10 \times 10 \times 300$ [mm³], MPPCx1s on old board
- Setup for measurement: underconstructing
 $5 \times 11 \times 300$ [mm³], MPPCx1s on new board

Between scintillators:
~58 mm


$10 \times 10 \times 300$ [mm³],
MPPCx1s on old board



✓ Trigger logic


- Coincidence of 4-CHs of reference \oplus clock. (carryout from scaler 0.5 Hz)

$5 \times 11 \times 300$ [mm³],
MPPCx1s on new board



ToF-T

$10 \times 10 \times 300$ [mm³],
MPPCx1s on old board





ToF-C

ToF-B


- First plan: All coin. of 6-CHs \oplus clock.
- But too low event rate (1147 events for ~ 14 hours run $\Rightarrow \sim 1.4$ counts/min.)
- Now testing for data taking.

- Problem of MPPC amp circuit: Large over shoot
- Adding variable resistance \Rightarrow pole zero correction




- Comparison for various value


407Ω



203 Ω




96 Ω




- Comparison for various value

203 Ω



177 Ω



⇒ Employed 170-177 Ω

- JPS application:

Title

Japanese: 「ELPHにおける Λ ハイパー核実験のためのMPPCを用いた新ToF測定器の開発」

English: “Development of a new ToF counter with MPPC for Λ hypernuclear experiments at ELPH”

- Hypernuclear physics seminar (today)

