Article Summary

Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



Gender	Unisex	Legacy Product Class	Men's Shirts	Fit Type	Relaxed
Technical Designer	Selena Meza				





COLORS

White (000)
11-0601 TCX
Bright White (#F4F5F0)

SIZES

XS, S, M, L, LT, XL, XLT, 2XL, 2XLT, 3XL, 3XLT, 4XLT, 5XLT, 6XLT

Powered by WFX. All rights reserved.

Bill of Materials

Version 1

Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops	
	Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

Part	Material	Placement	Size	Qty.	UOM.	Supplier	Comments	000 White
Fabric								
	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)		None	0	Yards	Philips Apparel (PA)		None
Trims								
	Fusible Non-Woven Interlining (T0009)	Collar, Collarstand TOP layer	None	0	Yards		Heavy Weight	White 000 11-0601 TCX Bright White #F4F5F0
	Fusible Non-Woven Interlining (T0009)	Placket - Top and Bottom -Top Layer	None	0	Yards		Mid Weight	White 000 11-0601 TCX Bright White #F4F5F0
	DTM Poly 4-hole Rimmed Button (T0008)	Collar Band Placket Pockets Epaulets	18L(18L)	13	Eaches		# OF BUTTONS ON PLACKET + COLLAR STAND: SEE MEASUREMENT PAGE 1 per pocket 1 per epaulet 2 per cuff	White 000 11-0601 TCX Bright White #F4F5F0
	Sewn-In Collar Stay (T0011) Permanent collar stay, plastic, 0.0014 x 3/8" x 2 1/2"	Collar points	None	2	Eaches		SPI 10-12	None
	Spun Poly Thread (T0013) 100% Polyester	All join seams and topstitching	None	0	Yards		SPI 10-12	White 000 11-0601 TCX Bright White #F4F5F0
	Spun Poly Thread (T0013) 100% Polyester	Bartacks and Buttonholes	None	0	Yards		SPI 85-90	White 000 11-0601 TCX Bright White #F4F5F0
	Spun Poly Thread (T0013) 100% Polyester	Buttonsew	None	0	Yards		16 Total Stiches	White 000 11-0601 TCX Bright White #F4F5F0

Powered by WFX. All rights reserved.

Bill of Materials

Version 1

Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops	
	Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

Part	Material	Placement	Size	Qty.	UOM.	Supplier	Comments	000 White
	VELCRO/Hook and Loop Tape (T0131) Vecro brand: Hook 88 & Loop 1000	Pocket Flap - Loop Pocket - Hook	None	0	Yards		3/4"x3/4" square	None
Labels								
	TRIM-MAIN WOVEN ENDCUT LABEL (TMWLE) New Edwards End Cut label	Center and sew 1/2" below center back neck seam. 1/16" edge stitch all sides to inner yoke layer only.	None	1	Eaches			None
	SIZE COO LABEL (SCOL) New Edwards 2022 label .625 w x 2" - FOLDED	Sew to bottom of main label, centered.	None	1	Eaches			None
	CARE SATIN LOOP LABEL (CARE) White satin label with black print. Finished size: 1 1/4" W x 3" H without seam allowance. Font: Arial - must be legible/readable. Refer to PO label files for details. Care label image in spec has the size at the top of the label. Please ignore. "Size" not needed. Print must withstand 25 wash cycles.	Sew to wearer's left side seam, 4" from sweep edge to bottom of label. (folded)	None	1	Eaches			White 000 11-0601 TCX Bright White #F4F5F0
Packaging								
	RECYCLED POLYBAG STANDARD (RECPOLYSM) See file for pdf artwork. If polybag is certified use GRS icon. If not certified, do not use icon.		None	1	Eaches	Multi Sourcing		None
	Plastic Shirt Clips (CLIPS)		None	3	Eaches			None

Powered by WFX. All rights reserved.

Bill of Materials Material Image Sheet

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

					
T0131	TMWLE	SCOL	CARE	RECPOLYSM	CLIPS
VELCRO/Hook and Loop Tape	TRIM-MAIN WOVEN ENDCUT LABEL	SIZE COO LABEL	CARE SATIN LOOP LABEL	RECYCLED POLYBAG STANDARD	Plastic Shirt Clips

Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



	POM Code	POM Name	-Tol	+Tol	XXS	XS	S	M	L	XL
!	BL20	BODY LENGTH FROM HPS	1/2	1/2	-1	-3/4	-1/2	31	+1	+2
!	BL21	BODY LENGTH FROM HPS TALL	1/2	1/2	-1	-3/4	NR	0	+3 4	+35
	CL20	COLLAR OUTER LENGTH	1/4	1/4	-2	-1 1/2	-1	17	+1 1/8	+2 3/8
	CL10	COLLAR OPENING BUTTON TO BUTTONHOLE	1/8	1/4	-2	-1 1/2	-1	16 1/4	+1 1/8	+2 3/8
	A	EPAULET LENGTH AT CENTER	1/8	1/8	-3/8	-1/4	-1/8	5 3/4	+1/8	+1/4
	CL30	COLLAR POINT	1/8	1/8	0	0	0	2 3/4	0	0
	CL34	COLLAR HEIGHT AT CB	1/8	1/8	0	0	0	2	0	0
	CL35	COLLAR STAND HEIGHT AT CB	1/8	1/8	0	0	0	1 3/8	0	0
	NK12	FRONT NECK DROP TO SEAM	1/4	1/4	-1/2	-3/8	-1/4	3 1/2	+1/4	+1/2
	NK14	BACK NECK DROP TO SEAM	1/8	1/8	0	0	0	5/8	+1/4	+1/2
	PL20	1ST BUTTON PLACEMENT FROM NECK SEAM	1/8	1/8	0	0	0	2 3/4	0	0
	PL21	BUTTON SPACING PLACKET REGULAR	1/8	1/8	0	0	0	3 3/4	0	0
	PL22	BUTTON SPACING PLACKET TALL	1/8	1/8	0	0	0	0	+3 3/4	+3 3/4
	PL11	PLACKET WIDTH	1/8	1/8	0	0	0	1 1/4	0	0
	PL12	UNDER PLACKET WIDTH	0	1/8	0	0	0	7/8	0	0
	SH10	SHOULDER SLOPE	1/8	1/8	0	0	0	2 1/4	0	0
	SH13	FORWARD SHOULDER SEAM	1/8	1/8	0	0	0	1	0	0
!	AB11	ACROSS SHOULDER, FRONT SEAM TO SEAM	3/8	3/8	-2 1/4	-1 1/2	-3/4	19 1/2	+1	+2
	AB78	X" = ACROSS FRONT/BACK PLACEMENT FROM HPS	0	0	-3/4	-1/2	-1/4	7	+1/4	+1/2
	AB74	ACROSS FRONT X" FROM HPS SEAM TO SEAM	3/8	3/8	-2 1/4	-1 1/2	-3/4	17	+1	+2
	AB75	ACROSS BACK X" FROM HPS SEAM TO SEAM	3/8	3/8	-2 1/4	-1 1/2	-3/4	18 3/4	+1	+2
	SH21	BACK YOKE HEIGHT FROM CB	1/8	1/8	0	0	0	3 1/2	0	0
!	AB30	CHEST 1" BELOW ARMHOLE (Circumf)	3/4	3/4	-8	-6	-4	46	+4	+8
!	AB70	SWEEP (Circumf)	3/4	3/4	-8	-6	-4	46	+4	+8
	DE40	SHIRT TAIL HEIGHT	1/4	1/4	0	0	0	3	0	0
	DE41	DROP TAIL HEIGHT	1/4	1/4	0	0	0	1	0	0
	DE52	HEM HEIGHT SWEEP	1/8	1/8	0	0	0	3/16	0	0
!	AH10	ARMHOLE DROP	1/4	1/4	-1	-3/4	-1/2	12	+1/2	+1
!	SL10 31	CB SLEEVE LENGTH 31	1/2	1/2	0	0	0	31 1/2	NR	NR
!	SL10 33	CB SLEEVE LENGTH 33	1/2	1/2	0	0	0	33 1/2	0	0
!	SL10 35	CB SLEEVE LENGTH 35	1/2	1/2	NR	NR	NR	35 1/2	0	0
!	SL10 37	CB SLEEVE LENGTH 37	1/2	1/2	NR	NR	NR	0	+37 1/2	+37 1/2
	SL26	MUSCLE 1" BELOW ARMHOLE (Circumf)	1/2	1/2	-2	-1 1/2	-1	18 1/2	+1	+2
	SL14	SLEEVE OPENING LONG SLEEVE (Circumf)	1/4	1/4	0	-1/2	-1/4	9 1/2	+1/4	+1/2
	SL48	CUFF HEIGHT	1/8	1/8	0	0	0	2 1/2	0	0
	PK39	POCKET PLACEMENT FROM SHOULDER SEAM	1/4	1/4	-1	-3/4	-1/2	8 3/4	+1/2	+1
	PK42	POCKET PLACEMENT FROM CF CHEST	1/8	1/8	-3/8	-1/4	-1/8	2 1/4	+1/4	+5/8
	PK14	POCKET FLAP WIDTH EDGE TO EDGE	1/8	1/8	0	0	0	5 3/4	+1/4	+1/4
	PK12	POCKET FLAP HEIGHT CENTER	1/8	1/8	0	0	0	2 5/8	0	0
	PK13	POCKET FLAP HEIGHT SIDE	1/8	1/8	0	0	0	2 3/8	0	0
	PK22	POCKET WIDTH AT TOP	1/8	1/8	-1/2	-1/2	0	5 1/2	+1/4	+1/4
	PK20	POCKET HEIGHT CENTER INCLUDING FLAP	1/8	1/8	-1/2	-1/2	0	6 1/4	+1/4	+1/4
	PK21	POCKET HEIGHT SIDE INCLUDING FLAP	1/8	1/8	-1/2	-1/2	0	5 1/2	+1/4	+1/4
	DE53	HEM HEIGHT POCKET AT CENTER	1/8	1/8	0	0	0	1	0	0
	DE60	SLEEVE PLEAT PLCMNT FROM PLACKET	1/8	1/8	0	0	0	3/4	0	0
	DE62	SLEEVE PLEAT DEPTH	1/8	1/8	0	0	0	3/4	0	0
	PL15	SLEEVE PLACKET LENGTH	1/8	1/8	0	0	0	5	0	0
	PL16	SLEEVE PLACKET WIDTH TOP PLKT	1/8	1/8	0	0	0	1	0	0
	PL17	SLEEVE UNDER PLACKET WIDTH	1/8	1/8	0	0	0	1	0	0
	PL30	NUMBER OF BUTTON ON PLACKET AND STAND REGULAR	0	0	0	0	0	7	0	+1

Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



POM Code	POM Name	-Tol	+Tol	XXS	XS	S	M	L	XL
PL31	NUMBER OF BUTTON ON PLACKET AND STAND TALL	0	0	NR	NR	NR	0	+8	+8

Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



	POM Code	POM Name	-Tol	+Tol	XXS	XS	S	M	L	XL
!	BL20	BODY LENGTH FROM HPS	1/2	1/2	30	30 1/4	30 1/2	31	32	33
!	BL21	BODY LENGTH FROM HPS TALL	1/2	1/2	-1	-3/4	NR	0	34	35
	CL20	COLLAR OUTER LENGTH	1/4	1/4	15	15 1/2	16	17	18 1/8	19 3/8
	CL10	COLLAR OPENING BUTTON TO BUTTONHOLE	1/8	1/4	14 1/4	14 3/4	15 1/4	16 1/4	17 3/8	18 5/8
	A	EPAULET LENGTH AT CENTER	1/8	1/8	5 3/8	5 1/2	5 5/8	5 3/4	5 7/8	6
	CL30	COLLAR POINT	1/8	1/8	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4
	CL34	COLLAR HEIGHT AT CB	1/8	1/8	2	2	2	2	2	2
	CL35	COLLAR STAND HEIGHT AT CB	1/8	1/8	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8
	NK12	FRONT NECK DROP TO SEAM	1/4	1/4	3	3 1/8	3 1/4	3 1/2	3 3/4	4
	NK14	BACK NECK DROP TO SEAM	1/8	1/8	5/8	5/8	5/8	5/8	7/8	1 1/8
	PL20	1ST BUTTON PLACEMENT FROM NECK SEAM	1/8	1/8	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4
	PL21	BUTTON SPACING PLACKET REGULAR	1/8	1/8	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4
	PL22	BUTTON SPACING PLACKET TALL	1/8	1/8	0	0	0	0	3 3/4	3 3/4
	PL11	PLACKET WIDTH	1/8	1/8	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
	PL12	UNDER PLACKET WIDTH	0	1/8	7/8	7/8	7/8	7/8	7/8	7/8
	SH10	SHOULDER SLOPE	1/8	1/8	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4
	SH13	FORWARD SHOULDER SEAM	1/8	1/8	1	1	1	1	1	1
!	AB11	ACROSS SHOULDER, FRONT SEAM TO SEAM	3/8	3/8	17 1/4	18	18 3/4	19 1/2	20 1/2	21 1/2
	AB78	X" = ACROSS FRONT/BACK PLACEMENT FROM HPS	0	0	6 1/4	6 1/2	6 3/4	7	7 1/4	7 1/2
	AB74	ACROSS FRONT X" FROM HPS SEAM TO SEAM	3/8	3/8	14 3/4	15 1/2	16 1/4	17	18	19
	AB75	ACROSS BACK X" FROM HPS SEAM TO SEAM	3/8	3/8	16 1/2	17 1/4	18	18 3/4	19 3/4	20 3/4
	SH21	BACK YOKE HEIGHT FROM CB	1/8	1/8	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2
!	AB30	CHEST 1" BELOW ARMHOLE (Circumf)	3/4	3/4	38	40	42	46	50	54
!	AB70	SWEEP (Circumf)	3/4	3/4	38	40	42	46	50	54
	DE40	SHIRT TAIL HEIGHT	1/4	1/4	3	3	3	3	3	3
	DE41	DROP TAIL HEIGHT	1/4	1/4	1	1	1	1	1	1
	DE52	HEM HEIGHT SWEEP	1/8	1/8	3/16	3/16	3/16	3/16	3/16	3/16
!	AH10	ARMHOLE DROP	1/4	1/4	11	11 1/4	11 1/2	12	12 1/2	13
!	SL10 31	CB SLEEVE LENGTH 31	1/2	1/2	31 1/2	31 1/2	31 1/2	31 1/2	NR	NR
!	SL10 33	CB SLEEVE LENGTH 33	1/2	1/2	33 1/2	33 1/2	33 1/2	33 1/2	33 1/2	33 1/2
!	SL10 35	CB SLEEVE LENGTH 35	1/2	1/2	NR	NR	NR	35 1/2	35 1/2	35 1/2
!	SL10 37	CB SLEEVE LENGTH 37	1/2	1/2	NR	NR	NR	0	37 1/2	37 1/2
	SL26	MUSCLE 1" BELOW ARMHOLE (Circumf)	1/2	1/2	16 1/2	17	17 1/2	18 1/2	19 1/2	20 1/2
	SL14	SLEEVE OPENING LONG SLEEVE (Circumf)	1/4	1/4	9 1/2	9	9 1/4	9 1/2	9 3/4	10
	SL48	CUFF HEIGHT	1/8	1/8	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2
	PK39	POCKET PLACEMENT FROM SHOULDER SEAM	1/4	1/4	7 3/4	8	8 1/4	8 3/4	9 1/4	9 3/4
	PK42	POCKET PLACEMENT FROM CF CHEST	1/8	1/8	1 7/8	2	2 1/8	2 1/4	2 1/2	2 7/8
	PK14	POCKET FLAP WIDTH EDGE TO EDGE	1/8	1/8	5 3/4	5 3/4	5 3/4	5 3/4	6	6
	PK12	POCKET FLAP HEIGHT CENTER	1/8	1/8	2 5/8	2 5/8	2 5/8	2 5/8	2 5/8	2 5/8
	PK13	POCKET FLAP HEIGHT SIDE	1/8	1/8	2 3/8	2 3/8	2 3/8	2 3/8	2 3/8	2 3/8
	PK22	POCKET WIDTH AT TOP	1/8	1/8	5	5	5 1/2	5 1/2	5 3/4	5 3/4
	PK20	POCKET HEIGHT CENTER INCLUDING FLAP	1/8	1/8	5 3/4	5 3/4	6 1/4	6 1/4	6 1/2	6 1/2
	PK21	POCKET HEIGHT SIDE INCLUDING FLAP	1/8	1/8	5	5	5 1/2	5 1/2	5 3/4	5 3/4
	DE53	HEM HEIGHT POCKET AT CENTER	1/8	1/8	1	1	1	1	1	1
	DE60	SLEEVE PLEAT PLCMNT FROM PLACKET	1/8	1/8	3/4	3/4	3/4	3/4	3/4	3/4
	DE62	SLEEVE PLEAT DEPTH	1/8	1/8	3/4	3/4	3/4	3/4	3/4	3/4
	PL15	SLEEVE PLACKET LENGTH	1/8	1/8	5	5	5	5	5	5
	PL16	SLEEVE PLACKET WIDTH TOP PLKT	1/8	1/8	1	1	1	1	1	1
	PL17	SLEEVE UNDER PLACKET WIDTH	1/8	1/8	1	1	1	1	1	1
	PL30	NUMBER OF BUTTON ON PLACKET AND STAND REGULAR	0	0	7	7	7	7	7	8

Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT					All measurements are in Inch		Version 1
Edwards EST. 1867	**Article Code**	1276	**Description**		**Product Group**	Tops	
	Article Name	LS Cotton Blend Security Shirt			**Product Sub-**	Short Sleeve	
	Created On	09/20/23 12:47:36 PM	**Material Description**	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	**Season**	Active Development	
	Last Modified	07/29/25 8:19:27 AM			**Life Cycle Stage**	Production	

POM Code	POM Name	-Tol	+Tol	XXS	XS	S	M	L	XL
PL31	NUMBER OF BUTTON ON PLACKET AND STAND TALL	0	0	NR	NR	NR	0	8	8

NOTES

10.29.24 - Refitting:
Updated measurements to our New Fit Standard. Please compare current measurement chart to Refit Measurement Chart.
01.24.25 - refit approved with HN Start using this REFIT measurement sheet
05.30.25 - refit approved with SP Start using this REFIT measurement sheet

Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT					All measurements are in Inch	Version 1
Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops
	Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



How to measure

BL20-BODY LENGTH FROM HPS MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE		**BL21-BODY LENGTH FROM HPS TALL** MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE	
CL20-COLLAR OUTER LENGTH MEASURE ALONG OUTER EDGE OF COLLAR, COLLAR POINT TO COLLAR POINT		**CL10-COLLAR OPENING BUTTON TO BUTTONHOLE** MEASURE ALONG MIDDLE OF COLLAR STAND FROM CENTER OF BUTTON TO FAR END OF BUTTONHOLE	
A-EPAULET LENGTH AT CENTER		**CL30-COLLAR POINT** MEASURE FROM COLLAR JOIN SEAM TO COLLAR POINT	
CL34-COLLAR HEIGHT AT CB MEASURE FROM SEAM TO EDGE AT CENTER BACK		**CL35-COLLAR STAND HEIGHT AT CB** MEASURE FROM SEAM TO SEAM AT CENTER BACK	
NK12-FRONT NECK DROP TO SEAM MEASURE FROM HPS TO NECK SEAM		**NK14-BACK NECK DROP TO SEAM** MEASURE FROM HPS TO NECK SEAM	
PL20-1ST BUTTON PLACEMENT FROM NECK SEAM MEASURE FROM NECK SEAM TO CENTER OF 1ST BUTTON ON PLACKET		**PL21-BUTTON SPACING PLACKET REGULAR** MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON	

Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



PL22-BUTTON SPACING PLACKET TALL

MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON



PL11-PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



PL12-UNDER PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



SH10-SHOULDER SLOPE

MEASURE FROM HPS STRAIGHT DOWN TO NATURAL FOLD OF SHOULDER AT ARMHOLE



SH13-FORWARD SHOULDER SEAM

MEASURE FROM HPS TO SEAM



AB11-ACROSS SHOULDER, FRONT SEAM TO SEAM

MEASURE ACROSS FRONT FROM SEAM TO SEAM



AB78-X" = ACROSS FRONT/BACK PLACEMENT FROM HPS

THE DISTANCE FROM HPS STRAIGHT DOWN TO WHERE YOU MEASURE X-FRONT/X-BACK



AB74-ACROSS FRONT X" FROM HPS SEAM TO SEAM

MEASURE ACROSS FRONT X" FROM HPS, SEAM TO SEAM



AB75-ACROSS BACK X" FROM HPS SEAM TO SEAM

MEASURE ACROSS BACK X" FROM HPS, SEAM TO SEAM



SH21-BACK YOKE HEIGHT FROM CB

MEASURE FROM CENTER BACK NECK SEAM TO YOKE SEAM



AB30-CHEST 1" BELOW ARMHOLE (Circumf)

MEASURE ACROSS FRONT 1" BELOW ARMHOLE, OUTSIDE EDGE TO OUTSIDE EDGE

AB70-SWEEP (Circumf)

MEASURE ACROSS BOTTOM OPENING, OUTSIDE EDGE TO OUTSIDE EDGE



DE40-SHIRT TAIL HEIGHT

MEASURE FROM BOTTOM OF GARMENT AT SIDE SEAM TO BOTTOM OF FRONT SHIRT TAIL



DE41-DROP TAIL HEIGHT

MEASURE FROM EDGE OF CF SWEEP TO EDGE OF CB SWEEP



Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



DE52-HEM HEIGHT SWEEP

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



AH10-ARMHOLE DROP

MEASURE FROM HPS TO UNDERARM SEAM (SLEEVELESS TO EDGE).
MEASURING TAPE SHOULD BE PARALLEL TO CF

SL10 31-CB SLEEVE LENGTH 31

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT

SL10 33-CB SLEEVE LENGTH 33

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT



SL10 35-CB SLEEVE LENGTH 35

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT



SL10 37-CB SLEEVE LENGTH 37

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT

SL26-MUSCLE 1" BELOW ARMHOLE (Circumf)

MEASURE 1" BELOW ARMHOLE, EDGE TO EDGE. TAPE MEASURE PERPENDICULAR TO SLEEVE EDGE



SL14-SLEEVE OPENING LONG SLEEVE (Circumf)

MEASURE AT BOTTOM OF SLEEVE HEM EDGE TO EDGE

SL48-CUFF HEIGHT

MEASURE FROM EDGE OF CUFF TO CUFF JOIN SEAM



PK39-POCKET PLACEMENT FROM SHOULDER SEAM

MEASURE STRAIGHT FROM HP SHOULDER SEAM TO TOP OF POCKET (FOR ANGLED POCKETS MEASURE TO HIGHEST POINT OF PKT)



PK42-POCKET PLACEMENT FROM CF CHEST

MEASURE FROM CENTER FRONT TO TOP CORNER OF POCKET

PK14-POCKET FLAP WIDTH EDGE TO EDGE

MEASURE FROM EDGE TO EDGE ALONG TOP EDGE OF POCKET FLAP



PK12-POCKET FLAP HEIGHT CENTER

MEASURE FROM TOP FOLD TO BOTTOM EDGE IN CENTER OF POCKET FLAP



PK13-POCKET FLAP HEIGHT SIDE

MEASURE FROM TOP FOLD TO BOTTOM CORNER AT SIDE OF POCKET FLAP



Powered by WFX. All rights reserved.

REFIT Measurement Chart XXS-XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



PK22-POCKET WIDTH AT TOP

MEASURE TOP WIDTH FROM EDGE TO EDGE



PK20-POCKET HEIGHT CENTER INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM EDGE AT CENTER OF POCKET



PK21-POCKET HEIGHT SIDE INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM SIDE POINT



DE53-HEM HEIGHT POCKET AT CENTER

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



DE60-SLEEVE PLEAT PLCMNT FROM PLACKET

MEASURE FROM PLACKET SEAM EDGE TO PLEAT OPENING AT CUFF SEAM



DE62-SLEEVE PLEAT DEPTH

MEASURE SLEEVE PLEAT DEPTH AT CUFF SEAM



PL15-SLEEVE PLACKET LENGTH

MEASURE FROM CUFF JOIN SEAM TO TOP EDGE



PL16-SLEEVE PLACKET WIDTH TOP PLKT

MEASURE FROM EDGE TO SEAM



PL17-SLEEVE UNDER PLACKET WIDTH

MEASURE FROM EDGE TO SEAM



PL30-NUMBER OF BUTTON ON PLACKET AND STAND REGULAR

COUNT BUTTONS

PL31-NUMBER OF BUTTON ON PLACKET AND STAND TALL

COUNT BUTTONS



Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

BL20-BODY LENGTH FROM HPS

MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE



BL21-BODY LENGTH FROM HPS TALL

MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE

CL20-COLLAR OUTER LENGTH

MEASURE ALONG OUTER EDGE OF COLLAR, COLLAR POINT TO COLLAR POINT

CL10-COLLAR OPENING BUTTON TO BUTTONHOLE

MEASURE ALONG MIDDLE OF COLLAR STAND FROM CENTER OF BUTTON TO FAR END OF BUTTONHOLE

A-EPAULET LENGTH AT CENTER

CL30-COLLAR POINT

MEASURE FROM COLLAR JOIN SEAM TO COLLAR POINT



CL34-COLLAR HEIGHT AT CB

MEASURE FROM SEAM TO EDGE AT CENTER BACK



CL35-COLLAR STAND HEIGHT AT CB

MEASURE FROM SEAM TO SEAM AT CENTER BACK



NK12-FRONT NECK DROP TO SEAM

MEASURE FROM HPS TO NECK SEAM



NK14-BACK NECK DROP TO SEAM

MEASURE FROM HPS TO NECK SEAM



PL20-1ST BUTTON PLACEMENT FROM NECK SEAM

MEASURE FROM NECK SEAM TO CENTER OF 1ST BUTTON ON PLACKET



PL21-BUTTON SPACING PLACKET REGULAR

MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON



PL22-BUTTON SPACING PLACKET TALL

MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON



PL11-PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

PL12-UNDER PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



SH10-SHOULDER SLOPE

MEASURE FROM HPS STRAIGHT DOWN TO NATURAL FOLD OF SHOULDER AT ARMHOLE



SH13-FORWARD SHOULDER SEAM

MEASURE FROM HPS TO SEAM



AB11-ACROSS SHOULDER, FRONT SEAM TO SEAM

MEASURE ACROSS FRONT FROM SEAM TO SEAM



AB78-X" = ACROSS FRONT/BACK PLACEMENT FROM HPS

THE DISTANCE FROM HPS STRAIGHT DOWN TO WHERE YOU MEASURE X-FRONT/X-BACK



AB74-ACROSS FRONT X" FROM HPS SEAM TO SEAM

MEASURE ACROSS FRONT X" FROM HPS, SEAM TO SEAM



AB75-ACROSS BACK X" FROM HPS SEAM TO SEAM

MEASURE ACROSS BACK X" FROM HPS, SEAM TO SEAM



SH21-BACK YOKE HEIGHT FROM CB

MEASURE FROM CENTER BACK NECK SEAM TO YOKE SEAM



AB30-CHEST 1" BELOW ARMHOLE (Circumf)

MEASURE ACROSS FRONT 1" BELOW ARMHOLE, OUTSIDE EDGE TO OUTSIDE EDGE

AB70-SWEEP (Circumf)

MEASURE ACROSS BOTTOM OPENING, OUTSIDE EDGE TO OUTSIDE EDGE



DE40-SHIRT TAIL HEIGHT

MEASURE FROM BOTTOM OF GARMENT AT SIDE SEAM TO BOTTOM OF FRONT SHIRT TAIL



DE41-DROP TAIL HEIGHT

MEASURE FROM EDGE OF CF SWEEP TO EDGE OF CB SWEEP



DE52-HEM HEIGHT SWEEP

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



AH10-ARMHOLE DROP

MEASURE FROM HPS TO UNDERARM SEAM (SLEEVELESS TO EDGE).
MEASURING TAPE SHOULD BE PARALLEL TO CF

Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

SL10 31-CB SLEEVE LENGTH 31

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT

SL10 33-CB SLEEVE LENGTH 33

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT

SL10 35-CB SLEEVE LENGTH 35

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT



SL10 37-CB SLEEVE LENGTH 37

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT

SL26-MUSCLE 1" BELOW ARMHOLE (Circumf)

MEASURE 1" BELOW ARMHOLE, EDGE TO EDGE. TAPE MEASURE PERPENDICULAR TO SLEEVE EDGE



SL14-SLEEVE OPENING LONG SLEEVE (Circumf)

MEASURE AT BOTTOM OF SLEEVE HEM EDGE TO EDGE



SL48-CUFF HEIGHT

MEASURE FROM EDGE OF CUFF TO CUFF JOIN SEAM



PK39-POCKET PLACEMENT FROM SHOULDER SEAM

MEASURE STRAIGHT FROM HP SHOULDER SEAM TO TOP OF POCKET (FOR ANGLED POCKETS MEASURE TO HIGHEST POINT OF PKT)



PK42-POCKET PLACEMENT FROM CF CHEST

MEASURE FROM CENTER FRONT TO TOP CORNER OF POCKET



PK14-POCKET FLAP WIDTH EDGE TO EDGE

MEASURE FROM EDGE TO EDGE ALONG TOP EDGE OF POCKET FLAP



PK12-POCKET FLAP HEIGHT CENTER

MEASURE FROM TOP FOLD TO BOTTOM EDGE IN CENTER OF POCKET FLAP



PK13-POCKET FLAP HEIGHT SIDE

MEASURE FROM TOP FOLD TO BOTTOM CORNER AT SIDE OF POCKET FLAP



PK22-POCKET WIDTH AT TOP

MEASURE TOP WIDTH FROM EDGE TO EDGE



PK20-POCKET HEIGHT CENTER INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM EDGE AT CENTER OF POCKET



Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

PK21-POCKET HEIGHT SIDE INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM SIDE POINT



DE53-HEM HEIGHT POCKET AT CENTER

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



DE60-SLEEVE PLEAT PLCMNT FROM PLACKET

MEASURE FROM PLACKET SEAM EDGE TO PLEAT OPENING AT CUFF SEAM



DE62-SLEEVE PLEAT DEPTH

MEASURE SLEEVE PLEAT DEPTH AT CUFF SEAM



PL15-SLEEVE PLACKET LENGTH

MEASURE FROM CUFF JOIN SEAM TO TOP EDGE



PL16-SLEEVE PLACKET WIDTH TOP PLKT

MEASURE FROM EDGE TO SEAM



PL17-SLEEVE UNDER PLACKET WIDTH

MEASURE FROM EDGE TO SEAM



PL30-NUMBER OF BUTTON ON PLACKET AND STAND REGULAR

COUNT BUTTONS

PL31-NUMBER OF BUTTON ON PLACKET AND STAND TALL

COUNT BUTTONS



Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



	POM Code	POM Name	-Tol	+Tol	2XL	3XL	4XL	5XL	6XL	7XL	8XL
!	BL20	BODY LENGTH FROM HPS	1/2	1/2	33 1/2	+3/4	+1 1/2	+2 1/4	+3	+3 3/4	+4 1/2
!	BL21	BODY LENGTH FROM HPS TALL	1/2	1/2	35 1/2	+3/4	+1 1/2	+2 1/4	+3	+3 3/4	+4 1/2
	CL20	COLLAR OUTER LENGTH	1/4	1/4	19 3/4	+1	+2	+3	+4	+5	+6
	CL10	COLLAR OPENING BUTTON TO BUTTONHOLE	1/8	1/4	19 1/4	+1	+2	+3	+4	+5	+6
	A	EPAULET LENGTH AT CENTER	1/8	1/8	6	0	0	0	0	0	0
	CL30	COLLAR POINT	1/8	1/8	2 3/4	0	0	0	0	+1/4	+1/4
	CL34	COLLAR HEIGHT AT CB	1/8	1/8	2	0	0	0	0	0	0
	CL35	COLLAR STAND HEIGHT AT CB	1/8	1/8	1 3/8	0	0	0	0	0	0
	NK12	FRONT NECK DROP TO SEAM	1/4	1/4	4 1/4	+1/4	+1/2	+3/4	+1	+1 1/4	+1 1/2
	NK14	BACK NECK DROP TO SEAM	1/8	1/8	1 1/8	+1/8	+3/8	+1/2	+3/4	+7/8	+1 1/8
	PL20	1ST BUTTON PLACEMENT FROM NECK SEAM	1/8	1/8	2 3/4	0	0	0	0	0	0
	PL21	BUTTON SPACING PLACKET REGULAR	1/8	1/8	3 3/4	0	0	0	0	-1/4	-1/4
	PL22	BUTTON SPACING PLACKET TALL	1/8	1/8	3 3/4	0	0	0	0	0	0
	PL11	PLACKET WIDTH	1/8	1/8	1 1/4	0	0	0	0	0	0
	PL12	UNDER PLACKET WIDTH	0	1/8	7/8	0	0	0	0	0	0
	SH10	SHOULDER SLOPE	1/8	1/8	2 1/4	0	0	0	0	0	0
	SH13	FORWARD SHOULDER SEAM from HPS	1/8	1/8	1 1/4	0	0	0	0	0	0
!	AB11	ACROSS SHOULDER, FRONT SEAM TO SEAM	3/8	3/8	22 1/2	+3/4	+1 1/2	+2 1/4	+3	+3 3/4	+4 1/2
	AB78	X" = ACROSS FRONT/BACK PLACEMENT FROM HPS	0	0	8	+1/4	+1/2	+3/4	+1	+1 1/4	+1 1/2
	AB74	ACROSS FRONT X" FROM HPS SEAM TO SEAM	3/8	3/8	20	+3/4	+1 1/2	+2 1/4	+3	+3 3/4	+4 1/2
	AB75	ACROSS BACK X" FROM HPS SEAM TO SEAM	3/8	3/8	21 3/4	+3/4	+1 1/2	+2 1/4	+3	+3 3/4	+4 1/2
	SH21	BACK YOKE HEIGHT FROM CB	1/8	1/8	4	0	0	0	0	0	0
!	AB30	CHEST 1" BELOW ARMHOLE (Circumf)	3/4	3/4	58	+4	+8	+12	+16	+20	+24
!	AB70	SWEEP (Circumf)	3/4	3/4	57	+4	+8	+12	+16	+20	+24
	DE40	SHIRT TAIL HEIGHT	1/4	1/4	3 1/2	0	0	0	0	0	0
	DE41	DROP TAIL HEIGHT	1/4	1/4	1	0	0	0	0	0	0
	DE52	HEM HEIGHT SWEEP	1/8	1/8	3/16	0	0	0	0	0	0
!	AH10	ARMHOLE DROP	1/4	1/4	13 1/4	+5/8	+1 1/4	+1 3/4	+2 1/2	+3	+3 1/2
!	SL10 35	CB SLEEVE LENGTH 35	1/2	1/2	35 1/2	0	NR	NR	NR	NR	NR
!	SL10 37	CB SLEEVE LENGTH 37	1/2	1/2	37 1/2	0	0	0	0	0	0
	SL26	MUSCLE 1" BELOW ARMHOLE (Circumf)	1/2	1/2	21 1/2	+1 1/4	+2 1/2	+3 1/2	+5	+6	+7
	SL14	SLEEVE OPENING LONG SLEEVE (Circumf)	1/8	1/8	10 1/4	+1/4	+3/8	+1/2	+5/8	+3/4	+7/8
	SL48	CUFF HEIGHT	1/8	1/8	2 1/2	0	0	0	0	0	0
	PK39	POCKET PLACEMENT FROM SHOULDER SEAM	1/4	1/4	9 1/2	+1/2	+1	+1 1/2	+2	+2 1/2	+3
	PK42	POCKET PLACEMENT FROM CF CHEST	1/8	1/8	2 7/8	+1/8	+1/4	+1/2	+3/4	+7/8	+1 1/8
	PK14	POCKET FLAP WIDTH EDGE TO EDGE	1/8	1/8	6 1/4	0	+1/4	+1/4	+1/2	+1/2	+3/4
	PK12	POCKET FLAP HEIGHT CENTER	1/8	1/8	2 5/8	0	0	0	0	0	0
	PK13	POCKET FLAP HEIGHT SIDE	1/8	1/8	2 3/8	0	0	0	0	0	0
	PK22	POCKET WIDTH AT TOP	1/8	1/8	6	0	+1/4	+1/4	+1/2	+1/2	+3/4
	PK20	POCKET HEIGHT CENTER INCLUDING FLAP	1/8	1/8	6 3/4	0	+1/4	+1/4	+1/2	+1/2	+3/4
	PK21	POCKET HEIGHT SIDE INCLUDING FLAP	1/8	1/8	6	0	+1/4	+1/4	+1/2	+1/2	+3/4
	DE53	HEM HEIGHT POCKET AT CENTER	1/8	1/8	1	0	0	0	0	0	0
	DE60	SLEEVE PLEAT PLCMNT FROM PLACKET	1/8	1/8	3/4	0	0	0	0	0	0
	DE62	SLEEVE PLEAT DEPTH	1/8	1/8	1/2	0	0	0	0	0	0
	DE61	SLEEVE PLEATS APART	0	1/8	1/2	0	0	0	0	0	0
	DE63	SLEEVE PLEAT DEPTH FARTHEST FROM PLACKET	1/8	1/8	1/2	0	0	0	0	0	0
	PL15	SLEEVE PLACKET LENGTH	1/8	1/8	5	0	0	0	0	0	0
	PL16	SLEEVE PLACKET WIDTH TOP PLKT	0	1/8	1	0	0	0	0	0	0
	PL17	SLEEVE UNDER PLACKET WIDTH	0	1/8	1	0	0	0	0	0	0
	PL30	NUMBER OF BUTTON ON PLACKET AND STAND REGULAR	0	0	8	0	0	0	0	+1	+1

Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



POM Code	POM Name	-Tol	+Tol	2XL	3XL	4XL	5XL	6XL	7XL	8XL
PL31	NUMBER OF BUTTON ON PLACKET AND STAND TALL	0	0	8	0	0	+1	+1	+1	+1

Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT

All measurements are in Inch

Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



	POM Code	POM Name	-Tol	+Tol	2XL	3XL	4XL	5XL	6XL	7XL	8XL
!	BL20	BODY LENGTH FROM HPS	1/2	1/2	33 1/2	34 1/4	35	35 3/4	36 1/2	37 1/4	38
!	BL21	BODY LENGTH FROM HPS TALL	1/2	1/2	35 1/2	36 1/4	37	37 3/4	38 1/2	39 1/4	40
	CL20	COLLAR OUTER LENGTH	1/4	1/4	19 3/4	20 3/4	21 3/4	22 3/4	23 3/4	24 3/4	25 3/4
	CL10	COLLAR OPENING BUTTON TO BUTTONHOLE	1/8	1/4	19 1/4	20 1/4	21 1/4	22 1/4	23 1/4	24 1/4	25 1/4
	A	EPAULET LENGTH AT CENTER	1/8	1/8	6	6	6	6	6	6	6
	CL30	COLLAR POINT	1/8	1/8	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	3	3
	CL34	COLLAR HEIGHT AT CB	1/8	1/8	2	2	2	2	2	2	2
	CL35	COLLAR STAND HEIGHT AT CB	1/8	1/8	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8
	NK12	FRONT NECK DROP TO SEAM	1/4	1/4	4 1/4	4 1/2	4 3/4	5	5 1/4	5 1/2	5 3/4
	NK14	BACK NECK DROP TO SEAM	1/8	1/8	1 1/8	1 1/4	1 1/2	1 5/8	1 7/8	2	2 1/4
	PL20	1ST BUTTON PLACEMENT FROM NECK SEAM	1/8	1/8	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4
	PL21	BUTTON SPACING PLACKET REGULAR	1/8	1/8	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 1/2	3 1/2
	PL22	BUTTON SPACING PLACKET TALL	1/8	1/8	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4
	PL11	PLACKET WIDTH	1/8	1/8	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
	PL12	UNDER PLACKET WIDTH	0	1/8	7/8	7/8	7/8	7/8	7/8	7/8	7/8
	SH10	SHOULDER SLOPE	1/8	1/8	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4
	SH13	FORWARD SHOULDER SEAM from HPS	1/8	1/8	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
!	AB11	ACROSS SHOULDER, FRONT SEAM TO SEAM	3/8	3/8	22 1/2	23 1/4	24	24 3/4	25 1/2	26 1/4	27
	AB78	X" = ACROSS FRONT/BACK PLACEMENT FROM HPS	0	0	8	8 1/4	8 1/2	8 3/4	9	9 1/4	9 1/2
	AB74	ACROSS FRONT X" FROM HPS SEAM TO SEAM	3/8	3/8	20	20 3/4	21 1/2	22 1/4	23	23 3/4	24 1/2
	AB75	ACROSS BACK X" FROM HPS SEAM TO SEAM	3/8	3/8	21 3/4	22 1/2	23 1/4	24	24 3/4	25 1/2	26 1/4
	SH21	BACK YOKE HEIGHT FROM CB	1/8	1/8	4	4	4	4	4	4	4
!	AB30	CHEST 1" BELOW ARMHOLE (Circumf)	3/4	3/4	58	62	66	70	74	78	82
!	AB70	SWEEP (Circumf)	3/4	3/4	57	61	65	69	73	77	81
	DE40	SHIRT TAIL HEIGHT	1/4	1/4	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2
	DE41	DROP TAIL HEIGHT	1/4	1/4	1	1	1	1	1	1	1
	DE52	HEM HEIGHT SWEEP	1/8	1/8	3/16	3/16	3/16	3/16	3/16	3/16	3/16
!	AH10	ARMHOLE DROP	1/4	1/4	13 1/4	13 7/8	14 1/2	15	15 3/4	16 1/4	16 3/4
!	SL10 35	CB SLEEVE LENGTH 35	1/2	1/2	35 1/2	35 1/2	NR	NR	NR	NR	NR
!	SL10 37	CB SLEEVE LENGTH 37	1/2	1/2	37 1/2	37 1/2	37 1/2	37 1/2	37 1/2	37 1/2	37 1/2
	SL26	MUSCLE 1" BELOW ARMHOLE (Circumf)	1/2	1/2	21 1/2	22 3/4	24	25	26 1/2	27 1/2	28 1/2
	SL14	SLEEVE OPENING LONG SLEEVE (Circumf)	1/8	1/8	10 1/4	10 1/2	10 5/8	10 3/4	10 7/8	11	11 1/8
	SL48	CUFF HEIGHT	1/8	1/8	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2
	PK39	POCKET PLACEMENT FROM SHOULDER SEAM	1/4	1/4	9 1/2	10	10 1/2	11	11 1/2	12	12 1/2
	PK42	POCKET PLACEMENT FROM CF CHEST	1/8	1/8	2 7/8	3	3 1/8	3 3/8	3 5/8	3 3/4	4
	PK14	POCKET FLAP WIDTH EDGE TO EDGE	1/8	1/8	6 1/4	6 1/4	6 1/2	6 1/2	6 3/4	6 3/4	7
	PK12	POCKET FLAP HEIGHT CENTER	1/8	1/8	2 5/8	2 5/8	2 5/8	2 5/8	2 5/8	2 5/8	2 5/8
	PK13	POCKET FLAP HEIGHT SIDE	1/8	1/8	2 3/8	2 3/8	2 3/8	2 3/8	2 3/8	2 3/8	2 3/8
	PK22	POCKET WIDTH AT TOP	1/8	1/8	6	6	6 1/4	6 1/4	6 1/2	6 1/2	6 3/4
	PK20	POCKET HEIGHT CENTER INCLUDING FLAP	1/8	1/8	6 3/4	6 3/4	7	7	7 1/4	7 1/4	7 1/2
	PK21	POCKET HEIGHT SIDE INCLUDING FLAP	1/8	1/8	6	6	6 1/4	6 1/4	6 1/2	6 1/2	6 3/4
	DE53	HEM HEIGHT POCKET AT CENTER	1/8	1/8	1	1	1	1	1	1	1
	DE60	SLEEVE PLEAT PLCMNT FROM PLACKET	1/8	1/8	3/4	3/4	3/4	3/4	3/4	3/4	3/4
	DE62	SLEEVE PLEAT DEPTH	1/8	1/8	1/2	1/2	1/2	1/2	1/2	1/2	1/2
	DE61	SLEEVE PLEATS APART	0	1/8	1/2	1/2	1/2	1/2	1/2	1/2	1/2
	DE63	SLEEVE PLEAT DEPTH FARTHEST FROM PLACKET	1/8	1/8	1/2	1/2	1/2	1/2	1/2	1/2	1/2
	PL15	SLEEVE PLACKET LENGTH	1/8	1/8	5	5	5	5	5	5	5
	PL16	SLEEVE PLACKET WIDTH TOP PLKT	0	1/8	1	1	1	1	1	1	1
	PL17	SLEEVE UNDER PLACKET WIDTH	0	1/8	1	1	1	1	1	1	1
	PL30	NUMBER OF BUTTON ON PLACKET AND STAND REGULAR	0	0	8	8	8	8	8	9	9

Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



POM Code	POM Name	-Tol	+Tol	2XL	3XL	4XL	5XL	6XL	7XL	8XL
PL31	NUMBER OF BUTTON ON PLACKET AND STAND TALL	0	0	8	8	8	9	9	9	9

NOTES

10.29.24 - Refitting:
Updated measurements to our New Fit Standard. Please compare current measurement chart to Refit Measurement Chart.
01.24.25 - refit approved with HN Start using this REFIT measurement sheet
05.30.25 - refit approved with SP Start using this REFIT measurement sheet

Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT					All measurements are in Inch	Version 1
Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops
	Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



How to measure

PL20-1ST BUTTON PLACEMENT FROM NECK SEAM

MEASURE FROM NECK SEAM TO CENTER OF 1ST BUTTON ON PLACKET



PL21-BUTTON SPACING PLACKET REGULAR

MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON



PL22-BUTTON SPACING PLACKET TALL

MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON



PL11-PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



PL12-UNDER PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



SH10-SHOULDER SLOPE

MEASURE FROM HPS STRAIGHT DOWN TO NATURAL FOLD OF SHOULDER AT ARMHOLE



SH13-FORWARD SHOULDER SEAM from HPS

MEASURE FROM HPS TO SEAM



AB11-ACROSS SHOULDER, FRONT SEAM TO SEAM

MEASURE ACROSS FRONT FROM SEAM TO SEAM



AB78-X" = ACROSS FRONT/BACK PLACEMENT FROM HPS

THE DISTANCE FROM HPS STRAIGHT DOWN TO WHERE YOU MEASURE X-FRONT/X-BACK



AB74-ACROSS FRONT X" FROM HPS SEAM TO SEAM

MEASURE ACROSS FRONT X" FROM HPS, SEAM TO SEAM



DE61-SLEEVE PLEATS APART

MEASURE FROM PLEAT TO PLEAT AT CUFF SEAM



AB75-ACROSS BACK X" FROM HPS SEAM TO SEAM

MEASURE ACROSS BACK X" FROM HPS, SEAM TO SEAM



Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



SH21-BACK YOKE HEIGHT FROM CB

MEASURE FROM CENTER BACK NECK SEAM TO YOKE SEAM



AB30-CHEST 1" BELOW ARMHOLE (Circumf)

MEASURE ACROSS FRONT 1" BELOW ARMHOLE, OUTSIDE EDGE TO OUTSIDE EDGE



AB70-SWEEP (Circumf)

MEASURE ACROSS BOTTOM OPENING, OUTSIDE EDGE TO OUTSIDE EDGE



DE40-SHIRT TAIL HEIGHT

MEASURE FROM BOTTOM OF GARMENT AT SIDE SEAM TO BOTTOM OF FRONT SHIRT TAIL



DE41-DROP TAIL HEIGHT

MEASURE FROM EDGE OF CF SWEEP TO EDGE OF CB SWEEP



DE52-HEM HEIGHT SWEEP

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



AH10-ARMHOLE DROP

MEASURE FROM HPS TO UNDERARM SEAM (SLEEVELESS TO EDGE).
MEASURING TAPE SHOULD BE PARALLEL TO CF



SL10 35-CB SLEEVE LENGTH 35

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT



SL10 37-CB SLEEVE LENGTH 37

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT

SL26-MUSCLE 1" BELOW ARMHOLE (Circumf)

MEASURE 1" BELOW ARMHOLE, EDGE TO EDGE. TAPE MEASURE PERPENDICULAR TO SLEEVE EDGE



SL14-SLEEVE OPENING LONG SLEEVE (Circumf)

MEASURE AT BOTTOM OF SLEEVE HEM EDGE TO EDGE



SL48-CUFF HEIGHT

MEASURE FROM EDGE OF CUFF TO CUFF JOIN SEAM



PK39-POCKET PLACEMENT FROM SHOULDER SEAM

MEASURE STRAIGHT FROM HP SHOULDER SEAM TO TOP OF POCKET (FOR ANGLED POCKETS MEASURE TO HIGHEST POINT OF PKT)



PK42-POCKET PLACEMENT FROM CF CHEST

MEASURE FROM CENTER FRONT TO TOP CORNER OF POCKET



Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



PK14-POCKET FLAP WIDTH EDGE TO EDGE

MEASURE FROM EDGE TO EDGE ALONG TOP EDGE OF POCKET FLAP



PK12-POCKET FLAP HEIGHT CENTER

MEASURE FROM TOP FOLD TO BOTTOM EDGE IN CENTER OF POCKET FLAP



PK13-POCKET FLAP HEIGHT SIDE

MEASURE FROM TOP FOLD TO BOTTOM CORNER AT SIDE OF POCKET FLAP



PK22-POCKET WIDTH AT TOP

MEASURE TOP WIDTH FROM EDGE TO EDGE



PK20-POCKET HEIGHT CENTER INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM EDGE AT CENTER OF POCKET



PK21-POCKET HEIGHT SIDE INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM SIDE POINT



DE53-HEM HEIGHT POCKET AT CENTER

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



DE60-SLEEVE PLEAT PLCMNT FROM PLACKET

MEASURE FROM PLACKET SEAM EDGE TO PLEAT OPENING AT CUFF SEAM



DE62-SLEEVE PLEAT DEPTH

MEASURE SLEEVE PLEAT DEPTH AT CUFF SEAM



DE63-SLEEVE PLEAT DEPTH FARTHEST FROM PLACKET

MEASURE SLEEVE PLEAT DEPTH AT CUFF SEAM



PL15-SLEEVE PLACKET LENGTH

MEASURE FROM CUFF JOIN SEAM TO TOP EDGE



PL16-SLEEVE PLACKET WIDTH TOP PLKT

MEASURE FROM EDGE TO SEAM



Powered by WFX. All rights reserved.

REFIT Measurement Chart 2XL-8XLT

All measurements are in Inch | Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



PL17-SLEEVE UNDER PLACKET WIDTH

MEASURE FROM EDGE TO SEAM



PL30-NUMBER OF BUTTON ON PLACKET AND STAND REGULAR

COUNT BUTTONS

PL31-NUMBER OF BUTTON ON PLACKET AND STAND TALL

COUNT BUTTONS



BL20-BODY LENGTH FROM HPS

MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE



BL21-BODY LENGTH FROM HPS TALL

MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE

CL20-COLLAR OUTER LENGTH

MEASURE ALONG OUTER EDGE OF COLLAR, COLLAR POINT TO COLLAR POINT

CL10-COLLAR OPENING BUTTON TO BUTTONHOLE

MEASURE ALONG MIDDLE OF COLLAR STAND FROM CENTER OF BUTTON TO FAR END OF BUTTONHOLE

A-EPAULET LENGTH AT CENTER

CL30-COLLAR POINT

MEASURE FROM COLLAR JOIN SEAM TO COLLAR POINT



CL34-COLLAR HEIGHT AT CB

MEASURE FROM SEAM TO EDGE AT CENTER BACK



CL35-COLLAR STAND HEIGHT AT CB

MEASURE FROM SEAM TO SEAM AT CENTER BACK

NK12-FRONT NECK DROP TO SEAM

MEASURE FROM HPS TO NECK SEAM



NK14-BACK NECK DROP TO SEAM

MEASURE FROM HPS TO NECK SEAM



Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

BL20-BODY LENGTH FROM HPS

MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE



BL21-BODY LENGTH FROM HPS TALL

MEASURE STRAIGHT FROM HIGH POINT SHOULDER TO BOTTOM EDGE

CL20-COLLAR OUTER LENGTH

MEASURE ALONG OUTER EDGE OF COLLAR, COLLAR POINT TO COLLAR POINT

CL10-COLLAR OPENING BUTTON TO BUTTONHOLE

MEASURE ALONG MIDDLE OF COLLAR STAND FROM CENTER OF BUTTON TO FAR END OF BUTTONHOLE

A-EPAULET LENGTH AT CENTER

CL30-COLLAR POINT

MEASURE FROM COLLAR JOIN SEAM TO COLLAR POINT



CL34-COLLAR HEIGHT AT CB

MEASURE FROM SEAM TO EDGE AT CENTER BACK



CL35-COLLAR STAND HEIGHT AT CB

MEASURE FROM SEAM TO SEAM AT CENTER BACK



NK12-FRONT NECK DROP TO SEAM

MEASURE FROM HPS TO NECK SEAM



NK14-BACK NECK DROP TO SEAM

MEASURE FROM HPS TO NECK SEAM



PL20-1ST BUTTON PLACEMENT FROM NECK SEAM

MEASURE FROM NECK SEAM TO CENTER OF 1ST BUTTON ON PLACKET



PL21-BUTTON SPACING PLACKET REGULAR

MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON



PL22-BUTTON SPACING PLACKET TALL

MEASURE FROM CENTER OF BUTTON TO CENTER OF BUTTON



PL11-PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

PL12-UNDER PLACKET WIDTH

MEASURE STRAIGHT ACROSS PLACKET FROM EDGE TO EDGE OR OUTERMOST STITCH ROW



SH10-SHOULDER SLOPE

MEASURE FROM HPS STRAIGHT DOWN TO NATURAL FOLD OF SHOULDER AT ARMHOLE



SH13-FORWARD SHOULDER SEAM from HPS

MEASURE FROM HPS TO SEAM



AB11-ACROSS SHOULDER, FRONT SEAM TO SEAM

MEASURE ACROSS FRONT FROM SEAM TO SEAM



AB78-X" = ACROSS FRONT/BACK PLACEMENT FROM HPS

THE DISTANCE FROM HPS STRAIGHT DOWN TO WHERE YOU MEASURE X-FRONT/X-BACK



AB74-ACROSS FRONT X" FROM HPS SEAM TO SEAM

MEASURE ACROSS FRONT X" FROM HPS, SEAM TO SEAM



DE61-SLEEVE PLEATS APART

MEASURE FROM PLEAT TO PLEAT AT CUFF SEAM



AB75-ACROSS BACK X" FROM HPS SEAM TO SEAM

MEASURE ACROSS BACK X" FROM HPS, SEAM TO SEAM



SH21-BACK YOKE HEIGHT FROM CB

MEASURE FROM CENTER BACK NECK SEAM TO YOKE SEAM



AB30-CHEST 1" BELOW ARMHOLE (Circumf)

MEASURE ACROSS FRONT 1" BELOW ARMHOLE, OUTSIDE EDGE TO OUTSIDE EDGE



AB70-SWEEP (Circumf)

MEASURE ACROSS BOTTOM OPENING, OUTSIDE EDGE TO OUTSIDE EDGE



DE40-SHIRT TAIL HEIGHT

MEASURE FROM BOTTOM OF GARMENT AT SIDE SEAM TO BOTTOM OF FRONT SHIRT TAIL



Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

DE41-DROP TAIL HEIGHT

MEASURE FROM EDGE OF CF SWEEP TO EDGE OF CB SWEEP



DE52-HEM HEIGHT SWEEP

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



AH10-ARMHOLE DROP

MEASURE FROM HPS TO UNDERARM SEAM (SLEEVELESS TO EDGE).
MEASURING TAPE SHOULD BE PARALLEL TO CF



SL10 35-CB SLEEVE LENGTH 35

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT



SL10 37-CB SLEEVE LENGTH 37

TAKE HALF OF ACROSS SHOULDER MEASUREMENT, THEN ADD
SHOULDER POINT TO BOTTOM EDGE OF SLEEVE MEASUREMENT

SL26-MUSCLE 1" BELOW ARMHOLE (Circumf)

MEASURE 1" BELOW ARMHOLE, EDGE TO EDGE. TAPE MEASURE PERPENDICULAR TO SLEEVE EDGE



SL14-SLEEVE OPENING LONG SLEEVE (Circumf)

MEASURE AT BOTTOM OF SLEEVE HEM EDGE TO EDGE



SL48-CUFF HEIGHT

MEASURE FROM EDGE OF CUFF TO CUFF JOIN SEAM



PK39-POCKET PLACEMENT FROM SHOULDER SEAM

MEASURE STRAIGHT FROM HP SHOULDER SEAM TO TOP OF POCKET (FOR ANGLED POCKETS MEASURE TO HIGHEST POINT OF PKT)



PK42-POCKET PLACEMENT FROM CF CHEST

MEASURE FROM CENTER FRONT TO TOP CORNER OF POCKET



PK14-POCKET FLAP WIDTH EDGE TO EDGE

MEASURE FROM EDGE TO EDGE ALONG TOP EDGE OF POCKET FLAP



PK12-POCKET FLAP HEIGHT CENTER

MEASURE FROM TOP FOLD TO BOTTOM EDGE IN CENTER OF POCKET FLAP



PK13-POCKET FLAP HEIGHT SIDE

MEASURE FROM TOP FOLD TO BOTTOM CORNER AT SIDE OF POCKET FLAP



PK22-POCKET WIDTH AT TOP

MEASURE TOP WIDTH FROM EDGE TO EDGE



Powered by WFX. All rights reserved.

How To Measure

Version 1

Article Code	1276	Description		Product Group	Tops	
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve	
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development	
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production	

PK20-POCKET HEIGHT CENTER INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM EDGE AT CENTER OF POCKET



PK21-POCKET HEIGHT SIDE INCLUDING FLAP

MEASURE FROM TOP EDGE TO BOTTOM SIDE POINT



DE53-HEM HEIGHT POCKET AT CENTER

MEASURE FROM EDGE OF HEM TO STITCH LINE. IF TWO NEEDLES MEASURE TO TOP STITCH LINE.



DE60-SLEEVE PLEAT PLCMNT FROM PLACKET

MEASURE FROM PLACKET SEAM EDGE TO PLEAT OPENING AT CUFF SEAM



DE62-SLEEVE PLEAT DEPTH

MEASURE SLEEVE PLEAT DEPTH AT CUFF SEAM



DE63-SLEEVE PLEAT DEPTH FARTHEST FROM PLACKET

MEASURE SLEEVE PLEAT DEPTH AT CUFF SEAM



PL15-SLEEVE PLACKET LENGTH

MEASURE FROM CUFF JOIN SEAM TO TOP EDGE



PL16-SLEEVE PLACKET WIDTH TOP PLKT

MEASURE FROM EDGE TO SEAM



PL17-SLEEVE UNDER PLACKET WIDTH

MEASURE FROM EDGE TO SEAM



PL30-NUMBER OF BUTTON ON PLACKET AND STAND REGULAR

COUNT BUTTONS

PL31-NUMBER OF BUTTON ON PLACKET AND STAND TALL

COUNT BUTTONS



Powered by WFX. All rights reserved.

How To Measure

Edwards EST. 1867	**Article Code**	1276	**Description**		**Product Group**	Tops	
	Article Name	LS Cotton Blend Security Shirt			**Product Sub-Category**	Short Sleeve	
	Created On	09/20/23 12:47:36 PM	**Material Description**	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	**Season**	Active Development	
	Last Modified	07/29/25 8:19:27 AM			**Life Cycle Stage**	Production	

Powered by WFX. All rights reserved.

Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops
	Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



301 Topstitch
1/4" Gauge: Collar, Placket, Cuff, Pocket flap set
Edgestitch: Pocket, Pocket Flap, Cuff, Sleeve Placket, Collarstand
301 Pintucks front and back



Powered by WFX. All rights reserved.

Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops
	Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production





Faux buttonhole
with button
x-stitched to flap



3/4" square
hook and loop
301 LS all sides

Triangle reinf
top corners pkt,
Vertical Bartack
top of pen slot

Inverted box pleat centered on pockets
1/2" pleat depth each side

Powered by WFX. All rights reserved.

Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops
	Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production







Powered by WFX. All rights reserved.

Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops
	Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



Powered by WFX. All rights reserved.

Edwards EST. 1867	Article Code	1276	Description		Product Group	Tops
	Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve
	Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
	Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



ALL STITCHING 301
CUFF CLEAN FINISH WITH 2N 301, 1/4" GAUGE
301, 1/4" BOTTOM/SIDE EDGE
SLEEVE PLACKET EDGESTITCHED OPENING & DOGHOUSE



SINGLE PLEAT FOR SIZE XS-XLT



PLEATS SEAM ALLOWANCE PRESSED
AWAY FROM PLACKET



DOUBLE PLEATS FOR SIZE 2XL-6XLT

Powered by WFX. All rights reserved.

Care Instructions

Version 1

Article Code	1276	Description		Product Group	Tops
Article Name	LS Cotton Blend Security Shirt			Product Sub-Category	Short Sleeve
Created On	09/20/23 12:47:36 PM	Material Description	Poly/Cotton Security Fabric (F0082) 65% Polyester/35% Cotton, 5oz Supplier: Philips Apparel (PA)	Season	Active Development
Last Modified	07/29/25 8:19:27 AM			Life Cycle Stage	Production



Care Symbols

Care Symbols
Machine Wash Warm
Do Not Bleach
Tumble Dry Low
Cool Iron

Care Instructions

07A - 65% Polyester/35% Cotton

65% POLYESTER / POLIÉSTER / POLYESTER

35% COTTON / ALGODÓN/COTON

- **MACHINE WASH WARM, DO NOT BLEACH, TUMBLE DRY LOW, COOL IRON.**
- **LAVAR A MÁQUINA TIBIO, NO BLANQUEADOR, SECADO TEMP BAJA, PLANCHA FRIA.**
- **LAVAGE EN MACHINE CHAUD, NE PAS JAVELLISER, SÈCHE-LINGE À FAIBLE, FER REFROIDIR.**

Fiber Content

Layout

CARE007–A

Powered by WFX. All rights reserved.