
Searching

Searching

- You have a list.
- How do you find something in the list?
- Basic idea: go through the list from start to finish one element at a time.

Linear Search

• Idea: go through the list from start to finish



Found 3.

Linear Search

Idea: go through the list from start to finish

```
# equivalent code
for i in [5, 2, 3, 4]:
   if i == 3:
      return True
```

Linear Search

Implemented as a function:

```
def linear_search(value, lst):
    for i in lst:
        if i == value:
            return True
    return False
```

What kind of performance can we expect? Large vs small lists? O(n)

Can we do better? Of course la!

Searching

IDEA:

If the elements in the list were sorted in order, life would be much easier.


Why?




IDEA

If list is sorted, we can "divide-and-conquer"

Assuming a list is sorted in ascending order:





if the $k^{\rm th}$ element is larger than what we are looking for, then we only need to search in the indices < k

- 1. Find the middle element.
- 2. If it is what we are looking for (key), return True.
- 3. If our key is smaller than the middle element, repeat search on the left of the list.
- 4. Else, repeat search on the right of the list.

Looking for 25 (key)

5	9	12	18	25	34	85	100	123	345

Find the middle element: 34



Not the thing we're looking for: $34 \neq 25$



25 < 34, so we repeat our search on the left half:

5	9	12	18	25	34	85	100	123	345


Find the middle element: 12




25 > 12, so we repeat the search on the right half:



Find the middle element: 25



Great success: 25 is what we want



"Divide and Conquer"

In large sorted lists, performs much better than linear search on average.

Algorithm (assume sorted list):

- Find the middle element.
- 2. If it is we are looking for (key), return True.
- 3. A) If our key is smaller than the middle element, repeat search on the left of the element.
 - B) Else, repeat search on the right of the element.

```
def binary_search(key, seq):
    if seq == []:
        return False
    mid = len(seq) // 2
    if key == seq[mid]:
        return True
    elif key < seq[mid]:
        return binary_search(key, seq[:mid])
    else:
        return binary_search(key, seq[mid+1:])</pre>
```

```
def binary_search(key, seq): # seq is sorted
    def helper(low, high):
        if low > high:
            return False
        mid = (low + high) // 2 # get middle
        if key == seq[mid]:
            return True
        elif key < seq[mid]:</pre>
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Now let's try searching for 11:

```
5 9 12 18 25 34 85 100 123 345
```

```
def binary_search(key, seq):
    def helper(low, high):
        if low > high:
            return False
        mid = (low + high) // 2
        if key == seq[mid]:
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
        return helper(0, len(seq)-1)</pre>
```

Step 1. Find the middle element.

```
5
                                                  123
           9
                12
                      18
                            25
                                  34
                                       85
                                            100
                                                        345
def binary_search(key, seq):
                                             key \rightarrow 11
    def helper(low, high):
        if low > high:
            return False
        mid = (low + high) // 2
        if key == seq[mid]:
            return True
        elif key < seq[mid]:</pre>
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
                                             helper(0, 10-1)
    return helper(0, len(seq)-1)
```

Now let's try searching for 11:

```
5 9 12 18 25 34 85 100 123 345
```

```
def binary_search(key, seq):
    def helper(low, high): # 0, 9
        if low > high:
            return False
        mid = (low + high) // 2 # mid=4
        if key == seq[mid]:
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
        return helper(0, len(seq)-1)</pre>
```

Step 1. Find the middle element.

Now let's try searching for 11:

```
5 9 12 18 <mark>25</mark> 34 85 100 123 345
```

```
def binary_search(key, seq):
    def helper(low, high): # 0, 9
        if low > high:
            return False
        mid = (low + high) // 2 # mid=4
        if key == seq[mid]: # 11 == 25
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
        return helper(0, len(seq)-1)</pre>
```

Step 2. If it is what we are looking for, return True


```
5
           9
                12
                     18
                           25
                                34
                                      85
                                           100
                                                123
                                                      345
def binary search(key, seq):
                                           Step 3a. If key is
    def helper(low, high): # 0, 9
       if low > high:
                                           smaller, look at
           return False
       mid = (low + high) // 2 # mid=4
                                                 left side
       if key == seq[mid]: # 11 == 25
           return True
       elif key < seq[mid]: # 11 < 25</pre>
           return helper(low, mid-1) # helper(0, 4-1)
       else:
           return helper(mid+1, high)
   return helper(0, len(seq)-1)
```

Now let's try searching for 11:

```
5 9 12 18 25 34 85 100 123 345
```

```
def binary_search(key, seq):
    def helper(low, high): # 0, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=4
        if key == seq[mid]: # 11 == 25
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
        return helper(0, len(seq)-1)</pre>
```

Step 3a. If key is smaller, look at left side



Now let's try searching for 11:



```
def binary_search(key, seq):
    def helper(low, high): # 0, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=1
        if key == seq[mid]: # 11 == 9
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
        return helper(0, len(seq)-1)</pre>
```

Step 2. If it is what we are looking for, return True


Now let's try searching for 11:

return helper(low, mid-1)


return helper(mid+1, high)


return helper(0, len(seq)-1)


else:



```
5
           9
               12
                     18
                          25
                                     85
                                          100
                                               123
                                                    345
                                34
def binary search(key, seq):
                                           Step 3b. Else
   def helper(low, high): # 0, 3
       if low > high:
                                            look at right
           return False
       mid = (low + high) // 2 # mid=1
                                                  side
       if key == seq[mid]: # 11 == 9
           return True
       elif key < seq[mid]: # 11 < 9
           return helper(low, mid-1)
       else:
           return helper(mid+1, high) # helper(1+1, 3)
   return helper(0, len(seq)-1)
```







Now let's try searching for 11:


elif key < seq[mid]:</pre>

return helper(0, len(seq)-1)


else:

return helper(low, mid-1)

return helper(mid+1, high)



what we are looking for, return True




Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 2, 1
        if low > high:
            return False
        mid = (low + high) // 2
        if key == seq[mid]:
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
        return helper(0, len(seq)-1)</pre>
```

Step 3a. If key is smaller, look at left side

Now let's try searching for 11:



```
def binary_search(key, seq):
    def helper(low, high): # 2, 1
        if low > high: # 2 > 1
            return False
        mid = (low + high) // 2
        if key == seq[mid]:
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
        return helper(0, len(seq)-1)</pre>
```

Key cannot be found. Return False

- Each step eliminates the problem size by half.
 - The problem size gets reduced to 1 very quickly
- This is a simple yet powerful strategy, of halving the solution space in each step
- What is the order of growth?

 $O(\log n)$

Wishful Thinking

We assumed the list was sorted.

Now, let's deal with this assumption!

Sorting

Sorting

- High-level idea:
 - 1. some objects
 - 2. function that can order two objects
 - \Rightarrow order all the objects

How Many Ways to Sort? Too many. ©


Example

Let's sort some playing cards?
















What do you do when you play cards?


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.








Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.






Sorted



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.






Sorted




Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.






Sorted



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.






Sorted

Smallest



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted Smallest



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted













Sorted




Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted \$\begin{align*} \begin{align*} \begin{ali



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Repeat

Unsorted











Sorted







Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.






Repeat







Sorted



Smallest

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Repeat







Sorted







Smallest



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted




Repeat





Sorted



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Repeat





Sorted












Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Repeat



Sorted













Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted

Repeat



Sorted













Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted

Repeat



Sorted















Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted

Done

Sorted











There is actually a name for this: Selection Sort!

Let's Implement it!

```
a = [4,12,3,1,11]
sort = []
while a: # a is not []
    smallest = a[0]
    for element in a:
        if element < smallest:</pre>
            smallest = element
    a.remove(smallest)
    sort.append(smallest)
    print(a)
```

Output

```
[4, 12, 3, 11]
[4, 12, 11]
[12, 11]
[12]
print(a)
print(sort)
[1, 3, 4, 11, 12]
```

Order of Growth?

• Time: Worst $O(n^2)$

Average $O(n^2)$

Best $O(n^2)$

• Space:



Let's try something else... suppose you have a friend

• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.


Split into halves































































































• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.





How to combine the 2 sorted halves?


• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.




• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.







• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.














• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.












• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.











• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.








• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.





• Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.




There is also a name for this: Merge Sort!

Let's Implement It!

First observation: RECURSION!

- Base case: n< 2, return lst
- Otherwise:



- Divide list into two
- Sort each of them
- Merge!

Merge Sort

```
def merge_sort(lst):
    if len(lst) < 2: # Base case!
        return lst
    mid = len(lst) // 2
    left = merge_sort(lst[:mid]) #sort left
    right = merge_sort(lst[mid:]) #sort right
    return merge(left, right)</pre>
```

How to merge?

How to merge?

- Compare first element
- Take the smaller of the two
- Repeat until no more elements

Merging

```
def merge(left, right):
    results = []
    while left and right:
        if left[0] < right[0]:
            results.append(left.pop(0))
        else:
            results.append(right.pop(0))
    results.extend(left)
    results.extend(right)
    return results</pre>
```

Order of Growth?

 $O(n \log n)$ • Time: Worst Average $O(n \log n)$ $O(n \log n)$

Best

• Space: O(n)

No need to memorize

Sort Properties

In-place: uses a small, constant amount of extra storage space, i.e., O(1) space

Selection Sort: No (Possible)

Merge Sort: No (Possible)

Sort Properties

Stability: maintains the relative order of items with equal keys (i.e., values)

Selection Sort: Yes (maybe)

Merge Sort: Yes

How Many Ways to Sort? Too many. ©

Summary

- Python Lists are mutable data structures
- Searching
 - Linear Search
 - Binary Search: Divide-and-conquer
- Sorting
 - Selection Sort
 - Merge Sort: Divide-and-conquer + recursion
 - Properties: In-place & Stability

Ok, now I know how to guess a number quickly





Google?





How much data does Google handle?

- About 10 to 15 Exabyte of data
 - 1 Exabyte(EB)= 1024 Petabyte(PB)
 - 1 Petabyte(PB) = 1024 Terabytes(TB)
 - 1 Terabyte(PB) = 1024 Gigabytes(TB)
 - •= 4 X 256GB iPhone
- So Google is handling about 60 millions of iPhones

How fast is my desktop?

```
import time
                                                Return the time in
                                                seconds since the
def create list(n):
                                                epoch (1970/1/1
    start time = time.time()
                                                00:00) as a floating
    l = [i for i in range(n)]
                                                point number.
    end time = time.time()
    print('Duration = ' +
           str(end time-start time) + ' s')
create list(1000)
create list(1000*1000)
                                         Create 100M of
create list(1000*1000*100) <
                                         numbers, estimated
                                         to be 400MB of data
Output:
Duration = 0.0 s
Duration = 0.04769182205200195 s
Duration = 6.026865720748901 s
```

Let's calculate

- 400M of data needs 6 seconds
- 15 Exabyte of data needs how long?
 - 15 EB = 15 x 1024 x 1024 x 1024 x 1024 MB
 - To search through 15EB of data.....
 - •7845 years.....
- If we do it with Binary Search
 - $-\log_2(15EB) = 43 \text{ steps}!!!!!$

The Power of Algorithm

