
Installing Python Packages

- Python comes with built-in functions
- However, you need to manually install additional packages
 - In Assignment 0, the instructions asked you to install, imageio, numpy, etc
- In this lecture we will need "imageio"
 - To install "imageio" (or any other packages), go to cmd.exe
 - Type "pip install imageio"

- Provided you have your internet connected
- pip will download the package and install it for you

We have all these photo apps



https://www.everydayfamily.com/slideshow/10-hilariously-awful-photoshop-fails/





to me -

Hey, just wondering if you could edit this photo of me and my boyfriend. I was hoping you could make his corn dog whole again... with no bites taken out... thanks!





Done.





 To load an image, you can use the package "imageio"

```
cat_pic = imageio.imread('cute cat.jpg')
plt.imshow(cat_pic)
plt.show()
>>> type(cat_pic)
<class 'imageio.core.util.Array'>
>>> cat_pic.shape
(600, 600, 3)
>>>
```

import matplotlib.pyplot as plt

import imageio






Col 0 Col 1 Col 2 Col 599 600 x 600 pixel (R,G,B) (R,G,B) (R,G,B) (R,G,B) Row 0 -[R, G, B](R,G,B)Row 1 100 (R,G,B) Row 2 - 0 <= R,G,B <=255 200 300 400 500 >>> type(cat_pic) (R,G,B) (R,G,B) **Row 599** <class 'imageio.core.util.A</pre> 100 200 300 500 400 >>> cat pic.shape (600, 600, 3)

>>>

Remember sub-matrix, string slicing, etc.?


```
cat_pic2 = cat_pic[150:400,150:400]
plt.imshow(cat_pic2)
plt.show()
```



Broadcasting

```
cat_pic2 = cat_pic * [0, 1, 0]
plt.imshow(cat_pic2)
plt.show()
```


- every pixel multiply by
 - $-[R,G,B] \times [0,1,0] =$
 - $-[R \times 0, G \times 1, B \times 0]$
 - -[0, G, 0]



Array Broadcasting

Negative Image


```
cat_pic2 = 255 - cat_pic
plt.imshow(cat_pic2)
plt.show()
```




```
2D Array looping
```

```
for i in range(cat_pic.shape[0]):
    for j in range(cat_pic.shape[1]):
        if j < cat_pic.shape[1]/4:
            cat_pic[i][j] = 255 - cat_pic[i][j]</pre>
```

plt.imshow(cat_pic)
plt.show()




How to....?




Making a Mask

```
dim = cat_pic.shape
xcenter = dim[1]//2
ycenter = dim[0]//2

for i in range(cat_pic.shape[0]):
    for j in range(cat_pic.shape[1]):
        if (i-xcenter)**2 + (j-ycenter)**2 > (dim[0]//3)**2:
            cat_pic[i][j] = cat_pic[i][j]*0.3
```






Making a Mask

```
If the pixel is out
                                                    of the circle
dim = cat pic.shape
xcenter = dim[1]//2
ycenter = dim[0]//2
for i in range(cat pic.shape[0]):
    for j in range(cat pic.shape[1]):
        if (i-xcenter)**2 + (j-ycenter)**2 > (dim[0]//3)**2:
             cat pic[i][j] = cat pic[i][j]*0.3
                                                  Each color of the
```


pixel is divided by 2



imageio.imsave('file name.png', cat_pic)

Rotating an Image

```
from scipy import ndimage
rcat1 = ndimage.rotate(cat_pic, 45)
rcat2 = ndimage.rotate(cat_pic, 45, reshape=False)
plt.subplot(121)
plt.imshow(rcat1)
plt.subplot(122)
plt.imshow(rcat2)
plt.show()
```



Applying Filters


```
from scipy import misc, ndimage
import matplotlib.pyplot as plt
import numpy as np
cat_pic = misc.imread('cute cat.jpg')
blurred_cat_pic = ndimage.gaussian_filter(
    cat_pic, sigma=(9,9,1)
plt.imshow(blurred_cat_pic)
plt.show()
            Blending on x
                                        NO Blending on
                                        colors
                    Blending on y
```

Applying Filters

blurred_cat = ndimage.gaussian_filter(cat_pic, sigma=(9,9,1))

• sigma = (3,3,1)

• sigma = (9,9,1)




Edge Detection

Anyhow generate an image

```
img = np.zeros((256, 256))
img[64:-64, 64:-64] = 1


img = ndimage.rotate(img, 15, mode='constant')
img = ndimage.gaussian_filter(img, 1)
```



```
# Applying Sobel filter to the image
sx = ndimage.sobel(img, axis=0, mode='constant')
sy = ndimage.sobel(img, axis=1, mode='constant')
sob = np.hypot(sx, sy)
                                           Sobel filter
                             square
plt.subplot(121)
plt.imshow(img)
plt.axis('off')
plt.title('square')
plt.subplot(122)
plt.imshow(sob)
plt.axis('off')
plt.title('Sobel filter')
```

More in Numpy and Scipy

- Fourier Transform
- Uniform filter
- Histogram
- Laplace... etc



- More on
 - https://docs.scipy.org/doc/scipy/reference/ndimage.h tml

PILLOW

A Fork in PIL

PILLOW is a fork of PIL

PIL stands for Python Imaging Library

```
from PIL import Image

pic = Image.open('my flight delay.JPG')
pic.show()
```

Let's get the secret out

ST	FLIGH	T VIA/TO		GATE	STATUS	STD	FLIGHT	VIA/TO	GATE	STATUS	STD	FLIGHT	VIA/TO	GATE	STATUS
14:0			*//	1 43	JIATOS	16:55		U Chengdu	53	Delayed	17:45		(Hangzhou	59	e Weather Co
15:2		3 Nanjing		15	Last Call		87 MF14	AND DESCRIPTION OF THE PERSON	21	Delayed	17:45	TV9832	1gdu/linzhi	24	e Weather Co
		C Nanton		60	ed			(! Qingdao	58	Delayed	17:45	Z9334	bo/Qingdao	41	e Weather Co
15:30	ZH980	Wuxi		59	Last Call	17:00	Z	Ha	27	Delayed	17:50	A3272	nghai Hongqiao	42	Delayed
15:40	HU726	3 Hohhot		16	Delayed	17:00	48 ZH43	4 Chongqing	61A	Delayed	17:50	9C8776	nghai Hongqiao	49	e Weather Co
15:45)	(Huangsh	an	39	Gate	17:05	CZ6473	BiJie	41	Delayed	17:55	HU776	Nanjing	25	e Weather Co
15:55	HU7255	Zhengzh	ou	17	W	17:05	44 MF15	ie IN	50B	Delayed	17:55	Z9215	Nanjing	46	e Weather C
15:55	HU7326	Taiyuan		46	ed	17:10	10 MF19	e Shenyang	30	Delayed	18:00)	(Beijing	14	a Weather C
15:55	1076	Wuxi		78	ed	17:15	Z	l- Hefei	32	Delayed	18:00)	nghai Pudong	76	a Weather C
16:00	314	Beijing		14	ed	17:20	14 ZH43	31 Chengdu	35	Delayed	18:0		Hangzhou	61A	
16:00	672	Tianjin		26	ed	17:20	MU575	581	36	Delayed	18:0		3zhou/Shenyar		e Weather
16:05	010	1		32	≥d	17:25	HU7708	Beijing	20	Delayed		0 021	Chongqing	18	THE RESERVE AND ADDRESS OF THE PERSON NAMED IN
16:05				61A	ed	17:25	HU7715	Jinan	25	Delayed			70 Chengdu	78	The second second
16:20	454			71	ed	17:25	BK2860	Tianjin	54	Delayed	18:1		ngzhou/Hohho		William William
16:25	053	Beijing		62B	ed	17:30	CZ6913	Nanjing	34	Cancelled	18:1			72	A STATE OF THE PARTY.
16:30	ZH9877	Hangzhou		54	ed	17:30	FM9334	l iao	51	Delayed	18:		hen/Shangha		
16:30 3	50 CZ97		Shi	44	ed	17:30	CZ8649	Xining	28	Delayed	18:		28 Dalian	3	Name and Address of the Owner, where
16:35	3U8784	Chongqin	9	48	A	17:35		35 Hangzhou	38	Cancelled			MU3 ing/Nanyuan		Glad Art on City
16:35	KN5858	Nanyuan		62A	elled	17:35	2	!H Nanjing	77	Cancelled			111 Yichun/Beijii	100	7
16:35	CA4846	Yantai		50A	ed be	17:40		Chongqing	62A		18		Guiyang		22 e Weath
16:40 15	09	Nanchang		61B	∍d	17:40	91 MF1	0E Beijing	63	Delayed	The state of		5354 nghai Hongo	No. of Contract of	Cancel
	Z8250		Ch	29	∍d	17:40	HU7067	7 Xuzhou	44	Delayed	18	:35	CZ Chengdu		63 e Weat

```
from PIL import Image
from PIL.ExifTags import TAGS, GPSTAGS
pic = Image.open('my flight delay.JPG')
def get exif data(image):
    exif data = {}
    info = image. getexif()
    if info:
        for tag, value in info.items():
            decoded = TAGS.get(tag, tag)
            if decoded == "GPSInfo":
                gps data = {}
                for t in value:
                    sub decoded = GPSTAGS.get(t, t)
                    gps data[sub decoded] = value[t]
                exif data[decoded] = gps data
            else:
                exif data[decoded] = value
    return exif data
print(get exif data(pic)['GPSInfo'])
pic.show()
```

PILLOW

Cannot escape!

```
{'GPSLatitudeRef': 'N', 'GPSLatitude': ((22, 1),
    (38, 1), (1484, 100)), 'GPSLongitudeRef': 'E', 'G
PSLongitude': ((113, 1), (48, 1), (2726, 100)), '
GPSAltitudeRef': b'\x00', 'GPSAltitude': (2761, 2
25), 'GPSTimeStamp': ((10, 1), (34, 1), (1420, 10
0)), 'GPSSpeedRef': 'K', 'GPSSpeed': (0, 1), 'GPS
ImgDirectionRef': 'T', 'GPSImgDirection': (11511,
542), 'GPSDestBearingRef': 'T', 'GPSDestBearing':
    (11511, 542), 'GPSDateStamp': '2017:07:17', 'GPSH
PositioningError': (1414, 1)}
```

PILLOW

```
from PIL import Image
from PIL import ImageFilter
pic = Image.open('cute cat.jpg')

pic.show()

blurred_pic = pic.filter(ImageFilter.BLUR)
blurred_pic.show()

sharpen_pic = pic.filter(ImageFilter.SHARPEN)
sharpen_pic.show()
```



Original



Blurred



Sharpen

Copy And Paste

from PIL import Image

Copy (crop) the part of the picture

```
pic = Image.open('cute cat.JPG')
part = pic.crop((200,200,400,400))
```

```
pic.paste(part, (0, 400))
pic.show()
```

Paste it on the position (0,400)



```
from PIL import Image, ImageDraw, ImageFont

pic = Image.open('cute cat.JPG')

draw = ImageDraw.Draw(pic)
draw.ellipse((20, 30, 160, 120), fill='blue')
draw.text((60,65),'Cute Cat', fill = 'gray')
```

pic.show()



Other operations

- resize
- rotation/flipping
- traspose
- Drawing shapes
- etc. etc..



Other Than Scipy and Numpy

Faces found

- OpenCV
- skimage

Orignal Image

– scikit-image

