

Word Equations as Abstract Domain for String Manipulating Programs

*Presented by:
Alexei Lisitsa*

*Antonina Nepeivoda
Program Systems Institute of RAS
a_nevod@mail.ru*

Abstract Program Properties

- We are interested in satisfiability of program properties w.r.t. some predicate set Δ over program data. The set Δ is to be expressed in a chosen language \mathcal{L}_Δ .
- Then any program run can be considered in terms of abstracted structures w.r.t. preserving properties in Δ , i.e. **abstracted** to \mathcal{L}_Δ .


Example

- Checking division by 0 \Rightarrow
 $\mathcal{L}_\Delta = \{\text{IsZero}, \text{IsNonZero}, \text{Unknown}, \text{Error}\}.$
- Checking overflows in arithmetics $\Rightarrow \mathcal{L}_\Delta$ can be an interval predicate set
 $\{(x \in (a, b)) \mid a, b \in \mathbb{R} \cup \{-\infty, \infty\}\} \cup \{\text{Error}\}.$



Function Lifting

- Every function $f : S \rightarrow S$, where S is the program data domain, is to be lifted to the abstract values domain.
- The lifted image of f (denoted f_Δ) must respect the original function f properties.




Galois Connection in Abstract Interpretation


Let S and \mathcal{L}_Δ be sets of concrete and abstract data values. We say that $a \propto \rho$ iff $a \in S$ satisfies the predicate $\rho \in \mathcal{L}_\Delta$.

The two functions are crucial to analyse the abstract properties:

- **Abstraction** $\alpha : 2^S \rightarrow \mathcal{L}_\Delta$;
 $\alpha(A) = \text{most specific predicate } \rho \in \mathcal{L}_\Delta \text{ s. t. } \forall a (a \in A \Rightarrow a \propto \rho)$;
- **Concretisation** $\gamma : \mathcal{L}_\Delta \rightarrow 2^S$;
 $\gamma(\rho) = \{a \in S \mid a \propto \rho\}$.



$$A \subseteq \gamma(\alpha(A))$$



$$\rho \preceq \alpha(\gamma(\rho))$$

Such a relation between any two sets is called a **Galois connection**.




Partial Order on \mathcal{L}_Δ and Lattice Axioms

\mathcal{L}_Δ is equipped by partial order \preceq and a pair of functions $\alpha : 2^S \rightarrow \mathcal{L}_\Delta$, $\gamma : \mathcal{L}_\Delta \rightarrow 2^S$ **over-approximate** elements of 2^S w.r.t. \preceq and \subseteq .

- $A \subseteq \gamma(\alpha(A))$;
- $\rho \preceq \alpha(\gamma(\rho))$.

Collecting semantics

Given $\rho_1, \rho_2 \in \mathcal{L}_\Delta$, a joined value ρ' s.t. $\rho_1 \preceq \rho'$ and $\rho_2 \preceq \rho'$ is to be unique $\Rightarrow \rho'$ is **a unique least upper bound** of ρ_1, ρ_2 .



An ordering with multiple least upper bounds cannot produce an unambiguous semantics of the joined values.



Partial Order on \mathcal{L}_Δ and Lattice Axioms

\mathcal{L}_Δ is equipped by partial order \preceq and a pair of functions $\alpha : 2^S \rightarrow \mathcal{L}_\Delta$, $\gamma : \mathcal{L}_\Delta \rightarrow 2^S$ **over-approximate** elements of 2^S w.r.t. \preceq and \subseteq .

- $A \subseteq \gamma(\alpha(A))$;
- $\rho \preceq \alpha(\gamma(\rho))$.

In a **lattice**, any two elements ρ_1, ρ_2 of \mathcal{L}_Δ have a supremum ($\rho_1 \vee \rho_2$) and an infimum ($\rho_1 \wedge \rho_2$) w.r.t. the partial order \preceq .

Lattice Axioms

- $(x \vee (x \wedge y) = x) \ \& \ (x \wedge (x \vee y) = x)$;
 - $(x \vee y = y \vee x) \ \& \ (x \wedge y = y \wedge x)$;
 - $(x \vee (y \vee z) = (x \vee y) \vee z) \ \& \ (x \wedge (y \wedge z) = (x \wedge y) \wedge z)$.
-




Existing Lattices for Strings

Let Σ be a letter alphabet, $S \subseteq \Sigma^*$.

- The simplest lattice over predicates $\{X \doteq \xi \mid \xi \in \Sigma^*\}$ (denoted \mathcal{Latt}_{Eq}). Finite height, imprecise.
- | | | |
|--------------------------------------|---|--|
| mapping to
commutative
algebra | { | <ul style="list-style-type: none">• Lattice tracking string lengths: $\{ X = n \mid n \in \mathbb{N}\}$.• Lattice tracking letter occurrences in strings:
$\{(X _q > 0) \mid q \in \Sigma\}$. |
| incomplete | | <ul style="list-style-type: none">• Lattice tracking prefixes and suffixes of strings:
$\{\exists \tau_1, \tau_2 (X = \xi_1 \tau_1) \ \& \ (X = \tau_2 \xi_2) \mid \xi_i \in \Sigma^*\}$.• Lattice checking membership in regular languages:
$\{X \in \tau \mid \tau \text{ is a regular expression}\}$.• Lattice tracking program-specific predicates
(JSAI, Kashyap et al, 2014).
Desirable to be parameterizable with predicates. |



Regular Languages Lattice



requires **widening** { Both infinite ascending chains (e.g. $a, a|a^2, \dots$)
and infinite descending chains (e.g. $a^*, (a^2)^*, \dots$).



The Research Questions Arise

- Find an expressible language describing string predicates set, whose elements form a lattice of string abstract values:
 - being complete (and, moreover, finite-height);
 - extending the trivial lattice \mathcal{Latt}_{Eq} considered above;
 - capturing non-commutative string properties.
- Improve flexibility of the given language set using lattice operations.

We suggest **a word equation language** as a candidate for such a set of abstract values.



Word Equations by Example

Given two alphabets:

- Σ is a set of constant (e.g. lowercase Latin) characters;
- \mathcal{V} is a set of variables (e.g. capitalized Latin characters).

Consider two **constant words**:

aababaa

aababaa



Word Equations by Example

Given two alphabets:

- Σ is a set of constant (e.g. lowercase Latin) characters;
- \mathcal{V} is a set of variables (e.g. capitalized Latin characters).

Replace some of occurrences of their subwords with variables:

$$\begin{array}{ccc} aababaaba & & aabababaa \\ a^2 \mapsto X, & a^2ba \mapsto Y, & b \mapsto Z \\ XZabY & & YbaZX \end{array}$$



Word Equations by Example

Given two alphabets:

- Σ is a set of constant (e.g. lowercase Latin) characters;
- \mathcal{V} is a set of variables (e.g. capitalized Latin characters).

Insert the equality sign between the resulted words:

$$\begin{array}{ccc} aabababaa & & aabababaa \\ a^2 \mapsto X, & a^2ba \mapsto Y, & b \mapsto Z \\ XZabY & & YbaZX \\ XZabY & \doteq & YbaZX \end{array}$$



Word Equations by Example

Given two alphabets:

- Σ is a set of constant (e.g. lowercase Latin) characters;
- \mathcal{V} is a set of variables (e.g. capitalized Latin characters).

$$\begin{array}{l} aababaaaba \qquad aabababaa \\ a^2 \mapsto X, \quad a^2ba \mapsto Y, \quad b \mapsto Z \\ XZabY \quad \doteq \quad YbaZX \end{array}$$

We have obtained a **word equation**.

A **solution** of the equation is the following **substitution**:

$$X \mapsto a^2, \quad Y \mapsto a^2ba, \quad Z \mapsto b$$



Word Equations by Example

Given two alphabets:

- Σ is a set of constant (e.g. lowercase Latin) characters;
- \mathcal{V} is a set of variables (e.g. capitalized Latin characters).

$$\begin{array}{l} \text{aabab} \text{aaba} \qquad \text{aabababaa} \\ a^2 \mapsto X, \quad a^2ba \mapsto Y, \quad b \mapsto Z \\ XZabY \quad \doteq \quad YbaZX \end{array}$$

We have obtained a **word equation**.

A **solution** of the equation is the following **substitution**:

$$X \mapsto a^2, \quad Y \mapsto a^2ba, \quad Z \mapsto b$$

Another **solution** of the equation :

$$X \mapsto \varepsilon, Y \mapsto a, Z \mapsto \varepsilon, \text{ where } \varepsilon \text{ is the empty word.}$$



Word Equations

Given a finite alphabet Σ of constant characters and an alphabet \mathcal{V} of variables; ε stands for the empty word. Small Greek letters stand for words in Σ^* .

Definition

A **word equation** is an equation of the form $\Psi \doteq \Phi$, where $\Psi, \Phi \in \{\Sigma \cup \mathcal{V}\}^*$. One may see the equation as a pair $\langle \Phi, \Psi \rangle$.

Given a word equation $\Psi \doteq \Phi$, where $\Psi, \Phi \in \{\Sigma \cup \mathcal{V}\}^*$. A **solution** of the equation is a **morphism** $\sigma : \{\Sigma \cup \mathcal{V}\}^* \rightarrow \Sigma^*$ s.t. $\Psi\sigma = \Phi\sigma$, where the morphism σ respects the concatenation operation, and $\forall a \in \Sigma (a\sigma = a)$.



Word Equations in Program Analysis

How do word equations naturally arise in the context of program analysis?

The variables X, X_1, Y, U, Z range over strings. Their values may be completely unknown or partially known in compile (analyse) time.

$$X \doteq UbaYabZ$$

```
if ( includes(X, 'ba' + Y + 'ab') )  
  then { ..... }  
  else { ..... }
```

$$aX_1 \doteq X_1a$$

```
if ( startsWith(X,'a') && endsWith(X,'a') )  
  then { X1 := substring(X, 1, length(X))  
        X2 := substring(X, 0, length(X)-1)  
        if (X1 == X2) return true; }  
  }
```



Word Equations in Program Analysis

Example source: P.A. Abdulla, M.F. Atig, Y. Chen, B.P. Diep, L. Holik, A. Rezine, Ph. Rümmer: Flatten and conquer: a framework for efficient analysis of string constraints, PLDI, 2017, ACM, pp. 602–617.

Initial program	Simplified program
<pre>main(X,Y,Z) = eq(g(Z)++X, 'a'++g(Z)++Y); g('i'++X) = 'a'++g(X)++'b'; g('s'++X) = g(X)++'b'; g(ε) = ε; eq(X, X) = true; eq(X, Y) = false;</pre>	<pre>main'(X,Y,'i'++Z) = false; main'(X,Y,'s'++Z) = false; main>('a'++Y,Y,ε) = true; main'(X,Y,ε) = false;</pre>


- Quadratic equation $WX \doteq aWY$ ($W := g(Z)$) appears as a constraint generated by rule `eq(X, X) = true`, and its solution set includes $W \in a^*$, which is incompatible with any trace of g -computation except the trivial one.



String Solvers

In recent years:


- Many studies are conducted on developing automated reasoning tools capable of **proving or disproving statements involving words**.
 - Their task is to automatically determine the satisfiability of that formula.



String Solvers


- Some string solving tools using word equations as constraint sets:

— HAMPI	bounded
— Norn	acyclic
— OSTRICH	straight-line
— Sloth	straight-line & acyclic
— Woorpje	bounded
— CertiStr	acyclic
— MSCP-A	regularly-cyclic
— CVC5, Z3Str3	acyclic & bounded
— Z3-Trau	chain-free



\mathcal{WL} vs. \mathcal{RL}

The word equation language \mathcal{WL} vs. the regular expression language \mathcal{RL} : intersect but are not subsets each of other:



- There is no word equation with solution-set represented by $(a|b)^*$ over the alphabet $\{a, b, c\}$.
 - J. Karhumäki, F. Mignosi, W. Plandowski. The expressibility of languages and relations by word equations. Journal of the ACM (JACM), 47(3), pp: 483-505, (2000).



Unary Quantifier-Free Predicates

Given a predicate P expressed by a word equation E , let us assume that E is a **one-variable word equation**.

- What string properties can be expressed by such equations?
- How can be such equations **normalized**, in order to represent language properties consistently?

Non-trivial question: *Can the solution-set be constructively described simpler as compared to the description provided by the original equation itself?*

Equations $aX \doteq Xa$, $aaX \doteq Xaa$, and $aXX \doteq XXa$ all have the same solution set a^* .



One-Variable Equations*

Theorem (Nowotka-Saarela, 2018).

Every one-variable word equation has either infinitely many or at most three solutions.

Definition

A word $\eta \in \Sigma^+$ is said to be **primitive**, if for any $\xi \in \Sigma^*$, $n \in \mathbb{N}$ s.t. $\eta = \xi^n$ the equality $n = 1$ holds.

If an X -variable word equation has infinitely many solutions, then its whole solution-set is described with the fractional powers

$$\left\{ \underbrace{(\xi\zeta)}_{\text{primitive word}}^n \xi \mid n \in \mathbb{N} \right\}$$

Hence, such an equation can be **normalised** to $\underbrace{\xi\zeta}_{\text{primitive}} X \doteq X\zeta\xi$.



Join and Meet for One-Variable Equations

Given the language

$$WL_0 = \left\{ \perp, \top, \{X \doteq \zeta\}, \{\xi_1 \xi_2 X \doteq X \xi_2 \xi_1\} \mid \zeta, \xi_i \in \Sigma^* \text{ \& } \xi_1 \xi_2 \text{ is primitive} \right\}$$

and the order \preceq induced by the solution set inclusion, we are required to check that the following situation **is impossible**:

$$\begin{array}{ccc} \xi_5 \xi_6 X \doteq X \xi_6 \xi_5 & & \xi_3 \xi_4 X \doteq X \xi_4 \xi_3 \\ \swarrow & & \searrow \\ X \doteq \xi_2 & & X \doteq \xi_1 \end{array}$$

If supremums and infimums are uniquely determined, then WL_0 is a lattice w.r.t. \preceq .



Base Lattice WL_0 and its Sublattices

Lemma


Normalised one-variable equations with infinite solution sets and trivial equations of the form $X \doteq \eta$, together with \top , \perp form a complete lattice, that is:

- Given any constant words ξ_1, ξ_2 , at most one infinite-solution one-variable word equation in the normal form is satisfied by both.
- Given any two distinct normalised infinite-solution equations $\xi_1\xi_2X \doteq X\xi_2\xi_1$, $\xi_3\xi_4X \doteq X\xi_4\xi_3$, at most one word in Σ^* satisfies both.

Base lattice WL_0 includes all elements $\{X \doteq \eta\}$, $\{\xi_1\xi_2X \doteq X\xi_2\xi_1\}$ (where $\xi_1\xi_2$ is primitive); its finite sublattices $WL_0(\mathcal{P})$ depend on programs \mathcal{P} , i.e. on the finite set of strings explicitly occurring in \mathcal{P} .



A Lattice Based on $\{\varepsilon, a, a^2, b, ab, aba\}$



- A non-trivial one-variable word equation with an infinite solution set can be reduced to an equivalent one

$$\underbrace{\eta_1 \eta_2 X \doteq X \eta_2 \eta_1}_{\text{normal-form condition}} \quad (\eta_1 \eta_2 \text{ is primitive}).$$

- $((\eta_1 \eta_2)^n X \doteq X (\eta_2 \eta_1)^n) \Leftrightarrow (\eta_1 \eta_2 X \doteq X \eta_2 \eta_1) \quad (n \geq 1)$, hence the widening problem is resolved.



Lifting JS String Operations to Abstract Domain

Simple example — string concatenation in JavaScript. We assume that $x \neq \perp, y \neq \perp$, otherwise concatenation results in an error.

$x + y =$

$$\left\{ \begin{array}{l} \{X \doteq \xi_1 \xi_2\}, \text{ if } x = \{X \doteq \xi_1\}, y = \{X \doteq \xi_2\}; \\ \{ \xi_4 \xi_5 X \doteq X \xi_5 \xi_4 \}, \text{ if } x = \{X \doteq \xi_1\} \ \& \ y = \{ \xi_2 \xi_3 X \doteq X \xi_3 \xi_2 \} \\ \quad \text{and } \xi_4, \xi_5 \text{ are s.t. } \xi_5 \xi_4 = \xi_3 \xi_2 \text{ and } \exists n (\xi_1 \xi_2 = (\xi_4 \xi_5)^n \xi_4); \\ \{ \xi_4 \xi_5 X \doteq X \xi_5 \xi_4 \}, \text{ if } x = \{ \xi_1 \xi_2 X \doteq X \xi_2 \xi_1 \} \ \& \ y = \{X \doteq \xi_3\} \\ \quad \text{and } \xi_4, \xi_5 \text{ are s.t. } \xi_4 \xi_5 = \xi_1 \xi_2 \text{ and } \exists n (\xi_1 \xi_3 = (\xi_4 \xi_5)^n \xi_4); \\ \{ \xi_5 \xi_6 X \doteq X \xi_6 \xi_5 \}, \text{ if } x = \{ \xi_1 \xi_2 X \doteq X \xi_2 \xi_1 \} \ \& \ y = \{ \xi_3 \xi_4 X \doteq X \xi_4 \xi_3 \} \\ \quad \text{and } \xi_2 \xi_1 = \xi_3 \xi_4 \\ \quad \text{and } \xi_5, \xi_6 \text{ are s.t. } \xi_5 \xi_6 = \xi_1 \xi_2 \text{ and } \exists n (\xi_1 \xi_3 = (\xi_1 \xi_2)^n \xi_5); \\ \top, \text{ otherwise.} \end{array} \right.$$

Below we consider in details the only non-trivial case, when x and y are **infinite-solution** equations.



Lifting JS String Operations to Abstract Domain

$x + y =$

$$\left\{ \begin{array}{l} \dots \\ \{ \xi_5 \xi_6 X \doteq X \xi_6 \xi_5 \}, \text{ if } x = \{ \xi_1 \xi_2 X \doteq X \xi_2 \xi_1 \} \ \& \ y = \{ \xi_3 \xi_4 X \doteq X \xi_4 \xi_3 \} \\ \hspace{15em} \text{and } \xi_2 \xi_1 = \xi_3 \xi_4 \\ \text{and } \xi_5, \xi_6 \text{ are s.t. } \xi_5 \xi_6 = \xi_1 \xi_2 \text{ and } \exists n (\xi_1 \xi_3 = (\xi_1 \xi_2)^n \xi_5); \\ \top, \text{ otherwise.} \end{array} \right.$$

Where do ξ_5, ξ_6 come from?

$$\begin{array}{c} \exists \xi_5, \xi_6 \forall m, n \exists k \underbrace{((\xi_1 \xi_2)^m \xi_1)}_{x \text{ values}} \underbrace{(\xi_3 \xi_4)^n \xi_3}_{y \text{ values}} = \underbrace{(\xi_5 \xi_6)^k \xi_5}_{x+y \text{ values}} \\ \Downarrow \\ (\xi_1 \xi_2 = \xi_5 \xi_6) \ \& \ \forall n \exists k (\underbrace{\xi_1 (\xi_3 \xi_4)^n \xi_3}_{y \text{ values}} = \underbrace{\xi_1 (\xi_2 \xi_1)^k \xi_2 \xi_5}_{(\xi_5 \xi_6)^{k+1}}) \end{array}$$



String Morphisms and Fixpoints

Classical Lemma

If σ is a solution to equation $\Psi \doteq \Phi$, and h is a morphism, then $h \circ \sigma$ is a solution to $h(\Psi) \doteq h(\Phi)$.

Corollary: string morphisms $h : \Sigma \rightarrow \Sigma^*$, extended to WL_0 elements by normalising the morphic images of the equation sides, are **monotone lattice mappings**. Namely,


$$(E_1 \preceq E_2) \Rightarrow (h(E_1) \preceq h(E_2)).$$

By Knaster–Tarski theorem, string morphisms' fixpoints form a complete sublattice of WL_0 .



Expressibility via Transformations

Given a monotone mapping h , we can track properties expressed by inverse morphisms of concretisations of the abstract values, refining expressibility of the basic abstract domain.




There $h^{-1} : 2^S \rightarrow 2^S$ is defined as usual:

- $\forall s \in S \left(h^{-1}(\{s\}) = \{s' \mid h(s') = s\} \right);$
- $h^{-1}(\mathcal{M}_1 \cup \mathcal{M}_2) = h^{-1}(\mathcal{M}_1) \cup h^{-1}(\mathcal{M}_2).$




Fixpoint Example



The sublattice generated by the morphism $h(x) = a$ tracks string lengths in a given program.




Expressibility of Fixpoint Lattices



- $h_{\Sigma \rightarrow a} \stackrel{\Delta}{=} a$ a morphism that maps a to itself and other letters to ε ;
- $h_{\Sigma \setminus \Sigma' \rightarrow \varepsilon} \stackrel{\Delta}{=} \varepsilon$ a morphism that maps all the letters from Σ' to a and all the other letters to ε .
- Let $\Sigma = \Sigma_1 \cup \Sigma_2 \cup \dots \cup \Sigma_n$, where $\forall i, j (i \neq j \Rightarrow \Sigma_i \cap \Sigma_j = \emptyset)$.
 $h_{\Sigma_1, \dots, \Sigma_k} \stackrel{\Delta}{=} a$ a morphism that maps all the elements of the disjoint sets to a single letter.



Inverse Images of String Morphisms



An inverse mapping of a morphism h is **border-preserving** wrt \mathcal{L} , if for any element $\{\xi_1 \xi_2 X \doteq X \xi_2 \xi_1\}$ of \mathcal{L} and for any $a \in \Sigma$, $h(a)$ either contains no border of $\xi_1 \xi_2 X \doteq X \xi_2 \xi_1$, or is equal to ξ_2 , and $\xi_1 = \varepsilon$.

Lemma


Given lattice $WL_0(\mathcal{P})$ and a string morphism h satisfying the conditions above, for any order induced on Σ , h_{\min}^{-1} is a lattice morphism.



Expressibility of Inverse Mappings

Let RESERVED be a set of reserved words v_i (keywords, constants, etc), s.t. morphism $h_{\{a_i \rightarrow v_i\}}$ mapping fresh letters from Σ' to v_i is border-preserving.

Then an inverse image lattice $h_{\{a_i \rightarrow v_i\}}^{-1}$ can be used to track occurrences of the keywords inside strings.



Word Equations in Abstract Interpretation (Program Analysis)

Simple Example: abstract interpretation over $WL_0(\mathcal{P})$ -lattice shows the sanitization given in line 5 is sound (line 7 is unreachable).

```
1  z = ξ;  
2  x = '<script' + z;  
3  if (x != z + z) {  
4      x = x + x };  
5  replaceAll(x, 'ip', 'ipv4');  
6  if (contains(x, 'script')) {  
7      return 'Possible code injection'; }
```



Word Equations in Abstract Interpretation (Program Analysis)

The sanitization given in line 5 is sound.

1	$z = \xi;$	$z \mapsto \{X \doteq \xi\}$
2	$x = \text{'<script' + z};$	$x \mapsto \{X \doteq \eta\}$
3	$\text{if } (x \neq z + z) \{$	(does not change)
4	$x = x + x \};$	$\{X \doteq \eta\} \vee \{X \doteq \eta + \eta\}$
	$= \{prm(\eta)X \doteq X prm(\eta)\};$	$x \mapsto \{prm(\eta)X \doteq X prm(\eta)\}$
5	$\text{replaceAll}(x, \text{'ip'}, \text{'ipv4'});$	$x \mapsto^* \{\eta' X \doteq X \eta'\}$
6	$\text{if } (\text{contains}(x, \text{'script'})) \{$	(never holds for the abstract value of x)
7	$\text{return 'Possible code injection';}$	(is unreachable)

- $prm(\eta)$ is a primitive* root of η ;
- $\eta = \text{'<script' + } \xi$; $\eta' = \text{replaceAll}(prm(\eta), \text{'ip'}, \text{'ipv4'})$.
- predicate $\text{contains}(x, \text{'script'})$ fails for any value of X satisfying $\eta' X \doteq X \eta'$.



Conclusion

- An infinite-solution subset of one-variable word equations together with predicates $\mathcal{Latt}_{Eq} = \{X \doteq \xi\}$ form a finite-height lattice WL_0 . Sublattices of the lattice WL_0 can be used for abstract interpretation of string-manipulating programs.
- Monotone lattice mappings by means of string morphisms and special cases of inverses of string morphisms generate fixpoint lattices upon WL_0 , which can track additional program properties, non-expressible in the word equations language directly.



- A word-equation-lattice-based framework for analysing real-world string-manipulating programs.
- Lattice modifications capturing relations between variable values.

A simple instance:

$$\left\{ \text{WL}_0(\mathcal{P})[X] \times \text{WL}_0(\mathcal{P})[Y] \times \langle \top, \perp, \{XY \doteq YX\} \rangle \right\}.$$



Thanks for Attention

- Any questions?



\mathcal{WL} — existential string theory

(concatenation + equality = word equations).

Theory	Replace All (Const Args)	letter count	length count	\mathcal{RL}	Complexity
$\mathcal{WL} + \mathcal{RL}$	✗	✗	✗	✓	PSPACE
$\mathcal{WL} + \text{len}$	✗	✗	✓	✗	???
$\mathcal{WL} + \text{count}$	✗	✓	✗	✗	Undec.
$\mathcal{WL} + \text{repl}$	✓	✗	✗	✗	Undec.



References-I

1. P.A. Abdulla, et al.: String Constraints for Verification. In: CAV 2014. LNCS, Vol. 8559, pp. 150–166 (2014).
2. P.A. Abdulla, et al.: Norn: an SMT solver for string constraints. In: CAV 2015. LNCS, vol. 9206, pp. 462–469 (2015).
3. P.A. Abdulla, et al.: Flatten and conquer: a framework for efficient analysis of string constraints, PLDI, 2017, ACM, pp. 602–617.
4. H. Barbosa, et al.: CVC5: a versatile and industrial-strength SMT solver. In: TACAS 2022. LNCS, vol. 13243, pp. 415–442, (2022).
5. J. Berstel, and J. Karhumaki. Combinatorics on words: a tutorial. Bulletin of the EATCS 79.178 (2003): 9.
6. E. Czeizler, The non-parametrizability of the word equation $xyz = zvx$: a short proof. Theoret. Comput. Sci. 345(2–3), 296–303 (2005).
- ...



References-II

7. T. Chen, M. Hague, A.W. Lin, P. Rummer, Z. Wu: Decision procedures for path feasibility of string-manipulating programs with complex operations. *Proc. ACM Program. Lang.* 3(POPL), 1–30 (2019).
8. J.D. Day, et al.: On solving word equations using SAT. In: *RP 2019. LNCS*, vol. 11674, pp. 93–106 (2019).
9. J.D. Day. Word Equations in the Context of String Solving. In *Int. Conf. on Developments in Language Theory*. 2022, pp. 13–32.
10. L. Holik, P. Janku, A.W. Lin, P. Rummer, T. Vojnar: String constraints with concatenation and transducers solved efficiently. In: *Proc. of the ACM on Programming Languages*, vol. 2, pp. 1–32 (2018).
11. L. Ilie, W. Plandowski. Two-variable word equations. *RAIRO-Theoret. Inform. Appl.* 34(6), 467–501 (2000).
- ...



References-III

12. A. Jez. Recompression: a simple and powerful technique for word equations. J. ACM (JACM) 63(1), 1–51 (2016).
13. S. Kan, A.W. Lin, P. Rummer, M. Schrader: CertiStr: a certified string solver. In: Proc. of the 11th ACM SIGPLAN International Conf. on Certified Programs and Proofs, pp. 210–224 (2022).
14. J. Karhumaki, F. Mignosi, and W. Plandowski, The expressibility of languages and relations by word equations, J. ACM, vol. 47, no. 3, pp. 483–505, May 2000.
15. A. Kiezun, V. Ganesh, S. Artzi, P.J. Guo, P. Hooimeijer, M.D. Ernst: HAMPI: a solver for word equations over strings, regular expressions, and context-free grammars. ACM Trans. Softw. Eng. Methodol. (TOSEM) 21(4), 1–28 (2013).
- ...



References-IV

16. Yu. I. Khmelevskii, Equations in a free semigroup, Trudy Mat. Inst. Steklov., 107, 1971, 3–288; Proc. Steklov Inst. Math., 107 (1971), pp: 1–270.
17. N.K. Kosovskij, Some properties of solutions to equations in a semigroup (in Russian), Zap. Nauch. Sem. LOMI, vol. 32, pp. 21–28, 1972. Available at <https://www.mathnet.ru/rus/zns12560>
18. G.S. Makanin, The problem of solvability of equations in a free semigroup, Math. USSR-Sb., 32:2 (1977), pp: 129–198.
19. F. Mora, M. Berzish, M. Kulczynski, D. Nowotka, V. Ganesh: Z3Str4: a multi-armed string solver. In: FM 2021. LNCS, vol. 13047, pp. 389–406, (2021).



References-V

- 20. D. Nowotka, and A. Saarela. An optimal bound on the solution sets of one-variable word equations and its consequences. *SIAM Journal on Computing* 51.1 (2022): pp: 1-18.
- 21. W. Plandowski. An efficient algorithm for solving word equations. In: *Proc. of the Thirty-Eighth Annual ACM Symposium on Theory of Computing*, pp. 467–476 (2006).
- 22. W. Plandowski. An efficient algorithm for solving word equations. *Theoretical Computer Science Volume 792*, 5 November 2019, Pages 20-61.
- 23. A.A. Razborov. On systems of equations in free groups. In: *Combinatorial and Geometric Group Theory*, pp. 269–283 (1993).

