

# Database Management System Lab

Name: Tonmoy Biswas

Roll No: 002110501133

Class: BCSE 3<sup>rd</sup> Year 2<sup>nd</sup> Sem

Section: A3

Assignment No: 4

Problem Statement:

Consider the following tables:

Table: ORDERMAST

Structure:

ORDER\_NO CHAR(5) primary key

ORDER\_DT DATE

Table: ORDERDETAILS

Structure:

ORDER\_NO CHAR(5)

ITEM\_NO CHAR(5)

QTY NUMBER

ORDER\_NO + ITEM\_NO is primary key

Table: DELIVERYMAST

Structure:

DELV\_NO CHAR(5) primary key

ORDER\_NO CHAR(5)

DELV\_DT DATE

Table: DELIVERY\_DETAILS

Structure:

DELV\_NO CHAR(5)

ITEM\_NO CHAR(5)

QTY NUMBER

DELV\_NO+ITEM\_NO is primary key

Write a PL/SQL block which accepts two dates & find the information of the pending delivery for the orders placed between the two dates supplied by the user. Note, an order can have request for multiple items. Against an order, multiple delivery with partial shipment is possible.

Solution:

Here's a PL/SQL block that accepts two dates and finds the information of the pending deliveries for the orders placed between those two dates:

DECLARE

    v\_start\_date DATE := TO\_DATE('&start\_date', 'YYYY-MM-DD'); -- Assuming you'll provide the start date in 'YYYY-MM-DD' format

    v\_end\_date DATE := TO\_DATE('&end\_date', 'YYYY-MM-DD'); -- Assuming you'll provide the end date in 'YYYY-MM-DD' format

BEGIN

```

FOR order_rec IN (
    SELECT DISTINCT om.ORDER_NO, om.ORDER_DT
    FROM ORDERMAST om
    WHERE om.ORDER_DT BETWEEN v_start_date AND v_end_date
) LOOP
    -- Display order information
    DBMS_OUTPUT.PUT_LINE('Order Number: ' || order_rec.ORDER_NO);
    DBMS_OUTPUT.PUT_LINE('Order Date: ' || TO_CHAR(order_rec.ORDER_DT, 'YYYY-MM-DD'));

    -- Fetch pending delivery information
    FOR delivery_rec IN (
        SELECT dd.DELV_NO, dd.ITEM_NO, dd.QTY
        FROM DELIVERY_DETAILS dd
        INNER JOIN DELIVERYMAST dm ON dd.DELV_NO = dm.DELV_NO
        WHERE dm.ORDER_NO = order_rec.ORDER_NO
        AND dm.DELV_DT IS NULL -- Check for pending deliveries
    ) LOOP
        -- Display pending delivery details
        DBMS_OUTPUT.PUT_LINE('Pending Delivery Number: ' || delivery_rec.DELV_NO);
        DBMS_OUTPUT.PUT_LINE('Item Number: ' || delivery_rec.ITEM_NO);
        DBMS_OUTPUT.PUT_LINE('Quantity: ' || delivery_rec.QTY);
        DBMS_OUTPUT.PUT_LINE('-----');
    END LOOP;

    DBMS_OUTPUT.PUT_LINE("");
END LOOP;

EXCEPTION
    WHEN NO_DATA_FOUND THEN
        DBMS_OUTPUT.PUT_LINE('No pending deliveries found for the specified period. ');
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);

```

END;

/

This PL/SQL block retrieves the distinct order numbers and order dates for the orders placed between the provided start and end dates. Then, for each order, it fetches the pending delivery details by joining the DELIVERY\_DETAILS and DELIVERYMAST tables. Finally, it displays the order information along with the details of pending deliveries, if any. If no pending deliveries are found for the specified period, it displays a message indicating the same.