

BEAM COUPLING IMPEDANCE OF THE NEW BEAM SCREEN OF THE LHC INJECTION KICKER MAGNETS

H. Day^{*†}, M.J. Barnes[†], F. Caspers[†], E. Métral[†], B. Salvant[†], J. Uythoven[†]
[†] CERN, Switzerland




Figure 1: Structure of the injection kicker magnets.

Abstract

The LHC injection kicker magnets experienced significant beam induced heating of the ferrite yoke, with high intensity beam circulating for many hours, during operation of the LHC in 2011 and 2012. The causes of this beam coupling impedance were studied in depth and an improved beam screen implemented to reduce the impedance. Results of measurements and simulations of the new beam screen design are presented in this paper: these are used to predict power loss and temperature of the ferrite yoke for operation after long shutdown 1 and for proposed HL-LHC operational parameters.

INTRODUCTION

During the 2011 and 2012 runs of the LHC, high temperatures were observed in several devices in the LHC [2], a critical piece being the LHC injection kicker magnets (MKIs) Fig. 1, which were attributed to beam-induced heating due to high power loss from the interaction of the circulating beam with the longitudinal beam coupling impedance. This heating was observed to raise the temperature of the ferrite yoke of one of the MKIs above its Curie point during fills, thereby necessitating waiting times of several hours for the ferrite to cool before safe injection could be carried out [3]. A magnet with an improved beam screen was inserted during technical stop 3 (TS3) (23/09/12-27/09/12), replacing the MKI8D which was measured to have the highest temperature [4]; the replacement magnet was subsequently measured to have the lowest temperature of all magnets.

Building on this success a new design has been proposed to satisfy competing needs of low rates of electrical breakdown during magnet pulsing and a low beam coupling impedance to reduce the power lost into the structure by wakefields; in addition to meeting strict requirements for magnet operation for field rise time and flat top stability [1].




Figure 2: Cross section of the new beam screen design

NEW BEAM SCREEN DESIGN

The new design involves a redesign of the capacitively coupled end of the beam screen, intended to reduce the electrical field due to the induced potentials on the screen conductors during magnet pulsing. This reduced electric field reduces the possibility of surface breakdown on the internal face of the beam screen allowing additional beam screens to be inserted where previously they had been removed due to being located in regions of high electric field Fig. 2 providing complete screening of the ferrite yoke of the magnet. See [6] for more information on behaviour relating to surface flashover.

IMPEDANCE MEASUREMENTS

In order to observe the effect of manufacturing tolerances between magnets and as part of the campaign to characterise the impedance of all devices placed into the LHC each of the MKIs with the new beam screen is

POWER LOSS AND FUTURE IMPROVEMENTS

INTRODUCTION

REFERENCES

- [1] M.J. Barnes *et al.*, *Upgrade of the LHC Injection Kicker Magnets*, IPAC'13, Shanghai, China, MOPWA030
- [2] E. Métral *et al.*, *Beam-Induced Heating/Bunch Length/RF and Lessons for 2012*, LHC Performance Workshop, Chamonix 2012, CERN-ATS-2012-069.
- [3] M.J. Barnes *et al.*, *"Analysis of Measured Ferrite Heating of the LHC Injection Kickers and Proposals for Future Reduction of Temperature"*, IPAC'12, New Orleans, USA, 2012, TUPPR090.

* hugo.day@hep.manchester.ac.uk

- [4] M.J. Barnes *et al.*, "*Beam Induced Ferrite Heating of the LHC Injection Kickers and Proposals for Improved Cooling*", IPAC'13, Shanghai, China, MOPWA031.
- [5] H. Day *et al.*, "*Evaluation of the Beam Coupling Impedance of new Beam Screen Designs for the LHC Injection Kicker Magnets*", IPAC'12, New Orleans, USA, 2012, WEPPR071.
- [6] M.J. Barnes *et al.*, "*Reduction of Surface Flashover of the Beam Screen of the LHC Injection Kickers*", IPAC'13, Shanghai, China, MOPWA031.
- [7] <http://www.cst.com>.
- [8] PhD Thesis, H. Day, 2013.
- [9] P. Baudrenghien *et al.*, "*The LHC RF System - Experience with Beam Operation*", IPAC'11, San Sebastian, 2011, MOPC054.