

# Algorithm Library

Liu Yang

February 1, 2019

## Contents

# 1 String

## 1.1 AhoCorasickAutomaton

```
#include <bits/stdc++.h>

const int maxn = "Edit";

struct AhoCorasickAutomaton {
    // 子节点记录数组
    int Son[maxn][26];
    int Val[maxn];
    // 失配指针 Fail 数组
    int Fail[maxn];
    // 节点数量
    int Tot;

    // Trie Tree 初始化
    void TrieInit() {
        Tot = 0;
        memset(Son, 0, sizeof(Son));
        memset(Val, 0, sizeof(Val));
        memset(Fail, 0, sizeof(Fail));
    }

    // 计算字母下标
    int Pos(char X) {
        return X - 'a';
    }

    // 向 Trie Tree 中插入 Str 模式字符串
    void Insert(string Str) {
        int Cur = 0, Len = int(Str.length());
        for (int i = 0; i < Len; ++i) {
            int Index = Pos(Str[i]);
            if (!Son[Cur][Index]) {
                Son[Cur][Index] = ++Tot;
            }
            Cur = Son[Cur][Index];
        }
        Val[Cur]++;
    }

    // Bfs 求得 Trie Tree 上失配指针
    void GetFail() {
        std::queue<int> Que;
        for (int i = 0; i < 26; ++i) {
            if (Son[0][i]) {
                Fail[Son[0][i]] = 0;
                Que.push(Son[0][i]);
            }
        }
    }
};
```

```
    }
}
while (!Que.empty()) {
    int Cur = Que.front(); Que.pop();
    for (int i = 0; i < 26; ++i) {
        if (Son[Cur][i]) {
            Fail[Son[Cur][i]] = Son[Fail[Cur]][i];
            Que.push(Son[Cur][i]);
        }
        else {
            Son[Cur][i] = Son[Fail[Cur]][i];
        }
    }
}
}

// 询问 Str 中出现的模式串数量
int Query(string Str) {
    int Len = int(Str.length());
    int Cur = 0, Ans = 0;
    for (int i = 0; i < Len; ++i) {
        Cur = Son[Cur][Pos(Str[i])];
        for (int j = Cur; j && ~Val[j]; j = Fail[j]) {
            Ans += Val[j];
            Val[j] = -1;
        }
    }
    return Ans;
}
};
```

## 1.2 KMP

```
#include <bits/stdc++.h>

// 对模式串 Pattern 计算 Next 数组
void KMPPre(string Pattern, vector<int> &Next) {
    int i = 0, j = -1;
    Next[0] = -1;
    int Len = int(Pattern.length());
    while (i != Len) {
        if (j == -1 || Pattern[i] == Pattern[j]) {
            Next[++i] = ++j;
        }
        else {
            j = Next[j];
        }
    }
}
```

// 优化对模式串 *Pattern* 计算 *Next* 数组

```
void PreKMP(string Pattern, vector<int> &Next) {
    int i, j;
    i = 0;
    j = Next[0] = -1;
    int Len = int(Pattern.length());
    while (i < Len) {
        while (j != -1 && Pattern[i] != Pattern[j]) {
            j = Next[j];
        }
        if (Pattern[++i] == Pattern[++j]) {
            Next[i] = Next[j];
        }
        else {
            Next[i] = j;
        }
    }
}
```

// 利用预处理 *Next* 数组计数模式串 *Pattern* 在主串 *Main* 中出现次数

```
int KMPCount(string Pattern, string Main) {
    int PatternLen = int(Pattern.length()), MainLen = int(Main.length());
    vector<int> Next(PatternLen + 1, 0);
    //PreKMP(Pattern, Next);
    KMPPre(Pattern, Next);
    int i = 0, j = 0;
    int Ans = 0;
    while (i < MainLen) {
        while (j != -1 && Main[i] != Pattern[j]) {
            j = Next[j];
        }
        i++; j++;
        if (j >= PatternLen) {
            Ans++;
            j = Next[j];
        }
    }
    return Ans;
}
```

### 1.3 Manacher

```
#include <bits/stdc++.h>
```

```
const int maxn = "Edit";
```

```
char ConvertStr[maxn << 1];
```

```
int Len[maxn << 1];
```

// Manacher 算法求 *Str* 字符串最长回文子串长度

```

int Manacher(char Str[]) {
    int L = 0, StrLen = int(strlen(Str));
    ConvertStr[L++] = '$'; ConvertStr[L++] = '#';
    for (int i = 0; i < StrLen; ++i) {
        ConvertStr[L++] = Str[i];
        ConvertStr[L++] = '#';
    }
    int MX = 0, ID = 0, Ans = 0;
    for (int i = 0; i < L; ++i) {
        Len[i] = MX > i ? min(Len[2 * ID - i], MX - i) : 1;
        while (ConvertStr[i + Len[i]] == ConvertStr[i - Len[i]]) {
            Len[i]++;
        }
        if (i + Len[i] > MX) {
            MX = i + Len[i];
            ID = i;
        }
        Ans = max(Ans, Len[i] - 1);
    }
    return Ans;
}

```

## 1.4 PalindromicTree

```
#include <bits/stdc++.h>
```

```
const int maxn = "Edit";
```

```

struct PalindromicTree {
    // 子节点记录数组
    long long Son[maxn][26];
    // 失配指针 Fail 数组
    long long Fail[maxn];
    // Len[i]: 节点 i 表示的回文串长度 (一个节点表示一个回文串)
    long long Len[maxn];
    // Cnt[i]: 节点 i 表示的本质不同的串的个数 (最后需要运行 Count() 函数才可求出正确
    // 结果)
    long long Cnt[maxn];
    // Num[i]: 以节点 i 表示的最长回文串的最右端为回文串结尾的回文串个数
    long long Num[maxn];
    // 字符
    long long Str[maxn];
    // 新添加字符后最长回文串表示的节点
    long long Last;
    // 字符数量
    long long StrLen;
    // 节点数量
    long long Tot;

    // 新建节点

```

```
long long NewNode(long long X) {
    for (long long i = 0; i < 26; ++i) {
        Son[Tot][i] = 0;
    }
    Cnt[Tot] = 0;
    Num[Tot] = 0;
    Len[Tot] = X;
    return Tot++;
}

// 初始化
void Init() {
    Tot = 0;
    NewNode(0); NewNode(-1);
    Last = 0;
    StrLen = 0;
    // 开头存字符集中没有的字符，减少特判
    Str[0] = -1;
    Fail[0] = 1;
}

long long GetFail(long long X) {
    while (Str[StrLen - Len[X] - 1] != Str[StrLen]) {
        X = Fail[X];
    }
    return X;
}

void Add(long long Char) {
    Char -= 'a';
    Str[++StrLen] = Char;
    long long Cur = GetFail(Last);
    if (!Son[Cur][Char]) {
        long long New = NewNode(Len[Cur] + 2);
        Fail[New] = Son[GetFail(Fail[Cur])][Char];
        Son[Cur][Char] = New;
        Num[New] = Num[Fail[New]] + 1;
    }
    Last = Son[Cur][Char];
    Cnt[Last]++;
}

void Count() {
    // 若 Fail[V]=U, 则 U 一定是 V 回文子串, 所以双亲累加孩子的 Cnt
    for (long long i = Tot - 1; i >= 0; --i) {
        Cnt[Fail[i]] += Cnt[i];
    }
}

};
```

## 2 Math

### 2.1 Catalan

```
#include <bits/stdc++.h>

const int maxn = "Edit";

long long Catalan[maxn];

// 递推求卡特兰数
void CalalanInit() {
    memset(Catalan, 0, sizeof(Catalan));
    Catalan[0] = Catalan[1] = 1;
    for (int i = 2; i < maxn; ++i) {
        Catalan[i] = Catalan[i - 1] * (4 * i - 2) / (i + 1);
    }
}
```

### 2.2 Derangement

```
#include <bits/stdc++.h>

const int maxn = "Edit";
const int mod = 1e9 + 7;

// Staggered: 错排数
long long Staggered[maxn];

// 求错排数
void StaggeredInit() {
    Staggered[1] = 0;
    Staggered[2] = 1;
    // 递推求错排数
    for (int i = 3; i < maxn; ++i) {
        Staggered[i] = (i - 1) * (Staggered[i - 1] + Staggered[i - 2]) % mod;
    }
}
```

### 2.3 Euler

#### 2.3.1 Euler

```
#include <bits/stdc++.h>

// 单独求解欧拉函数
int Phi(int X) {
    int Ans = X;
    for (int i = 2; i * i <= X; ++i) {
        if (!(X % i)) {
            Ans = Ans / i * (i - 1);
        }
    }
}
```



```
        while (!(X % i)) {
            X /= i;
        }
    }
}
if (X > 1) {
    Ans = Ans / X * (X - 1);
}
return Ans;
}
```

### 2.3.2 PrimeEuler

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// 素数标记
bool IsPrime[maxn];
// 欧拉函数
int Phi[maxn];
// 素数
int Prime[maxn];
// 素数个数
int Tot;

// 同时求得欧拉函数和素数表
void PhiPrime() {
    memset(IsPrime, false, sizeof(IsPrime));
    Phi[1] = 1;
    Tot = 0;
    for (int i = 2; i < maxn; ++i) {
        if (!IsPrime[i]) {
            Prime[Tot++] = i;
            Phi[i] = i - 1;
        }
        for (int j = 0; j < Tot; ++j) {
            if (i * Prime[j] > maxn) {
                break;
            }
            IsPrime[i * Prime[j]] = true;
            if (!(i % Prime[j])) {
                Phi[i * Prime[j]] = Phi[i] * Prime[j];
                break;
            }
            else {
                Phi[i * Prime[j]] = Phi[i] * (Prime[j] - 1);
            }
        }
    }
}
```

```
}
```

### 2.3.3 Sieve

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// 欧拉函数
int Phi[maxn];

// 筛法求欧拉函数
void Euler() {
    for (int i = 1; i < maxn; ++i) {
        Phi[i] = i;
    }
    for (int i = 2; i < maxn; i += 2) {
        Phi[i] /= 2;
    }
    for (int i = 3; i < maxn; i += 2) {
        if (Phi[i] == i) {
            for (int j = i; j < maxn; j += i) {
                Phi[j] = Phi[j] / i * (i - 1);
            }
        }
    }
}
```

## 2.4 FFT

```
#include <bits/stdc++.h>

const int maxn = "Edit";
const double pi = acos(-1.0);

// 复数
struct Complex {
    double X, Y;

    Complex operator + (const Complex &B) const {
        return Complex {X + B.X, Y + B.Y};
    }

    Complex operator - (const Complex &B) const {
        return Complex {X - B.X, Y - B.Y};
    }

    Complex operator * (const Complex &B) const {
        return Complex {X * B.X - Y * B.Y, X * B.Y + Y * B.X};
    }
}
```

```
Complex operator / (const Complex &B) const {
    double Temp = B.X * B.X + B.Y * B.Y;
    return Complex {(X * B.X + Y * B.Y) / Temp, (Y * B.X - X * B.Y) / Temp};
}
};

// 多项式系数数量
int N, M;
int L;
int Limit;
int R[maxn << 2];

// 快速傅里叶变换 (FFT)
void FFT(Complex F[], int Op) {
    for (int i = 0; i < Limit; ++i) {
        if (i < R[i]) {
            std::swap(F[i], F[R[i]]);
        }
    }
    for (int j = 1; j < Limit; j <= 1) {
        Complex Temp = Complex {cos(pi / j), Op * sin(pi / j)};
        for (int k = 0; k < Limit; k += (j < 1)) {
            Complex Buffer = Complex {1.0, 0.0};
            for (int l = 0; l < j; ++l) {
                Complex Tx = F[k + l], Ty = Buffer * F[k + j + l];
                F[k + l] = Tx + Ty;
                F[k + j + l] = Tx - Ty;
                Buffer = Buffer * Temp;
            }
        }
    }
}

// 多项式系数
Complex A[maxn], B[maxn];

// 多项式卷积计算
void Cal() {
    Limit = 1; L = 0;
    while (Limit <= N + M) {
        Limit <= 1;
        L++;
    }
    for (int i = 0; i < Limit; ++i) {
        R[i] = (R[i >> 1] >> 1) | ((i & 1) << (L - 1));
    }
    FFT(A, 1);
    FFT(B, 1);
}
```

```
    for (int i = 0; i <= Limit; ++i) {  
        A[i] = A[i] * B[i];  
    }  
    FFT(A, -1);  
}
```

## 2.5 Fibonacci

```
#include <bits/stdc++.h>
```

```
const int mod = 1e9 + 7;
```

```
// 矩阵结构体
```

```
struct Matrix {  
    // 矩阵  
    long long Mat[2][2];  
};
```

```
// 重载矩阵乘法
```

```
Matrix operator * (Matrix &Key1, Matrix &Key2) const {  
    Matrix Res;  
    memset(Res.Mat, 0, sizeof(Res.Mat));  
    for (int i = 0; i < 2; ++i) {  
        for (int j = 0; j < 2; ++j) {  
            for (int k = 0; k < 2; ++k) {  
                Res.Mat[i][j] = (Res.Mat[i][j] + Key1.Mat[i][k] * Key2.Mat[k][j] %  
                    ↪ mod) % mod;  
            }  
        }  
    }  
    return Res;  
}
```

```
// 重载矩阵快速幂
```

```
Matrix operator ^ (Matrix Base, long long K) {  
    Matrix Res;  
    memset(Res.Mat, 0, sizeof(Res.Mat));  
    Res.Mat[0][0] = Res.Mat[1][1] = 1;  
    while (K) {  
        if (K & 1) {  
            Res = Res * Base;  
        }  
        Base = Base * Base;  
        K >>= 1;  
    }  
    return Res;  
}
```

```
// 斐波那契数列中第 x 项
```

```
long long Fib(long long X) {
```

```
Matrix Base;
Base.Mat[0][0] = Base.Mat[1][0] = Base.Mat[0][1] = 1;
Base.Mat[1][1] = 0;
return (Base ^ X).Mat[0][1];
}
```

## 2.6 GeneratingFunction

```
#include <bits/stdc++.h>

const int maxn = "Edit";

void GeneratingFunction() {
    int n;
    int c1[maxn], c2[maxn];
    scanf("%d", &n);
    for (int i = 0; i < maxn; ++i) {
        c1[i] = 1;
        c2[i] = 0;
    }
    // c1[i] 为  $x^i$  的系数
    // c2 为中间变量
    for (int i = 2; i <= n; ++i) {
        for (int j = 0; j <= n; ++j) {
            for (int k = 0; k + j <= n; k += i) {
                c2[j + k] += c1[i];
            }
        }
        for (int j = 0; j <= n; ++j) {
            c1[j] = c2[j];
            c2[j] = 0;
        }
    }
}
```

## 2.7 InverseElement

### 2.7.1 ExtendGcd

```
#include <bits/stdc++.h>

// 扩展欧几里得,  $A*X+B*Y=D$ 
long long ExtendGcd(long long A, long long B, long long &X, long long &Y) {
    // 无最大公约数
    if (A == 0 && B == 0) {
        return -1;
    }
    if (B == 0) {
        X = 1;
        Y = 0;
        return A;
    }
```

```
    }
    long long D = ExtendGcd(B, A % B, Y, X);
    Y -= A / B * X;
    return D;
}
```

```
// 逆元,  $AX = 1 \pmod M$ 
long long Inv(long long A, long long N) {
    long long X, Y;
    long long D = ExtendGcd(A, N, X, Y);
    if (D == 1) {
        return (X % N + N) % N;
    }
    else {
        return -1;
    }
}
```

### 2.7.2 Factorial

```
#include <bits/stdc++.h>

const int mod = 1e9 + 7;
const int maxn = "Edit";

// 快速乘
long long QuickMul(long long A, long long B) {
    long long Ans = 0;
    while (B) {
        if (B & 1) {
            Ans = (Ans + A) % mod;
        }
        A = (A + A) % mod;
        B >>= 1;
    }
    return Ans;
}
```

```
// 快速幂
long long QuickPow(long long A, long long B) {
    long long Ans = 1;
    while (B) {
        if (B & 1) {
            Ans = QuickMul(Ans, A) % mod;
        }
        A = QuickMul(A, A) % mod;
        B >>= 1;
    }
    return Ans;
}
```

```
// Factorial: 阶乘, FactorialInv: 阶乘逆元
long long Factorial[maxn], FactorialInv[maxn];

// 求阶乘逆元
void FactorialInvInit() {
    // 求阶乘
    Factorial[0] = 0;
    Factorial[1] = 1;
    for (int i = 2; i < maxn; ++i) {
        Factorial[i] = (Factorial[i - 1] * i) % mod;
    }
    // 费马小定理求最大值阶乘逆元
    FactorialInv[maxn - 1] = QuickPow(Factorial[maxn - 1], mod - 2);
    // 递推求阶乘逆元
    for (int i = maxn - 2; i >= 0; --i) {
        FactorialInv[i] = (FactorialInv[i + 1] * (i + 1)) % mod;
    }
}
```

### 2.7.3 FermatLittleTheorem

```
#include <bits/stdc++.h>

const int mod = 1e9 + 7;

// 快速幂、费马小定理求逆元
long long Inv(long long X) {
    return QuickPow(X, mod - 2);
}
```

### 2.7.4 Recursive

```
#include <bits/stdc++.h>

const int mod = 1e9 + 7;
const int maxn = "Edit";

long long Inv[maxn];

// 递推求逆元
void InvInit() {
    Inv[1] = 1;
    for (int i = 2; i < maxn; ++i) {
        Inv[i] = (mod - mod / i) * Inv[mod % i] % mod;
    }
}
```

## 2.8 Moblus

```
#include <bits/stdc++.h>

const int maxn = "Edit";

bool IsPrime[maxn];
int Tot;
int Prime[maxn];
int Mu[maxn];

void Moblus() {
    for (int i = 0; i < maxn; ++i) IsPrime[i] = true;
    Mu[1] = 1;
    for (int i = 2; i < maxn; ++i) {
        if (IsPrime[i]) {
            Prime[Tot++] = i;
            Mu[i] = -1;
        }
        for (int j = 0; j < Tot && Prime[j] * i < maxn; ++j) {
            IsPrime[i * Prime[j]] = false;
            if (i % Prime[j] == 0) {
                Mu[i * Prime[j]] = 0;
                break;
            }
            Mu[i * Prime[j]] = -Mu[i];
        }
    }
}
```

## 2.9 Prime

### 2.9.1 PrimeFactor

```
#include <bits/stdc++.h>

const int maxn = "Edit"

bool IsPrime[maxn];
vector<int> PrimeFactor[maxn];

void Init() {
    memset(IsPrime, true, sizeof(IsPrime));
    for (long long i = 2; i < maxn; ++i) {
        if (IsPrime[i]) {
            PrimeFactor[i].push_back(i);
            for (long long j = i + i; j < maxn; ++j) {
                IsPrime[j] = false;
                PrimeFactor[j].push_back(i);
            }
        }
    }
}
```



```
    }  
    IsPrime[1] = false;  
}
```

## 2.9.2 SieveOfEratosthenes

```
#include <bits/stdc++.h>  
  
const int maxn = "Edit";  
  
bool IsPrime[maxn];  
  
void Init() {  
    memset(IsPrime, true, sizeof(IsPrime));  
    IsPrime[0] = IsPrime[1] = false;  
    for (long long i = 2; i < maxn; ++i) {  
        if (IsPrime[i]) {  
            for (long long j = i * i; j < maxn; j += i) {  
                IsPrime[j] = false;  
            }  
        }  
    }  
}
```

## 2.10 QuickPow

```
#include <bits/stdc++.h>  
  
const int mod = 1e9 + 7;  
  
// 快速乘求  $A*B\%mod$   
long long QuickMul(long long A, long long B) {  
    long long Ans = 0;  
    while (B) {  
        if (B & 1) {  
            Ans = (Ans + A) % mod;  
        }  
        A = (A + A) % mod;  
        B >>= 1;  
    }  
    return Ans;  
}  
  
// 快速幂求  $A^B\%mod$   
long long QuickPow(long long A, long long B) {  
    long long Ans = 1;  
    while (B) {  
        if (B & 1) {  
            //  $Ans = Ans * A \% mod$ ;  
            Ans = QuickMul(Ans, A) % mod;  
        }  
        A = (A + A) % mod;  
        B >>= 1;  
    }  
    return Ans;  
}
```

```
    }  
    // Ans = A * A % mod;  
    A = QuickMul(A, A) % mod;  
    B >>= 1;  
}  
return Ans;  
}
```

## 2.11 Stirling

```
#include <bits/stdc++.h>  
  
const double pi = acos(-1.0);  
const double e = 2.718281828459;  
  
int Stirling(int x) {  
    if (x <= 1) {  
        return 1;  
    }  
    return int(ceil(log10(2 * pi * x) / 2 + x * log10(x / e)));  
}
```

### 3 DataStructure

#### 3.1 BinaryIndexedTree

```
#include <bits/stdc++.h>
#define lowbit(x) (x&(-x))

const int maxn = "Edit";

// 树状数组
int Array[maxn];

// 更新树状数组信息
void Update(int X, int Val) {
    while (X < maxn) {
        Array[X] += Val;
        X += lowbit(X);
    }
}

// 查询
int Query(int X) {
    int Ans = 0;
    while (X > 0) {
        Ans += Array[X];
        X -= lowbit(X);
    }
    return Ans;
}
```

#### 3.2 DfsOrder

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// 链式前向星建图
struct Link {
    int V, Next;
};

Link edges[maxn << 1];
int Head[maxn];
int Tot = 0;

void Init() {
    Tot = 0;
    memset(Head, -1, sizeof(Head));
}
```

```
void AddEdge(int U, int V) {
    edges[++Tot] = Link {V, Head[U]};
    Head[U] = Tot;
    edges[++Tot] = Link {U, Head[V]};
    Head[V] = Tot;
}

int Cnt;
int InIndex[maxn], OutIndex[maxn];

// Dfs 序
void DfsSequence(int Node, int Pre) {
    Cnt++;
    InIndex[Node] = Cnt;
    for (int i = Head[U]; i != -1; i = edges[i].Next) {
        if (edges[i].V != Pre) {
            DfsSequence(edges[i].V, Node);
        }
    }
    OutIndex[U] = Cnt;
}
```

### 3.3 SegmentTree

#### 3.3.1 SegmentTree

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// Sum: 线段树信息 (此模板为求和), Lazy: 惰性标记
int Sum[maxn << 2], Lazy[maxn << 2];

// 更新节点信息, 这里是求和
void PushUp(int Root) {
    Sum[Root] = Sum[Root << 1] + Sum[Root << 1 | 1];
}

// 下推标记函数, LeftNum, RightNum: 分别为左右子树的数字数量
void PushDown(int Root, int LeftNum, int RightNum) {
    if (Lazy[Root]) {
        // 下推标记
        Lazy[Root << 1] += Lazy[Root];
        Lazy[Root << 1 | 1] += Lazy[Root];
        // 根据惰性标修改子节点的值
        Sum[Root << 1] += Lazy[Root] * LeftNum;
        Sum[Root << 1 | 1] += Lazy[Root] * RightNum;
        // 清除本节点惰性标记
        Lazy[Root] = 0;
    }
}
```

```
}

// 建树, Left、Right: 当前节点区间, Root: 当前节点编号
void Build(int Left, int Right, int Root) {
    Lazy[Root] = 0;
    // 到达叶子节点
    if (Left == Right) {
        scanf("%d", &Sum[Root]);
        return;
    }
    int Mid = (Left + Right) >> 1;
    // 左子树
    Build(Left, Mid, Root << 1);
    // 右子树
    Build(Mid + 1, Right, Root << 1 | 1);
    // 更新信息
    PushUp(Root);
}

// 单点修改, Pos: 修改点位置, Value: 修改值, Left、Right: 当前区间, Root: 当前节点编号
void PointUpdate(int Pos, int Value, int Left, int Right, int Root) {
    // 修改叶子节点
    if (Left == Right) {
        Sum[Root] += Value;
        return;
    }
    int Mid = (Left + Right) >> 1;
    // 根据条件判断调用左子树还是右子树
    if (Pos <= Mid) {
        PointUpdate(Pos, Value, Left, Mid, Root << 1);
    }
    else {
        PointUpdate(Pos, Value, Mid + 1, Right, Root << 1 | 1);
    }
    // 子节点更新后更新此节点
    PushUp(Root);
}

// 区间修改, OperateLeft、OperateRight: 操作区间, Left、Right: 当前区间, Root: 当前节点编号
void IntervalUpdate(int OperateLeft, int OperateRight, int Value, int Left, int
    → Right, int Root) {
    // 若本区间完全在操作区间内
    if (OperateLeft <= Left && OperateRight >= Right) {
        Sum[Root] += Value * (Right - Left + 1);
        // 增加惰性标记, 表示本区间 Sum 正确, 但子区间仍需要根据惰性标记调整更新
        Lazy[Root] += Value;
        return;
    }
}
```

```
int Mid = (Left + Right) >> 1;
// 下推标记
PushDown(Root, Mid - Left + 1, Right - Mid);
// 根据条件判断调用左子树还是右子树
if (OperateLeft <= Mid) {
    IntervalUpdate(OperateLeft, OperateRight, Value, Left, Mid, Root << 1);
}
if (OperateRight > Mid) {
    IntervalUpdate(OperateLeft, OperateRight, Value, Mid + 1, Right, Root << 1
        ↪ | 1);
}
// 更新当前节点信息
PushUp(Root);
}

// 区间查询, OperateLeft、OperateRight: 操作区间, Left、Right: 当前区间, Root: 当前节
↪ 点编号
int Query(int OperateLeft, int OperateRight, int Left, int Right, int Root) {
    // 区间内直接返回
    if (OperateLeft <= Left && OperateRight >= Right) {
        return Sum[Root];
    }
    int Mid = (Left + Right) >> 1;
    // 下推标记
    PushDown(Root, Mid - Left + 1, Right - Mid);
    // 叠加结果
    int Ans = 0;
    if (OperateLeft <= Mid) {
        Ans += Query(OperateLeft, OperateRight, Left, Mid, Root << 1);
    }
    if (OperateRight > Mid) {
        Ans += Query(OperateLeft, OperateRight, Mid + 1, Right, Root << 1 | 1);
    }
    // 返回结果
    return Ans;
}
```

### 3.3.2 SegmentTreestruct

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// 线段树节点
struct Node {
    int Left, Right;
    int Lazy, Tag;
    int Sum;
};
```

```
Node SegmentTree[maxn << 2];

// 更新节点信息
void PushUp(int Root) {
    SegmentTree[Root].Sum = SegmentTree[Root << 1].Sum + SegmentTree[Root << 1 |
    ↪ 1].Sum;
}

// 建树, Left、Right: 当前节点区间, Root: 当前节点编号
void Build(int Left, int Right, int Root) {
    SegmentTree[Root].Left = Left;
    SegmentTree[Root].Right = Right;
    SegmentTree[Root].Lazy = 0;
    SegmentTree[Root].Tag = 0;
    // 叶子节点
    if (Left == Right) {
        scanf("%d", &SegmentTree[Root].Sum);
        return;
    }
    // 左右子树
    int Mid = (Left + Right) >> 1;
    Build(Left, Mid, Root << 1);
    Build(Mid + 1, Right, Root << 1 | 1);
    // 更新
    PushUp(Root);
}

// 单点更新, Pos: 修改点位置, Value: 修改值, Root: 当前节点编号
void PointUpdate(int Pos, int Value, int Root) {
    SegmentTree[Root].Sum += Value;
    if (SegmentTree[Root].Left == Pos && SegmentTree[Root].Right == Pos) {
        return;
    }
    int Mid = (SegmentTree[Root].Left + SegmentTree[Root].Right) >> 1;
    if (Pos <= Mid) {
        PointUpdate(Pos, Value, Root << 1);
    }
    else {
        PointUpdate(Pos, Value, Root << 1 | 1);
    }
    PushUp(Root);
}

// 区间修改, Left、Right: 修改区间, Value: 修改值, Root: 当前节点编号
void IntervalUpdate(int Left, int Right, int Value, int Root) {
    if (SegmentTree[Root].Left == Left && SegmentTree[Root].Right == Right) {
        SegmentTree[Root].Lazy = 1;
        SegmentTree[Root].Tag = Value;
        SegmentTree[Root].Sum = (Right - Left + 1) * Value;
    }
```

```
        return;
    }
    int Mid = (SegmentTree[Root].Left + SegmentTree[Root].Right) >> 1;
    // 下推更新
    if (SegmentTree[Root].Lazy == 1) {
        SegmentTree[Root].Lazy = 0;
        IntervalUpdate(SegmentTree[Root].Left, Mid, SegmentTree[Root].Tag, Root << 1);
        IntervalUpdate(Mid + 1, SegmentTree[Root].Right, SegmentTree[Root].Tag, Root << 1 | 1);
        SegmentTree[Root].Tag = 0;
    }
    if (Right <= Mid) {
        IntervalUpdate(Left, Right, Value, Root << 1);
    }
    else if (Left > Mid) {
        IntervalUpdate(Left, Right, Value, Root << 1 | 1);
    }
    else {
        IntervalUpdate(Left, Mid, Value, Root << 1);
        IntervalUpdate(Mid + 1, Right, Value, Root << 1 | 1);
    }
    PushUp(Root);
}

// 区间查询, Left、Right: 查询区间, Root: 当前节点编号
int Query(int Left, int Right, int Root) {
    if (Left == SegmentTree[Root].Left && Right == SegmentTree[Root].Right) {
        return SegmentTree[Root].Sum;
    }
    int Mid = (SegmentTree[Root].Left + SegmentTree[Root].Right) >> 1;
    if (Right <= Mid) {
        return Query(Left, Right, Root << 1);
    }
    else if (Left > Mid) {
        return Query(Left, Right, Root << 1 | 1);
    }
    else {
        return Query(Left, Mid, Root << 1) + Query(Mid + 1, Right, Root << 1 | 1);
    }
}
```

## 3.4 Splay

### 3.4.1 SplayTree

```
#include <bits/stdc++.h>

const int maxn = "Edit";
```



```
struct SplayTree {
    // Root:Splay Tree 根节点
    int Root, Tot;
    // Son[i][0]:i 节点的左孩子, Son[i][1]:i 节点的右孩子
    int Son[maxn][2];
    // Pre[i]:i 节点的父节点
    int Pre[maxn];
    // Val[i]:i 节点的权值
    int Val[maxn];
    // Size[i]: 以 i 节点为根的 Splay Tree 的节点数 (包含自身)
    int Size[maxn];
    // Cnt[i]: 节点 i 的权值的出现次数
    int Cnt[maxn];

    void PushUp(int X) {
        Size[X] = Size[Son[X][0]] + Size[Son[X][1]] + Cnt[X];
    }

    // 判断 x 节点是其父节点的左孩子还是右孩子
    bool Self(int X) {
        return X == Son[Pre[X]][1];
    }

    void Clear(int X) {
        Son[X][0] = Son[X][1] = Pre[X] = Val[X] = Size[X] = Cnt[X] = 0;
    }

    // 旋转
    void Rotate(int X) {
        int Fa = Pre[X], FaFa = Pre[Fa], XJ = Self(X);
        Son[Fa][XJ] = Son[X][XJ ^ 1];
        Pre[Son[Fa][XJ]] = Pre[X];
        Son[X][XJ ^ 1] = Pre[X];
        Pre[Fa] = X;
        Pre[X] = FaFa;
        if (FaFa) {
            Son[FaFa][Fa == Son[FaFa][1]] = X;
        }
        PushUp(Fa);
        PushUp(X);
    }

    // 旋转 x 节点到根节点
    void Splay(int X) {
        for (int i = Pre[X]; i = Pre[X]; Rotate(X)) {
            if (Pre[i]) {
                Rotate(Self(X) == Self(i) ? i : X);
            }
        }
    }
}
```

```
    Root = X;
}

// 插入数 X
void Insert(int X) {
    if (!Root) {
        Val[++Tot] = X;
        Cnt[Tot]++;
        Root = Tot;
        PushUp(Root);
        return;
    }
    int Cur = Root, F = 0;
    while (true) {
        if (Val[Cur] == X) {
            Cnt[Cur]++;
            PushUp(Cur);
            PushUp(F);
            Splay(Cur);
            break;
        }
        F = Cur;
        Cur = Son[Cur][Val[Cur] < X];
        if (!Cur) {
            Val[++Tot] = X;
            Cnt[Tot]++;
            Pre[Tot] = F;
            Son[F][Val[F] < X] = Tot;
            PushUp(Tot);
            PushUp(F);
            Splay(Tot);
            break;
        }
    }
}

// 查询 X 的排名
int Rank(int X) {
    int Ans = 0, Cur = Root;
    while (true) {
        if (X < Val[Cur]) {
            Cur = Son[Cur][0];
        }
        else {
            Ans += Size[Son[Cur][0]];
            if (X == Val[Cur]) {
                Splay(Cur);
                return Ans + 1;
            }
        }
    }
}
```

```
        Ans += Cnt[Cur];
        Cur = Son[Cur][1];
    }
}

// 查询排名为 X 的数
int Kth(int X) {
    int Cur = Root;
    while (true) {
        if (Son[Cur][0] && X <= Size[Son[Cur][0]]) {
            Cur = Son[Cur][0];
        }
        else {
            X -= Cnt[Cur] + Size[Son[Cur][0]];
            if (X <= 0) {
                return Val[Cur];
            }
            Cur = Son[Cur][1];
        }
    }
}

/*
 * 在 Insert 操作时 X 已经 Splay 到根了
 * 所以 X 的前驱就是 X 的左子树的最右边的节点
 * 后继就是 X 的右子树的最左边的节点
 */

// 求前驱
int GetPath() {
    int Cur = Son[Root][0];
    while (Son[Cur][1]) {
        Cur = Son[Cur][1];
    }
    return Cur;
}

// 求后继
int GetNext() {
    int Cur = Son[Root][1];
    while (Son[Cur][0]) {
        Cur = Son[Cur][0];
    }
    return Cur;
}

// 删除值为 X 的节点
void Delete(int X) {
```

```
// 将  $x$  旋转到根
Rank(X);
if (Cnt[Root] > 1) {
    Cnt[Root]--;
    PushUp(Root);
    return;
}
if (!Son[Root][0] && !Son[Root][1]) {
    Clear(Root);
    Root = 0;
    return;
}
if (!Son[Root][0]) {
    int Temp = Root;
    Root = Son[Root][1];
    Pre[Root] = 0;
    Clear(Temp);
    return;
}
if (!Son[Root][1]) {
    int Temp = Root;
    Root = Son[Root][0];
    Pre[Root] = 0;
    Clear(Temp);
    return;
}
int Temp = GetPath(), Old = Root;
Splay(Temp);
Pre[Son[Old][1]] = Temp;
Son[Temp][1] = Son[Old][1];
Clear(Old);
PushUp(Root);
}
};
```

### 3.4.2 SplayTreeArray

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// Root:Splay Tree 根节点
int Root, Tot;
// Son[i][0]:i 节点的左孩子, Son[i][1]:i 节点的右孩子
int Son[maxn][2];
// Pre[i]:i 节点的父节点
int Pre[maxn];
// Val[i]:i 节点的权值
int Val[maxn];
// Size[i]: 以 i 节点为根的 Splay Tree 的节点数 (包含自身)
```

```
int Size[maxn];
// 惰性标记数组
bool Lazy[maxn];

void PushUp(int X) {
    Size[X] = Size[Son[X][0]] + Size[Son[X][1]] + 1;
}

void PushDown(int X) {
    if (Lazy[X]) {
        std::swap(Son[X][0], Son[X][1]);
        if (Son[X][0]) {
            Lazy[Son[X][0]] ^= 1;
        }
        if (Son[X][1]) {
            Lazy[Son[X][1]] ^= 1;
        }
        Lazy[X] = 0;
    }
}

// 判断 X 节点是其父节点的左孩子还是右孩子
bool Self(int X) {
    return Son[Pre[X]][1] == X;
}

// 旋转节点 X
void Rotate(int X) {
    int Fa = Pre[X], FaFa = Pre[Fa], XJ = Self(X);
    PushDown(Fa); PushDown(X);
    Son[Fa][XJ] = Son[X][XJ ^ 1];
    Pre[Son[Fa][XJ]] = Pre[X];
    Son[X][XJ ^ 1] = Pre[X];
    Pre[Fa] = X;
    Pre[X] = FaFa;
    if (FaFa) {
        Son[FaFa][Fa == Son[FaFa][1]] = X;
    }
    PushUp(Fa); PushUp(X);
}

// 旋转 X 节点到节点 Goal
void Splay(int X, int Goal = 0) {
    for (int Cur = Pre[X]; (Cur = Pre[X]) != Goal; Rotate(X)) {
        PushDown(Pre[Cur]); PushDown(Cur); PushDown(X);
        if (Pre[Cur] != Goal) {
            if (Self(X) == Self(Cur)) {
                Rotate(Cur);
            }
        }
    }
}
```

```
        else {
            Rotate(X);
        }
    }
}
if (!Goal) {
    Root = X;
}
}

// 获取以 R 为根节点 Splay Tree 中的第 K 大个元素在 Splay Tree 中的位置
int Kth(int R, int K) {
    PushDown(R);
    int Temp = Size[Son[R][0]] + 1;
    if (Temp == K) {
        return R;
    }
    if (Temp > K) {
        return Kth(Son[R][0], K);
    }
    else {
        return Kth(Son[R][1], K - Temp);
    }
}

// 获取 Splay Tree 中以 X 为根节点子树的最小值位置
int GetMin(int X) {
    PushDown(X);
    while (Son[X][0]) {
        X = Son[X][0];
        PushDown(X);
    }
    return X;
}

// 获取 Splay Tree 中以 X 为根节点子树的最大值位置
int GetMax(int X) {
    PushDown(X);
    while (Son[X][1]) {
        X = Son[X][1];
        PushDown(X);
    }
    return X;
}

// 求节点 X 的前驱节点
int GetPath(int X) {
    Splay(X, Root);
    int Cur = Son[Root][0];
```

```
    while (Son[Cur][1]) {
        Cur = Son[Cur][1];
    }
    return Cur;
}

// 求节点 y 的后继节点
int GetNext(int X) {
    Splay(X, Root);
    int Cur = Son[Root][1];
    while (Son[Cur][0]) {
        Cur = Son[Cur][0];
    }
    return Cur;
}

// 翻转 Splay Tree 中 Left~Right 区间
void Reverse(int Left, int Right) {
    int X = Kth(Root, Left), Y = Kth(Root, Right);
    Splay(X, 0);
    Splay(Y, X);
    Lazy[Son[Y][0]] ^= 1;
}

// 建立 Splay Tree
void Build(int Left, int Right, int Cur) {
    if (Left > Right) {
        return;
    }
    int Mid = (Left + Right) >> 1;
    Build(Left, Mid - 1, Mid);
    Build(Mid + 1, Right, Mid);
    Pre[Mid] = Cur;
    Val[Mid] = Mid - 1;
    Lazy[Mid] = 0;
    PushUp(Mid);
    if (Mid < Cur) {
        Son[Cur][0] = Mid;
    }
    else {
        Son[Cur][1] = Mid;
    }
}

// 输出 Splay Tree
void Print(int Cur) {
    PushDown(Cur);
    if (Son[Cur][0]) {
        Print(Son[Cur][0]);
    }
}
```

```
}  
// 哨兵节点判断  
if (Val[Cur] != -INF && Val[Cur] != INF) {  
    printf("%d ", Val[Cur]);  
}  
if (Val[Son[Cur][1]]) {  
    Print(Son[Cur][1]);  
}  
}
```

### 3.5 TrieTree

```
#include <bits/stdc++.h>  
  
const int maxn = "Edit";  
  
struct Trie {  
    // Trie Tree 节点  
    int Son[maxn][26];  
    // Trie Tree 节点数量  
    int Tot;  
  
    // 字符串数量统计数组  
    int Cnt[maxn];  
  
    // Trie Tree 初始化  
    void TrieInit() {  
        Tot = 0;  
        memset(Cnt, 0, sizeof(Cnt));  
        memset(Son, 0, sizeof(Son));  
    }  
  
    // 计算字母下标  
    int Pos(char X) {  
        return X - 'a';  
    }  
  
    // 向 Trie Tree 中插入字符串 Str  
    void Insert(string Str) {  
        int Cur = 0, Len = int(Str.length());  
        for (int i = 0; i < Len; ++i) {  
            int Index = Pos(Str[i]);  
            if (!Son[Cur][Index]) {  
                Son[Cur][Index] = ++Tot;  
            }  
            Cur = Son[Cur][Index];  
  
            Cnt[Cur]++;  
        }  
    }  
}
```



```
// 查找字符串 Str, 存在返回 true, 不存在返回 false
bool Find(string Str) {
    int Cur = 0, Len = int(Str.length());
    for (int i = 0; i < Len; ++i) {
        int Index = Pos(Str[i]);
        if (!Son[Cur][Index]) {
            return false;
        }
        Cur = Son[Cur][Index];
    }
    return true;
}

// 查询字典树中以 Str 为前缀的字符串数量
int PathCnt(string Str) {
    int Cur = 0, Len = int(Str.length());
    for (int i = 0; i < Len; ++i) {
        int Index = Pos(Str[i]);
        if (!Son[Cur][Index]) {
            return 0;
        }
        Cur = Son[Cur][Index];
    }
    return Cnt[Cur];
}

};
```

## 4 GraphTheory

### 4.1 LCA

#### 4.1.1 DFS+ST

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// 链式前向星存图
struct Edge {
    int V, Weight, Next;
};

Edge edges[maxn << 1];
int Head[maxn];
int Tot;

void Init() {
    Tot = 0;
    memset(Head, -1, sizeof(Head));
}

void AddEdge(int U, int V, int Weight) {
    edges[Tot] = Edge {V, Weight, Head[U]};
    Head[U] = Tot++;
}

struct LCAOnline {
    // 节点深度
    int Rmq[maxn << 1];
    // 深搜遍历顺序
    int Vertex[maxn << 1];
    // 节点在深搜中第一次出现的位置
    int First[maxn];
    // 记录父节点
    int Parent[maxn];
    // 记录与根节点距离
    int Dis[maxn];
    // 遍历节点数量
    int LCATot;

    // 最小值对应下标
    int Dp[maxn << 1][20];

    // RMQ 初始化
    void Work(int N) {
        for (int i = 1; i <= N; ++i) {
            Dp[i][0] = i;
        }
    }
};
```

```

    for (int j = 1; (1 << j) <= N; ++j) {
        for (int i = 1; i + (1 << j) - 1 <= N; ++i) {
            Dp[i][j] = Rmq[Dp[i][j - 1]] < Rmq[Dp[i + (1 << (j - 1))][j - 1]] ?
                ↪ Dp[i][j - 1] : Dp[i + (1 << (j - 1))][j - 1];
        }
    }
}

// 深搜
void Dfs(int Cur, int Pre, int Depth) {
    Vertex[++LCATot] = Cur;
    First[Cur] = LCATot;
    Rmq[LCATot] = Depth;
    Parent[Cur] = Pre;
    for (int i = Head[Cur]; ~i; i = edges[i].Next) {
        if (edges[i].V == Pre) {
            continue;
        }
        Dis[edges[i].V] = Dis[Cur] + edges[i].Weight;
        Dfs(edges[i].V, Cur, Depth + 1);
        Vertex[++LCATot] = Cur;
        Rmq[LCATot] = Depth;
    }
}

// RMQ 查询
int Query(int Left, int Right) {
    if (Left > Right) {
        swap(Left, Right);
    }
    int Len = int(log2(Right - Left + 1));
    return Rmq[Dp[Left][Len]] <= Rmq[Dp[Right - (1 << Len) + 1][Len]] ?
        ↪ Dp[Left][Len] : Dp[Right - (1 << Len) + 1][Len];
}

// LCA 初始化
void Init(int Root, int NodeNum) {
    memset(Dis, 0, sizeof(Dis));
    LCATot = 0;
    Dfs(Root, 0, 0);
    Parent[1] = 0;
    Work(2 * NodeNum - 1);
}

// 查询节点 U、V 的距离
int GetDis(int U, int V) {
    return Dis[U] + Dis[V] - 2 * Dis[LCA(U, V)];
}

```

```
// 查询节点  $U$ 、 $V$  的最近公共祖先 (LCA)
int LCA(int U, int V) {
    return Vertex[Query(First[U], First[V])];
}
}LCA;
```

#### 4.1.2 Tarjan

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// 树边
struct Edge {
    int V, Next;
};

// 询问
struct Query {
    int Q, Next;
    int Index;
};

// 并查集数组
int Pre[maxn << 2];
// 树边
Edge edges[maxn << 2];
int Head[maxn];
int Tot;
// 询问
Query queries[maxn << 2];
int QHead[maxn];
int QTot;
// 访问标记
int Vis[maxn];
int Ancestor[maxn];
// 结果
int Answer[maxn];

// 并查集查找
int Find(int X) {
    int R = X;
    while (Pre[R] != -1) {
        R = Pre[R];
    }
    return R;
}

// 并查集合并
void Join(int U, int V) {
```

```
    int RU = Find(U);
    int RV = Find(V);
    if (RU != RV) {
        Pre[RU] = RV;
    }
}

// 添加树边
void AddEdge(int U, int V) {
    edges[Tot] = Edge {V, Head[U]};
    Head[U] = Tot++;
}

// 添加询问
void AddQuery(int U, int V, int Index) {
    queries[QTot] = Query {V, QHead[U], Index};
    QHead[U] = QTot++;
    queries[QTot] = Query {U, QHead[V], Index};
    QHead[V] = QTot++;
}

// 初始化
void Init() {
    Tot = 0;
    memset(Head, -1, sizeof(Head));
    QTot = 0;
    memset(QHead, -1, sizeof(QHead));
    memset(Vis, false, sizeof(Vis));
    memset(Pre, -1, sizeof(Pre));
    memset(Ancestor, 0, sizeof(Ancestor));
}

// LCA 离线 Tarjan 算法
void Tarjan(int Node) {
    Ancestor[Node] = Node;
    Vis[Node] = true;
    for (int i = Head[Node]; i != -1; i = edges[i].Next) {
        if (Vis[edges[i].V]) {
            continue;
        }
        Tarjan(edges[i].V);
        Join(Node, edges[i].V);
        Ancestor[Find(Node)] = Node;
    }
    for (int i = QHead[Node]; i != -1; i = queries[i].Next) {
        if (Vis[queries[i].Q]) {
            Answer[queries[i].Index] = Ancestor[Find(queries[i].Q)];
        }
    }
}
```

```
}
```

## 4.2 MinimumSpanningTree

### 4.2.1 Kruskal

```
#include <bits/stdc++.h>

const int maxn = "Edit";

struct Edge {
    int U, V, Dis;

    bool operator < (const Edge &B) const {
        return Dis < B.Dis;
    }
};

// N: 顶点数, E: 边数, Pre 并查集
int N, E, Pre[maxn];
// edges: 边
Edge edges[maxn];

void Init() {
    // 并查集初始化
    for (int i = 0; i <= N; ++i) {
        Pre[i] = i;
    }
}

// 并查集查询
int Find(int X) {
    int R = X;
    while (Pre[R] != R) {
        R = Pre[R];
    }
    int I = X, J;
    while (I != R) {
        J = Pre[I];
        Pre[I] = R;
        I = J;
    }
    return R;
}

// 并查集合并
void Join(int X, int Y) {
    int XX = Find(X);
    int YY = Find(Y);
    if (XX != YY) {
```

```
        Pre[XX] = YY;
    }
}

// Kruskal 算法
int Kruskal() {
    // 贪心排序
    std::sort(edges + 1, edges + E + 1);
    Init();
    int Res = 0;
    // 选边计算
    for (int i = 1; i <= E; ++i) {
        Edge Temp = edges[i];
        if (Find(Temp.U) != Find(Temp.V)) {
            Join(Temp.U, Temp.V);
            Res += Temp.Dis;
        }
    }
    return Res;
}
```

#### 4.2.2 Prim

```
#include <bits/stdc++.h>

const int INF = "Edit";
const int maxn = "Edit";

struct Edge {
    // V: 连接点, Dis: 边权
    int V, Dis;
};

// N: 顶点数, E: 边数
int N, E;
// 松弛更新权值数组
int Dis[maxn];
// 访问标记数组
int Vis[maxn];
// 邻接表
std::vector<Edge> Adj[maxn];

// 建图加边, U, V: 顶点, Weight: 权值
void AddEdge(int U, int V, int Weight) {
    Adj[U].push_back(Edge (V, Weight));
    // 无向图反向建边
    Adj[V].push_back(Edge (U, Weight));
}

// Prim 算法
```

```
int Prim(int Start) {
    memset(Dis, INF, sizeof(Dis));
    memset(Vis, 0, sizeof(Vis));
    Dis[Start] = 0;
    int Res = 0;
    for (int i = 1; i <= N; ++i) {
        // 选择距已生成树权值最小的顶点
        int U = -1, Min = INF;
        for (int j = 1; j <= N; ++j) {
            if (!Vis[j] && Dis[j] < Min) {
                U = j;
                Min = Dis[j];
            }
        }
        // 更新、标记
        Vis[U] = 1;
        Res += Min;
        // 松弛
        for (int j = 0; j < int(Adj[U].size()); ++j) {
            int V = Adj[U][j].V;
            if (!Vis[V] && Adj[U][j].Dis < Dis[V]) {
                Dis[V] = Adj[U][j].Dis;
            }
        }
    }
    // 返回结果
    return Res;
}
```

## 4.3 NetworkFlow

### 4.3.1 Dinic

```
#include <bits/stdc++.h>

const int INF = "Edit";
const int maxn = "Edit";

// 边
struct Edge {
    // V: 连接点, Weight: 权值, Next: 上一条边的编号
    int V, Weight, Next;
};

// 边, 一定要开到足够大
Edge edges[maxn << 1];
// Head[i] 为点 i 上最后一条边的编号
int Head[maxn];
// 增加边时更新编号
int Tot;
```



```
// N: 顶点数, E: 边数
int N, E;
// Bfs 分层深度
int Depth[maxn];
// 当前弧优化
int Current[maxn];

// 链式向前星初始化
void Init() {
    Tot = 0;
    memset(Head, -1, sizeof(Head));
}

// 添加一条由 U 至 V 权值为 Weight 的边
void AddEdge(int U, int V, int Weight, int ReverseWeight = 0) {
    edges[Tot] = Edge(V, Weight, Head[U]);
    Head[U] = Tot++;
    // 反向建边
    edges[Tot] = Edge(U, ReverseWeight, Head[V]);
    Head[V] = Tot++;
}

// Bfs 搜索分层图, Start: 起点, End: 终点
bool Bfs(int Start, int End) {
    memset(Depth, -1, sizeof(Depth));
    std::queue<int> Que;
    Depth[Start] = 0;
    Que.push(Start);
    while (!Que.empty()) {
        int Cur = Que.front();
        Que.pop();
        for (int i = Head[Cur]; ~i; i = edges[i].Next) {
            if (Depth[edges[i].V] == -1 && edges[i].Weight > 0) {
                Depth[edges[i].V] = Depth[Cur] + 1;
                Que.push(edges[i].V);
            }
        }
    }
    return Depth[End] != -1;
}

// Dfs 搜索增广路径, Cur: 当前搜索顶点, End: 终点, NowFlow: 当前最大流
int Dfs(int Cur, int End, int NowFlow) {
    // 搜索到终点或者可用当前最大流为 0 返回
    if (Cur == End || NowFlow == 0) {
        return NowFlow;
    }
    // UsableFlow: 可用流量, 当达到 NowFlow 时不可再增加, FindFlow: 递归深搜到的最大流
    int UsableFlow = 0, FindFlow;
```

```

// &i=Current[Cur] 为当前弧优化, 每次更新 Current[Cur]
for (int &i = Current[Cur]; ~i; i = edges[i].Next) {
    if (edges[i].Weight > 0 && Depth[edges[i].V] == Depth[Cur] + 1) {
        FindFlow = Dfs(edges[i].V, End, std::min(NowFlow - UsableFlow,
            ↪ edges[i].Weight));
        if (FindFlow > 0) {
            edges[i].Weight -= FindFlow;
            // 反边
            edges[i ^ 1].Weight += FindFlow;
            UsableFlow += FindFlow;
            if (UsableFlow == NowFlow) {
                return NowFlow;
            }
        }
    }
}
// 炸点优化
if (!UsableFlow) {
    Depth[Cur] = -2;
}
return UsableFlow;
}

// Dinic 算法, Start: 起点, End: 终点
int Dinic(int Start, int End) {
    int MaxFlow = 0;
    while (Bfs(Start, End)) {
        // 当前弧优化
        for (int i = 1; i <= N; ++i) {
            Current[i] = Head[i];
        }
        MaxFlow += Dfs(Start, End, INF);
    }
    // 返回结果
    return MaxFlow;
}

```

#### 4.3.2 FordFulkerson

```

#include <bits/stdc++.h>
// 正无穷
const int INF = "Edit";
const int maxn = "Edit";

// N: 顶点数, E: 边数
int N, E;
// 访问标记数组
bool Vis[maxn];
// 邻接矩阵
int Adj[maxn][maxn];

```

```
// Dfs 搜索增广路径, Vertex: 当前搜索顶点, End: 搜索终点, NowFlow: 当前最大流量
int Dfs(int Vertex, int End, int NowFlow) {
    // 搜索到终点结束
    if (Vertex == End) {
        return NowFlow;
    }
    // 标记访问过的顶点
    Vis[Vertex] = true;
    // 枚举寻找顶点
    for (int i = 1; i <= N; ++i) {
        if (!Vis[i] && Adj[Vertex][i]) {
            int FindFlow = Dfs(i, End, NowFlow < Adj[Vertex][i] ? NowFlow :
                               ↪ Adj[Vertex][i]);
            if (!FindFlow) {
                continue;
            }
            // 找到增广路径后更新邻接矩阵残留网
            Adj[Vertex][i] -= FindFlow;
            Adj[i][Vertex] += FindFlow;
            // 返回搜索结果
            return FindFlow;
        }
    }
    // 未找到增广路径, 搜索失败
    return false;
}

// Ford-Fulkerson 算法, Start: 起点, End: 终点
int FordFulkerson(int Start, int End) {
    // MaxFlow: 最大流, Flow: 搜索到的增广路径最大流
    int MaxFlow = 0, Flow = 0;
    memset(Vis, false, sizeof(Vis));
    // 搜索增广路径
    while (Flow = Dfs(Start, End, INF)) {
        MaxFlow += Flow;
        memset(Vis, false, sizeof(Vis));
    }
    // 返回结果
    return MaxFlow;
}
```

#### 4.3.3 MinCostMaxFlow

```
#include <bits/stdc++.h>

const int INF = "Edit";
const int maxn = "Edit";

// 边
```

```
struct Edge {
    // V: 连接点, Flow: 流量, Cost: 费用
    int V, Cap, Cost, Flow, Next;
};

// N: 顶点数, E: 边数
int N, E;
int Head[maxn];
// 前驱记录数组
int Path[maxn];
int Dis[maxn];
// 访问标记数组
bool Vis[maxn];
int Tot;
// 链式前向星
Edge edges[maxn];

// 链式前向星初始化
void Init() {
    Tot = 0;
    memset(Head, -1, sizeof(Head));
}

// 建图加边, U, V 之间建立一条费用为 Cost 的边
void AddEdge(int U, int V, int Cap, int Cost) {
    edges[Tot] = Edge {V, Cap, Cost, 0, Head[U]};
    Head[U] = Tot++;
    edges[Tot] = Edge {U, 0, -Cost, 0, Head[V]};
    Head[V] = Tot++;
}

// SPFA 算法, Start: 起点, End: 终点
bool SPFA(int Start, int End) {
    memset(Dis, INF, sizeof(Dis));
    memset(Vis, false, sizeof(Vis));
    memset(Path, -1, sizeof(Path));
    Dis[Start] = 0;
    Vis[Start] = true;
    std::queue<int> Que;
    while (!Que.empty()) {
        Que.pop();
    }
    Que.push(Start);
    while (!Que.empty()) {
        int U = Que.front();
        Que.pop();
        Vis[U] = false;
        for (int i = Head[U]; ~i; i = edges[i].Next) {
            int V = edges[i].V;
```

```

        if (edges[i].Cap > edges[i].Flow && Dis[V] > Dis[U] + edges[i].Cost) {
            Dis[V] = Dis[U] + edges[i].Cost;
            Path[V] = i;
            if (!Vis[V]) {
                Vis[V] = true;
                Que.push(V);
            }
        }
    }
}
return Path[End] != -1;
}

```

// 最小费用最大流, *Start*: 起点, *End*: 终点, *Cost*: 最小费用

```

int MinCostMaxFlow(int Start, int End, int &MinCost) {
    int MaxFlow = 0;
    MinCost = 0;
    while (SPFA(Start, End)) {
        int Min = INF;
        for (int i = Path[End]; ~i; i = Path[edges[i ^ 1].V]) {
            if (edges[i].Cap - edges[i].Flow < Min) {
                Min = edges[i].Cap - edges[i].Flow;
            }
        }
        for (int i = Path[End]; ~i; i = Path[edges[i ^ 1].V]) {
            edges[i].Flow += Min;
            edges[i ^ 1].Flow -= Min;
            MinCost += edges[i].Cost * Min;
        }
        MaxFlow += Min;
    }
    // 返回最大流
    return MaxFlow;
}

```

## 4.4 ShortestPath

### 4.4.1 BellmanFord

```

#include <bits/stdc++.h>

const int INF = "Edit";
const int maxn = "Edit";

struct Edge {
    // U V: 顶点, Dis: 边权
    int U, V;
    int Dis;
};
// 松弛更新数组

```

```
int Dis[maxn];
// 边
std::vector<Edge> edges;

// Bellman_Ford 算法判断是否存在负环回路
bool BellmanFord(int Start, int N) {
    memset(Dis, INF, sizeof(Dis));
    Dis[Start] = 0;
    // 最多做 N-1 次
    for (int i = 1; i < N; ++i) {
        bool flag = false;
        for (int j = 0; j < int(edges.size()); ++j) {
            if (Dis[edges[j].V] > Dis[edges[j].U] + edges[j].Dis) {
                Dis[edges[j].V] = Dis[edges[j].U] + edges[j].Dis;
                flag = true;
            }
        }
        // 没有负环回路
        if (!flag) {
            return true;
        }
    }
    // 有负环回路
    for (int j = 0; j < int(edges.size()); ++j) {
        if (Dis[edges[j].V] > Dis[edges[j].U] + edges[j].Dis) {
            return false;
        }
    }
    // 没有负环回路
    return true;
}
```

#### 4.4.2 Dijkstra

```
#include <bits/stdc++.h>

const int maxn = "Edit";
const int INF = "Edit";

// 边
struct Edge {
    // V: 连接点, Weight: 权值, Next: 上一条边的编号
    int V, Weight, Next;
};

// 边, 一定要开到足够大
Edge edges[maxn << 1];
// Head[i] 为点 i 上最后一条边的编号
int Head[maxn];
// 增加边时更新编号
```

```
int Tot;
// 松弛更新数组, 最短路
int Dis[maxn];

// 链式前向星初始化
void Init() {
    Tot = 0;
    memset(Head, -1, sizeof(Head));
}

// 添加一条 U 至 V 权值为 Weight 的边
void AddEdge(int U, int V, int Weight) {
    edges[Tot] = Edge(V, Weight, Head[U]);
    Head[U] = Tot++;
}

// 最短路优化堆排序规则
struct Cmp {
    bool operator() (const int &A, const int &B) {
        return Dis[A] > Dis[B];
    }
};

// N: 顶点数, E: 边数
int N, E;

// Dijkstra 算法, Start: 起点
void Dijkstra(int Start) {
    std::priority_queue<int, std::vector<int>, Cmp> Que;
    memset(Dis, INF, sizeof(Dis));
    Dis[Start] = 0;
    Que.push(Start);
    while (!Que.empty()) {
        int U = Que.top(); Que.pop();
        for (int i = Head[U]; ~i; i = edges[i].Next) {
            if (Dis[edges[i].V] > Dis[U] + edges[i].Weight) {
                Dis[edges[i].V] = Dis[U] + edges[i].Weight;
                Que.push(edges[i].V);
            }
        }
    }
}
```

#### 4.4.3 Floyd

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// N: 顶点数
```

```
int N;
// Dis[i][j] 为 i 点到 j 点的最短路
int Dis[maxn][maxn];

// Floyd 算法
void Floyd() {
    for (int k = 1; k <= N; ++k) {
        for (int i = 1; i <= N; ++i) {
            for (int j = 1; j <= N; ++j) {
                Dis[i][j] = std::min(Dis[i][j], Dis[i][k] + Dis[k][j]);
            }
        }
    }
}
```

#### 4.4.4 SPFA

```
#include <bits/stdc++.h>

const int INF = "Edit";
const int maxn = "Edit";

// 边
struct Edge {
    // V: 连接点, Dis: 边权
    int V, Dis;
};

// N: 顶点数, E: 边数
int N, E;
// 访问标记数组
bool Vis[maxn];
// 每个点的入队列次数
int Cnt[maxn];
// 最短路数组
int Dis[maxn];
// 邻接表
std::vector<Edge> Adj[maxn];

// 建图加边, U, V 之间权值为 Weight 的边
void AddEdge (int U, int V, int Weight) {
    Adj[U].push_back(Edge (V, Weight));
    // 无向图建立反向边
    Adj[V].push_back(Edge (U, Weight));
}

// SPFA 算法, Start: 起点
bool SPFA(int Start) {
    memset(Vis, false, sizeof(Vis));
    memset(Dis, INF, sizeof(Dis));
```



```
memset(Cnt, 0, sizeof(Cnt));
Vis[Start] = true;
Dis[Start] = 0;
Cnt[Start] = 1;
std::queue<int> Que;
while (!Que.empty()) {
    Que.pop();
}
Que.push(Start);
while (!Que.empty()) {
    int U = Que.front();
    Que.pop();
    Vis[U] = false;
    for (int i = 0; i < int(Adj[U].size()); ++i) {
        int V = Adj[U][i].V;
        if (Dis[V] > Dis[U] + Adj[U][i].Dis) {
            Dis[V] = Dis[U] + Adj[U][i].Dis;
            if (!Vis[V]) {
                Vis[V] = true;
                Que.push(V);
                // Cnt[i] 为 i 顶点入队列次数, 用来判定是否存在负环回路
                if (++Cnt[V] > N) {
                    return false;
                }
            }
        }
    }
}
return true;
}
```

## 5 DynamicProgramming

### 5.1 Contour

```
#include <bits/stdc++.h>

const int maxn = "Edit";

int Dp[2][1 << maxn];

void Update(int Cur, int A, int B) {
    if (B & (1 << M)) {
        Dp[Cur][B ^ (1 << M)] = Dp[Cur][B ^ (1 << M)] + Dp[Cur ^ 1][A];
    }
}

// 轮廓线 Dp(1*2 在 N*M 图上摆放数)
int Contour(int N, int M) {
    memset(Dp, 0, sizeof(Dp));
    int Cur = 0;
    Dp[Cur][(1 << M) - 1] = 1;
    for (int i = 0; i < N; ++i) {
        for (int j = 0; j < M; ++j) {
            Cur ^= 1;
            memset(Dp[Cur], 0, sizeof(Dp[Cur]));
            for (int k = 0; k < (1 << M); ++k) {
                Update(Cur, k, k << 1);
                if (i && !(k & (1 << (M - 1)))) {
                    Update(Cur, k, (k << 1) ^ (1 << M) ^ 1);
                }
                if (j && !(k & 1)) {
                    Update(Cur, k, (k << 1) ^ 3);
                }
            }
        }
    }
    return Dp[Cur][(1 << M) - 1];
}
```

### 5.2 Digit

```
#include <bits/stdc++.h>

const int maxn = "Edit";

long long Digit[25];
long long Dp[25][maxn];

// Site: 数位, Statu: 状态, Pre: 前导零, Limit: 数位上界
long long Dfs(long long Site, long long Statu, bool Pre, bool Limit) {
```

```
    if (Site == 0) {
        return ?;
    }
    if (!Limit && ~Dp[Site][Statu]) {
        return Dp[Site][Statu];
    }
    long long Max = Limie ? Digit[Site] : 9;
    long long Ans = 0;
    for (int i = 0; i <= Max; ++i) {
        long long NowStatu = /* 状态转移 */;
        if (NowStatu?) {
            Ans += Dfs(Site - 1, NowStatu, Pre && i == 0, Limit && i == Max);
        }
    }
    if (!Limit) {
        Dp[Site][Statu] = Ans;
    }
    return Ans;
}

long long Cal(long long X) {
    // 数位分解
    long long Len = 0;
    while (X) {
        Digit[++Len] = X % 10;
        X /= 10;
    }
    return Dfs(Len, 0, true, true);
}
```

### 5.3 LCS

```
#include <bits/stdc++.h>

const int maxn = "Edit";

// Dp[i][j]:Str1[1]~Str1[i] 和 Str2[1]~Str2[j] 对应的公共子序列长度
int Dp[maxn][maxn];

// 最长公共子序列 (LCS)
void LCS(std::string Str1, std::string Str2) {
    for (int i = 0; i < int(Str1.length()); ++i) {
        for (int j = 0; j < int(Str2.length()); ++j) {
            if (Str1[i] == Str2[j]) {
                Dp[i + 1][j + 1] = Dp[i][j] + 1;
            }
            else {
                Dp[i + 1][j + 1] = std::max(Dp[i][j + 1], Dp[i + 1][j]);
            }
        }
    }
}
```

```
    }  
}
```

## 5.4 LIS

```
#include <bits/stdc++.h>  
  
// 最长不下降子序列 (LIS), Num: 序列  
int LIS(std::vector<int> &Num) {  
    int Ans = 1;  
    // Last[i] 为长度为 i 的不下降子序列末尾元素的最小值  
    std::vector<int> Last(int(Num.size()) + 1, 0);  
    Last[1] = Num[1];  
    for (int i = 2; i <= int(Num.size()); ++i) {  
        if (Num[i] >= Last[Ans]) {  
            Last[++Ans] = Num[i];  
        }  
        else {  
            int Index = std::upper_bound(Last.begin() + 1, Last.end(), Num[i]) -  
                Last.begin();  
            Last[Index] = Num[i];  
        }  
    }  
    // 返回结果  
    return Ans;  
}
```

## 5.5 Pack

```
#include <bits/stdc++.h>  
  
const int maxn = "Edit";  
  
int Dp[maxn];  
// NValue: 背包容量, NKind: 总物品数  
int NValue, NKind;  
  
// 01 背包, 代价为 Cost, 获得的价值为 Weight  
void ZeroOnePack(int Cost, int Weight) {  
    for (int i = NValue; i >= Cost; --i) {  
        Dp[i] = std::max(Dp[i], Dp[i - Cost] + Weight);  
    }  
}  
  
// 完全背包, 代价为 Cost, 获得的价值为 Weight  
void CompletePack(int Cost, int Weight) {  
    for (int i = Cost; i <= NValue; ++i) {  
        Dp[i] = std::max(Dp[i], Dp[i - Cost] + Weight);  
    }  
}
```

```
// 多重背包, 代价为 Cost, 获得的价值为 Weight, 数量为 Amount
void MultiplePack(int Cost, int Weight, int Amount) {
    if (Cost * Amount >= NValue) {
        CompletePack(Cost, Weight);
    }
    else {
        int k = 1;
        while (k < Amount) {
            ZeroOnePack(k * Cost, k * Weight);
            Amount -= k;
            k <<= 1;
        }
        ZeroOnePack(Amount * Cost, Amount * Weight);
    }
}
```

## 6 ComputationalGeometry

### 6.1 Plane

```
#include<bits/stdc++.h>

namespace Geometry {
    const double INF = 1e20;
    const int maxn = 1;
    const double eps = 1e-8;
    const double delta = 0.98;

    int Sgn(double Key) {
        if (fabs(Key) < eps) {
            return 0;
        }
        return Key < 0 ? -1 : 1;
    }

    /*-----点 (向量)-----*/
    struct Point {
        double X, Y;
    };

    typedef Point Vector;

    bool operator == (Point Key1, Point Key2) {
        return Sgn(Key1.X - Key2.X) == 0 && Sgn(Key1.Y - Key2.Y) == 0;
    }

    Vector operator + (Vector Key1, Vector Key2) {
        return (Vector){Key1.X + Key2.X, Key1.Y + Key2.Y};
    }

    Vector operator - (Vector Key1, Vector Key2) {
        return (Vector){Key1.X - Key2.X, Key1.Y - Key2.Y};
    }

    double operator * (Vector Key1, Vector Key2) {
        return Key1.X * Key2.X + Key1.Y * Key2.Y;
    }

    double Length(Vector Key) {
        return sqrt(Key * Key);
    }

    double operator ^ (Vector Key1, Vector Key2) {
        return Length((Vector){Key1.X * Key2.Y - Key1.Y * Key2.X});
    }
}
```

```
Vector operator * (Vector Key1, double Key2) {
    return (Vector){Key1.X * Key2, Key1.Y * Key2};
}

Vector operator / (Vector Key1, double Key2) {
    return (Vector){Key1.X / Key2, Key1.Y / Key2};
}

double DisPointToPoint(Point Key1, Point Key2) {
    return sqrt((Key1 - Key2) * (Key1 - Key2));
}

double GetAngle(Vector Key1, Vector Key2) {
    return fabs(atan2(fabs(Key1 ^ Key2), Key1 * Key2));
}

bool IsConvexHull(vector<Point> points) {
    int N = (int)points.size();
    for (int i = 0; i < N; ++i) {
        if (Sgn((points[(i + 1) % N] - points[i]) ^ (points[(i + 2) % N] -
            ↪ points[(i + 1) % N])) < 0) {
            return false;
        }
    }
    return true;
}

/*-----多边形-----*/
typedef vector<Point> Polygon;

Polygon ConvexHull(vector<Point> points) {
    int N = (int)points.size();
    Polygon Ans;
    if (N < 3) {
        return Ans;
    }
    int Basic = 0;
    for (int i = 0; i < N; ++i) {
        if (points[i].Y > points[Basic].Y || (points[i].Y == points[Basic].Y &&
            ↪ points[i].X < points[Basic].X)) {
            Basic = i;
        }
    }
    std::swap(points[0], points[Basic]);
    std::sort(points.begin() + 1, points.end(), [&] (Point &Key1, Point &Key2)
        ↪ {
        double Temp = (Key1 - points[0]) ^ (Key2 - points[0]);
        if (Temp > 0) {
            return true;
        }
    });
}
```

```
    }
    else if (!Temp && Distance(Key1, points[0]) < Distance(Key2,
    ↪ points[0])) {
        return true;
    }
    return false;
});
Ans.push_back(points[0]);
for (int i = 2; i < N; ++i) {
    while ((int)Ans.size() >= 2 && Sgn((Ans.back() - Ans[(Ans.size()) - 2])
    ↪ ^ (points[i] - Ans[(int)Ans.size() - 2])) <= 0) {
        Ans.pop_back();
    }
}
return Ans;
}

double MinimimCircleCoverage(vector<Point> points) {
    Point Cur = points[0];
    double Probability = 10000, Ans = INF;
    while (Probability > eps) {
        int Book = 0;
        for (int i = 0; i < (int)points.size(); ++i) {
            if (Distance(Cur, points[i]) > Distance(Cur, points[Book])) {
                Book = i;
            }
        }
        double Radius = Distance(Cur, points[Book]);
        Ans = min(Ans, Radius);
        Cur = Cur + (points[Book] - Cur) / Radius * Probability;
        Probability *= delta;
    }
    return Ans;
}

/*-----线 (线段)-----*/
struct Line {
    Point S, T;
};

typedef Line Segment;

double Length(Segment Key) {
    return DisPointToPoint(Key.S, Key.T);
}

double DisPointToLine(Point Key1, Line Key2) {
    return fabs((Key1 - Key2.S) ^ (Key2.T - Key2.S)) / Length(Key2);
}
```



```

double DisPointToSegment(Point Key1, Segment Key2) {
    if (Sgn((Key1 - Key2.S) * (Key2.T - Key2.S)) < 0 || Sgn((Key1 - Key2.T) *
        ↪ (Key2.S - Key2.T)) < 0) {
        return min(DisPointToPoint(Key1, Key2.S), DisPointToPoint(Key1,
            ↪ Key2.T));
    }
    return DisPointToLine(Key1, Key2);
}

bool IsParallel(Line Key1, Line Key2) {
    return Sgn((Key1.S - Key1.T) ^ (Key2.S - Key2.T)) == 0;
}

bool IsSegInterSeg(Segment Key1, Segment Key2) {
    return
        max(Key1.S.X, Key1.T.X) >= min(Key2.S.X, Key2.T.X) &&
        max(Key2.S.X, Key2.T.X) >= min(Key1.S.X, Key1.T.X) &&
        max(Key1.S.Y, Key1.T.Y) >= min(Key2.S.Y, Key2.T.Y) &&
        max(Key2.S.Y, Key2.T.Y) >= min(Key1.S.Y, Key1.T.Y) &&
        Sgn((Key2.S - Key1.T) ^ (Key1.S - Key1.T)) * Sgn((Key2.T - Key1.T) ^
            ↪ (Key1.S - Key1.T)) <= 0 &&
        Sgn((Key1.S - Key2.T) ^ (Key2.S - Key2.T)) * Sgn((Key1.T - Key2.T) ^
            ↪ (Key2.S - Key2.T)) <= 0;
}

bool IsLineInterSeg(Line Key1, Segment Key2) {
    return Sgn((Key2.S - Key1.T) ^ (Key1.S - Key1.T)) * Sgn((Key2.T - Key1.T) ^
        ↪ (Key1.S - Key1.T)) <= 0;
}

bool IsLineInterLine(Line Key1, Line Key2) {
    return !IsParallel(Key1, Key2) || (IsParallel(Key1, Key2) && !(Sgn((Key1.S
        ↪ - Key2.S) ^ (Key2.T - Key2.S)) == 0));
}

Point Cross(Line Key1, Line Key2) {
    double Temp = ((Key1.S - Key2.S) ^ (Key2.S - Key2.T)) / ((Key1.S - Key1.T)
        ↪ ^ (Key2.S - Key2.T));
    return (Point){Key1.S.X + (Key1.T.X - Key1.S.X) * Temp, Key1.S.Y +
        ↪ (Key1.T.Y - Key1.S.Y) * Temp};
}

/*-----半平面-----*/
// 表示 S->T 逆时针 (左侧) 的半平面
struct HalfPlane:public Line {
    double Angle;
};

```

```
void CalAngle(HalfPlane Key) {
    Key.Angle = atan2(Key.T.Y - Key.S.Y, Key.T.X - Key.S.X);
}

bool operator < (HalfPlane Key1, HalfPlane Key2) {
    if (Sgn(Key1.Angle - Key2.Angle) > 0) {
        return Key1.Angle < Key2.Angle;
    }
    return Sgn((Key1.S - Key2.S) ^ (Key2.T - Key2.S)) < 0;
}

struct HalfPlaneInsert {
    int Tot;
    HalfPlane halfplanes[maxn];
    HalfPlane Deque[maxn];
    Point points[maxn];
    Point Res[maxn];
    int Front, Tail;

    void Push(HalfPlane Key) {
        halfplanes[Tot++] = Key;
    }

    void Unique() {
        int Cnt = 1;
        for (int i = 1; i < Tot; ++i) {
            if (fabs(halfplanes[i].Angle - halfplanes[i - 1].Angle) > eps) {
                halfplanes[Cnt++] = halfplanes[i];
            }
        }
        Tot = Cnt;
    }

    bool IsHalfPlaneInsert() {
        for (int i = 0; i < Tot; ++i) {
            CalAngle(halfplanes[i]);
        }
        sort(halfplanes, halfplanes + Tot);
        Unique();
        Deque[Front = 0] = halfplanes[0];
        Deque[Tail = 1] = halfplanes[1];
        for (int i = 2; i < Tot; ++i) {
            if (fabs((Deque[Tail].T - Deque[Tail].S) ^ (Deque[Tail - 1].T -
                ↪ Deque[Tail - 1].S)) < eps || fabs((Deque[Front].T -
                ↪ Deque[Front].S) ^ (Deque[Front + 1].T - Deque[Front + 1].S)) <
                ↪ eps) {
                return false;
            }
        }
    }
}
```

```

        while (Front < Tail && ((Cross(Deque[Tail], Deque[Tail - 1]) -
        ↪ halfplanes[i].S) ^ (halfplanes[i].T - halfplanes[i].S)) > eps)
        ↪ {
            Tail--;
        }
        while (Front < Tail && ((Cross(Deque[Front], Deque[Front + 1]) -
        ↪ halfplanes[i].S) ^ (halfplanes[i].T - halfplanes[i].S)) > eps)
        ↪ {
            Front++;
        }
        Deque[++Tail] = halfplanes[i];
    }
    while (Front < Tail && ((Cross(Deque[Tail], Deque[Tail - 1]) -
    ↪ Deque[Front].S) ^ (Deque[Front].T - Deque[Front].S)) > eps) {
        Tail--;
    }
    while (Front < Tail && ((Cross(Deque[Front], Deque[Front - 1]) -
    ↪ Deque[Tail].S) ^ (Deque[Tail].T - Deque[Tail].T)) > eps) {
        Front++;
    }
    if (Tail <= Front + 1) {
        return false;
    }
    return true;
}

void GetHalfPlaneInsertConvex() {
    int Cnt = 0;
    for (int i = Front; i < Tail; ++i) {
        Res[Cnt++] = Cross(Deque[i], Deque[i + 1]);
    }
    if (Front < Tail - 1) {
        Res[Cnt++] = Cross(Deque[Front], Deque[Tail]);
    }
}

};

/*-----圆-----*/
struct Circle {
    Point Center;
    double Radius;
};

};
using namespace Geometry;

```

## 6.2 Stereoscopic

```
#include<bits/stdc++.h>
```

```
namespace Geometry3D {
```

```
const double INF = 1e20;
const int maxn = "Edit";
const double eps = 1e-8;
const double delta = 0.98;

int Sgn(double Key) {
    if (fabs(Key) < eps) {
        return 0;
    }
    return Key < 0 ? -1 : 1;
}

/*-----点 (向量)-----*/
struct Point {
    double X, Y, Z;
};

typedef Point Vector;

bool operator == (Point Key1, Point Key2) {
    return Sgn(Key1.X - Key2.X) == 0 && Sgn(Key1.Y - Key2.Y) == 0 && Sgn(Key1.Z
    ↪ - Key2.Z) == 0;
}

Vector operator + (Vector Key1, Vector Key2) {
    return (Vector){Key1.X + Key2.X, Key1.Y + Key2.Y, Key1.Z + Key2.Z};
}

Vector operator - (Vector Key1, Vector Key2) {
    return (Vector){Key1.X - Key2.X, Key1.Y - Key2.Y, Key1.Z - Key2.Z};
}

double operator * (Vector Key1, Vector Key2) {
    return Key1.X * Key2.X + Key1.Y * Key2.Y + Key1.Z * Key2.Z;
}

double Length(Vector Key) {
    return sqrt(Key * Key);
}

double operator ^ (Vector Key1, Vector Key2) {
    return Length((Vector){Key1.Y * Key2.Z - Key1.Z * Key2.Y, Key1.Z * Key2.X -
    ↪ Key1.X * Key2.Z, Key1.X * Key2.Y - Key1.Y * Key2.X});
}

Vector operator * (Vector Key1, double Key2) {
    return (Vector){Key1.X * Key2, Key1.Y * Key2, Key1.Z * Key2};
}
```

```
Vector operator / (Vector Key1, double Key2) {
    return (Vector){Key1.X / Key2, Key1.Y / Key2, Key1.Z / Key2};
}

double DisPointToPoint(Point Key1, Point Key2) {
    return sqrt((Key1 - Key2) * (Key1 - Key2));
}

double GetAngle(Vector Key1, Vector Key2) {
    return fabs(atan2(fabs(Key1 ^ Key2), Key1 * Key2));
}

double MinimimSphereCoverage(vector<Point> points, int N) {
    Point Cur = points[0];
    double Probability = 10000, Ans = INF;
    while (Probability > eps) {
        int Book = 0;
        for (int i = 0; i < (int)points.size(); ++i) {
            if (Distance(Cur, points[i]) > Distance(Cur, points[Book])) {
                Book = i;
            }
        }
        double Radius = Distance(Cur, points[Book]);
        Ans = min(Ans, Radius);
        Cur = Cur + (points[Book] - Cur) / Radius * Probability;
        Probability *= delta;
    }
    return Ans;
}

/*-----线 (线段)-----*/
struct Line {
    Point S, T;
};

typedef Line Segment;

double Length(Segment Key) {
    return DisPointToPoint(Key.S, Key.T);
}

double DisPointToLine(Point Key1, Line Key2) {
    return fabs((Key1 - Key2.S) ^ (Key2.T - Key2.S)) / Length(Key2);
}

double DisPointToSegment(Point Key1, Segment Key2) {
    if (Sgn((Key1 - Key2.S) * (Key2.T - Key2.S)) < 0 || Sgn((Key1 - Key2.T) *
        ↪ (Key2.S - Key2.T)) < 0) {
        return min(DisPointToPoint(Key1, Key2.S), DisPointToPoint(Key1,
            ↪ Key2.T));
    }
}
```

```
    }
    return DisPointToLine(Key1, Key2);
}

/*-----球-----*/
struct Sphere {
    Point Center;
    double Radius;
};

double CalVolume(Sphere Key) {
    return 4.0 / 3.0 * pi * Key.Radius * Key.Radius * Key.Radius;
}

double SphereIntersectVolume(Sphere Key1, Sphere Key2) {
    double Ans = 0.0;
    double Dis = DisPointToPoint(Key1.Center, Key2.Center);
    if (Sgn(Dis - Key1.Radius - Key2.Radius) >= 0) {
        return Ans;
    }
    if (Sgn(Key2.Radius - (Dis + Key1.Radius)) >= 0) {
        return CalVolume(Key1);
    }
    else if (Sgn(Key1.Radius - (Dis + Key2.Radius)) >= 0) {
        return CalVolume(Key2);
    }
    double Length1 = ((Key1.Radius * Key1.Radius - Key2.Radius * Key2.Radius) /
        ↪ Dis + Dis) / 2;
    double Length2 = Dis - Length1;
    double X1 = Key1.Radius - Length1, X2 = Key2.Radius - Length2;
    double V1 = pi * X1 * X1 * (Key1.Radius - X1 / 3.0);
    double V2 = pi * X2 * X2 * (Key2.Radius - X2 / 3.0);
    return V1 + V2;
}
};
using namespace Geometry3D;
```

## 7 Others

### 7.1 Factorial

```
#include <bits/stdc++.h>

void Factorial() {
    int res[10010];
    int Book = 1;
    int BaoFour = 0;
    res[Book] = 1;
    int n;
    scanf("%d", &n);
    // 乘法计算
    for (int i = 1; i <= n; ++i) {
        BaoFour = 0;
        for (int j = 1; j <= Book; ++j) {
            res[j] = res[j] * i + BaoFour;
            BaoFour = res[j] / 10000;
            res[j] = res[j] % 10000;
        }
        if (BaoFour > 0) {
            res[++Book] += BaoFour;
        }
    }
    printf("%d", res[Book]);
    // 补零输出
    for (int i = Book - 1; i > 0; --i) {
        if (res[i] >= 1000) {
            printf("%d", res[i]);
        }
        else if (res[i] >= 100) {
            printf("0%d", res[i]);
        }
        else if (res[i] >= 10) {
            printf("00%d", res[i]);
        }
        else {
            printf("000%d", res[i]);
        }
    }
    putchar('\n');
}
```

### 7.2 FastIO

```
#include <bits/stdc++.h>

// 普通读入挂
template <class T>
```

```
inline bool read(T &ret) {
    char c;
    int sgn;
    if (c = getchar(), c == EOF) {
        return false;
    }
    while (c != '-' && (c < '0' || c > '9')) {
        c = getchar();
    }
    sgn = (c == '-') ? -1 : 1;
    ret = (c == '-') ? 0 : (c - '0');
    while (c = getchar(), c >= '0' && c <= '9') {
        ret = ret * 10 + (c - '0');
    }
    ret *= sgn;
    return true;
}

// 普通输出挂
template <class T>
inline void out(T x) {
    if (x < 0) {
        putchar('-');
        x = -x;
    }
    if (x > 9) {
        out(x / 10);
    }
    putchar(x % 10 + '0');
}

// 牛逼读入挂
namespace FastIO {
    const int MX = 4e7;
    char buf[MX];
    int c, sz;
    void begin() {
        c = 0;
        sz = fread(buf, 1, MX, stdin);
    }
    template <class T>
    inline bool read(T &t) {
        while (c < sz && buf[c] != '-' && (buf[c] < '0' || buf[c] > '9')) {
            c++;
        }
        if (c >= sz) {
            return false;
        }
        bool flag = 0;
```



```

    if (buf[c] == '-') {
        flag = 1;
        c++;
    }
    for (t = 0; c < sz && '0' <= buf[c] && buf[c] <= '9'; ++c) {
        t = t * 10 + buf[c] - '0';
    }
    if (flag) {
        t = -t;
    }
    return true;
}
};

// 超级读写挂
namespace IO{
#define BUF_SIZE 100000
#define OUT_SIZE 100000
#define ll long long
//fread->read

bool IOerror=0;
inline char nc(){
    static char buf[BUF_SIZE],*p1=buf+BUF_SIZE,*pend=buf+BUF_SIZE;
    if (p1==pend){
        p1=buf; pend=buf+fread(buf,1,BUF_SIZE,stdin);
        if (pend==p1){IOerror=1;return -1;}
        //printf("IO error!\n");system("pause");for (;;)exit(0);}
    }
    return *p1++;
}

inline bool blank(char ch){return ch==' '||ch=='\n'||ch=='\r'||ch=='\t';}
inline void read(int &x){
    bool sign=0; char ch=nc(); x=0;
    for (;blank(ch);ch=nc());
    if (IOerror)return;
    if (ch=='-')sign=1,ch=nc();
    for (;ch>='0'&&ch<='9';ch=nc())x=x*10+ch-'0';
    if (sign)x=-x;
}

inline void read(ll &x){
    bool sign=0; char ch=nc(); x=0;
    for (;blank(ch);ch=nc());
    if (IOerror)return;
    if (ch=='-')sign=1,ch=nc();
    for (;ch>='0'&&ch<='9';ch=nc())x=x*10+ch-'0';
    if (sign)x=-x;
}

inline void read(double &x){

```

```
bool sign=0; char ch=nc(); x=0;
for (;blank(ch);ch=nc());
if (IOerror)return;
if (ch=='-')sign=1,ch=nc();
for (;ch>='0'&&ch<='9';ch=nc())x=x*10+ch-'0';
if (ch=='.'){
    double tmp=1; ch=nc();
    for (;ch>='0'&&ch<='9';ch=nc())tmp/=10.0,x+=tmp*(ch-'0');
}
if (sign)x=-x;
}
inline void read(char *s){
    char ch=nc();
    for (;blank(ch);ch=nc());
    if (IOerror)return;
    for (;!blank(ch)&&!IOerror;ch=nc())*s++=ch;
    *s=0;
}
inline void read(char &c){
    for (c=nc();blank(c);c=nc());
    if (IOerror){c=-1;return;}
}
//fwrite->write
struct Ostream_fwrite{
    char *buf,*p1,*pend;
    Ostream_fwrite(){buf=new char[BUF_SIZE];p1=buf;pend=buf+BUF_SIZE;}
    void out(char ch){
        if (p1==pend){
            fwrite(buf,1,BUF_SIZE,stdout);p1=buf;
        }
        *p1++=ch;
    }
}
void print(int x){
    static char s[15],*s1;s1=s;
    if (!x)*s1++='0';if (x<0)out('-'),x=-x;
    while(x)*s1++=x%10+'0',x/=10;
    while(s1--!=s)out(*s1);
}
void println(int x){
    static char s[15],*s1;s1=s;
    if (!x)*s1++='0';if (x<0)out('-'),x=-x;
    while(x)*s1++=x%10+'0',x/=10;
    while(s1--!=s)out(*s1); out('\n');
}
void print(ll x){
    static char s[25],*s1;s1=s;
    if (!x)*s1++='0';if (x<0)out('-'),x=-x;
    while(x)*s1++=x%10+'0',x/=10;
    while(s1--!=s)out(*s1);
```

```

}
void println(ll x){
    static char s[25],*s1;s1=s;
    if (!x)*s1++='0';if (x<0)out('-'),x=-x;
    while(x)*s1++=x%10+'0',x/=10;
    while(s1--!=s)out(*s1); out('\n');
}
void print(double x,int y){
    static ll mul[]={1,10,100,1000,10000,100000,1000000,10000000,100000000,
        ↪ 1000000000,10000000000LL,100000000000LL,1000000000000LL,10000000000000LL,
        ↪ 100000000000000LL,1000000000000000LL,10000000000000000LL,100000000000000000LL,
    if (x<-1e-12)out('-'),x=-x;x*=mul[y];
    ll x1=(ll)floor(x); if (x-floor(x)>=0.5)++x1;
    ll x2=x1/mul[y],x3=x1-x2*mul[y]; print(x2);
    if (y>0){out('.'); for (size_t i=1;i<y&& x3*mul[i]<mul[y];out('0'),++i);
        ↪ print(x3);}
}
void println(double x,int y){print(x,y);out('\n');}
void print(char *s){while (*s)out(*s++);}
void println(char *s){while (*s)out(*s++);out('\n');}
void flush(){if (p1!=buf){fwrite(buf,1,p1-buf,stdout);p1=buf;}}
~Ostream_fwrite(){flush();}
}Ostream;
inline void print(int x){Ostream.print(x);}
inline void println(int x){Ostream.println(x);}
inline void print(char x){Ostream.out(x);}
inline void println(char x){Ostream.out(x);Ostream.out('\n');}
inline void print(ll x){Ostream.print(x);}
inline void println(ll x){Ostream.println(x);}
inline void print(double x,int y){Ostream.print(x,y);}
inline void println(double x,int y){Ostream.println(x,y);}
inline void print(char *s){Ostream.print(s);}
inline void println(char *s){Ostream.println(s);}
inline void println(){Ostream.out('\n');}
inline void flush(){Ostream.flush();}
#undef ll
#undef OUT_SIZE
#undef BUF_SIZE
};
using namespace IO;

```

### 7.3 LeapYear

```

#include <bits/stdc++.h>

inline bool Leap(int Year) {
    return (!(Year % 4) && (Year % 100)) || !(Year % 400);
}

```

## 7.4 NimGame

```
#include <bits/stdc++.h>

// 尼姆博弈
bool Nim(std::vector<int> Num) {
    int Ans = 0;
    for (int i = 0; i < int(Num.size()); ++i) {
        Ans ^= Num[i];
    }
    // ans 不为零则先手赢, 否则为后手赢
    return Ans != 0 ? true : false;
}
```

## 7.5 vim

```
syntax on
set nu
set tabstop=4
set shiftwidth=4
set cindent
set mouse=a
set expandtab
set backspace=indent,eol,start
```

```
map <F2> :call SetTitle(<CR>
```

```
func SetTitle()
    let l = 0
    let l = l + 1 | call setline(l, "#include <bits/stdc++.h>")
    let l = l + 1 | call setline(l, "using namespace std;")
    let l = l + 1 | call setline(l, "")
    let l = l + 1 | call setline(l, "int main(int argc, char *argv[]) {")
    let l = l + 1 | call setline(l, "    return 0;")
    let l = l + 1 | call setline(l, "}")
    let l = l + 1 | call setline(l, "")
endfunc
```