

APIs

Paul Bradshaw

What is an API (for)?

- **Interface** between your machine and a database
- Especially useful for getting the **latest** data
- And for getting **contextual** data

For example...

- The [police API](#) will give you the latest crime data for a particular force/location
- The [postcodes.io](#) API will give you the constituency etc for a given postcode
- [TheyWorkForYou's API](#) will give you the MP/party representing that postcode



global witness

Report / 23 Oct 2015

JADE: MYANMAR'S "BIG STATE SECRET"

The biggest natural resources heist in modern history?


Reconciliation with OpenCorporates API

Transliteration always introduces some ambiguity and there are often numerous ways to convert a specific company name from one script to another. Fortunately, OpenCorporates has a service that lets users find company names in the database that are near but not exact matches. This all happens via an [‘endpoint’](#) through which users can load the data they want to reconcile into [OpenRefine](#). OpenCorporates will then return a likely set of matches against the company names you have imported. In the case of this investigation, many of the companies returned multiple matches. The mining, gems and trading arms of companies were often separated into different legal entities under the same name. Take for example, Max Burma Company: there is a [general limited company](#), a [gems and jewellery arm](#) as well as a [construction company](#).

Online fashion twice as 'racy' as High Street

By Will Dahlgreen & Colletta Smith
BBC News

🕒 17 October 2019



How Google defines 'racy'

Scores given by Google Vision AI



Source: Misguided (a), Nasty Gal (b), Pretty Little Thing (c), Mennace (d), Urban Outfitters (e), Boohoo (f), Topman (g), Asos (h)

BBC

Google's software scores images from one to five in terms of how likely they are to be, what they call, "racy".

It is part of their "Safe Search" tool, which detects adult, spoof, medical, violent and "racy" images.

The BBC's analysis only counted images with a score of four ('likely racy') or five ('very likely racy') as "racy". For comparison, the average picture in lads magazine FHM's "100 Sexiest Women" 2005 edition had a "racy" score of four.

<https://www.bbc.co.uk/news/business-49987037>

Faces

Objects

Labels

Web


Text

Properties

Safe Search



305799.jpg



Likelihood values are Unknown, Very I
Possible, Likely, and Very Likely

Faces

Objects

Labels

Web

Text

Properties

Safe Search



305799.jpg

+Page 1

+Block 1

17

+Block 2

AVAILABLE IN BIG , TALL & SHORT

<https://cloud.google.com/vision/>



APIs

AV Live Logging

[Download](#)[Learn more](#)[Explore data](#)

Bills

[Download](#)[Learn more](#)[Explore data](#)

Committee Reports

[Release TBC](#)[Learn more](#)

Commons Answered Questions

[Download](#)[Learn more](#)[Explore data](#)

Commons Committee Inquiries

[Release TBC](#)[Learn more](#)

Commons Committee Publications

[Release TBC](#)[Learn more](#)

Commons Divisions

[Download](#)[Learn more](#)[Explore data](#)


Commons Oral Question Times

[Download](#)[Learn more](#)[Explore data](#)

Commons Oral Questions









[Download](#)[Learn more](#)[Explore data](#)

Use Google APIs in Sheets



API examples in Google Sheets

File Edit View Insert Format Data Tools Add-ons Help All

    100%  £ % .0  .00  123  Arial

fx

=GOOGLETRANSLATE(A3,"en","es")

	A	B
1	Documentation at	https://support.google.com/docs/answer/3093331?vi
2	Text to translate	Formula: translate English ("en") to Spanish ("es") F
3	Hello friend	Hola amigo
4	Until later	Hasta más tarde
5	I cannot do that	No puedo hacer eso
6	I speak beautiful Spanish	Hablo español hermosa
7		

Look at an example

- Go to data.police.uk and click on the [API tab](#)
- This is the ‘documentation’ for the API, telling you how to get data out of it — but it’s full of jargon...

API Functions



- [convertURL](#)
Converts a parliament URL into a TheyWorkForYou one, if possible
- [getConstituency](#)
Searches for a UK Parliament constituency and returns details
- [getConstituencies](#)
Returns list of UK Parliament constituencies
- [getPerson](#)
Returns main details for
- [getMP](#)
Returns main details for
- [getMPInfo](#)
Returns extra information

Methods



The following is a list of API methods

Postcode Lookup


Lookup a postcode. Returns all available data if found. Returns 404 if postcode does not

```
https://api.postcodes.io/postcodes/:postcode
```

Bulk Postcode Lookup

Accepts a JSON object containing an array of postcodes. Returns a list of matching postcodes and respective available data.

Methods



[Availability](#)

Force related:

[Forces](#)

[Specific force](#)

[Force senior officers](#)

Crime related:

[Street level crimes](#)

[Street level outcomes](#)

[Crimes at location](#)

[Crimes with no location](#)

[Crime categories](#)

[Last updated](#)

[Outcomes for a specific crime](#)

Methods, functions and parameters

- **Methods/functions** - words to get different types of information (e.g. 'getMPname')
- **Parameters/arguments** - words that specify what you want data on (e.g. date range, lat/long, etc)

Force related:

[Forces](#)

[Specific force](#)

[Force senior officers](#)

Crime related:

[Street level crimes](#)

[Street level outcomes](#)

[Crimes at location](#)

[Crimes with no location](#)

[Crime categories](#)

[Last updated](#)

[Outcomes for a specific crime](#)

Neighbourhood related:

[Neighbourhoods](#)

[Specific neighbourhood](#)

[Neighbourhood boundary](#)

[Neighbourhood team](#)

[Neighbourhood events](#)

[Neighbourhood priorities](#)

[Locate neighbourhood](#)

Stop and search related:

[Stop and searches by area](#)

[Stop and searches by location](#)

[Stop and searches with no location](#)

[Stop and searches by force](#)

Request parameters

location_id	The ID of the location to get stop and searches for
date	Optional. (YYYY-MM) Limit results to a specific month. The latest month will be shown by default.

Example request

https://data.police.uk/api/stops-at-location?location_id=883407&date=2017-01

Request parameters

force	The force ID of the force to get stop and searches for
date	Optional. (YYYY-MM) Limit results to a specific month. The latest month will be shown by default, even if no data is available for that force . API method to pick a date if this is significant for you

Example request

<https://data.police.uk/api/stops-force?force=avon-and-somerset&date=2017-01>

TheyWorkForYou API

getConstituency function

<http://www.theyworkforyou.com/api/getConstituency>

Fetch a UK Parliament constituency.

Arguments

name

Fetch the data associated to the constituency.

postcode

Fetch the constituency with associated postcode.

Explorer

Try out this function without writing any code!

name:

postcode:

Output: ☒ JS ☐ XML ☐ Serialised PHP ☐ RABX

Output

URL for this: [http://www.theyworkforyou.com/api/getConstituency?](http://www.theyworkforyou.com/api/getConstituency?name=Birmingham%2C+Perry+Barr&postcode=b422su&output=js)

[name=Birmingham%2C+Perry+Barr&postcode=b422su&output=js](http://www.theyworkforyou.com/api/getConstituency?name=Birmingham%2C+Perry+Barr&postcode=b422su&output=js)

```
{
  "bbc_constituency_id" : "59",
  "guardian_election_results" : "http://www.guardian.co.uk/politics/constituency/720/birmingham-per",
  "guardian_id" : "720",
  "guardian_name" : "Birmingham Perry Barr",
  "pa_id" : "63",
  "name" : "Birmingham, Perry Barr"
}
```

API Endpoint & Methods



Lookup a postcode

GET

api.postcodes.io/postcodes/:postcode

Request



GET companies/:jurisdiction_code/:company_number

Description: This returns the core data for the given company. The jurisdiction code is the code for the jurisdiction which registered the company. If this is a country it is simply the two-letter ISO code for that country, e.g. Spain = es, United Kingdom = gb. If this is a state or province it is an underscore version of the ISO 3166-2 code for the jurisdiction, eg. Michigan in the US is us_mi.

Queries and endpoints

- **A query/request/GET** - Your question - normally formulated as a URL
- **A response** - the data you get (at that URL)
- **Endpoint** - Another word for the URL

Request parameters

location_id	The ID of the location to get stop and searches for
date	Optional. (YYYY-MM) Limit results to a specific month. The latest month will be shown by default.

Example request

https://data.police.uk/api/stops-at-location?location_id=883407&date=2017-01

Request parameters

force	The force ID of the force to get stop and searches for
date	Optional. (YYYY-MM) Limit results to a specific month. The latest month will be shown by default, even if no data is available for that force . API method to pick a date if this is significant for you

Example request

<https://data.police.uk/api/stops-force?force=avon-and-somerset&date=2017-01>

Authentication and keys

- Some APIs require a 'key'
- This is just a password - apply for it on the site
- Use it by including in your 'request' URL

Overview

1. **Get an API key.**
2. All requests are made by GETting a particular URL with a number of parameters. *key* is required; *output* is optional, and defaults to `js`.

**`http://www.theyworkforyou.com/api/function?
key=key&output=output&other_variables`**

The current version of the API is *1.0.0*. If we make changes to the API functions, we'll increase the version number and make it an argument so you can still use the old version.

Outputs

The *output* argument can take any of the following values:

xml. XML. The root element is `twfy`.

php. Serialized PHP, that can be turned back into useful information with the `unserialize()` command. Quite useful in Python as well, using **PHPUnserialize**.

js. A JavaScript object. You can provide a callback function with the *callback* variable, and then that function will be called with the data as its argument.

rabx. "RPC over Anything But XML".

Errors

If there's an error, either in the arguments provided or in trying to perform the request, this is returned as a top-level error string, ie. in XML it returns `<twfy><error>ERROR</error></twfy>`; in JS `{"error": "ERROR"}`; and in PHP and RABX a serialised array containing one entry with key `error`.


Call/rate limits

- APIs often involve making multiple ‘calls’ for data, e.g. hundreds of postcodes
- May be a limit on rate (per second) and number (per day)

Looking at a response

- Try an example URL given (*tip: change the year on police URLs - it's now too long ago*)
- E.g. <https://data.police.uk/api/forces>
- Or <https://data.police.uk/api/forces/leicestershire>

[{"nid": "25674", "title": "202 Anglers Road", "lat": "0", "lng": "0", "type": "463", "image": "", "type_label": "Building", "build_img": "", "contain_img": "", "grave_img": "hreflang=\"und\">204 Anglers", "lat": "0", "lng": "0", "type": "463", "image": "", "type_label": "Building", "build_img": "", "cont href=\"\\buildings\\104-beebe-avenue\" hreflang=\"und\">104 Beebe Avenue", "lat": "38.776808", "lng": "-75.142949", "type": "463", "image": "", "type_label": "Building", "build_img": "", "contain_i href=\"\\buildings\\106-beebe-avenue\" hreflang=\"und\">106 Beebe Avenue", "lat": "38.770182", "lng": "-75.142674", "type": "463", "image": "", "type_label": "Building", "build_img": "", "contain_i href=\"\\buildings\\106-beebe-avenue-0\" hreflang=\"und\">106 Beebe Avenue", "lat": "38.770182", "lng": "-75.142674", "type": "463", "image": "", "type_label": "Building", "build_img": "public:\\\\2 href=\"\\buildings\\107-109-beebe-avenue\" hreflang=\"und\">107 -109 Beebe Avenue", "lat": "38.770423", "lng": "-75.142371", "type": "463", "image": "", "type_label": "Building", "build_img": "", "contain_i href=\"\\buildings\\107-109-beebe-avenue-0\" hreflang=\"und\">107 -109 Beebe Avenue", "lat": "38.770423", "lng": "-75.142371", "type": "463", "image": "", "type_label": "Building", "build_img": "public:\\\\2 {"nid": "25681", "title": "108 Beebe Avenue", "lat": "38.770072", "lng": "-75.142588", "type": "463", "image": "", "type_label": "Building", "build_img": "", "contain_i href=\"\\buildings\\108-beebe-avenue-0\" hreflang=\"und\">108 Beebe Avenue", "lat": "38.770072", "lng": "-75.142588", "type": "463", "image": "", "type_label": "Building", "build_img": "public:\\\\2 href=\"\\buildings\\110-beebe-avenue\" hreflang=\"und\">110 Beebe Avenue", "lat": "38.770038", "lng": "-75.142438", "type": "463", "image": "", "type_label": "Building", "build_img": "", "contain_i href=\"\\buildings\\110-beebe-avenue-0\" hreflang=\"und\">110 Beebe Avenue", "lat": "38.770038", "lng": "-75.142438", "type": "463", "image": "", "type_label": "Building", "build_img": "public:\\\\2 {"nid": "25685", "title": "112 Beebe Avenue", "lat": "38.770000", "lng": "-75.142300", "type": "463", "image": "", "type_label": "Building", "build_img": "public:\\\\2



Install JSONView extension



JSONView

offered by [gildas](#)

★★★★★ (2598)

[Developer Tools](#)

1,079,459 users

ADDED TO CHROME



OVERVIEW

REVIEWS

SUPPORT

RELATED



```
- indices: [
  119,
  139
],
expanded_url: "https://dev.twitter.com/form/seattle-dev-te",
display_url: "dev.twitter.com/form/seattle-d...",
url: "http://t.co/afOxBauf"
},
- user_mentions: [
  - {
    name: "Twitter API",
    screen_name: "twitterapi",
    id_str: "6253282",
    - indices: [
      80,
      91
    ]
  }
]
```

[+ - View source](#)



Compatible with your device

Validate and view JSON documents

JSONView port for Chrome.

Original firefox extension is here:
<http://benhollis.net/software/jsonview/>

Notes:

- JSON is validated using a client-side javascript implementation of JSONLint (<http://github.com/zaach/jsonlint>)
- this extension displays JSON text compliant with rfc 4627 (<http://www.ietf.org/rfc/rfc4627.txt>).
- JSONP (<http://en.wikipedia.org/wiki/JSONP>) is

[Website](#)

<https://data.police.uk/api/forces>

```
[
  - {
    id: "avon-and-somerset",
    name: "Avon and Somerset Constabulary"
  },
  - {
    id: "bedfordshire",
    name: "Bedfordshire Police"
  },
  - {
    id: "cambridgeshire",
    name: "Cambridgeshire Constabulary"
  },
  - {
    id: "cheshire",
    name: "Cheshire Constabulary"
  },
]
```



Table of contents



+ Code + Text

Connect ▾

Editing



Using APIs for data



Importing pandas to fetch the data from the API



Reading data from an online source

Querying the postcodes API

Drilling into the JSON

Forming a 'request' for the police data API

Using json_normalize

Checking which fields are dictionaries

Deprecated?

Merging the resulting branches

+ Section



▼ Using APIs for data

An API is one way of getting data from a web resource. Typically you get data by forming a URL - the URL is basically your 'question' (**query** or **request**), and the webpage that is delivered to you (the **endpoint**) contains the 'response' with the data, often in JSON format.

The [postcodes API](#), for example, can be queried by putting a postcode (without spaces) at the *end* of this URL:

```
http://api.postcodes.io/postcodes/
```

To ask about the postcode B42 2SU, then, you would add it to the end to form the URL:

```
http://api.postcodes.io/postcodes/b422su
```

If you go to that URL you will get a bunch of code in **JSON** - this is the data for that postcode. If you want it to look a bit easier to understand use the browser extension [JSONView](#).

▼ Importing pandas to fetch the data from the API

To import JSON files we need to import the `pandas` library. This can load data directly from a URL which we will generate to query the API for JSON data.

```
[ ] #import the pandas library and call it 'pd' for the rest of the notebook
```

Use pandas's read_json() function

```
mydata = pd.read_json("URLHERE")
```

▼ Importing pandas to fetch the data from the API

To import JSON files we need to import the pandas library. This can load data directly from a URL which we will generate to query the API for JSON data.

```
[ ] #import the pandas library and call it 'pd' for the rest of the notebook
    import pandas as pd
```

▼ Reading data from an online source

The `.read_json()` function from the pandas library can be used to import JSON an online source - you just need to use the URL of the file.

Below we import JSON [from data.police.uk](https://data.police.uk)

```
[ ] policedata = pd.read_json("https://data.police.uk/api/forces")
    print(policedata.head(3))
```

	id	name
0	avon-and-somerset	Avon and Somerset Constabulary
1	bedfordshire	Bedfordshire Police
2	cambridgeshire	Cambridgeshire Constabulary

Loop to get data on multiple items

```
for postcode in listofpostcodes:
```

```
    apirequest = BASEURL+postcode
```

```
    thisdata = pd.read_json(apirequest)
```

Key points

- Use an API to get the latest data or data to complement other info
- Form a 'request' in the form of a URL that contains details on what you want data on (and any 'key')
- Results often in JSON/XML format - and need looping through