

Contents

1	C++20	1
1.1	format / println	1
2	Basic	1
2.1	compile	1
2.2	default code	1
2.3	debug list	1
2.4	時間複雜度	1
3	Dark Code	1
3.1	IO optimization	1
4	Geometry	1
4.1	2D point	1
4.2	兩線段交點	1
4.3	兩圓交點	1
4.4	Convex Hull	1
5	Flow	1
5.1	Dinic	1
5.2	min cost flow	1
6	Mathematics	1
6.1	ax+by=gcd(a,b)	1
6.2	GaussElimination	1
6.3	Inverse	1
6.4	LinearPrime 歐拉篩	1
6.5	Miller Rabin	1
6.6	Pollard's rho	1
6.7	NTT	1
6.8	數論基本工具	1
6.9	Mobius	1
6.10	SG	1
6.11	歐拉定理	1
6.12	Theorem	1
7	Graph	1
7.1	BCC	1
7.2	Prim	1
7.3	Bellman Ford	1
7.4	Kruskal	1
7.5	Dijkstra	1
7.6	Strongly Connected Component(SCC)	1
7.7	Hungarian	1
7.8	KM	1
7.9	最小平均環	1
7.10	偵測負環	1
7.11	Tarjan	1
7.12	Topological Sort	1
8	Data Structure	1
8.1	2D Range Tree	1
8.2	Segment Tree	1
8.3	ZKW 線段樹	1
8.4	Sparse Table	1
8.5	Lazy Tag	1
8.6	BIT 樹狀樹組	1
8.7	並查集 union find	1
8.8	Treap	1
8.9	2D BIT	1
9	String	1
9.1	KMP	1
9.2	smallest rotation	1
9.3	Suffix Array	1
9.4	Z-value	1
9.5	旋轉哈希	1
9.6	後綴自動機	1
10	Others	1
10.1	矩陣樹定理	1
10.2	1D/1D dp 優化	1
10.3	Theorem - DP optimization	1
10.4	Stable Marriage	1
10.5	莫隊	1
10.6	莫隊帶修改	1
10.7	矩陣乘法	1
10.8	c++ 小抄	1
10.9	python 小抄	1
10.10	萬年曆	1
10.11	多重背包	1

1 C++20

1.1 format / println

```
#include <format>

template<class... t>
void println(format_string<t...> fmt, t&&... args) {
    cout << format(fmt, forward<t>(args)...) << '\n';
}

/*
format("{} + {} = {}", 2, 3, 5); // "2 + 3 = 5"
format("{} {} {}", "a", "b");    // "b a"

double x = 3.1415926;
format("{:.3f}", x); // "3.142": fixed, 3 digits after
                    decimal point
format("{:.3}", x);  // "3.14": 3 significant digits
format("{:8.2f}", x); // width 8, fixed 2 digits

format("{:<8}", "hi"); // Left align
format("{:^8}", "hi"); // center
format("{:>8}", "hi"); // right align
format("{:08}", 42);   // "00000042"
format("{:+}", 42);    // "+42"
format("{:#x}", 255);  // "0xff"
format("{}{}", 42);    // "{42}"

println("answer = {}", 42);
println("pi = {:.6f}", numbers::pi);

C++23 has std::println; this is the C++20 replacement.
Do not add custom functions to namespace std.
*/
```

2 Basic

2.1 compile

```
# preset before coding
echo "cd ~/Desktop" >> ~/.bashrc
gedit -> preference -> tab width: 4

# Editor
gedit a.cpp

# Compile
g++ a.cpp -std=c++20 -O2 -pipe -Wall

g++ -std=c++20 -Wall -Wextra -Wshadow -Wconversion
-g -fsanitize=address,undefined
main.cpp -o main

// -Wmisleading-indentation # 檢測縮排不對 for loop 沒
// 括號卻寫兩行
// -Wfatal-errors #讓編譯器只跳一個錯

ASAN_OPTIONS=detect_leaks=0 ./main #叫他不要叫mem leak
// -fsanitize=address 檢測記憶體違規存取

**All file will be compiled to a.out unless you use -o(
not recommended, just use a.out)**

# Run
./a.out

# Run with file input
./a.out < input.txt

# Run with file input and output
./a.out < input.txt > output.txt

# Python Run
python3 a.py < input.txt > output.txt

# Copy Paste In Ubuntu
* copy: ctrl+insert
```

```
* paste: shift+insert
# 比對文件相同
sdiff a.txt b.txt
```

2.2 default code

```
#include <bits/stdc++.h>
using namespace std;

using ll = long long;

int main() {
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
}
```

2.3 debug list

記得測試 python 的內建函數庫有哪些
bits/stdc++.h 跟 global variable y1 衝突，不能用
模板要記得 init
priority_queue 要清空
事先將把邊界測資加入測試
邊界條件（過程溢位，題目數據範圍），會不會爆 long long
是否讀錯題目，想不到時可以自己讀一次題目
比較容易有問題的地方換人寫
注意公式有沒有推錯或抄錯
精度誤差 sqrt(大大的東西) + EPS
喇分 random_shuffle 隨機演算法

2.4 時間複雜度

時間複雜度	可處理的最大 N 數量級 (約)
$O(1)$	幾乎沒限制
$O(\log N)$	10^{18} 級別 (如快速幕)
$O(\sqrt{N})$	10^{10}
$O(N)$	10^8
$O(N \log N)$	$10^6 \sim 5 \times 10^6$
$O(N\sqrt{N})$	$1 \times 10^5 \sim 2 \times 10^5$
$O(N^2)$	$3 \times 10^3 \sim 10^4$
$O(N^2 \log N)$	$10^3 \sim 3 \times 10^3$
$O(N^3)$	$300 \sim 500$
$O(2^N)$	$N \leq 20$
$O(N!)$	$N \leq 10$

3 Dark Code

3.1 IO optimization

```
// fread input. read(x) returns false on eof.
struct fast_input {
    static constexpr size_t size = 1 << 16;
    array<char, size> buf{};
    size_t pos = 0, len = 0;

    int get() {
        if (pos == len) {
            len = fread(buf.data(), 1, size, stdin);
            pos = 0;
            if (!len) return EOF;
        }
        return buf[pos++];
    }

    template<class t>
    bool read(t &x) {
        int c = get(), sign = 1;
        while (c != EOF && c != '-' && (c < '0' || c > '9')) c = get();
        if (c == EOF) return false;
        if (c == '-') sign = -1, c = get();
        x = 0;

```

```
while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = get();
x *= sign;
return true;
}
};
```

4 Geometry

4.1 2D point

```
using ld = long double;
const ld eps = 1e-12L;

struct point {
    ld x = 0, y = 0;
};

point operator+(point a, point b) { return {a.x + b.x, a.y + b.y}; }
point operator-(point a, point b) { return {a.x - b.x, a.y - b.y}; }
point operator*(point p, ld k) { return {p.x * k, p.y * k}; }
ld dot(point a, point b) { return a.x * b.x + a.y * b.y; }
ld cross(point a, point b) { return a.x * b.y - a.y * b.x; }
ld norm2(point p) { return dot(p, p); }
ld norm(point p) { return sqrtl(norm2(p)); }
```

4.2 兩線段交點

```
using i128 = __int128_t;

struct ipoint {
    long long x, y;
};

i128 cross(ipoint a, ipoint b, ipoint c) {
    return (i128(b.x) - a.x) * (i128(c.y) - a.y) -
        (i128(b.y) - a.y) * (i128(c.x) - a.x);
}

int sign(i128 x) { return (x > 0) - (x < 0); }

bool on_segment(ipoint a, ipoint b, ipoint p) {
    return cross(a, b, p) == 0 &&
        min(a.x, b.x) <= p.x && p.x <= max(a.x, b.x) &&
        min(a.y, b.y) <= p.y && p.y <= max(a.y, b.y);
}

bool segments_intersect(ipoint a, ipoint b, ipoint c, ipoint d) {
    i128 x = cross(a, b, c), y = cross(a, b, d);
    i128 z = cross(c, d, a), w = cross(c, d, b);
    if (!x && on_segment(a, b, c)) return true;
    if (!y && on_segment(a, b, d)) return true;
    if (!z && on_segment(c, d, a)) return true;
    if (!w && on_segment(c, d, b)) return true;
    return sign(x) != sign(y) && sign(z) != sign(w);
}
```

4.3 兩圓交點

```
// count: -1 identical circles; otherwise number of points
struct circle_hit {
    int count;
    vector<point> p;
};
```

```

circle_hit circle_intersections(point a, ld r, point b,
ld s) {
    point d = b - a;
    ld d2 = norm2(d), len = sqrtl(d2);
    if (len <= eps && fabs1(r - s) <= eps) return {-1,
    {}};
    if (len <= eps || len > r + s + eps || len < fabs1(
    r - s) - eps)
        return {0, {}};

    ld x = (d2 + r * r - s * s) / (2 * len);
    ld h2 = max<ld>(0, r * r - x * x);
    point mid = a + d * (x / len);
    if (h2 <= eps) return {1, {mid}};
    point off{-d.y * sqrtl(h2) / len, d.x * sqrtl(h2) /
    len};
    return {2, {mid + off, mid - off}};
}

```

4.4 Convex Hull

```

// needs point, cross and eps from 2Dpoint.cpp
vector<point> convex_hull(vector<point> p) {
    ranges::sort(p, [](point a, point b) {
        return tie(a.x, a.y) < tie(b.x, b.y);
    });
    p.erase(ranges::unique(p, [](point a, point b) {
        return fabs1(a.x - b.x) <= eps && fabs1(a.y - b
        .y) <= eps;
    })).begin(), p.end());
    if (p.size() <= 1) return p;

    vector<point> h;
    for (int pass = 0; pass < 2; ++pass) {
        size_t base = h.size();
        for (point q : p) {
            while (h.size() >= base + 2 &&
                cross(h.back() - h[h.size() - 2], q
                - h.back()) <= eps)
                h.pop_back();
            h.push_back(q);
        }
        h.pop_back();
        ranges::reverse(p);
    }
    return h; // ccw; first point is not repeated
}

```

5 Flow

5.1 Dinic

```

using ll = long long;
const ll inf = LLONG_MAX / 4;

struct dinic {
    struct edge { int to, rev; ll cap; };
    vector<vector<edge>> g;
    vector<int> level, it;

    dinic(int n) : g(n), level(n), it(n) {}
    void add_edge(int u, int v, ll cap) {
        int a = g[u].size(), b = g[v].size();
        g[u].push_back({v, b, cap});
        g[v].push_back({u, a, 0});
    }
    bool bfs(int s, int t) {
        ranges::fill(level, -1);
        queue<int> q;
        level[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (auto &e : g[u]) if (e.cap && level[e.
            to] == -1)

```

```

                level[e.to] = level[u] + 1, q.push(e.to
                );
            }
            return level[t] != -1;
        }
        ll dfs(int u, int t, ll flow) {
            if (u == t) return flow;
            for (int &i = it[u]; i < ssize(g[u]); ++i) {
                edge &e = g[u][i];
                if (!e.cap || level[e.to] != level[u] + 1)
                    continue;
                ll got = dfs(e.to, t, min(flow, e.cap));
                if (!got) continue;
                e.cap -= got;
                g[e.to][e.rev].cap += got;
                return got;
            }
            return 0;
        }
        ll max_flow(int s, int t) {
            ll ans = 0, got;
            while (bfs(s, t)) {
                ranges::fill(it, 0);
                while ((got = dfs(s, t, inf))) ans += got;
            }
            return ans;
        }
        vector<char> min_cut_side(int s) {
            vector<char> seen(g.size());
            vector<int> stack{ s };
            seen[s] = true;
            while (!stack.empty()) {
                int u = stack.back();
                stack.pop_back();
                for (auto &e : g[u]) if (e.cap && !seen[e.
                to])
                    seen[e.to] = true, stack.push_back(e.to
                    );
            }
            return seen;
        }
    };

    /*
    Lower bounds [low, high]:
    add u->v with high-low; balance[u]-=low, balance[v]+=
    low.
    add ss->v for positive balance, v->tt for negative
    balance.
    for s-t flow also add t->s with inf before the
    feasibility flow.
    after feasibility, remove ss/tt and t->s:
    max = base + max_flow(s,t), min = base - max_flow(t,s).
    */

```

5.2 min cost flow

```

using ll = long long;
const ll inf = LLONG_MAX / 4;

struct min_cost_flow {
    struct edge { int to, rev; ll cap, cost; };
    vector<vector<edge>> g;

    min_cost_flow(int n) : g(n) {}
    void add_edge(int u, int v, ll cap, ll cost) {
        int a = g[u].size(), b = g[v].size();
        g[u].push_back({v, b, cap, cost});
        g[v].push_back({u, a, 0, -cost});
    }
    pair<ll, ll> solve(int s, int t, ll limit = inf) {
        ll flow = 0, cost = 0;
        int n = g.size();
        vector<ll> dist(n);
        vector<int> pv(n), pe(n);
        vector<char> in_queue(n);
        while (flow < limit) {
            ranges::fill(dist, inf);
            ranges::fill(in_queue, false);
            queue<int> q;

```

```

        dist[s] = 0;
        q.push(s);
        in_queue[s] = true;
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            in_queue[u] = false;
            for (int i = 0; i < ssize(g[u]); ++i) {
                edge &e = g[u][i];
                __int128 raw = (__int128)dist[u] +
                    e.cost;
                ll nd = raw < -inf ? -inf : raw >
                    inf ? inf : (ll)raw;
                if (e.cap && dist[e.to] > nd) {
                    dist[e.to] = nd;
                    pv[e.to] = u, pe[e.to] = i;
                    if (!in_queue[e.to]) q.push(e.to), in_queue[e.to] = true;
                }
            }
        }
        if (dist[t] == inf) break;
        ll add = limit - flow;
        for (int v = t; v != s; v = pv[v]) add =
            min(add, g[pv[v]][pe[v]].cap);
        for (int v = t; v != s; v = pv[v]) {
            edge &e = g[pv[v]][pe[v]];
            e.cap -= add;
            g[v][e.rev].cap += add;
        }
        flow += add;
        cost += add * dist[t];
    }
    return {flow, cost};
};

```

6 Mathematics

6.1 $ax+by=gcd(a,b)$

```

using ll = long long;

// returns {g, x, y}: ax + by = g = gcd(a,b)
tuple<ll, ll, ll> ext_gcd(ll a, ll b) {
    if (!b) return {abs(a), a < 0 ? -1 : 1, 0};
    ll g, x, y;
    tie(g, x, y) = ext_gcd(b, a % b);
    return {g, y, x - a / b * y};
}

```

6.2 GaussElimination

```

using ld = long double;
const ld eps = 1e-12L;

// augmented matrix; returns 0=no solution, 1=unique,
// 2=infinite
int gauss(vector<vector<ld>> a, vector<ld> &answer) {
    int n = a.size(), m = a.empty() ? 0 : a[0].size() -
        1, row = 0;
    vector<int> where(m, -1);
    for (int col = 0; col < m && row < n; ++col) {
        int best = row;
        for (int i = row; i < n; ++i)
            if (fabsl(a[i][col]) > fabsl(a[best][col]))
                best = i;
        if (fabsl(a[best][col]) <= eps) continue;
        swap(a[best], a[row]);
        where[col] = row;
        ld div = a[row][col];
        for (int j = col; j <= m; ++j) a[row][j] /= div;
        for (int i = 0; i < n; ++i) if (i != row) {
            ld mul = a[i][col];
            for (int j = col; j <= m; ++j) a[i][j] -=
                mul * a[row][j];
        }
    }
}

```

```

    }
    ++row;
}
answer.assign(m, 0);
for (int i = 0; i < m; ++i) if (where[i] != -1)
    answer[i] = a[where[i]][m];
for (auto &r : a) {
    ld sum = 0;
    for (int i = 0; i < m; ++i) sum += r[i] *
        answer[i];
    if (fabsl(sum - r[m]) > eps) return 0;
}
return ranges::count(where, -1) ? 2 : 1;
}

```

6.3 Inverse

```

using ll = long long;

ll power(ll a, ll n, ll mod) {
    ll ans = 1;
    for (; n; n /= 2, a = (__int128)a * a % mod)
        if (n & 1) ans = (__int128)ans * a % mod;
    return ans;

    // mod must be prime; 1 <= n < mod
    vector<ll> inverse_table(int n, ll mod) {
        assert(1 <= n && n < mod);
        vector<ll> inv(n + 1);
        inv[1] = 1;
        for (int i = 2; i <= n; ++i)
            inv[i] = mod - (__int128)(mod / i) * inv[mod %
                i] % mod;
        return inv;
    }
}

```

6.4 LinearPrime 歐拉篩

```

vector<int> linear_sieve(int n) {
    vector<int> primes, min_prime(n + 1);
    for (int i = 2; i <= n; ++i) {
        if (!min_prime[i]) min_prime[i] = i, primes.
            push_back(i);
        for (int p : primes) {
            if (p > min_prime[i] || (long long)i * p >
                n) break;
            min_prime[i * p] = p;
        }
    }
    return primes;
}

```

6.5 Miller Rabin

```

using u64 = uint64_t;
using u128 = __uint128_t;

u64 mod_mul(u64 a, u64 b, u64 mod) { return u128(a) * b
    % mod; }
u64 mod_power(u64 a, u64 n, u64 mod) {
    u64 ans = 1;
    for (; n; n /= 2, a = mod_mul(a, a, mod))
        if (n & 1) ans = mod_mul(ans, a, mod);
    return ans;
}

bool is_prime(u64 n) {
    if (n < 2) return false;
    for (u64 p : array<u64, 7>{{2, 3, 5, 7, 11, 13, 17}})
        if (n % p == 0) return n == p;
    }
    u64 d = n - 1, s = 0;
    while (!(d & 1)) d /= 2, ++s;
}

```

```

for (u64 a : array<u64, 7>{2, 325, 9375, 28178,
450775, 9780504, 1795265022}) {
    if (a % n == 0) continue;
    u64 x = mod_power(a % n, d, n);
    if (x == 1 || x == n - 1) continue;
    bool composite = true;
    for (u64 r = 1; r < s; ++r) {
        x = mod_mul(x, x, n);
        if (x == n - 1) {
            composite = false;
            break;
        }
    }
    if (composite) return false;
}
return true;
}

```

6.6 Pollard's rho

```

// needs is_prime() and mod_mul() from Miller-Rabin.cpp
using u64 = uint64_t;

u64 pollard(u64 n) {
    if (!(n & 1)) return 2;
    static mt19937_64 rng(chrono::steady_clock::now().
        time_since_epoch().count());
    while (true) {
        u64 c = uniform_int_distribution<u64>(1, n - 1)
            (rng);
        u64 x = uniform_int_distribution<u64>(0, n - 1)
            (rng), y = x, d = 1;
        auto f = [&](u64 v) { return (__uint128_t(
            mod_mul(v, v, n)) + c) % n; };
        while (d == 1) {
            x = f(x), y = f(f(y));
            d = gcd(x > y ? x - y : y - x, n);
        }
        if (d != n) return d;
    }
}

void factor(u64 n, map<u64, int> &count) {
    if (n == 1) return;
    if (is_prime(n)) return ++count[n], void();
    u64 d = pollard(n);
    factor(d, count);
    factor(n / d, count);
}

```

6.7 NTT

```

// coefficients must be in [0, mod)
const int mod = 998244353, root = 3;

int power(int a, int n) {
    long long ans = 1;
    for (; n; n /= 2, a = (long long)a * a % mod)
        if (n & 1) ans = ans * a % mod;
    return ans;
}

void ntt(vector<int> &a, bool inverse) {
    int n = a.size();
    assert(n && !(n & (n - 1)) && (mod - 1) % n == 0);
    for (int i = 1, j = 0; i < n; ++i) {
        int bit = n / 2;
        for (; j & bit; bit /= 2) j ^= bit;
        j ^= bit;
        if (i < j) swap(a[i], a[j]);
    }
    for (int len = 2; len <= n; len *= 2) {
        int wlen = power(root, (mod - 1) / len);
        if (inverse) wlen = power(wlen, mod - 2);
        for (int i = 0; i < n; i += len) {
            long long w = 1;
            for (int j = 0; j < len / 2; ++j) {

```

```

                int u = a[i + j], v = w * a[i + j + len
                    / 2] % mod;
                a[i + j] = u + v < mod ? u + v : u + v
                    - mod;
                a[i + j + len / 2] = u - v >= 0 ? u - v
                    : u - v + mod;
                w = w * wlen % mod;
            }
        }
    }
    if (inverse) {
        int inv = power(n, mod - 2);
        for (int &x : a) x = (long long)x * inv % mod;
    }
}

vector<int> convolution(vector<int> a, vector<int> b) {
    if (a.empty() || b.empty()) return {};
    int need = a.size() + b.size() - 1, n = 1;
    while (n < need) n *= 2;
    assert(n <= (1 << 23));
    a.resize(n), b.resize(n);
    ntt(a, false), ntt(b, false);
    for (int i = 0; i < n; ++i) a[i] = (long long)a[i]
        * b[i] % mod;
    ntt(a, true);
    a.resize(need);
    return a;
}

```

6.8 數論基本工具

```

using ll = long long;

ll mod_power(ll a, ll n, ll mod) {
    ll ans = 1;
    for (; n; n /= 2, a = (__int128)a * a % mod)
        if (n & 1) ans = (__int128)ans * a % mod;
    return ans;
}

// mod must be prime and n < mod
struct combinations {
    ll mod;
    vector<ll> fact, inv_fact;
    combinations(int n, ll mod) : mod(mod), fact(n + 1,
        1), inv_fact(n + 1) {
        for (int i = 1; i <= n; ++i) fact[i] = fact[i -
            1] * i % mod;
        inv_fact[n] = mod_power(fact[n], mod - 2, mod);
        for (int i = n; i --; i) inv_fact[i - 1] =
            inv_fact[i] * i % mod;
    }
    ll choose(int n, int k) {
        if (k < 0 || k > n) return 0;
        return fact[n] * inv_fact[k] % mod * inv_fact[n
            - k] % mod;
    }
};

```

6.9 Mobius

```

vector<int> mobius(int n) {
    vector<int> mu(n + 1), primes;
    vector<char> composite(n + 1);
    if (n < 1) return mu;
    mu[1] = 1;
    for (int i = 2; i <= n; ++i) {
        if (!composite[i]) primes.push_back(i), mu[i] =
            -1;
        for (int p : primes) {
            if ((long long)i * p > n) break;
            composite[i * p] = true;
            if (i % p == 0) {
                mu[i * p] = 0;
                break;
            }
            mu[i * p] = -mu[i];
        }
    }
}

```

```

    }
}
return mu;
}

```

6.10 SG

```

/*
finite impartial game:
sg[u] = mex({sg[v] | u -> v}).
xor the sg values only when combining independent games
.
normal play: xor != 0 wins.
misere nim: if every pile is 1, odd pile count loses;
otherwise xor != 0 wins.
*/
vector<int> Grundy(const vector<vector<int>>& g) {
    vector<int> sg(g.size(), -1);
    function<int(int)> dfs = [&](int u) {
        if (sg[u] != -1) return sg[u];
        vector<int> seen(g[u].size() + 1);
        for (int v : g[u]) {
            int x = dfs(v);
            if (x < seen.size()) seen[x] = true;
        }
        return sg[u] = ranges::find(seen, 0) - seen.begin();
    };
    for (int u = 0; u < g.size(); ++u) dfs(u);
    return sg;
}

```

6.11 歐拉定理

歐拉降冪對於任何正整數 m 、整數 a 和非負整數 k

$$a^k \equiv \begin{cases} a^{k \bmod \varphi(m)}, & \gcd(a, m) = 1, \\ a^k, & \gcd(a, m) \neq 1, k < \varphi(m), \pmod{m} \\ a^{(k \bmod \varphi(m)) + \varphi(m)}, & \gcd(a, m) \neq 1, k \geq \varphi(m). \end{cases}$$

6.12 Theorem

```

/*
Lucas's Theorem
For non-negative integer n,m and prime P,
C(m,n) mod P = C(m/P,n/P) * C(m%P,n%P) mod P
= mult_i ( C(m_i,n_i) )
where m_i is the i-th digit of m in base P.
-----
Pick's Theorem
A = i + b/2 - 1
-----
Kirchhoff's theorem
A_{ii} = deg(i), A_{ij} = (i,j) \in E ? -1 : 0
Deleting any one row, one column, and cal the det(A)
-----
Nth Catalan recursive function:
C_0 = 1, C_{n+1} = C_n * 2(2n + 1)/(n+2)
-----
Mobius Formula
u(n) = 1, if n = 1
      (-1)^m, 若 n 無平方數因數, 且 n = p1*p2*p3*...*pk
      0, 若 n 有大於 1 的平方數因數
- Property
1. (積性函數) u(a)u(b) = u(ab)
2. \sum_{d|n} u(d) = [n == 1]
-----
Mobius Inversion Formula
if f(n) = \sum_{d|n} g(d)
then g(n) = \sum_{d|n} u(n/d)f(d)
          = \sum_{d|n} u(d)f(n/d)
- Application
the number/power of gcd(i, j) = k
- Trick

```

分塊, $O(\sqrt{n})$

Chinese Remainder Theorem (m_i 兩兩互質)

```

x = a_1 (mod m_1)
x = a_2 (mod m_2)
....
x = a_i (mod m_i)

```

construct a solution:

```

Let M = m_1 * m_2 * m_3 * ... * m_n
Let M_i = M / m_i

```

```

t_i = 1 / M_i
t_i * M_i = 1 (mod m_i)

```

```

solution x = a_1 * t_1 * M_1 + a_2 * t_2 * M_2 + ...
            + a_n * t_n * M_n + k * M
            = k*M + \sum a_i * t_i * M_i, k is any integer.

```

```

under mod M, there is one solution x = \sum a_i * t_i * M_i

```

Burnside's Lemma

$|G| * |X/G| = \sum |X^g|$ where g in G

總方法數：每一種旋轉下不動點的個數總和 除以 旋轉的方法數

*/

7 Graph

7.1 BCC

// undirected edge-biconnected components; parallel edges are allowed

```

struct edge_bcc {
    struct edge { int to, id; };
    vector<vector<edge>> g;
    vector<int> dfn, low, comp;
    vector<char> bridge;
    int time = 0;

    edge_bcc(int n) : g(n), dfn(n), low(n), comp(n, -1) {}
    void add_edge(int u, int v) {
        int id = bridge.size();
        bridge.push_back(false);
        g[u].push_back({v, id});
        g[v].push_back({u, id});
    }
    void dfs(int u, int parent_edge = -1) {
        dfn[u] = low[u] = ++time;
        for (edge e : g[u]) {
            if (e.id == parent_edge) continue;
            if (!dfn[e.to]) {
                dfs(e.to, e.id);
                low[u] = min(low[u], low[e.to]);
                if (low[e.to] > dfn[u]) bridge[e.id] = true;
            } else low[u] = min(low[u], dfn[e.to]);
        }
    }
    void paint(int u, int id) {
        comp[u] = id;
        for (edge e : g[u])
            if (!bridge[e.id] && comp[e.to] == -1)
                paint(e.to, id);
    }
    int solve() {
        for (int u = 0; u < g.size(); ++u) if (!dfn[u])
            dfs(u);
        int count = 0;
        for (int u = 0; u < g.size(); ++u)
            if (comp[u] == -1) paint(u, count++);
        return count;
    }
};

```

7.2 Prim

```
using ll = long long;
using edge = pair<ll, int>; // weight, to

// {connected, mst weight}; zero and parallel edges are
// allowed
pair<bool, ll> prim(const vector<vector<edge>> &g, int
    root = 0) {
    if (g.empty()) return {true, 0};
    vector<char> used(g.size());
    priority_queue<edge, vector<edge>, greater<edge>>
        pq;
    pq.push({0, root});
    ll total = 0;
    int seen = 0;
    while (!pq.empty()) {
        ll w = pq.top().first;
        int u = pq.top().second;
        pq.pop();
        if (used[u]) continue;
        used[u] = true;
        total += w;
        ++seen;
        for (edge e : g[u]) if (!used[e.second]) pq.
            push(e);
    }
    return {seen == ssize(g), total};
}
```

7.3 Bellman Ford

```
using ll = long long;
const ll inf = LLONG_MAX / 4;

struct edge {
    int from, to;
    ll weight;
};

struct bellman_result {
    vector<ll> dist;
    vector<int> parent;
    bool negative_cycle;
};

bellman_result bellman_ford(int n, int source, const
    vector<edge> &edges) {
    vector<ll> dist(n, inf);
    vector<int> parent(n, -1);
    dist[source] = 0;
    bool changed = false;
    for (int i = 0; i < n; ++i) {
        changed = false;
        for (edge e : edges) {
            if (dist[e.from] == inf) continue;
            __int128 raw = (__int128)dist[e.from] + e.
                weight;
            ll nd = raw < -inf ? -inf : raw > inf ? inf
                : (ll)raw;
            if (nd < dist[e.to]) {
                dist[e.to] = nd;
                parent[e.to] = e.from;
                changed = true;
            }
        }
        if (!changed) break;
    }
    return {dist, parent, changed}; // reachable
    negative cycle iff changed
}
```

7.4 Kruskal

```
using ll = long long;

struct edge {
    int u, v;
```

```
    ll weight;
};

struct dsu {
    vector<int> p, size;
    dsu(int n) : p(n), size(n, 1) { iota(p.begin(), p.
        end(), 0); }
    int find(int x) { return p[x] == x ? x : p[x] =
        find(p[x]); }
    bool unite(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (size[a] < size[b]) swap(a, b);
        p[b] = a;
        size[a] += size[b];
        return true;
    }
};

pair<bool, ll> kruskal(int n, vector<edge> edges) {
    ranges::sort(edges, {}, &edge::weight);
    dsu uf(n);
    ll total = 0;
    int used = 0;
    for (edge e : edges) if (uf.unite(e.u, e.v))
        total += e.weight, ++used;
    return {used == n - 1, total};
}
```

7.5 Dijkstra

```
using ll = long long;
using graph_edge = pair<int, ll>; // to, weight
using state = pair<ll, int>; // distance, vertex
const ll inf = LLONG_MAX / 4;

vector<ll> dijkstra(int source, const vector<vector<
    graph_edge>> &g) {
    vector<ll> dist(g.size(), inf);
    priority_queue<state, vector<state>, greater<state>
        >> pq;
    dist[source] = 0;
    pq.push({0, source}); // distance, vertex
    while (!pq.empty()) {
        ll d = pq.top().first;
        int u = pq.top().second;
        pq.pop();
        if (d != dist[u]) continue;
        for (graph_edge e : g[u]) {
            int v = e.first;
            ll w = e.second;
            assert(w >= 0);
            if (dist[v] > d + w) {
                dist[v] = d + w;
                pq.push({dist[v], v});
            }
        }
    }
    return dist;
}
```

7.6 Strongly Connected Component(SCC)

```
struct kosaraju {
    vector<vector<int>> g, rev;
    vector<int> used, order, comp;

    kosaraju(int n) : g(n), rev(n), used(n), comp(n) {}
    void add_edge(int u, int v) { g[u].push_back(v),
        rev[v].push_back(u); }
    void dfs(int u) {
        used[u] = true;
        for (int v : g[u]) if (!used[v]) dfs(v);
        order.push_back(u);
    }
    void rdfs(int u, int id) {
        comp[u] = id;
        used[u] = true;
        for (int v : rev[u]) if (!used[v]) rdfs(v, id);
    }
}
```

```

    }
    int solve() {
        ranges::fill(used, 0);
        order.clear();
        for (int u = 0; u < ssize(g); ++u) if (!used[u])
            dfs(u);
        ranges::fill(used, 0);
        ranges::reverse(order);
        int count = 0;
        for (int u : order) if (!used[u]) rdfs(u, count++);
        return count;
    }
};

```

7.7 Hungarian

```

// maximum cardinality bipartite matching
struct bipartite_matching {
    vector<vector<int>> g;
    vector<int> right_match, seen;
    int stamp = 0;

    bipartite_matching(int left, int right)
        : g(left), right_match(right, -1), seen(right) {}

    void add_edge(int left, int right) { g[left].push_back(right); }
    bool dfs(int u) {
        for (int v : g[u]) if (seen[v] != stamp) {
            seen[v] = stamp;
            if (right_match[v] == -1 || dfs(right_match[v]))
                return right_match[v] = u, true;
        }
        return false;
    }

    int solve() {
        int ans = 0;
        for (int u = 0; u < ssize(g); ++u) ++stamp, ans += dfs(u);
        return ans;
    }
};

```

7.8 KM

```

using ll = long long;
const ll missing = LLONG_MIN / 4;
const ll inf = LLONG_MAX / 4;

struct assignment_result {
    bool perfect;
    ll weight;
    vector<int> right_match;
};

// square maximum-weight assignment; use missing for absent edges
assignment_result max_weight_matching(const vector<vector<ll>> &weight) {
    int n = weight.size();
    for (auto &row : weight) assert(ssize(row) == n);
    vector<ll> u(n + 1), v(n + 1);
    vector<int> p(n + 1), way(n + 1);

    for (int i = 1; i <= n; ++i) {
        p[0] = i;
        vector<ll> best(n + 1, inf);
        vector<char> used(n + 1);
        int col = 0;
        do {
            used[col] = true;
            int row = p[col], next = 0;
            ll delta = inf;
            for (int j = 1; j <= n; ++j) if (!used[j])

```

```

                ll cost = weight[row - 1][j - 1] ==
                    missing
                        ? inf / 2 : -weight[row - 1][j - 1];
            ll cur = cost - u[row] - v[j];
            if (cur < best[j]) best[j] = cur, way[j] = col;
            if (best[j] < delta) delta = best[j], next = j;
        }
        for (int j = 0; j <= n; ++j)
            if (used[j]) u[p[j]] += delta, v[j] -= delta;
        else best[j] -= delta;
        col = next;
    } while (p[col]);
    do {
        int prev = way[col];
        p[col] = p[prev];
        col = prev;
    } while (col);

    vector<int> match(n, -1);
    ll sum = 0;
    for (int col = 1; col <= n; ++col) {
        int row = p[col] - 1;
        match[col - 1] = row;
        if (weight[row][col - 1] == missing) return {false, 0, {}};
        sum += weight[row][col - 1];
    }
    return {true, sum, match};
}

```

7.9 最小平均環

```

using ld = long double;
const ld inf = 1e100L;

struct edge {
    int from, to;
    ld weight;
};

// {has cycle, minimum mean}; karp, O(nm)
pair<bool, ld> min_mean_cycle(int n, const vector<edge> &edges) {
    vector<vector<ld>> dp(n + 1, vector<ld>(n, inf));
    ranges::fill(dp[0], 0); // super source
    for (int k = 1; k <= n; ++k)
        for (edge e : edges)
            if (dp[k - 1][e.from] != inf)
                dp[k][e.to] = min(dp[k][e.to], dp[k - 1][e.from] + e.weight);

    ld ans = inf;
    for (int v = 0; v < n; ++v) if (dp[n][v] != inf) {
        ld worst = -inf;
        for (int k = 0; k < n; ++k) if (dp[k][v] != inf)
            worst = max(worst, (dp[n][v] - dp[k][v]) / (n - k));
        ans = min(ans, worst);
    }
    return {ans != inf, ans};
}

```

7.10 偵測負環

```

using ll = long long;
const ll inf = LLONG_MAX / 4;

struct floyd_result {
    vector<vector<ll>> dist;
    vector<vector<char>> negative;
};

```

```
floyd_result floyd_warshall(vector<vector<ll>> dist) {
    int n = dist.size();
    for (int k = 0; k < n; ++k)
        for (int i = 0; i < n; ++i) if (dist[i][k] != inf)
            for (int j = 0; j < n; ++j) if (dist[k][j] != inf) {
                __int128 x = (__int128)dist[i][k] +
                    dist[k][j];
                ll value = x < -inf ? -inf : x > inf ?
                    inf : (ll)x;
                dist[i][j] = min(dist[i][j], value);
            }

    vector<vector<char>> negative(n, vector<char>(n));
    for (int k = 0; k < n; ++k) if (dist[k][k] < 0)
        for (int i = 0; i < n; ++i) if (dist[i][k] != inf)
            for (int j = 0; j < n; ++j) if (dist[k][j] != inf)
                negative[i][j] = true;
    return {dist, negative};
}
```

7.11 Tarjan

```
// directed strongly connected components
struct tarjan {
    vector<vector<int>> g;
    vector<int> dfn, low, comp, stack;
    vector<char> in_stack;
    int time = 0, count = 0;

    tarjan(int n)
        : g(n), dfn(n), low(n), comp(n, -1), in_stack(n) {}
    void add_edge(int u, int v) { g[u].push_back(v); }
    void dfs(int u) {
        dfn[u] = low[u] = ++time;
        stack.push_back(u);
        in_stack[u] = true;
        for (int v : g[u]) {
            if (!dfn[v]) dfs(v), low[u] = min(low[u], low[v]);
            else if (in_stack[v]) low[u] = min(low[u], dfn[v]);
        }
        if (low[u] != dfn[u]) return;
        while (true) {
            int v = stack.back();
            stack.pop_back();
            in_stack[v] = false;
            comp[v] = count;
            if (v == u) break;
        }
        ++count;
    }
    int solve() {
        for (int u = 0; u < ssize(g); ++u) if (!dfn[u])
            dfs(u);
        return count;
    }
};
```

7.12 Topological Sort

```
// empty result means the graph has a cycle
vector<int> topological_sort(const vector<vector<int>>
    &g) {
    vector<int> indeg(g.size()), order;
    for (auto &es : g) for (int v : es) ++indeg[v];
    queue<int> q;
    for (int i = 0; i < ssize(g); ++i)
        if (!indeg[i]) q.push(i);
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        order.push_back(u);
    }
```

```
        for (int v : g[u]) if (!--indeg[v]) q.push(v);
    }
    if (order.size() != g.size()) order.clear();
    return order;
}
```

8 Data Structure

8.1 2D Range Tree

```
// static rectangle point count, inclusive bounds
struct range_tree_2d {
    vector<int> xs;
    vector<vector<int>> ys;

    range_tree_2d(vector<pair<int, int>> p) {
        ranges::sort(p);
        for (auto q : p) xs.push_back(q.first);
        ys.resize(4 * max<size_t>(1, p.size()));
        if (!p.empty()) build(1, 0, p.size(), p);
    }
    void build(int o, int l, int r, const vector<pair<
        int, int>> &p) {
        if (r - l == 1) return ys[o].push_back(p[l].
            second);
        int m = (l + r) / 2;
        build(o * 2, l, m, p);
        build(o * 2 + 1, m, r, p);
        ranges::merge(ys[o * 2], ys[o * 2 + 1],
            back_inserter(ys[o]));
    }
    int query(int ql, int qr, int y1, int y2, int o,
        int l, int r) {
        if (ql <= l && r <= qr)
            return ranges::upper_bound(ys[o], y2) -
                ranges::lower_bound(ys[o], y1);
        int m = (l + r) / 2, ans = 0;
        if (ql < m) ans += query(ql, qr, y1, y2, o * 2,
            l, m);
        if (m < qr) ans += query(ql, qr, y1, y2, o * 2
            + 1, m, r);
        return ans;
    }
    int count(int x1, int y1, int x2, int y2) {
        int l = ranges::lower_bound(xs, x1) - xs.begin
            ();
        int r = ranges::upper_bound(xs, x2) - xs.begin
            ();
        return l == r ? 0 : query(l, r, y1, y2, 1, 0,
            xs.size());
    }
};
```

8.2 Segment Tree

```
// range add, range maximum; public ranges are [l, r]
struct segtree {
    struct node { long long mx = 0, lazy = 0; };
    int n;
    vector<node> t;

    segtree(int n) : n(n), t(4 * max(1, n)) { assert(n
        > 0); }
    void apply(int o, long long v) { t[o].mx += v, t[o
        ].lazy += v; }
    void push(int o) {
        if (!t[o].lazy) return;
        apply(o * 2, t[o].lazy);
        apply(o * 2 + 1, t[o].lazy);
        t[o].lazy = 0;
    }
    void add(int ql, int qr, long long v, int o, int l,
        int r) {
        if (ql <= l && r <= qr) return apply(o, v);
        push(o);
        int m = (l + r) / 2;
```

```

    if (ql < m) add(ql, qr, v, o * 2, l, m);
    if (m < qr) add(ql, qr, v, o * 2 + 1, m, r);
    t[o].mx = max(t[o * 2].mx, t[o * 2 + 1].mx);
}
long long max_query(int ql, int qr, int o, int l,
    int r) {
    if (ql <= l && r <= qr) return t[o].mx;
    push(o);
    int m = (l + r) / 2;
    long long ans = LLONG_MIN;
    if (ql < m) ans = max(ans, max_query(ql, qr, o
        * 2, l, m));
    if (m < qr) ans = max(ans, max_query(ql, qr, o
        * 2 + 1, m, r));
    return ans;
}
void add(int l, int r, long long v) {
    if (l <= r) add(l, r + 1, v, 1, 0, n);
}
long long max_query(int l, int r) {
    assert(l <= r);
    return max_query(l, r + 1, 1, 0, n);
}
};

```

8.3 ZKW 線段樹

```

// iterative segment tree: point add and range sum [l,
// r]
struct zkw_sum {
    int n = 1;
    vector<long long> t;
    zkw_sum(int size) {
        while (n < size) n *= 2;
        t.assign(2 * n, 0);
    }
    void add(int p, long long v) {
        for (t[p += n] += v, p /= 2; p; p /= 2)
            t[p] = t[p * 2] + t[p * 2 + 1];
    }
    long long sum(int l, int r) {
        long long ans = 0;
        for (l += n, r += n + 1; l < r; l /= 2, r /= 2)
            if (l & 1) ans += t[l++];
            if (r & 1) ans += t[--r];
        return ans;
    }
};

```

8.4 Sparse Table

```

// idempotent rmq: minimum on [l, r]
template<class t>
struct sparse_table {
    vector<int> lg;
    vector<vector<t>> st;

    sparse_table(const vector<t> &a) : lg(a.size() + 1)
    {
        for (int i = 2; i < ssize(lg); ++i) lg[i] = lg[
            i / 2] + 1;
        int k = a.empty() ? 0 : lg[a.size()] + 1;
        st.assign(k, vector<t>(a.size()));
        if (a.empty()) return;
        st[0] = a;
        for (int j = 1; j < k; ++j)
            for (int i = 0; i + (1 << j) <= ssize(a);
                ++i)
                st[j][i] = min(st[j - 1][i], st[j - 1][
                    i + (1 << (j - 1))]);
    }
    t query(int l, int r) {
        assert(l <= r);
        int k = lg[r - l + 1];
        return min(st[k][l], st[k][r - (1 << k) + 1]);
    }
};

```

```
};
```

8.5 Lazy Tag

```

// range add, range sum; public ranges are [l, r]
struct lazy_sum {
    int n;
    vector<long long> sum, tag;
    lazy_sum(int n) : n(n), sum(4 * max(1, n)), tag(sum
        .size()) {
        assert(n > 0);
    }
    void apply(int o, int l, int r, long long v) {
        sum[o] += v * (r - l + 1);
        tag[o] += v;
    }
    void push(int o, int l, int r) {
        if (!tag[o]) return;
        int m = (l + r) / 2;
        apply(o * 2, l, m, tag[o]);
        apply(o * 2 + 1, m + 1, r, tag[o]);
        tag[o] = 0;
    }
    void add(int ql, int qr, long long v, int o, int l,
        int r) {
        if (ql <= l && r <= qr) return apply(o, l, r, v);
        push(o, l, r);
        int m = (l + r) / 2;
        if (ql < m) add(ql, qr, v, o * 2, l, m);
        if (m < qr) add(ql, qr, v, o * 2 + 1, m + 1, r);
        sum[o] = sum[o * 2] + sum[o * 2 + 1];
    }
    long long query(int ql, int qr, int o, int l, int r)
    {
        if (ql <= l && r <= qr) return sum[o];
        push(o, l, r);
        int m = (l + r) / 2;
        long long ans = 0;
        if (ql < m) ans += query(ql, qr, o * 2, l, m);
        if (m < qr) ans += query(ql, qr, o * 2 + 1, m + 1,
            r);
        return ans;
    }
    void add(int l, int r, long long v) {
        if (l <= r) add(l, r + 1, v, 1, 0, n);
    }
    long long query(int l, int r) {
        return l <= r ? query(l, r + 1, 1, 0, n) : 0;
    }
};

```

8.6 BIT 樹狀樹組

```

// public indices are 0-based
struct bit {
    using ll = long long;
    vector<ll> t;
    bit(int n) : t(n + 1) {}

    void add(int p, ll x) {
        for (++p; p < ssize(t); p += p & -p) t[p] += x;
    }
    ll prefix(int r) { // [0, r]
        ll ans = 0;
        for (++r; r > 0; r -= r & -r) ans += t[r];
        return ans;
    }
    ll sum(int l, int r) { // [l, r]
        return l > r ? 0 : prefix(r) - (l ? prefix(l -
            1) : 0);
    }
};

```

8.7 並查集 union find

```

struct dsu {
    vector<int> parent, size;
    dsu(int n) : parent(n), size(n, 1) { iota(parent.
        begin(), parent.end(), 0); }
    int find(int x) { return parent[x] == x ? x :
        parent[x] = find(parent[x]); }
    bool unite(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (size[a] < size[b]) swap(a, b);
        parent[b] = a;
        size[a] += size[b];
        return true;
    }
    bool same(int a, int b) { return find(a) == find(b)
        ; }
};

```

8.8 Treap

```

// implicit/key treap primitives; node 0 means null
struct treap {
    struct node {
        int value = 0, priority = 0, size = 0, left =
            0, right = 0;
    };
    struct split_result { int left, right; };
    vector<node> t{node{}};
    mt19937 rng{uint32_t(chrono::steady_clock::now().
        time_since_epoch().count())};

    int make_node(int value) {
        t.push_back({value, rng(), 1, 0, 0});
        return t.size() - 1;
    }
    int size(int u) { return u ? t[u].size : 0; }
    void pull(int u) { t[u].size = 1 + size(t[u].left)
        + size(t[u].right); }

    split_result split_size(int u, int k) {
        if (!u) return {0, 0};
        if (size(t[u].left) >= k) {
            auto s = split_size(t[u].left, k);
            t[u].left = s.right;
            pull(u);
            return {s.left, u};
        }
        auto s = split_size(t[u].right, k - size(t[u].
            left) - 1);
        t[u].right = s.left;
        pull(u);
        return {u, s.right};
    }
    split_result split_value(int u, int value) {
        if (!u) return {0, 0};
        if (t[u].value <= value) {
            auto s = split_value(t[u].right, value);
            t[u].right = s.left;
            pull(u);
            return {u, s.right};
        }
        auto s = split_value(t[u].left, value);
        t[u].left = s.right;
        pull(u);
        return {s.left, u};
    }
    int merge(int a, int b) {
        if (!a || !b) return a ? a : b;
        if (t[a].priority < t[b].priority) {
            t[a].right = merge(t[a].right, b);
            pull(a);
            return a;
        }
        t[b].left = merge(a, t[b].left);
        pull(b);
        return b;
    }
};

```

```

};

```

8.9 2D BIT

```

// 1-based rectangle add and rectangle sum; memory is
// 32*n*m bytes
struct bit2d {
    using ll = long long;
    int n, m;
    array<vector<vector<ll>>, 4> t;

    bit2d(int n, int m) : n(n), m(m) {
        for (auto &a : t) a.assign(n + 1, vector<ll>(m
            + 1));
    }

    void add_one(int x, int y, ll v) {
        for (int i = x; i <= n; i += i & -i)
            for (int j = y; j <= m; j += j & -j) {
                t[0][i][j] += v;
                t[1][i][j] += v * (x - 1);
                t[2][i][j] += v * (y - 1);
                t[3][i][j] += v * (x - 1) * (y - 1);
            }
    }

    ll get(int k, int x, int y) {
        ll ans = 0;
        for (int i = x; i > 0; i -= i & -i)
            for (int j = y; j > 0; j -= j & -j) ans +=
                t[k][i][j];
        return ans;
    }

    void add(int x1, int y1, int x2, int y2, ll v) {
        assert(1 <= x1 && x1 <= x2 && x2 <= n);
        assert(1 <= y1 && y1 <= y2 && y2 <= m);
        add_one(x1, y1, v);
        if (y2 < m) add_one(x1, y2 + 1, -v);
        if (x2 < n) add_one(x2 + 1, y1, -v);
        if (x2 < n && y2 < m) add_one(x2 + 1, y2 + 1, v
            );
    }

    ll prefix(int x, int y) {
        if (x <= 0 || y <= 0) return 0;
        return get(0, x, y) * x * y - get(1, x, y) * y
            - get(2, x, y) * x + get(3, x, y);
    }

    ll sum(int x1, int y1, int x2, int y2) {
        return prefix(x2, y2) - prefix(x1 - 1, y2) -
            prefix(x2, y1 - 1) + prefix(x1 - 1, y1 -
                1);
    }
};

```

9 String

9.1 KMP

```

vector<int> prefix_function(const string &s) {
    vector<int> pi(s.size());
    for (int i = 1; i < ssize(s); ++i) {
        int j = pi[i - 1];
        while (j && s[i] != s[j]) j = pi[j - 1];
        if (s[i] == s[j]) ++j;
        pi[i] = j;
    }
    return pi;
}

vector<int> kmp(const string &text, const string &
    pattern) {
    if (pattern.empty()) return {};
    vector<int> pi = prefix_function(pattern), pos;

```

```

    for (int i = 0, j = 0; i < ssize(text); ++i) {
        while (j && text[i] != pattern[j]) j = pi[j - 1];
        if (text[i] == pattern[j]) ++j;
        if (j == ssize(pattern)) {
            pos.push_back(i - j + 1);
            j = pi[j - 1];
        }
    }
    return pos;
}

```

9.2 smallest rotation

```

string smallest_rotation(string s) {
    int n = s.size();
    if (!n) return s;
    s += s;
    int i = 0, j = 1;
    while (i < n && j < n) {
        int k = 0;
        while (k < n && s[i + k] == s[j + k]) ++k;
        if (k == n) break;
        if (s[i + k] < s[j + k]) j += k + 1;
        else i += k + 1;
        if (i == j) ++j;
    }
    return s.substr(min(i, j), n);
}

```

9.3 Suffix Array

```

struct suffix_data {
    vector<int> sa, rank, lcp;
};

suffix_data suffix_array(const string &s) {
    int n = s.size();
    if (!n) return {};
    vector<int> sa(n), rank(n), next(n), temp(n), count(
        max(n, 256));

    for (unsigned char c : s) ++count[c];
    partial_sum(count.begin(), count.end(), count.begin(
        ));
    for (int i = n - 1; i >= 0; --i) sa[--count[(
        unsigned char)s[i]]] = i;
    int classes = 0;
    for (int i = 0; i < n; ++i) {
        if (i && s[sa[i]] != s[sa[i - 1]]) ++classes;
        rank[sa[i]] = classes;
    }
    ++classes;

    for (int len = 1; len < n && classes < n; len *= 2)
    {
        int p = 0;
        for (int i = max(0, n - len); i < n; ++i) temp[
            p++] = i;
        for (int x : sa) if (x >= len) temp[p++] = x -
            len;

        fill(count.begin(), count.begin() + classes, 0)
            ;
        for (int x : temp) ++count[rank[x]];
        partial_sum(count.begin(), count.begin() +
            classes, count.begin());
        for (int i = n - 1; i >= 0; --i)
            sa[--count[rank[temp[i]]]] = temp[i];

        next[sa[0]] = 0;
        int new_classes = 1;
        for (int i = 1; i < n; ++i) {
            int a = sa[i - 1], b = sa[i];
            int ar = a + len < n ? rank[a + len] : -1;
            int br = b + len < n ? rank[b + len] : -1;
            if (rank[a] != rank[b] || ar != br) ++
                new_classes;
        }
    }
}

```

```

        next[b] = new_classes - 1;
    }
    rank.swap(next);
    classes = new_classes;
}

vector<int> lcp(n);
for (int i = 0, h = 0; i < n; ++i) {
    if (!rank[i]) continue;
    int j = sa[rank[i] - 1];
    while (i + h < n && j + h < n && s[i + h] == s[
        j + h]) ++h;
    lcp[rank[i]] = h;
    if (h) --h;
}
return {sa, rank, lcp};
}

```

9.4 Z-value

```

vector<int> z_function(const string &s) {
    int n = s.size();
    vector<int> z(n);
    for (int i = 1, l = 0, r = 0; i < n; ++i) {
        if (i <= r) z[i] = min(r - i + 1, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            ++z[i];
        if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
    }
    return z;
}

// radius of odd palindrome centered at i, including
// the center
vector<int> manacher_odd(const string &s) {
    int n = s.size();
    vector<int> radius(n);
    for (int i = 0, l = 0, r = -1; i < n; ++i) {
        int k = i > r ? 1 : min(radius[l + r - i], r -
            i + 1);
        while (i - k >= 0 && i + k < n && s[i - k] == s
            [i + k]) ++k;
        radius[i] = k--;
        if (i + k > r) l = i - k, r = i + k;
    }
    return radius;
}

```

9.5 旋轉哈希

```

using u64 = uint64_t;
using u128 = __uint128_t;
const u64 mod = (1ULL << 61) - 1;

u64 mod_add(u64 a, u64 b) {
    u64 x = a + b;
    return x >= mod ? x - mod : x;
}

u64 mod_mul(u64 a, u64 b) { return u128(a) * b % mod; }

struct rolling_hash {
    u64 base;
    vector<u64> hash, power;

    rolling_hash(const string &s, u64 base = 911382323)
        : base(base) {
        assert(1 < base && base < mod);
        hash.resize(s.size() + 1);
        power.assign(s.size() + 1, 1);
        for (int i = 0; i < ssize(s); ++i) {
            power[i + 1] = mod_mul(power[i], base);
            hash[i + 1] = mod_add(mod_mul(hash[i], base
                ), (unsigned char)s[i] + 1);
        }
    }

    u64 get(int l, int r) { // [l, r]
        u64 cut = mod_mul(hash[l], power[r - l + 1]);
    }
}

```

```

        return hash[r + 1] >= cut ? hash[r + 1] - cut :
            hash[r + 1] + mod - cut;
    }
};

```

9.6 後綴自動機

```

struct sam {
    struct state {
        int len = 0, link = -1;
        array<int, 26> next{};
    };
    vector<state> st{state{}};
    int last = 0;

    void add(char ch) {
        int c = ch - 'a';
        assert(0 <= c && c < 26);
        int cur = st.size(), p = last;
        st.push_back({});
        st[cur].len = st[last].len + 1;
        while (p != -1 && !st[p].next[c])
            st[p].next[c] = cur, p = st[p].link;
        if (p == -1) st[cur].link = 0;
        else {
            int q = st[p].next[c];
            if (st[p].len + 1 == st[q].len) st[cur].link = q;
            else {
                int clone = st.size();
                st.push_back(st[q]);
                st[clone].len = st[p].len + 1;
                while (p != -1 && st[p].next[c] == q)
                    st[p].next[c] = clone, p = st[p].link;
                st[q].link = st[cur].link = clone;
            }
        }
        last = cur;
    }
};

```

10 Others

10.1 矩陣樹定理

```

using ll = long long;

ll mod_power(ll a, ll n, ll mod) {
    ll ans = 1;
    for (; n; n /= 2, a = (__int128)a * a % mod)
        if (n & 1) ans = (__int128)ans * a % mod;
    return ans;
}

// undirected multigraph; mod must be prime
ll spanning_trees(int n, const vector<pair<int, int>> &
    edges, ll mod) {
    if (n == 1) return 1;
    vector<vector<ll>> a(n - 1, vector<ll>(n - 1));
    for (auto e : edges) {
        int u = e.first, v = e.second;
        if (u == v) continue;
        if (u < n - 1) a[u][u] = (a[u][u] + 1) % mod;
        if (v < n - 1) a[v][v] = (a[v][v] + 1) % mod;
        if (u < n - 1 && v < n - 1) {
            a[u][v] = (a[u][v] + mod - 1) % mod;
            a[v][u] = (a[v][u] + mod - 1) % mod;
        }
    }
    ll det = 1;
    for (int col = 0; col < n - 1; ++col) {
        int pivot = col;
        while (pivot < n - 1 && !a[pivot][col]) ++pivot;
        if (pivot == n - 1) return 0;
    }

```

```

        if (pivot != col) swap(a[pivot], a[col]), det =
            mod - det;
        det = (__int128)det * a[col][col] % mod;
        ll inv = mod_power(a[col][col], mod - 2, mod);
        for (int row = col + 1; row < n - 1; ++row) {
            ll mul = (__int128)a[row][col] * inv % mod;
            for (int j = col; j < n - 1; ++j)
                a[row][j] = (a[row][j] - (__int128)mul
                    * a[col][j] % mod + mod) % mod;
        }
    }
    return det;
}

```

10.2 1D/1D dp 優化

```

using ld = long double;

ld int_power(ld x, int p) {
    ld ans = 1;
    for (; p; p /= 2, x *= x) if (p & 1) ans *= x;
    return ans;
}

// original line-breaking transition; returns dp[n]
ld line_break_dp(const vector<int> &length, int limit,
    int power) {
    struct interval { int l, r, pos; };
    int n = length.size();
    vector<long long> prefix(n + 1);
    vector<ld> dp(n + 1);
    for (int i = 1; i <= n; ++i) prefix[i] = prefix[i - 1] + length[i - 1];
    auto cost = [&](int i, int j) {
        ld extra = fabsl(prefix[i] - prefix[j] + i - j
            - 1 - limit);
        return dp[j] + int_power(extra, power);
    };

    vector<interval> stack(n + 2);
    int top = 0, bottom = 0;
    stack[0] = {1, n + 1, 0};
    for (int i = 1; i <= n; ++i) {
        while (i >= stack[bottom].r) ++bottom;
        dp[i] = cost(i, stack[bottom].pos);
        while (top > bottom && i < stack[top].l &&
            cost(stack[top].l, i) < cost(stack[top].l,
                stack[top].pos)) {
            stack[top - 1].r = stack[top].r;
            --top;
        }
        int l = stack[top].l, r = stack[top].r, old =
            stack[top].pos;
        while (l < r) {
            int m = (l + r) / 2;
            if (cost(m, i) < cost(m, old)) r = m;
            else l = m + 1;
        }
        if (l < stack[top].r) {
            int old_r = stack[top].r;
            stack[top].r = l;
            stack[++top] = {l, old_r, i};
        }
    }
    return dp[n];
}

```

10.3 Theorem - DP optimization

Monotonicity & 1D/1D DP & 2D/1D DP

```

Definition xD/yD
1D/1D DP[j] = min(0 ≤ i < j) { DP[i] + w(i, j) }; DP[0] = k
2D/1D DP[i][j] = min(i < k ≤ j) { DP[i][k - 1] + DP[k][j] }
    + w(i, j); DP[i][i] = 0

```

Monotonicity

c d

```

-----
a | w(a, c) w(a, d)
b | w(b, c) w(b, d)

Monge Condition
Concave(凹四邊形不等式):  $w(a, c) + w(b, d) \geq w(a, d) + w(b, c)$ 
Convex (凸四邊形不等式):  $w(a, c) + w(b, d) \leq w(a, d) + w(b, c)$ 

Totally Monotone
Concave(凹單調):  $w(a, c) \leq w(b, d) \rightarrow w(a, d) \leq w(b, c)$ 
Convex (凸單調):  $w(a, c) \geq w(b, d) \rightarrow w(a, d) \geq w(b, c)$ 
-----
1D/1D DP  $O(n^2) \rightarrow O(n \lg n)$ 
**CONSIDER THE TRANSITION POINT**
Solve 1D/1D Concave by Stack
Solve 1D/1D Convex by Deque
-----
2D/1D Convex DP (Totally Monotone)  $O(n^3) \rightarrow O(n^2)$ 
 $h(i, j - 1) \leq h(i, j) \leq h(i + 1, j)$ 

```

10.4 Stable Marriage

```

// preference[a][rank] = b; order[b][a] = rank
vector<int> stable_marriage(const vector<vector<int>> &
    preference,
                           const vector<vector<int>> &
    order) {
    int n = preference.size();
    vector<int> next(n), partner(n, -1);
    queue<int> free;
    for (int a = 0; a < n; ++a) free.push(a);
    while (!free.empty()) {
        int a = free.front();
        free.pop();
        int b = preference[a][next[a]++];
        if (partner[b] == -1) partner[b] = a;
        else if (order[b][a] < order[b][partner[b]])
            free.push(partner[b]), partner[b] = a;
        else free.push(a);
    }
    return partner; // partner[b] = a
}

```

10.5 莫隊

```

// all ranges are [l, r]
struct query {
    int l, r, id;
};

void sort_mo(vector<query> &queries, int n) {
    int block = max(1, int(n / sqrt(max<size_t>(1,
        queries.size()))));
    ranges::sort(queries, [&](query a, query b) {
        int x = a.l / block, y = b.l / block;
        if (x != y) return x < y;
        return x & 1 ? a.r < b.r : a.r > b.r;
    });
}

/*
start with l=0, r=-1 (empty).
move in this order:
while (l > q.l) add(--l); while (r < q.r) add(++r);
while (l < q.l) remove(l--); while (r > q.r) remove(r
--);
*/

```

10.6 莫隊帶修改

```

// all ranges are [l, r]; time = number of applied
updates
struct time_query {
    int l, r, time, id;
};

void sort_mo_with_updates(vector<time_query> &queries,
    int n) {
    int block = max(1, int(pow(max(1, n), 2.0 / 3)));
    ranges::sort(queries, [&](time_query a, time_query
        b) {
        int al = a.l / block, bl = b.l / block;
        if (al != bl) return al < bl;
        int ar = a.r / block, br = b.r / block;
        if (ar != br) return al & 1 ? ar < br : ar > br
            ;
        return ar & 1 ? a.time < b.time : a.time > b.
            time;
    });
}

// start with l=0, r=-1, time=0; apply/undo updates
while moving time

```

10.7 矩陣乘法

```

using ll = long long;
using matrix = vector<vector<ll>>;

matrix multiply(const matrix &a, const matrix &b, ll
    mod) {
    assert(!a.empty() && !b.empty() && a[0].size() == b
        .size());
    matrix c(a.size(), vector<ll>(b[0].size()));
    for (int i = 0; i < ssize(a); ++i)
        for (int k = 0; k < ssize(b); ++k)
            for (int j = 0; j < ssize(b[0]); ++j)
                c[i][j] = (c[i][j] + (__int128)a[i][k]
                    * b[k][j]) % mod;
    return c;
}

```

10.8 c++ 小抄

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/priority_queue.hpp>
using namespace __gnu_pbds;

using ordered_set = tree<int, null_type, less<int>,
    rb_tree_tag,
    tree_order_statistics_node_update
>;
// s.find_by_order(k): iterator to k-th smallest, 0-
// based
// s.order_of_key(x): number of values strictly smaller
// than x

using pairing_heap = __gnu_pbds::priority_queue<int,
    less<int>, pairing_heap_tag>;
// auto it = q.push(x); q.modify(it, y); q.erase(it); q
// .join(other);

// __builtin_popcount(x), __builtin_popcountll(x)
// __builtin_clz(x), __builtin_ctz(x): x must be
// nonzero
// __builtin_*_overflow(a, b, &answer)

int random_int(int l, int r) {
    static mt19937 rng(chrono::steady_clock::now().
        time_since_epoch().count());
    return uniform_int_distribution<int>(l, r)(rng);
}

// sorted unique:
// a.erase(ranges::unique(a).begin(), a.end());

```

10.9 python 小抄

```
#!/usr/bin/env python3
from collections import deque
import sys

def ints():
    return map(int, input().split())

def all_ints():
    return list(map(int, sys.stdin.buffer.read().split(
        )))

def lcs(a, b):
    dp = [0] * (len(b) + 1)
    for x in a:
        prev = 0
        for j, y in enumerate(b, 1):
            old = dp[j]
            if x == y:
                dp[j] = prev + 1
            else:
                dp[j] = max(dp[j], dp[j - 1])
            prev = old
    return dp[-1]

# stack: append, pop, stack[-1]
# queue = deque(); append, popleft, queue[0]
# sorted unique values: sorted(set(values))
```

```
}
    }
}
    return dp;
}
```

10.10 萬年曆

$$h = \left(q + \left\lfloor \frac{13(m+1)}{5} \right\rfloor + K + \left\lfloor \frac{K}{4} \right\rfloor + \left\lfloor \frac{J}{4} \right\rfloor + 5J \right) \bmod 7$$

h : 星期 (0 = 星期六, 1 = 星期日, 2 = 星期一, ...)
 q : 日期 (日)
 m : 月份 (3= 三月, ...; 一、二月改成 13、14, 且年份先減一)
 K : 調整後年份的後兩位數 (year mod 100)
 J : 調整後年份的前兩位數 (year ÷ 100)

10.11 多重背包

```
using ll = long long;

struct item {
    int weight, count;
    ll value;
};

// dp[w] = maximum value with total weight at most w
vector<ll> bounded_knapsack(int capacity, const vector<
    item> &items) {
    vector<ll> dp(capacity + 1);
    for (item x : items) {
        assert(x.weight >= 0 && x.count >= 0);
        if (!x.weight) {
            if (x.value > 0)
                for (ll &value : dp) value += x.value *
                    x.count;
            continue;
        }
        for (int r = 0; r < x.weight && r <= capacity;
            ++r) {
            deque<pair<ll, int>> q;
            for (int k = 0, w = r; w <= capacity; ++k,
                w += x.weight) {
                ll value = dp[w] - ll(k) * x.value;
                while (!q.empty() && q.back().first <=
                    value) q.pop_back();
                q.push_back({value, k});
                while (q.front().second < k - x.count)
                    q.pop_front();
                dp[w] = q.front().first + ll(k) * x.
                    value;
            }
        }
    }
}
```