

---

# **Sage Reference Manual: Modules**

***Release 6.9***

**The Sage Development Team**

October 13, 2015



## CONTENTS

<b>1</b>	<b>Abstract base class for modules</b>	<b>1</b>
<b>2</b>	<b>Free modules</b>	<b>5</b>
<b>3</b>	<b>Discrete Subgroups of <math>\mathbb{Z}^n</math>.</b>	<b>61</b>
<b>4</b>	<b>Elements of free modules</b>	<b>71</b>
<b>5</b>	<b>Free modules of finite rank</b>	<b>119</b>
<b>6</b>	<b>Pickling for the old CDF vector class</b>	<b>151</b>
<b>7</b>	<b>Pickling for the old RDF vector class</b>	<b>153</b>
<b>8</b>	<b>Vectors over callable symbolic rings</b>	<b>155</b>
<b>9</b>	<b>Space of Morphisms of Vector Spaces (Linear Transformations)</b>	<b>157</b>
<b>10</b>	<b>Vector Space Morphisms (aka Linear Transformations)</b>	<b>161</b>
10.1	Creation . . . . .	161
10.2	Properties . . . . .	162
10.3	Restrictions and Representations . . . . .	163
10.4	Equality . . . . .	165
<b>11</b>	<b>Homspaces between free modules</b>	<b>175</b>
<b>12</b>	<b>Morphisms of free modules</b>	<b>179</b>
<b>13</b>	<b>Morphisms defined by a matrix</b>	<b>189</b>
<b>14</b>	<b>Finitely generated modules over a PID</b>	<b>203</b>
<b>15</b>	<b>Elements of finitely generated modules over a PID</b>	<b>217</b>
<b>16</b>	<b>Morphisms between finitely generated modules over a PID</b>	<b>221</b>
<b>17</b>	<b>Diamond cutting implementation</b>	<b>225</b>
<b>18</b>	<b>Concrete classes related to modules with a distinguished basis.</b>	<b>227</b>
<b>19</b>	<b>Module with basis morphisms</b>	<b>229</b>
<b>20</b>	<b>Quotients of Modules With Basis</b>	<b>243</b>

<b>21</b>	<b>Iterators over finite submodules of a <math>\mathbb{Z}</math>-module</b>	<b>247</b>
<b>22</b>	<b>Free quadratic modules</b>	<b>251</b>
<b>23</b>	<b>Miscellaneous module-related functions.</b>	<b>263</b>
<b>24</b>	<b>Quotients of finite rank free modules over a field.</b>	<b>265</b>
<b>25</b>	<b>Dense complex double vectors using a NumPy backend.</b>	<b>269</b>
<b>26</b>	<b>Dense vectors using a NumPy backend.</b>	<b>271</b>
<b>27</b>	<b>Vectors with integer entries</b>	<b>277</b>
<b>28</b>	<b>Vectors with elements in <math>\text{GF}(2)</math>.</b>	<b>279</b>
<b>29</b>	<b>Vectors with integer mod <math>n</math> entries, with <math>n</math> small.</b>	<b>281</b>
<b>30</b>	<b>Vectors with rational entries.</b>	<b>283</b>
<b>31</b>	<b>Dense real double vectors using a NumPy backend.</b>	<b>285</b>
<b>32</b>	<b>Vectors over the symbolic ring.</b>	<b>287</b>
<b>33</b>	<b>Indices and Tables</b>	<b>295</b>
	<b>Bibliography</b>	<b>297</b>

## ABSTRACT BASE CLASS FOR MODULES

Two classes for modules are defined here: `Module_old` and `Module`. The former is a legacy class which should not be used for new code anymore as it does not conform to the coercion model. Eventually all occurrences shall be ported to `Module`.

AUTHORS:

- William Stein: initial version
- Julian Rueth (2014-05-10): category parameter for `Module`, doc cleanup

EXAMPLES:

A minimal example of a module:

```
sage: class MyElement(sage.structure.element.ModuleElement):
....:     def __init__(self, parent, x):
....:         self.x = x
....:         sage.structure.element.ModuleElement.__init__(self, parent=parent)
....:     def _rmul_(self, c):
....:         return self.parent()(c*self.x)
....:     def _add_(self, other):
....:         return self.parent()(self.x + other.x)
....:     def __cmp__(self, other):
....:         return cmp(self.x, other.x)
....:     def __hash__(self):
....:         return hash(self.x)
....:     def _repr_(self):
....:         return repr(self.x)

sage: class MyModule(sage.modules.module.Module):
....:     Element = MyElement
....:     def _element_constructor_(self, x):
....:         if isinstance(x, MyElement): x = x.x
....:         return self.element_class(self, self.base_ring()(x))
....:     def __cmp__(self, other):
....:         if not isinstance(other, MyModule): return cmp(type(other), MyModule)
....:         return cmp(self.base_ring(), other.base_ring())

sage: M = MyModule(QQ)
sage: M(1)
1

sage: import __main__
sage: __main__.MyModule = MyModule
sage: __main__.MyElement = MyElement
sage: TestSuite(M).run()
```

**class** `sage.modules.module.Module`

Bases: `sage.structure.parent.Parent`

Generic module class.

INPUT:

- `base` – a ring. The base ring of the module.
- `category` – a category (default: `None`), the category for this module. If `None`, then this is set to the category of modules/vector spaces over `base`.

EXAMPLES:

```
sage: from sage.modules.module import Module
sage: M = Module(ZZ)
sage: M.base_ring()
Integer Ring
sage: M.category()
Category of modules over Integer Ring
```

Normally the category is set to the category of modules over `base`. If `base` is a field, then the category is the category of vector spaces over `base`:

```
sage: M_QQ = Module(QQ)
sage: M_QQ.category()
Category of vector spaces over Rational Field
```

The `category` parameter can be used to set a more specific category:

```
sage: N = Module(ZZ, category=FiniteDimensionalModulesWithBasis(ZZ))
sage: N.category()
Category of finite dimensional modules with basis over Integer Ring
```

TESTS:

We check that `:trac:'8119'` has been resolved::

```
sage: M = ZZ^3
sage: h = M.__hash__()
sage: M.rename('toto')
sage: h == M.__hash__()
True
```

**`base_extend(R)`**

Return the base extension of `self` to `R`.

This is the same as `self.change_ring(R)` except that a `TypeError` is raised if there is no canonical coerce map from the base ring of `self` to `R`.

INPUT:

- `R` – ring

EXAMPLES:

```
sage: V = ZZ^7
sage: V.base_extend(QQ)
Vector space of dimension 7 over Rational Field
```

TESTS:

```

sage: N = ModularForms(6, 4)
sage: N.base_extend(CyclotomicField(7))
Modular Forms space of dimension 5 for Congruence Subgroup Gamma0(6) of weight 4 over Cyclotomic Field of order 7 and degree 6

sage: m = ModularForms(DirichletGroup(13).0^2, 2); m
Modular Forms space of dimension 3, character [zeta6] and weight 2 over Cyclotomic Field of order 6 and degree 6
sage: m.base_extend(CyclotomicField(12))
Modular Forms space of dimension 3, character [zeta6] and weight 2 over Cyclotomic Field of order 12 and degree 6

sage: chi = DirichletGroup(109, CyclotomicField(3)).0
sage: S3 = CuspForms(chi, 2)
sage: S9 = S3.base_extend(CyclotomicField(9))
sage: S9
Cuspidal subspace of dimension 8 of Modular Forms space of dimension 10, character [zeta3 + zeta3^2] and weight 2 over Cyclotomic Field of order 9 and degree 6
sage: S9.has_coerce_map_from(S3) # not implemented
True
sage: S9.base_extend(CyclotomicField(3))
Traceback (most recent call last):
...
TypeError: Base extension of self (over 'Cyclotomic Field of order 9 and degree 6') to ring

```

**change\_ring(*R*)**

Return the base change of self to *R*.

EXAMPLES:

```

sage: sage.modular.modform.space.ModularFormsSpace(Gamma0(11), 2, DirichletGroup(1)[0], QQ)
Traceback (most recent call last):
...
NotImplementedError: the method change_ring() has not yet been implemented

```

**endomorphism\_ring()**

Return the endomorphism ring of this module in its category.

EXAMPLES:

```

sage: from sage.modules.module import Module
sage: M = Module(ZZ)
sage: M.endomorphism_ring()
Set of Morphisms from <type 'sage.modules.module.Module'> to <type 'sage.modules.module.Module'>

```

**class sage.modules.module.Module\_old**

Bases: sage.structure.parent\_gens.ParentWithAdditiveAbelianGens

Generic module class.

sage.modules.module.is\_Module(*x*)

Return True if *x* is a module, False otherwise.

INPUT:

• *x* – anything.

EXAMPLES:

```

sage: from sage.modules.module import is_Module
sage: M = FreeModule(RationalField(), 30)
sage: is_Module(M)
True
sage: is_Module(10)
False

```

`sage.modules.module.is_VectorSpace(x)`

Return True if `x` is a vector space, False otherwise.

INPUT:

- `x` – anything.

EXAMPLES:

```
sage: from sage.modules.module import is_Module, is_VectorSpace
```

```
sage: M = FreeModule(RationalField(), 30)
```

```
sage: is_VectorSpace(M)
```

```
True
```

```
sage: M = FreeModule(IntegerRing(), 30)
```

```
sage: is_Module(M)
```

```
True
```

```
sage: is_VectorSpace(M)
```

```
False
```



## FREE MODULES

Sage supports computation with free modules over an arbitrary commutative ring. Nontrivial functionality is available over  $\mathbf{Z}$ , fields, and some principal ideal domains (e.g.  $\mathbf{Q}[x]$  and rings of integers of number fields). All free modules over an integral domain are equipped with an embedding in an ambient vector space and an inner product, which you can specify and change.

Create the free module of rank  $n$  over an arbitrary commutative ring  $R$  using the command `FreeModule(R, n)`. Equivalently,  $R^n$  also creates that free module.

The following example illustrates the creation of both a vector space and a free module over the integers and a submodule of it. Use the functions `FreeModule`, `span` and member functions of free modules to create free modules. *Do not use the `FreeModule_XXX` constructors directly.*

EXAMPLES:

```
sage: V = VectorSpace(QQ, 3)
sage: W = V.subspace([[1, 2, 7], [1, 1, 0]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -7]
[ 0  1  7]
sage: C = VectorSpaces(FiniteField(7))
sage: C
Category of vector spaces over Finite Field of size 7
sage: C(W)
Vector space of degree 3 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0 0]
[0 1 0]

sage: M = ZZ^3
sage: C = VectorSpaces(FiniteField(7))
sage: C(M)
Vector space of dimension 3 over Finite Field of size 7
sage: W = M.submodule([[1, 2, 7], [8, 8, 0]])
sage: C(W)
Vector space of degree 3 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0 0]
[0 1 0]
```

We illustrate the exponent notation for creation of free modules.

```
sage: ZZ^4
Ambient free module of rank 4 over the principal ideal domain Integer Ring
```

```
sage: QQ^2
Vector space of dimension 2 over Rational Field
sage: RR^3
Vector space of dimension 3 over Real Field with 53 bits of precision
```

Base ring:

```
sage: R.<x,y> = QQ[]
sage: M = FreeModule(R,2)
sage: M.base_ring()
Multivariate Polynomial Ring in x, y over Rational Field

sage: VectorSpace(QQ, 10).base_ring()
Rational Field
```

TESTS: We intersect a zero-dimensional vector space with a 1-dimension submodule.

```
sage: V = (QQ^1).span([])
sage: W = ZZ^1
sage: V.intersection(W)
Free module of degree 1 and rank 0 over Integer Ring
Echelon basis matrix:
[]
```

We construct subspaces of real and complex double vector spaces and verify that the element types are correct:

```
sage: V = FreeModule(RDF, 3); V
Vector space of dimension 3 over Real Double Field
sage: V.0
(1.0, 0.0, 0.0)
sage: type(V.0)
<type 'sage.modules.vector_real_double_dense.Vector_real_double_dense'>
sage: W = V.span([V.0]); W
Vector space of degree 3 and dimension 1 over Real Double Field
Basis matrix:
[1.0 0.0 0.0]
sage: type(W.0)
<type 'sage.modules.vector_real_double_dense.Vector_real_double_dense'>
sage: V = FreeModule(CDF, 3); V
Vector space of dimension 3 over Complex Double Field
sage: type(V.0)
<type 'sage.modules.vector_complex_double_dense.Vector_complex_double_dense'>
sage: W = V.span_of_basis([CDF.0 * V.1]); W
Vector space of degree 3 and dimension 1 over Complex Double Field
User basis matrix:
[ 0.0 1.0*I 0.0]
sage: type(W.0)
<type 'sage.modules.vector_complex_double_dense.Vector_complex_double_dense'>
```

Basis vectors are immutable:

```
sage: A = span([[1,2,3], [4,5,6]], ZZ)
sage: A.0
(1, 2, 3)
sage: A.0[0] = 5
Traceback (most recent call last):
...
ValueError: vector is immutable; please change a copy instead (use copy())
```

Among other things, this tests that we can save and load submodules and elements:

```
sage: M = ZZ^3
sage: TestSuite(M).run()
sage: W = M.span_of_basis([[1, 2, 3], [4, 5, 19]])
sage: TestSuite(W).run()
sage: v = W.0 + W.1
sage: TestSuite(v).run()
```

#### AUTHORS:

- William Stein (2005, 2007)
- David Kohel (2007, 2008)
- Niles Johnson (2010-08): Trac #3893: `random_element()` should pass on `*args` and `**kwargs`.
- Simon King (2010-12): Trac #8800: Fixing a bug in `denominator()`.
- Simon King (2010-12), Peter Bruin (June 2014): Trac #10513: New coercion model and category framework.

```
class sage.modules.free_module.ComplexDoubleVectorSpace_class(n)
    Bases: sage.modules.free_module.FreeModule_ambient_field
    coordinates(v)
```

```
class sage.modules.free_module.FreeModuleFactory
    Bases: sage.structure.factory.UniqueFactory
```

Create the free module over the given commutative ring of the given rank.

#### INPUT:

- `base_ring` - a commutative ring
- `rank` - a nonnegative integer
- `sparse` - bool; (default False)
- `inner_product_matrix` - the inner product matrix (default None)

OUTPUT: a free module

---

**Note:** In Sage it is the case that there is only one dense and one sparse free ambient module of rank  $n$  over  $R$ .

---

#### EXAMPLES:

First we illustrate creating free modules over various base fields. The base field affects the free module that is created. For example, free modules over a field are vector spaces, and free modules over a principal ideal domain are special in that more functionality is available for them than for completely general free modules.

```
sage: FreeModule(Integers(8), 10)
Ambient free module of rank 10 over Ring of integers modulo 8
sage: FreeModule(QQ, 10)
Vector space of dimension 10 over Rational Field
sage: FreeModule(ZZ, 10)
Ambient free module of rank 10 over the principal ideal domain Integer Ring
sage: FreeModule(FiniteField(5), 10)
Vector space of dimension 10 over Finite Field of size 5
sage: FreeModule(Integers(7), 10)
Vector space of dimension 10 over Ring of integers modulo 7
sage: FreeModule(PolynomialRing(QQ, 'x'), 5)
Ambient free module of rank 5 over the principal ideal domain Univariate Polynomial Ring in x ov
```

```
sage: FreeModule(PolynomialRing(ZZ, 'x'), 5)
Ambient free module of rank 5 over the integral domain Univariate Polynomial Ring in x over Inte
```

Of course we can make rank 0 free modules:

```
sage: FreeModule(RealField(100), 0)
Vector space of dimension 0 over Real Field with 100 bits of precision
```

Next we create a free module with sparse representation of elements. Functionality with sparse modules is *identical* to dense modules, but they may use less memory and arithmetic may be faster (or slower!).

```
sage: M = FreeModule(ZZ, 200, sparse=True)
sage: M.is_sparse()
True
sage: type(M.0)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
```

The default is dense.

```
sage: M = ZZ^200
sage: type(M.0)
<type 'sage.modules.vector_integer_dense.Vector_integer_dense'>
```

Note that matrices associated in some way to sparse free modules are sparse by default:

```
sage: M = FreeModule(Integers(8), 2)
sage: A = M.basis_matrix()
sage: A.is_sparse()
False
sage: Ms = FreeModule(Integers(8), 2, sparse=True)
sage: M == Ms # as mathematical objects they are equal
True
sage: Ms.basis_matrix().is_sparse()
True
```

We can also specify an inner product matrix, which is used when computing inner products of elements.

```
sage: A = MatrixSpace(ZZ, 2) ([[1, 0], [0, -1]])
sage: M = FreeModule(ZZ, 2, inner_product_matrix=A)
sage: v, w = M.gens()
sage: v.inner_product(w)
0
sage: v.inner_product(v)
1
sage: w.inner_product(w)
-1
sage: (v+2*w).inner_product(w)
-2
```

You can also specify the inner product matrix by giving anything that coerces to an appropriate matrix. This is only useful if the inner product matrix takes values in the base ring.

```
sage: FreeModule(ZZ, 2, inner_product_matrix=1).inner_product_matrix()
[1 0]
[0 1]
sage: FreeModule(ZZ, 2, inner_product_matrix=[1, 2, 3, 4]).inner_product_matrix()
[1 2]
[3 4]
sage: FreeModule(ZZ, 2, inner_product_matrix=[[1, 2], [3, 4]]).inner_product_matrix()
[1 2]
```

[3 4]

---

**Todo**

Refactor modules such that it only counts what category the base ring belongs to, but not what is its Python class.

---

**create\_key** (*base\_ring*, *rank*, *sparse=False*, *inner\_product\_matrix=None*)

TESTS:

```
sage: loads(dumps(ZZ^6)) is ZZ^6
True
sage: loads(dumps(RDF^3)) is RDF^3
True
```

TODO: replace the above by `TestSuite(...).run()`, once `_test_pickling()` will test unique representation and not only equality.

**create\_object** (*version*, *key*)

**class** `sage.modules.free_module.FreeModule_ambient` (*base\_ring*, *rank*, *sparse=False*, *coordinate\_ring=None*)

Bases: `sage.modules.free_module.FreeModule_generic`

Ambient free module over a commutative ring.

**ambient\_module** ()

Return self, since self is ambient.

EXAMPLES:

```
sage: A = QQ^5; A.ambient_module()
Vector space of dimension 5 over Rational Field
sage: A = ZZ^5; A.ambient_module()
Ambient free module of rank 5 over the principal ideal domain Integer Ring
```

**basis** ()

Return a basis for this ambient free module.

OUTPUT:

- Sequence - an immutable sequence with universe this ambient free module

EXAMPLES:

```
sage: A = ZZ^3; B = A.basis(); B
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
sage: B.universe()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

**change\_ring** (*R*)

Return the ambient free module over *R* of the same rank as self.

EXAMPLES:

```
sage: A = ZZ^3; A.change_ring(QQ)
Vector space of dimension 3 over Rational Field
```

```
sage: A = ZZ^3; A.change_ring(GF(5))
Vector space of dimension 3 over Finite Field of size 5
```

For ambient modules any change of rings is defined.

```
sage: A = GF(5)**3; A.change_ring(QQ)
Vector space of dimension 3 over Rational Field
```

**coordinate\_vector**(*v*, *check=True*)

Write *v* in terms of the standard basis for self and return the resulting coefficients in a vector over the fraction field of the base ring.

Returns a vector *c* such that if *B* is the basis for self, then

$$\sum c_i B_i = v.$$

If *v* is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = Integers(16)^3
sage: v = V.coordinate_vector([1,5,9]); v
(1, 5, 9)
sage: v.parent()
Ambient free module of rank 3 over Ring of integers modulo 16
```

**echelon\_coordinate\_vector**(*v*, *check=True*)

Same as `self.coordinate_vector(v)`, since self is an ambient free module.

INPUT:

- *v* - vector
- *check* - bool (default: True); if True, also verify that *v* is really in self.

OUTPUT: list

EXAMPLES:

```
sage: V = QQ^4
sage: v = V([-1/2, 1/2, -1/2, 1/2])
sage: v
(-1/2, 1/2, -1/2, 1/2)
sage: V.coordinate_vector(v)
(-1/2, 1/2, -1/2, 1/2)
sage: V.echelon_coordinate_vector(v)
(-1/2, 1/2, -1/2, 1/2)
sage: W = V.submodule_with_basis([[1/2, 1/2, 1/2, 1/2], [1, 0, 1, 0]])
sage: W.coordinate_vector(v)
(1, -1)
sage: W.echelon_coordinate_vector(v)
(-1/2, 1/2)
```

**echelon\_coordinates**(*v*, *check=True*)

Returns the coordinate vector of *v* in terms of the echelon basis for self.

EXAMPLES:

```
sage: U = VectorSpace(QQ, 3)
sage: [ U.coordinates(v) for v in U.basis() ]
[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
sage: [ U.echelon_coordinates(v) for v in U.basis() ]
```

```

[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
sage: V = U.submodule([[1,1,0],[0,1,1]])
sage: V
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  1]
sage: [ V.coordinates(v) for v in V.basis() ]
[[1, 0], [0, 1]]
sage: [ V.echelon_coordinates(v) for v in V.basis() ]
[[1, 0], [0, 1]]
sage: W = U.submodule_with_basis([[1,1,0],[0,1,1]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 1 0]
[0 1 1]
sage: [ W.coordinates(v) for v in W.basis() ]
[[1, 0], [0, 1]]
sage: [ W.echelon_coordinates(v) for v in W.basis() ]
[[1, 1], [0, 1]]

```

**echelonized\_basis()**

Return a basis for this ambient free module in echelon form.

**EXAMPLES:**

```

sage: A = ZZ^3; A.echelonized_basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]

```

**echelonized\_basis\_matrix()**

The echelonized basis matrix of self.

**EXAMPLES:**

```

sage: V = ZZ^4
sage: W = V.submodule([ V.gen(i)-V.gen(0) for i in range(1,4) ])
sage: W.basis_matrix()
[ 1  0  0 -1]
[ 0  1  0 -1]
[ 0  0  1 -1]
sage: W.echelonized_basis_matrix()
[ 1  0  0 -1]
[ 0  1  0 -1]
[ 0  0  1 -1]
sage: U = V.submodule_with_basis([ V.gen(i)-V.gen(0) for i in range(1,4) ])
sage: U.basis_matrix()
[-1  1  0  0]
[-1  0  1  0]
[-1  0  0  1]
sage: U.echelonized_basis_matrix()
[ 1  0  0 -1]
[ 0  1  0 -1]
[ 0  0  1 -1]

```

**gen** (*i*=0)Return the *i*-th generator for `self`.Here *i* is between 0 and rank - 1, inclusive.

INPUT:

- *i* – an integer (default 0)

OUTPUT: *i*-th basis vector for `self`.

EXAMPLES:

```
sage: n = 5
sage: V = QQ^n
sage: B = [V.gen(i) for i in range(n)]
sage: B
[(1, 0, 0, 0, 0),
 (0, 1, 0, 0, 0),
 (0, 0, 1, 0, 0),
 (0, 0, 0, 1, 0),
 (0, 0, 0, 0, 1)]
sage: V.gens() == tuple(B)
True
```

TESTS:

```
sage: (QQ^3).gen(4/3)
Traceback (most recent call last):
...
TypeError: rational is not an integer
```

Check that `trac ticket #10262` and `trac ticket #13304` are fixed (coercions involving `FreeModule_ambient` used to take quadratic time and space in the rank of the module):

```
sage: vector([0]*50000)/1
(0, 0, 0, ..., 0)
```

**is\_ambient** ()

Return True since this module is an ambient module.

EXAMPLES:

```
sage: A = QQ^5; A.is_ambient()
True
sage: A = (QQ^5).span([[1,2,3,4,5]]); A.is_ambient()
False
```

**linear\_combination\_of\_basis** (*v*)Return the linear combination of the basis for `self` obtained from the elements of the list *v*.

INPUTS:

- *v* - list

EXAMPLES:

```
sage: V = span([[1,2,3], [4,5,6]], ZZ)
sage: V
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1 2 3]
[0 3 6]
```



```
sage: V.linear_combination_of_basis([1,1])
(1, 5, 9)
```

This should raise an error if the resulting element is not in self:

```
sage: W = span([[2,4]], ZZ)
sage: W.linear_combination_of_basis([1/2])
Traceback (most recent call last):
...
TypeError: element [1, 2] is not in free module
```

**random\_element** (*prob=1.0, \*args, \*\*kws*)

Returns a random element of self.

INPUT:

- **prob** - float. Each coefficient will be set to zero with probability  $1 - \text{prob}$ . Otherwise coefficients will be chosen randomly from base ring (and may be zero).

- **\*args, \*\*kws** - passed on to `random_element` function of base ring.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.random_element()
(-1, 2, 1)
sage: M.random_element()
(-95, -1, -2)
sage: M.random_element()
(-12, 0, 0)
```

Passes extra positional or keyword arguments through:

```
sage: M.random_element(5,10)
(5, 5, 5)

sage: M = FreeModule(ZZ, 16)
sage: M.random_element()
(-6, 5, 0, 0, -2, 0, 1, -4, -6, 1, -1, 1, 1, -1, 1, -1)
sage: M.random_element(prob=0.3)
(0, 0, 0, 0, -3, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, -3)
```

```
class sage.modules.free_module.FreeModule_ambient_domain(base_ring, rank,
                                                           sparse=False, coordi-
                                                           nate_ring=None)
```

Bases: `sage.modules.free_module.FreeModule_ambient`

Ambient free module over an integral domain.

**ambient\_vector\_space** ()

Returns the ambient vector space, which is this free module tensored with its fraction field.

EXAMPLES:

```
sage: M = ZZ^3;
sage: V = M.ambient_vector_space(); V
Vector space of dimension 3 over Rational Field
```

If an inner product on the module is specified, then this is preserved on the ambient vector space.

```
sage: N = FreeModule(ZZ,4,inner_product_matrix=1)
sage: U = N.ambient_vector_space()
```

```

sage: U
Ambient quadratic space of dimension 4 over Rational Field
Inner product matrix:
[1 0 0 0]
[0 1 0 0]
[0 0 1 0]
[0 0 0 1]
sage: P = N.submodule_with_basis([[1,-1,0,0],[0,1,-1,0],[0,0,1,-1]])
sage: P.gram_matrix()
[ 2 -1  0]
[-1  2 -1]
[ 0 -1  2]
sage: U == N.ambient_vector_space()
True
sage: U == V
False

```

#### **coordinate\_vector** (*v*, *check=True*)

Write *v* in terms of the standard basis for self and return the resulting coefficients in a vector over the fraction field of the base ring.

INPUT:

- *v* – vector
- *check* – bool (default: True); if True, also verify that *v* is really in self.

OUTPUT: list

Returns a vector *c* such that if *B* is the basis for self, then

$$\sum c_i B_i = v.$$

If *v* is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```

sage: V = ZZ^3
sage: v = V.coordinate_vector([1,5,9]); v
(1, 5, 9)
sage: v.parent()
Vector space of dimension 3 over Rational Field

```

#### **vector\_space** (*base\_field=None*)

Returns the vector space obtained from self by tensoring with the fraction field of the base ring and extending to the field.

EXAMPLES:

```

sage: M = ZZ^3; M.vector_space()
Vector space of dimension 3 over Rational Field

```

```

class sage.modules.free_module.FreeModule_ambient_field(base_field, dimension,
                                                         sparse=False)
    Bases: sage.modules.free_module.FreeModule_generic_field,
           sage.modules.free_module.FreeModule_ambient_pid

```

#### **ambient\_vector\_space** ()

Returns self as the ambient vector space.

EXAMPLES:

```
sage: M = QQ^3
sage: M.ambient_vector_space()
Vector space of dimension 3 over Rational Field
```

**base\_field()**

Returns the base field of this vector space.

EXAMPLES:

```
sage: M = QQ^3
sage: M.base_field()
Rational Field
```

```
class sage.modules.free_module.FreeModule_ambient_pid(base_ring, rank, sparse=False,
                                                    coordinate_ring=None)
Bases: sage.modules.free_module.FreeModule_generic_pid,
sage.modules.free_module.FreeModule_ambient_domain
```

Ambient free module over a principal ideal domain.

```
class sage.modules.free_module.FreeModule_generic(base_ring, rank, degree, sparse=False,
                                                    coordinate_ring=None, category=None)
```

Bases: `sage.modules.module.Module`

Base class for all free modules.

TESTS:

Check that [trac ticket #17576](#) is fixed:

```
sage: V = VectorSpace(RDF, 3)
sage: v = vector(RDF, [1, 2, 3, 4])
sage: v in V
False
```

**ambient\_module()**

Return the ambient module associated to this module.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: M = FreeModule(R, 2)
sage: M.ambient_module()
Ambient free module of rank 2 over the integral domain Multivariate Polynomial Ring in x, y

sage: V = FreeModule(QQ, 4).span([[1,2,3,4], [1,0,0,0]]); V
Vector space of degree 4 and dimension 2 over Rational Field
Basis matrix:
[ 1  0  0  0]
[ 0  1 3/2  2]
sage: V.ambient_module()
Vector space of dimension 4 over Rational Field
```

**are\_linearly\_dependent** (vecs)

Return True if the vectors `vecs` are linearly dependent and False otherwise.

EXAMPLES:

```
sage: M = QQ^3
sage: vecs = [M([1,2,3]), M([4,5,6])]
sage: M.are_linearly_dependent(vecs)
```

```
False
sage: vecs.append(M([3,3,3]))
sage: M.are_linearly_dependent(vecs)
True

sage: R.<x> = QQ[]
sage: M = FreeModule(R, 2)
sage: vecs = [M([x^2+1, x+1]), M([x+2, 2*x+1])]
sage: M.are_linearly_dependent(vecs)
False
sage: vecs.append(M([-2*x+1, -2*x^2+1]))
sage: M.are_linearly_dependent(vecs)
True
```

**base\_field()**

Return the base field, which is the fraction field of the base ring of this module.

**EXAMPLES:**

```
sage: FreeModule(GF(3), 2).base_field()
Finite Field of size 3
sage: FreeModule(ZZ, 2).base_field()
Rational Field
sage: FreeModule(PolynomialRing(GF(7), 'x'), 2).base_field()
Fraction Field of Univariate Polynomial Ring in x over Finite Field of size 7
```

**basis()**

Return the basis of this module.

**EXAMPLES:**

```
sage: FreeModule(Integers(12), 3).basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
```

**basis\_matrix (ring=None)**

Return the matrix whose rows are the basis for this free module.

**INPUT:**

- ring – (default: `self.coordinate_ring()`) a ring over which the matrix is defined

**EXAMPLES:**

```
sage: FreeModule(Integers(12), 3).basis_matrix()
[1 0 0]
[0 1 0]
[0 0 1]

sage: M = FreeModule(GF(7), 3).span([[2,3,4],[1,1,1]]); M
Vector space of degree 3 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0 6]
[0 1 2]
sage: M.basis_matrix()
[1 0 6]
[0 1 2]
```

```

sage: M = FreeModule(GF(7), 3).span_of_basis([[2, 3, 4], [1, 1, 1]]);
sage: M.basis_matrix()
[2 3 4]
[1 1 1]

sage: M = FreeModule(QQ, 2).span_of_basis([[1, -1], [1, 0]]); M
Vector space of degree 2 and dimension 2 over Rational Field
User basis matrix:
[ 1 -1]
[ 1  0]
sage: M.basis_matrix()
[ 1 -1]
[ 1  0]

```

**TESTS:**

See [trac ticket #3699](#):

```

sage: K = FreeModule(ZZ, 2000)
sage: I = K.basis_matrix()

```

See [trac ticket #17585](#):

```

sage: ((ZZ^2)*2).basis_matrix().parent()
Full MatrixSpace of 2 by 2 dense matrices over Integer Ring
sage: ((ZZ^2)*2).basis_matrix(RDF).parent()
Full MatrixSpace of 2 by 2 dense matrices over Real Double Field

sage: M = (ZZ^2)*(1/2)
sage: M.basis_matrix()
[1/2  0]
[ 0 1/2]
sage: M.basis_matrix().parent()
Full MatrixSpace of 2 by 2 dense matrices over Rational Field
sage: M.basis_matrix(QQ).parent()
Full MatrixSpace of 2 by 2 dense matrices over Rational Field
sage: M.basis_matrix(ZZ)
Traceback (most recent call last):
...
TypeError: matrix has denominators so can't change to ZZ.

```

**cardinality()**

Return the cardinality of the free module.

**OUTPUT:**

Either an integer or +Infinity.

**EXAMPLES:**

```

sage: k.<a> = FiniteField(9)
sage: V = VectorSpace(k, 3)
sage: V.cardinality()
729
sage: W = V.span([[1, 2, 1], [0, 1, 1]])
sage: W.cardinality()
81
sage: R = IntegerModRing(12)
sage: M = FreeModule(R, 2)
sage: M.cardinality()
144

```

```
sage: (QQ^3).cardinality()
+Infinity
```

### construction()

The construction functor and base ring for self.

EXAMPLES:

```
sage: R = PolynomialRing(QQ, 3, 'x')
sage: V = R^5
sage: V.construction()
(VectorFunctor, Multivariate Polynomial Ring in x0, x1, x2 over Rational Field)
```

### coordinate\_module(V)

Suppose  $V$  is a submodule of self (or a module commensurable with self), and that self is a free module over  $R$  of rank  $n$ . Let  $\phi$  be the map from self to  $R^n$  that sends the basis vectors of self in order to the standard basis of  $R^n$ . This function returns the image  $\phi(V)$ .

**Warning:** If there is no integer  $d$  such that  $dV$  is a submodule of self, then this function will give total nonsense.

EXAMPLES:

We illustrate this function with some  $\mathbf{Z}$ -submodules of  $\mathbf{Q}^3$ .

```
sage: V = (ZZ^3).span([[1/2, 3, 5], [0, 1, -3]])
sage: W = (ZZ^3).span([[1/2, 4, 2]])
sage: V.coordinate_module(W)
Free module of degree 2 and rank 1 over Integer Ring
User basis matrix:
[1 4]
sage: V.0 + 4*V.1
(1/2, 4, 2)
```

In this example, the coordinate module isn't even in  $\mathbf{Z}^3$ .

```
sage: W = (ZZ^3).span([[1/4, 2, 1]])
sage: V.coordinate_module(W)
Free module of degree 2 and rank 1 over Integer Ring
User basis matrix:
[1/2  2]
```

The following more elaborate example illustrates using this function to write a submodule in terms of integral cuspidal modular symbols:

```
sage: M = ModularSymbols(54)
sage: S = M.cuspidal_subspace()
sage: K = S.integral_structure(); K
Free module of degree 19 and rank 8 over Integer Ring
Echelon basis matrix:
[ 0  1  0  0 -1  0  0  0  0  0  0  0  0  0  0  0  0  0  0]
...
sage: L = M[0].integral_structure(); L
Free module of degree 19 and rank 2 over Integer Ring
Echelon basis matrix:
[ 0  1  1  0 -2  1 -1  1 -1 -2  2  0  0  0  0  0  0  0  0]
[ 0  0  3  0 -3  2 -1  2 -1 -4  2 -1 -2  1  2  0  0 -1  1]
sage: K.coordinate_module(L)
Free module of degree 8 and rank 2 over Integer Ring
```

```

User basis matrix:
[ 1  1  1 -1  1 -1  0  0]
[ 0  3  2 -1  2 -1 -1 -2]
sage: K.coordinate_module(L).basis_matrix() * K.basis_matrix()
[ 0  1  1  0 -2  1 -1  1 -1 -2  2  0  0  0  0  0  0  0]
[ 0  0  3  0 -3  2 -1  2 -1 -4  2 -1 -2  1  2  0  0 -1  1]

```

**coordinate\_ring()**

Return the ring over which the entries of the vectors are defined.

This is the same as `base_ring()` unless an explicit basis was given over the fraction field.

**EXAMPLES:**

```

sage: M = ZZ^2
sage: M.coordinate_ring()
Integer Ring

sage: M = (ZZ^2) * (1/2)
sage: M.base_ring()
Integer Ring
sage: M.coordinate_ring()
Rational Field

sage: R.<x> = QQ[]
sage: L = R^2
sage: L.coordinate_ring()
Univariate Polynomial Ring in x over Rational Field
sage: L.span([(x,0), (1,x)]).coordinate_ring()
Univariate Polynomial Ring in x over Rational Field
sage: L.span([(x,0), (1,1/x)]).coordinate_ring()
Fraction Field of Univariate Polynomial Ring in x over Rational Field
sage: L.span([]).coordinate_ring()
Univariate Polynomial Ring in x over Rational Field

```

**coordinate\_vector(v, check=True)**

Return the vector whose coefficients give  $v$  as a linear combination of the basis for self.

**INPUT:**

- $v$  – vector
- **check** – bool (default: True); if True, also verify that  $v$  is really in self.

OUTPUT: list

**EXAMPLES:**

```

sage: M = FreeModule(ZZ, 2); M0,M1=M.gens()
sage: W = M.submodule([M0 + M1, M0 - 2*M1])
sage: W.coordinate_vector(2*M0 - M1)
(2, -1)

```

**coordinates(v, check=True)**

Write  $v$  in terms of the basis for self.

**INPUT:**

- $v$  – vector
- **check** – bool (default: True); if True, also verify that  $v$  is really in self.

OUTPUT: list

Returns a list  $c$  such that if  $B$  is the basis for self, then

$$\sum c_i B_i = v.$$

If  $v$  is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2); M0,M1=M.gens()
sage: W = M.submodule([M0 + M1, M0 - 2*M1])
sage: W.coordinates(2*M0-M1)
[2, -1]
```

**degree()**

Return the degree of this free module. This is the dimension of the ambient vector space in which it is embedded.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 10)
sage: W = M.submodule([M.gen(0), 2*M.gen(3) - M.gen(0), M.gen(0) + M.gen(3)])
sage: W.degree()
10
sage: W.rank()
2
```

**dense\_module()**

Return corresponding dense module.

EXAMPLES:

We first illustrate conversion with ambient spaces:

```
sage: M = FreeModule(QQ, 3)
sage: S = FreeModule(QQ, 3, sparse=True)
sage: M.sparse_module()
Sparse vector space of dimension 3 over Rational Field
sage: S.dense_module()
Vector space of dimension 3 over Rational Field
sage: M.sparse_module() == S
True
sage: S.dense_module() == M
True
sage: M.dense_module() == M
True
sage: S.sparse_module() == S
True
```

Next we create a subspace:

```
sage: M = FreeModule(QQ, 3, sparse=True)
sage: V = M.span([ [1,2,3] ] ); V
Sparse vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
sage: V.sparse_module()
Sparse vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
```



**dimension()**

Return the dimension of this free module.

## EXAMPLES:

```
sage: M = FreeModule(FiniteField(19), 100)
sage: W = M.submodule([M.gen(50)])
sage: W.dimension()
1
```

**direct\_sum(*other*)**

Return the direct sum of self and other as a free module.

## EXAMPLES:

```
sage: V = (ZZ^3).span([[1/2, 3, 5], [0, 1, -3]]); V
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1/2  0  14]
[  0  1  -3]
sage: W = (ZZ^3).span([[1/2, 4, 2]]); W
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1/2  4  2]
sage: V.direct_sum(W)
Free module of degree 6 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  0  14  0  0  0]
[  0  1  -3  0  0  0]
[  0  0  0  1/2  4  2]
```

**discriminant()**

Return the discriminant of this free module.

## EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.discriminant()
1
sage: W = M.span([[1, 2, 3]])
sage: W.discriminant()
14
sage: W2 = M.span([[1, 2, 3], [1, 1, 1]])
sage: W2.discriminant()
6
```

**echelonized\_basis\_matrix()**

The echelonized basis matrix (not implemented for this module).

This example works because M is an ambient module. Submodule creation should exist for generic modules.

## EXAMPLES:

```
sage: R = IntegerModRing(12)
sage: S.<x,y> = R[]
sage: M = FreeModule(S, 3)
sage: M.echelonized_basis_matrix()
[1 0 0]
[0 1 0]
[0 0 1]
```

TESTS:

```
sage: from sage.modules.free_module import FreeModule_generic
sage: FreeModule_generic.echelonized_basis_matrix(M)
Traceback (most recent call last):
...
NotImplementedError
```

**free\_module()**

Return this free module. (This is used by the FreeModule functor, and simply returns self.)

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.free_module()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

**gen(*i*=0)**

Return the *i*-th generator for self.

Here *i* is between 0 and rank - 1, inclusive.

INPUT:

- *i* – an integer (default 0)

OUTPUT: *i*-th basis vector for self.

EXAMPLES:

```
sage: n = 5
sage: V = QQ^n
sage: B = [V.gen(i) for i in range(n)]
sage: B
[(1, 0, 0, 0, 0),
 (0, 1, 0, 0, 0),
 (0, 0, 1, 0, 0),
 (0, 0, 0, 1, 0),
 (0, 0, 0, 0, 1)]
sage: V.gens() == tuple(B)
True
```

TESTS:

```
sage: (QQ^3).gen(4/3)
Traceback (most recent call last):
...
TypeError: rational is not an integer
```

**gens()**

Return a tuple of basis elements of self.

EXAMPLES:

```
sage: FreeModule(Integers(12), 3).gens()
((1, 0, 0), (0, 1, 0), (0, 0, 1))
```

**gram\_matrix()**

Return the gram matrix associated to this free module, defined to be  $G = B * A * B.transpose()$ , where *A* is the inner product matrix (induced from the ambient space), and *B* the basis matrix.

EXAMPLES:

```

sage: V = VectorSpace(QQ, 4)
sage: u = V([1/2, 1/2, 1/2, 1/2])
sage: v = V([0, 1, 1, 0])
sage: w = V([0, 0, 1, 1])
sage: M = span([u, v, w], ZZ)
sage: M.inner_product_matrix() == V.inner_product_matrix()
True
sage: L = M.submodule_with_basis([u, v, w])
sage: L.inner_product_matrix() == M.inner_product_matrix()
True
sage: L.gram_matrix()
[1 1 1]
[1 2 1]
[1 1 2]

```

**has\_user\_basis()**

Return True if the basis of this free module is specified by the user, as opposed to being the default echelon form.

EXAMPLES:

```

sage: V = QQ^3
sage: W = V.subspace([[2, '1/2', 1]])
sage: W.has_user_basis()
False
sage: W = V.subspace_with_basis([[2, '1/2', 1]])
sage: W.has_user_basis()
True

```

**inner\_product\_matrix()**

Return the default identity inner product matrix associated to this module.

By definition this is the inner product matrix of the ambient space, hence may be of degree greater than the rank of the module.

TODO: Differentiate the image ring of the inner product from the base ring of the module and/or ambient space. E.g. On an integral module over ZZ the inner product pairing could naturally take values in ZZ, QQ, RR, or CC.

EXAMPLES:

```

sage: M = FreeModule(ZZ, 3)
sage: M.inner_product_matrix()
[1 0 0]
[0 1 0]
[0 0 1]

```

**is\_ambient()**

Returns False since this is not an ambient free module.

EXAMPLES:

```

sage: M = FreeModule(ZZ, 3).span([[1, 2, 3]]); M
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1 2 3]
sage: M.is_ambient()
False
sage: M = (ZZ^2).span([[1, 0], [0, 1]])
sage: M

```

```
Free module of degree 2 and rank 2 over Integer Ring
Echelon basis matrix:
[1 0]
[0 1]
sage: M.is_ambient()
False
sage: M == M.ambient_module()
True
```

**is\_dense()**

Return True if the underlying representation of this module uses dense vectors, and False otherwise.

## EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_dense()
True
sage: FreeModule(ZZ, 2, sparse=True).is_dense()
False
```

**is\_finite()**

Returns True if the underlying set of this free module is finite.

## EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_finite()
False
sage: FreeModule(Integers(8), 2).is_finite()
True
sage: FreeModule(ZZ, 0).is_finite()
True
```

**is\_full()**

Return True if the rank of this module equals its degree.

## EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_full()
True
sage: M = FreeModule(ZZ, 2).span([[1, 2]])
sage: M.is_full()
False
```

**is\_sparse()**

Return True if the underlying representation of this module uses sparse vectors, and False otherwise.

## EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_sparse()
False
sage: FreeModule(ZZ, 2, sparse=True).is_sparse()
True
```

**is\_submodule(*other*)**

Return True if self is a submodule of other.

## EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: V = M.ambient_vector_space()
sage: X = V.span([[1/2, 1/2, 0], [1/2, 0, 1/2]], ZZ)
sage: Y = V.span([[1, 1, 1]], ZZ)
sage: N = X + Y
```

```

sage: M.is_submodule(X)
False
sage: M.is_submodule(Y)
False
sage: Y.is_submodule(M)
True
sage: N.is_submodule(M)
False
sage: M.is_submodule(N)
True

sage: M = FreeModule(ZZ, 2)
sage: M.is_submodule(M)
True
sage: N = M.scale(2)
sage: N.is_submodule(M)
True
sage: M.is_submodule(N)
False
sage: N = M.scale(1/2)
sage: N.is_submodule(M)
False
sage: M.is_submodule(N)
True

```

Since `basis()` is not implemented in general, submodule testing does not work for all PID's. However, trivial cases are already used (and useful) for coercion, e.g.

```

sage: QQ(1/2) * vector(ZZ['x']['y'], [1, 2, 3, 4])
(1/2, 1, 3/2, 2)
sage: vector(ZZ['x']['y'], [1, 2, 3, 4]) * QQ(1/2)
(1/2, 1, 3/2, 2)

```

### `list()`

Return a list of all elements of `self`.

EXAMPLES:

```

sage: (GF(3)^2).list()
[(0, 0), (1, 0), (2, 0), (0, 1), (1, 1), (2, 1), (0, 2), (1, 2), (2, 2)]
sage: (ZZ^2).list()
Traceback (most recent call last):
...

```

`NotImplementedError`: since it is infinite, cannot list Ambient free module of rank 2 over th

### `matrix()`

Return the basis matrix of this module, which is the matrix whose rows are a basis for this module.

EXAMPLES:

```

sage: M = FreeModule(ZZ, 2)
sage: M.matrix()
[1 0]
[0 1]
sage: M.submodule([M.gen(0) + M.gen(1), M.gen(0) - 2*M.gen(1)]).matrix()
[1 1]
[0 3]

```

### `ngens()`

Returns the number of basis elements of this free module.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).ngens()
2
sage: FreeModule(ZZ, 0).ngens()
0
sage: FreeModule(ZZ, 2).span([[1,1]]).ngens()
1
```

**nonembedded\_free\_module()**

Returns an ambient free module that is isomorphic to this free module.

Thus if this free module is of rank  $n$  over a ring  $R$ , then this function returns  $R^n$ , as an ambient free module.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).span([[1,1]]).nonembedded_free_module()
Ambient free module of rank 1 over the principal ideal domain Integer Ring
```

**random\_element** (*prob=1.0, \*args, \*\*kws*)

Returns a random element of self.

INPUT:

– **prob** - float. Each coefficient will be set to zero with probability  $1 - \text{prob}$ . Otherwise coefficients will be chosen randomly from base ring (and may be zero).

– **\*args, \*\*kws** - passed on to **random\_element()** function of base ring.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2).span([[1,1]])
sage: M.random_element()
(-1, -1)
sage: M.random_element()
(2, 2)
sage: M.random_element()
(1, 1)
```

Passes extra positional or keyword arguments through:

```
sage: M.random_element(5,10)
(9, 9)
```

**rank()**

Return the rank of this free module.

EXAMPLES:

```
sage: FreeModule(Integers(6), 10000000).rank()
10000000
sage: FreeModule(ZZ, 2).span([[1,1], [2,2], [3,4]]).rank()
2
```

**sparse\_module()**

Return the corresponding sparse module with the same defining data.

EXAMPLES:

We first illustrate conversion with ambient spaces:

```

sage: M = FreeModule(Integers(8), 3)
sage: S = FreeModule(Integers(8), 3, sparse=True)
sage: M.sparse_module()
Ambient sparse free module of rank 3 over Ring of integers modulo 8
sage: S.dense_module()
Ambient free module of rank 3 over Ring of integers modulo 8
sage: M.sparse_module() is S
True
sage: S.dense_module() is M
True
sage: M.dense_module() is M
True
sage: S.sparse_module() is S
True

```

Next we convert a subspace:

```

sage: M = FreeModule(QQ, 3)
sage: V = M.span([ [1, 2, 3] ] ); V
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
sage: V.sparse_module()
Sparse vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]

```

#### **uses\_ambient\_inner\_product()**

Return True if the inner product on this module is the one induced by the ambient inner product.

EXAMPLES:

```

sage: M = FreeModule(ZZ, 2)
sage: W = M.submodule([[1, 2]])
sage: W.uses_ambient_inner_product()
True
sage: W.inner_product_matrix()
[1 0]
[0 1]

sage: W.gram_matrix()
[5]

```

#### **zero()**

Returns the zero vector in this free module.

EXAMPLES:

```

sage: M = FreeModule(ZZ, 2)
sage: M.zero()
(0, 0)
sage: M.span([[1, 1]]).zero()
(0, 0)
sage: M.zero_submodule().zero()
(0, 0)
sage: M.zero_submodule().zero().is_mutable()
False

```

#### **zero\_vector()**

Returns the zero vector in this free module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2)
sage: M.zero_vector()
(0, 0)
sage: M(0)
(0, 0)
sage: M.span([[1, 1]]).zero_vector()
(0, 0)
sage: M.zero_submodule().zero_vector()
(0, 0)
```

**class** sage.modules.free\_module.**FreeModule\_generic\_field**(*base\_field, dimension, degree,*  
*sparse=False*)

Bases: sage.modules.free\_module.FreeModule\_generic\_pid

Base class for all free modules over fields.

**complement**()

Return the complement of self in the `ambient_vector_space()`.

EXAMPLES:

```
sage: V = QQ^3
sage: V.complement()
Vector space of degree 3 and dimension 0 over Rational Field
Basis matrix:
[]
sage: V == V.complement().complement()
True
sage: W = V.span([[1, 0, 1]])
sage: X = W.complement(); X
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  0]
sage: X.complement() == W
True
sage: X + W == V
True
```

Even though we construct a subspace of a subspace, the orthogonal complement is still done in the ambient vector space  $\mathbb{Q}^3$ :

```
sage: V = QQ^3
sage: W = V.subspace_with_basis([[1, 0, 1], [-1, 1, 0]])
sage: X = W.subspace_with_basis([[1, 0, 1]])
sage: X.complement()
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  0]
```

All these complements are only done with respect to the inner product in the usual basis. Over finite fields, this means we can get complements which are only isomorphic to a vector space decomposition complement.

```
sage: F2 = GF(2, x)
sage: V = F2^6
sage: W = V.span([[1, 1, 0, 0, 0, 0]])
sage: W
```



```

Vector space of degree 6 and dimension 1 over Finite Field of size 2
Basis matrix:
[1 1 0 0 0 0]
sage: W.complement()
Vector space of degree 6 and dimension 5 over Finite Field of size 2
Basis matrix:
[1 1 0 0 0 0]
[0 0 1 0 0 0]
[0 0 0 1 0 0]
[0 0 0 0 1 0]
[0 0 0 0 0 1]
sage: W.intersection(W.complement())
Vector space of degree 6 and dimension 1 over Finite Field of size 2
Basis matrix:
[1 1 0 0 0 0]

```

**echelonized\_basis\_matrix()**

Return basis matrix for self in row echelon form.

**EXAMPLES:**

```

sage: V = FreeModule(QQ, 3).span_of_basis([[1,2,3],[4,5,6]])
sage: V.basis_matrix()
[1 2 3]
[4 5 6]
sage: V.echelonized_basis_matrix()
[ 1  0 -1]
[ 0  1  2]

```

**intersection (other)**

Return the intersection of self and other, which must be R-submodules of a common ambient vector space.

**EXAMPLES:**

```

sage: V = VectorSpace(QQ,3)
sage: W1 = V.submodule([V.gen(0), V.gen(0) + V.gen(1)])
sage: W2 = V.submodule([V.gen(1), V.gen(2)])
sage: W1.intersection(W2)
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[0 1 0]
sage: W2.intersection(W1)
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[0 1 0]
sage: V.intersection(W1)
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 0 0]
[0 1 0]
sage: W1.intersection(V)
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 0 0]
[0 1 0]
sage: Z = V.submodule([])
sage: W1.intersection(Z)
Vector space of degree 3 and dimension 0 over Rational Field
Basis matrix:

```

[ ]

### **is\_subspace** (*other*)

True if this vector space is a subspace of *other*.

EXAMPLES:

```
sage: V = VectorSpace(QQ, 3)
sage: W = V.subspace([V.gen(0), V.gen(0) + V.gen(1)])
sage: W2 = V.subspace([V.gen(1)])
sage: W.is_subspace(V)
True
sage: W2.is_subspace(V)
True
sage: W.is_subspace(W2)
False
sage: W2.is_subspace(W)
True
```

### **linear\_dependence** (*vectors*, *zeros*='left', *check*=True)

Returns a list of vectors giving relations of linear dependence for the input list of vectors. Can be used to check linear independence of a set of vectors.

INPUT:

- *vectors* – A list of vectors, all from the same vector space.
- *zeros* – default: 'left' - 'left' or 'right' as a general preference for where zeros are located in the returned coefficients
- *check* – default: True - if True each item in the list *vectors* is checked for membership in *self*. Set to False if you can be certain the vectors come from the vector space.

OUTPUT:

Returns a list of vectors. The scalar entries of each vector provide the coefficients for a linear combination of the input vectors that will equal the zero vector in *self*. Furthermore, the returned list is linearly independent in the vector space over the same base field with degree equal to the length of the list *vectors*.

The linear independence of *vectors* is equivalent to the returned list being empty, so this provides a test - see the examples below.

The returned vectors are always independent, and with *zeros* set to 'left' they have 1's in their first non-zero entries and a qualitative disposition to having zeros in the low-index entries. With *zeros* set to 'right' the situation is reversed with a qualitative disposition for zeros in the high-index entries.

If the vectors in *vectors* are made the rows of a matrix *V* and the returned vectors are made the rows of a matrix *R*, then the matrix product *RV* is a zero matrix of the proper size. And *R* is a matrix of full rank. This routine uses kernels of matrices to compute these relations of linear dependence, but handles all the conversions between sets of vectors and matrices. If speed is important, consider working with the appropriate matrices and kernels instead.

EXAMPLES:

We begin with two linearly independent vectors, and add three non-trivial linear combinations to the set. We illustrate both types of output and check a selected relation of linear dependence.

```
sage: v1 = vector(QQ, [2, 1, -4, 3])
sage: v2 = vector(QQ, [1, 5, 2, -2])
sage: V = QQ^4
sage: V.linear_dependence([v1, v2])
[
```

```

]

sage: v3 = v1 + v2
sage: v4 = 3*v1 - 4*v2
sage: v5 = -v1 + 2*v2
sage: L = [v1, v2, v3, v4, v5]

sage: relations = V.linear_dependence(L, zeros='left')
sage: relations
[
(1, 0, 0, -1, -2),
(0, 1, 0, -1/2, -3/2),
(0, 0, 1, -3/2, -7/2)
]
sage: v2 + (-1/2)*v4 + (-3/2)*v5
(0, 0, 0, 0)

sage: relations = V.linear_dependence(L, zeros='right')
sage: relations
[
(-1, -1, 1, 0, 0),
(-3, 4, 0, 1, 0),
(1, -2, 0, 0, 1)
]
sage: z = sum([relations[2][i]*L[i] for i in range(len(L))])
sage: z == zero_vector(QQ, 4)
True

```

A linearly independent set returns an empty list, a result that can be tested.

```

sage: v1 = vector(QQ, [0,1,-3])
sage: v2 = vector(QQ, [4,1,0])
sage: V = QQ^3
sage: relations = V.linear_dependence([v1, v2]); relations
[

]
sage: relations == []
True

```

Exact results result from exact fields. We start with three linearly independent vectors and add in two linear combinations to make a linearly dependent set of five vectors.

```

sage: F = FiniteField(17)
sage: v1 = vector(F, [1, 2, 3, 4, 5])
sage: v2 = vector(F, [2, 4, 8, 16, 15])
sage: v3 = vector(F, [1, 0, 0, 0, 1])
sage: (F^5).linear_dependence([v1, v2, v3]) == []
True
sage: L = [v1, v2, v3, 2*v1+v2, 3*v2+6*v3]
sage: (F^5).linear_dependence(L)
[
(1, 0, 16, 8, 3),
(0, 1, 2, 0, 11)
]
sage: v1 + 16*v3 + 8*(2*v1+v2) + 3*(3*v2+6*v3)
(0, 0, 0, 0, 0)
sage: v2 + 2*v3 + 11*(3*v2+6*v3)

```

```
(0, 0, 0, 0, 0)
sage: (F^5).linear_dependence(L, zeros='right')
[
(15, 16, 0, 1, 0),
(0, 14, 11, 0, 1)
]
```

**TESTS:**

With `check=True` (the default) a mismatch between vectors and the vector space is caught.

```
sage: v1 = vector(RR, [1,2,3])
sage: v2 = vector(RR, [1,2,3,4])
sage: (RR^3).linear_dependence([v1,v2], check=True)
Traceback (most recent call last):
...
ValueError: vector (1.000000000000000, 2.000000000000000, 3.000000000000000, 4.000000000000000)
```

The `zeros` keyword is checked.

```
sage: (QQ^3).linear_dependence([vector(QQ,[1,2,3])], zeros='bogus')
Traceback (most recent call last):
...
ValueError: 'zeros' keyword must be 'left' or 'right', not 'bogus'
```

An empty input set is linearly independent, vacuously.

```
sage: (QQ^3).linear_dependence([]) == []
True
```

**quotient** (*sub*, *check=True*)

Return the quotient of self by the given subspace *sub*.

**INPUT:**

- *sub* - a submodule of self, or something that can be turned into one via `self.submodule(sub)`.
- *check* - (default: `True`) whether or not to check that *sub* is a submodule.

**EXAMPLES:**

```
sage: A = QQ^3; V = A.span([[1,2,3], [4,5,6]])
sage: Q = V.quotient( [V.0 + V.1] ); Q
Vector space quotient V/W of dimension 1 over Rational Field where
V: Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
W: Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 1 1]
sage: Q(V.0 + V.1)
(0)
```

We illustrate the the base rings must be the same:

```
sage: (QQ^2)/(ZZ^2)
Traceback (most recent call last):
...
ValueError: base rings must be the same
```

**quotient\_abstract** (*sub*, *check=True*)

Returns an ambient free module isomorphic to the quotient space of self modulo sub, together with maps from self to the quotient, and a lifting map in the other direction.

Use `self.quotient(sub)` to obtain the quotient module as an object equipped with natural maps in both directions, and a canonical coercion.

INPUT:

- *sub* - a submodule of self, or something that can be turned into one via `self.submodule(sub)`.
- *check* - (default: True) whether or not to check that sub is a submodule.

OUTPUT:

- *U* - the quotient as an abstract *ambient* free module
- *pi* - projection map to the quotient
- *lift* - lifting map back from quotient

EXAMPLES:

```
sage: V = GF(19)^3
sage: W = V.span_of_basis([ [1,2,3], [1,0,1] ])
sage: U, pi, lift = V.quotient_abstract(W)
sage: pi(V.2)
(18)
sage: pi(V.0)
(1)
sage: pi(V.0 + V.2)
(0)
```

Another example involving a quotient of one subspace by another.

```
sage: A = matrix(QQ, 4, 4, [0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0])
sage: V = (A^3).kernel()
sage: W = A.kernel()
sage: U, pi, lift = V.quotient_abstract(W)
sage: [pi(v) == 0 for v in W.gens()]
[True]
sage: [pi(lift(b)) == b for b in U.basis()]
[True, True]
```

**scale** (*other*)

Return the product of self by the number other, which is the module spanned by other times each basis vector. Since self is a vector space this product equals self if other is nonzero, and is the zero vector space if other is 0.

EXAMPLES:

```
sage: V = QQ^4
sage: V.scale(5)
Vector space of dimension 4 over Rational Field
sage: V.scale(0)
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

sage: W = V.span([[1,1,1,1]])
sage: W.scale(2)
Vector space of degree 4 and dimension 1 over Rational Field
Basis matrix:
```

```
[1 1 1 1]
sage: W.scale(0)
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

sage: V = QQ^4; V
Vector space of dimension 4 over Rational Field
sage: V.scale(3)
Vector space of dimension 4 over Rational Field
sage: V.scale(0)
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]
```

**span** (*gens*, *base\_ring=None*, *check=True*, *already\_echelonized=False*)

Return the K-span of the given list of gens, where K is the base field of self or the user-specified *base\_ring*. Note that this span is a subspace of the ambient vector space, but need not be a subspace of self.

INPUT:

- *gens* - list of vectors
- *check* - bool (default: True): whether or not to coerce entries of gens into base field
- *already\_echelonized* - bool (default: False): set this if you know the gens are already in echelon form

EXAMPLES:

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
sage: W.span([[1,1,1]])
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 1 1]
```

TESTS:

```
sage: V = FreeModule(RDF, 3)
sage: W = V.submodule([V.gen(0)])
sage: W.span([V.gen(1)], base_ring=GF(7))
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[0 1 0]
sage: v = V((1, pi, log(2))); v
(1.0, 3.141592653589793, 0.6931471805599453)
sage: W.span([v], base_ring=GF(7))
Traceback (most recent call last):
...
ValueError: Argument gens (= [(1.0, 3.141592653589793, 0.6931471805599453)]) is not compatible
sage: W = V.submodule([v])
sage: W.span([V.gen(2)], base_ring=GF(7))
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[0 0 1]
```

**span\_of\_basis** (*basis*, *base\_ring=None*, *check=True*, *already\_echelonized=False*)

Return the free K-module with the given basis, where K is the base field of self or user specified base\_ring.

Note that this span is a subspace of the ambient vector space, but need not be a subspace of self.

INPUT:

- *basis* - list of vectors
- *check* - bool (default: True): whether or not to coerce entries of gens into base field
- *already\_echelonized* - bool (default: False): set this if you know the gens are already in echelon form

EXAMPLES:

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
sage: W.span_of_basis([[2,2,2], [3,3,0]])
Vector space of degree 3 and dimension 2 over Finite Field of size 7
User basis matrix:
[2 2 2]
[3 3 0]
```

The basis vectors must be linearly independent or a `ValueError` exception is raised:

```
sage: W.span_of_basis([[2,2,2], [3,3,3]])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.
```

**subspace** (*gens*, *check=True*, *already\_echelonized=False*)

Return the subspace of self spanned by the elements of gens.

INPUT:

- *gens* - list of vectors
- *check* - bool (default: True) verify that gens are all in self.
- *already\_echelonized* - bool (default: False) set to True if you know the gens are in Echelon form.

EXAMPLES:

First we create a 1-dimensional vector subspace of an ambient 3-dimensional space over the finite field of order 7:

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
```

Next we create an invalid subspace, but it's allowed since *check=False*. This is just equivalent to computing the span of the element:

```
sage: W.subspace([[1,1,0]], check=False)
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 1 0]
```

With `check=True` (the default) the mistake is correctly detected and reported with an `ArithmeticError` exception:

```
sage: W.subspace([[1,1,0]], check=True)
Traceback (most recent call last):
...
ArithmeticError: Argument gens (= [[1, 1, 0]]) does not generate a submodule of self.
```

**subspace\_with\_basis** (*gens, check=True, already\_echelonized=False*)

Same as `self.submodule_with_basis(...)`.

EXAMPLES:

We create a subspace with a user-defined basis.

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace_with_basis([[2,2,2], [1,2,3]]); W
Vector space of degree 3 and dimension 2 over Finite Field of size 7
User basis matrix:
[2 2 2]
[1 2 3]
```

We then create a subspace of the subspace with user-defined basis.

```
sage: W1 = W.subspace_with_basis([[3,4,5]]); W1
Vector space of degree 3 and dimension 1 over Finite Field of size 7
User basis matrix:
[3 4 5]
```

Notice how the basis for the same subspace is different if we merely use the `subspace` command.

```
sage: W2 = W.subspace([[3,4,5]]); W2
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 6 4]
```

Nonetheless the two subspaces are equal (as mathematical objects):

```
sage: W1 == W2
True
```

**subspaces** (*dim*)

Iterate over all subspaces of dimension `dim`.

INPUT:

- `dim` - int, dimension of subspaces to be generated

EXAMPLE:

```
sage: V = VectorSpace(GF(3), 5)
sage: len(list(V.subspaces(0)))
1
sage: len(list(V.subspaces(1)))
121
sage: len(list(V.subspaces(2)))
1210
sage: len(list(V.subspaces(3)))
1210
sage: len(list(V.subspaces(4)))
121
sage: len(list(V.subspaces(5)))
1
```



```

sage: V = VectorSpace(GF(3), 5)
sage: V = V.subspace([V([1,1,0,0,0]),V([0,0,1,1,0])])
sage: list(V.subspaces(1))
[Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[1 1 0 0 0],
  Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[1 1 1 1 0],
  Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[1 1 2 2 0],
  Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[0 0 1 1 0]]

```

#### **vector\_space**(*base\_field=None*)

Return the vector space associated to self. Since self is a vector space this function simply returns self, unless the base field is different.

##### EXAMPLES:

```

sage: V = span([[1,2,3]],QQ); V
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
sage: V.vector_space()
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]

```

#### **zero\_submodule**()

Return the zero submodule of self.

##### EXAMPLES:

```

sage: (QQ^4).zero_submodule()
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

```

#### **zero\_subspace**()

Return the zero subspace of self.

##### EXAMPLES:

```

sage: (QQ^4).zero_subspace()
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

```

```

class sage.modules.free_module.FreeModule_generic_pid(base_ring, rank, degree,
                                                         sparse=False, coordi-
                                                         nate_ring=None)

```

Bases: `sage.modules.free_module.FreeModule_generic`

Base class for all free modules over a PID.

#### **denominator**()

The denominator of the basis matrix of self (i.e. the LCM of the coordinate entries with respect to the basis of the ambient space).

EXAMPLES:

```
sage: V = QQ^3
sage: L = V.span([[1, 1/2, 1/3], [-1/5, 2/3, 3]], ZZ)
sage: L
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1/5 19/6 37/3]
[  0 23/6 46/3]
sage: L.denominator()
30
```

**index\_in**(*other*)

Return the lattice index [other:self] of self in other, as an element of the base field. When self is contained in other, the lattice index is the usual index. If the index is infinite, then this function returns infinity.

EXAMPLES:

```
sage: L1 = span([[1, 2]], ZZ)
sage: L2 = span([[3, 6]], ZZ)
sage: L2.index_in(L1)
3
```

Note that the free modules being compared need not be integral.

```
sage: L1 = span(['1/2', '1/3'], [4, 5], ZZ)
sage: L2 = span([1, 2], [3, 4], ZZ)
sage: L2.index_in(L1)
12/7
sage: L1.index_in(L2)
7/12
sage: L1.discriminant() / L2.discriminant()
49/144
```

The index of a lattice of infinite index is infinite.

```
sage: L1 = FreeModule(ZZ, 2)
sage: L2 = span([1, 2], ZZ)
sage: L2.index_in(L1)
+Infinity
```

**index\_in\_saturation**()

Return the index of this module in its saturation, i.e., its intersection with  $R^n$ .

EXAMPLES:

```
sage: W = span([2, 4, 6], ZZ)
sage: W.index_in_saturation()
2
sage: W = span([1/2, 1/3], ZZ)
sage: W.index_in_saturation()
1/6
```

**intersection**(*other*)

Return the intersection of self and other.

EXAMPLES:

We intersect two submodules one of which is clearly contained in the other.

```

sage: A = ZZ^2
sage: M1 = A.span([[1,1]])
sage: M2 = A.span([[3,3]])
sage: M1.intersection(M2)
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[3 3]
sage: M1.intersection(M2) is M2
True

```

We intersect two submodules of  $\mathbf{Z}^3$  of rank 2, whose intersection has rank 1.

```

sage: A = ZZ^3
sage: M1 = A.span([[1,1,1], [1,2,3]])
sage: M2 = A.span([[2,2,2], [1,0,0]])
sage: M1.intersection(M2)
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[2 2 2]

```

We compute an intersection of two  $\mathbf{Z}$ -modules that are not submodules of  $\mathbf{Z}^2$ .

```

sage: A = ZZ^2
sage: M1 = A.span([[1,2]]).scale(1/6)
sage: M2 = A.span([[1,2]]).scale(1/15)
sage: M1.intersection(M2)
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[1/3 2/3]

```

We intersect a  $\mathbf{Z}$ -module with a  $\mathbf{Q}$ -vector space.

```

sage: A = ZZ^3
sage: L = ZZ^3
sage: V = QQ^3
sage: W = L.span([[1/2,0,1/2]])
sage: K = V.span([[1,0,1], [0,0,1]])
sage: W.intersection(K)
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1/2 0 1/2]
sage: K.intersection(W)
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1/2 0 1/2]

```

We intersect two modules over the ring of integers of a number field:

```

sage: L.<w> = NumberField(x^2 - x + 2)
sage: OL = L.ring_of_integers()
sage: V = L**3; W1 = V.span([[0,w/5,0], [1,0,-1/17]], OL); W2 = V.span([[0,(1-w)/5,0]], OL)
sage: W1.intersection(W2)
Free module of degree 3 and rank 1 over Maximal Order in Number Field in w with defining pol
Echelon basis matrix:
[ 0 2/5 0]

```

**quotient** (*sub*, *check=True*)

Return the quotient of self by the given submodule *sub*.

INPUT:

- sub - a submodule of self, or something that can be turned into one via self.submodule(sub).
- check - (default: True) whether or not to check that sub is a submodule.

EXAMPLES:

```
sage: A = ZZ^3; V = A.span([[1,2,3], [4,5,6]])
sage: Q = V.quotient( [V.0 + V.1] ); Q
Finitely generated module V/W over Integer Ring with invariants (0)
```

**saturation()**

Return the saturated submodule of  $R^n$  that spans the same vector space as self.

EXAMPLES:

We create a 1-dimensional lattice that is obviously not saturated and saturate it.

```
sage: L = span([[9,9,6]], ZZ); L
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[9 9 6]
sage: L.saturation()
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[3 3 2]
```

We create a lattice spanned by two vectors, and saturate. Computation of discriminants shows that the index of lattice in its saturation is 3, which is a prime of congruence between the two generating vectors.

```
sage: L = span([[1,2,3], [4,5,6]], ZZ)
sage: L.saturation()
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: L.discriminant()
54
sage: L.saturation().discriminant()
6
```

Notice that the saturation of a non-integral lattice  $L$  is defined, but the result is integral hence does not contain  $L$ :

```
sage: L = span(['1/2', 1, 3], ZZ)
sage: L.saturation()
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1 2 6]
```

**scale (other)**

Return the product of this module by the number other, which is the module spanned by other times each basis vector.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.scale(2)
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[2 0 0]
[0 2 0]
[0 0 2]
```

```

sage: a = QQ('1/3')
sage: M.scale(a)
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/3  0   0]
[  0 1/3  0]
[  0  0 1/3]

```

**span** (*gens*, *base\_ring=None*, *check=True*, *already\_echelonized=False*)

Return the R-span of the given list of gens, where R = base\_ring. The default R is the base ring of self. Note that this span need not be a submodule of self, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R.

EXAMPLES:

```

sage: V = FreeModule(ZZ, 3)
sage: W = V.submodule([V.gen(0)])
sage: W.span([V.gen(1)])
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[0 1 0]
sage: W.submodule([V.gen(1)])
Traceback (most recent call last):
...
ArithmeticError: Argument gens (= [(0, 1, 0)]) does not generate a submodule of self.
sage: V.span([(1, 0, 0), (1/5, 4, 0), (6, 3/4, 0)])
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1/5  0   0]
[  0 1/4  0]

```

It also works with other things than integers:

```

sage: R.<x>=QQ[]
sage: L=R^1
sage: a=L.span([(1/x)])
sage: a
Free module of degree 1 and rank 1 over Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[1/x]
sage: b=L.span([(1/x)])
sage: a(b.gens()[0])
(1/x)
sage: L2 = R^2
sage: L2.span([(x^2+x)/(x^2-3*x+2), 1/5], [(x^2+2*x)/(x^2-4*x+3), x])
Free module of degree 2 and rank 2 over Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[x/(x^3 - 6*x^2 + 11*x - 6)  2/15*x^2 - 17/75*x - 1/75]
[                                0 x^3 - 11/5*x^2 - 3*x + 4/5]

```

Note that the base\_ring can make a huge difference. We repeat the previous example over the fraction field of R and get a simpler vector space.

```

sage: L2.span([(x^2+x)/(x^2-3*x+2), 1/5], [(x^2+2*x)/(x^2-4*x+3), x], base_ring=R.fraction_field())
Vector space of degree 2 and dimension 2 over Fraction Field of Univariate Polynomial Ring in x over Rational Field
Basis matrix:
[1 0]
[0 1]

```

**span\_of\_basis** (*basis*, *base\_ring=None*, *check=True*, *already\_echelonized=False*)

Return the free R-module with the given basis, where R is the base ring of self or user specified *base\_ring*.

Note that this R-module need not be a submodule of self, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: W = M.span_of_basis([M([1, 2, 3])])
```

Next we create two free  $\mathbf{Z}$ -modules, neither of which is a submodule of  $W$ .

```
sage: W.span_of_basis([M([2, 4, 0])])
Free module of degree 3 and rank 1 over Integer Ring
User basis matrix:
[2 4 0]
```

The following module isn't in the ambient module  $\mathbf{Z}^3$  but is contained in the ambient vector space  $\mathbf{Q}^3$ :

```
sage: V = M.ambient_vector_space()
sage: W.span_of_basis([ V([1/5, 2/5, 0]), V([1/7, 1/7, 0]) ])
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1/5 2/5 0]
[1/7 1/7 0]
```

Of course the input basis vectors must be linearly independent:

```
sage: W.span_of_basis([ [1, 2, 0], [2, 4, 0] ])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.
```

**submodule** (*gens*, *check=True*, *already\_echelonized=False*)

Create the R-submodule of the ambient vector space with given generators, where R is the base ring of self.

INPUT:

- *gens* - a list of free module elements or a free module
- *check* - (default: True) whether or not to verify that the *gens* are in self.

OUTPUT:

- `FreeModule` - the submodule spanned by the vectors in the list *gens*. The basis for the subspace is always put in reduced row echelon form.

EXAMPLES:

We create a submodule of  $\mathbf{Z}^3$ :

```
sage: M = FreeModule(ZZ, 3)
sage: B = M.basis()
sage: W = M.submodule([B[0]+B[1], 2*B[1]-B[2]])
sage: W
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  1  0]
[ 0  2 -1]
```

We create a submodule of a submodule.

```
sage: W.submodule([3*B[0] + 3*B[1]])
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[3 3 0]
```

We try to create a submodule that isn't really a submodule, which results in an `ArithmeticError` exception:

```
sage: W.submodule([B[0] - B[1]])
Traceback (most recent call last):
...
ArithmeticError: Argument gens (= [(1, -1, 0)]) does not generate a submodule of self.
```

Next we create a submodule of a free module over the principal ideal domain  $\mathbb{Q}[x]$ , which uses the general Hermite normal form functionality:

```
sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: M = FreeModule(R, 3)
sage: B = M.basis()
sage: W = M.submodule([x*B[0], 2*B[1]-x*B[2]]); W
Free module of degree 3 and rank 2 over Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[ x  0  0]
[ 0  2 -x]
sage: W.ambient_module()
Ambient free module of rank 3 over the principal ideal domain Univariate Polynomial Ring in
```

**submodule\_with\_basis** (*basis*, *check=True*, *already\_echelonized=False*)

Create the  $R$ -submodule of the ambient vector space with given basis, where  $R$  is the base ring of self.

INPUT:

- **basis** – a list of linearly independent vectors
- **check** – whether or not to verify that each gen is in the ambient vector space

OUTPUT:

- `FreeModule` – the  $R$ -submodule with given basis

EXAMPLES:

First we create a submodule of  $\mathbb{Z}^3$ :

```
sage: M = FreeModule(ZZ, 3)
sage: B = M.basis()
sage: N = M.submodule_with_basis([B[0]+B[1], 2*B[1]-B[2]])
sage: N
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  1  0]
[ 0  2 -1]
```

A list of vectors in the ambient vector space may fail to generate a submodule.

```
sage: V = M.ambient_vector_space()
sage: X = M.submodule_with_basis([V(B[0]+B[1])/2, V(B[1]-B[2])/2])
Traceback (most recent call last):
...
ArithmeticError: The given basis does not generate a submodule of self.
```

However, we can still determine the R-span of vectors in the ambient space, or over-ride the submodule check by setting check to False.

```
sage: X = V.span([ V(B[0]+B[1])/2, V(B[1]-B[2])/2 ], ZZ)
sage: X
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1/2  0  1/2]
[  0  1/2 -1/2]
sage: Y = M.submodule([ V(B[0]+B[1])/2, V(B[1]-B[2])/2 ], check=False)
sage: X == Y
True
```

Next we try to create a submodule of a free module over the principal ideal domain  $\mathbb{Q}[x]$ , using our general Hermite normal form implementation:

```
sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: M = FreeModule(R, 3)
sage: B = M.basis()
sage: W = M.submodule_with_basis([x*B[0], 2*B[0]-x*B[2]]); W
Free module of degree 3 and rank 2 over Univariate Polynomial Ring in x over Rational Field
User basis matrix:
[ x  0  0]
[ 2  0 -x]
```

**vector\_space\_span** (*gens*, *check=True*)

Create the vector subspace of the ambient vector space with given generators.

INPUT:

- gens - a list of vector in self
- check - whether or not to verify that each gen is in the ambient vector space

OUTPUT: a vector subspace

EXAMPLES:

We create a 2-dimensional subspace of  $\mathbb{Q}^3$ .

```
sage: V = VectorSpace(QQ, 3)
sage: B = V.basis()
sage: W = V.vector_space_span([B[0]+B[1], 2*B[1]-B[2]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0  1/2]
[  0  1 -1/2]
```

We create a subspace of a vector space over  $\mathbb{Q}(i)$ .

```
sage: R.<x> = QQ[]
sage: K = NumberField(x^2 + 1, 'a'); a = K.gen()
sage: V = VectorSpace(K, 3)
sage: V.vector_space_span([2*V.gen(0) + 3*V.gen(2)])
Vector space of degree 3 and dimension 1 over Number Field in a with defining polynomial x^2 + 1
Basis matrix:
[ 1  0 3/2]
```

We use the `vector_space_span` command to create a vector subspace of the ambient vector space of a submodule of  $\mathbb{Z}^3$ .



```

sage: M = FreeModule(ZZ, 3)
sage: W = M.submodule([M([1, 2, 3])])
sage: W.vector_space_span([M([2, 3, 4])])
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[ 1 3/2  2]

```

### **vector\_space\_span\_of\_basis** (*basis*, *check=True*)

Create the vector subspace of the ambient vector space with given basis.

INPUT:

- **basis** – a list of linearly independent vectors
- **check** – whether or not to verify that each gen is in the ambient vector space

OUTPUT: a vector subspace with user-specified basis

EXAMPLES:

```

sage: V = VectorSpace(QQ, 3)
sage: B = V.basis()
sage: W = V.vector_space_span_of_basis([B[0]+B[1], 2*B[1]-B[2]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  1  0]
[ 0  2 -1]

```

### **zero\_submodule** ()

Return the zero submodule of this module.

EXAMPLES:

```

sage: V = FreeModule(ZZ, 2)
sage: V.zero_submodule()
Free module of degree 2 and rank 0 over Integer Ring
Echelon basis matrix:
[]

```

```

class sage.modules.free_module.FreeModule_submodule_field(ambient, gens,
                                                            check=True, al-
                                                            ready_echelonized=False)

```

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_field`

An embedded vector subspace with echelonized basis.

EXAMPLES:

Since this is an embedded vector subspace with echelonized basis, the `echelon_coordinates()` and `user_coordinates()` agree:

```

sage: V = QQ^3
sage: W = V.span([1, 2, 3], [4, 5, 6])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]

```

```

sage: v = V([1, 5, 9])
sage: W.echelon_coordinates(v)

```

```
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.basis_matrix()
(1, 5, 9)
sage: v = V([1, 5, 9])
sage: W.coordinates(v)
[1, 5]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

**coordinate\_vector** (*v*, *check=True*)

Write *v* in terms of the user basis for self.

INPUT:

- *v* – vector

- *check* – bool (default: True); if True, also verify that *v* is really in self.

OUTPUT: list

Returns a list *c* such that if *B* is the basis for self, then

$$\sum c_i B_i = v.$$

If *v* is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.span([[1, 2, 3], [4, 5, 6]]); W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: v = V([1, 5, 9])
sage: W.coordinate_vector(v)
(1, 5)
sage: W.coordinates(v)
[1, 5]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)

sage: V = VectorSpace(QQ, 5, sparse=True)
sage: W = V.subspace([[0, 1, 2, 0, 0], [0, -1, 0, 0, -1/2]])
sage: W.coordinate_vector([0, 0, 2, 0, -1/2])
(0, 2)
```

**echelon\_coordinates** (*v*, *check=True*)

Write *v* in terms of the echelonized basis of self.

INPUT:

- *v* - vector

- *check* - bool (default: True); if True, also verify that *v* is really in self.

OUTPUT: list

Returns a list *c* such that if *B* is the basis for self, then

$$\sum c_i B_i = v.$$

If  $v$  is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.span([[1,2,3],[4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]

sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

**has\_user\_basis()**

Return True if the basis of this free module is specified by the user, as opposed to being the default echelon form.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.subspace([[2,'1/2', 1]])
sage: W.has_user_basis()
False
sage: W = V.subspace_with_basis([[2,'1/2',1]])
sage: W.has_user_basis()
True
```

**class** sage.modules.free\_module.**FreeModule\_submodule\_pid**(*ambient, gens, check=True, already\_echelonized=False*)

Bases: sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid

An  $R$ -submodule of  $K^n$  where  $K$  is the fraction field of a principal ideal domain  $R$ .

EXAMPLES:

```
sage: M = ZZ^3
sage: W = M.span_of_basis([[1,2,3],[4,5,19]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  2  3]
[ 4  5 19]
```

Generic tests, including saving and loading submodules and elements:

```
sage: TestSuite(W).run()
sage: v = W.0 + W.1
sage: TestSuite(v).run()
```

**coordinate\_vector**( $v$ , *check=True*)

Write  $v$  in terms of the user basis for self.

INPUT:

- $v$  – vector
- **check** – bool (default: True); if True, also verify that  $v$  is really in self.

OUTPUT: list

Returns a list  $c$  such that if  $B$  is the basis for self, then

$$\sum c_i B_i = v.$$

If  $v$  is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = ZZ^3
sage: W = V.span_of_basis([[1,2,3],[4,5,6]])
sage: W.coordinate_vector([1,5,9])
(5, -1)
```

**has\_user\_basis()**

Return True if the basis of this free module is specified by the user, as opposed to being the default echelon form.

EXAMPLES:

```
sage: A = ZZ^3; A
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: A.has_user_basis()
False
sage: W = A.span_of_basis([[2,'1/2',1]])
sage: W.has_user_basis()
True
sage: W = A.span([[2,'1/2',1]])
sage: W.has_user_basis()
False
```

```
class sage.modules.free_module.FreeModule_submodule_with_basis_field(ambient,
                                                                    basis,
                                                                    check=True,
                                                                    echelo-
                                                                    nize=False,
                                                                    echelo-
                                                                    nized_basis=None,
                                                                    al-
                                                                    ready_echelonized=False)

Bases: sage.modules.free_module.FreeModule_generic_field,
sage.modules.free_module.FreeModule_submodule_with_basis_pid
```

An embedded vector subspace with a distinguished user basis.

EXAMPLES:

```
sage: M = QQ^3; W = M.submodule_with_basis([[1,2,3],[4,5,19]]); W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  2  3]
[ 4  5 19]
```

Since this is an embedded vector subspace with a distinguished user basis possibly different than the echelonized basis, the `echelon_coordinates()` and `user coordinates()` do not agree:

```
sage: V = QQ^3
sage: W = V.submodule_with_basis([[1,2,3],[4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
```

```
[1 2 3]
[4 5 6]
```

```
sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.echelonized_basis_matrix()
(1, 5, 9)

sage: v = V([1,5,9])
sage: W.coordinates(v)
[5, -1]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

Generic tests, including saving and loading submodules and elements:

```
sage: TestSuite(W).run()

sage: K.<x> = FractionField(PolynomialRing(QQ, 'x'))
sage: M = K^3; W = M.span_of_basis([[1,1,x]])
sage: TestSuite(W).run()
```

**is\_ambient()**

Return False since this is not an ambient module.

EXAMPLES:

```
sage: V = QQ^3
sage: V.is_ambient()
True
sage: W = V.span_of_basis([[1,2,3],[4,5,6]])
sage: W.is_ambient()
False
```

```
class sage.modules.free_module.FreeModule_submodule_with_basis_pid(ambient,
                                                                    basis,
                                                                    check=True,
                                                                    echelo-
                                                                    nize=False,
                                                                    echelo-
                                                                    nized_basis=None,
                                                                    al-
                                                                    ready_echelonized=False)
```

Bases: `sage.modules.free_module.FreeModule_generic_pid`

Construct a submodule of a free module over PID with a distinguished basis.

INPUT:

- **ambient** – ambient free module over a principal ideal domain  $R$ , i.e.  $R^n$ ;
- **basis** – list of elements of  $K^n$ , where  $K$  is the fraction field of  $R$ . These elements must be linearly independent and will be used as the default basis of the constructed submodule;
- **check** – (default: True) if False, correctness of the input will not be checked and type conversion may be omitted, use with care;
- **echelonize** – (default: False) if True, **basis** will be echelonized and the result will be used as the default basis of the constructed submodule;

- “echelonized\_basis” – (default: None) if not None, must be the echelonized basis spanning the same submodule as basis;
- already\_echelonized – (default: False) if True, basis must be already given in the echelonized form.

OUTPUT:

- $R$ -submodule of  $K^n$  with the user-specified basis.

EXAMPLES:

```
sage: M = ZZ^3
sage: W = M.span_of_basis([[1, 2, 3], [4, 5, 6]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1 2 3]
[4 5 6]
```

Now we create a submodule of the ambient vector space, rather than  $M$  itself:

```
sage: W = M.span_of_basis([[1, 2, 3/2], [4, 5, 6]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  2 3/2]
[ 4  5  6]
```

**ambient\_module()**

Return the ambient module related to the  $R$ -module self, which was used when creating this module, and is of the form  $R^n$ . Note that self need not be contained in the ambient module, though self will be contained in the ambient vector space.

EXAMPLES:

```
sage: A = ZZ^3
sage: M = A.span_of_basis([[1, 2, '3/7'], [4, 5, 6]])
sage: M
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  2 3/7]
[ 4  5  6]
sage: M.ambient_module()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: M.is_submodule(M.ambient_module())
False
```

**ambient\_vector\_space()**

Return the ambient vector space in which this free module is embedded.

EXAMPLES:

```
sage: M = ZZ^3; M.ambient_vector_space()
Vector space of dimension 3 over Rational Field

sage: N = M.span_of_basis([[1, 2, '1/5']])
sage: N
Free module of degree 3 and rank 1 over Integer Ring
User basis matrix:
[ 1  2 1/5]
sage: M.ambient_vector_space()
Vector space of dimension 3 over Rational Field
sage: M.ambient_vector_space() is N.ambient_vector_space()
```

True

If an inner product on the module is specified, then this is preserved on the ambient vector space.

```
sage: M = FreeModule(ZZ, 4, inner_product_matrix=1)
sage: V = M.ambient_vector_space()
sage: V
Ambient quadratic space of dimension 4 over Rational Field
Inner product matrix:
[1 0 0 0]
[0 1 0 0]
[0 0 1 0]
[0 0 0 1]
sage: N = M.submodule([[1, -1, 0, 0], [0, 1, -1, 0], [0, 0, 1, -1]])
sage: N.gram_matrix()
[2 1 1]
[1 2 1]
[1 1 2]
sage: V == N.ambient_vector_space()
True
```

### **basis()**

Return the user basis for this free module.

EXAMPLES:

```
sage: V = ZZ^3
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
sage: M = V.span_of_basis([[1/8, 2, 1]])
sage: M.basis()
[
(1/8, 2, 1)
]
```

### **change\_ring(*R*)**

Return the free module over  $R$  obtained by coercing each element of the basis of `self` into a vector over the fraction field of  $R$ , then taking the resulting  $R$ -module.

INPUT:

- $R$  - a principal ideal domain

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.subspace([[2, 1/2, 1]])
sage: W.change_ring(GF(7))
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 2 4]

sage: M = (ZZ^2) * (1/2)
sage: N = M.change_ring(QQ)
sage: N
Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
```

```
[1 0]
[0 1]
sage: N = M.change_ring(QQ['x'])
sage: N
Free module of degree 2 and rank 2 over Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[1/2  0]
[ 0 1/2]
sage: N.coordinate_ring()
Univariate Polynomial Ring in x over Rational Field
```

The ring must be a principal ideal domain:

```
sage: M.change_ring(ZZ['x'])
Traceback (most recent call last):
...
TypeError: the new ring Univariate Polynomial Ring in x over Integer Ring should be a principal ideal domain
```

#### **construction()**

Returns the functorial construction of self, namely, the subspace of the ambient module spanned by the given basis.

EXAMPLE:

```
sage: M = ZZ^3
sage: W = M.span_of_basis([[1,2,3],[4,5,6]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1 2 3]
[4 5 6]
sage: c, V = W.construction()
sage: c(V) == W
True
```

#### **coordinate\_vector**(*v*, *check=True*)

Write *v* in terms of the user basis for self.

INPUT:

- *v* – vector
- *check* – bool (default: True); if True, also verify that *v* is really in self.

OUTPUT: list

Returns a vector *c* such that if *B* is the basis for self, then

$$\sum c_i B_i = v.$$

If *v* is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = ZZ^3
sage: M = V.span_of_basis([[1/8, 2, 1]])
sage: M.coordinate_vector([1, 16, 8])
(8)
```

#### **echelon\_coordinate\_vector**(*v*, *check=True*)

Write *v* in terms of the echelonized basis for self.

INPUT:



- $v$  - vector
- `check` - bool (default: `True`); if `True`, also verify that  $v$  is really in self.

Returns a list  $c$  such that if  $B$  is the echelonized basis for self, then

$$\sum c_i B_i = v.$$

If  $v$  is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = ZZ^3
sage: M = V.span_of_basis([[1/2, 3, 1], [0, 1/6, 0]])
sage: B = M.echelonized_basis(); B
[
(1/2, 0, 1),
(0, 1/6, 0)
]
sage: M.echelon_coordinate_vector([1/2, 3, 1])
(1, 18)
```

**echelon\_coordinates** ( $v$ , `check=True`)

Write  $v$  in terms of the echelonized basis for self.

INPUT:

- $v$  - vector
- `check` - bool (default: `True`); if `True`, also verify that  $v$  is really in self.

OUTPUT: list

Returns a list  $c$  such that if  $B$  is the basis for self, then

$$\sum c_i B_i = v.$$

If  $v$  is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: A = ZZ^3
sage: M = A.span_of_basis([[1, 2, 3/7], [4, 5, 6]])
sage: M.coordinates([8, 10, 12])
[0, 2]
sage: M.echelon_coordinates([8, 10, 12])
[8, -2]
sage: B = M.echelonized_basis(); B
[
(1, 2, 3/7),
(0, 3, -30/7)
]
sage: 8*B[0] - 2*B[1]
(8, 10, 12)
```

We do an example with a sparse vector space:

```
sage: V = VectorSpace(QQ, 5, sparse=True)
sage: W = V.subspace_with_basis([[0, 1, 2, 0, 0], [0, -1, 0, 0, -1/2]])
sage: W.echelonized_basis()
[
(0, 1, 0, 0, 1/2),
```

```
(0, 0, 1, 0, -1/4)
]
sage: W.echelon_coordinates([0,0,2,0,-1/2])
[0, 2]
```

**echelon\_to\_user\_matrix()**

Return matrix that transforms the echelon basis to the user basis of self. This is a matrix  $A$  such that if  $v$  is a vector written with respect to the echelon basis for self then  $vA$  is that vector written with respect to the user basis of self.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.span_of_basis([[1,2,3],[4,5,6]])
sage: W.echelonized_basis()
[
(1, 0, -1),
(0, 1, 2)
]
sage: A = W.echelon_to_user_matrix(); A
[-5/3  2/3]
[ 4/3 -1/3]
```

The vector  $(1,1,1)$  has coordinates  $v = (1,1)$  with respect to the echelonized basis for self. Multiplying  $vA$  we find the coordinates of this vector with respect to the user basis.

```
sage: v = vector(QQ, [1,1]); v
(1, 1)
sage: v * A
(-1/3, 1/3)
sage: u0, u1 = W.basis()
sage: (-u0 + u1)/3
(1, 1, 1)
```

**echelonized\_basis()**

Return the basis for self in echelon form.

EXAMPLES:

```
sage: V = ZZ^3
sage: M = V.span_of_basis([[1/2,3,1],[0,1/6,0]])
sage: M.basis()
[
(1/2, 3, 1),
(0, 1/6, 0)
]
sage: B = M.echelonized_basis(); B
[
(1/2, 0, 1),
(0, 1/6, 0)
]
sage: V.span(B) == M
True
```

**echelonized\_basis\_matrix()**

Return basis matrix for self in row echelon form.

EXAMPLES:

```

sage: V = FreeModule(ZZ, 3).span_of_basis([[1,2,3],[4,5,6]])
sage: V.basis_matrix()
[1 2 3]
[4 5 6]
sage: V.echelonized_basis_matrix()
[1 2 3]
[0 3 6]

```

**has\_user\_basis()**

Return True if the basis of this free module is specified by the user, as opposed to being the default echelon form.

**EXAMPLES:**

```

sage: V = ZZ^3; V.has_user_basis()
False
sage: M = V.span_of_basis([[1,3,1]]); M.has_user_basis()
True
sage: M = V.span([1,3,1]); M.has_user_basis()
False

```

**linear\_combination\_of\_basis(v)**

Return the linear combination of the basis for self obtained from the coordinates of v.

**INPUTS:**

- v - list

**EXAMPLES:**

```

sage: V = span([[1,2,3],[4,5,6]], ZZ); V
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1 2 3]
[0 3 6]
sage: V.linear_combination_of_basis([1,1])
(1, 5, 9)

```

This should raise an error if the resulting element is not in self:

```

sage: W = (QQ**2).span([[2, 0], [0, 8]], ZZ)
sage: W.linear_combination_of_basis([1, -1/2])
Traceback (most recent call last):
...
TypeError: element [2, -4] is not in free module

```

**user\_to\_echelon\_matrix()**

Return matrix that transforms a vector written with respect to the user basis of self to one written with respect to the echelon basis. The matrix acts from the right, as is usual in Sage.

**EXAMPLES:**

```

sage: A = ZZ^3
sage: M = A.span_of_basis([[1,2,3],[4,5,6]])
sage: M.echelonized_basis()
[
(1, 2, 3),
(0, 3, 6)
]
sage: M.user_to_echelon_matrix()

```

```
[ 1  0]
[ 4 -1]
```

The vector  $v = (5, 7, 9)$  in  $M$  is  $(1, 1)$  with respect to the user basis. Multiplying the above matrix on the right by this vector yields  $(5, -1)$ , which has components the coordinates of  $v$  with respect to the echelon basis.

```
sage: v0,v1 = M.basis(); v = v0+v1
sage: e0,e1 = M.echelonized_basis()
sage: v
(5, 7, 9)
sage: 5*e0 + (-1)*e1
(5, 7, 9)
```

**vector\_space** (*base\_field=None*)

Return the vector space associated to this free module via tensor product with the fraction field of the base ring.

EXAMPLES:

```
sage: A = ZZ^3; A
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: A.vector_space()
Vector space of dimension 3 over Rational Field
sage: M = A.span_of_basis([[1/3, 2, 3/7], [4, 5, 6]]); M
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1/3  2 3/7]
[ 4   5  6]
sage: M.vector_space()
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1/3  2 3/7]
[ 4   5  6]
```

**class** sage.modules.free\_module.**RealDoubleVectorSpace\_class** (*n*)

Bases: sage.modules.free\_module.FreeModule\_ambient\_field

**coordinates** (*v*)

sage.modules.free\_module.**VectorSpace** (*K*, *dimension*, *sparse=False*, *inner\_product\_matrix=None*)

EXAMPLES:

The base can be complicated, as long as it is a field.

```
sage: V = VectorSpace(FractionField(PolynomialRing(ZZ, 'x')), 3)
sage: V
Vector space of dimension 3 over Fraction Field of Univariate Polynomial Ring in x over Integer Ring
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
```

The base must be a field or a `TypeError` is raised.

```
sage: VectorSpace(ZZ, 5)
Traceback (most recent call last):
```

```
...
TypeError: Argument K (= Integer Ring) must be a field.
```

`sage.modules.free_module.basis_seq(V, vecs)`

This converts a list `vecs` of vectors in `V` to an Sequence of immutable vectors.

Should it? I.e. in most other parts of the system the return type of `basis` or `generators` is a tuple.

EXAMPLES:

```
sage: V = VectorSpace(QQ, 2)
sage: B = V.gens()
sage: B
((1, 0), (0, 1))
sage: v = B[0]
sage: v[0] = 0 # immutable
Traceback (most recent call last):
...
ValueError: vector is immutable; please change a copy instead (use copy())
sage: sage.modules.free_module.basis_seq(V, V.gens())
[
(1, 0),
(0, 1)
]
```

`sage.modules.free_module.element_class(R, is_sparse)`

The class of the vectors (elements of a free module) with base ring `R` and boolean `is_sparse`.

EXAMPLES:

```
sage: FF = FiniteField(2)
sage: P = PolynomialRing(FF, 'x')
sage: sage.modules.free_module.element_class(QQ, is_sparse=True)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(QQ, is_sparse=False)
<type 'sage.modules.vector_rational_dense.Vector_rational_dense'>
sage: sage.modules.free_module.element_class(ZZ, is_sparse=True)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(ZZ, is_sparse=False)
<type 'sage.modules.vector_integer_dense.Vector_integer_dense'>
sage: sage.modules.free_module.element_class(FF, is_sparse=True)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(FF, is_sparse=False)
<type 'sage.modules.vector_mod2_dense.Vector_mod2_dense'>
sage: sage.modules.free_module.element_class(GF(7), is_sparse=False)
<type 'sage.modules.vector_modn_dense.Vector_modn_dense'>
sage: sage.modules.free_module.element_class(P, is_sparse=True)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(P, is_sparse=False)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_dense'>
```

`sage.modules.free_module.is_FreeModule(M)`

Return True if `M` inherits from `FreeModule_generic`.

EXAMPLES:

```
sage: from sage.modules.free_module import is_FreeModule
sage: V = ZZ^3
sage: is_FreeModule(V)
True
sage: W = V.span([ V.random_element() for i in range(2) ])
```

```
sage: is_FreeModule(W)
True
```

`sage.modules.free_module.span(gens, base_ring=None, check=True, already_echelonized=False)`  
Return the span of the vectors in `gens` using scalars from `base_ring`.

INPUT:

- `gens` - a list of either vectors or lists of ring elements used to generate the span
- `base_ring` - default: `None` - a principal ideal domain for the ring of scalars
- `check` - default: `True` - passed to the `span()` method of the ambient module
- `already_echelonized` - default: `False` - set to `True` if the vectors form the rows of a matrix in echelon form, in order to skip the computation of an echelonized basis for the span.

OUTPUT:

A module (or vector space) that is all the linear combinations of the free module elements (or vectors) with scalars from the ring (or field) given by `base_ring`. See the examples below describing behavior when the base ring is not specified and/or the module elements are given as lists that do not carry explicit base ring information.

EXAMPLES:

The vectors in the list of generators can be given as lists, provided a base ring is specified and the elements of the list are in the ring (or the fraction field of the ring). If the base ring is a field, the span is a vector space.

```
sage: V = span([[1,2,5], [2,2,2]], QQ); V
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -3]
[ 0  1  4]
```

```
sage: span([V.gen(0)], QuadraticField(-7,'a'))
Vector space of degree 3 and dimension 1 over Number Field in a with defining polynomial x^2 + 7
Basis matrix:
[ 1  0 -3]
```

```
sage: span([[1,2,3], [2,2,2], [1,2,5]], GF(2))
Vector space of degree 3 and dimension 1 over Finite Field of size 2
Basis matrix:
[1 0 1]
```

If the base ring is not a field, then a module is created. The entries of the vectors can lie outside the ring, if they are in the fraction field of the ring.

```
sage: span([[1,2,5], [2,2,2]], ZZ)
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  0 -3]
[ 0  2  8]
```

```
sage: span([[1,1,1], [1,1/2,1]], ZZ)
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  0  1]
[ 0 1/2  0]
```

```
sage: R.<x> = QQ[]
sage: M= span([ [x, x^2+1], [1/x, x^3]], R); M
```

```

Free module of degree 2 and rank 2 over
Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[      1/x      x^3]
[      0 x^5 - x^2 - 1]
sage: M.basis()[0][0].parent()
Fraction Field of Univariate Polynomial Ring in x over Rational Field

```

A base ring can be inferred if the generators are given as a list of vectors.

```

sage: span([vector(QQ, [1,2,3]), vector(QQ, [4,5,6])])
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: span([vector(QQ, [1,2,3]), vector(ZZ, [4,5,6])])
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: span([vector(ZZ, [1,2,3]), vector(ZZ, [4,5,6])])
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1 2 3]
[0 3 6]

```

#### TESTS:

```

sage: span([[1,2,3], [2,2,2], [1,2/3,5]], ZZ)
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[ 1  0 13]
[ 0 2/3 6]
[ 0  0 14]
sage: span([[1,2,3], [2,2,2], [1,2,QQ['x'].gen()]], ZZ)
Traceback (most recent call last):
...
ValueError: The elements of gens (= [[1, 2, 3], [2, 2, 2], [1, 2, x]]) must be defined over base

```

For backwards compatibility one can also give the base ring as the first argument.

```

sage: span(QQ, [[1,2], [3,4]])
Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]

```

The base ring must be a principal ideal domain (PID).

```

sage: span([[1,2,3]], Integers(6))
Traceback (most recent call last):
...
TypeError: The base_ring (= Ring of integers modulo 6)
must be a principal ideal domain.

```

Fix [trac ticket #5575](#):

```

sage: V = QQ^3
sage: span([V.0, V.1])
Vector space of degree 3 and dimension 2 over Rational Field

```

```
Basis matrix:  
[1 0 0]  
[0 1 0]
```

Improve error message from [trac ticket #12541](#):

```
sage: span({0:vector([0,1])}, QQ)  
Traceback (most recent call last):  
...  
TypeError: generators must be lists of ring elements  
or free module elements!
```



## DISCRETE SUBGROUPS OF $\mathbb{Z}^N$ .

### AUTHORS:

- Martin Albrecht (2014-03): initial version
- Jan Pöschko (2012-08): some code in this module was taken from Jan Pöschko's 2012 GSoC project

### TESTS:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice(random_matrix(ZZ, 10, 10))
sage: TestSuite(L).run()
```

```
class sage.modules.free_module_integer.FreeModule_submodule_with_basis_integer(ambient,
ba-
sis,
check=True,
ech-
e-
l-
o-
nize=False,
ech-
e-
l-
o-
nized_basis=None,
al-
ready_echelonized=
lll_reduce=True)
```

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_pid`

This class represents submodules of  $\mathbb{Z}^n$  with a distinguished basis.

However, most functionality in excess of standard submodules over PID is for these submodules considered as discrete subgroups of  $\mathbb{Z}^n$ , i.e. as lattices. That is, this class provides functions for computing LLL and BKZ reduced bases for this free module with respect to the standard Euclidean norm.

### EXAMPLE:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice(sage.crypto.gen_lattice(type='modular', m=10, seed=42, dual=True)); L
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[ 0  1  2  0  1  2 -1  0 -1 -1]
[ 0  1  0 -3  0  0  0  0  3 -1]
[ 1  1 -1  0 -3  0  0  1  2 -2]
```

```

[-1  2 -1 -1  2 -2  1 -1  0 -1]
[ 1  0 -4  2  0  1 -2 -1  0  0]
[ 2  3  0  1  1  0 -2  3  0  0]
[-2 -3 -2  0  0  1 -1  1  3 -2]
[-3  0 -1  0 -2 -1 -2  1 -1  1]
[ 1  4 -1  1  2  2  1  0  3  1]
[-1 -1  0 -3 -1  2  2  3 -1  0]
sage: L.shortest_vector()
(0, 1, 2, 0, 1, 2, -1, 0, -1, -1)

```

**BKZ** (\*args, \*\*kws)

Return a Block Korkine-Zolotareff reduced basis for self.

INPUT:

- args – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.BKZ()`
- kws – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.BKZ()`

OUTPUT:

An integer matrix which is a BKZ-reduced basis for this lattice.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='random', n=1, m=60, q=2^60, seed=42)
sage: L = IntegerLattice(A, lll_reduce=False)
sage: min(v.norm().n() for v in L.reduced_basis)
4.17330740711759e15

sage: L.LLL()
60 x 60 dense matrix over Integer Ring (use the '.str()' method to see the entries)

sage: min(v.norm().n() for v in L.reduced_basis)
5.19615242270663

sage: L.BKZ(block_size=10)
60 x 60 dense matrix over Integer Ring (use the '.str()' method to see the entries)

sage: min(v.norm().n() for v in L.reduced_basis)
4.12310562561766

```

---

**Note:** If `block_size == L.rank()` where `L` is this lattice, then this function performs Hermite-Korkine-Zolotareff (HKZ) reduction.

---

**HKZ** (\*args, \*\*kws)

Hermite-Korkine-Zolotarev (HKZ) reduce the basis.

A basis  $B$  of a lattice  $L$ , with orthogonalized basis  $B^*$  such that  $B = M \cdot B^*$  is HKZ reduced, if and only if, the following properties are satisfied:

1. The basis  $B$  is size-reduced, i.e., all off-diagonal coefficients of  $M$  satisfy  $|\mu_{i,j}| \leq 1/2$
2. The vector  $b_1$  realizes the first minimum  $\lambda_1(L)$ .
3. The projection of the vectors  $b_2, \dots, b_r$  orthogonally to  $b_1$  form an HKZ reduced basis.

---

**Note:** This is realised by calling `sage.modules.free_module_integer.FreeModule_submodule_with_block_size == self.rank()`.

---

INPUT:

- `*args` – passed through to `BKZ()`
- `**kwargs` – passed through to `BKZ()`

OUTPUT:

An integer matrix which is a HKZ-reduced basis for this lattice.

EXAMPLE:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = sage.crypto.gen_lattice(type='random', n=1, m=40, q=2^60, seed=42, lattice=True)
sage: L.HKZ()
40 x 40 dense matrix over Integer Ring (use the '.str()' method to see the entries)

sage: L.reduced_basis[0]
(-1, 0, 0, 0, 0, 0, 1, 0, -1, 0, 0, 0, 0, 0, -2, 0, 0, 0, 0, 0,
-1, 1, 0, 1, 1, 0, 0, 0, 3, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0)
```

**LLL** (*\*args, \*\*kwargs*)

Return an LLL reduced basis for self.

A lattice basis  $(b_1, b_2, \dots, b_d)$  is  $(\delta, \eta)$ -LLL-reduced if the two following conditions hold:

- For any  $i > j$ , we have  $|\mu_{i,j}| \leq \eta$ .
- For any  $i < d$ , we have  $\delta |b_i^*|^2 \leq |b_{i+1}^* + \mu_{i+1,i} b_i^*|^2$ ,

where  $\mu_{i,j} = \langle b_i, b_j^* \rangle / \langle b_j^*, b_j^* \rangle$  and  $b_i^*$  is the  $i$ -th vector of the Gram-Schmidt orthogonalisation of  $(b_1, b_2, \dots, b_d)$ .

The default reduction parameters are  $\delta = 3/4$  and  $\eta = 0.501$ .

The parameters  $\delta$  and  $\eta$  must satisfy:  $0.25 < \delta \leq 1.0$  and  $0.5 \leq \eta < \sqrt{\delta}$ . Polynomial time complexity is only guaranteed for  $\delta < 1$ .

INPUT:

- `*args` – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.LLL()`
- `**kwargs` – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.LLL()`

OUTPUT:

An integer matrix which is an LLL-reduced basis for this lattice.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = random_matrix(ZZ, 10, 10, x=-2000, y=2000)
sage: L = IntegerLattice(A, lll_reduce=False); L
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[ -645 -1037 -1775 -1619 1721 -1434 1766 1701 1669 1534]
[ 1303 960 1998 -1838 1683 -1332 149 327 -849 -1562]
[-1113 -1366 1379 669 54 1214 -1750 -605 -1566 1626]
[-1367 1651 926 1731 -913 627 669 -1437 -132 1712]
[ -549 1327 -1353 68 1479 -1803 -456 1090 -606 -317]
[ -221 -1920 -1361 1695 1139 111 -1792 1925 -656 1992]
[-1934 -29 88 890 1859 1820 -1912 -1614 -1724 1606]
[ -590 -1380 1768 774 656 760 -746 -849 1977 -1576]
[ 312 -242 -1732 1594 -439 -1069 458 -1195 1715 35]
[ 391 1229 -1815 607 -413 -860 1408 1656 1651 -628]
sage: min(v.norm().n() for v in L.reduced_basis)
```

3346.57...

```
sage: L.LLL()
[ -888    53 -274   243   -19   431   710   -83   928   347]
[  448 -330   370  -511   242  -584    -8  1220   502   183]
[ -524 -460   402  1338  -247  -279 -1038   -28  -159  -794]
[  166 -190  -162  1033  -340   -77 -1052  1134  -843   651]
[  -47 -1394  1076  -132   854  -151   297  -396  -580  -220]
[-1064   373  -706   601  -587 -1394   424   796   -22  -133]
[-1126   398   565 -1418  -446  -890  -237  -378   252   247]
[ -339   799   295   800   425  -605  -730 -1160   808   666]
[  755 -1206  -918  -192 -1063   -37  -525   -75   338   400]
[  382 -199 -1839  -482   984   -15  -695   136   682   563]
sage: L.reduced_basis[0].norm().n()
1613.74...
```

### **closest\_vector**(*t*)

Compute the closest vector in the embedded lattice to a given vector.

INPUT:

- *t* – the target vector to compute the closest vector to

OUTPUT:

The vector in the lattice closest to *t*.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[1, 0], [0, 1]])
sage: L.closest_vector((-6, 5/3))
(-6, 2)
```

ALGORITHM:

Uses the algorithm from [Mic2010].

REFERENCES:

### **discriminant**()

Return  $|\det(G)|$ , i.e. the absolute value of the determinant of the Gram matrix  $B \cdot B^T$  for any basis  $B$ .

OUTPUT:

An integer.

EXAMPLE:

```
sage: L = sage.crypto.gen_lattice(m=10, seed=42, lattice=True)
sage: L.discriminant()
214358881
```

### **is\_unimodular**()

Return True if this lattice is unimodular.

OUTPUT:

A boolean.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[1, 0], [0, 1]])
```

```

sage: L.is_unimodular()
True
sage: IntegerLattice([[2, 0], [0, 3]]).is_unimodular()
False

```

**reduced\_basis**

This attribute caches the currently best known reduced basis for `self`, where “best” is defined by the Euclidean norm of the first row vector.

EXAMPLE:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice(random_matrix(ZZ, 10, 10), lll_reduce=False)
sage: L.reduced_basis
[ -8      2      0      0      1     -1      2      1    -95     -1]
[ -2     -12      0      0      1     -1      1     -1     -2     -1]
[  4      -4     -6      5      0      0     -2      0      1     -4]
[ -6      1     -1      1      1     -1      1     -1     -3      1]
[  1      0      0     -3      2     -2      0     -2      1      0]
[ -1      1      0      0      1     -1      4     -1      1     -1]
[ 14      1     -5      4     -1      0      2      4      1      1]
[ -2     -1      0      4     -3      1     -5      0     -2     -1]
[ -9     -1     -1      3      2      1     -1      1     -2      1]
[ -1      2     -7      1      0      2      3   -1955    -22     -1]

sage: _ = L.LLL()
sage: L.reduced_basis
[  1      0      0     -3      2     -2      0     -2      1      0]
[ -1      1      0      0      1     -1      4     -1      1     -1]
[ -2      0      0      1      0     -2     -1     -3      0     -2]
[ -2     -2      0     -1      3      0     -2      0      2      0]
[  1      1      1      2      3     -2     -2      0      3      1]
[ -4      1     -1      0      1      1      2      2     -3      3]
[  1     -3     -7      2      3     -1      0      0     -1     -1]
[  1     -9      1      3      1     -3      1     -1     -1      0]
[  8      5     19      3     27      6     -3      8    -25    -22]
[ 172    -25     57    248    261    793     76   -839    -41    376]

```

**shortest\_vector** (*update\_reduced\_basis=True*, *algorithm='fplll'*, *\*args*, *\*\*kws*)

Return a shortest vector.

INPUT:

- `update_reduced_basis` – (default: `True`) set this flag if the found vector should be used to improve the basis
- `algorithm` – (default: `"fplll"`) either `"fplll"` or `"pari"`
- `*args` – passed through to underlying implementation
- `**kws` – passed through to underlying implementation

OUTPUT:

A shortest non-zero vector for this lattice.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='random', n=1, m=30, q=2^40, seed=42)
sage: L = IntegerLattice(A, lll_reduce=False)
sage: min(v.norm().n() for v in L.reduced_basis)

```

```
6.03890756700000e10
```

```
sage: L.shortest_vector().norm().n()
3.74165738677394
```

```
sage: L = IntegerLattice(A, lll_reduce=False)
sage: min(v.norm().n() for v in L.reduced_basis)
6.03890756700000e10
```

```
sage: L.shortest_vector(algorithm="pari").norm().n()
3.74165738677394
```

```
sage: L = IntegerLattice(A, lll_reduce=True)
sage: L.shortest_vector(algorithm="pari").norm().n()
3.74165738677394
```

#### **update\_reduced\_basis**(w)

Inject the vector w and run LLL to update the basis.

INPUT:

- w – a vector

OUTPUT:

Nothing is returned but the internal state is modified.

EXAMPLE:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='random', n=1, m=30, q=2^40, seed=42)
sage: L = IntegerLattice(A)
sage: B = L.reduced_basis
sage: v = L.shortest_vector(update_reduced_basis=False)
sage: L.update_reduced_basis(v)
sage: bool(L.reduced_basis[0].norm() < B[0].norm())
True
```

#### **volume**()

Return  $\text{vol}(L)$  which is  $\sqrt{\det(B \cdot B^T)}$  for any basis  $B$ .

OUTPUT:

An integer.

EXAMPLE:

```
sage: L = sage.crypto.gen_lattice(m=10, seed=42, lattice=True)
sage: L.volume()
14641
```

#### **voronoi\_cell**(radius=None)

Compute the Voronoi cell of a lattice, returning a Polyhedron.

INPUT:

- radius – (default: automatic determination) radius of ball containing considered vertices

OUTPUT:

The Voronoi cell as a Polyhedron instance.

The result is cached so that subsequent calls to this function return instantly.

## EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[1, 0], [0, 1]])
sage: V = L.voronoi_cell()
sage: V.Vrepresentation()
(A vertex at (1/2, -1/2), A vertex at (1/2, 1/2), A vertex at (-1/2, 1/2), A vertex at (-1/2, -1/2))
```

The volume of the Voronoi cell is the square root of the discriminant of the lattice:

```
sage: L = IntegerLattice(Matrix(ZZ, 4, 4, [[0, 0, 1, -1], [1, -1, 2, 1], [-6, 0, 3, 3], [-6, -24, -6, -5]]))
Free module of degree 4 and rank 4 over Integer Ring
User basis matrix:
[ 0  0  1 -1]
[ 1 -1  2  1]
[-6  0  3  3]
[-6 -24 -6 -5]
sage: V = L.voronoi_cell() # long time
sage: V.volume()           # long time
678
sage: sqrt(L.discriminant())
678
```

Lattices not having full dimension are handled as well:

```
sage: L = IntegerLattice([[2, 0, 0], [0, 2, 0]])
sage: V = L.voronoi_cell()
sage: V.Hrepresentation()
(An inequality (-1, 0, 0) x + 1 >= 0, An inequality (0, -1, 0) x + 1 >= 0, An inequality (1, 0, 0) x + 1 >= 0)
```

## ALGORITHM:

Uses parts of the algorithm from [Vit1996].

## REFERENCES:

**voronoi\_relevant\_vectors()**

Compute the embedded vectors inducing the Voronoi cell.

## OUTPUT:

The list of Voronoi relevant vectors.

## EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[3, 0], [4, 0]])
sage: L.voronoi_relevant_vectors()
[(-1, 0), (1, 0)]
```

`sage.modules.free_module_integer.IntegerLattice(basis, lll_reduce=True)`

Construct a new integer lattice from `basis`.

## INPUT:

- `basis` – can be one of the following:
  - a list of vectors
  - a matrix over the integers
  - an element of an absolute order
- `lll_reduce` – (default: `True`) run LLL reduction on the basis on construction.

## EXAMPLES:

We construct a lattice from a list of rows:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: IntegerLattice([[1,0,3], [0,2,1], [0,2,7]])
Free module of degree 3 and rank 3 over Integer Ring
User basis matrix:
[-2  0  0]
[ 0  2  1]
[ 1 -2  2]
```

Sage includes a generator for hard lattices from cryptography:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='modular', m=10, seed=42, dual=True)
sage: IntegerLattice(A)
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[ 0  1  2  0  1  2 -1  0 -1 -1]
[ 0  1  0 -3  0  0  0  0  3 -1]
[ 1  1 -1  0 -3  0  0  1  2 -2]
[-1  2 -1 -1  2 -2  1 -1  0 -1]
[ 1  0 -4  2  0  1 -2 -1  0  0]
[ 2  3  0  1  1  0 -2  3  0  0]
[-2 -3 -2  0  0  1 -1  1  3 -2]
[-3  0 -1  0 -2 -1 -2  1 -1  1]
[ 1  4 -1  1  2  2  1  0  3  1]
[-1 -1  0 -3 -1  2  2  3 -1  0]
```

You can also construct the lattice directly:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: sage.crypto.gen_lattice(type='modular', m=10, seed=42, dual=True, lattice=True)
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[ 0  1  2  0  1  2 -1  0 -1 -1]
[ 0  1  0 -3  0  0  0  0  3 -1]
[ 1  1 -1  0 -3  0  0  1  2 -2]
[-1  2 -1 -1  2 -2  1 -1  0 -1]
[ 1  0 -4  2  0  1 -2 -1  0  0]
[ 2  3  0  1  1  0 -2  3  0  0]
[-2 -3 -2  0  0  1 -1  1  3 -2]
[-3  0 -1  0 -2 -1 -2  1 -1  1]
[ 1  4 -1  1  2  2  1  0  3  1]
[-1 -1  0 -3 -1  2  2  3 -1  0]
```

We construct an ideal lattice from an element of an absolute order:

```
sage: K.<a> = CyclotomicField(17)
sage: O = K.ring_of_integers()
sage: f = O.random_element(); f
-a^15 - a^12 - a^10 - 8*a^9 - a^8 - 4*a^7 + 3*a^6 + a^5 + 2*a^4 + 8*a^3 - a^2 + a + 1

sage: from sage.modules.free_module_integer import IntegerLattice
sage: IntegerLattice(f)
Free module of degree 16 and rank 16 over Integer Ring
User basis matrix:
[ 1  1 -1  8  2  1  3 -4 -1 -8 -1  0 -1  0  0 -1]
[-1  0  1  1 -1  8  2  1  3 -4 -1 -8 -1  0 -1  0]
[ 1  1  0  1  2  2  0  9  3  2  4 -3  0 -7  0  1]
```



```
[ 1  0  1  1  0  1  2  2  0  9  3  2  4 -3  0 -7]
[ 2 -5 -2 -9 -2 -1 -2 -1 -1 -2 -1  0  0 -2  7  1]
[ 1  4  0 -5 -3  0  3  5 -2  2  0 -7  4  0 -6 -2]
[-7  4  0 -6 -2  0  1  4  0 -5 -3  0  3  5 -2  2]
[-1  0  0 -1  0  1  1 -1  8  2  1  3 -4 -1 -8 -1]
[-1 -1 -2  4  1  9  1 -1  0  1 -8 -1 -1 -4  3  2]
[-1 -2  6 -6  8  1 -3  5  3  1  1  0 -2  4  3  2]
[ 4  8  2  7 -3  2 -1  2  0 -4  0  3  6  3  0 -4]
[ 0 -1  0  1  1 -1  8  2  1  3 -4 -1 -8 -1  0 -1]
[ 2 -7 -1  0 -2  5  2  9  2  1  2  1  1  2  1  0]
[-1  7 -5  9  2 -2  6  4  2  2  1 -1  5  4  3  1]
[ 3  1 -6  0  3  1 -5  2  2  8 -4  4 -3  2 -6 -7]
[ 2  6 -4  4  0 -1  7  0 -6  3  9  1 -3 -1  4  3]
```

We construct  $\mathbb{Z}^n$ :

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: IntegerLattice(ZZ^10)
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[1 0 0 0 0 0 0 0 0 0]
[0 1 0 0 0 0 0 0 0 0]
[0 0 1 0 0 0 0 0 0 0]
[0 0 0 1 0 0 0 0 0 0]
[0 0 0 0 1 0 0 0 0 0]
[0 0 0 0 0 1 0 0 0 0]
[0 0 0 0 0 0 1 0 0 0]
[0 0 0 0 0 0 0 1 0 0]
[0 0 0 0 0 0 0 0 1 0]
[0 0 0 0 0 0 0 0 0 1]
```

Sage also interfaces with fpLLL's lattice generator:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: from sage.libs.fpLLL.fpLLL import gen_simdioph
sage: IntegerLattice(gen_simdioph(8, 20, 10), lll_reduce=False)
Free module of degree 8 and rank 8 over Integer Ring
User basis matrix:
[ 1024  829556  161099  11567  521155  769480  639201  689979]
[      0 1048576      0      0      0      0      0]
[      0      0 1048576      0      0      0      0]
[      0      0      0 1048576      0      0      0]
[      0      0      0      0 1048576      0      0]
[      0      0      0      0      0 1048576      0]
[      0      0      0      0      0      0 1048576      0]
[      0      0      0      0      0      0      0 1048576]
```



## ELEMENTS OF FREE MODULES

### AUTHORS:

- William Stein
- Josh Kantor
- Thomas Feulner (2012-11): Added `FreeModuleElement.hamming_weight()` and `FreeModuleElement_generic_sparse.hamming_weight()`
- Jeroen Demeyer (2015-02-24): Implement fast Cython methods `get_unsafe` and `set_unsafe` similar to other places in Sage ([trac ticket #17562](#))

EXAMPLES: We create a vector space over  $\mathbb{Q}$  and a subspace of this space.

```
sage: V = QQ^5
sage: W = V.span([V.1, V.2])
```

Arithmetic operations always return something in the ambient space, since there is a canonical map from  $W$  to  $V$  but not from  $V$  to  $W$ .

```
sage: parent(W.0 + V.1)
Vector space of dimension 5 over Rational Field
sage: parent(V.1 + W.0)
Vector space of dimension 5 over Rational Field
sage: W.0 + V.1
(0, 2, 0, 0, 0)
sage: W.0 - V.0
(-1, 1, 0, 0, 0)
```

Next we define modules over  $\mathbb{Z}$  and a finite field.

```
sage: K = ZZ^5
sage: M = GF(7)^5
```

Arithmetic between the  $\mathbb{Q}$  and  $\mathbb{Z}$  modules is defined, and the result is always over  $\mathbb{Q}$ , since there is a canonical coercion map to  $\mathbb{Q}$ .

```
sage: K.0 + V.1
(1, 1, 0, 0, 0)
sage: parent(K.0 + V.1)
Vector space of dimension 5 over Rational Field
```

Since there is no canonical coercion map to the finite field from  $\mathbb{Q}$  the following arithmetic is not defined:

```
sage: V.0 + M.0
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for '+': 'Vector space of dimension 5 over Rational Field' a
```

However, there is a map from  $\mathbb{Z}$  to the finite field, so the following is defined, and the result is in the finite field.

```
sage: w = K.0 + M.0; w
(2, 0, 0, 0, 0)
sage: parent(w)
Vector space of dimension 5 over Finite Field of size 7
sage: parent(M.0 + K.0)
Vector space of dimension 5 over Finite Field of size 7
```

Matrix vector multiply:

```
sage: MS = MatrixSpace(QQ, 3)
sage: A = MS([0, 1, 0, 1, 0, 0, 0, 0, 1])
sage: V = QQ^3
sage: v = V([1, 2, 3])
sage: v * A
(2, 1, 3)
```

TESTS:

```
sage: D = 46341
sage: u = 7
sage: R = Integers(D)
sage: p = matrix(R, [[84, 97, 55, 58, 51]])
sage: 2*p.row(0)
(168, 194, 110, 116, 102)
```

**class** sage.modules.free\_module\_element.**FreeModuleElement**  
Bases: sage.structure.element.Vector

An element of a generic free module.

**Mod**( $p$ )

EXAMPLES:

```
sage: V = vector(ZZ, [5, 9, 13, 15])
sage: V.Mod(7)
(5, 2, 6, 1)
sage: parent(V.Mod(7))
Vector space of dimension 4 over Ring of integers modulo 7
```

**additive\_order**()

Return the additive order of self.

EXAMPLES:

```
sage: v = vector(Integers(4), [1, 2])
sage: v.additive_order()
4

sage: v = vector([1, 2, 3])
sage: v.additive_order()
+Infinity
```

```

sage: v = vector(Integers(30), [6, 15]); v
(6, 15)
sage: v.additive_order()
10
sage: 10*v
(0, 0)

```

**apply\_map** (*phi*, *R=None*, *sparse=None*)

Apply the given map *phi* (an arbitrary Python function or callable object) to this free module element. If *R* is not given, automatically determine the base ring of the resulting element.

**INPUT:**

**sparse – True or False will control whether the result** is sparse. By default, the result is sparse iff self is sparse.

- *phi* - arbitrary Python function or callable object
- *R* - (optional) ring

**OUTPUT:** a free module element over *R*

**EXAMPLES:**

```

sage: m = vector([1, x, sin(x+1)])
sage: m.apply_map(lambda x: x^2)
(1, x^2, sin(x + 1)^2)
sage: m.apply_map(sin)
(sin(1), sin(x), sin(sin(x + 1)))

sage: m = vector(ZZ, 9, range(9))
sage: k.<a> = GF(9)
sage: m.apply_map(k)
(0, 1, 2, 0, 1, 2, 0, 1, 2)

```

In this example, we explicitly specify the codomain.

```

sage: s = GF(3)
sage: f = lambda x: s(x)
sage: n = m.apply_map(f, k); n
(0, 1, 2, 0, 1, 2, 0, 1, 2)
sage: n.parent()
Vector space of dimension 9 over Finite Field in a of size 3^2

```

If your map sends 0 to a non-zero value, then your resulting vector is not mathematically sparse:

```

sage: v = vector([0] * 6 + [1], sparse=True); v
(0, 0, 0, 0, 0, 0, 1)
sage: v2 = v.apply_map(lambda x: x+1); v2
(1, 1, 1, 1, 1, 1, 2)

```

but it's still represented with a sparse data type:

```

sage: parent(v2)
Ambient sparse free module of rank 7 over the principal ideal domain Integer Ring

```

This data type is inefficient for dense vectors, so you may want to specify *sparse=False*:

```

sage: v2 = v.apply_map(lambda x: x+1, sparse=False); v2
(1, 1, 1, 1, 1, 1, 2)

```

```
sage: parent(v2)
Ambient free module of rank 7 over the principal ideal domain Integer Ring
```

Or if you have a map that will result in mostly zeroes, you may want to specify `sparse=True`:

```
sage: v = vector(srange(10))
sage: v2 = v.apply_map(lambda x: 0 if x else 1, sparse=True); v2
(1, 0, 0, 0, 0, 0, 0, 0, 0, 0)
sage: parent(v2)
Ambient sparse free module of rank 10 over the principal ideal domain Integer Ring
```

TESTS:

```
sage: m = vector(SR, [])
sage: m.apply_map(lambda x: x*x) == m
True
```

Check that we don't unnecessarily apply phi to 0 in the sparse case:

```
sage: m = vector(ZZ, range(1, 4), sparse=True)
sage: m.apply_map(lambda x: 1/x)
(1, 1/2, 1/3)
```

```
sage: parent(vector(RDF, (), sparse=True).apply_map(lambda x: x, sparse=True))
Sparse vector space of dimension 0 over Real Double Field
sage: parent(vector(RDF, (), sparse=True).apply_map(lambda x: x, sparse=False))
Vector space of dimension 0 over Real Double Field
sage: parent(vector(RDF, (), sparse=False).apply_map(lambda x: x, sparse=True))
Sparse vector space of dimension 0 over Real Double Field
sage: parent(vector(RDF, (), sparse=False).apply_map(lambda x: x, sparse=False))
Vector space of dimension 0 over Real Double Field
```

Check that the bug in [trac ticket #14558](#) has been fixed:

```
sage: F.<a> = GF(9)
sage: v = vector([a, 0,0,0], sparse=True)
sage: f = F.hom([a**3])
sage: v.apply_map(f)
(2*a + 1, 0, 0, 0)
```

**change\_ring(*R*)**

Change the base ring of this vector.

EXAMPLES:

```
sage: v = vector(QQ['x,y'], [1..5]); v.change_ring(GF(3))
(1, 2, 0, 1, 2)
```

**column()**

Return a matrix with a single column and the same entries as the vector `self`.

OUTPUT:

A matrix over the same ring as the vector (or free module element), with a single column. The entries of the column are identical to those of the vector, and in the same order.

EXAMPLES:

```
sage: v = vector(ZZ, [1,2,3])
sage: w = v.column(); w
[1]
```

```

[2]
[3]
sage: w.parent()
Full MatrixSpace of 3 by 1 dense matrices over Integer Ring

sage: x = vector(FiniteField(13), [2,4,8,16])
sage: x.column()
[2]
[4]
[8]
[3]

```

There is more than one way to get one-column matrix from a vector. The `column` method is about equally efficient to making a row and then taking a transpose. Notice that supplying a vector to the matrix constructor demonstrates Sage's preference for rows.

```

sage: x = vector(RDF, [sin(i*pi/20) for i in range(10)])
sage: x.column() == matrix(x).transpose()
True
sage: x.column() == x.row().transpose()
True

```

Sparse or dense implementations are preserved.

```

sage: d = vector(RR, [1.0, 2.0, 3.0])
sage: s = vector(CDF, {2:5.0+6.0*I})
sage: dm = d.column()
sage: sm = s.column()
sage: all([d.is_dense(), dm.is_dense(), s.is_sparse(), sm.is_sparse()])
True

```

#### TESTS:

The `column()` method will return a specified column of a matrix as a vector. So here are a couple of round-trips.

```

sage: A = matrix(ZZ, [[1],[2],[3]])
sage: A == A.column(0).column()
True
sage: v = vector(ZZ, [4,5,6])
sage: v == v.column().column(0)
True

```

And a very small corner case.

```

sage: v = vector(ZZ, [])
sage: w = v.column()
sage: w.parent()
Full MatrixSpace of 0 by 1 dense matrices over Integer Ring

```

#### `conjugate()`

Returns a vector where every entry has been replaced by its complex conjugate.

#### OUTPUT:

A vector of the same length, over the same ring, but with each entry replaced by the complex conjugate, as implemented by the `conjugate()` method for elements of the base ring, which is presently always complex conjugation.

#### EXAMPLES:

```

sage: v = vector(CDF, [2.3 - 5.4*I, -1.7 + 3.6*I])
sage: w = v.conjugate(); w
(2.3 + 5.4*I, -1.7 - 3.6*I)
sage: w.parent()
Vector space of dimension 2 over Complex Double Field

```

Even if conjugation seems nonsensical over a certain ring, this method for vectors cooperates silently.

```

sage: u = vector(ZZ, range(6))
sage: u.conjugate()
(0, 1, 2, 3, 4, 5)

```

Sage implements a few specialized subfields of the complex numbers, such as the cyclotomic fields. This example uses such a field containing a primitive 7-th root of unity named  $a$ .

```

sage: F.<a> = CyclotomicField(7)
sage: v = vector(F, [a^i for i in range(7)])
sage: v
(1, a, a^2, a^3, a^4, a^5, -a^5 - a^4 - a^3 - a^2 - a - 1)
sage: v.conjugate()
(1, -a^5 - a^4 - a^3 - a^2 - a - 1, a^5, a^4, a^3, a^2, a)

```

Sparse vectors are returned as such.

```

sage: v = vector(CC, {1: 5 - 6*I, 3: -7*I}); v
(0.0000000000000000, 5.000000000000000 - 6.000000000000000*I, 0.0000000000000000, -7.000000000000000*I, 0.0000000000000000, 0.0000000000000000)
sage: v.is_sparse()
True
sage: vc = v.conjugate(); vc
(0.0000000000000000, 5.000000000000000 + 6.000000000000000*I, 0.0000000000000000, 7.000000000000000*I, 0.0000000000000000, 0.0000000000000000)
sage: vc.conjugate()
(0.0000000000000000, 5.000000000000000 - 6.000000000000000*I, 0.0000000000000000, -7.000000000000000*I, 0.0000000000000000, 0.0000000000000000)

```

TESTS:

```

sage: n = 15
sage: x = vector(CDF, [sin(i*pi/n)+cos(i*pi/n)*I for i in range(n)])
sage: x + x.conjugate() in RDF^n
True
sage: I*(x - x.conjugate()) in RDF^n
True

```

The parent of the conjugate is the same as that of the original vector. We test this by building a specialized vector space with a non-standard inner product, and constructing a test vector in this space.

```

sage: V = VectorSpace(CDF, 2, inner_product_matrix = [[2,1],[1,5]])
sage: v = vector(CDF, [2-3*I, 4+5*I])
sage: w = V(v)
sage: w.parent()
Ambient quadratic space of dimension 2 over Complex Double Field
Inner product matrix:
[2.0 1.0]
[1.0 5.0]
sage: w.conjugate().parent()
Ambient quadratic space of dimension 2 over Complex Double Field
Inner product matrix:
[2.0 1.0]
[1.0 5.0]

```

`coordinate_ring()`



Return the ring from which the coefficients of this vector come.

This is different from `base_ring()`, which returns the ring of scalars.

EXAMPLES:

```
sage: M = (ZZ^2) * (1/2)
sage: v = M([0, 1/2])
sage: v.base_ring()
Integer Ring
sage: v.coordinate_ring()
Rational Field
```

### **cross\_product** (*right*)

Return the cross product of self and right, which is only defined for vectors of length 3 or 7.

INPUT:

- *right* - A vector of the same size as *self*, either degree three or degree seven.

OUTPUT:

The cross product (vector product) of *self* and *right*, a vector of the same size of *self* and *right*.

This product is performed under the assumption that the basis vectors are orthonormal.

EXAMPLES:

```
sage: v = vector([1, 2, 3]); w = vector([0, 5, -9])
sage: v.cross_product(v)
(0, 0, 0)
sage: u = v.cross_product(w); u
(-33, 9, 5)
sage: u.dot_product(v)
0
sage: u.dot_product(w)
0
```

The cross product is defined for degree seven vectors as well. [\[WIKIPEDIA:CROSSPRODUCT\]](#) The 3-D cross product is achieved using the quaternions, whereas the 7-D cross product is achieved using the octonions.

```
sage: u = vector(QQ, [1, -1/3, 57, -9, 56/4, -4, 1])
sage: v = vector(QQ, [37, 55, -99/57, 9, -12, 11/3, 4/98])
sage: u.cross_product(v)
(1394815/2793, -2808401/2793, 39492/49, -48737/399, -9151880/2793, 62513/2793, -326603/171)
```

The degree seven cross product is anticommutative.

```
sage: u.cross_product(v) + v.cross_product(u)
(0, 0, 0, 0, 0, 0, 0)
```

The degree seven cross product is distributive across addition.

```
sage: v = vector([-12, -8/9, 42, 89, -37, 60/99, 73])
sage: u = vector([31, -42/7, 97, 80, 30/55, -32, 64])
sage: w = vector([-25/4, 40, -89, -91, -72/7, 79, 58])
sage: v.cross_product(u + w) - (v.cross_product(u) + v.cross_product(w))
(0, 0, 0, 0, 0, 0, 0)
```

The degree seven cross product respects scalar multiplication.

```
sage: v = vector([2, 17, -11/5, 21, -6, 2/17, 16])
sage: u = vector([-8, 9, -21, -6, -5/3, 12, 99])
```

```
sage: (5*v).cross_product(u) - 5*(v.cross_product(u))
(0, 0, 0, 0, 0, 0, 0)
sage: v.cross_product(5*u) - 5*(v.cross_product(u))
(0, 0, 0, 0, 0, 0, 0)
sage: (5*v).cross_product(u) - (v.cross_product(5*u))
(0, 0, 0, 0, 0, 0, 0)
```

The degree seven cross product respects the scalar triple product.

```
sage: v = vector([2, 6, -7/4, -9/12, -7, 12, 9])
sage: u = vector([22, -7, -9/11, 12, 15, 15/7, 11])
sage: w = vector([-11, 17, 19, -12/5, 44, 21/56, -8])
sage: v.dot_product(u.cross_product(w)) - w.dot_product(v.cross_product(u))
0
```

TESTS:

Both vectors need to be of length three or both vectors need to be of length seven.

```
sage: u = vector(range(7))
sage: v = vector(range(3))
sage: u.cross_product(v)
Traceback (most recent call last):
...
TypeError: Cross product only defined for vectors of length three or seven, not (7 and 3)
```

REFERENCES:

AUTHOR:

Billy Wonderly (2010-05-11), Added 7-D Cross Product

#### **cross\_product\_matrix()**

Return the matrix which describes a cross product between `self` and some other vector.

This operation is sometimes written using the [hat operator](#). It is only defined for vectors of length 3 or 7. For a vector  $v$  the cross product matrix  $\hat{v}$  is a matrix which satisfies  $\hat{v} \cdot w = v \times w$  and also  $w \cdot \hat{v} = w \times v$  for all vectors  $w$ . The basis vectors are assumed to be orthonormal.

OUTPUT:

The cross product matrix of this vector.

EXAMPLES:

```
sage: v = vector([1, 2, 3])
sage: vh = v.cross_product_matrix()
sage: vh
[ 0 -3  2]
[ 3  0 -1]
[-2  1  0]
sage: w = random_vector(3, x=1, y=100)
sage: vh*w == v.cross_product(w)
True
sage: w*vh == w.cross_product(v)
True
sage: vh.is_alternating()
True
```

TESTS:

```

sage: F = GF(previous_prime(2^32))
sage: v = random_vector(F, 3)
sage: w = random_vector(F, 3)
sage: vh = v.cross_product_matrix()
sage: vh*w == v.cross_product(w)
True
sage: w*vh == w.cross_product(v)
True
sage: vh.is_alternating()
True
sage: v = random_vector(F, 7)
sage: w = random_vector(F, 7)
sage: vh = v.cross_product_matrix()
sage: vh*w == v.cross_product(w)
True
sage: w*vh == w.cross_product(v)
True
sage: vh.is_alternating()
True
sage: random_vector(F, 5).cross_product_matrix()
Traceback (most recent call last):
...
TypeError: Cross product only defined for vectors of length three or seven, not 5

```

**curl** (*variables=None*)

Return the curl of this two-dimensional or three-dimensional vector function.

**EXAMPLES:**

```

sage: R.<x,y,z> = QQ[]
sage: vector([-y, x, 0]).curl()
(0, 0, 2)
sage: vector([y, -x, x*y*z]).curl()
(x*z, -y*z, -2)
sage: vector([y^2, 0, 0]).curl()
(0, 0, -2*y)
sage: (R^3).random_element().curl().div()
0

```

For rings where the variable order is not well defined, it must be defined explicitly:

```

sage: v = vector(SR, [-y, x, 0])
sage: v.curl()
Traceback (most recent call last):
...
ValueError: Unable to determine ordered variable names for Symbolic Ring
sage: v.curl([x, y, z])
(0, 0, 2)

```

Note that callable vectors have well defined variable orderings:

```

sage: v(x, y, z) = (-y, x, 0)
sage: v.curl()
(x, y, z) |--> (0, 0, 2)

```

In two-dimensions, this returns a scalar value:

```

sage: R.<x,y> = QQ[]
sage: vector([-y, x]).curl()
2

```

**degree()**

Return the degree of this vector, which is simply the number of entries.

EXAMPLES:

```
sage: sage.modules.free_module_element.FreeModuleElement(QQ^389).degree()
389
sage: vector([1, 2/3, 8]).degree()
3
```

**denominator()**

Return the least common multiple of the denominators of the entries of self.

EXAMPLES:

```
sage: v = vector([1/2, 2/5, 3/14])
sage: v.denominator()
70
sage: 2*5*7
70

sage: M = (ZZ^2)*(1/2)
sage: M.basis()[0].denominator()
2
```

TESTS:

The following was fixed in [trac ticket #8800](#):

```
sage: M = GF(5)^3
sage: v = M((4, 0, 2))
sage: v.denominator()
1
```

**dense\_vector()**

Return dense version of self. If self is dense, just return self; otherwise, create and return correspond dense vector.

EXAMPLES:

```
sage: vector([-1, 0, 3, 0, 0, 0]).dense_vector().is_dense()
True
sage: vector([-1, 0, 3, 0, 0, 0], sparse=True).dense_vector().is_dense()
True
sage: vector([-1, 0, 3, 0, 0, 0], sparse=True).dense_vector()
(-1, 0, 3, 0, 0, 0)
```

**derivative(\*args)**

Derivative with respect to variables supplied in args.

Multiple variables and iteration counts may be supplied; see documentation for the `global derivative()` function for more details.

`diff()` is an alias of this function.

EXAMPLES:

```
sage: v = vector([1, x, x^2])
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
```

```

True
sage: v = vector([1,x,x^2], sparse=True)
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
True
sage: v.derivative(x,x)
(0, 0, 2)

```

**dict** (*copy=True*)

Return dictionary of nonzero entries of self.

INPUT:

- *copy* – bool (default: True)

OUTPUT:

- Python dictionary

EXAMPLES:

```

sage: v = vector([0,0,0,0,1/2,0,3/14])
sage: v.dict()
{4: 1/2, 6: 3/14}

```

In some cases when *copy=False*, we get back a dangerous reference:

```

sage: v = vector({0:5, 2:3/7}, sparse=True)
sage: v.dict(copy=False)
{0: 5, 2: 3/7}
sage: v.dict(copy=False)[0] = 18
sage: v
(18, 0, 3/7)

```

**diff** (*\*args*)

Derivative with respect to variables supplied in args.

Multiple variables and iteration counts may be supplied; see documentation for the `global derivative()` function for more details.

`diff()` is an alias of this function.

EXAMPLES:

```

sage: v = vector([1,x,x^2])
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
True
sage: v = vector([1,x,x^2], sparse=True)
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
True
sage: v.derivative(x,x)
(0, 0, 2)

```

**div** (*variables=None*)

Return the divergence of this vector function.

EXAMPLES:

```

sage: R.<x,y,z> = QQ[]
sage: vector([x, y, z]).div()
3
sage: vector([x*y, y*z, z*x]).div()
x + y + z

sage: R.<x,y,z,w> = QQ[]
sage: vector([x*y, y*z, z*x]).div([x, y, z])
x + y + z
sage: vector([x*y, y*z, z*x]).div([z, x, y])
0
sage: vector([x*y, y*z, z*x]).div([x, y, w])
y + z

sage: vector(SR, [x*y, y*z, z*x]).div()
Traceback (most recent call last):
...
ValueError: Unable to determine ordered variable names for Symbolic Ring
sage: vector(SR, [x*y, y*z, z*x]).div([x, y, z])
x + y + z

```

**dot\_product** (*right*)

Return the dot product of *self* and *right*, which is the sum of the product of the corresponding entries.

INPUT:

- *right* – a vector of the same degree as *self*. It does not need to belong to the same parent as *self*, so long as the necessary products and sums are defined.

OUTPUT:

If *self* and *right* are the vectors  $\vec{x}$  and  $\vec{y}$ , of degree  $n$ , then this method returns

$$\sum_{i=1}^n x_i y_i$$

---

**Note:** The `inner_product()` is a more general version of this method, and the `hermitian_inner_product()` method may be more appropriate if your vectors have complex entries.

---

**EXAMPLES:**

```

sage: V = FreeModule(ZZ, 3)
sage: v = V([1, 2, 3])
sage: w = V([4, 5, 6])
sage: v.dot_product(w)
32

sage: R.<x> = QQ[]
sage: v = vector([x, x^2, 3*x]); w = vector([2*x, x, 3+x])
sage: v*w
x^3 + 5*x^2 + 9*x
sage: (x*2*x) + (x^2*x) + (3*x*(3+x))
x^3 + 5*x^2 + 9*x
sage: w*v
x^3 + 5*x^2 + 9*x

```

The vectors may be from different vector spaces, provided the necessary operations make sense. Notice that coercion will generate a result of the same type, even if the order of the arguments is reversed.:

```
sage: v = vector(ZZ, [1,2,3])
sage: w = vector(FiniteField(3), [0,1,2])
sage: ip = w.dot_product(v); ip
2
sage: ip.parent()
Finite Field of size 3

sage: ip = v.dot_product(w); ip
2
sage: ip.parent()
Finite Field of size 3
```

The dot product of a vector with itself is the 2-norm, squared.

```
sage: v = vector(QQ, [3, 4, 7])
sage: v.dot_product(v) - v.norm()^2
0
```

#### TESTS:

The second argument must be a free module element.

```
sage: v = vector(QQ, [1,2])
sage: v.dot_product('junk')
Traceback (most recent call last):
...
TypeError: Cannot convert str to sage.modules.free_module_element.FreeModuleElement
```

The degrees of the arguments must match.

```
sage: v = vector(QQ, [1,2])
sage: w = vector(QQ, [1,2,3])
sage: v.dot_product(w)
Traceback (most recent call last):
...
ArithmeticError: degrees (2 and 3) must be the same
```

Check that vectors with different base rings play out nicely ([trac ticket #3103](#)):

```
sage: vector(CDF, [2, 2]) * vector(ZZ, [1, 3])
8.0
```

Zero-dimensional vectors work:

```
sage: v = vector(ZZ, [])
sage: v.dot_product(v)
0
```

#### `element()`

Simply returns self. This is useful, since for many objects, `self.element()` returns a vector corresponding to self.

#### EXAMPLES:

```
sage: v = vector([1/2, 2/5, 0]); v
(1/2, 2/5, 0)
sage: v.element()
(1/2, 2/5, 0)
```

**get** (*i*)Like `__getitem__` but without bounds checking: *i* must satisfy  $0 \leq i < \text{self.degree}$ .

EXAMPLES:

```
sage: vector(SR, [1/2, 2/5, 0]).get(0)
1/2
```

**hamming\_weight** ()Return the number of positions *i* such that `self[i] != 0`.

EXAMPLES:

```
sage: vector([-1, 0, 3, 0, 0, 0, 0.01]).hamming_weight()
3
```

**hermitian\_inner\_product** (*right*)

Returns the dot product, but with the entries of the first vector conjugated beforehand.

INPUT:

- *right* - a vector of the same degree as *self*

OUTPUT:

If *self* and *right* are the vectors  $\vec{x}$  and  $\vec{y}$  of degree *n* then this routine computes

$$\sum_{i=1}^n \overline{x_i} y_i$$

where the bar indicates complex conjugation.

---

**Note:** If your vectors do not contain complex entries, then `dot_product()` will return the same result without the overhead of conjugating elements of *self*.

If you are not computing a weighted inner product, and your vectors do not have complex entries, then the `dot_product()` will return the same result.

---

EXAMPLES:

```
sage: v = vector(CDF, [2+3*I, 5-4*I])
sage: w = vector(CDF, [6-4*I, 2+3*I])
sage: v.hermitian_inner_product(w)
-2.0 - 3.0*I
```

Sage implements a few specialized fields over the complex numbers, such as cyclotomic fields and quadratic number fields. So long as the base rings have a conjugate method, then the Hermitian inner product will be available.

```
sage: Q.<a> = QuadraticField(-7)
sage: a^2
-7
sage: v = vector(Q, [3+a, 5-2*a])
sage: w = vector(Q, [6, 4+3*a])
sage: v.hermitian_inner_product(w)
17*a - 4
```

The Hermitian inner product should be additive in each argument (we only need to test one), linear in each argument (with conjugation on the first scalar), and anti-commutative.

```
sage: alpha = CDF(5.0 + 3.0*I)
sage: u = vector(CDF, [2+4*I, -3+5*I, 2-7*I])
```



```

sage: v = vector(CDF, [-1+3*I, 5+4*I, 9-2*I])
sage: w = vector(CDF, [8+3*I, -4+7*I, 3-6*I])
sage: (u+v).hermitian_inner_product(w) == u.hermitian_inner_product(w) + v.hermitian_inner_p
True
sage: (alpha*u).hermitian_inner_product(w) == alpha.conjugate()*u.hermitian_inner_product(w)
True
sage: u.hermitian_inner_product(alpha*w) == alpha*u.hermitian_inner_product(w)
True
sage: u.hermitian_inner_product(v) == v.hermitian_inner_product(u).conjugate()
True

```

For vectors with complex entries, the Hermitian inner product has a more natural relationship with the 2-norm (which is the default for the `norm()` method). The norm squared equals the Hermitian inner product of the vector with itself.

```

sage: v = vector(CDF, [-0.66+0.47*I, -0.60+0.91*I, -0.62-0.87*I, 0.53+0.32*I])
sage: abs(v.norm()^2 - v.hermitian_inner_product(v)) < 1.0e-10
True

```

#### TESTS:

This method is built on the `dot_product()` method, which allows for a wide variety of inputs. Any error handling happens there.

```

sage: v = vector(CDF, [2+3*I])
sage: w = vector(CDF, [5+2*I, 3+9*I])
sage: v.hermitian_inner_product(w)
Traceback (most recent call last):
...
ArithmeticError: degrees (1 and 2) must be the same

```

#### **inner\_product** (*right*)

Returns the inner product of `self` and `right`, possibly using an inner product matrix from the parent of `self`.

##### INPUT:

- `right` - a vector of the same degree as `self`

##### OUTPUT:

If the parent vector space does not have an inner product matrix defined, then this is the usual dot product (`dot_product()`). If `self` and `right` are considered as single column matrices,  $\vec{x}$  and  $\vec{y}$ , and  $A$  is the inner product matrix, then this method computes

$$(\vec{x})^t A \vec{y}$$

where  $t$  indicates the transpose.

---

**Note:** If your vectors have complex entries, the `hermitian_inner_product()` may be more appropriate for your purposes.

---

#### EXAMPLES:

```

sage: v = vector(QQ, [1,2,3])
sage: w = vector(QQ, [-1,2,-3])
sage: v.inner_product(w)
-6
sage: v.inner_product(w) == v.dot_product(w)
True

```

The vector space or free module that is the parent to `self` can have an inner product matrix defined, which will be used by this method. This matrix will be passed through to subspaces.

```
sage: ipm = matrix(ZZ, [[2,0,-1], [0,2,0], [-1,0,6]])
sage: M = FreeModule(ZZ, 3, inner_product_matrix = ipm)
sage: v = M([1,0,0])
sage: v.inner_product(v)
2
sage: K = M.span_of_basis([[0/2,-1/2,-1/2], [0,1/2,-1/2],[2,0,0]])
sage: (K.0).inner_product(K.0)
2
sage: w = M([1,3,-1])
sage: v = M([2,-4,5])
sage: w.row()*ipm*v.column() == w.inner_product(v)
True
```

Note that the inner product matrix comes from the parent of `self`. So if a vector is not an element of the correct parent, the result could be a source of confusion.

```
sage: V = VectorSpace(QQ, 2, inner_product_matrix=[[1,2],[2,1]])
sage: v = V([12, -10])
sage: w = vector(QQ, [10,12])
sage: v.inner_product(w)
88
sage: w.inner_product(v)
0
sage: w = V(w)
sage: w.inner_product(v)
88
```

---

**Note:** The use of an inner product matrix makes no restrictions on the nature of the matrix. In particular, in this context it need not be Hermitian and positive-definite (as it is in the example above).

---

#### TESTS:

Most error handling occurs in the `dot_product()` method. But with an inner product defined, this method will check that the input is a vector or free module element.

```
sage: W = VectorSpace(RDF, 2, inner_product_matrix = matrix(RDF, 2, [1.0,2.0,3.0,4.0]))
sage: v = W([2.0, 4.0])
sage: v.inner_product(5)
Traceback (most recent call last):
...
TypeError: right must be a free module element
```

#### **integral** (\*args, \*\*kws)

Returns a symbolic integral of the vector, component-wise.

`integrate()` is an alias of the function.

#### EXAMPLES:

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: r.integral(t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: integrate(r,t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: r.integrate(t,0,1)
(1/2, 1/3, -cos(1) + 1)
```

**integrate** (\*args, \*\*kws)

Returns a symbolic integral of the vector, component-wise.

`integrate()` is an alias of the function.

EXAMPLES:

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: r.integral(t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: integrate(r,t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: r.integrate(t,0,1)
(1/2, 1/3, -cos(1) + 1)
```

**is\_dense**()

Return True if this is a dense vector, which is just a statement about the data structure, not the number of nonzero entries.

EXAMPLES:

```
sage: vector([1/2,2/5,0]).is_dense()
True
sage: vector([1/2,2/5,0],sparse=True).is_dense()
False
```

**is\_immutable**()

Return True if this vector is immutable, i.e., the entries cannot be changed.

EXAMPLES:

```
sage: v = vector(QQ['x,y'], [1..5]); v.is_immutable()
False
sage: v.set_immutable()
sage: v.is_immutable()
True
```

**is\_mutable**()

Return True if this vector is mutable, i.e., the entries can be changed.

EXAMPLES:

```
sage: v = vector(QQ['x,y'], [1..5]); v.is_mutable()
True
sage: v.set_immutable()
sage: v.is_mutable()
False
```

**is\_sparse**()

Return True if this is a sparse vector, which is just a statement about the data structure, not the number of nonzero entries.

EXAMPLES:

```
sage: vector([1/2,2/5,0]).is_sparse()
False
sage: vector([1/2,2/5,0],sparse=True).is_sparse()
True
```

**is\_vector**()

Return True, since this is a vector.

EXAMPLES:

```
sage: vector([1/2, 2/5, 0]).is_vector()
True
```

**iteritems()**

Return iterator over self.

EXAMPLES:

```
sage: v = vector([1, 2/3, pi])
sage: v.iteritems()
<dictionary-itemiterator object at ...>
sage: list(v.iteritems())
[(0, 1), (1, 2/3), (2, pi)]
```

**lift()**

EXAMPLES:

```
sage: V = vector(Integers(7), [5, 9, 13, 15]) ; V
(5, 2, 6, 1)
sage: V.lift()
(5, 2, 6, 1)
sage: parent(V.lift())
Ambient free module of rank 4 over the principal ideal domain Integer Ring
```

**list (copy=True)**

Return list of elements of self.

INPUT:

- copy – bool, whether returned list is a copy that is safe to change, is ignored.

EXAMPLES:

```
sage: P.<x,y,z> = QQ[]
sage: v = vector([x,y,z], sparse=True)
sage: type(v)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: a = v.list(); a
[x, y, z]
sage: a[0] = x*y; v
(x, y, z)
```

The optional argument copy is ignored:

```
sage: a = v.list(copy=False); a
[x, y, z]
sage: a[0] = x*y; v
(x, y, z)
```

**list\_from\_positions (positions)**

Return list of elements chosen from this vector using the given positions of this vector.

INPUT:

- positions – iterable of ints

EXAMPLES:

```
sage: v = vector([1, 2/3, pi])
sage: v.list_from_positions([0, 0, 0, 2, 1])
[1, 1, 1, pi, 2/3]
```

**monic()**

Return this vector divided through by the first nonzero entry of this vector.

**EXAMPLES:**

```
sage: v = vector(QQ, [0, 4/3, 5, 1, 2])
sage: v.monic()
(0, 1, 15/4, 3/4, 3/2)
sage: v = vector(QQ, [])
sage: v.monic()
()
```

**nintegral(\*args, \*\*kws)**

Returns a numeric integral of the vector, component-wise, and the result of the nintegral command on each component of the input.

`nintegrate()` is an alias of the function.

**EXAMPLES:**

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: vec,answers=r.nintegral(t,0,1)
sage: vec
(0.5, 0.3333333333333334, 0.4596976941318602)
sage: type(vec)
<type 'sage.modules.vector_real_double_dense.Vector_real_double_dense'>
sage: answers
[(0.5, 5.551115123125784e-15, 21, 0), (0.3333333333333333..., 3.70074341541719e-15, 21, 0), (0.4596976941318602, 3.70074341541719e-15, 21, 0)]

sage: r=vector([t,0,1], sparse=True)
sage: r.nintegral(t,0,1)
((0.5, 0.0, 1.0), {0: (0.5, 5.551115123125784e-15, 21, 0), 2: (1.0, 1.11022302462515...e-14, 21, 0)})
```

**nintegrate(\*args, \*\*kws)**

Returns a numeric integral of the vector, component-wise, and the result of the nintegral command on each component of the input.

`nintegrate()` is an alias of the function.

**EXAMPLES:**

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: vec,answers=r.nintegral(t,0,1)
sage: vec
(0.5, 0.3333333333333334, 0.4596976941318602)
sage: type(vec)
<type 'sage.modules.vector_real_double_dense.Vector_real_double_dense'>
sage: answers
[(0.5, 5.551115123125784e-15, 21, 0), (0.3333333333333333..., 3.70074341541719e-15, 21, 0), (0.4596976941318602, 3.70074341541719e-15, 21, 0)]

sage: r=vector([t,0,1], sparse=True)
sage: r.nintegral(t,0,1)
((0.5, 0.0, 1.0), {0: (0.5, 5.551115123125784e-15, 21, 0), 2: (1.0, 1.11022302462515...e-14, 21, 0)})
```

**nonzero\_positions()**

Return the sorted list of integers  $i$  such that  $\text{self}[i] \neq 0$ .

**EXAMPLES:**

```
sage: vector([-1,0,3,0,0,0,0.01]).nonzero_positions()
[0, 2, 6]
```

**norm**(*p*='\_\_two\_\_')

Return the  $p$ -norm of *self*.

INPUT:

- *p* - default: 2 - *p* can be a real number greater than 1, infinity (`oo` or `Infinity`), or a symbolic expression.

- *p* = 1: the taxicab (Manhattan) norm

- *p* = 2: the usual Euclidean norm (the default)

- *p* =  $\infty$ : the maximum entry (in absolute value)

---

**Note:** See also `sage.misc.functional.norm()`

---

EXAMPLES:

```
sage: v = vector([1,2,-3])
```

```
sage: v.norm(5)
```

```
276^(1/5)
```

The default is the usual Euclidean norm.

```
sage: v.norm()
```

```
sqrt(14)
```

```
sage: v.norm(2)
```

```
sqrt(14)
```

The infinity norm is the maximum size (in absolute value) of the entries.

```
sage: v.norm(Infinity)
```

```
3
```

```
sage: v.norm(oo)
```

```
3
```

Real or symbolic values may be used for *p*.

```
sage: v=vector(RDF,[1,2,3])
```

```
sage: v.norm(5)
```

```
3.077384885394063
```

```
sage: v.norm(pi/2)      #abs tol 1e-15
```

```
4.216595864704748
```

```
sage: __=var('a b c d p'); v=vector([a, b, c, d])
```

```
sage: v.norm(p)
```

```
(abs(a)^p + abs(b)^p + abs(c)^p + abs(d)^p)^(1/p)
```

Notice that the result may be a symbolic expression, owing to the necessity of taking a square root (in the default case). These results can be converted to numerical values if needed.

```
sage: v = vector(ZZ, [3,4])
```

```
sage: nrm = v.norm(); nrm
```

```
5
```

```
sage: nrm.parent()
```

```
Rational Field
```

```
sage: v = vector(QQ, [3, 5])
```

```
sage: nrm = v.norm(); nrm
```

```

sqrt(34)
sage: nrm.parent()
Symbolic Ring
sage: numeric = N(nrm); numeric
5.83095189484...
sage: numeric.parent()
Real Field with 53 bits of precision

```

**TESTS:**

The value of  $p$  must be greater than, or equal to, one.

```

sage: v = vector(QQ, [1,2])
sage: v.norm(0.99)
Traceback (most recent call last):
...
ValueError: 0.9900000000000000 is not greater than or equal to 1

```

Norm works with Python integers (see [trac ticket #13502](#)).

```

sage: v = vector(QQ, [1,2])
sage: v.norm(int(2))
sqrt(5)

```

**normalized** ( $p='\_two\_'$ )

Return the input vector divided by the  $p$ -norm.

**INPUT:**

- “ $p$ ” - default: 2 -  $p$  value for the norm

**EXAMPLES:**

```

sage: v = vector(QQ, [4, 1, 3, 2])
sage: v.normalized()
(2/15*sqrt(30), 1/30*sqrt(30), 1/10*sqrt(30), 1/15*sqrt(30))
sage: sum(v.normalized(1))
1

```

Note that normalizing the vector may change the base ring:

```

sage: v.base_ring() == v.normalized().base_ring()
False
sage: u = vector(RDF, [-3, 4, 6, 9])
sage: u.base_ring() == u.normalized().base_ring()
True

```

**numpy** ( $dtype='object'$ )

Converts self to a numpy array.

**INPUT:**

- dtype** – the **numpy dtype** of the returned array

**EXAMPLES:**

```

sage: v = vector([1,2,3])
sage: v.numpy()
array([1, 2, 3], dtype=object)
sage: v.numpy() * v.numpy()
array([1, 4, 9], dtype=object)

```

```
sage: vector(QQ, [1, 2, 5/6]).numpy()
array([1, 2, 5/6], dtype=object)
```

By default the object `dtype` is used. Alternatively, the desired dtype can be passed in as a parameter:

```
sage: v = vector(QQ, [1, 2, 5/6])
sage: v.numpy()
array([1, 2, 5/6], dtype=object)
sage: v.numpy(dtype=float)
array([ 1.          ,  2.          ,  0.83333333])
sage: v.numpy(dtype=int)
array([1, 2, 0])
sage: import numpy
sage: v.numpy(dtype=numpy.uint8)
array([1, 2, 0], dtype=uint8)
```

Passing a dtype of `None` will let numpy choose a native type, which can be more efficient but may have unintended consequences:

```
sage: v.numpy(dtype=None)
array([ 1.          ,  2.          ,  0.83333333])

sage: w = vector(ZZ, [0, 1, 2^63 - 1]); w
(0, 1, 9223372036854775807)
sage: wn = w.numpy(dtype=None); wn
array([ 0, 1, 9223372036854775807]...)
sage: wn.dtype
dtype('int64')
sage: w.dot_product(w)
85070591730234615847396907784232501250
sage: wn.dot(wn)
2
```

Numpy can give rather obscure errors; we wrap these to give a bit of context:

```
sage: vector([1, 1/2, QQ['x'].0]).numpy(dtype=float)
Traceback (most recent call last):
...
ValueError: Could not convert vector over Univariate Polynomial Ring in x over Rational Field
```

### `outer_product` (*right*)

Returns a matrix, the outer product of two vectors `self` and `right`.

INPUT:

- `right` - a vector (or free module element) of any size, whose elements are compatible (with regard to multiplication) with the elements of `self`.

OUTPUT:

The outer product of two vectors  $x$  and  $y$  (respectively `self` and `right`) can be described several ways. If we interpret  $x$  as a  $m \times 1$  matrix and interpret  $y$  as a  $1 \times n$  matrix, then the outer product is the  $m \times n$  matrix from the usual matrix product  $xy$ . Notice how this is the “opposite” in some ways from an inner product (which would require  $m = n$ ).

If we just consider vectors, use each entry of  $x$  to create a scalar multiples of the vector  $y$  and use these vectors as the rows of a matrix. Or use each entry of  $y$  to create a scalar multiples of  $x$  and use these vectors as the columns of a matrix.

EXAMPLES:



```

sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.outer_product(v)
[ 30  90 300]
[ 20  60 200]
[ 15  45 150]
[ 12  36 120]
sage: M = v.outer_product(u); M
[ 30  20  15  12]
[ 90  60  45  36]
[300 200 150 120]
sage: M.parent()
Full MatrixSpace of 3 by 4 dense matrices over Rational Field

```

The more general `sage.matrix.matrix2.tensor_product()` is an operation on a pair of matrices. If we construe a pair of vectors as a column vector and a row vector, then an outer product and a tensor product are identical. Thus *tensor<sub>p</sub>product* is a synonym for this method.

```

sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.tensor_product(v) == (u.column()).tensor_product(v.row())
True

```

The result is always a dense matrix, no matter if the two vectors are, or are not, dense.

```

sage: d = vector(ZZ, [4,5], sparse=False)
sage: s = vector(ZZ, [1,2,3], sparse=True)
sage: dd = d.outer_product(d)
sage: ds = d.outer_product(s)
sage: sd = s.outer_product(d)
sage: ss = s.outer_product(s)
sage: all([dd.is_dense(), ds.is_dense(), sd.is_dense(), ss.is_dense()])
True

```

Vectors with no entries do the right thing.

```

sage: v = vector(ZZ, [])
sage: z = v.outer_product(v)
sage: z.parent()
Full MatrixSpace of 0 by 0 dense matrices over Integer Ring

```

There is a fair amount of latitude in the value of the right vector, and the matrix that results can have entries from a new ring large enough to contain the result. If you know better, you can sometimes bring the result down to a less general ring.

```

sage: R.<t> = ZZ[]
sage: v = vector(R, [12, 24*t])
sage: w = vector(QQ, [1/2, 1/3, 1/4])
sage: op = v.outer_product(w)
sage: op
[ 6  4  3]
[12*t 8*t 6*t]
sage: op.base_ring()
Univariate Polynomial Ring in t over Rational Field
sage: m = op.change_ring(R); m
[ 6  4  3]
[12*t 8*t 6*t]
sage: m.base_ring()
Univariate Polynomial Ring in t over Integer Ring

```

But some inputs are not compatible, even if vectors.

```
sage: w = vector(GF(5), [1,2])
sage: v = vector(GF(7), [1,2,3,4])
sage: z = w.outer_product(v)
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for '*': 'Full MatrixSpace of 2 by 1 dense matrices'
```

And some inputs don't make any sense at all.

```
sage: w=vector(QQ, [5,10])
sage: z=w.outer_product(6)
Traceback (most recent call last):
...
TypeError: right operand in an outer product must be a vector, not an element of Integer Ring
```

### **pairwise\_product** (*right*)

Return the pairwise product of self and right, which is a vector of the products of the corresponding entries.

INPUT:

- right - vector of the same degree as self. It need not be in the same vector space as self, as long as the coefficients can be multiplied.

EXAMPLES:

```
sage: V = FreeModule(ZZ, 3)
sage: v = V([1,2,3])
sage: w = V([4,5,6])
sage: v.pairwise_product(w)
(4, 10, 18)
sage: sum(v.pairwise_product(w)) == v.dot_product(w)
True

sage: W = VectorSpace(GF(3), 3)
sage: w = W([0,1,2])
sage: w.pairwise_product(v)
(0, 2, 0)
sage: w.pairwise_product(v).parent()
Vector space of dimension 3 over Finite Field of size 3
```

Implicit coercion is well defined (regardless of order), so we get 2 even if we do the dot product in the other order.

```
sage: v.pairwise_product(w).parent()
Vector space of dimension 3 over Finite Field of size 3
```

TESTS:

```
sage: x, y = var('x, y')

sage: parent(vector(ZZ, [1,2]).pairwise_product(vector(ZZ, [1,2])))
Ambient free module of rank 2 over the principal ideal domain Integer Ring
sage: parent(vector(ZZ, [1,2]).pairwise_product(vector(QQ, [1,2])))
Vector space of dimension 2 over Rational Field
sage: parent(vector(QQ, [1,2]).pairwise_product(vector(ZZ, [1,2])))
Vector space of dimension 2 over Rational Field
sage: parent(vector(QQ, [1,2]).pairwise_product(vector(QQ, [1,2])))
Vector space of dimension 2 over Rational Field
```

```

sage: parent(vector(QQ, [1, 2, 3, 4]).pairwise_product(vector(ZZ['x'], [1, 2, 3, 4])))
Ambient free module of rank 4 over the principal ideal domain Univariate Polynomial Ring in
sage: parent(vector(ZZ[x], [1, 2, 3, 4]).pairwise_product(vector(QQ, [1, 2, 3, 4])))
Ambient free module of rank 4 over the principal ideal domain Univariate Polynomial Ring in

sage: parent(vector(QQ, [1, 2, 3, 4]).pairwise_product(vector(ZZ['x']['y'], [1, 2, 3, 4])))
Ambient free module of rank 4 over the integral domain Univariate Polynomial Ring in y over
sage: parent(vector(ZZ[x][y], [1, 2, 3, 4]).pairwise_product(vector(QQ, [1, 2, 3, 4])))
Ambient free module of rank 4 over the integral domain Univariate Polynomial Ring in y over

sage: parent(vector(QQ['x'], [1, 2, 3, 4]).pairwise_product(vector(ZZ['x']['y'], [1, 2, 3, 4])))
Ambient free module of rank 4 over the integral domain Univariate Polynomial Ring in y over
sage: parent(vector(ZZ[x][y], [1, 2, 3, 4]).pairwise_product(vector(QQ['x'], [1, 2, 3, 4])))
Ambient free module of rank 4 over the integral domain Univariate Polynomial Ring in y over

sage: parent(vector(QQ['y'], [1, 2, 3, 4]).pairwise_product(vector(ZZ['x']['y'], [1, 2, 3, 4])))
Ambient free module of rank 4 over the integral domain Univariate Polynomial Ring in y over
sage: parent(vector(ZZ[x][y], [1, 2, 3, 4]).pairwise_product(vector(QQ['y'], [1, 2, 3, 4])))
Ambient free module of rank 4 over the integral domain Univariate Polynomial Ring in y over

sage: parent(vector(ZZ['x'], [1, 2, 3, 4]).pairwise_product(vector(ZZ['y'], [1, 2, 3, 4])))
Traceback (most recent call last):
...
TypeError: no common canonical parent for objects with parents: 'Ambient free module of rank
sage: parent(vector(ZZ['x'], [1, 2, 3, 4]).pairwise_product(vector(QQ['y'], [1, 2, 3, 4])))
Traceback (most recent call last):
...
TypeError: no common canonical parent for objects with parents: 'Ambient free module of rank
sage: parent(vector(QQ['x'], [1, 2, 3, 4]).pairwise_product(vector(ZZ['y'], [1, 2, 3, 4])))
Traceback (most recent call last):
...
TypeError: no common canonical parent for objects with parents: 'Ambient free module of rank
sage: parent(vector(QQ['x'], [1, 2, 3, 4]).pairwise_product(vector(QQ['y'], [1, 2, 3, 4])))
Traceback (most recent call last):
...
TypeError: no common canonical parent for objects with parents: 'Ambient free module of rank
sage: v = vector({1: 1, 3: 2}) # test sparse vectors
sage: w = vector({0: 6, 3: -4})
sage: v.pairwise_product(w)
(0, 0, 0, -8)
sage: w.pairwise_product(v) == v.pairwise_product(w)
True

```

**plot** (*plot\_type=None*, *start=None*, *\*\*kws*)

INPUT:

• **plot\_type** - (default: 'arrow' if *v* has 3 or fewer components, otherwise 'step') type of plot.

Options are:

- 'arrow' to draw an arrow
- 'point' to draw a point at the coordinates specified by the vector
- 'step' to draw a step function representing the coordinates of the vector.

Both 'arrow' and 'point' raise exceptions if the vector has more than 3 dimensions.

• **start** - (default: origin in correct dimension) may be a tuple, list, or vector.

EXAMPLES:

The following both plot the given vector:

```
sage: v = vector(RDF, (1,2))
sage: A = plot(v)
sage: B = v.plot()
sage: A+B # should just show one vector
Graphics object consisting of 2 graphics primitives
```

Examples of the plot types:

```
sage: A = plot(v, plot_type='arrow')
sage: B = plot(v, plot_type='point', color='green', size=20)
sage: C = plot(v, plot_type='step') # calls v.plot_step()
sage: A+B+C
Graphics object consisting of 3 graphics primitives
```

You can use the optional arguments for `plot_step()`:

```
sage: eps = 0.1
sage: plot(v, plot_type='step', eps=eps, xmax=5, hue=0)
Graphics object consisting of 1 graphics primitive
```

Three-dimensional examples:

```
sage: v = vector(RDF, (1,2,1))
sage: plot(v) # defaults to an arrow plot
Graphics3d Object

sage: plot(v, plot_type='arrow')
Graphics3d Object

sage: from sage.plot.plot3d.shapes2 import frame3d
sage: plot(v, plot_type='point')+frame3d((0,0,0), v.list())
Graphics3d Object

sage: plot(v, plot_type='step') # calls v.plot_step()
Graphics object consisting of 1 graphics primitive

sage: plot(v, plot_type='step', eps=eps, xmax=5, hue=0)
Graphics object consisting of 1 graphics primitive
```

With greater than three coordinates, it defaults to a step plot:

```
sage: v = vector(RDF, (1,2,3,4))
sage: plot(v)
Graphics object consisting of 1 graphics primitive
```

One dimensional vectors are plotted along the horizontal axis of the coordinate plane:

```
sage: plot(vector([1]))
Graphics object consisting of 1 graphics primitive
```

An optional start argument may also be specified by a tuple, list, or vector:

```
sage: u = vector([1,2]); v = vector([2,5])
sage: plot(u, start=v)
Graphics object consisting of 1 graphics primitive
```

TESTS:

```

sage: u = vector([1,1]); v = vector([2,2,2]); z=(3,3,3)
sage: plot(u) #test when start=None
Graphics object consisting of 1 graphics primitive

sage: plot(u, start=v) #test when coordinate dimension mismatch exists
Traceback (most recent call last):
...
ValueError: vector coordinates are not of the same dimension
sage: P = plot(v, start=z) #test when start coordinates are passed as a tuple
sage: P = plot(v, start=list(z)) #test when start coordinates are passed as a list

```

**plot\_step** (*xmin=0, xmax=1, eps=None, res=None, connect=True, \*\*kws*)

INPUT:

- *xmin* - (default: 0) start x position to start plotting
- *xmax* - (default: 1) stop x position to stop plotting
- *eps* - (default: determined by *xmax*) we view this vector as defining a function at the points *xmin*, *xmin* + *eps*, *xmin* + 2\**eps*, ...,
- *res* - (default: all points) total number of points to include in the graph
- *connect* - (default: True) if True draws a line; otherwise draw a list of points.

EXAMPLES:

```

sage: eps=0.1
sage: v = vector(RDF, [sin(n*eps) for n in range(100)])
sage: v.plot_step(eps=eps, xmax=5, hue=0)
Graphics object consisting of 1 graphics primitive

```

**row** ()

Return a matrix with a single row and the same entries as the vector *self*.

OUTPUT:

A matrix over the same ring as the vector (or free module element), with a single row. The entries of the row are identical to those of the vector, and in the same order.

EXAMPLES:

```

sage: v = vector(ZZ, [1,2,3])
sage: w = v.row(); w
[1 2 3]
sage: w.parent()
Full MatrixSpace of 1 by 3 dense matrices over Integer Ring

sage: x = vector(FiniteField(13), [2,4,8,16])
sage: x.row()
[2 4 8 3]

```

There is more than one way to get one-row matrix from a vector, but the `row` method is more efficient than making a column and then taking a transpose. Notice that supplying a vector to the matrix constructor demonstrates Sage's preference for rows.

```

sage: x = vector(RDF, [sin(i*pi/20) for i in range(10)])
sage: x.row() == matrix(x)
True
sage: x.row() == x.column().transpose()
True

```

Sparse or dense implementations are preserved.

```
sage: d = vector(RR, [1.0, 2.0, 3.0])
sage: s = vector(CDF, {2:5.0+6.0*I})
sage: dm = d.row()
sage: sm = s.row()
sage: all([d.is_dense(), dm.is_dense(), s.is_sparse(), sm.is_sparse()])
True
```

TESTS:

The `row()` method will return a specified row of a matrix as a vector. So here are a couple of round-trips.

```
sage: A = matrix(ZZ, [[1, 2, 3]])
sage: A == A.row(0).row()
True
sage: v = vector(ZZ, [4, 5, 6])
sage: v == v.row().row(0)
True
```

And a very small corner case.

```
sage: v = vector(ZZ, [])
sage: w = v.row()
sage: w.parent()
Full MatrixSpace of 1 by 0 dense matrices over Integer Ring
```

**set** (*i*, *value*)

Like `__setitem__` but without type or bounds checking: *i* must satisfy  $0 \leq i < \text{self.degree}$  and *value* must be an element of the coordinate ring.

EXAMPLES:

```
sage: v = vector(SR, [1/2, 2/5, 0]); v
(1/2, 2/5, 0)
sage: v.set(2, pi); v
(1/2, 2/5, pi)
```

**set\_immutable** ()

Make this vector immutable. This operation can't be undone.

EXAMPLES:

```
sage: v = vector([1..5]); v
(1, 2, 3, 4, 5)
sage: v[1] = 10
sage: v.set_immutable()
sage: v[1] = 10
Traceback (most recent call last):
...
ValueError: vector is immutable; please change a copy instead (use copy())
```

**sparse\_vector** ()

Return sparse version of self. If self is sparse, just return self; otherwise, create and return correspond sparse vector.

EXAMPLES:

```
sage: vector([-1, 0, 3, 0, 0, 0]).sparse_vector().is_sparse()
True
sage: vector([-1, 0, 3, 0, 0, 0]).sparse_vector().is_sparse()
True
```

```
sage: vector([-1,0,3,0,0,0]).sparse_vector()
(-1, 0, 3, 0, 0, 0)
```

**subs** (*in\_dict=None*, *\*\*kws*)

EXAMPLES:

```
sage: var('a,b,d,e')
(a, b, d, e)
sage: v = vector([a, b, d, e])
sage: v.substitute(a=1)
(1, b, d, e)
sage: v.subs(a=b, b=d)
(b, d, d, e)
```

**support** ()

Return the integers  $i$  such that  $\text{self}[i] \neq 0$ . This is the same as the `nonzero_positions` function.

EXAMPLES:

```
sage: vector([-1,0,3,0,0,0,0.01]).support()
[0, 2, 6]
```

**tensor\_product** (*right*)

Returns a matrix, the outer product of two vectors `self` and `right`.

INPUT:

- `right` - a vector (or free module element) of any size, whose elements are compatible (with regard to multiplication) with the elements of `self`.

OUTPUT:

The outer product of two vectors  $x$  and  $y$  (respectively `self` and `right`) can be described several ways. If we interpret  $x$  as a  $m \times 1$  matrix and interpret  $y$  as a  $1 \times n$  matrix, then the outer product is the  $m \times n$  matrix from the usual matrix product  $xy$ . Notice how this is the “opposite” in some ways from an inner product (which would require  $m = n$ ).

If we just consider vectors, use each entry of  $x$  to create a scalar multiples of the vector  $y$  and use these vectors as the rows of a matrix. Or use each entry of  $y$  to create a scalar multiples of  $x$  and use these vectors as the columns of a matrix.

EXAMPLES:

```
sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.outer_product(v)
[ 30  90 300]
[ 20  60 200]
[ 15  45 150]
[ 12  36 120]
sage: M = v.outer_product(u); M
[ 30  20  15  12]
[ 90  60  45  36]
[300 200 150 120]
sage: M.parent()
Full MatrixSpace of 3 by 4 dense matrices over Rational Field
```

The more general `sage.matrix.matrix2.tensor_product()` is an operation on a pair of matrices. If we construe a pair of vectors as a column vector and a row vector, then an outer product and a

tensor product are identical. Thus *tensor<sub>p</sub>product* is a synonym for this method.

```
sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.tensor_product(v) == (u.column()).tensor_product(v.row())
True
```

The result is always a dense matrix, no matter if the two vectors are, or are not, dense.

```
sage: d = vector(ZZ, [4,5], sparse=False)
sage: s = vector(ZZ, [1,2,3], sparse=True)
sage: dd = d.outer_product(d)
sage: ds = d.outer_product(s)
sage: sd = s.outer_product(d)
sage: ss = s.outer_product(s)
sage: all([dd.is_dense(), ds.is_dense(), sd.is_dense(), ss.is_dense()])
True
```

Vectors with no entries do the right thing.

```
sage: v = vector(ZZ, [])
sage: z = v.outer_product(v)
sage: z.parent()
Full MatrixSpace of 0 by 0 dense matrices over Integer Ring
```

There is a fair amount of latitude in the value of the `right` vector, and the matrix that results can have entries from a new ring large enough to contain the result. If you know better, you can sometimes bring the result down to a less general ring.

```
sage: R.<t> = ZZ[]
sage: v = vector(R, [12, 24*t])
sage: w = vector(QQ, [1/2, 1/3, 1/4])
sage: op = v.outer_product(w)
sage: op
[ 6 4 3]
[12*t 8*t 6*t]
sage: op.base_ring()
Univariate Polynomial Ring in t over Rational Field
sage: m = op.change_ring(R); m
[ 6 4 3]
[12*t 8*t 6*t]
sage: m.base_ring()
Univariate Polynomial Ring in t over Integer Ring
```

But some inputs are not compatible, even if vectors.

```
sage: w = vector(GF(5), [1,2])
sage: v = vector(GF(7), [1,2,3,4])
sage: z = w.outer_product(v)
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for '*': 'Full MatrixSpace of 2 by 1 dense matrices over GF(5)' and 'Full MatrixSpace of 4 by 1 dense matrices over GF(7)'
```

And some inputs don't make any sense at all.

```
sage: w=vector(QQ, [5,10])
sage: z=w.outer_product(6)
Traceback (most recent call last):
...
TypeError: right operand in an outer product must be a vector, not an element of Integer Ring
```



**class** `sage.modules.free_module_element.FreeModuleElement_generic_dense`  
 Bases: `sage.modules.free_module_element.FreeModuleElement`

A generic dense element of a free module.

TESTS:

```
sage: V = ZZ^3
sage: loads(dumps(V)) == V
True
sage: v = V.0
sage: loads(dumps(v)) == v
True
sage: v = (QQ['x']^3).0
sage: loads(dumps(v)) == v
True

sage: v = vector([1, 2/3, pi])
sage: v == v
True

sage: v = vector(RR, [1, 2/3, pi])
sage: v.set_immutable()
sage: isinstance(hash(v), int)
True
```

**function** (\*args)

Returns a vector over a callable symbolic expression ring.

EXAMPLES:

```
sage: x,y=var('x,y')
sage: v=vector([x,y,x*sin(y)])
sage: w=v.function([x,y]); w
(x, y) |--> (x, y, x*sin(y))
sage: w.coordinate_ring()
Callable function ring with arguments (x, y)
sage: w(1,2)
(1, 2, sin(2))
sage: w(2,1)
(2, 1, 2*sin(1))
sage: w(y=1,x=2)
(2, 1, 2*sin(1))

sage: x,y=var('x,y')
sage: v=vector([x,y,x*sin(y)])
sage: w=v.function([x]); w
x |--> (x, y, x*sin(y))
sage: w.coordinate_ring()
Callable function ring with argument x
sage: w(4)
(4, y, 4*sin(y))
```

**list** (copy=True)

Return list of elements of self.

INPUT:

- copy – bool, return list of underlying entries

EXAMPLES:

```
sage: P.<x,y,z> = QQ[]
sage: v = vector([x,y,z])
sage: type(v)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_dense'>
sage: a = v.list(); a
[x, y, z]
sage: a[0] = x*y; v
(x, y, z)
sage: a = v.list(copy=False); a
[x, y, z]
sage: a[0] = x*y; v
(x*y, y, z)
```

**class** sage.modules.free\_module\_element.**FreeModuleElement\_generic\_sparse**  
Bases: sage.modules.free\_module\_element.FreeModuleElement

A generic sparse free module element is a dictionary with keys ints  $i$  and entries in the base ring.

TESTS:

```
sage: v = vector([1,2/3,pi], sparse=True)
sage: v.set_immutable()
sage: isinstance(hash(v), int)
True
```

Pickling works:

```
sage: v = FreeModule(ZZ, 3, sparse=True).0
sage: loads(dumps(v)) == v
True
sage: v = FreeModule(Integers(8)['x,y'], 5, sparse=True).1
sage: loads(dumps(v)) - v
(0, 0, 0, 0, 0)

sage: a = vector([-1,0,1/1], sparse=True); b = vector([-1/1,0,0], sparse=True)
sage: a.parent()
Sparse vector space of dimension 3 over Rational Field
sage: b - a
(0, 0, -1)
sage: (b-a).dict()
{2: -1}
```

**denominator()**

Return the least common multiple of the denominators of the entries of self.

EXAMPLES:

```
sage: v = vector([1/2,2/5,3/14], sparse=True)
sage: v.denominator()
70
```

**dict** (*copy=True*)

Return dictionary of nonzero entries of self.

INPUT:

- *copy* – bool (default: True)

OUTPUT:

- Python dictionary

EXAMPLES:

```
sage: v = vector([0,0,0,0,1/2,0,3/14], sparse=True)
sage: v.dict()
{4: 1/2, 6: 3/14}
```

**hamming\_weight()**

Returns the number of positions  $i$  such that  $\text{self}[i] \neq 0$ .

EXAMPLES:

```
sage: v = vector({1: 1, 3: -2})
sage: w = vector({1: 4, 3: 2})
sage: v+w
(0, 5, 0, 0)
sage: (v+w).hamming_weight()
1
```

**iteritems()**

Return iterator over the entries of self.

EXAMPLES:

```
sage: v = vector([1,2/3,pi], sparse=True)
sage: v.iteritems()
<dictionary-itemiterator object at ...>
sage: list(v.iteritems())
[(0, 1), (1, 2/3), (2, pi)]
```

**list (copy=True)**

Return list of elements of self.

INPUT:

- copy – ignored for sparse vectors

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: M = FreeModule(R, 3, sparse=True) * (1/x)
sage: v = M([-x^2, 3/x, 0])
sage: type(v)
<type 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: a = v.list()
sage: a
[-x^2, 3/x, 0]
sage: [parent(c) for c in a]
[Fraction Field of Univariate Polynomial Ring in x over Rational Field,
 Fraction Field of Univariate Polynomial Ring in x over Rational Field,
 Fraction Field of Univariate Polynomial Ring in x over Rational Field]
```

**nonzero\_positions()**

Returns the list of numbers  $i$  such that  $\text{self}[i] \neq 0$ .

EXAMPLES:

```
sage: v = vector({1: 1, 3: -2})
sage: w = vector({1: 4, 3: 2})
sage: v+w
(0, 5, 0, 0)
sage: (v+w).nonzero_positions()
[1]
```

`sage.modules.free_module_element.free_module_element` (*arg0*, *arg1=None*, *arg2=None*,  
*sparse=None*)

Return a vector or free module element with specified entries.

#### CALL FORMATS:

This constructor can be called in several different ways. In each case, `sparse=True` or `sparse=False` can be supplied as an option. `free_module_element()` is an alias for `vector()`.

1. `vector(object)`
2. `vector(ring, object)`
3. `vector(object, ring)`
4. `vector(ring, degree, object)`
5. `vector(ring, degree)`

#### INPUT:

- `object` – a list, dictionary, or other iterable containing the entries of the vector, including any object that is palatable to the `Sequence` constructor
- `ring` – a base ring (or field) for the vector space or free module, which contains all of the elements
- `degree` – an integer specifying the number of entries in the vector or free module element
- `sparse` – boolean, whether the result should be a sparse vector

In call format 4, an error is raised if the `degree` does not match the length of `object` so this call can provide some safeguards. Note however that using this format when `object` is a dictionary is unlikely to work properly.

#### OUTPUT:

An element of the ambient vector space or free module with the given base ring and implied or specified dimension or rank, containing the specified entries and with correct degree.

In call format 5, no entries are specified, so the element is populated with all zeros.

If the `sparse` option is not supplied, the output will generally have a dense representation. The exception is if `object` is a dictionary, then the representation will be sparse.

#### EXAMPLES:

```
sage: v = vector([1, 2, 3]); v
(1, 2, 3)
sage: v.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: v = vector([1, 2, 3/5]); v
(1, 2, 3/5)
sage: v.parent()
Vector space of dimension 3 over Rational Field
```

All entries must *canonically* coerce to some common ring:

```
sage: v = vector([17, GF(11)(5), 19/3]); v
Traceback (most recent call last):
...
TypeError: unable to find a common ring for all elements

sage: v = vector([17, GF(11)(5), 19]); v
(6, 5, 8)
sage: v.parent()
Vector space of dimension 3 over Finite Field of size 11
sage: v = vector([17, GF(11)(5), 19], QQ); v
```

```

(17, 5, 19)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector((1,2,3), QQ); v
(1, 2, 3)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(QQ, (1,2,3)); v
(1, 2, 3)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(vector([1,2,3])); v
(1, 2, 3)
sage: v.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring

```

You can also use `free_module_element`, which is the same as `vector`.

```

sage: free_module_element([1/3, -4/5])
(1/3, -4/5)

```

We make a vector mod 3 out of a vector over  $\mathbb{Z}$ .

```

sage: vector(vector([1,2,3]), GF(3))
(1, 2, 0)

```

The degree of a vector may be specified:

```

sage: vector(QQ, 4, [1,1/2,1/3,1/4])
(1, 1/2, 1/3, 1/4)

```

But it is an error if the degree and size of the list of entries are mismatched:

```

sage: vector(QQ, 5, [1,1/2,1/3,1/4])
Traceback (most recent call last):
...
ValueError: incompatible degrees in vector constructor

```

Providing no entries populates the vector with zeros, but of course, you must specify the degree since it is not implied. Here we use a finite field as the base ring.

```

sage: w = vector(FiniteField(7), 4); w
(0, 0, 0, 0)
sage: w.parent()
Vector space of dimension 4 over Finite Field of size 7

```

The fastest method to construct a zero vector is to call the `zero_vector()` method directly on a free module or vector space, since `vector(...)` must do a small amount of type checking. Almost as fast as the `zero_vector()` method is the `zero_vector()` constructor, which defaults to the integers.

```

sage: vector(ZZ, 5)          # works fine
(0, 0, 0, 0, 0)
sage: (ZZ^5).zero_vector()   # very tiny bit faster
(0, 0, 0, 0, 0)
sage: zero_vector(ZZ, 5)     # similar speed to vector(...)
(0, 0, 0, 0, 0)
sage: z = zero_vector(5); z
(0, 0, 0, 0, 0)
sage: z.parent()
Ambient free module of rank 5 over

```

the principal ideal domain Integer Ring

Here we illustrate the creation of sparse vectors by using a dictionary.

```
sage: vector({1:1.1, 3:3.14})
(0.0000000000000000, 1.1000000000000000, 0.0000000000000000, 3.1400000000000000)
```

With no degree given, a dictionary of entries implicitly declares a degree by the largest index (key) present. So you can provide a terminal element (perhaps a zero?) to set the degree. But it is probably safer to just include a degree in your construction.

```
sage: v = vector(QQ, {0:1/2, 4:-6, 7:0}); v
(1/2, 0, 0, 0, -6, 0, 0, 0)
sage: v.degree()
8
sage: v.is_sparse()
True
sage: w = vector(QQ, 8, {0:1/2, 4:-6})
sage: w == v
True
```

It is an error to specify a negative degree.

```
sage: vector(RR, -4, [1.0, 2.0, 3.0, 4.0])
Traceback (most recent call last):
...
ValueError: cannot specify the degree of a vector as a negative integer (-4)
```

It is an error to create a zero vector but not provide a ring as the first argument.

```
sage: vector('junk', 20)
Traceback (most recent call last):
...
TypeError: first argument must be base ring of zero vector, not junk
```

And it is an error to specify an index in a dictionary that is greater than or equal to a requested degree.

```
sage: vector(ZZ, 10, {3:4, 7:-2, 10:637})
Traceback (most recent call last):
...
ValueError: dictionary of entries has a key (index) exceeding the requested degree
```

A 1-dimensional numpy array of type float or complex may be passed to vector. Unless an explicit ring is given, the result will be a vector in the appropriate dimensional vector space over the real double field or the complex double field. The data in the array must be contiguous, so column-wise slices of numpy matrices will raise an exception.

```
sage: import numpy
sage: x = numpy.random.randn(10)
sage: y = vector(x)
sage: parent(y)
Vector space of dimension 10 over Real Double Field
sage: parent(vector(RDF, x))
Vector space of dimension 10 over Real Double Field
sage: parent(vector(CDF, x))
Vector space of dimension 10 over Complex Double Field
sage: parent(vector(RR, x))
Vector space of dimension 10 over Real Field with 53 bits of precision
sage: v = numpy.random.randn(10) * numpy.complex(0,1)
sage: w = vector(v)
```

```
sage: parent(w)
Vector space of dimension 10 over Complex Double Field
```

Multi-dimensional arrays are not supported:

```
sage: import numpy as np
sage: a = np.array([[1, 2, 3], [4, 5, 6]], np.float64)
sage: vector(a)
Traceback (most recent call last):
...
TypeError: cannot convert 2-dimensional array to a vector
```

If any of the arguments to `vector` have Python type `int`, `long`, `real`, or `complex`, they will first be coerced to the appropriate Sage objects. This fixes [trac ticket #3847](#).

```
sage: v = vector([int(0)]); v
(0)
sage: v[0].parent()
Integer Ring
sage: v = vector(range(10)); v
(0, 1, 2, 3, 4, 5, 6, 7, 8, 9)
sage: v[3].parent()
Integer Ring
sage: v = vector([float(23.4), int(2), complex(2+7*I), long(1)]); v
(23.4, 2.0, 2.0 + 7.0*I, 1.0)
sage: v[1].parent()
Complex Double Field
```

If the argument is a vector, it doesn't change the base ring. This fixes [trac ticket #6643](#):

```
sage: K.<sqrt3> = QuadraticField(3)
sage: u = vector(K, (1/2, sqrt3/2) )
sage: vector(u).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3
sage: v = vector(K, (0, 1) )
sage: vector(v).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3
```

Constructing a vector from a numpy array behaves as expected:

```
sage: import numpy
sage: a=numpy.array([1,2,3])
sage: v=vector(a); v
(1, 2, 3)
sage: parent(v)
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

Complex numbers can be converted naturally to a sequence of length 2. And then to a vector.

```
sage: c = CDF(2 + 3*I)
sage: v = vector(c); v
(2.0, 3.0)
```

A generator, or other iterable, may also be supplied as input. Anything that can be converted to a `Sequence` is a possible input.

```
sage: type(i^2 for i in range(3))
<type 'generator'>
sage: v = vector(i^2 for i in range(3)); v
(0, 1, 4)
```

An empty list, without a ring given, will default to the integers.

```
sage: x = vector([]); x
()
sage: x.parent()
Ambient free module of rank 0 over the principal ideal domain Integer Ring
```

`sage.modules.free_module_element.is_FreeModuleElement(x)`

EXAMPLES:

```
sage: sage.modules.free_module_element.is_FreeModuleElement(0)
False
sage: sage.modules.free_module_element.is_FreeModuleElement(vector([1, 2, 3]))
True
```

`sage.modules.free_module_element.make_FreeModuleElement_generic_dense(parent, entries, de-  
gree)`

EXAMPLES:

```
sage: sage.modules.free_module_element.make_FreeModuleElement_generic_dense(QQ^3, [1, 2, -3/7], 3)
(1, 2, -3/7)
```

`sage.modules.free_module_element.make_FreeModuleElement_generic_dense_v1(parent, entries, de-  
gree, is_mutable)`

EXAMPLES:

```
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_dense_v1(QQ^3, [1, 2, -3/7], 3, True)
(1, 2, -3/7)
sage: v[0] = 10; v
(10, 2, -3/7)
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_dense_v1(QQ^3, [1, 2, -3/7], 3, False)
(1, 2, -3/7)
sage: v[0] = 10
Traceback (most recent call last):
...
ValueError: vector is immutable; please change a copy instead (use copy())
```

`sage.modules.free_module_element.make_FreeModuleElement_generic_sparse(parent, entries, de-  
gree)`

EXAMPLES:

```
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_sparse(QQ^3, {2: 5/2}, 3)
(0, 0, 5/2)
```



```
sage.modules.free_module_element.make_FreeModuleElement_generic_sparse_v1(parent,
                                                                              en-
                                                                              tries,
                                                                              de-
                                                                              gree,
                                                                              is_mutable)
```

**EXAMPLES:**

```
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_sparse_v1(QQ^3, {2:5/2,
(0, 0, 5/2)
sage: v.is_mutable()
False
```

```
sage.modules.free_module_element.prepare(v, R, degree=None)
```

Converts an object describing elements of a vector into a list of entries in a common ring.

**INPUT:**

- **v** - a dictionary with non-negative integers as keys, or a list or other object that can be converted by the Sequence constructor
- **R** - a ring containing all the entries, possibly given as None
- **degree** - a requested size for the list when the input is a dictionary, otherwise ignored

**OUTPUT:**

A pair.

The first item is a list of the values specified in the object **v**. If the object is a dictionary, entries are placed in the list according to the indices that were their keys in the dictionary, and the remainder of the entries are zero. The value of **degree** is assumed to be larger than any index provided in the dictionary and will be used as the number of entries in the returned list.

The second item returned is a ring that contains all of the entries in the list. If **R** is given, the entries are coerced in. Otherwise a common ring is found. For more details, see the Sequence object. When **v** has no elements and **R** is None, the ring returned is the integers.

**EXAMPLES:**

```
sage: from sage.modules.free_module_element import prepare
sage: prepare([1,2/3,5],None)
([1, 2/3, 5], Rational Field)

sage: prepare([1,2/3,5],RR)
([1.000000000000000, 0.666666666666667, 5.00000000000000], Real Field with 53 bits of precision)

sage: prepare({1:4, 3:-2}, ZZ, 6)
([0, 4, 0, -2, 0, 0], Integer Ring)

sage: prepare({3:1, 5:3}, QQ, 6)
([0, 0, 0, 1, 0, 3], Rational Field)

sage: prepare([1,2/3,'10',5],RR)
([1.000000000000000, 0.666666666666667, 10.0000000000000, 5.00000000000000], Real Field with 53 b

sage: prepare({},QQ, 0)
([], Rational Field)

sage: prepare([1,2/3,'10',5],None)
Traceback (most recent call last):
```

```
...
TypeError: unable to find a common ring for all elements
```

Some objects can be converted to sequences even if they are not always thought of as sequences.

```
sage: c = CDF(2+3*I)
sage: prepare(c, None)
([2.0, 3.0], Real Double Field)
```

This checks a bug listed at Trac #10595. Without good evidence for a ring, the default is the integers.

```
sage: prepare([], None)
([], Integer Ring)
```

`sage.modules.free_module_element.random_vector(ring, degree=None, *args, **kwargs)`  
Returns a vector (or module element) with random entries.

INPUT:

- ring - default: `ZZ` - the base ring for the entries
- degree - a non-negative integer for the number of entries in the vector
- sparse - default: `False` - whether to use a sparse implementation
- args, kwds - additional arguments and keywords are passed to the `random_element()` method of the ring

OUTPUT:

A vector, or free module element, with `degree` elements from `ring`, chosen randomly from the ring according to the ring's `random_element()` method.

---

**Note:** See below for examples of how random elements are generated by some common base rings.

---

EXAMPLES:

First, module elements over the integers. The default distribution is tightly clustered around -1, 0, 1. Uniform distributions can be specified by giving bounds, though the upper bound is never met. See `sage.rings.integer_ring.IntegerRing_class.random_element()` for several other variants.

```
sage: random_vector(10)
(-8, 2, 0, 0, 1, -1, 2, 1, -95, -1)
```

```
sage: sorted(random_vector(20))
[-12, -6, -4, -4, -2, -2, -2, -1, -1, -1, 0, 0, 0, 0, 0, 1, 1, 1, 4, 5]
```

```
sage: random_vector(ZZ, 20, x=4)
(2, 0, 3, 0, 1, 0, 2, 0, 2, 3, 0, 3, 1, 2, 2, 2, 1, 3, 2, 3)
```

```
sage: random_vector(ZZ, 20, x=-20, y=100)
(43, 47, 89, 31, 56, -20, 23, 52, 13, 53, 49, -12, -2, 94, -1, 95, 60, 83, 28, 63)
```

```
sage: random_vector(ZZ, 20, distribution="1/n")
(0, -1, -2, 0, -1, -2, 0, 0, 27, -1, 1, 1, 0, 2, -1, 1, -1, -2, -1, 3)
```

If the ring is not specified, the default is the integers, and parameters for the random distribution may be passed without using keywords. This is a random vector with 20 entries uniformly distributed between -20 and 100.

```
sage: random_vector(20, -20, 100)
(70, 19, 98, 2, -18, 88, 36, 66, 76, 52, 82, 99, 55, -17, 82, -15, 36, 28, 79, 18)
```

Now over the rationals. Note that bounds on the numerator and denominator may be specified. See `sage.rings.rational_field.RationalField.random_element()` for documentation.

```
sage: random_vector(QQ, 10)
(0, -1, -4/3, 2, 0, -13, 2/3, 0, -4/5, -1)
```

```
sage: random_vector(QQ, 10, num_bound = 15, den_bound = 5)
(-12/5, 9/4, -13/3, -1/3, 1, 5/4, 4, 1, -15, 10/3)
```

Inexact rings may be used as well. The reals have uniform distributions, with the range  $(-1, 1)$  as the default. More at: `sage.rings.real_mpfr.RealField_class.random_element()`

```
sage: random_vector(RR, 5)
(0.248997268533725, -0.112200126330480, 0.776829203293064, -0.899146461031406, 0.534465018743125)
```

```
sage: random_vector(RR, 5, min = 8, max = 14)
(8.43260944052606, 8.34129413391087, 8.92391495103829, 11.5784799413416, 11.0973561568002)
```

Any ring with a `random_element()` method may be used.

```
sage: F = FiniteField(23)
sage: hasattr(F, 'random_element')
True
sage: random_vector(F, 10)
(21, 6, 5, 2, 6, 2, 18, 9, 9, 7)
```

The default implementation is a dense representation, equivalent to setting `sparse=False`.

```
sage: v = random_vector(10)
sage: v.is_sparse()
False
```

```
sage: w = random_vector(ZZ, 20, sparse=True)
sage: w.is_sparse()
True
```

Inputs get checked before constructing the vector.

```
sage: random_vector('junk')
Traceback (most recent call last):
...
TypeError: degree of a random vector must be an integer, not None

sage: random_vector('stuff', 5)
Traceback (most recent call last):
...
TypeError: elements of a vector, or module element, must come from a ring, not stuff

sage: random_vector(ZZ, -9)
Traceback (most recent call last):
...
ValueError: degree of a random vector must be non-negative, not -9
```

`sage.modules.free_module_element.vector(arg0, arg1=None, arg2=None, sparse=None)`

Return a vector or free module element with specified entries.

CALL FORMATS:

This constructor can be called in several different ways. In each case, `sparse=True` or `sparse=False` can be supplied as an option. `free_module_element()` is an alias for `vector()`.

1. `vector(object)`
2. `vector(ring, object)`
3. `vector(object, ring)`
4. `vector(ring, degree, object)`
5. `vector(ring, degree)`

INPUT:

- `object` – a list, dictionary, or other iterable containing the entries of the vector, including any object that is palatable to the `Sequence` constructor
- `ring` – a base ring (or field) for the vector space or free module, which contains all of the elements
- `degree` – an integer specifying the number of entries in the vector or free module element
- `sparse` – boolean, whether the result should be a sparse vector

In call format 4, an error is raised if the `degree` does not match the length of `object` so this call can provide some safeguards. Note however that using this format when `object` is a dictionary is unlikely to work properly.

OUTPUT:

An element of the ambient vector space or free module with the given base ring and implied or specified dimension or rank, containing the specified entries and with correct degree.

In call format 5, no entries are specified, so the element is populated with all zeros.

If the `sparse` option is not supplied, the output will generally have a dense representation. The exception is if `object` is a dictionary, then the representation will be sparse.

EXAMPLES:

```
sage: v = vector([1, 2, 3]); v
(1, 2, 3)
sage: v.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: v = vector([1, 2, 3/5]); v
(1, 2, 3/5)
sage: v.parent()
Vector space of dimension 3 over Rational Field
```

All entries must *canonically* coerce to some common ring:

```
sage: v = vector([17, GF(11)(5), 19/3]); v
Traceback (most recent call last):
...
TypeError: unable to find a common ring for all elements

sage: v = vector([17, GF(11)(5), 19]); v
(6, 5, 8)
sage: v.parent()
Vector space of dimension 3 over Finite Field of size 11
sage: v = vector([17, GF(11)(5), 19], QQ); v
(17, 5, 19)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector((1, 2, 3), QQ); v
(1, 2, 3)
```

```

sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(QQ, (1,2,3)); v
(1, 2, 3)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(vector([1,2,3])); v
(1, 2, 3)
sage: v.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring

```

You can also use `free_module_element`, which is the same as `vector`.

```

sage: free_module_element([1/3, -4/5])
(1/3, -4/5)

```

We make a vector mod 3 out of a vector over  $\mathbb{Z}$ .

```

sage: vector(vector([1,2,3]), GF(3))
(1, 2, 0)

```

The degree of a vector may be specified:

```

sage: vector(QQ, 4, [1,1/2,1/3,1/4])
(1, 1/2, 1/3, 1/4)

```

But it is an error if the degree and size of the list of entries are mismatched:

```

sage: vector(QQ, 5, [1,1/2,1/3,1/4])
Traceback (most recent call last):
...
ValueError: incompatible degrees in vector constructor

```

Providing no entries populates the vector with zeros, but of course, you must specify the degree since it is not implied. Here we use a finite field as the base ring.

```

sage: w = vector(FiniteField(7), 4); w
(0, 0, 0, 0)
sage: w.parent()
Vector space of dimension 4 over Finite Field of size 7

```

The fastest method to construct a zero vector is to call the `zero_vector()` method directly on a free module or vector space, since `vector(...)` must do a small amount of type checking. Almost as fast as the `zero_vector()` method is the `zero_vector()` constructor, which defaults to the integers.

```

sage: vector(ZZ, 5)           # works fine
(0, 0, 0, 0, 0)
sage: (ZZ^5).zero_vector()    # very tiny bit faster
(0, 0, 0, 0, 0)
sage: zero_vector(ZZ, 5)      # similar speed to vector(...)
(0, 0, 0, 0, 0)
sage: z = zero_vector(5); z
(0, 0, 0, 0, 0)
sage: z.parent()
Ambient free module of rank 5 over
the principal ideal domain Integer Ring

```

Here we illustrate the creation of sparse vectors by using a dictionary.

```
sage: vector({1:1.1, 3:3.14})
(0.0000000000000000, 1.1000000000000000, 0.0000000000000000, 3.1400000000000000)
```

With no degree given, a dictionary of entries implicitly declares a degree by the largest index (key) present. So you can provide a terminal element (perhaps a zero?) to set the degree. But it is probably safer to just include a degree in your construction.

```
sage: v = vector(QQ, {0:1/2, 4:-6, 7:0}); v
(1/2, 0, 0, 0, -6, 0, 0, 0)
sage: v.degree()
8
sage: v.is_sparse()
True
sage: w = vector(QQ, 8, {0:1/2, 4:-6})
sage: w == v
True
```

It is an error to specify a negative degree.

```
sage: vector(RR, -4, [1.0, 2.0, 3.0, 4.0])
Traceback (most recent call last):
...
ValueError: cannot specify the degree of a vector as a negative integer (-4)
```

It is an error to create a zero vector but not provide a ring as the first argument.

```
sage: vector('junk', 20)
Traceback (most recent call last):
...
TypeError: first argument must be base ring of zero vector, not junk
```

And it is an error to specify an index in a dictionary that is greater than or equal to a requested degree.

```
sage: vector(ZZ, 10, {3:4, 7:-2, 10:637})
Traceback (most recent call last):
...
ValueError: dictionary of entries has a key (index) exceeding the requested degree
```

A 1-dimensional numpy array of type float or complex may be passed to vector. Unless an explicit ring is given, the result will be a vector in the appropriate dimensional vector space over the real double field or the complex double field. The data in the array must be contiguous, so column-wise slices of numpy matrices will raise an exception.

```
sage: import numpy
sage: x = numpy.random.randn(10)
sage: y = vector(x)
sage: parent(y)
Vector space of dimension 10 over Real Double Field
sage: parent(vector(RDF, x))
Vector space of dimension 10 over Real Double Field
sage: parent(vector(CDF, x))
Vector space of dimension 10 over Complex Double Field
sage: parent(vector(RR, x))
Vector space of dimension 10 over Real Field with 53 bits of precision
sage: v = numpy.random.randn(10) * numpy.complex(0,1)
sage: w = vector(v)
sage: parent(w)
Vector space of dimension 10 over Complex Double Field
```

Multi-dimensional arrays are not supported:

```
sage: import numpy as np
sage: a = np.array([[1, 2, 3], [4, 5, 6]], np.float64)
sage: vector(a)
Traceback (most recent call last):
...
TypeError: cannot convert 2-dimensional array to a vector
```

If any of the arguments to `vector` have Python type `int`, `long`, `real`, or `complex`, they will first be coerced to the appropriate Sage objects. This fixes [trac ticket #3847](#).

```
sage: v = vector([int(0)]); v
(0)
sage: v[0].parent()
Integer Ring
sage: v = vector(range(10)); v
(0, 1, 2, 3, 4, 5, 6, 7, 8, 9)
sage: v[3].parent()
Integer Ring
sage: v = vector([float(23.4), int(2), complex(2+7*I), long(1)]); v
(23.4, 2.0, 2.0 + 7.0*I, 1.0)
sage: v[1].parent()
Complex Double Field
```

If the argument is a vector, it doesn't change the base ring. This fixes [trac ticket #6643](#):

```
sage: K.<sqrt3> = QuadraticField(3)
sage: u = vector(K, (1/2, sqrt3/2))
sage: vector(u).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3
sage: v = vector(K, (0, 1))
sage: vector(v).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3
```

Constructing a vector from a numpy array behaves as expected:

```
sage: import numpy
sage: a=numpy.array([1,2,3])
sage: v=vector(a); v
(1, 2, 3)
sage: parent(v)
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

Complex numbers can be converted naturally to a sequence of length 2. And then to a vector.

```
sage: c = CDF(2 + 3*I)
sage: v = vector(c); v
(2.0, 3.0)
```

A generator, or other iterable, may also be supplied as input. Anything that can be converted to a `Sequence` is a possible input.

```
sage: type(i^2 for i in range(3))
<type 'generator'>
sage: v = vector(i^2 for i in range(3)); v
(0, 1, 4)
```

An empty list, without a ring given, will default to the integers.

```
sage: x = vector([]); x
()
sage: x.parent()
Ambient free module of rank 0 over the principal ideal domain Integer Ring
```

`sage.modules.free_module_element.zero_vector(arg0, arg1=None)`

Returns a vector or free module element with a specified number of zeros.

CALL FORMATS:

1. `zero_vector(degree)`
2. `zero_vector(ring, degree)`

INPUT:

- `degree` - the number of zero entries in the vector or free module element
- `ring` - default `ZZ` - the base ring of the vector space or module containing the constructed zero vector

OUTPUT:

A vector or free module element with `degree` entries, all equal to zero and belonging to the ring if specified. If no ring is given, a free module element over `ZZ` is returned.

EXAMPLES:

A zero vector over the field of rationals.

```
sage: v = zero_vector(QQ, 5); v
(0, 0, 0, 0, 0)
sage: v.parent()
Vector space of dimension 5 over Rational Field
```

A free module zero element.

```
sage: w = zero_vector(Integers(6), 3); w
(0, 0, 0)
sage: w.parent()
Ambient free module of rank 3 over Ring of integers modulo 6
```

If no ring is given, the integers are used.

```
sage: u = zero_vector(9); u
(0, 0, 0, 0, 0, 0, 0, 0, 0)
sage: u.parent()
Ambient free module of rank 9 over the principal ideal domain Integer Ring
```

Non-integer degrees produce an error.

```
sage: zero_vector(5.6)
Traceback (most recent call last):
...
TypeError: Attempt to coerce non-integral RealNumber to Integer
```

Negative degrees also give an error.

```
sage: zero_vector(-3)
Traceback (most recent call last):
...
ValueError: rank (=-3) must be nonnegative
```

Garbage instead of a ring will be recognized as such.



```
sage: zero_vector(x^2, 5)
Traceback (most recent call last):
...
TypeError: first argument must be a ring
```



## FREE MODULES OF FINITE RANK

The class `FiniteRankFreeModule` implements free modules of finite rank over a commutative ring.

A *free module of finite rank* over a commutative ring  $R$  is a module  $M$  over  $R$  that admits a *finite basis*, i.e. a finite family of linearly independent generators. Since  $R$  is commutative, it has the invariant basis number property, so that the rank of the free module  $M$  is defined uniquely, as the cardinality of any basis of  $M$ .

No distinguished basis of  $M$  is assumed. On the contrary, many bases can be introduced on the free module along with change-of-basis rules (as module automorphisms). Each module element has then various representations over the various bases.

---

**Note:** The class `FiniteRankFreeModule` does not inherit from class `FreeModule_generic` nor from class `CombinatorialFreeModule`, since both classes deal with modules with a *distinguished basis* (see details *below*). Accordingly, the class `FiniteRankFreeModule` inherits directly from the generic class `Parent` with the category set to `Modules` (and not to `ModulesWithBasis`).

---

### Todo

- implement submodules
  - create a `FreeModules` category (cf. the *TODO* statement in the documentation of `Modules`: *Implement a “FreeModules(R)” category, when so prompted by a concrete use case*)
- 

### AUTHORS:

- Eric Gourgoulhon, Michal Bejger (2014-2015): initial version

### REFERENCES:

- Chap. 10 of R. Godement : *Algebra*, Hermann (Paris) / Houghton Mifflin (Boston) (1968)
- Chap. 3 of S. Lang : *Algebra*, 3rd ed., Springer (New York) (2002)

### EXAMPLES:

Let us define a free module of rank 2 over  $\mathbb{Z}$ :

```
sage: M = FiniteRankFreeModule(ZZ, 2, name='M') ; M
Rank-2 free module M over the Integer Ring
sage: M.category()
Category of modules over Integer Ring
```

We introduce a first basis on M:

```
sage: e = M.basis('e') ; e
Basis (e_0,e_1) on the Rank-2 free module M over the Integer Ring
```

The elements of the basis are of course module elements:

```
sage: e[0]
Element e_0 of the Rank-2 free module M over the Integer Ring
sage: e[1]
Element e_1 of the Rank-2 free module M over the Integer Ring
sage: e[0].parent()
Rank-2 free module M over the Integer Ring
```

We define a module element by its components w.r.t. basis e:

```
sage: u = M([2,-3], basis=e, name='u')
sage: u.display(e)
u = 2 e_0 - 3 e_1
```

Module elements can also be created by arithmetic expressions:

```
sage: v = -2*u + 4*e[0] ; v
Element of the Rank-2 free module M over the Integer Ring
sage: v.display(e)
6 e_1
sage: u == 2*e[0] - 3*e[1]
True
```

We define a second basis on M from a family of linearly independent elements:

```
sage: f = M.basis('f', from_family=(e[0]-e[1], -2*e[0]+3*e[1])) ; f
Basis (f_0,f_1) on the Rank-2 free module M over the Integer Ring
sage: f[0].display(e)
f_0 = e_0 - e_1
sage: f[1].display(e)
f_1 = -2 e_0 + 3 e_1
```

We may of course express the elements of basis e in terms of basis f:

```
sage: e[0].display(f)
e_0 = 3 f_0 + f_1
sage: e[1].display(f)
e_1 = 2 f_0 + f_1
```

as well as any module element:

```
sage: u.display(f)
u = -f_1
sage: v.display(f)
12 f_0 + 6 f_1
```

The two bases are related by a module automorphism:

```
sage: a = M.change_of_basis(e,f) ; a
Automorphism of the Rank-2 free module M over the Integer Ring
sage: a.parent()
General linear group of the Rank-2 free module M over the Integer Ring
sage: a.matrix(e)
[ 1 -2]
[-1  3]
```

Let us check that basis f is indeed the image of basis e by a:

```
sage: f[0] == a(e[0])
True
sage: f[1] == a(e[1])
True
```

The reverse change of basis is of course the inverse automorphism:

```
sage: M.change_of_basis(f,e) == a^(-1)
True
```

We introduce a new module element via its components w.r.t. basis  $f$ :

```
sage: v = M([2,4], basis=f, name='v')
sage: v.display(f)
v = 2 f_0 + 4 f_1
```

The sum of the two module elements  $u$  and  $v$  can be performed even if they have been defined on different bases, thanks to the known relation between the two bases:

```
sage: s = u + v ; s
Element u+v of the Rank-2 free module M over the Integer Ring
```

We can display the result in either basis:

```
sage: s.display(e)
u+v = -4 e_0 + 7 e_1
sage: s.display(f)
u+v = 2 f_0 + 3 f_1
```

Tensor products of elements are implemented:

```
sage: t = u*v ; t
Type-(2,0) tensor u*v on the Rank-2 free module M over the Integer Ring
sage: t.parent()
Free module of type-(2,0) tensors on the
Rank-2 free module M over the Integer Ring
sage: t.display(e)
u*v = -12 e_0*e_0 + 20 e_0*e_1 + 18 e_1*e_0 - 30 e_1*e_1
sage: t.display(f)
u*v = -2 f_1*f_0 - 4 f_1*f_1
```

We can access to tensor components w.r.t. to a given basis via the square bracket operator:

```
sage: t[e,0,1]
20
sage: t[f,1,0]
-2
sage: u[e,0]
2
sage: u[e,:]
[2, -3]
sage: u[f,:]
[0, -1]
```

The parent of the automorphism  $a$  is the group  $GL(M)$ , but  $a$  can also be considered as a tensor of type  $(1, 1)$  on  $M$ :

```
sage: a.parent()
General linear group of the Rank-2 free module M over the Integer Ring
```

```
sage: a.tensor_type()
(1, 1)
sage: a.display(e)
e_0*e^0 - 2 e_0*e^1 - e_1*e^0 + 3 e_1*e^1
sage: a.display(f)
f_0*f^0 - 2 f_0*f^1 - f_1*f^0 + 3 f_1*f^1
```

As such, we can form its tensor product with  $t$ , yielding a tensor of type  $(3, 1)$ :

```
sage: t*a
Type-(3,1) tensor on the Rank-2 free module M over the Integer Ring
sage: (t*a).display(e)
-12 e_0*e_0*e_0*e^0 + 24 e_0*e_0*e_0*e^1 + 12 e_0*e_0*e_1*e^0
- 36 e_0*e_0*e_1*e^1 + 20 e_0*e_1*e_0*e^0 - 40 e_0*e_1*e_0*e^1
- 20 e_0*e_1*e_1*e^0 + 60 e_0*e_1*e_1*e^1 + 18 e_1*e_0*e_0*e^0
- 36 e_1*e_0*e_0*e^1 - 18 e_1*e_0*e_1*e^0 + 54 e_1*e_0*e_1*e^1
- 30 e_1*e_1*e_0*e^0 + 60 e_1*e_1*e_0*e^1 + 30 e_1*e_1*e_1*e^0
- 90 e_1*e_1*e_1*e^1
```

The parent of  $t \otimes a$  is itself a free module of finite rank over  $\mathbb{Z}$ :

```
sage: T = (t*a).parent() ; T
Free module of type-(3,1) tensors on the Rank-2 free module M over the
Integer Ring
sage: T.base_ring()
Integer Ring
sage: T.rank()
16
```

### Differences between `FiniteRankFreeModule` and `FreeModule` (or `VectorSpace`)

To illustrate the differences, let us create two free modules of rank 3 over  $\mathbb{Z}$ , one with `FiniteRankFreeModule` and the other one with `FreeModule`:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M') ; M
Rank-3 free module M over the Integer Ring
sage: N = FreeModule(ZZ, 3) ; N
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

The main difference is that `FreeModule` returns a free module with a distinguished basis, while `FiniteRankFreeModule` does not:

```
sage: N.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
sage: M.bases()
[]
sage: M.print_bases()
No basis has been defined on the Rank-3 free module M over the Integer Ring
```

This is also revealed by the category of each module:

```
sage: M.category()
Category of modules over Integer Ring
sage: N.category()
Category of modules with basis over (euclidean domains and infinite enumerated sets)
```

In other words, the module created by `FreeModule` is actually  $\mathbf{Z}^3$ , while, in the absence of any distinguished basis, no *canonical* isomorphism relates the module created by `FiniteRankFreeModule` to  $\mathbf{Z}^3$ :

```
sage: N is ZZ^3
True
sage: M is ZZ^3
False
sage: M == ZZ^3
False
```

Because it is  $\mathbf{Z}^3$ , `N` is unique, while there may be various modules of the same rank over the same ring created by `FiniteRankFreeModule`; they are then distinguished by their names (actually by the complete sequence of arguments of `FiniteRankFreeModule`):

```
sage: N1 = FreeModule(ZZ, 3) ; N1
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: N1 is N # FreeModule(ZZ, 3) is unique
True
sage: M1 = FiniteRankFreeModule(ZZ, 3, name='M_1') ; M1
Rank-3 free module M_1 over the Integer Ring
sage: M1 is M # M1 and M are different rank-3 modules over ZZ
False
sage: M1b = FiniteRankFreeModule(ZZ, 3, name='M_1') ; M1b
Rank-3 free module M_1 over the Integer Ring
sage: M1b is M1 # because M1b and M1 have the same name
True
```

As illustrated above, various bases can be introduced on the module created by `FiniteRankFreeModule`:

```
sage: e = M.basis('e') ; e
Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring
sage: f = M.basis('f', from_family=(-e[0], e[1]-e[2], -2*e[1]+3*e[2])) ; f
Basis (f_0,f_1,f_2) on the Rank-3 free module M over the Integer Ring
sage: M.bases()
[Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring,
 Basis (f_0,f_1,f_2) on the Rank-3 free module M over the Integer Ring]
```

Each element of a basis is accessible via its index:

```
sage: e[0]
Element e_0 of the Rank-3 free module M over the Integer Ring
sage: e[0].parent()
Rank-3 free module M over the Integer Ring
sage: f[1]
Element f_1 of the Rank-3 free module M over the Integer Ring
sage: f[1].parent()
Rank-3 free module M over the Integer Ring
```

while on module `N`, the element of the (unique) basis is accessible directly from the module symbol:

```
sage: N.0
(1, 0, 0)
sage: N.1
```

```
(0, 1, 0)
sage: N.0.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

The arithmetic of elements is similar; the difference lies in the display: a basis has to be specified for elements of  $M$ , while elements of  $N$  are displayed directly as elements of  $\mathbb{Z}^3$ :

```
sage: u = 2*e[0] - 3*e[2] ; u
Element of the Rank-3 free module M over the Integer Ring
sage: u.display(e)
2 e_0 - 3 e_2
sage: u.display(f)
-2 f_0 - 6 f_1 - 3 f_2
sage: u[e,:]
[2, 0, -3]
sage: u[f,:]
[-2, -6, -3]
sage: v = 2*N.0 - 3*N.2 ; v
(2, 0, -3)
```

For the case of  $M$ , in order to avoid to specify the basis if the user is always working with the same basis (e.g. only one basis has been defined), the concept of *default basis* has been introduced:

```
sage: M.default_basis()
Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring
sage: M.print_bases()
Bases defined on the Rank-3 free module M over the Integer Ring:
- (e_0,e_1,e_2) (default basis)
- (f_0,f_1,f_2)
```

This is different from the *distinguished basis* of  $N$ : it simply means that the mention of the basis can be omitted in function arguments:

```
sage: u.display() # equivalent to u.display(e)
2 e_0 - 3 e_2
sage: u[:] # equivalent to u[e,:]
[2, 0, -3]
```

At any time, the default basis can be changed:

```
sage: M.set_default_basis(f)
sage: u.display()
-2 f_0 - 6 f_1 - 3 f_2
```

Another difference between `FiniteRankFreeModule` and `FreeModule` is that for the former the range of indices can be specified (by default, it starts from 0):

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M', start_index=1) ; M
Rank-3 free module M over the Integer Ring
sage: e = M.basis('e') ; e # compare with (e_0,e_1,e_2) above
Basis (e_1,e_2,e_3) on the Rank-3 free module M over the Integer Ring
sage: e[1], e[2], e[3]
(Element e_1 of the Rank-3 free module M over the Integer Ring,
 Element e_2 of the Rank-3 free module M over the Integer Ring,
 Element e_3 of the Rank-3 free module M over the Integer Ring)
```

All the above holds for `VectorSpace` instead of `FreeModule`: the object created by `VectorSpace` is actually a Cartesian power of the base field:



```

sage: V = VectorSpace(QQ, 3) ; V
Vector space of dimension 3 over Rational Field
sage: V.category()
Category of vector spaces with basis over quotient fields
sage: V is QQ^3
True
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]

```

To create a vector space without any distinguished basis, one has to use `FiniteRankFreeModule`:

```

sage: V = FiniteRankFreeModule(QQ, 3, name='V') ; V
3-dimensional vector space V over the Rational Field
sage: V.category()
Category of vector spaces over Rational Field
sage: V.bases()
[]
sage: V.print_bases()
No basis has been defined on the 3-dimensional vector space V over the
Rational Field

```

The class `FiniteRankFreeModule` has been created for the needs of the [SageManifolds project](#), where free modules do not have any distinguished basis. Too kinds of free modules occur in the context of differentiable manifolds (see [here](#) for more details):

- the tangent vector space at any point of the manifold
- the set of vector fields on a parallelizable open subset  $U$  of the manifold, which is a free module over the algebra of scalar fields on  $U$ .

For instance, without any specific coordinate choice, no basis can be distinguished in a tangent space.

On the other side, the modules created by `FreeModule` have much more algebraic functionalities than those created by `FiniteRankFreeModule`. In particular, submodules have not been implemented yet in `FiniteRankFreeModule`. Moreover, modules resulting from `FreeModule` are tailored to the specific kind of their base ring:

- free module over a commutative ring that is not an integral domain ( $\mathbb{Z}/6\mathbb{Z}$ ):

```

sage: R = IntegerModRing(6) ; R
Ring of integers modulo 6
sage: FreeModule(R, 3)
Ambient free module of rank 3 over Ring of integers modulo 6
sage: type(FreeModule(R, 3))
<class 'sage.modules.free_module.FreeModule_ambient_with_category'>

```

- free module over an integral domain that is not principal ( $\mathbb{Z}[X]$ ):

```

sage: R.<X> = ZZ[] ; R
Univariate Polynomial Ring in X over Integer Ring
sage: FreeModule(R, 3)
Ambient free module of rank 3 over the integral domain Univariate
Polynomial Ring in X over Integer Ring
sage: type(FreeModule(R, 3))
<class 'sage.modules.free_module.FreeModule_ambient_domain_with_category'>

```

- free module over a principal ideal domain ( $\mathbb{Z}$ ):

```
sage: R = ZZ ; R
Integer Ring
sage: FreeModule(R, 3)
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: type(FreeModule(R, 3))
<class 'sage.modules.free_module.FreeModule_ambient_pid_with_category'>
```

On the contrary, all objects constructed with `FiniteRankFreeModule` belong to the same class:

```
sage: R = IntegerModRing(6)
sage: type(FiniteRankFreeModule(R, 3))
<class 'sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule_with_category'>
sage: R.<X> = ZZ[]
sage: type(FiniteRankFreeModule(R, 3))
<class 'sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule_with_category'>
sage: R = ZZ
sage: type(FiniteRankFreeModule(R, 3))
<class 'sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule_with_category'>
```

### Differences between `FiniteRankFreeModule` and `CombinatorialFreeModule`

An alternative to construct free modules in Sage is `CombinatorialFreeModule`. However, as `FreeModule`, it leads to a module with a distinguished basis:

```
sage: N = CombinatorialFreeModule(ZZ, [1, 2, 3]) ; N
Free module generated by {1, 2, 3} over Integer Ring
sage: N.category()
Category of finite dimensional modules with basis over Integer Ring
```

The distinguished basis is returned by the method `basis()`:

```
sage: b = N.basis() ; b
Finite family {1: B[1], 2: B[2], 3: B[3]}
sage: b[1]
B[1]
sage: b[1].parent()
Free module generated by {1, 2, 3} over Integer Ring
```

For the free module `M` created above with `FiniteRankFreeModule`, the method `basis` has at least one argument: the symbol string that specifies which basis is required:

```
sage: e = M.basis('e') ; e
Basis (e_1, e_2, e_3) on the Rank-3 free module M over the Integer Ring
sage: e[1]
Element e_1 of the Rank-3 free module M over the Integer Ring
sage: e[1].parent()
Rank-3 free module M over the Integer Ring
```

The arithmetic of elements is similar:

```
sage: u = 2*e[1] - 5*e[3] ; u
Element of the Rank-3 free module M over the Integer Ring
sage: v = 2*b[1] - 5*b[3] ; v
2*B[1] - 5*B[3]
```

One notices that elements of  $N$  are displayed directly in terms of their expansions on the distinguished basis. For elements of  $M$ , one has to use the method `display()` in order to specify the basis:

```
sage: u.display(e)
2 e_1 - 5 e_3
```

The components on the basis are returned by the square bracket operator for  $M$  and by the method `coefficient` for  $N$ :

```
sage: [u[e,i] for i in {1,2,3}]
[2, 0, -5]
sage: u[e,:] # a shortcut for the above
[2, 0, -5]
sage: [v.coefficient(i) for i in {1,2,3}]
[2, 0, -5]
```

```
class sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule(ring,
                                                                           rank,
                                                                           name=None,
                                                                           la-
                                                                           tex_name=None,
                                                                           start_index=0,
                                                                           out-
                                                                           put_formatter=None)

Bases:      sage.structure.unique_representation.UniqueRepresentation,
           sage.structure.parent.Parent
```

Free module of finite rank over a commutative ring.

A *free module of finite rank* over a commutative ring  $R$  is a module  $M$  over  $R$  that admits a *finite basis*, i.e. a finite family of linearly independent generators. Since  $R$  is commutative, it has the invariant basis number property, so that the rank of the free module  $M$  is defined uniquely, as the cardinality of any basis of  $M$ .

No distinguished basis of  $M$  is assumed. On the contrary, many bases can be introduced on the free module along with change-of-basis rules (as module automorphisms). Each module element has then various representations over the various bases.

---

**Note:** The class `FiniteRankFreeModule` does not inherit from class `FreeModule_generic` nor from class `CombinatorialFreeModule`, since both classes deal with modules with a *distinguished basis* (see details [above](#)). Moreover, following the recommendation exposed in trac ticket [#16427](#) the class `FiniteRankFreeModule` inherits directly from `Parent` (with the category set to `Modules`) and not from the Cython class `Module`.

---

The class `FiniteRankFreeModule` is a Sage *parent* class, the corresponding *element* class being `FiniteRankFreeModuleElement`.

INPUT:

- `ring` – commutative ring  $R$  over which the free module is constructed
- `rank` – positive integer; rank of the free module
- `name` – (default: `None`) string; name given to the free module
- `latex_name` – (default: `None`) string; LaTeX symbol to denote the freemodule; if none is provided, it is set to `name`
- `start_index` – (default: 0) integer; lower bound of the range of indices in bases defined on the free module

- `output_formatter` – (default: None) function or unbound method called to format the output of the tensor components; `output_formatter` must take 1 or 2 arguments: the first argument must be an element of the ring  $R$  and the second one, if any, some format specification

EXAMPLES:

Free module of rank 3 over  $\mathbb{Z}$ :

```
sage: FiniteRankFreeModule._clear_cache() # for doctests only
sage: M = FiniteRankFreeModule(ZZ, 3) ; M
Rank-3 free module over the Integer Ring
sage: M = FiniteRankFreeModule(ZZ, 3, name='M') ; M # declaration with a name
Rank-3 free module M over the Integer Ring
sage: M.category()
Category of modules over Integer Ring
sage: M.base_ring()
Integer Ring
sage: M.rank()
3
```

If the base ring is a field, the free module is in the category of vector spaces:

```
sage: V = FiniteRankFreeModule(QQ, 3, name='V') ; V
3-dimensional vector space V over the Rational Field
sage: V.category()
Category of vector spaces over Rational Field
```

The LaTeX output is adjusted via the parameter `latex_name`:

```
sage: latex(M) # the default is the symbol provided in the string ``name``
M
sage: M = FiniteRankFreeModule(ZZ, 3, name='M', latex_name=r'\mathcal{M}')
sage: latex(M)
\mathcal{M}
```

The free module  $M$  has no distinguished basis:

```
sage: M in ModulesWithBasis(ZZ)
False
sage: M in Modules(ZZ)
True
```

In particular, no basis is initialized at the module construction:

```
sage: M.print_bases()
No basis has been defined on the Rank-3 free module M over the Integer Ring
sage: M.bases()
[]
```

Bases have to be introduced by means of the method `basis()`, the first defined basis being considered as the *default basis*, meaning it can be skipped in function arguments required a basis (this can be changed by means of the method `set_default_basis()`):

```
sage: e = M.basis('e') ; e
Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring
sage: M.default_basis()
Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring
```

A second basis can be created from a family of linearly independent elements expressed in terms of basis  $e$ :

```
sage: f = M.basis('f', from_family=(-e[0], e[1]+e[2], 2*e[1]+3*e[2]))
sage: f
```

```

Basis (f_0,f_1,f_2) on the Rank-3 free module M over the Integer Ring
sage: M.print_bases()
Bases defined on the Rank-3 free module M over the Integer Ring:
- (e_0,e_1,e_2) (default basis)
- (f_0,f_1,f_2)
sage: M.bases()
[Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring,
Basis (f_0,f_1,f_2) on the Rank-3 free module M over the Integer Ring]

```

M is a *parent* object, whose elements are instances of `FiniteRankFreeModuleElement` (actually a dynamically generated subclass of it):

```

sage: v = M.an_element() ; v
Element of the Rank-3 free module M over the Integer Ring
sage: from sage.tensor.modules.free_module_tensor import FiniteRankFreeModuleElement
sage: isinstance(v, FiniteRankFreeModuleElement)
True
sage: v in M
True
sage: M.is_parent_of(v)
True
sage: v.display() # expansion w.r.t. the default basis (e)
e_0 + e_1 + e_2
sage: v.display(f)
-f_0 + f_1

```

The test suite of the category of modules is passed:

```
sage: TestSuite(M).run()
```

Constructing an element of M from (the integer) 0 yields the zero element of M:

```

sage: M(0)
Element zero of the Rank-3 free module M over the Integer Ring
sage: M(0) is M.zero()
True

```

Non-zero elements are constructed by providing their components in a given basis:

```

sage: v = M([-1,0,3]) ; v # components in the default basis (e)
Element of the Rank-3 free module M over the Integer Ring
sage: v.display() # expansion w.r.t. the default basis (e)
-e_0 + 3 e_2
sage: v.display(f)
f_0 - 6 f_1 + 3 f_2
sage: v = M([-1,0,3], basis=f) ; v # components in a specific basis
Element of the Rank-3 free module M over the Integer Ring
sage: v.display(f)
-f_0 + 3 f_2
sage: v.display()
e_0 + 6 e_1 + 9 e_2
sage: v = M([-1,0,3], basis=f, name='v') ; v
Element v of the Rank-3 free module M over the Integer Ring
sage: v.display(f)
v = -f_0 + 3 f_2
sage: v.display()
v = e_0 + 6 e_1 + 9 e_2

```

An alternative is to construct the element from an empty list of components and to set the nonzero components

afterwards:

```
sage: v = M([], name='v')
sage: v[e,0] = -1
sage: v[e,2] = 3
sage: v.display(e)
v = -e_0 + 3 e_2
```

Indices on the free module, such as indices labelling the element of a basis, are provided by the generator method `irange()`. By default, they range from 0 to the module's rank minus one:

```
sage: for i in M.irange(): print i,
0 1 2
```

This can be changed via the parameter `start_index` in the module construction:

```
sage: M1 = FiniteRankFreeModule(ZZ, 3, name='M', start_index=1)
sage: for i in M1.irange(): print i,
1 2 3
```

The parameter `output_formatter` in the constructor of the free module is used to set the output format of tensor components:

```
sage: N = FiniteRankFreeModule(QQ, 3, output_formatter=Rational.numerical_approx)
sage: e = N.basis('e')
sage: v = N([1/3, 0, -2], basis=e)
sage: v[e,:]
[0.3333333333333333, 0.0000000000000000, -2.0000000000000000]
sage: v.display(e) # default format (53 bits of precision)
0.3333333333333333 e_0 - 2.0000000000000000 e_2
sage: v.display(e, format_spec=10) # 10 bits of precision
0.33 e_0 - 2.0 e_2
```

### Element

alias of `FiniteRankFreeModuleElement`

**alternating\_form**(*degree*, *name=None*, *latex\_name=None*)

Construct an alternating form on the free module.

INPUT:

- *degree* – the degree of the alternating form (i.e. its tensor rank)
- *name* – (default: `None`) string; name given to the alternating form
- *latex\_name* – (default: `None`) string; LaTeX symbol to denote the alternating form; if none is provided, the LaTeX symbol is set to *name*

OUTPUT:

- instance of `FreeModuleAltForm`

EXAMPLES:

Alternating forms on a rank-3 module:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: a = M.alternating_form(2, 'a') ; a
Alternating form a of degree 2 on the
Rank-3 free module M over the Integer Ring
```

The nonzero components in a given basis have to be set in a second step, thereby fully specifying the alternating form:

```

sage: e = M.basis('e') ; e
Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring
sage: a.set_comp(e)[0,1] = 2
sage: a.set_comp(e)[1,2] = -3
sage: a.display(e)
a = 2 e^0/\e^1 - 3 e^1/\e^2

```

An alternating form of degree 1 is a linear form:

```

sage: a = M.alternating_form(1, 'a') ; a
Linear form a on the Rank-3 free module M over the Integer Ring

```

To construct such a form, it is preferable to call the method `linear_form()` instead:

```

sage: a = M.linear_form('a') ; a
Linear form a on the Rank-3 free module M over the Integer Ring

```

See `FreeModuleAltForm` for more documentation.

**automorphism** (*matrix=None, basis=None, name=None, latex\_name=None*)

Construct a module automorphism of `self`.

Denoting `self` by  $M$ , an automorphism of `self` is an element of the general linear group  $GL(M)$ .

INPUT:

- `matrix` – (default: `None`) matrix of size  $\text{rank}(M) \times \text{rank}(M)$  representing the automorphism with respect to `basis`; this entry can actually be any material from which a matrix of elements of `self` base ring can be constructed; the *columns* of `matrix` must be the components w.r.t. `basis` of the images of the elements of `basis`. If `matrix` is `None`, the automorphism has to be initialized afterwards by method `set_comp()` or via the operator `[]`.
- `basis` – (default: `None`) basis of `self` defining the matrix representation; if `None` the default basis of `self` is assumed.
- `name` – (default: `None`) string; name given to the automorphism
- `latex_name` – (default: `None`) string; LaTeX symbol to denote the automorphism; if none is provided, the LaTeX symbol is set to `name`

OUTPUT:

- instance of `FreeModuleAutomorphism`

EXAMPLES:

Automorphism of a rank-2 free  $\mathbb{Z}$ -module:

```

sage: M = FiniteRankFreeModule(ZZ, 2, name='M')
sage: e = M.basis('e')
sage: a = M.automorphism(matrix=[[1,2],[1,3]], basis=e, name='a') ; a
Automorphism a of the Rank-2 free module M over the Integer Ring
sage: a.parent()
General linear group of the Rank-2 free module M over the Integer Ring
sage: a.matrix(e)
[1 2]
[1 3]

```

An automorphism is a tensor of type (1,1):

```

sage: a.tensor_type()
(1, 1)

```

```
sage: a.display(e)
a = e_0*e^0 + 2 e_0*e^1 + e_1*e^0 + 3 e_1*e^1
```

The automorphism components can be specified in a second step, as components of a type-(1,1) tensor:

```
sage: a1 = M.automorphism(name='a')
sage: a1[e,:] = [[1,2],[1,3]]
sage: a1.matrix(e)
[1 2]
[1 3]
sage: a1 == a
True
```

Component by component specification:

```
sage: a2 = M.automorphism(name='a')
sage: a2[0,0] = 1 # component set in the module's default basis (e)
sage: a2[0,1] = 2
sage: a2[1,0] = 1
sage: a2[1,1] = 3
sage: a2.matrix(e)
[1 2]
[1 3]
sage: a2 == a
True
```

See `FreeModuleAutomorphism` for more documentation.

#### **bases()**

Return the list of bases that have been defined on the free module `self`.

Use the method `print_bases()` to get a formatted output with more information.

OUTPUT:

- list of instances of class `FreeModuleBasis`

EXAMPLES:

Bases on a rank-3 free module:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M_3', start_index=1)
sage: M.bases()
[]
sage: e = M.basis('e')
sage: M.bases()
[Basis (e_1,e_2,e_3) on the Rank-3 free module M_3 over the Integer Ring]
sage: f = M.basis('f')
sage: M.bases()
[Basis (e_1,e_2,e_3) on the Rank-3 free module M_3 over the Integer Ring,
Basis (f_1,f_2,f_3) on the Rank-3 free module M_3 over the Integer Ring]
```

#### **basis(symbol, latex\_symbol=None, from\_family=None)**

Define or return a basis of the free module `self`.

Let  $M$  denotes the free module `self` and  $n$  its rank.

The basis can be defined from a set of  $n$  linearly independent elements of  $M$  by means of the argument `from_family`. If `from_family` is not specified, the basis is created from scratch and, at this stage, is unrelated to bases that could have been defined previously on  $M$ . It can be related afterwards by means of the method `set_change_of_basis()`.



If the basis specified by the given symbol already exists, it is simply returned, whatever the value of the arguments `latex_symbol` or `from_family`.

Note that another way to construct a basis of `self` is to use the method `new_basis()` on an existing basis, with the automorphism relating the two bases as an argument.

INPUT:

- `symbol` – string; a letter (of a few letters) to denote a generic element of the basis
- `latex_symbol` – (default: `None`) string; symbol to denote a generic element of the basis; if `None`, the value of `symbol` is used
- `from_family` – (default: `None`) a tuple of  $n$  linearly independent elements of the free module `self` ( $n$  being the rank of `self`)

OUTPUT:

- instance of `FreeModuleBasis` representing a basis on `self`

EXAMPLES:

Bases on a rank-3 free module:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: e = M.basis('e') ; e
Basis (e_0,e_1,e_2) on the Rank-3 free module M over the Integer Ring
sage: e[0]
Element e_0 of the Rank-3 free module M over the Integer Ring
sage: latex(e)
\left(e_0,e_1,e_2\right)
```

The LaTeX symbol can be set explicitly, as the second argument of `basis()`:

```
sage: eps = M.basis('eps', r'\epsilon') ; eps
Basis (eps_0,eps_1,eps_2) on the Rank-3 free module M
over the Integer Ring
sage: latex(eps)
\left(\epsilon_0,\epsilon_1,\epsilon_2\right)
```

If the provided symbol is that of an already defined basis, the latter is returned (no new basis is created):

```
sage: M.basis('e') is e
True
sage: M.basis('eps') is eps
True
```

The individual elements of the basis are labelled according the parameter `start_index` provided at the free module construction:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M', start_index=1)
sage: e = M.basis('e') ; e
Basis (e_1,e_2,e_3) on the Rank-3 free module M over the Integer Ring
sage: e[1]
Element e_1 of the Rank-3 free module M over the Integer Ring
```

Construction of a basis from a family of linearly independent module elements:

```
sage: f1 = -e[2]
sage: f2 = 4*e[1] + 3*e[3]
sage: f3 = 7*e[1] + 5*e[3]
sage: f = M.basis('f', from_family=(f1,f2,f3))
sage: f[1].display()
```

```

f_1 = -e_2
sage: f[2].display()
f_2 = 4 e_1 + 3 e_3
sage: f[3].display()
f_3 = 7 e_1 + 5 e_3

```

The change-of-basis automorphisms have been registered:

```

sage: M.change_of_basis(e, f).matrix(e)
[ 0  4  7]
[-1  0  0]
[ 0  3  5]
sage: M.change_of_basis(f, e).matrix(e)
[ 0 -1  0]
[-5  0  7]
[ 3  0 -4]
sage: M.change_of_basis(f, e) == M.change_of_basis(e, f).inverse()
True

```

Check of the change-of-basis  $e \rightarrow f$ :

```

sage: a = M.change_of_basis(e, f) ; a
Automorphism of the Rank-3 free module M over the Integer Ring
sage: all( f[i] == a(e[i]) for i in M.irange() )
True

```

For more documentation on bases see `FreeModuleBasis`.

#### **change\_of\_basis** (*basis1*, *basis2*)

Return a module automorphism linking two bases defined on the free module `self`.

If the automorphism has not been recorded yet (in the internal dictionary `self._basis_changes`), it is computed by transitivity, i.e. by performing products of recorded changes of basis.

INPUT:

- `basis1` – a basis of `self`, denoted  $(e_i)$  below
- `basis2` – a basis of `self`, denoted  $(f_i)$  below

OUTPUT:

- instance of `FreeModuleAutomorphism` describing the automorphism  $P$  that relates the basis  $(e_i)$  to the basis  $(f_i)$  according to  $f_i = P(e_i)$

EXAMPLES:

Changes of basis on a rank-2 free module:

```

sage: FiniteRankFreeModule._clear_cache_() # for doctests only
sage: M = FiniteRankFreeModule(ZZ, 2, name='M', start_index=1)
sage: e = M.basis('e')
sage: f = M.basis('f', from_family=(e[1]+2*e[2], e[1]+3*e[2]))
sage: P = M.change_of_basis(e, f) ; P
Automorphism of the Rank-2 free module M over the Integer Ring
sage: P.matrix(e)
[1 1]
[2 3]

```

Note that the columns of this matrix contain the components of the elements of basis  $f$  w.r.t. to basis  $e$ :

```
sage: f[1].display(e)
f_1 = e_1 + 2 e_2
sage: f[2].display(e)
f_2 = e_1 + 3 e_2
```

The change of basis is cached:

```
sage: P is M.change_of_basis(e, f)
True
```

Check of the change-of-basis automorphism:

```
sage: f[1] == P(e[1])
True
sage: f[2] == P(e[2])
True
```

Check of the reverse change of basis:

```
sage: M.change_of_basis(f, e) == P^(-1)
True
```

We have of course:

```
sage: M.change_of_basis(e, e)
Identity map of the Rank-2 free module M over the Integer Ring
sage: M.change_of_basis(e, e) is M.identity_map()
True
```

Let us introduce a third basis on M:

```
sage: h = M.basis('h', from_family=(3*e[1]+4*e[2], 5*e[1]+7*e[2]))
```

The change of basis  $e \rightarrow h$  has been recorded directly from the definition of  $h$ :

```
sage: Q = M.change_of_basis(e, h) ; Q.matrix(e)
[3 5]
[4 7]
```

The change of basis  $f \rightarrow h$  is computed by transitivity, i.e. from the changes of basis  $f \rightarrow e$  and  $e \rightarrow h$ :

```
sage: R = M.change_of_basis(f, h) ; R
Automorphism of the Rank-2 free module M over the Integer Ring
sage: R.matrix(e)
[-1 2]
[-2 3]
sage: R.matrix(f)
[ 5 8]
[-2 -3]
```

Let us check that  $R$  is indeed the change of basis  $f \rightarrow h$ :

```
sage: h[1] == R(f[1])
True
sage: h[2] == R(f[2])
True
```

A related check is:

```
sage: R == Q*P^(-1)
True
```

**default\_basis()**

Return the default basis of the free module *self*.

The *default basis* is simply a basis whose name can be skipped in methods requiring a basis as an argument. By default, it is the first basis introduced on the module. It can be changed by the method `set_default_basis()`.

OUTPUT:

•instance of `FreeModuleBasis`

EXAMPLES:

At the module construction, no default basis is assumed:

```
sage: M = FiniteRankFreeModule(ZZ, 2, name='M', start_index=1)
```

```
sage: M.default_basis()
```

```
No default basis has been defined on the
Rank-2 free module M over the Integer Ring
```

The first defined basis becomes the default one:

```
sage: e = M.basis('e') ; e
```

```
Basis (e_1,e_2) on the Rank-2 free module M over the Integer Ring
```

```
sage: M.default_basis()
```

```
Basis (e_1,e_2) on the Rank-2 free module M over the Integer Ring
```

```
sage: f = M.basis('f') ; f
```

```
Basis (f_1,f_2) on the Rank-2 free module M over the Integer Ring
```

```
sage: M.default_basis()
```

```
Basis (e_1,e_2) on the Rank-2 free module M over the Integer Ring
```

**dual()**

Return the dual module of *self*.

EXAMPLE:

Dual of a free module over **Z**:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
```

```
sage: M.dual()
```

```
Dual of the Rank-3 free module M over the Integer Ring
```

```
sage: latex(M.dual())
```

```
 $M^*$ 
```

The dual is a free module of the same rank as *M*:

```
sage: isinstance(M.dual(), FiniteRankFreeModule)
```

```
True
```

```
sage: M.dual().rank()
```

```
3
```

It is formed by alternating forms of degree 1, i.e. linear forms:

```
sage: M.dual() is M.dual_exterior_power(1)
```

```
True
```

```
sage: M.dual().an_element()
```

```
Linear form on the Rank-3 free module M over the Integer Ring
```

```
sage: a = M.linear_form()
```

```
sage: a in M.dual()
```

```
True
```

The elements of a dual basis belong of course to the dual module:

```
sage: e = M.basis('e')
sage: e.dual_basis()[0] in M.dual()
True
```

**dual\_exterior\_power**(*p*)

Return the  $p$ -th exterior power of the dual of `self`.

If  $M$  stands for the free module `self`, the  $p$ -th exterior power of the dual of  $M$  is the set  $\Lambda^p(M^*)$  of all alternating forms of degree  $p$  on  $M$ , i.e. of all multilinear maps

$$\underbrace{M \times \cdots \times M}_p \longrightarrow R$$

that vanish whenever any of two of their arguments are equal.  $\Lambda^p(M^*)$  is a free module of rank  $\binom{n}{p}$  over the same ring as  $M$ , where  $n$  is the rank of  $M$ .

INPUT:

- $p$  – non-negative integer

OUTPUT:

- for  $p \geq 1$ , instance of `ExtPowerFreeModule` representing the free module  $\Lambda^p(M^*)$ ; for  $p = 0$ , the base ring  $R$  is returned instead

EXAMPLES:

Exterior powers of the dual of a free  $\mathbf{Z}$ -module of rank 3:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: e = M.basis('e')
sage: M.dual_exterior_power(0) # return the base ring
Integer Ring
sage: M.dual_exterior_power(1) # return the dual module
Dual of the Rank-3 free module M over the Integer Ring
sage: M.dual_exterior_power(1) is M.dual()
True
sage: M.dual_exterior_power(2)
2nd exterior power of the dual of the Rank-3 free module M over the Integer Ring
sage: M.dual_exterior_power(2).an_element()
Alternating form of degree 2 on the Rank-3 free module M over the Integer Ring
sage: M.dual_exterior_power(2).an_element().display()
e^0/\e^1
sage: M.dual_exterior_power(3)
3rd exterior power of the dual of the Rank-3 free module M over the Integer Ring
sage: M.dual_exterior_power(3).an_element()
Alternating form of degree 3 on the Rank-3 free module M over the Integer Ring
sage: M.dual_exterior_power(3).an_element().display()
e^0/\e^1/\e^2
```

See `ExtPowerFreeModule` for more documentation.

**endomorphism**(*matrix\_rep*, *basis=None*, *name=None*, *latex\_name=None*)

Construct an endomorphism of the free module `self`.

The returned object is a module morphism  $\phi : M \rightarrow M$ , where  $M$  is `self`.

INPUT:

- `matrix_rep` – matrix of size  $\text{rank}(M) \times \text{rank}(M)$  representing the endomorphism with respect to `basis`; this entry can actually be any material from which a matrix of elements of `self` base ring

can be constructed; the *columns* of *matrix\_rep* must be the components w.r.t. *basis* of the images of the elements of *basis*.

- *basis* – (default: None) basis of *self* defining the matrix representation; if None the default basis of *self* is assumed.
- *name* – (default: None) string; name given to the endomorphism
- *latex\_name* – (default: None) string; LaTeX symbol to denote the endomorphism; if none is provided, *name* will be used.

OUTPUT:

- the endomorphism  $\phi : M \rightarrow M$  corresponding to the given specifications, as an instance of `FiniteRankFreeModuleMorphism`

EXAMPLES:

Construction of an endomorphism with minimal data (module's default basis and no name):

```
sage: M = FiniteRankFreeModule(ZZ, 2, name='M')
sage: e = M.basis('e')
sage: phi = M.endomorphism([[1,-2], [-3,4]]) ; phi
Generic endomorphism of Rank-2 free module M over the Integer Ring
sage: phi.matrix() # matrix w.r.t the default basis
[ 1 -2]
[-3  4]
```

Construction with full list of arguments (matrix given a basis different from the default one):

```
sage: a = M.automorphism() ; a[0,1], a[1,0] = 1, -1
sage: ep = e.new_basis(a, 'ep', latex_symbol="e'")
sage: phi = M.endomorphism([[1,-2], [-3,4]], basis=ep, name='phi',
....:                      latex_name=r'\phi')
sage: phi
Generic endomorphism of Rank-2 free module M over the Integer Ring
sage: phi.matrix(ep) # the input matrix
[ 1 -2]
[-3  4]
sage: phi.matrix() # matrix w.r.t the default basis
[4 3]
[2 1]
```

See `FiniteRankFreeModuleMorphism` for more documentation.

**general\_linear\_group()**

Return the general linear group of *self*.

If *self* is the free module *M*, the *general linear group* is the group  $GL(M)$  of automorphisms of *M*.

OUTPUT:

- instance of class `FreeModuleLinearGroup` representing  $GL(M)$

EXAMPLES:

The general linear group of a rank-3 free module:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: e = M.basis('e')
sage: GL = M.general_linear_group() ; GL
General linear group of the Rank-3 free module M over the Integer Ring
sage: GL.category()
Category of groups
```

```
sage: type(GL)
<class 'sage.tensor.modules.free_module_linear_group.FreeModuleLinearGroup_with_category'>
```

There is a unique instance of the general linear group:

```
sage: M.general_linear_group() is GL
True
```

The group identity element:

```
sage: GL.one()
Identity map of the Rank-3 free module M over the Integer Ring
sage: GL.one().matrix(e)
[1 0 0]
[0 1 0]
[0 0 1]
```

An element:

```
sage: GL.an_element()
Automorphism of the Rank-3 free module M over the Integer Ring
sage: GL.an_element().matrix(e)
[ 1  0  0]
[ 0 -1  0]
[ 0  0  1]
```

See `FreeModuleLinearGroup` for more documentation.

**hom** (*codomain*, *matrix\_rep*, *bases=None*, *name=None*, *latex\_name=None*)

Homomorphism from `self` to a free module.

Define a module homomorphism

$$\phi: M \longrightarrow N,$$

where  $M$  is `self` and  $N$  is a free module of finite rank over the same ring  $R$  as `self`.

---

**Note:** This method is a redefinition of `sage.structure.parent.Parent.hom()` because the latter assumes that `self` has some privileged generators, while an instance of `FiniteRankFreeModule` has no privileged basis.

---

INPUT:

- *codomain* – the target module  $N$
- *matrix\_rep* – matrix of size  $\text{rank}(N) \times \text{rank}(M)$  representing the homomorphism with respect to the pair of bases defined by *bases*; this entry can actually be any material from which a matrix of elements of  $R$  can be constructed; the *columns* of *matrix\_rep* must be the components w.r.t. *basis\_N* of the images of the elements of *basis\_M*.
- *bases* – (default: `None`) pair (*basis\_M*, *basis\_N*) defining the matrix representation, *basis\_M* being a basis of `self` and *basis\_N* a basis of module  $N$ ; if `None` the pair formed by the default bases of each module is assumed.
- *name* – (default: `None`) string; name given to the homomorphism
- *latex\_name* – (default: `None`) string; LaTeX symbol to denote the homomorphism; if `None`, *name* will be used.

OUTPUT:

- the homomorphism  $\phi : M \rightarrow N$  corresponding to the given specifications, as an instance of `FiniteRankFreeModuleMorphism`

## EXAMPLES:

Homomorphism between two free modules over  $\mathbb{Z}$ :

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: N = FiniteRankFreeModule(ZZ, 2, name='N')
sage: e = M.basis('e')
sage: f = N.basis('f')
sage: phi = M.hom(N, [[-1,2,0], [5,1,2]]) ; phi
Generic morphism:
  From: Rank-3 free module M over the Integer Ring
  To:   Rank-2 free module N over the Integer Ring
```

Homomorphism defined by a matrix w.r.t. bases that are not the default ones:

```
sage: ep = M.basis('ep', latex_symbol=r"e' ")
sage: fp = N.basis('fp', latex_symbol=r"f' ")
sage: phi = M.hom(N, [[3,2,1], [1,2,3]], bases=(ep, fp)) ; phi
Generic morphism:
  From: Rank-3 free module M over the Integer Ring
  To:   Rank-2 free module N over the Integer Ring
```

Call with all arguments specified:

```
sage: phi = M.hom(N, [[3,2,1], [1,2,3]], bases=(ep, fp),
....:               name='phi', latex_name=r'\phi')
```

The parent:

```
sage: phi.parent() is Hom(M,N)
True
```

See class `FiniteRankFreeModuleMorphism` for more documentation.

**identity\_map** (*name='Id', latex\_name=None*)

Return the identity map of the free module `self`.

INPUT:

- `name` – (string; default: 'Id') name given to the identity map
- `latex_name` – (string; default: None) LaTeX symbol to denote the identity map; if none is provided, the LaTeX symbol is set to `\mathrm{Id}` if `name` is 'Id' and to `name` otherwise

OUTPUT:

- the identity map of `self` as an instance of `FreeModuleAutomorphism`

## EXAMPLES:

Identity map of a rank-3  $\mathbb{Z}$ -module:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: e = M.basis('e')
sage: Id = M.identity_map() ; Id
Identity map of the Rank-3 free module M over the Integer Ring
sage: Id.parent()
General linear group of the Rank-3 free module M over the Integer Ring
sage: Id.matrix(e)
[1 0 0]
```



```
[0 1 0]
[0 0 1]
```

The default LaTeX symbol:

```
sage: latex(Id)
\mathrm{Id}
```

It can be changed by means of the method `set_name()`:

```
sage: Id.set_name(latex_name=r'\mathrm{1}_M')
sage: latex(Id)
\mathrm{1}_M
```

The identity map is actually the identity element of  $GL(M)$ :

```
sage: Id is M.general_linear_group().one()
True
```

It is also a tensor of type-(1,1) on  $M$ :

```
sage: Id.tensor_type()
(1, 1)
sage: Id.comp(e)
Kronecker delta of size 3x3
sage: Id[:]
[1 0 0]
[0 1 0]
[0 0 1]
```

Example with a LaTeX symbol different from the default one and set at the creation of the object:

```
sage: N = FiniteRankFreeModule(ZZ, 3, name='N')
sage: f = N.basis('f')
sage: Id = N.identity_map(name='Id_N', latex_name=r'\mathrm{Id}_N')
sage: Id
Identity map of the Rank-3 free module N over the Integer Ring
sage: latex(Id)
\mathrm{Id}_N
```

**irange** (*start=None*)

Single index generator, labelling the elements of a basis of `self`.

INPUT:

- `start` – (default: `None`) integer; initial value of the index; if none is provided, `self._sindex` is assumed

OUTPUT:

- an iterable index, starting from `start` and ending at `self._sindex + self.rank() - 1`

EXAMPLES:

Index range on a rank-3 module:

```
sage: M = FiniteRankFreeModule(ZZ, 3)
sage: for i in M.irange(): print i,
0 1 2
sage: for i in M.irange(start=1): print i,
1 2
```

The default starting value corresponds to the parameter `start_index` provided at the module construction (the default value being 0):

```
sage: M1 = FiniteRankFreeModule(ZZ, 3, start_index=1)
sage: for i in M1.irange(): print i,
1 2 3
sage: M2 = FiniteRankFreeModule(ZZ, 3, start_index=-4)
sage: for i in M2.irange(): print i,
-4 -3 -2
```

**linear\_form** (*name=None, latex\_name=None*)

Construct a linear form on the free module `self`.

A *linear form* on a free module  $M$  over a ring  $R$  is a map  $M \rightarrow R$  that is linear. It can be viewed as a tensor of type  $(0, 1)$  on  $M$ .

INPUT:

- `name` – (default: None) string; name given to the linear form
- `latex_name` – (default: None) string; LaTeX symbol to denote the linear form; if none is provided, the LaTeX symbol is set to `name`

OUTPUT:

- instance of `FreeModuleAltForm`

EXAMPLES:

Linear form on a rank-3 free module:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: e = M.basis('e')
sage: a = M.linear_form('A') ; a
Linear form A on the Rank-3 free module M over the Integer Ring
sage: a[:] = [2, -1, 3] # components w.r.t. the module's default basis (e)
sage: a.display()
A = 2 e^0 - e^1 + 3 e^2
```

A linear form maps module elements to ring elements:

```
sage: v = M([1, 1, 1])
sage: a(v)
4
```

Test of linearity:

```
sage: u = M([-5, -2, 7])
sage: a(3*u - 4*v) == 3*a(u) - 4*a(v)
True
```

See `FreeModuleAltForm` for more documentation.

**print\_bases** ()

Display the bases that have been defined on the free module `self`.

Use the method `bases` () to get the raw list of bases.

EXAMPLES:

Bases on a rank-4 free module:

```
sage: M = FiniteRankFreeModule(ZZ, 4, name='M', start_index=1)
sage: M.print_bases()
No basis has been defined on the
```

```

Rank-4 free module M over the Integer Ring
sage: e = M.basis('e')
sage: M.print_bases()
Bases defined on the Rank-4 free module M over the Integer Ring:
- (e_1, e_2, e_3, e_4) (default basis)
sage: f = M.basis('f')
sage: M.print_bases()
Bases defined on the Rank-4 free module M over the Integer Ring:
- (e_1, e_2, e_3, e_4) (default basis)
- (f_1, f_2, f_3, f_4)
sage: M.set_default_basis(f)
sage: M.print_bases()
Bases defined on the Rank-4 free module M over the Integer Ring:
- (e_1, e_2, e_3, e_4)
- (f_1, f_2, f_3, f_4) (default basis)

```

**rank()**

Return the rank of the free module `self`.

Since the ring over which `self` is built is assumed to be commutative (and hence has the invariant basis number property), the rank is defined uniquely, as the cardinality of any basis of `self`.

EXAMPLES:

Rank of free modules over  $\mathbb{Z}$ :

```

sage: M = FiniteRankFreeModule(ZZ, 3)
sage: M.rank()
3
sage: M.tensor_module(0,1).rank()
3
sage: M.tensor_module(0,2).rank()
9
sage: M.tensor_module(1,0).rank()
3
sage: M.tensor_module(1,1).rank()
9
sage: M.tensor_module(1,2).rank()
27
sage: M.tensor_module(2,2).rank()
81

```

**set\_change\_of\_basis** (*basis1, basis2, change\_of\_basis, compute\_inverse=True*)

Relates two bases by an automorphism of `self`.

This updates the internal dictionary `self._basis_changes`.

INPUT:

- `basis1` – basis 1, denoted  $(e_i)$  below
- `basis2` – basis 2, denoted  $(f_i)$  below
- `change_of_basis` – instance of class `FreeModuleAutomorphism` describing the automorphism  $P$  that relates the basis  $(e_i)$  to the basis  $(f_i)$  according to  $f_i = P(e_i)$
- `compute_inverse` (default: `True`) – if set to `True`, the inverse automorphism is computed and the change from basis  $(f_i)$  to  $(e_i)$  is set to it in the internal dictionary `self._basis_changes`

EXAMPLES:

Defining a change of basis on a rank-2 free module:

```

sage: M = FiniteRankFreeModule(QQ, 2, name='M')
sage: e = M.basis('e')
sage: f = M.basis('f')
sage: a = M.automorphism()
sage: a[:] = [[1, 2], [-1, 3]]
sage: M.set_change_of_basis(e, f, a)

```

The change of basis and its inverse have been recorded:

```

sage: M.change_of_basis(e, f).matrix(e)
[ 1  2]
[-1  3]
sage: M.change_of_basis(f, e).matrix(e)
[ 3/5 -2/5]
[ 1/5  1/5]

```

and are effective:

```

sage: f[0].display(e)
f_0 = e_0 - e_1
sage: e[0].display(f)
e_0 = 3/5 f_0 + 1/5 f_1

```

#### **set\_default\_basis** (*basis*)

Sets the default basis of self.

The *default basis* is simply a basis whose name can be skipped in methods requiring a basis as an argument. By default, it is the first basis introduced on the module.

INPUT:

- *basis* – instance of `FreeModuleBasis` representing a basis on self

EXAMPLES:

Changing the default basis on a rank-3 free module:

```

sage: M = FiniteRankFreeModule(ZZ, 3, name='M', start_index=1)
sage: e = M.basis('e') ; e
Basis (e_1, e_2, e_3) on the Rank-3 free module M over the Integer Ring
sage: f = M.basis('f') ; f
Basis (f_1, f_2, f_3) on the Rank-3 free module M over the Integer Ring
sage: M.default_basis()
Basis (e_1, e_2, e_3) on the Rank-3 free module M over the Integer Ring
sage: M.set_default_basis(f)
sage: M.default_basis()
Basis (f_1, f_2, f_3) on the Rank-3 free module M over the Integer Ring

```

#### **sym\_bilinear\_form** (*name=None, latex\_name=None*)

Construct a symmetric bilinear form on the free module self.

INPUT:

- *name* – (default: None) string; name given to the symmetric bilinear form
- *latex\_name* – (default: None) string; LaTeX symbol to denote the symmetric bilinear form; if none is provided, the LaTeX symbol is set to *name*

OUTPUT:

- instance of `FreeModuleTensor` of tensor type  $(0, 2)$  and symmetric

## EXAMPLES:

Symmetric bilinear form on a rank-3 free module:

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: a = M.sym_bilinear_form('A') ; a
Symmetric bilinear form A on the
Rank-3 free module M over the Integer Ring
```

A symmetric bilinear form is a type-(0,2) tensor that is symmetric:

```
sage: a.parent()
Free module of type-(0,2) tensors on the
Rank-3 free module M over the Integer Ring
sage: a.tensor_type()
(0, 2)
sage: a.tensor_rank()
2
sage: a.symmetries()
symmetry: (0, 1); no antisymmetry
```

Components with respect to a given basis:

```
sage: e = M.basis('e')
sage: a[0,0], a[0,1], a[0,2] = 1, 2, 3
sage: a[1,1], a[1,2] = 4, 5
sage: a[2,2] = 6
```

Only independent components have been set; the other ones are deduced by symmetry:

```
sage: a[1,0], a[2,0], a[2,1]
(2, 3, 5)
sage: a[:]
[1 2 3]
[2 4 5]
[3 5 6]
```

A symmetric bilinear form acts on pairs of module elements:

```
sage: u = M([2,-1,3]) ; v = M([-2,4,1])
sage: a(u,v)
61
sage: a(v,u) == a(u,v)
True
```

The sum of two symmetric bilinear forms is another symmetric bilinear form:

```
sage: b = M.sym_bilinear_form('B')
sage: b[0,0], b[0,1], b[1,2] = -2, 1, -3
sage: s = a + b ; s
Symmetric bilinear form A+B on the
Rank-3 free module M over the Integer Ring
sage: a[:], b[:], s[:]
(
[1 2 3] [-2 1 0] [-1 3 3]
[2 4 5] [ 1 0 -3] [ 3 4 2]
[3 5 6], [ 0 -3 0], [ 3 2 6]
)
```

Adding a symmetric bilinear form with a non-symmetric one results in a generic type-(0,2) tensor:

```

sage: c = M.tensor((0,2), name='C')
sage: c[0,1] = 4
sage: s = a + c ; s
Type-(0,2) tensor A+C on the Rank-3 free module M over the Integer Ring
sage: s.symmetries()
no symmetry; no antisymmetry
sage: s[:]
[1 6 3]
[2 4 5]
[3 5 6]

```

See `FreeModuleTensor` for more documentation.

**tensor** (*tensor\_type*, *name=None*, *latex\_name=None*, *sym=None*, *antisym=None*)

Construct a tensor on the free module `self`.

INPUT:

- *tensor\_type* – pair  $(k, l)$  with  $k$  being the contravariant rank and  $l$  the covariant rank
- *name* – (default: `None`) string; name given to the tensor
- *latex\_name* – (default: `None`) string; LaTeX symbol to denote the tensor; if none is provided, the LaTeX symbol is set to *name*
- *sym* – (default: `None`) a symmetry or a list of symmetries among the tensor arguments: each symmetry is described by a tuple containing the positions of the involved arguments, with the convention `position = 0` for the first argument. For instance:
  - *sym* =  $(0, 1)$  for a symmetry between the 1st and 2nd arguments
  - *sym* =  $[(0, 2), (1, 3, 4)]$  for a symmetry between the 1st and 3rd arguments and a symmetry between the 2nd, 4th and 5th arguments.
- *antisym* – (default: `None`) antisymmetry or list of antisymmetries among the arguments, with the same convention as for *sym*

OUTPUT:

- instance of `FreeModuleTensor` representing the tensor defined on `self` with the provided characteristics

EXAMPLES:

Tensors on a rank-3 free module:

```

sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: t = M.tensor((1,0), name='t') ; t
Element t of the Rank-3 free module M over the Integer Ring
sage: t = M.tensor((0,1), name='t') ; t
Linear form t on the Rank-3 free module M over the Integer Ring
sage: t = M.tensor((1,1), name='t') ; t
Type-(1,1) tensor t on the Rank-3 free module M over the Integer Ring
sage: t = M.tensor((0,2), name='t', sym=(0,1)) ; t
Symmetric bilinear form t on the
Rank-3 free module M over the Integer Ring
sage: t = M.tensor((0,2), name='t', antisym=(0,1)) ; t
Alternating form t of degree 2 on the
Rank-3 free module M over the Integer Ring
sage: t = M.tensor((1,2), name='t') ; t
Type-(1,2) tensor t on the Rank-3 free module M over the Integer Ring

```

See `FreeModuleTensor` for more examples and documentation.

**tensor\_from\_comp** (*tensor\_type*, *comp*, *name=None*, *latex\_name=None*)

Construct a tensor on `self` from a set of components.

The tensor symmetries are deduced from those of the components.

INPUT:

- *tensor\_type* – pair (*k*, *l*) with *k* being the contravariant rank and *l* the covariant rank
- *comp* – instance of `Components` representing the tensor components in a given basis
- *name* – (default: `None`) string; name given to the tensor
- *latex\_name* – (default: `None`) string; LaTeX symbol to denote the tensor; if none is provided, the LaTeX symbol is set to *name*

OUTPUT:

- instance of `FreeModuleTensor` representing the tensor defined on `self` with the provided characteristics.

EXAMPLES:

Construction of a tensor of rank 1:

```
sage: from sage.tensor.modules.comp import Components, CompWithSym, CompFullySym, CompFullyA
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: e = M.basis('e') ; e
Basis (e_0, e_1, e_2) on the Rank-3 free module M over the Integer Ring
sage: c = Components(ZZ, e, 1)
sage: c[:]
[0, 0, 0]
sage: c[:] = [-1, 4, 2]
sage: t = M.tensor_from_comp((1, 0), c)
sage: t
Element of the Rank-3 free module M over the Integer Ring
sage: t.display(e)
-e_0 + 4 e_1 + 2 e_2
sage: t = M.tensor_from_comp((0, 1), c) ; t
Linear form on the Rank-3 free module M over the Integer Ring
sage: t.display(e)
-e^0 + 4 e^1 + 2 e^2
```

Construction of a tensor of rank 2:

```
sage: c = CompFullySym(ZZ, e, 2)
sage: c[0, 0], c[1, 2] = 4, 5
sage: t = M.tensor_from_comp((0, 2), c) ; t
Symmetric bilinear form on the
Rank-3 free module M over the Integer Ring
sage: t.symmetries()
symmetry: (0, 1); no antisymmetry
sage: t.display(e)
4 e^0*e^0 + 5 e^1*e^2 + 5 e^2*e^1
sage: c = CompFullyAntiSym(ZZ, e, 2)
sage: c[0, 1], c[1, 2] = 4, 5
sage: t = M.tensor_from_comp((0, 2), c) ; t
Alternating form of degree 2 on the
Rank-3 free module M over the Integer Ring
sage: t.display(e)
4 e^0/\e^1 + 5 e^1/\e^2
```

**tensor\_module** ( $k, l$ )Return the free module of all tensors of type  $(k, l)$  defined on self.

INPUT:

- $k$  – non-negative integer; the contravariant rank, the tensor type being  $(k, l)$
- $l$  – non-negative integer; the covariant rank, the tensor type being  $(k, l)$

OUTPUT:

- instance of `TensorFreeModule` representing the free module  $T^{(k,l)}(M)$  of type- $(k, l)$  tensors on the free module self

EXAMPLES:

Tensor modules over a free module over  $\mathbf{Z}$ :

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: T = M.tensor_module(1,2) ; T
Free module of type-(1,2) tensors on the Rank-3 free module M
over the Integer Ring
sage: T.an_element()
Type-(1,2) tensor on the Rank-3 free module M over the Integer Ring
```

Tensor modules are unique:

```
sage: M.tensor_module(1,2) is T
True
```

The base module is itself the module of all type- $(1, 0)$  tensors:

```
sage: M.tensor_module(1,0) is M
True
```

See `TensorFreeModule` for more documentation.**zero** ()

Return the zero element of self.

EXAMPLES:

Zero elements of free modules over  $\mathbf{Z}$ :

```
sage: M = FiniteRankFreeModule(ZZ, 3, name='M')
sage: M.zero()
Element zero of the Rank-3 free module M over the Integer Ring
sage: M.zero().parent() is M
True
sage: M.zero() is M(0)
True
sage: T = M.tensor_module(1,1)
sage: T.zero()
Type-(1,1) tensor zero on the Rank-3 free module M over the Integer Ring
sage: T.zero().parent() is T
True
sage: T.zero() is T(0)
True
```

Components of the zero element with respect to some basis:

```
sage: e = M.basis('e')
sage: M.zero()[e,:]
[0, 0, 0]
```



```
sage: all(M.zero()[e,i] == M.base_ring().zero() for i in M.irange())
True
sage: T.zero()[e,:]
[0 0 0]
[0 0 0]
[0 0 0]
sage: M.tensor_module(1,2).zero()[e,:]
[[[0, 0, 0], [0, 0, 0], [0, 0, 0]],
 [[0, 0, 0], [0, 0, 0], [0, 0, 0]],
 [[0, 0, 0], [0, 0, 0], [0, 0, 0]]]
```



## PICKLING FOR THE OLD CDF VECTOR CLASS

AUTHORS:

- Jason Grout

TESTS:

```
sage: v = vector(CDF, [(1,-1), (2,pi), (3,5)])
sage: v
(1.0 - 1.0*I, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: loads(dumps(v)) == v
True
```



## PICKLING FOR THE OLD RDF VECTOR CLASS

AUTHORS:

- Jason Grout

TESTS:

```
sage: v = vector(RDF, [1,2,3,4])  
sage: loads(dumps(v)) == v  
True
```



## VECTORS OVER CALLABLE SYMBOLIC RINGS

**AUTHOR:** – Jason Grout (2010)

EXAMPLES:

```
sage: f(r, theta, z) = (r*cos(theta), r*sin(theta), z)
sage: f.parent()
Vector space of dimension 3 over Callable function ring with arguments (r, theta, z)
sage: f
(r, theta, z) |--> (r*cos(theta), r*sin(theta), z)
sage: f[0]
(r, theta, z) |--> r*cos(theta)
sage: f+f
(r, theta, z) |--> (2*r*cos(theta), 2*r*sin(theta), 2*z)
sage: 3*f
(r, theta, z) |--> (3*r*cos(theta), 3*r*sin(theta), 3*z)
sage: f*f # dot product
(r, theta, z) |--> r^2*cos(theta)^2 + r^2*sin(theta)^2 + z^2
sage: f.diff()(0,1,2) # the matrix derivative
[cos(1)      0      0]
[sin(1)      0      0]
[      0      0      1]
```

TESTS:

```
sage: f(u,v,w) = (2*u+v,u-w,w^2+u)
sage: loads(dumps(f)) == f
True
```

```
class sage.modules.vector_callable_symbolic_dense.Vector_callable_symbolic_dense
    Bases: sage.modules.free_module_element.FreeModuleElement_generic_dense
```





## SPACE OF MORPHISMS OF VECTOR SPACES (LINEAR TRANSFORMATIONS)

AUTHOR:

- Rob Beezer: (2011-06-29)

A `VectorSpaceHomspace` object represents the set of all possible homomorphisms from one vector space to another. These mappings are usually known as linear transformations.

For more information on the use of linear transformations, consult the documentation for vector space morphisms at `sage.modules.vector_space_morphism`. Also, this is an extremely thin veneer on free module homspaces (`sage.modules.free_module_homspace`) and free module morphisms (`sage.modules.free_module_morphism`) - objects which might also be useful, and places where much of the documentation resides.

EXAMPLES:

Creation and basic examination is simple.

```
sage: V = QQ^3
sage: W = QQ^2
sage: H = Hom(V, W)
sage: H
Set of Morphisms (Linear Transformations) from
Vector space of dimension 3 over Rational Field to
Vector space of dimension 2 over Rational Field
sage: H.domain()
Vector space of dimension 3 over Rational Field
sage: H.codomain()
Vector space of dimension 2 over Rational Field
```

Homspaces have a few useful properties. A basis is provided by a list of matrix representations, where these matrix representatives are relative to the bases of the domain and codomain.

```
sage: K = Hom(GF(3)^2, GF(3)^2)
sage: B = K.basis()
sage: for f in B:
...     print f, "\n"
Vector space morphism represented by the matrix:
[1 0]
[0 0]
Domain: Vector space of dimension 2 over Finite Field of size 3
Codomain: Vector space of dimension 2 over Finite Field of size 3

Vector space morphism represented by the matrix:
[0 1]
```

```
[0 0]
Domain: Vector space of dimension 2 over Finite Field of size 3
Codomain: Vector space of dimension 2 over Finite Field of size 3

Vector space morphism represented by the matrix:
[0 0]
[1 0]
Domain: Vector space of dimension 2 over Finite Field of size 3
Codomain: Vector space of dimension 2 over Finite Field of size 3

Vector space morphism represented by the matrix:
[0 0]
[0 1]
Domain: Vector space of dimension 2 over Finite Field of size 3
Codomain: Vector space of dimension 2 over Finite Field of size 3
```

The zero and identity mappings are properties of the space. The identity mapping will only be available if the domain and codomain allow for endomorphisms (equal vector spaces with equal bases).

```
sage: H = Hom(QQ^3, QQ^3)
sage: g = H.zero()
sage: g([1, 1/2, -3])
(0, 0, 0)
sage: f = H.identity()
sage: f([1, 1/2, -3])
(1, 1/2, -3)
```

The homspace may be used with various representations of a morphism in the space to create the morphism. We demonstrate three ways to create the same linear transformation between two two-dimensional subspaces of  $\mathbb{Q}\mathbb{Q}^3$ . The  $V.n$  notation is a shortcut to the generators of each vector space, better known as the basis elements. Note that the matrix representations are relative to the bases, which are purposely fixed when the subspaces are created (“user bases”).

```
sage: U = QQ^3
sage: V = U.subspace_with_basis([U.0+U.1, U.1-U.2])
sage: W = U.subspace_with_basis([U.0, U.1+U.2])
sage: H = Hom(V, W)
```

First, with a matrix. Note that the matrix representation acts by matrix multiplication with the vector on the left. The input to the linear transformation,  $(3, 1, 2)$ , is converted to the coordinate vector  $(3, -2)$ , then matrix multiplication yields the vector  $(-3, -2)$ , which represents the vector  $(-3, -2, -2)$  in the codomain.

```
sage: m = matrix(QQ, [[1, 2], [3, 4]])
sage: f1 = H(m)
sage: f1
Vector space morphism represented by the matrix:
[1 2]
[3 4]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  1  0]
[ 0  1 -1]
Codomain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 0 0]
[0 1 1]
sage: f1([3,1,2])
(-3, -2, -2)
```

Second, with a list of images of the domain's basis elements.

```
sage: img = [1*(U.0) + 2*(U.1+U.2), 3*U.0 + 4*(U.1+U.2)]
sage: f2 = H(img)
sage: f2
Vector space morphism represented by the matrix:
[1 2]
[3 4]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  1  0]
[ 0  1 -1]
Codomain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 0 0]
[0 1 1]
sage: f2([3,1,2])
(-3, -2, -2)
```

Third, with a linear function taking the domain to the codomain.

```
sage: g = lambda x: vector(QQ, [-2*x[0]+3*x[1], -2*x[0]+4*x[1], -2*x[0]+4*x[1]])
sage: f3 = H(g)
sage: f3
Vector space morphism represented by the matrix:
[1 2]
[3 4]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  1  0]
[ 0  1 -1]
Codomain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 0 0]
[0 1 1]
sage: f3([3,1,2])
(-3, -2, -2)
```

The three linear transformations look the same, and are the same.

```
sage: f1 == f2
True
sage: f2 == f3
True
```

TESTS:

```
sage: V = QQ^2
sage: W = QQ^3
sage: H = Hom(QQ^2, QQ^3)
sage: loads(dumps(H))
Set of Morphisms (Linear Transformations) from
Vector space of dimension 2 over Rational Field to
Vector space of dimension 3 over Rational Field
sage: loads(dumps(H)) == H
True
```

```
class sage.modules.vector_space_homspace.VectorSpaceHomspace(X, Y, category=None,
                                                             check=True,
                                                             base=None)
```

Bases: `sage.modules.free_module_homspace.FreeModuleHomspace`

TESTS:

```
sage: X = ZZ['x']; X.rename("X")
```

```
sage: Y = ZZ['y']; Y.rename("Y")
```

```
sage: class MyHomset(HomsetWithBase):
```

```
...     def my_function(self, x):
```

```
...         return Y(x[0])
```

```
...     def _an_element_(self):
```

```
...         return sage.categories.morphism.SetMorphism(self, self.my_function)
```

```
...
```

```
sage: import __main__; __main__.MyHomset = MyHomset # fakes MyHomset being defined in a Python m
```

```
sage: H = MyHomset(X, Y, category=Monoids())
```

```
sage: H
```

```
Set of Morphisms from X to Y in Category of monoids
```

```
sage: H.base()
```

```
Integer Ring
```

```
sage: TestSuite(H).run()
```

```
sage.modules.vector_space_homspace.is_VectorSpaceHomspace(x)
```

Return True if `x` is a vector space homspace.

INPUT:

`x` - anything

EXAMPLES:

To be a vector space morphism, the domain and codomain must both be vector spaces, in other words, modules over fields. If either set is just a module, then the `Hom()` constructor will build a space of free module morphisms.

```
sage: H = Hom(QQ^3, QQ^2)
```

```
sage: type(H)
```

```
<class 'sage.modules.vector_space_homspace.VectorSpaceHomspace_with_category'>
```

```
sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace(H)
```

```
True
```

```
sage: K = Hom(QQ^3, ZZ^2)
```

```
sage: type(K)
```

```
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
```

```
sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace(K)
```

```
False
```

```
sage: L = Hom(ZZ^3, QQ^2)
```

```
sage: type(L)
```

```
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
```

```
sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace(L)
```

```
False
```

```
sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace('junk')
```

```
False
```

## VECTOR SPACE MORPHISMS (AKA LINEAR TRANSFORMATIONS)

AUTHOR:

- Rob Beezer: (2011-06-29)

A vector space morphism is a homomorphism between vector spaces, better known as a linear transformation. These are a specialization of Sage’s free module homomorphisms. (A free module is like a vector space, but with scalars from a ring that may not be a field.) So references to free modules in the documentation or error messages should be understood as simply reflecting a more general situation.

### 10.1 Creation

The constructor `linear_transformation()` is designed to accept a variety of inputs that can define a linear transformation. See the documentation of the function for all the possibilities. Here we give two.

First a matrix representation. By default input matrices are understood to act on vectors placed to left of the matrix. Optionally, an input matrix can be described as acting on vectors placed to the right.

```
sage: A = matrix(QQ, [[-1, 2, 3], [4, 2, 0]])
sage: phi = linear_transformation(A)
sage: phi
Vector space morphism represented by the matrix:
[-1  2  3]
[ 4  2  0]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 3 over Rational Field
sage: phi([2, -3])
(-14, -2, 6)
```

A symbolic function can be used to specify the “rule” for a linear transformation, along with explicit descriptions of the domain and codomain.

```
sage: F = Integers(13)
sage: D = F^3
sage: C = F^2
sage: x, y, z = var('x y z')
sage: f(x, y, z) = [2*x + 3*y + 5*z, x + z]
sage: rho = linear_transformation(D, C, f)
sage: f(1, 2, 3)
(23, 4)
sage: rho([1, 2, 3])
(10, 4)
```

A “vector space homspace” is the set of all linear transformations between two vector spaces. Various input can be coerced into a homspace to create a linear transformation. See `sage.modules.vector_space_homspace` for more.

```
sage: D = QQ^4
sage: C = QQ^2
sage: hom_space = Hom(D, C)
sage: images = [[1, 3], [2, -1], [4, 0], [3, 7]]
sage: zeta = hom_space(images)
sage: zeta
Vector space morphism represented by the matrix:
[ 1  3]
[ 2 -1]
[ 4  0]
[ 3  7]
Domain: Vector space of dimension 4 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
```

A homomorphism may also be created via a method on the domain.

```
sage: F = QQ[sqrt(3)]
sage: a = F.gen(0)
sage: D = F^2
sage: C = F^2
sage: A = matrix(F, [[a, 1], [2*a, 2]])
sage: psi = D.hom(A, C)
sage: psi
Vector space morphism represented by the matrix:
[ sqrt3  1]
[ 2*sqrt3 2]
Domain: Vector space of dimension 2 over Number Field in sqrt3 with defining polynomial x^2 - 3
Codomain: Vector space of dimension 2 over Number Field in sqrt3 with defining polynomial x^2 - 3
sage: psi([1, 4])
(9*sqrt3, 9)
```

## 10.2 Properties

Many natural properties of a linear transformation can be computed. Some of these are more general methods of objects in the classes `sage.modules.free_module_morphism.FreeModuleMorphism` and `sage.modules.matrix_morphism.MatrixMorphism`.

Values are computed in a natural way, an inverse image of an element can be computed with the `lift()` method, when the inverse image actually exists.

```
sage: A = matrix(QQ, [[1,2], [2,4], [3,6]])
sage: phi = linear_transformation(A)
sage: phi([1,2,0])
(5, 10)
sage: phi.lift([10, 20])
(10, 0, 0)
sage: phi.lift([100, 100])
Traceback (most recent call last):
...
ValueError: element is not in the image
```

Images and pre-images can be computed as vector spaces.

```

sage: A = matrix(QQ, [[1,2], [2,4], [3,6]])
sage: phi = linear_transformation(A)
sage: phi.image()
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 2]

sage: phi.inverse_image( (QQ^2).span([[1,2]]) )
Vector space of degree 3 and dimension 3 over Rational Field
Basis matrix:
[1 0 0]
[0 1 0]
[0 0 1]

sage: phi.inverse_image( (QQ^2).span([[1,1]]) )
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1    0 -1/3]
[ 0    1 -2/3]

```

Injectivity and surjectivity can be checked.

```

sage: A = matrix(QQ, [[1,2], [2,4], [3,6]])
sage: phi = linear_transformation(A)
sage: phi.is_injective()
False
sage: phi.is_surjective()
False

```

## 10.3 Restrictions and Representations

It is possible to restrict the domain and codomain of a linear transformation to make a new linear transformation. We will use those commands to replace the domain and codomain by equal vector spaces, but with alternate bases. The point here is that the matrix representation used to represent linear transformations are relative to the bases of both the domain and codomain.

```

sage: A = graphs.PetersenGraph().adjacency_matrix()
sage: V = QQ^10
sage: phi = linear_transformation(V, V, A)
sage: phi
Vector space morphism represented by the matrix:
[0 1 0 0 1 1 0 0 0 0]
[1 0 1 0 0 0 0 1 0 0]
[0 1 0 1 0 0 0 0 1 0]
[0 0 1 0 1 0 0 0 1 0]
[1 0 0 1 0 0 0 0 0 1]
[1 0 0 0 0 0 0 1 1 0]
[0 1 0 0 0 0 0 0 1 1]
[0 0 1 0 0 1 0 0 0 1]
[0 0 0 1 0 1 1 0 0 0]
[0 0 0 0 1 0 1 1 0 0]
Domain: Vector space of dimension 10 over Rational Field
Codomain: Vector space of dimension 10 over Rational Field

sage: B1 = [V.gen(i) + V.gen(i+1) for i in range(9)] + [V.gen(9)]

```

```
sage: B2 = [V.gen(0)] + [-V.gen(i-1) + V.gen(i) for i in range(1,10)]
sage: D = V.subspace_with_basis(B1)
sage: C = V.subspace_with_basis(B2)
sage: rho = phi.restrict_codomain(C)
sage: zeta = rho.restrict_domain(D)
sage: zeta
Vector space morphism represented by the matrix:
[6 5 4 3 3 2 1 0 0 0]
[6 5 4 3 2 2 2 1 0 0]
[6 6 5 4 3 2 2 2 1 0]
[6 5 5 4 3 2 2 2 2 1]
[6 4 4 4 3 3 3 3 2 1]
[6 5 4 4 4 4 4 4 3 1]
[6 6 5 4 4 4 3 3 3 2]
[6 6 6 5 4 4 2 1 1 1]
[6 6 6 6 5 4 3 1 0 0]
[3 3 3 3 3 2 2 1 0 0]
Domain: Vector space of degree 10 and dimension 10 over Rational Field
User basis matrix:
[1 1 0 0 0 0 0 0 0 0]
[0 1 1 0 0 0 0 0 0 0]
[0 0 1 1 0 0 0 0 0 0]
[0 0 0 1 1 0 0 0 0 0]
[0 0 0 0 1 1 0 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 0 1 1 0 0]
[0 0 0 0 0 0 0 1 1 0]
[0 0 0 0 0 0 0 0 1 1]
[0 0 0 0 0 0 0 0 0 1]
Codomain: Vector space of degree 10 and dimension 10 over Rational Field
User basis matrix:
[ 1  0  0  0  0  0  0  0  0  0]
[-1  1  0  0  0  0  0  0  0  0]
[ 0 -1  1  0  0  0  0  0  0  0]
[ 0  0 -1  1  0  0  0  0  0  0]
[ 0  0  0 -1  1  0  0  0  0  0]
[ 0  0  0  0 -1  1  0  0  0  0]
[ 0  0  0  0  0 -1  1  0  0  0]
[ 0  0  0  0  0  0 -1  1  0  0]
[ 0  0  0  0  0  0  0 -1  1  0]
[ 0  0  0  0  0  0  0  0 -1  1]
```

An endomorphism is a linear transformation with an equal domain and codomain, and here each needs to have the same basis. We are using a matrix that has well-behaved eigenvalues, as part of showing that these do not change as the representation changes.

```
sage: A = graphs.PetersenGraph().adjacency_matrix()
sage: V = QQ^10
sage: phi = linear_transformation(V, V, A)
sage: phi.eigenvalues()
[3, -2, -2, -2, -2, 1, 1, 1, 1, 1]

sage: B1 = [V.gen(i) + V.gen(i+1) for i in range(9)] + [V.gen(9)]
sage: C = V.subspace_with_basis(B1)
sage: zeta = phi.restrict(C)
sage: zeta
Vector space morphism represented by the matrix:
[ 1  0  1 -1  2 -1  2 -2  2 -2]
```



```

[ 1  0  1  0  0  0  1  0  0  0]
[ 0  1  0  1  0  0  0  1  0  0]
[ 1 -1  2 -1  2 -2  2 -2  3 -2]
[ 2 -2  2 -1  1 -1  1  0  1  0]
[ 1  0  0  0  0  0  0  1  1  0]
[ 0  1  0  0  0  1 -1  1  0  2]
[ 0  0  1  0  0  2 -1  1 -1  2]
[ 0  0  0  1  0  1  1  0  0  0]
[ 0  0  0  0  1 -1  2 -1  1 -1]
Domain: Vector space of degree 10 and dimension 10 over Rational Field
User basis matrix:
[1 1 0 0 0 0 0 0 0 0]
[0 1 1 0 0 0 0 0 0 0]
[0 0 1 1 0 0 0 0 0 0]
[0 0 0 1 1 0 0 0 0 0]
[0 0 0 0 1 1 0 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 0 1 1 0 0]
[0 0 0 0 0 0 0 1 1 0]
[0 0 0 0 0 0 0 0 1 1]
[0 0 0 0 0 0 0 0 0 1]
Codomain: Vector space of degree 10 and dimension 10 over Rational Field
User basis matrix:
[1 1 0 0 0 0 0 0 0 0]
[0 1 1 0 0 0 0 0 0 0]
[0 0 1 1 0 0 0 0 0 0]
[0 0 0 1 1 0 0 0 0 0]
[0 0 0 0 1 1 0 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 0 1 1 0 0]
[0 0 0 0 0 0 0 1 1 0]
[0 0 0 0 0 0 0 0 1 1]
[0 0 0 0 0 0 0 0 0 1]

sage: zeta.eigenvalues()
[3, -2, -2, -2, -2, 1, 1, 1, 1, 1]

```

## 10.4 Equality

Equality of linear transformations is a bit nuanced. The equality operator `==` tests if two linear transformations have equal matrix representations, while we determine if two linear transformations are the same function with the `.is_equal_function()` method. Notice in this example that the function never changes, just the representations.

```

sage: f = lambda x: vector(QQ, [x[1], x[0]+x[1], x[0]])
sage: H = Hom(QQ^2, QQ^3)
sage: phi = H(f)

sage: rho = linear_transformation(QQ^2, QQ^3, matrix(QQ, 2, 3, [[0,1,1], [1,1,0]]))

sage: phi == rho
True

sage: U = (QQ^2).subspace_with_basis([[1, 2], [-3, 1]])
sage: V = (QQ^3).subspace_with_basis([[0, 1, 0], [2, 3, 1], [-1, 1, 6]])
sage: K = Hom(U, V)

```

```
sage: zeta = K(f)

sage: zeta == phi
False
sage: zeta.is_equal_function(phi)
True
sage: zeta.is_equal_function(rho)
True
```

**TESTS:**

```
sage: V = QQ^2
sage: H = Hom(V, V)
sage: f = H([V.1, -2*V.0])
sage: loads(dumps(f))
Vector space morphism represented by the matrix:
[ 0  1]
[-2  0]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
sage: loads(dumps(f)) == f
True
```

**class** `sage.modules.vector_space_morphism.VectorSpaceMorphism` (*homspace*, *A*)  
Bases: `sage.modules.free_module_morphism.FreeModuleMorphism`

Create a linear transformation, a morphism between vector spaces.

**INPUT:**

- *homspace* - a homspace (of vector spaces) to serve as a parent for the linear transformation and a home for the domain and codomain of the morphism
- *A* - a matrix representing the linear transformation, which will act on vectors placed to the left of the matrix

**EXAMPLES:**

Nominally, we require a homspace to hold the domain and codomain and a matrix representation of the morphism (linear transformation).

```
sage: from sage.modules.vector_space_homspace import VectorSpaceHomspace
sage: from sage.modules.vector_space_morphism import VectorSpaceMorphism
sage: H = VectorSpaceHomspace(QQ^3, QQ^2)
sage: A = matrix(QQ, 3, 2, range(6))
sage: zeta = VectorSpaceMorphism(H, A)
sage: zeta
Vector space morphism represented by the matrix:
[0 1]
[2 3]
[4 5]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
```

See the constructor, `sage.modules.vector_space_morphism.linear_transformation()` for another way to create linear transformations.

The `.hom()` method of a vector space will create a vector space morphism.

```
sage: V = QQ^3; W = V.subspace_with_basis([[1,2,3], [-1,2,5/3], [0,1,-1]])
sage: phi = V.hom(matrix(QQ, 3, range(9)), codomain=W) # indirect doctest
```

```
sage: type(phi)
<class 'sage.modules.vector_space_morphism.VectorSpaceMorphism'>
```

A matrix may be coerced into a vector space homspace to create a vector space morphism.

```
sage: from sage.modules.vector_space_homspace import VectorSpaceHomspace
sage: H = VectorSpaceHomspace(QQ^3, QQ^2)
sage: A = matrix(QQ, 3, 2, range(6))
sage: rho = H(A) # indirect doctest
sage: type(rho)
<class 'sage.modules.vector_space_morphism.VectorSpaceMorphism'>
```

### **is\_invertible()**

Determines if the vector space morphism has an inverse.

OUTPUT:

True if the vector space morphism is invertible, otherwise False.

EXAMPLES:

If the dimension of the domain does not match the dimension of the codomain, then the morphism cannot be invertible.

```
sage: V = QQ^3
sage: U = V.subspace_with_basis([V.0 + V.1, 2*V.1 + 3*V.2])
sage: phi = V.hom([U.0, U.0 + U.1, U.0 - U.1], U)
sage: phi.is_invertible()
False
```

An invertible linear transformation.

```
sage: A = matrix(QQ, 3, [[-3, 5, -5], [4, -7, 7], [6, -8, 10]])
sage: A.determinant()
2
sage: H = Hom(QQ^3, QQ^3)
sage: rho = H(A)
sage: rho.is_invertible()
True
```

A non-invertible linear transformation, an endomorphism of a vector space over a finite field.

```
sage: F.<a> = GF(11^2)
sage: A = matrix(F, [[6*a + 3, 8*a + 2, 10*a + 3],
...                 [2*a + 7, 4*a + 3, 2*a + 3],
...                 [9*a + 2, 10*a + 10, 3*a + 3]])
sage: A.nullity()
1
sage: E = End(F^3)
sage: zeta = E(A)
sage: zeta.is_invertible()
False
```

`sage.modules.vector_space_morphism.is_VectorSpaceMorphism(x)`

Returns True if x is a vector space morphism (a linear transformation).

INPUT:

x - anything

OUTPUT:

True only if  $x$  is an instance of a vector space morphism, which are also known as linear transformations.

**EXAMPLES:**

```
sage: V = QQ^2; f = V.hom([V.1, -2*V.0])
sage: sage.modules.vector_space_morphism.is_VectorSpaceMorphism(f)
True
sage: sage.modules.vector_space_morphism.is_VectorSpaceMorphism('junk')
False
```

```
sage.modules.vector_space_morphism.linear_transformation(arg0, arg1=None,
                                                           arg2=None, side='left')
```

Create a linear transformation from a variety of possible inputs.

**FORMATS:**

In the following,  $D$  and  $C$  are vector spaces over the same field that are the domain and codomain (respectively) of the linear transformation.

`side` is a keyword that is either 'left' or 'right'. When a matrix is used to specify a linear transformation, as in the first two call formats below, you may specify if the function is given by matrix multiplication with the vector on the left, or the vector on the right. The default is 'left'. Internally representations are always carried as the 'left' version, and the default text representation is this version. However, the matrix representation may be obtained as either version, no matter how it is created.

- `linear_transformation(A, side='left')`

Where  $A$  is a matrix. The domain and codomain are inferred from the dimension of the matrix and the base ring of the matrix. The base ring must be a field, or have its fraction field implemented in Sage.

- `linear_transformation(D, C, A, side='left')`

$A$  is a matrix that behaves as above. However, now the domain and codomain are given explicitly. The matrix is checked for compatibility with the domain and codomain. Additionally, the domain and codomain may be supplied with alternate ("user") bases and the matrix is interpreted as being a representation relative to those bases.

- `linear_transformation(D, C, f)`

$f$  is any function that can be applied to the basis elements of the domain and that produces elements of the codomain. The linear transformation returned is the unique linear transformation that extends this mapping on the basis elements.  $f$  may come from a function defined by a Python `def` statement, or may be defined as a `lambda` function.

Alternatively,  $f$  may be specified by a callable symbolic function, see the examples below for a demonstration.

- `linear_transformation(D, C, images)`

`images` is a list, or tuple, of codomain elements, equal in number to the size of the basis of the domain. Each basis element of the domain is mapped to the corresponding element of the `images` list, and the linear transformation returned is the unique linear transformation that extends this mapping.

**OUTPUT:**

A linear transformation described by the input. This is a "vector space morphism", an object of the class `sage.modules.vector_space_morphism`.

**EXAMPLES:**

We can define a linear transformation with just a matrix, understood to act on a vector placed on one side or the other. The field for the vector spaces used as domain and codomain is obtained from the base ring of the matrix, possibly promoting to a fraction field.

```

sage: A = matrix(ZZ, [[1, -1, 4], [2, 0, 5]])
sage: phi = linear_transformation(A)
sage: phi
Vector space morphism represented by the matrix:
[ 1 -1  4]
[ 2  0  5]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 3 over Rational Field
sage: phi([1/2, 5])
(21/2, -1/2, 27)

sage: B = matrix(Integers(7), [[1, 2, 1], [3, 5, 6]])
sage: rho = linear_transformation(B, side='right')
sage: rho
Vector space morphism represented by the matrix:
[1 3]
[2 5]
[1 6]
Domain: Vector space of dimension 3 over Ring of integers modulo 7
Codomain: Vector space of dimension 2 over Ring of integers modulo 7
sage: rho([2, 4, 6])
(2, 6)

```

We can define a linear transformation with a matrix, while explicitly giving the domain and codomain. Matrix entries will be coerced into the common field of scalars for the vector spaces.

```

sage: D = QQ^3
sage: C = QQ^2
sage: A = matrix([[1, 7], [2, -1], [0, 5]])
sage: A.parent()
Full MatrixSpace of 3 by 2 dense matrices over Integer Ring
sage: zeta = linear_transformation(D, C, A)
sage: zeta.matrix().parent()
Full MatrixSpace of 3 by 2 dense matrices over Rational Field
sage: zeta
Vector space morphism represented by the matrix:
[ 1  7]
[ 2 -1]
[ 0  5]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

```

Matrix representations are relative to the bases for the domain and codomain.

```

sage: u = vector(QQ, [1, -1])
sage: v = vector(QQ, [2, 3])
sage: D = (QQ^2).subspace_with_basis([u, v])
sage: x = vector(QQ, [2, 1])
sage: y = vector(QQ, [-1, 4])
sage: C = (QQ^2).subspace_with_basis([x, y])
sage: A = matrix(QQ, [[2, 5], [3, 7]])
sage: psi = linear_transformation(D, C, A)
sage: psi
Vector space morphism represented by the matrix:
[2 5]
[3 7]
Domain: Vector space of degree 2 and dimension 2 over Rational Field
User basis matrix:
[ 1 -1]

```

```
[ 2  3]
Codomain: Vector space of degree 2 and dimension 2 over Rational Field
User basis matrix:
[ 2  1]
[-1  4]
sage: psi(u) == 2*x + 5*y
True
sage: psi(v) == 3*x + 7*y
True
```

Functions that act on the domain may be used to compute images of the domain's basis elements, and this mapping can be extended to a unique linear transformation. The function may be a Python function (via `def` or `lambda`) or a Sage symbolic function.

```
sage: def g(x):
...     return vector(QQ, [2*x[0]+x[2], 5*x[1]])
...
sage: phi = linear_transformation(QQ^3, QQ^2, g)
sage: phi
Vector space morphism represented by the matrix:
[2 0]
[0 5]
[1 0]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

sage: f = lambda x: vector(QQ, [2*x[0]+x[2], 5*x[1]])
sage: rho = linear_transformation(QQ^3, QQ^2, f)
sage: rho
Vector space morphism represented by the matrix:
[2 0]
[0 5]
[1 0]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

sage: x, y, z = var('x y z')
sage: h(x, y, z) = [2*x + z, 5*y]
sage: zeta = linear_transformation(QQ^3, QQ^2, h)
sage: zeta
Vector space morphism represented by the matrix:
[2 0]
[0 5]
[1 0]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

sage: phi == rho
True
sage: rho == zeta
True
```

We create a linear transformation relative to non-standard bases, and capture its representation relative to standard bases. With this, we can build functions that create the same linear transformation relative to the non-standard bases.

```
sage: u = vector(QQ, [1, -1])
sage: v = vector(QQ, [2, 3])
sage: D = (QQ^2).subspace_with_basis([u, v])
```

```

sage: x = vector(QQ, [2, 1])
sage: y = vector(QQ, [-1, 4])
sage: C = (QQ^2).subspace_with_basis([x, y])
sage: A = matrix(QQ, [[2, 5], [3, 7]])
sage: psi = linear_transformation(D, C, A)
sage: rho = psi.restrict_codomain(QQ^2).restrict_domain(QQ^2)
sage: rho.matrix()
[ -4/5  97/5]
[  1/5 -13/5]

sage: f = lambda x: vector(QQ, [(-4/5)*x[0] + (1/5)*x[1], (97/5)*x[0] + (-13/5)*x[1]])
sage: psi = linear_transformation(D, C, f)
sage: psi.matrix()
[2 5]
[3 7]

sage: s, t = var('s t')
sage: h(s, t) = [(-4/5)*s + (1/5)*t, (97/5)*s + (-13/5)*t]
sage: zeta = linear_transformation(D, C, h)
sage: zeta.matrix()
[2 5]
[3 7]

```

Finally, we can give an explicit list of images for the basis elements of the domain.

```

sage: x = polygen(QQ)
sage: F.<a> = NumberField(x^3+x+1)
sage: u = vector(F, [1, a, a^2])
sage: v = vector(F, [a, a^2, 2])
sage: w = u + v
sage: D = F^3
sage: C = F^3
sage: rho = linear_transformation(D, C, [u, v, w])
sage: rho.matrix()
[      1      a      a^2]
[      a      a^2      2]
[ a + 1 a^2 + a a^2 + 2]
sage: C = (F^3).subspace_with_basis([u, v])
sage: D = (F^3).subspace_with_basis([u, v])
sage: psi = linear_transformation(C, D, [u+v, u-v])
sage: psi.matrix()
[ 1  1]
[ 1 -1]

```

#### TESTS:

We test some bad inputs. First, the wrong things in the wrong places.

```

sage: linear_transformation('junk')
Traceback (most recent call last):
...
TypeError: first argument must be a matrix or a vector space, not junk

sage: linear_transformation(QQ^2, QQ^3, 'stuff')
Traceback (most recent call last):
...
TypeError: third argument must be a matrix, function, or list of images, not stuff

sage: linear_transformation(QQ^2, 'garbage')

```

```
Traceback (most recent call last):
...
TypeError: if first argument is a vector space, then second argument must be a vector space, not

sage: linear_transformation(QQ^2, Integers(7)^2)
Traceback (most recent call last):
...
TypeError: vector spaces must have the same field of scalars, not Rational Field and Ring of integers
```

Matrices must be over a field (or a ring that can be promoted to a field), and of the right size.

```
sage: linear_transformation(matrix(Integers(6), [[2, 3], [4, 5]]))
Traceback (most recent call last):
...
TypeError: matrix must have entries from a field, or a ring with a fraction field, not Ring of integers
```

```
sage: A = matrix(QQ, 3, 4, range(12))
sage: linear_transformation(QQ^4, QQ^4, A)
Traceback (most recent call last):
...
TypeError: domain dimension is incompatible with matrix size
```

```
sage: linear_transformation(QQ^3, QQ^3, A, side='right')
Traceback (most recent call last):
...
TypeError: domain dimension is incompatible with matrix size
```

```
sage: linear_transformation(QQ^3, QQ^3, A)
Traceback (most recent call last):
...
TypeError: codomain dimension is incompatible with matrix size
```

```
sage: linear_transformation(QQ^4, QQ^4, A, side='right')
Traceback (most recent call last):
...
TypeError: codomain dimension is incompatible with matrix size
```

Lists of images can be of the wrong number, or not really elements of the codomain.

```
sage: linear_transformation(QQ^3, QQ^2, [vector(QQ, [1,2])])
Traceback (most recent call last):
...
ValueError: number of images should equal the size of the domain's basis (=3), not 1
```

```
sage: C = (QQ^2).subspace_with_basis([vector(QQ, [1,1])])
sage: linear_transformation(QQ^1, C, [vector(QQ, [1,2])])
Traceback (most recent call last):
...
ArithmeticError: some proposed image is not in the codomain, because
element [1, 2] is not in free module
```

Functions may not apply properly to domain elements, or return values outside the codomain.

```
sage: f = lambda x: vector(QQ, [x[0], x[4]])
sage: linear_transformation(QQ^3, QQ^2, f)
Traceback (most recent call last):
...
ValueError: function cannot be applied properly to some basis element because
vector index out of range
```



```

sage: f = lambda x: vector(QQ, [x[0], x[1]])
sage: C = (QQ^2).span([vector(QQ, [1, 1])])
sage: linear_transformation(QQ^2, C, f)
Traceback (most recent call last):
...
ArithmeticError: some image of the function is not in the codomain, because
element [1, 0] is not in free module

```

A Sage symbolic function can come in a variety of forms that are not representative of a linear transformation.

```

sage: x, y = var('x, y')
sage: f(x, y) = [y, x, y]
sage: linear_transformation(QQ^3, QQ^3, f)
Traceback (most recent call last):
...
ValueError: symbolic function has the wrong number of inputs for domain

```

```

sage: linear_transformation(QQ^2, QQ^2, f)
Traceback (most recent call last):
...
ValueError: symbolic function has the wrong number of outputs for codomain

```

```

sage: x, y = var('x y')
sage: f(x, y) = [y, x*y]
sage: linear_transformation(QQ^2, QQ^2, f)
Traceback (most recent call last):
...
ValueError: symbolic function must be linear in all the inputs:
unable to convert y to a rational

```

```

sage: x, y = var('x y')
sage: f(x, y) = [x, 2*y]
sage: C = (QQ^2).span([vector(QQ, [1, 1])])
sage: linear_transformation(QQ^2, C, f)
Traceback (most recent call last):
...
ArithmeticError: some image of the function is not in the codomain, because
element [1, 0] is not in free module

```



## HOMSPACES BETWEEN FREE MODULES

EXAMPLES: We create  $\text{End}(\mathbb{Z}^2)$  and compute a basis.

```
sage: M = FreeModule(IntegerRing(), 2)
sage: E = End(M)
sage: B = E.basis()
sage: len(B)
4
sage: B[0]
Free module morphism defined by the matrix
[1 0]
[0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 2 over the principal ideal domain ...
```

We create  $\text{Hom}(\mathbb{Z}^3, \mathbb{Z}^2)$  and compute a basis.

```
sage: V3 = FreeModule(IntegerRing(), 3)
sage: V2 = FreeModule(IntegerRing(), 2)
sage: H = Hom(V3, V2)
sage: H
Set of Morphisms from Ambient free module of rank 3 over the
principal ideal domain Integer Ring to Ambient free module
of rank 2 over the principal ideal domain Integer Ring in
Category of modules with basis over (euclidean domains and
infinite enumerated sets)
sage: B = H.basis()
sage: len(B)
6
sage: B[0]
Free module morphism defined by the matrix
[1 0]
[0 0]
[0 0]...
```

TESTS:

```
sage: H = Hom(QQ^2, QQ^1)
sage: loads(dumps(H)) == H
True
```

See trac 5886:

```
sage: V = (ZZ^2).span_of_basis([[1, 2], [3, 4]])
sage: V.hom([V.0, V.1])
Free module morphism defined by the matrix
```

```
[1 0]
[0 1]...
```

```
class sage.modules.free_module_homspace.FreeModuleHomspace(X, Y, category=None,
                                                         check=True, base=None)
```

Bases: sage.categories.homset.HomsetWithBase

TESTS:

```
sage: X = ZZ['x']; X.rename("X")
sage: Y = ZZ['y']; Y.rename("Y")
sage: class MyHomset(HomsetWithBase):
...     def my_function(self, x):
...         return Y(x[0])
...     def _an_element_(self):
...         return sage.categories.morphism.SetMorphism(self, self.my_function)
...
sage: import __main__; __main__.MyHomset = MyHomset # fakes MyHomset being defined in a Python m
sage: H = MyHomset(X, Y, category=Monoids())
sage: H
Set of Morphisms from X to Y in Category of monoids
sage: H.base()
Integer Ring
sage: TestSuite(H).run()
```

**basis()**

Return a basis for this space of free module homomorphisms.

OUTPUT:

•tuple

EXAMPLES:

```
sage: H = Hom(ZZ^2, ZZ^1)
sage: H.basis()
(Free module morphism defined by the matrix
[1]
[0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 1 over the principal ideal domain ..., Free module mor
[0]
[1]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 1 over the principal ideal domain ...)
```

**identity()**

Return identity morphism in an endomorphism ring.

EXAMPLE:

```
sage: V=FreeModule(ZZ,5)
sage: H=V.Hom(V)
sage: H.identity()
Free module morphism defined by the matrix
[1 0 0 0 0]
[0 1 0 0 0]
[0 0 1 0 0]
[0 0 0 1 0]
[0 0 0 0 1]
Domain: Ambient free module of rank 5 over the principal ideal domain ...
```

Codomain: Ambient free module of rank 5 over the principal ideal domain ...

**zero()**

EXAMPLES:

```
sage: E = ZZ^2
sage: F = ZZ^3
sage: H = Hom(E, F)
sage: f = H.zero()
sage: f
Free module morphism defined by the matrix
[0 0 0]
[0 0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain Integer Ring
Codomain: Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: f(E.an_element())
(0, 0, 0)
sage: f(E.an_element()) == F.zero()
True
```

TESTS:

We check that `H.zero()` is picklable:

```
sage: loads(dumps(f.parent().zero()))
Free module morphism defined by the matrix
[0 0 0]
[0 0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain Integer Ring
Codomain: Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

`sage.modules.free_module_homspace.is_FreeModuleHomspace(x)`

Return True if `x` is a free module homspace.

EXAMPLES:

Notice that every vector space is a free module, but when we construct a set of morphisms between two vector spaces, it is a `VectorSpaceHomspace`, which qualifies as a `FreeModuleHomspace`, since the former is special case of the latter.

```
sage: H = Hom(ZZ^3, ZZ^2) sage: type(H) <class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(H) True

sage: K = Hom(QQ^3, ZZ^2) sage: type(K) <class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(K) True

sage: L = Hom(ZZ^3, QQ^2) sage: type(L) <class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(L) True

sage: P = Hom(QQ^3, QQ^2) sage: type(P) <class 'sage.modules.vector_space_homspace.VectorSpaceHomspace_with_category'
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(P) True

sage: sage.modules.free_module_homspace.is_FreeModuleHomspace('junk') False
```



## MORPHISMS OF FREE MODULES

### AUTHORS:

- William Stein: initial version
- Miguel Marco (2010-06-19): added eigenvalues, eigenvectors and minpoly functions

### TESTS:

```
sage: V = ZZ^2; f = V.hom([V.1, -2*V.0])
sage: loads(dumps(f))
Free module morphism defined by the matrix
[ 0  1]
[-2  0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 2 over the principal ideal domain ...
sage: loads(dumps(f)) == f
True
```

```
class sage.modules.free_module_morphism.FreeModuleMorphism(parent, A)
    Bases: sage.modules.matrix_morphism.MatrixMorphism
```

### INPUT:

- parent - a homspace in a (sub) category of free modules
- A - matrix

### EXAMPLES:

```
sage: V = ZZ^3; W = span([[1,2,3],[-1,2,8]], ZZ)
sage: phi = V.hom(matrix(ZZ,3,[1..9]))
sage: type(phi)
<class 'sage.modules.free_module_morphism.FreeModuleMorphism'>
```

### change\_ring(R)

Change the ring over which this morphism is defined. This changes the ring of the domain, codomain, and underlying matrix.

### EXAMPLES:

```
sage: V0 = span([[0,0,1],[0,2,0]], ZZ); V1 = span([[1/2,0],[0,2]], ZZ); W = span([[1,0],[0,6]])
sage: h = V0.hom([-3*V1.0-3*V1.1, -3*V1.0-3*V1.1])
sage: h.base_ring()
Integer Ring
sage: h
Free module morphism defined by the matrix
[-3 -3]
[-3 -3]...
```

```
sage: h.change_ring(QQ).base_ring()
Rational Field
sage: f = h.change_ring(QQ); f
Vector space morphism represented by the matrix:
[-3 -3]
[-3 -3]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[0 1 0]
[0 0 1]
Codomain: Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]
sage: f = h.change_ring(GF(7)); f
Vector space morphism represented by the matrix:
[4 4]
[4 4]
Domain: Vector space of degree 3 and dimension 2 over Finite Field of size 7
Basis matrix:
[0 1 0]
[0 0 1]
Codomain: Vector space of degree 2 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0]
[0 1]
```

**eigenspaces** (*extend=True*)

Compute a list of subspaces formed by eigenvectors of self.

INPUT:

- `extend` – (default: `True`) determines if field extensions should be considered

OUTPUT:

- a list of pairs (`eigenvalue`, `eigenspace`)

EXAMPLES:

```
sage: V = QQ^3
sage: h = V.hom([[1,0,0],[0,0,1],[0,-1,0]], V)
sage: h.eigenspaces()
[(1,
  Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
  [1 0 0]),
 (-1*I,
  Vector space of degree 3 and dimension 1 over Algebraic Field
  Basis matrix:
  [ 0 1 1*I]),
 (1*I,
  Vector space of degree 3 and dimension 1 over Algebraic Field
  Basis matrix:
  [ 0 1 -1*I])]

sage: h.eigenspaces(extend=False)
[(1,
  Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
```



```

[1 0 0]])

sage: h = V.hom([[2,1,0], [0,2,0], [0,0,-1]], V)
sage: h.eigenspaces()
[(-1, Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
  [0 0 1]),
 (2, Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
  [0 1 0])]

sage: h = V.hom([[2,1,0], [0,2,0], [0,0,2]], V)
sage: h.eigenspaces()
[(2, Vector space of degree 3 and dimension 2 over Rational Field
  Basis matrix:
  [0 1 0]
  [0 0 1])]

```

**eigenvalues** (*extend=True*)

Returns a list with the eigenvalues of the endomorphism of vector spaces.

INPUT:

- *extend* – boolean (default: True) decides if base field extensions should be considered or not.

EXAMPLES:

We compute the eigenvalues of an endomorphism of  $\mathbb{Q}^3$ :

```

sage: V=QQ^3
sage: H=V.endomorphism_ring() ([[1,-1,0], [-1,1,1], [0,3,1]])
sage: H.eigenvalues()
[3, 1, -1]

```

Note the effect of the *extend* option:

```

sage: V=QQ^2
sage: H=V.endomorphism_ring() ([[0,-1], [1,0]])
sage: H.eigenvalues()
[-1*I, 1*I]
sage: H.eigenvalues(extend=False)
[]

```

**eigenvectors** (*extend=True*)

Computes the subspace of eigenvectors of a given eigenvalue.

INPUT:

- *extend* – boolean (default: True) decides if base field extensions should be considered or not.

OUTPUT:

A sequence of tuples. Each tuple contains an eigenvalue, a sequence with a basis of the corresponding subspace of eigenvectors, and the algebraic multiplicity of the eigenvalue.

EXAMPLES:

```

sage: V=(QQ^4).subspace([[0,2,1,4], [1,2,5,0], [1,1,1,1]])
sage: H=(V.hom(V))(matrix(QQ, [[0,1,0], [-1,0,0], [0,0,3]]))
sage: H.eigenvectors()
[(3, [
(0, 0, 1, -6/7)

```

```

], 1), (-1*I, [
(1, 1*I, 0, -0.571428571428572? + 2.428571428571429?*I)
], 1), (1*I, [
(1, -1*I, 0, -0.571428571428572? - 2.428571428571429?*I)
], 1)]
sage: H.eigenvectors(extend=False)
[(3, [
(0, 0, 1, -6/7)
], 1)]
sage: H1=(V.Hom(V))(matrix(QQ, [[2,1,0],[0,2,0],[0,0,3]]))
sage: H1.eigenvectors()
[(3, [
(0, 0, 1, -6/7)
], 1), (2, [
(0, 1, 0, 17/7)
], 2)]
sage: H1.eigenvectors(extend=False)
[(3, [
(0, 0, 1, -6/7)
], 1), (2, [
(0, 1, 0, 17/7)
], 2)]

```

**inverse\_image(V)**

Given a submodule V of the codomain of self, return the inverse image of V under self, i.e., the biggest submodule of the domain of self that maps into V.

**EXAMPLES:**

We test computing inverse images over a field:

```

sage: V = QQ^3; W = span([[1,2,3],[-1,2,5/3]], QQ)
sage: phi = V.hom(matrix(QQ, 3, [1..9]))
sage: phi.rank()
2
sage: I = phi.inverse_image(W); I
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0  0]
[ 0  1 -1/2]
sage: phi(I.0) in W
True
sage: phi(I.1) in W
True
sage: W = phi.image()
sage: phi.inverse_image(W) == V
True

```

We test computing inverse images between two spaces embedded in different ambient spaces.:

```

sage: V0 = span([[0,0,1],[0,2,0]], ZZ); V1 = span([[1/2,0],[0,2]], ZZ); W = span([[1,0],[0,6]])
sage: h = V0.hom([-3*V1.0-3*V1.1, -3*V1.0-3*V1.1])
sage: h.inverse_image(W)
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[0 2 1]
[0 0 2]
sage: h(h.inverse_image(W)).is_submodule(W)
True
sage: h(h.inverse_image(W)).index_in(W)

```

```
+Infinity
sage: h(h.inverse_image(W))
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[ 3 12]
```

We test computing inverse images over the integers:

```
sage: V = QQ^3; W = V.span_of_basis([[2,2,3],[-1,2,5/3]], ZZ)
sage: phi = W.hom([W.0, W.0-W.1])
sage: Z = W.span([2*W.1]); Z
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[ 2 -4 -10/3]
sage: Y = phi.inverse_image(Z); Y
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[ 6 0 8/3]
sage: phi(Y) == Z
True
```

### **lift**(x)

Given an element of the image, return an element of the codomain that maps onto it.

Note that `lift` and `preimage_representative` are equivalent names for this method, with the latter suggesting that the return value is a coset representative of the domain modulo the kernel of the morphism.

EXAMPLE:

```
sage: X = QQ**2
sage: V = X.span([[2, 0], [0, 8]], ZZ)
sage: W = (QQ**1).span([[1/12]], ZZ)
sage: f = V.hom([W([1/3]), W([1/2])], W)
sage: f.lift([1/3])
(8, -16)
sage: f.lift([1/2])
(12, -24)
sage: f.lift([1/6])
(4, -8)
sage: f.lift([1/12])
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: f.lift([1/24])
Traceback (most recent call last):
...
TypeError: element [1/24] is not in free module
```

This works for vector spaces, too:

```
sage: V = VectorSpace(GF(3), 2)
sage: W = VectorSpace(GF(3), 3)
sage: f = V.hom([W.1, W.1 - W.0])
sage: f.lift(W.1)
(1, 0)
sage: f.lift(W.2)
Traceback (most recent call last):
...
ValueError: element is not in the image
```

```
sage: w = W((17, -2, 0))
sage: f(f.lift(w)) == w
True
```

This example illustrates the use of the `preimage_representative` as an equivalent name for this method.

```
sage: V = ZZ^3
sage: W = ZZ^2
sage: w = vector(ZZ, [1,2])
sage: f = V.hom([w, w, w], W)
sage: f.preimage_representative(vector(ZZ, [10, 20]))
(0, 0, 10)
```

**`minimal_polynomial`** (*var='x'*)

Computes the minimal polynomial.

`minpoly()` and `minimal_polynomial()` are the same method.

INPUT:

- *var* - string (default: 'x') a variable name

OUTPUT:

polynomial in *var* - the minimal polynomial of the endomorphism.

EXAMPLES:

Compute the minimal polynomial, and check it.

```
sage: V=GF(7)^3
sage: H=V.Hom(V) ([[0,1,2], [-1,0,3], [2,4,1]])
sage: H
Vector space morphism represented by the matrix:
[0 1 2]
[6 0 3]
[2 4 1]
Domain: Vector space of dimension 3 over Finite Field of size 7
Codomain: Vector space of dimension 3 over Finite Field of size 7

sage: H.minpoly()
x^3 + 6*x^2 + 6*x + 1

sage: H.minimal_polynomial()
x^3 + 6*x^2 + 6*x + 1

sage: H^3 + (H^2)*6 + H*6 + 1
Vector space morphism represented by the matrix:
[0 0 0]
[0 0 0]
[0 0 0]
Domain: Vector space of dimension 3 over Finite Field of size 7
Codomain: Vector space of dimension 3 over Finite Field of size 7
```

**`minpoly`** (*var='x'*)

Computes the minimal polynomial.

`minpoly()` and `minimal_polynomial()` are the same method.

INPUT:

- var - string (default: 'x') a variable name

OUTPUT:

polynomial in var - the minimal polynomial of the endomorphism.

EXAMPLES:

Compute the minimal polynomial, and check it.

```
sage: V=GF(7)^3
sage: H=V.Hom(V) ([[0,1,2], [-1,0,3], [2,4,1]])
sage: H
Vector space morphism represented by the matrix:
[0 1 2]
[6 0 3]
[2 4 1]
Domain: Vector space of dimension 3 over Finite Field of size 7
Codomain: Vector space of dimension 3 over Finite Field of size 7

sage: H.minpoly()
x^3 + 6*x^2 + 6*x + 1

sage: H.minimal_polynomial()
x^3 + 6*x^2 + 6*x + 1

sage: H^3 + (H^2)*6 + H*6 + 1
Vector space morphism represented by the matrix:
[0 0 0]
[0 0 0]
[0 0 0]
Domain: Vector space of dimension 3 over Finite Field of size 7
Codomain: Vector space of dimension 3 over Finite Field of size 7
```

### **preimage\_representative**(x)

Given an element of the image, return an element of the codomain that maps onto it.

Note that `lift` and `preimage_representative` are equivalent names for this method, with the latter suggesting that the return value is a coset representative of the domain modulo the kernel of the morphism.

EXAMPLE:

```
sage: X = QQ**2
sage: V = X.span([[2, 0], [0, 8]], ZZ)
sage: W = (QQ**1).span([[1/12]], ZZ)
sage: f = V.hom([W([1/3]), W([1/2])], W)
sage: f.lift([1/3])
(8, -16)
sage: f.lift([1/2])
(12, -24)
sage: f.lift([1/6])
(4, -8)
sage: f.lift([1/12])
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: f.lift([1/24])
Traceback (most recent call last):
...
TypeError: element [1/24] is not in free module
```

This works for vector spaces, too:

```
sage: V = VectorSpace(GF(3), 2)
sage: W = VectorSpace(GF(3), 3)
sage: f = V.hom([W.1, W.1 - W.0])
sage: f.lift(W.1)
(1, 0)
sage: f.lift(W.2)
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: w = W((17, -2, 0))
sage: f(f.lift(w)) == w
True
```

This example illustrates the use of the `preimage_representative` as an equivalent name for this method.

```
sage: V = ZZ^3
sage: W = ZZ^2
sage: w = vector(ZZ, [1, 2])
sage: f = V.hom([w, w, w], W)
sage: f.preimage_representative(vector(ZZ, [10, 20]))
(0, 0, 10)
```

#### **pushforward**(*x*)

Compute the image of a sub-module of the domain.

EXAMPLES:

```
sage: V = QQ^3; W = span([[1, 2, 3], [-1, 2, 5/3]], QQ)
sage: phi = V.hom(matrix(QQ, 3, [1..9]))
sage: phi.rank()
2
sage: phi(V) #indirect doctest
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
```

We compute the image of a submodule of a ZZ-module embedded in a rational vector space:

```
sage: V = QQ^3; W = V.span_of_basis([[2, 2, 3], [-1, 2, 5/3]], ZZ)
sage: phi = W.hom([W.0, W.0 - W.1]); phi
Free module morphism defined by the matrix
[ 1  0]
[ 1 -1]...
sage: phi(span([2*W.1], ZZ))
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[ 6  0 8/3]
sage: phi(2*W.1)
(6, 0, 8/3)
```

`sage.modules.free_module_morphism.is_FreeModuleMorphism`(*x*)

EXAMPLES:

```
sage: V = ZZ^2; f = V.hom([V.1, -2*V.0])
sage: sage.modules.free_module_morphism.is_FreeModuleMorphism(f)
True
sage: sage.modules.free_module_morphism.is_FreeModuleMorphism(0)
```

False





## MORPHISMS DEFINED BY A MATRIX

A matrix morphism is a morphism that is defined by multiplication by a matrix. Elements of domain must either have a method `vector()` that returns a vector that the defining matrix can hit from the left, or be coercible into vector space of appropriate dimension.

EXAMPLES:

```
sage: from sage.modules.matrix_morphism import MatrixMorphism, is_MatrixMorphism
sage: V = QQ^3
sage: T = End(V)
sage: M = MatrixSpace(QQ, 3)
sage: I = M.identity_matrix()
sage: m = MatrixMorphism(T, I); m
Morphism defined by the matrix
[1 0 0]
[0 1 0]
[0 0 1]
sage: is_MatrixMorphism(m)
True
sage: m.charpoly('x')
x^3 - 3*x^2 + 3*x - 1
sage: m.base_ring()
Rational Field
sage: m.det()
1
sage: m.fcp('x')
(x - 1)^3
sage: m.matrix()
[1 0 0]
[0 1 0]
[0 0 1]
sage: m.rank()
3
sage: m.trace()
3
```

AUTHOR:

- William Stein: initial versions
- David Joyner (2005-12-17): added examples
- William Stein (2005-01-07): added `__reduce__`
- Craig Citro (2008-03-18): refactored `MatrixMorphism` class
- Rob Beezer (2011-07-15): additional methods, bug fixes, documentation

**class** sage.modules.matrix\_morphism.**MatrixMorphism**(parent, A, copy\_matrix=True)

Bases: sage.modules.matrix\_morphism.MatrixMorphism\_abstract

A morphism defined by a matrix.

INPUT:

- parent – a homspace
- A – matrix or a `MatrixMorphism_abstract` instance
- copy\_matrix – (default: True) make an immutable copy of the matrix A if it is mutable; if False, then this makes A immutable

**is\_injective()**

Tell whether `self` is injective.

EXAMPLE:

```
sage: V1 = QQ^2
sage: V2 = QQ^3
sage: phi = V1.hom(Matrix([[1, 2, 3], [4, 5, 6]]), V2)
sage: phi.is_injective()
True
sage: psi = V2.hom(Matrix([[1, 2], [3, 4], [5, 6]]), V1)
sage: psi.is_injective()
False
```

AUTHOR:

– Simon King (2010-05)

**is\_surjective()**

Tell whether `self` is surjective.

EXAMPLES:

```
sage: V1 = QQ^2
sage: V2 = QQ^3
sage: phi = V1.hom(Matrix([[1, 2, 3], [4, 5, 6]]), V2)
sage: phi.is_surjective()
False
sage: psi = V2.hom(Matrix([[1, 2], [3, 4], [5, 6]]), V1)
sage: psi.is_surjective()
True
```

An example over a PID that is not  $\mathbb{Z}$ .

```
sage: R = PolynomialRing(QQ, 'x')
sage: A = R^2
sage: B = R^2
sage: H = A.hom([B([x^2-1, 1]), B([x^2, 1])])
sage: H.image()
Free module of degree 2 and rank 2 over Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[ 1  0]
[ 0 -1]
sage: H.is_surjective()
True
```

This tests if Trac #11552 is fixed.

```
sage: V = ZZ^2
sage: m = matrix(ZZ, [[1, 2], [0, 2]])
```

```

sage: phi = V.hom(m, V)
sage: phi.lift(vector(ZZ, [0, 1]))
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: phi.is_surjective()
False

```

#### AUTHORS:

- Simon King (2010-05)
- Rob Beezer (2011-06-28)

**matrix**(*side*='left')

Return a matrix that defines this morphism.

#### INPUT:

- side* – (default: 'left') the side of the matrix where a vector is placed to effect the morphism (function)

#### OUTPUT:

A matrix which represents the morphism, relative to bases for the domain and codomain. If the modules are provided with user bases, then the representation is relative to these bases.

Internally, Sage represents a matrix morphism with the matrix multiplying a row vector placed to the left of the matrix. If the option *side*='right' is used, then a matrix is returned that acts on a vector to the right of the matrix. These two matrices are just transposes of each other and the difference is just a preference for the style of representation.

#### EXAMPLES:

```

sage: V = ZZ^2; W = ZZ^3
sage: m = column_matrix([3*V.0 - 5*V.1, 4*V.0 + 2*V.1, V.0 + V.1])
sage: phi = V.hom(m, W)
sage: phi.matrix()
[ 3  4  1]
[-5  2  1]

sage: phi.matrix(side='right')
[ 3 -5]
[ 4  2]
[ 1  1]

```

#### TESTS:

```

sage: V = ZZ^2
sage: phi = V.hom([3*V.0, 2*V.1])
sage: phi.matrix(side='junk')
Traceback (most recent call last):
...
ValueError: side must be 'left' or 'right', not junk

```

**class** sage.modules.matrix\_morphism.**MatrixMorphism\_abstract**(*parent*)

Bases: sage.categories.morphism.Morphism

#### INPUT:

- parent* - a homspace

- `A` - matrix

EXAMPLES:

```
sage: from sage.modules.matrix_morphism import MatrixMorphism
sage: T = End(ZZ^3)
sage: M = MatrixSpace(ZZ, 3)
sage: I = M.identity_matrix()
sage: A = MatrixMorphism(T, I)
sage: loads(A.dumps()) == A
True
```

**base\_ring()**

Return the base ring of self, that is, the ring over which self is given by a matrix.

EXAMPLES:

```
sage: sage.modules.matrix_morphism.MatrixMorphism(ZZ**2).endomorphism_ring(), Matrix(ZZ, 2, 2, Integer Ring)
```

**characteristic\_polynomial** (*var='x'*)

Return the characteristic polynomial of this endomorphism.

`characteristic_polynomial` and `char_poly` are the same method.

INPUT:

- `var` – variable

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.characteristic_polynomial()
x^2 - 3*x + 2
sage: phi.charpoly()
x^2 - 3*x + 2
sage: phi.matrix().charpoly()
x^2 - 3*x + 2
sage: phi.charpoly('T')
T^2 - 3*T + 2
```

**charpoly** (*var='x'*)

Return the characteristic polynomial of this endomorphism.

`characteristic_polynomial` and `char_poly` are the same method.

INPUT:

- `var` – variable

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.characteristic_polynomial()
x^2 - 3*x + 2
sage: phi.charpoly()
x^2 - 3*x + 2
sage: phi.matrix().charpoly()
x^2 - 3*x + 2
sage: phi.charpoly('T')
T^2 - 3*T + 2
```

**decomposition** (*\*args, \*\*kws*)

Return decomposition of this endomorphism, i.e., sequence of subspaces obtained by finding invariant

subspaces of self.

See the documentation for `self.matrix().decomposition` for more details. All inputs to this function are passed onto the matrix one.

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.decomposition()
[
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[0 1],
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[ 1 -1]
]
```

**det()**

Return the determinant of this endomorphism.

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.det()
2
```

**fcp** (*var='x'*)

Return the factorization of the characteristic polynomial.

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.fcp()
(x - 2) * (x - 1)
sage: phi.fcp('T')
(T - 2) * (T - 1)
```

**image()**

Compute the image of this morphism.

EXAMPLES:

```
sage: V = VectorSpace(QQ, 3)
sage: phi = V.Hom(V) (matrix(QQ, 3, range(9)))
sage: phi.image()
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: hom(GF(7)^3, GF(7)^2, zero_matrix(GF(7), 3, 2)).image()
Vector space of degree 2 and dimension 0 over Finite Field of size 7
Basis matrix:
[]
```

Compute the image of the identity map on a  $\mathbb{Z}\mathbb{Z}$ -submodule:

```
sage: V = (ZZ^2).span([[1, 2], [3, 4]])
sage: phi = V.Hom(V) (identity_matrix(ZZ, 2))
sage: phi(V.0) == V.0
True
sage: phi(V.1) == V.1
```

```

True
sage: phi.image()
Free module of degree 2 and rank 2 over Integer Ring
Echelon basis matrix:
[1 0]
[0 2]
sage: phi.image() == V
True

```

**inverse()**

Returns the inverse of this matrix morphism, if the inverse exists.

Raises a `ZeroDivisionError` if the inverse does not exist.

**EXAMPLES:**

An invertible morphism created as a restriction of a non-invertible morphism, and which has an unequal domain and codomain.

```

sage: V = QQ^4
sage: W = QQ^3
sage: m = matrix(QQ, [[2, 0, 3], [-6, 1, 4], [1, 2, -4], [1, 0, 1]])
sage: phi = V.hom(m, W)
sage: rho = phi.restrict_domain(V.span([V.0, V.3]))
sage: zeta = rho.restrict_codomain(W.span([W.0, W.2]))
sage: x = vector(QQ, [2, 0, 0, -7])
sage: y = zeta(x); y
(-3, 0, -1)
sage: inv = zeta.inverse(); inv
Vector space morphism represented by the matrix:
[-1  3]
[ 1 -2]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 0 0]
[0 0 1]
Codomain: Vector space of degree 4 and dimension 2 over Rational Field
Basis matrix:
[1 0 0 0]
[0 0 0 1]
sage: inv(y) == x
True

```

An example of an invertible morphism between modules, (rather than between vector spaces).

```

sage: M = ZZ^4
sage: p = matrix(ZZ, [[ 0, -1,  1, -2],
...                  [ 1, -3,  2, -3],
...                  [ 0,  4, -3,  4],
...                  [-2,  8, -4,  3]])
sage: phi = M.hom(p, M)
sage: x = vector(ZZ, [1, -3, 5, -2])
sage: y = phi(x); y
(1, 12, -12, 21)
sage: rho = phi.inverse(); rho
Free module morphism defined by the matrix
[ -5   3  -1   1]
[ -9   4  -3   2]
[-20   8  -7   4]
[ -6   2  -2   1]

```

```

Domain: Ambient free module of rank 4 over the principal ideal domain ...
Codomain: Ambient free module of rank 4 over the principal ideal domain ...
sage: rho(y) == x
True

```

A non-invertible morphism, despite having an appropriate domain and codomain.

```

sage: V = QQ^2
sage: m = matrix(QQ, [[1, 2], [20, 40]])
sage: phi = V.hom(m, V)
sage: phi.is_bijective()
False
sage: phi.inverse()
Traceback (most recent call last):
...
ZeroDivisionError: matrix morphism not invertible

```

The matrix representation of this morphism is invertible over the rationals, but not over the integers, thus the morphism is not invertible as a map between modules. It is easy to notice from the definition that every vector of the image will have a second entry that is an even integer.

```

sage: V = ZZ^2
sage: q = matrix(ZZ, [[1, 2], [3, 4]])
sage: phi = V.hom(q, V)
sage: phi.matrix().change_ring(QQ).inverse()
[ -2      1]
[ 3/2 -1/2]
sage: phi.is_bijective()
False
sage: phi.image()
Free module of degree 2 and rank 2 over Integer Ring
Echelon basis matrix:
[1 0]
[0 2]
sage: phi.lift(vector(ZZ, [1, 1]))
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: phi.inverse()
Traceback (most recent call last):
...
ZeroDivisionError: matrix morphism not invertible

```

The unary invert operator ( $\sim$ , tilde, “wiggly”) is synonymous with the `inverse()` method (and a lot easier to type).

```

sage: V = QQ^2
sage: r = matrix(QQ, [[4, 3], [-2, 5]])
sage: phi = V.hom(r, V)
sage: rho = phi.inverse()
sage: zeta = ~phi
sage: rho.is_equal_function(zeta)
True

```

TESTS:

```

sage: V = QQ^2
sage: W = QQ^3
sage: U = W.span([W.0, W.1])

```

```
sage: m = matrix(QQ, [[2, 1], [3, 4]])
sage: phi = V.hom(m, U)
sage: inv = phi.inverse()
sage: (inv*phi).is_identity()
True
sage: (phi*inv).is_identity()
True
```

**is\_bijective()**

Tell whether `self` is bijective.

**EXAMPLES:**

Two morphisms that are obviously not bijective, simply on considerations of the dimensions. However, each fullfills half of the requirements to be a bijection.

```
sage: V1 = QQ^2
sage: V2 = QQ^3
sage: m = matrix(QQ, [[1, 2, 3], [4, 5, 6]])
sage: phi = V1.hom(m, V2)
sage: phi.is_injective()
True
sage: phi.is_bijective()
False
sage: rho = V2.hom(m.transpose(), V1)
sage: rho.is_surjective()
True
sage: rho.is_bijective()
False
```

We construct a simple bijection between two one-dimensional vector spaces.

```
sage: V1 = QQ^3
sage: V2 = QQ^2
sage: phi = V1.hom(matrix(QQ, [[1, 2], [3, 4], [5, 6]]), V2)
sage: x = vector(QQ, [1, -1, 4])
sage: y = phi(x); y
(18, 22)
sage: rho = phi.restrict_domain(V1.span([x]))
sage: zeta = rho.restrict_codomain(V2.span([y]))
sage: zeta.is_bijective()
True
```

**AUTHOR:**

•Rob Beezer (2011-06-28)

**is\_equal\_function(*other*)**

Determines if two morphisms are equal functions.

**INPUT:**

•`other` - a morphism to compare with `self`

**OUTPUT:**

Returns `True` precisely when the two morphisms have equal domains and codomains (as sets) and produce identical output when given the same input. Otherwise returns `False`.

This is useful when `self` and `other` may have different representations.



Sage’s default comparison of matrix morphisms requires the domains to have the same bases and the codomains to have the same bases, and then compares the matrix representations. This notion of equality is more permissive (it will return `True` “more often”), but is more correct mathematically.

#### EXAMPLES:

Three morphisms defined by combinations of different bases for the domain and codomain and different functions. Two are equal, the third is different from both of the others.

```
sage: B = matrix(QQ, [[-3, 5, -4, 2],
...                  [-1, 2, -1, 4],
...                  [ 4, -6, 5, -1],
...                  [-5, 7, -6, 1]])
sage: U = (QQ^4).subspace_with_basis(B.rows())
sage: C = matrix(QQ, [[-1, -6, -4],
...                  [ 3, -5, 6],
...                  [ 1, 2, 3]])
sage: V = (QQ^3).subspace_with_basis(C.rows())
sage: H = Hom(U, V)

sage: D = matrix(QQ, [[-7, -2, -5, 2],
...                  [-5, 1, -4, -8],
...                  [ 1, -1, 1, 4],
...                  [-4, -1, -3, 1]])
sage: X = (QQ^4).subspace_with_basis(D.rows())
sage: E = matrix(QQ, [[ 4, -1, 4],
...                  [ 5, -4, -5],
...                  [-1, 0, -2]])
sage: Y = (QQ^3).subspace_with_basis(E.rows())
sage: K = Hom(X, Y)

sage: f = lambda x: vector(QQ, [x[0]+x[1], 2*x[1]-4*x[2], 5*x[3]])
sage: g = lambda x: vector(QQ, [x[0]-x[2], 2*x[1]-4*x[2], 5*x[3]])

sage: rho = H(f)
sage: phi = K(f)
sage: zeta = H(g)

sage: rho.is_equal_function(phi)
True
sage: phi.is_equal_function(rho)
True
sage: zeta.is_equal_function(rho)
False
sage: phi.is_equal_function(zeta)
False
```

#### TEST:

```
sage: H = Hom(ZZ^2, ZZ^2)
sage: phi = H(matrix(ZZ, 2, range(4)))
sage: phi.is_equal_function('junk')
Traceback (most recent call last):
...
TypeError: can only compare to a matrix morphism, not junk
```

#### AUTHOR:

•Rob Beezer (2011-07-15)

`is_identity()`

Determines if this morphism is an identity function or not.

EXAMPLES:

A homomorphism that cannot possibly be the identity due to an unequal domain and codomain.

```
sage: V = QQ^3
sage: W = QQ^2
sage: m = matrix(QQ, [[1, 2], [3, 4], [5, 6]])
sage: phi = V.hom(m, W)
sage: phi.is_identity()
False
```

A bijection, but not the identity.

```
sage: V = QQ^3
sage: n = matrix(QQ, [[3, 1, -8], [5, -4, 6], [1, 1, -5]])
sage: phi = V.hom(n, V)
sage: phi.is_bijective()
True
sage: phi.is_identity()
False
```

A restriction that is the identity.

```
sage: V = QQ^3
sage: p = matrix(QQ, [[1, 0, 0], [5, 8, 3], [0, 0, 1]])
sage: phi = V.hom(p, V)
sage: rho = phi.restrict(V.span([V.0, V.2]))
sage: rho.is_identity()
True
```

An identity linear transformation that is defined with a domain and codomain with wildly different bases, so that the matrix representation is not simply the identity matrix.

```
sage: A = matrix(QQ, [[1, 1, 0], [2, 3, -4], [2, 4, -7]])
sage: B = matrix(QQ, [[2, 7, -2], [-1, -3, 1], [-1, -6, 2]])
sage: U = (QQ^3).subspace_with_basis(A.rows())
sage: V = (QQ^3).subspace_with_basis(B.rows())
sage: H = Hom(U, V)
sage: id = lambda x: x
sage: phi = H(id)
sage: phi([203, -179, 34])
(203, -179, 34)
sage: phi.matrix()
[ 1  0  1]
[-9 -18 -2]
[-17 -31 -5]
sage: phi.is_identity()
True
```

TEST:

```
sage: V = QQ^10
sage: H = Hom(V, V)
sage: id = H.identity()
sage: id.is_identity()
True
```

AUTHOR:

•Rob Beezer (2011-06-28)

**is\_zero()**

Determines if this morphism is a zero function or not.

## EXAMPLES:

A zero morphism created from a function.

```
sage: V = ZZ^5
sage: W = ZZ^3
sage: z = lambda x: zero_vector(ZZ, 3)
sage: phi = V.hom(z, W)
sage: phi.is_zero()
True
```

An image list that just barely makes a non-zero morphism.

```
sage: V = ZZ^4
sage: W = ZZ^6
sage: z = zero_vector(ZZ, 6)
sage: images = [z, z, W.5, z]
sage: phi = V.hom(images, W)
sage: phi.is_zero()
False
```

## TEST:

```
sage: V = QQ^10
sage: W = QQ^3
sage: H = Hom(V, W)
sage: rho = H.zero()
sage: rho.is_zero()
True
```

## AUTHOR:

•Rob Beezer (2011-07-15)

**kernel()**

Compute the kernel of this morphism.

## EXAMPLES:

```
sage: V = VectorSpace(QQ, 3)
sage: id = V.Hom(V) (identity_matrix(QQ, 3))
sage: null = V.Hom(V) (0*identity_matrix(QQ, 3))
sage: id.kernel()
Vector space of degree 3 and dimension 0 over Rational Field
Basis matrix:
[]
sage: phi = V.Hom(V) (matrix(QQ, 3, range(9)))
sage: phi.kernel()
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[ 1 -2  1]
sage: hom(CC^2, CC^2, matrix(CC, [[1, 0], [0, 1]])).kernel()
Vector space of degree 2 and dimension 0 over Complex Field with 53 bits of precision
Basis matrix:
[]
```

**matrix()**

## EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom(V.basis())
sage: phi.matrix()
[1 0]
[0 1]
sage: sage.modules.matrix_morphism.MatrixMorphism_abstract.matrix(phi)
Traceback (most recent call last):
...
NotImplementedError: this method must be overridden in the extension class
```

**nullity()**

Returns the nullity of the matrix representing this morphism, which is the dimension of its kernel.

**EXAMPLES:**

```
sage: V = ZZ^2; phi = V.hom(V.basis())
sage: phi.nullity()
0
sage: V = ZZ^2; phi = V.hom([V.0, V.0])
sage: phi.nullity()
1
```

**rank()**

Returns the rank of the matrix representing this morphism.

**EXAMPLES:**

```
sage: V = ZZ^2; phi = V.hom(V.basis())
sage: phi.rank()
2
sage: V = ZZ^2; phi = V.hom([V.0, V.0])
sage: phi.rank()
1
```

**restrict(sub)**

Restrict this matrix morphism to a subspace sub of the domain.

The codomain and domain of the resulting matrix are both sub.

**EXAMPLES:**

```
sage: V = ZZ^2; phi = V.hom([3*V.0, 2*V.1])
sage: phi.restrict(V.span([V.0]))
Free module morphism defined by the matrix
[3]
Domain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...
Codomain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...

sage: V = (QQ^2).span_of_basis([[1,2],[3,4]])
sage: phi = V.hom([V.0+V.1, 2*V.1])
sage: phi(V.1) == 2*V.1
True
sage: W = span([V.1])
sage: phi(W)
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[ 1 4/3]
sage: psi = phi.restrict(W); psi
Vector space morphism represented by the matrix:
[2]
```

```

Domain: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[ 1 4/3]
Codomain: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[ 1 4/3]
sage: psi.domain() == W
True
sage: psi(W.0) == 2*W.0
True

```

**restrict\_codomain** (*sub*)

Restrict this matrix morphism to a subspace *sub* of the codomain.

The resulting morphism has the same domain as before, but a new codomain.

**EXAMPLES:**

```

sage: V = ZZ^2; phi = V.hom([4*(V.0+V.1),0])
sage: W = V.span([2*(V.0+V.1)])
sage: phi
Free module morphism defined by the matrix
[4 4]
[0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 2 over the principal ideal domain ...
sage: psi = phi.restrict_codomain(W); psi
Free module morphism defined by the matrix
[2]
[0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...

```

An example in which the codomain equals the full ambient space, but with a different basis:

```

sage: V = QQ^2
sage: W = V.span_of_basis([[1,2],[3,4]])
sage: phi = V.hom(matrix(QQ,2,[1,0,2,0]),W)
sage: phi.matrix()
[1 0]
[2 0]
sage: phi(V.0)
(1, 2)
sage: phi(V.1)
(2, 4)
sage: X = V.span([[1,2]]); X
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 2]
sage: phi(V.0) in X
True
sage: phi(V.1) in X
True
sage: psi = phi.restrict_codomain(X); psi
Vector space morphism represented by the matrix:
[1]
[2]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of degree 2 and dimension 1 over Rational Field

```

```
Basis matrix:
[1 2]
sage: psi(V.0)
(1, 2)
sage: psi(V.1)
(2, 4)
sage: psi(V.0).parent() is X
True
```

**restrict\_domain(sub)**

Restrict this matrix morphism to a subspace *sub* of the domain. The subspace *sub* should have a `basis()` method and elements of the basis should be coercible into domain.

The resulting morphism has the same codomain as before, but a new domain.

**EXAMPLES:**

```
sage: V = ZZ^2; phi = V.hom([3*V.0, 2*V.1])
sage: phi.restrict_domain(V.span([V.0]))
Free module morphism defined by the matrix
[3 0]
Domain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...
Codomain: Ambient free module of rank 2 over the principal ideal domain ...
sage: phi.restrict_domain(V.span([V.1]))
Free module morphism defined by the matrix
[0 2]...
```

**trace()**

Return the trace of this endomorphism.

**EXAMPLES:**

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.trace()
3
```

`sage.modules.matrix_morphism.is_MatrixMorphism(x)`

Return True if *x* is a Matrix morphism of free modules.

**EXAMPLES:**

```
sage: V = ZZ^2; phi = V.hom([3*V.0, 2*V.1])
sage: sage.modules.matrix_morphism.is_MatrixMorphism(phi)
True
sage: sage.modules.matrix_morphism.is_MatrixMorphism(3)
False
```

## FINITELY GENERATED MODULES OVER A PID

You can use Sage to compute with finitely generated modules (FGM's) over a principal ideal domain  $R$  presented as a quotient  $V/W$ , where  $V$  and  $W$  are free.

NOTE: Currently this is only enabled over  $R=\mathbb{ZZ}$ , since it has not been tested and debugged over more general PIDs. All algorithms make sense whenever there is a Hermite form implementation. In theory the obstruction to extending the implementation is only that one has to decide how elements print. If you're annoyed that by this, fix things and post a patch!

We represent  $M=V/W$  as a pair  $(V,W)$  with  $W$  contained in  $V$ , and we internally represent elements of  $M$  non-canonically as elements  $x$  of  $V$ . We also fix independent generators  $g[i]$  for  $M$  in  $V$ , and when we print out elements of  $V$  we print their coordinates with respect to the  $g[i]$ ; over  $\mathbb{Z}$  this is canonical, since each coefficient is reduce modulo the additive order of  $g[i]$ . To obtain the vector in  $V$  corresponding to  $x$  in  $M$ , use  $x.lift()$ .

Morphisms between finitely generated  $R$  modules are well supported. You create a homomorphism by simply giving the images of generators of  $M_0$  in  $M_1$ . Given a morphism  $\phi: M_0 \rightarrow M_1$ , you can compute the image of  $\phi$ , the kernel of  $\phi$ , and using  $y=\phi.lift(x)$  you can lift an elements  $x$  in  $M_1$  to an element  $y$  in  $M_0$ , if such a  $y$  exists.

TECHNICAL NOTE: For efficiency, we introduce a notion of optimized representation for quotient modules. The optimized representation of  $M=V/W$  is the quotient  $V'/W'$  where  $V'$  has as basis lifts of the generators  $g[i]$  for  $M$ . We internally store a morphism from  $M_0=V_0/W_0$  to  $M_1=V_1/W_1$  by giving a morphism from the optimized representation  $V_0'$  of  $M_0$  to  $V_1$  that sends  $W_0$  into  $W_1$ .

The following TUTORIAL illustrates several of the above points.

First we create free modules  $V_0$  and  $W_0$  and the quotient module  $M_0$ . Notice that everything works fine even though  $V_0$  and  $W_0$  are not contained inside  $\mathbb{Z}^n$ , which is extremely convenient.

```
sage: V0 = span([[1/2, 0, 0], [3/2, 2, 1], [0, 0, 1]], ZZ); W0 = V0.span([V0.0+2*V0.1, 9*V0.0+2*V0.1, 4*V0.2])
sage: M0 = V0/W0; M0
Finitely generated module V/W over Integer Ring with invariants (4, 16)
```

The invariants are computed using the Smith normal form algorithm, and determine the structure of this finitely generated module.

You can get the  $V$  and  $W$  used in constructing the quotient module using  $V()$  and  $W()$  methods:

```
sage: M0.V()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  0  0]
[ 0  2  0]
[ 0  0  1]
sage: M0.W()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  4  0]
```

```
[ 0 32 0]
[ 0  0 4]
```

We note that the optimized representation of  $M_0$ , mentioned above in the technical note has a  $V$  that need not be equal to  $V_0$ , in general.

```
sage: M0.optimized()[0].V()
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[0 0 1]
[0 2 0]
```

Create elements of  $M_0$  either by coercing in elements of  $V_0$ , getting generators, or coercing in a list or tuple or coercing in 0. Finally, one can express an element as a linear combination of the smith form generators

```
sage: M0(V0.0)
(0, 14)
sage: M0(V0.0 + W0.0) # no difference modulo W0
(0, 14)
sage: M0.linear_combination_of_smith_form_gens([3, 20])
(3, 4)
sage: 3*M0.0 + 20*M0.1
(3, 4)
```

We make an element of  $M_0$  by taking a difference of two generators, and lift it. We also illustrate making an element from a list, which coerces to  $V_0$ , then take the equivalence class modulo  $W_0$ .

```
sage: x = M0.0 - M0.1; x
(1, 15)
sage: x.lift()
(0, -2, 1)
sage: M0(vector([1/2, 0, 0]))
(0, 14)
sage: x.additive_order()
16
```

Similarly, we construct  $V_1$  and  $W_1$ , and the quotient  $M_1$ , in a completely different 2-dimensional ambient space.

```
sage: V1 = span([1/2, 0], [3/2, 2], ZZ); W1 = V1.span([2*V1.0, 3*V1.1])
sage: M1 = V1/W1; M1
Finitely generated module V/W over Integer Ring with invariants (6)
```

We create the homomorphism from  $M_0$  to  $M_1$  that sends both generators of  $M_0$  to 3 times the generator of  $M_1$ . This is well defined since 3 times the generator has order 2.

```
sage: f = M0.hom([3*M1.0, 3*M1.0]); f
Morphism from module over Integer Ring with invariants (4, 16) to module with invariants (6,) that se
```

We evaluate the homomorphism on our element  $x$  of the domain, and on the first generator of the domain. We also evaluate at an element of  $V_0$ , which is coerced into  $M_0$ .

```
sage: f(x)
(0)
sage: f(M0.0)
(3)
sage: f(V0.1)
(3)
```



Here we illustrate lifting an element of the image of  $f$ , i.e., finding an element of  $M_0$  that maps to a given element of  $M_1$ :

```
sage: y = f.lift(3*M1.0); y
(0, 13)
sage: f(y)
(3)
```

We compute the kernel of  $f$ , i.e., the submodule of elements of  $M_0$  that map to 0. Note that the kernel is not explicitly represented as a submodule, but as another quotient  $V/W$  where  $V$  is contained in  $V_0$ . You can explicitly coerce elements of the kernel into  $M_0$  though.

```
sage: K = f.kernel(); K
Finitely generated module V/W over Integer Ring with invariants (2, 16)

sage: M0(K.0)
(2, 0)
sage: M0(K.1)
(3, 1)
sage: f(M0(K.0))
(0)
sage: f(M0(K.1))
(0)
```

We compute the image of  $f$ .

```
sage: f.image()
Finitely generated module V/W over Integer Ring with invariants (2)
```

Notice how the elements of the image are written as (0) and (1), despite the image being naturally a submodule of  $M_1$ , which has elements (0), (1), (2), (3), (4), (5). However, below we coerce the element (1) of the image into the codomain, and get (3):

```
sage: list(f.image())
[(0), (1)]
sage: list(M1)
[(0), (1), (2), (3), (4), (5)]
sage: x = f.image().0; x
(1)
sage: M1(x)
(3)
```

TESTS:

```
sage: from sage.modules.fg_pid.fgp_module import FGP_Module
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ)
sage: W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = FGP_Module(V, W); Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.linear_combination_of_smith_form_gens([1, 3])
(1, 3)
sage: Q(V([1, 3, 4]))
(0, 11)
sage: Q(W([1, 16, 0]))
(0, 0)
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], QQ)
sage: W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1])
sage: Q = FGP_Module(V, W); Q
```

Finitely generated module  $V/W$  over Rational Field with invariants (0)

```
sage: q = Q.an_element(); q
(1)
sage: q*(1/2)
(1/2)
sage: (1/2)*q
(1/2)
```

AUTHOR:

- William Stein, 2009

`sage.modules.fg_pid.fgp_module.FGP_Module(V, W, check=True)`

INPUT:

- $V$  – a free  $R$ -module
- $W$  – a free  $R$ -submodule of  $V$
- `check` – bool (default: `True`); if `True`, more checks on correctness are performed; in particular, we check the data types of  $V$  and  $W$ , and that  $W$  is a submodule of  $V$  with the same base ring.

OUTPUT:

- the quotient  $V/W$  as a finitely generated  $R$ -module

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: import sage.modules.fg_pid.fgp_module
sage: Q = sage.modules.fg_pid.fgp_module.FGP_Module(V, W)
sage: type(Q)
<class 'sage.modules.fg_pid.fgp_module.FGP_Module_class_with_category'>
sage: Q is sage.modules.fg_pid.fgp_module.FGP_Module(V, W, check=False)
True
```

**class** `sage.modules.fg_pid.fgp_module.FGP_Module_class(V, W, check=True)`

Bases: `sage.modules.module.Module`

A finitely generated module over a PID presented as a quotient  $V/W$ .

INPUT:

- $V$  – an  $R$ -module
- $W$  – an  $R$ -submodule of  $V$
- `check` – bool (default: `True`)

EXAMPLES:

```
sage: A = (ZZ^1)/span([[100]], ZZ); A
Finitely generated module V/W over Integer Ring with invariants (100)
sage: A.V()
Ambient free module of rank 1 over the principal ideal domain Integer Ring
sage: A.W()
Free module of degree 1 and rank 1 over Integer Ring
Echelon basis matrix:
[100]

sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
```

```
sage: type(Q)
<class 'sage.modules.fg_pid.fgp_module.FGP_Module_class_with_category'>
```

**Element**

alias of FGP\_Element

**V()**

If this module was constructed as a quotient  $V/W$ , returns  $V$ .

**EXAMPLES:**

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.V()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  0  0]
[  0  1  0]
[  0  0  1]
```

**W()**

If this module was constructed as a quotient  $V/W$ , returns  $W$ .

**EXAMPLES:**

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.W()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  8  0]
[  0 12  0]
[  0  0  4]
```

**annihilator()**

Return the ideal of the base ring that annihilates self. This is precisely the ideal generated by the LCM of the invariants of self if self is finite, and is 0 otherwise.

**EXAMPLES:**

```
sage: V = span([[1/2, 0, 0], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([V.0+2*V.1, 9*V.0+2*V.1, 4*V.2])
sage: Q = V/W; Q.annihilator()
Principal ideal (16) of Integer Ring
sage: Q.annihilator().gen()
16

sage: Q = V/V.span([V.0]); Q
Finitely generated module V/W over Integer Ring with invariants (0, 0)
sage: Q.annihilator()
Principal ideal (0) of Integer Ring
```

**base\_ring()****EXAMPLES:**

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.base_ring()
Integer Ring
```

**cardinality()**

Return the cardinality of this module as a set.

#### EXAMPLES:

```
sage: V = ZZ^2; W = V.span([[1,2],[3,4]]); A = V/W; A
Finitely generated module V/W over Integer Ring with invariants (2)
sage: A.cardinality()
2
sage: V = ZZ^2; W = V.span([[1,2]]); A = V/W; A
Finitely generated module V/W over Integer Ring with invariants (0)
sage: A.cardinality()
+Infinity
sage: V = QQ^2; W = V.span([[1,2]]); A = V/W; A
Vector space quotient V/W of dimension 1 over Rational Field where
V: Vector space of dimension 2 over Rational Field
W: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 2]
sage: A.cardinality()
+Infinity
```

#### `coordinate_vector` (*x*, *reduce=False*)

Return coordinates of *x* with respect to the optimized representation of self.

#### INPUT:

- *x* – element of self
- *reduce* – (default: False); if True, reduce coefficients modulo invariants; this is ignored if the base ring isn't ZZ.

#### OUTPUT:

The coordinates as a vector. That is, the same type as `self.V()`, but in general with fewer entries.

#### EXAMPLES:

```
sage: V = span([[1/4,0,0],[3/4,4,2],[0,0,2]],ZZ); W = V.span([4*V.0+12*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 0, 0)
sage: Q.coordinate_vector(-Q.0)
(-1, 0, 0)
sage: Q.coordinate_vector(-Q.0, reduce=True)
(3, 0, 0)
```

If *x* isn't in self, it is coerced in:

```
sage: Q.coordinate_vector(V.0)
(1, 0, -3)
sage: Q.coordinate_vector(Q(V.0))
(1, 0, -3)
```

#### TESTS:

```
sage: V = span([[1/2,0,0],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.coordinate_vector(Q.0 - Q.1)
(1, -1)

sage: O, X = Q.optimized()
sage: O.V()
Free module of degree 3 and rank 2 over Integer Ring
```

```

User basis matrix:
[0 0 1]
[0 2 0]
sage: phi = Q.hom([Q.0, 4*Q.1])
sage: x = Q(V.0); x
(0, 4)
sage: Q.coordinate_vector(x, reduce=True)
(0, 4)
sage: Q.coordinate_vector(-x, reduce=False)
(0, -4)
sage: x == 4*Q.1
True
sage: x = Q(V.1); x
(0, 1)
sage: Q.coordinate_vector(x)
(0, 1)
sage: x == Q.1
True
sage: x = Q(V.2); x
(1, 0)
sage: Q.coordinate_vector(x)
(1, 0)
sage: x == Q.0
True

```

**cover()**

If this module was constructed as  $V/W$ , returns the cover module  $V$ . This is the same as `self.V()`.

**EXAMPLES:**

```

sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.V()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  0  0]
[  0  1  0]
[  0  0  1]

```

**gen(i)**

Return the  $i$ -th generator of self.

**INPUT:**

- $i$  – integer

**EXAMPLES:**

```

sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.gen(0)
(1, 0)
sage: Q.gen(1)
(0, 1)
sage: Q.gen(2)
Traceback (most recent call last):
...
ValueError: Generator 2 not defined
sage: Q.gen(-1)

```

```
Traceback (most recent call last):
...
ValueError: Generator -1 not defined
```

**gens()**

Returns tuple of elements  $g_0, \dots, g_n$  of self such that the module generated by the  $g_i$  is isomorphic to the direct sum of  $R/e_i R$ , where  $e_i$  are the invariants of self and  $R$  is the base ring.

Note that these are not generally uniquely determined, and depending on how Smith normal form is implemented for the base ring, they may not even be deterministic.

This can safely be overridden in all derived classes.

**EXAMPLES:**

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.0+12*V.1])
sage: Q = V/W
sage: Q.gens()
((1, 0), (0, 1))
sage: Q.0
(1, 0)
```

**has\_canonical\_map\_to(A)**

Return True if self has a canonical map to A, relative to the given presentation of A. This means that A is a finitely generated quotient module, self.V() is a submodule of A.V() and self.W() is a submodule of A.W(), i.e., that there is a natural map induced by inclusion of the V's. Note that we do *not* require that this natural map be injective; for this use `is_submodule()`.

**EXAMPLES:**

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.0+12*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: A = Q.submodule((Q.0, Q.0 + 3*Q.1)); A
Finitely generated module V/W over Integer Ring with invariants (4, 4)
sage: A.has_canonical_map_to(Q)
True
sage: Q.has_canonical_map_to(A)
False
```

**hom(im\_gens, codomain=None, check=True)**

Homomorphism defined by giving the images of `self.gens()` in some fixed fg R-module.

---

**Note:** We do not assume that the generators given by `self.gens()` are the same as the Smith form generators, since this may not be true for a general derived class.

---

**INPUTS:**

- `im_gens` – a list of the images of `self.gens()` in some R-module

**EXAMPLES:**

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.0+12*V.1])
sage: Q = V/W
sage: phi = Q.hom([3*Q.1, Q.0])
sage: phi
Morphism from module over Integer Ring with invariants (4, 12) to module with invariants (4, 4)
sage: phi(Q.0)
(0, 3)
sage: phi(Q.1)
(0, 0)
```

```
(1, 0)
sage: Q.0 == phi(Q.1)
True
```

This example illustrates creating a morphism to a free module. The free module is turned into an FGP module (i.e., quotient  $V/W$  with  $W=0$ ), and the morphism is constructed:

```
sage: V = span([[1/2, 0, 0], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (2, 0, 0)
sage: phi = Q.hom([0, V.0, V.1]); phi
Morphism from module over Integer Ring with invariants (2, 0, 0) to module with invariants (0, 0, 0)
sage: phi.domain()
Finitely generated module V/W over Integer Ring with invariants (2, 0, 0)
sage: phi.codomain()
Finitely generated module V/W over Integer Ring with invariants (0, 0, 0)
sage: phi(Q.0)
(0, 0, 0)
sage: phi(Q.1)
(1, 0, 0)
sage: phi(Q.2) == V.1
True
```

Constructing two zero maps from the zero module:

```
sage: A = (ZZ^2)/(ZZ^2); A
Finitely generated module V/W over Integer Ring with invariants ()
sage: A.hom([])
Morphism from module over Integer Ring with invariants () to module with invariants () that
sage: A.hom([]).codomain() is A
True
sage: B = (ZZ^3)/(ZZ^3)
sage: A.hom([], codomain=B)
Morphism from module over Integer Ring with invariants () to module with invariants () that
sage: phi = A.hom([], codomain=B); phi
Morphism from module over Integer Ring with invariants () to module with invariants () that
sage: phi(A(0))
()
sage: phi(A(0)) == B(0)
True
```

A degenerate case:

```
sage: A = (ZZ^2)/(ZZ^2)
sage: phi = A.hom([]); phi
Morphism from module over Integer Ring with invariants () to module with invariants () that
sage: phi(A(0))
()
```

The code checks that the morphism is valid. In the example below we try to send a generator of order 2 to an element of order 14:

```
sage: V = span([[1/14, 3/14], [0, 1/2]], ZZ); W = ZZ^2
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (2, 14)
sage: Q.linear_combination_of_smith_form_gens([1, 1]).additive_order()
14
sage: f = Q.hom([Q.linear_combination_of_smith_form_gens([1, 1]), Q.linear_combination_of_smith_form_gens([1, 1])])
Traceback (most recent call last):
...
```

**ValueError:** phi must send optimized submodule of  $M.W()$  into  $N.W()$

### **invariants** (*include\_ones=False*)

Return the diagonal entries of the smith form of the relative matrix that defines self (see `_relative_matrix()`) padded with zeros, excluding 1's by default. Thus if  $v$  is the list of integers returned, then self is abstractly isomorphic to the product of cyclic groups  $Z/nZ$  where  $n$  is in  $v$ .

INPUT:

- `include_ones` – bool (default: False); if True, also include 1's in the output list.

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.invariants()
(4, 12)
```

An example with 1 and 0 rows:

```
sage: V = ZZ^3; W = V.span([[1, 2, 0], [0, 1, 0], [0, 2, 0]]); Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (0)
sage: Q.invariants()
(0,)
sage: Q.invariants(include_ones=True)
(1, 1, 0)
```

### **is\_finite** ()

Return True if self is finite and False otherwise.

EXAMPLES:

```
sage: V = span([[1/2, 0, 0], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([V.0+2*V.1, 9*V.0+2*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 16)
sage: Q.is_finite()
True
sage: Q = V/V.zero_submodule(); Q
Finitely generated module V/W over Integer Ring with invariants (0, 0, 0)
sage: Q.is_finite()
False
```

### **is\_submodule** (A)

Return True if self is a submodule of A. More precisely, this returns True if `self.V()` is a submodule of `A.V()`, with `self.W()` equal to `A.W()`.

Compare `has_canonical_map_to()`.

EXAMPLES:

```
sage: V = ZZ^2; W = V.span([[1, 2]]); W2 = W.scale(2)
sage: A = V/W; B = W/W2
sage: B.is_submodule(A)
False
sage: A = V/W2; B = W/W2
sage: B.is_submodule(A)
True
```

This example illustrates that this command works in a subtle cases.:



```

sage: A = ZZ^1
sage: Q3 = A / A.span([[3]])
sage: Q6 = A / A.span([[6]])
sage: Q6.is_submodule(Q3)
False
sage: Q6.has_canonical_map_to(Q3)
True
sage: Q = A.span([[2]]) / A.span([[6]])
sage: Q.is_submodule(Q6)
True

```

#### **linear\_combination\_of\_smith\_form\_gens**(x)

Compute a linear combination of the optimised generators of this module as returned by `smith_form_gens()`.

EXAMPLE:

```

sage: X = ZZ**2 / span([[3,0],[0,2]], ZZ)
sage: X.linear_combination_of_smith_form_gens([1])
(1)

```

#### **ngens**()

Return the number of generators of self.

(Note for developers: This is just the length of `gens()`, rather than of the minimal set of generators as returned by `smith_form_gens()`; these are the same in the `FGP_Module_class`, but not necessarily in derived classes.)

EXAMPLES:

```

sage: A = (ZZ**2) / span([[4,0],[0,3]], ZZ)
sage: A.ngens()
1

```

This works (but please don't do it in production code!)

```

sage: A.gens = lambda: [1,2,"Barcelona!"]
sage: A.ngens()
3

```

#### **optimized**()

Return a module isomorphic to this one, but with  $V$  replaced by a submodule of  $V$  such that the generators of self all lift trivially to generators of  $V$ . Replace  $W$  by the intersection of  $V$  and  $W$ . This has the advantage that  $V$  has small dimension and any homomorphism from self trivially extends to a homomorphism from  $V$ .

OUTPUT:

- $Q$  – an optimized quotient  $V_0/W_0$  with  $V_0$  a submodule of  $V$  such that  $\text{phi}: V_0/W_0 \rightarrow V/W$  is an isomorphism
- $Z$  – matrix such that if  $x$  is in  $\text{self.V}()$  and  $c$  gives the coordinates of  $x$  in terms of the basis for  $\text{self.V}()$ , then  $c*Z$  is in  $V_0$  and  $c*Z$  maps to  $x$  via  $\text{phi}$  above.

EXAMPLES:

```

sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: O, X = Q.optimized(); O
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: O.V()

```

```
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[0 0 1]
[0 1 0]
sage: O.W()
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 0 12  0]
[ 0  0  4]
sage: X
[0 4 0]
[0 1 0]
[0 0 1]
sage: OV = O.V()
sage: Q(OV([0,-8,0])) == V.0
True
sage: Q(OV([0,1,0])) == V.1
True
sage: Q(OV([0,0,1])) == V.2
True
```

**random\_element** (\*args, \*\*kws)

Create a random element of self=V/W, by creating a random element of V and reducing it modulo W.

All arguments are passed onto the random\_element method of V.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.random_element()
(1, 10)
```

**relations** ()

If this module was constructed as V/W, returns the relations module V. This is the same as self.W().

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.relations()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  8  0]
[ 0 12  0]
[ 0  0  4]
```

**smith\_form\_gen** (i)

Return the i-th generator of self. A private name (so we can freely override gen() in derived classes).

INPUT:

• i – integer

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.smith_form_gen(0)
(1, 0)
```

```
sage: Q.smith_form_gen(1)
(0, 1)
```

### **smith\_form\_gens()**

Return a set of generators for self which are in Smith normal form.

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.smith_form_gens()
((1, 0), (0, 1))
sage: [x.lift() for x in Q.smith_form_gens()]
[(0, 0, 1), (0, 1, 0)]
```

### **submodule(x)**

Return the submodule defined by x.

INPUT:

- x – list, tuple, or FGP module

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.gens()
((1, 0), (0, 1))
```

We create submodules generated by a list or tuple of elements:

```
sage: Q.submodule([Q.0])
Finitely generated module V/W over Integer Ring with invariants (4)
sage: Q.submodule([Q.1])
Finitely generated module V/W over Integer Ring with invariants (12)
sage: Q.submodule((Q.0, Q.0 + 3*Q.1))
Finitely generated module V/W over Integer Ring with invariants (4, 4)
```

A submodule defined by a submodule:

```
sage: A = Q.submodule((Q.0, Q.0 + 3*Q.1)); A
Finitely generated module V/W over Integer Ring with invariants (4, 4)
sage: Q.submodule(A)
Finitely generated module V/W over Integer Ring with invariants (4, 4)
```

Inclusion is checked:

```
sage: A.submodule(Q)
Traceback (most recent call last):
...
ValueError: x.V() must be contained in self's V.
```

### **sage.modules.fg\_pid.fgp\_module.is\_FGP\_Module(x)**

Return true if x is an FGP module, i.e., a finitely generated module over a PID represented as a quotient of finitely generated free modules over a PID.

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: sage.modules.fg_pid.fgp_module.is_FGP_Module(V)
False
```

```
sage: sage.modules.fg_pid.fgp_module.is_FGP_Module(Q)
True
```

`sage.modules.fg_pid.fgp_module.random_fgp_module(n, R=Integer Ring, finite=False)`  
Return a random FGP module inside a rank  $n$  free module over  $R$ .

INPUT:

- $n$  – nonnegative integer
- $R$  – base ring (default:  $\mathbb{Z}$ )
- `finite` – bool (default: `True`); if `True`, make the random module finite.

EXAMPLES:

```
sage: import sage.modules.fg_pid.fgp_module as fgp
sage: fgp.random_fgp_module(4)
Finitely generated module V/W over Integer Ring with invariants (4)
```

`sage.modules.fg_pid.fgp_module.random_fgp_morphism_0(*args, **kws)`  
Construct a random fgp module using `random_fgp_module`, then construct a random morphism that sends each generator to a random multiple of itself. Inputs are the same as to `random_fgp_module`.

EXAMPLES:

```
sage: import sage.modules.fg_pid.fgp_module as fgp
sage: fgp.random_fgp_morphism_0(4)
Morphism from module over Integer Ring with invariants (4,) to module with invariants (4,) that
```

`sage.modules.fg_pid.fgp_module.test_morphism_0(*args, **kws)`

EXAMPLES:

```
sage: import sage.modules.fg_pid.fgp_module as fgp
sage: s = 0 # we set a seed so results clearly and easily reproducible across runs.
sage: set_random_seed(s); v = [fgp.test_morphism_0(1) for _ in range(30)]
sage: set_random_seed(s); v = [fgp.test_morphism_0(2) for _ in range(30)]
sage: set_random_seed(s); v = [fgp.test_morphism_0(3) for _ in range(10)]
sage: set_random_seed(s); v = [fgp.test_morphism_0(i) for i in range(1,20)]
sage: set_random_seed(s); v = [fgp.test_morphism_0(4) for _ in range(50)] # long time
```

## ELEMENTS OF FINITELY GENERATED MODULES OVER A PID

### AUTHOR:

- William Stein, 2009

**class** sage.modules.fg\_pid.fgp\_element.FGP\_Element (parent, x, check=True)  
Bases: sage.structure.element.ModuleElement

An element of a finitely generated module over a PID.

### INPUT:

- parent – parent module M
- x – element of M.V()

### EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: x = Q(V.0-V.1); x #indirect doctest
(0, 3)
sage: isinstance(x, sage.modules.fg_pid.fgp_element.FGP_Element)
True
sage: type(x)
<class 'sage.modules.fg_pid.fgp_element.FGP_Module_class_with_category.element_class'>
sage: x is Q(x)
True
sage: x.parent() is Q
True
```

### TESTS:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: loads(dumps(Q.0)) == Q.0
True
```

### additive\_order()

Return the additive order of this element.

### EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.0.additive_order()
4
sage: Q.1.additive_order()
12
sage: (Q.0+Q.1).additive_order()
```

```
12
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (12, 0)
sage: Q.0.additive_order()
12
sage: type(Q.0.additive_order())
<type 'sage.rings.integer.Integer'>
sage: Q.1.additive_order()
+Infinity
```

**lift()**

Lift self to an element of  $V$ , where the parent of self is the quotient module  $V/W$ .

**EXAMPLES:**

```
sage: V = span([[1/2,0,0],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.0+12*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.0
(1, 0)
sage: Q.1
(0, 1)
sage: Q.0.lift()
(0, 0, 1)
sage: Q.1.lift()
(0, 2, 0)
sage: x = Q(V.0); x
(0, 4)
sage: x.lift()
(1/2, 0, 0)
sage: x == 4*Q.1
True
sage: x.lift().parent() == V
True
```

A silly version of the integers modulo 100:

```
sage: A = (ZZ^1)/span([[100]], ZZ); A
Finitely generated module V/W over Integer Ring with invariants (100)
sage: x = A([5]); x
doctest:...: DeprecationWarning: The default behaviour changed!
  If you *really* want a linear combination of smith generators,
  use .linear_combination_of_smith_form_gens.
See http://trac.sagemath.org/16261 for details.
(5)
sage: v = x.lift(); v
(5)
sage: v.parent()
Ambient free module of rank 1 over the principal ideal domain Integer Ring
```

**vector()****EXAMPLES:**

```
sage: V = span([[1/2,0,0],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.0+12*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: x = Q.0 + 3*Q.1; x
(1, 3)
```

```
sage: x.vector()
(1, 3)
sage: tuple(x)
(1, 3)
sage: list(x)
[1, 3]
sage: x.vector().parent()
Ambient free module of rank 2 over the principal ideal domain Integer Ring
```





## MORPHISMS BETWEEN FINITELY GENERATED MODULES OVER A PID

AUTHOR: - William Stein, 2009

```
sage.modules.fg_pid.fgp_morphism.FGP_Homset(X, Y)
```

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = Hom(Q) # indirect doctest
Set of Morphisms from Finitely generated module V/W over Integer Ring with invariants (4, 12) to
sage: True # Q.Hom(Q) is Q.Hom(Q)
True
sage: type(Q.Hom(Q))
<class 'sage.modules.fg_pid.fgp_morphism.FGP_Homset_class_with_category'>
```

```
class sage.modules.fg_pid.fgp_morphism.FGP_Homset_class(X, Y, category=None)
```

Bases: sage.categories.homset.Homset

Homsets of FGP\_Module

TESTS:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: H = Hom(Q, Q); H # indirect doctest
Set of Morphisms from Finitely generated module V/W over Integer Ring with invariants (4, 12) to
sage: type(H)
<class 'sage.modules.fg_pid.fgp_morphism.FGP_Homset_class_with_category'>
```

**Element**

alias of FGP\_Morphism

```
class sage.modules.fg_pid.fgp_morphism.FGP_Morphism(parent, phi, check=True)
```

Bases: sage.categories.morphism.Morphism

A morphism between finitely generated modules over a PID.

EXAMPLES:

An endomorphism:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: phi = Q.hom([Q.0+3*Q.1, -Q.1]); phi
Morphism from module over Integer Ring with invariants (4, 12) to module with invariants (4, 12)
sage: phi(Q.0) == Q.0 + 3*Q.1
True
sage: phi(Q.1) == -Q.1
True
```

A morphism between different modules  $V1/W1 \rightarrow V2/W2$  in different ambient spaces:

```
sage: V1 = ZZ^2; W1 = V1.span([[1,2],[3,4]]); A1 = V1/W1
sage: V2 = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W2 = V2.span([2*V2.0+4*V2.1, 9*V2.0+12*V2.1,
sage: A1
Finitely generated module V/W over Integer Ring with invariants (2)
sage: A2
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: phi = A1.hom([2*A2.0])
sage: phi(A1.0)
(2, 0)
sage: 2*A2.0
(2, 0)
sage: phi(2*A1.0)
(0, 0)
```

TESTS:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: phi = Q.hom([Q.0,Q.0 + 2*Q.1])
sage: loads(dumps(phi)) == phi
True
```

**im\_gens()**

Return tuple of the images of the generators of the domain under this morphism.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: phi = Q.hom([Q.0,Q.0 + 2*Q.1])
sage: phi.im_gens()
((1, 0), (1, 2))
sage: phi.im_gens() is phi.im_gens()
True
```

**image()**

Compute the image of this homomorphism.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.hom([Q.0+3*Q.1, -Q.1]).image()
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.hom([3*Q.1, Q.1]).image()
Finitely generated module V/W over Integer Ring with invariants (12)
```

**inverse\_image(A)**

Given a submodule A of the codomain of this morphism, return the inverse image of A under this morphism.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: phi = Q.hom([0, Q.1])
sage: phi.inverse_image(Q.submodule([]))
Finitely generated module V/W over Integer Ring with invariants (4)
sage: phi.kernel()
```

```

Finitely generated module V/W over Integer Ring with invariants (4)
sage: phi.inverse_image(phi.codomain())
Finitely generated module V/W over Integer Ring with invariants (4, 12)

sage: phi.inverse_image(Q.submodule([Q.0]))
Finitely generated module V/W over Integer Ring with invariants (4)
sage: phi.inverse_image(Q.submodule([Q.1]))
Finitely generated module V/W over Integer Ring with invariants (4, 12)

sage: phi.inverse_image(ZZ^3)
Traceback (most recent call last):
...
TypeError: A must be a finitely generated quotient module
sage: phi.inverse_image(ZZ^3 / W.scale(2))
Traceback (most recent call last):
...
ValueError: A must be a submodule of the codomain

```

**kernel()**

Compute the kernel of this homomorphism.

**EXAMPLES:**

```

sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.hom([0, Q.1]).kernel()
Finitely generated module V/W over Integer Ring with invariants (4)
sage: A = Q.hom([Q.0, 0]).kernel(); A
Finitely generated module V/W over Integer Ring with invariants (12)
sage: Q.1 in A
True
sage: phi = Q.hom([Q.0-3*Q.1, Q.0+Q.1])
sage: A = phi.kernel(); A
Finitely generated module V/W over Integer Ring with invariants (4)
sage: phi(A)
Finitely generated module V/W over Integer Ring with invariants ()

```

**lift(x)**

Given an element  $x$  in the codomain of self, if possible find an element  $y$  in the domain such that  $\text{self}(y) == x$ . Raise a `ValueError` if no such  $y$  exists.

**INPUT:**

- $x$  – element of the codomain of self.

**EXAMPLES:**

```

sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q=V/W; phi = Q.hom([2*Q.0, Q.1])
sage: phi.lift(Q.1)
(0, 1)
sage: phi.lift(Q.0)
Traceback (most recent call last):
...
ValueError: no lift of element to domain
sage: phi.lift(2*Q.0)
(1, 0)
sage: phi.lift(2*Q.0+Q.1)
(1, 1)

```

```
sage: V = span([[5, -1/2]], ZZ); W = span([[20, -2]], ZZ); Q = V/W; phi=Q.hom([2*Q.0])
sage: x = phi.image().0; phi(phi.lift(x)) == x
True
```

## DIAMOND CUTTING IMPLEMENTATION

AUTHORS:

- Jan Poeschko (2012-07-02): initial version

```
sage.modules.diamond_cutting.calculate_voronoi_cell(basis, radius=None, verbose=False)
```

Calculate the Voronoi cell of the lattice defined by basis

INPUT:

- `basis` – embedded basis matrix of the lattice
- `radius` – radius of basis vectors to consider
- `verbose` – whether to print debug information

OUTPUT:

A :class:Polyhedron instance.

EXAMPLES:

```
sage: from sage.modules.diamond_cutting import calculate_voronoi_cell
sage: V = calculate_voronoi_cell(matrix([[1, 0], [0, 1]]))
sage: V.volume()
1
```

```
sage.modules.diamond_cutting.diamond_cut(V, GM, C, verbose=False)
```

Perform diamond cutting on polyhedron `V` with basis matrix `GM` and radius `C`.

INPUT:

- `V` – polyhedron to cut from
- `GM` – half of the basis matrix of the lattice
- `C` – radius to use in cutting algorithm
- `verbose` – (default: `False`) whether to print debug information

OUTPUT:

A :class:Polyhedron instance.

EXAMPLES:

```
sage: from sage.modules.diamond_cutting import diamond_cut
sage: V = Polyhedron([[0], [2]])
sage: GM = matrix([2])
sage: V = diamond_cut(V, GM, 4)
sage: V.vertices()
(A vertex at (2), A vertex at (0))
```

`sage.modules.diamond_cutting.jacobi(M)`

Compute the upper-triangular part of the Cholesky/Jacobi decomposition of the symmetric matrix  $M$ .

Let  $M$  be a symmetric  $n \times n$ -matrix over a field  $F$ . Let  $m_{i,j}$  denote the  $(i,j)$ -th entry of  $M$  for any  $1 \leq i \leq n$  and  $1 \leq j \leq n$ . Then, the upper-triangular part computed by this method is the upper-triangular  $n \times n$ -matrix  $Q$  whose  $(i,j)$ -th entry  $q_{i,j}$  satisfies

$$q_{i,j} = \begin{cases} \frac{1}{q_{i,i}} (m_{i,j} - \sum_{r < i} q_{r,i} q_{r,j}) & i < j, \\ a_{i,j} - \sum_{r < i} q_{r,i} q_{r,i}^2 & i = j, \\ 0 & i > j, \end{cases}$$

for all  $1 \leq i \leq n$  and  $1 \leq j \leq n$ . (These equalities determine the entries of  $Q$  uniquely by recursion.) This matrix  $Q$  is defined for all  $M$  in a certain Zariski-dense open subset of the set of all  $n \times n$ -matrices.

EXAMPLES:

```
sage: from sage.modules.diamond_cutting import jacobi
```

```
sage: jacobi(identity_matrix(3) * 4)
```

```
[4 0 0]
```

```
[0 4 0]
```

```
[0 0 4]
```

```
sage: def testall(M):
```

```
.....:     Q = jacobi(M)
```

```
.....:     for j in range(3):
```

```
.....:         for i in range(j):
```

```
.....:             if Q[i,j] * Q[i,i] != M[i,j] - sum(Q[r,i] * Q[r,j] * Q[r,r] for r in range(i)):
```

```
.....:                 return False
```

```
.....:     for i in range(3):
```

```
.....:         if Q[i,i] != M[i,i] - sum(Q[r,i] ** 2 * Q[r,r] for r in range(i)):
```

```
.....:             return False
```

```
.....:         for j in range(i):
```

```
.....:             if Q[i,j] != 0:
```

```
.....:                 return False
```

```
.....:     return True
```

```
sage: M = Matrix(QQ, [[8,1,5], [1,6,0], [5,0,3]])
```

```
sage: Q = jacobi(M); Q
```

```
[ 8  1/8  5/8]
```

```
[ 0 47/8 -5/47]
```

```
[ 0  0 -9/47]
```

```
sage: testall(M)
```

```
True
```

```
sage: M = Matrix(QQ, [[3,6,-1,7], [6,9,8,5], [-1,8,2,4], [7,5,4,0]])
```

```
sage: testall(M)
```

```
True
```

`sage.modules.diamond_cutting.plane_inequality(v)`

Return the inequality for points on the same side as the origin with respect to the plane through  $v$  normal to  $v$ .

EXAMPLES:

```
sage: from sage.modules.diamond_cutting import plane_inequality
```

```
sage: ieq = plane_inequality([1, -1]); ieq
```

```
[2, -1, 1]
```

```
sage: ieq[0] + vector(ieq[1:]) * vector([1, -1])
```

```
0
```

## CONCRETE CLASSES RELATED TO MODULES WITH A DISTINGUISHED BASIS.

This module provides concrete classes for various constructions related to modules with a distinguished basis:

- `morphism` – Concrete classes for morphisms of modules with basis

**See also:**

The category `ModulesWithBasis`





## MODULE WITH BASIS MORPHISMS

This module contains a hierarchy of classes for morphisms of modules with a basis (category `Modules.WithBasis`):

- `ModuleMorphism`
- `ModuleMorphismByLinearity`
- `ModuleMorphismFromMatrix`
- `ModuleMorphismFromFunction`
- `TriangularModuleMorphism`
- `TriangularModuleMorphismByLinearity`
- `TriangularModuleMorphismFromFunction`

These are internal classes; it is recommended *not* to use them directly, and instead to construct morphisms through the `ModulesWithBasis.ParentMethods.module_morphism()` method of the domain, or through the homset. See the former for an overview of the possible arguments.

### EXAMPLES:

We construct a morphism through the method `ModulesWithBasis.ParentMethods.module_morphism()`, by specifying the image of each element of the distinguished basis:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4]); y = Y.basis()
sage: on_basis = lambda i: Y.monomial(i) + 2*Y.monomial(i+1)
```

```
sage: phi1 = X.module_morphism(on_basis, codomain=Y)
sage: phi1(x[1])
B[1] + 2*B[2]
```

```
sage: phi1
```

Generic morphism:

From: Free module generated by {1, 2, 3} over Rational Field

To: Free module generated by {1, 2, 3, 4} over Rational Field

```
sage: phi1.parent()
```

Set of Morphisms from Free module generated by {1, 2, 3} over Rational Field to Free module generated by {1, 2, 3, 4} over Rational Field

```
sage: phi1.__class__
```

```
<class 'sage.modules.with_basis.morphism.ModuleMorphismByLinearity_with_category'>
```

Constructing the same morphism from the homset:

```
sage: H = Hom(X, Y)
```

```
sage: phi2 = H(on_basis=on_basis)
```

```
sage: phi1 == phi2
True
```

Constructing the same morphism directly using the class; no backward compatibility is guaranteed in this case:

```
sage: from sage.modules.with_basis.morphism import ModuleMorphismByLinearity
sage: phi3 = ModuleMorphismByLinearity(X, on_basis, codomain=Y)
sage: phi3 == phi1
True
```

**Warning:** The hierarchy of classes implemented in this module is one of the first non-trivial hierarchies of classes for morphisms. It is hitting a couple scaling issues:

- There are many independent properties from which module morphisms can get code (being defined by linearity, from a matrix, or a function; being triangular, being diagonal, ...). How to mitigate the class hierarchy growth?

This will become even more stringent as more properties are added (e.g. being defined from generators for an algebra morphism, ...)

Categories, whose primary purpose is to provide infrastructure for handling such large hierarchy of classes, can't help at this point: there is no category whose morphisms are triangular morphisms, and it's not clear such a category would be sensible.

- How to properly handle `__init__` method calls and multiple inheritance?
- Who should be in charge of setting the default category: the classes themselves, or `ModulesWithBasis.ParentMethods.module_morphism()`?

Because of this, the hierarchy of classes, and the specific APIs, is likely to be refactored as better infrastructure and best practices emerge.

AUTHORS:

- Nicolas M. Thiery (2008-2015)
- Jason Bandlow and Florent Hivert (2010): Triangular Morphisms
- Christian Stump (2010): [trac ticket #9648](#) module\_morphism's to a wider class of codomains

Before [trac ticket #8678](#), this hierarchy of classes used to be in `sage.categories.modules_with_basis`; see [trac ticket #8678](#) for the complete log.

```
class sage.modules.with_basis.morphism.DiagonalModuleMorphism(domain, diagonal,
                                                                codomain=None,
                                                                category=None)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphismByLinearity`

A class for diagonal module morphisms.

See `ModulesWithBasis.ParentMethods.module_morphism()`.

INPUT:

- `domain, codomain` – two modules with basis  $F$  and  $G$ , respectively
- `diagonal` – a function  $d$

Assumptions:

- `domain` and `codomain` have the same base ring  $R$ ,
- their respective bases  $F$  and  $G$  have the same index set  $I$ ,
- $d$  is a function  $I \rightarrow R$ .

Return the diagonal module morphism from domain to codomain sending  $F(i) \mapsto d(i)G(i)$  for all  $i \in I$ .

By default, `codomain` is currently assumed to be `domain`. (Todo: make a consistent choice with `*ModuleMorphism`.)

---

#### Todo

- Implement an optimized `_call_()` function.
  - Generalize to a `mapcoeffs`.
  - Generalize to a `mapterms`.
- 

#### EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X")
sage: phi = X.module_morphism(diagonal=factorial, codomain=X)
sage: x = X.basis()
sage: phi(x[1]), phi(x[2]), phi(x[3])
(B[1], 2*B[2], 6*B[3])
```

```
class sage.modules.with_basis.morphism.ModuleMorphism(domain, codomain=None, cate-
                                                    gory=None, affine=False)
```

Bases: `sage.categories.morphism.Morphism`

The top abstract base class for module with basis morphisms.

#### INPUT:

- `domain` – a parent in `ModulesWithBasis(...)`
- `codomain` – a parent in `Modules(...)`;
- `category` – a category or `None` (default: `None`)
- `affine` – whether we define an affine module morphism (default: `False`).

Construct a module morphism from `domain` to `codomain` in the category `category`. By default, the `category` is the first of `Modules(R).WithBasis().FiniteDimensional()`, `Modules(R).WithBasis()`, `Modules(R)`, `CommutativeAdditiveMonoids()` that contains both the domain and the codomain. If initializing an affine morphism, then `Sets()` is used instead.

#### See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

The role of this class is minimal: it provides an `__init__()` method which:

- handles the choice of the default category
- handles the proper inheritance from categories by updating the class of `self` upon construction.

```
class sage.modules.with_basis.morphism.ModuleMorphismByLinearity(domain,
                                                                    on_basis=None,
                                                                    codomain=None,
                                                                    category=None,
                                                                    position=0,
                                                                    zero=None)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphism`

A class for module morphisms obtained by extending a function by linearity.

INPUT:

- `domain`, `codomain`, `category` – as for `ModuleMorphism`
- `on_basis` – a function which accepts indices of the basis of domain as position-th argument
- **codomain** – a parent in **Modules (...)** (default: `on_basis.codomain()`)
- `position` – a non-negative integer (default: 0)
- `zero` – the zero of the codomain (defaults: `codomain.zero()`)

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

---

**Note:** `on_basis` may alternatively be provided in derived classes by passing `None` as argument, and implementing or setting the attribute `_on_basis`

---

**on\_basis()**

Return the action of this morphism on basis elements, as per `ModulesWithBasis.Homsets.ElementMethods.on_basis()`.

OUTPUT:

- a function from the indices of the basis of the domain to the codomain

EXAMPLES:

```
sage: X = CombinatorialFreeModule(ZZ, [-2, -1, 1, 2])
```

```
sage: Y = CombinatorialFreeModule(ZZ, [1, 2])
```

```
sage: phi_on_basis = Y.monomial * abs
```

```
sage: phi = sage.modules.with_basis.morphism.ModuleMorphismByLinearity(X, on_basis = phi_on_
```

```
sage: x = X.basis()
```

```
sage: phi.on_basis() (-2)
```

```
B[2]
```

```
sage: phi.on_basis() == phi_on_basis
```

```
True
```

```
class sage.modules.with_basis.morphism.ModuleMorphismFromFunction(domain,
                                                                    function,
                                                                    codomain=None,
                                                                    cate-
                                                                    gory=None)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphism`,  
`sage.categories.morphism.SetMorphism`

A class for module morphisms implemented by a plain function.

INPUT:

- `domain`, `codomain`, `category` – as for `ModuleMorphism`

- function – any function or callable from domain to codomain

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

```
class sage.modules.with_basis.morphism.ModuleMorphismFromMatrix(domain, matrix,
                                                                codomain=None,
                                                                category=None,
                                                                side='left')
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphismByLinearity`

A class for module morphisms built from a matrix in the distinguished bases of the domain and codomain.

INPUT:

- domain, codomain – two finite dimensional modules over the same base ring  $R$  with basis  $F$  and  $G$ , respectively
- matrix – a matrix with base ring  $R$  and dimensions matching that of  $F$  and  $G$ , respectively
- side – “left” or “right” (default: “left”)

If side is “left”, this morphism is considered as acting on the left; i.e. each column of the matrix represents the image of an element of the basis of the domain.

- category – a category or None (default: None)

EXAMPLES:

```
sage: X = CombinatorialFreeModule(ZZ, [1,2]); X.rename("X"); x = X.basis()
```

```
sage: Y = CombinatorialFreeModule(ZZ, [3,4]); Y.rename("Y"); y = Y.basis()
```

```
sage: m = matrix([[1,2],[3,5]])
```

```
sage: phi = X.module_morphism(matrix=m, codomain=Y)
```

```
sage: phi.parent()
```

```
Set of Morphisms from X to Y in Category of finite dimensional modules with basis over Integer R
```

```
sage: phi.__class__
```

```
<class 'sage.modules.with_basis.morphism.ModuleMorphismFromMatrix_with_category'>
```

```
sage: phi(x[1])
```

```
B[3] + 3*B[4]
```

```
sage: phi(x[2])
```

```
2*B[3] + 5*B[4]
```

```
sage: m = matrix([[1,2],[3,5]])
```

```
sage: phi = X.module_morphism(matrix=m, codomain=Y, side="right",
```

```
....:                               category=Modules(ZZ).WithBasis())
```

```
sage: phi.parent()
```

```
Set of Morphisms from X to Y
```

```
in Category of modules with basis over Integer Ring
```

```
sage: phi(x[1])
```

```
B[3] + 2*B[4]
```

```
sage: phi(x[2])
```

```
3*B[3] + 5*B[4]
```

---

Todo

Possibly implement rank, addition, multiplication, matrix, etc, from the stored matrix.

```
class sage.modules.with_basis.morphism.PointwiseInverseFunction(f)
    Bases: sage.structure.sage_object.SageObject
```

A class for pointwise inverse functions.

The pointwise inverse function of a function  $f$  is the function sending every  $x$  to  $1/f(x)$ .

EXAMPLES:

```
sage: from sage.modules.with_basis.morphism import PointwiseInverseFunction
sage: f = PointwiseInverseFunction(factorial)
sage: f(0), f(1), f(2), f(3)
(1, 1, 1/2, 1/6)
```

```
pointwise_inverse()
```

TESTS:

```
sage: from sage.modules.with_basis.morphism import PointwiseInverseFunction
sage: g = PointwiseInverseFunction(operator.mul)
sage: g.pointwise_inverse() is operator.mul
True
```

```
class sage.modules.with_basis.morphism.TriangularModuleMorphism(triangular='upper',
                                                                    unitriangu-
                                                                    lar=False,
                                                                    cmp=None,
                                                                    inverse=None,
                                                                    inverse_on_support=<built-
                                                                    in      function
                                                                    identity>, invert-
                                                                    ible=None)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphism`

An abstract class for triangular module morphisms

Let  $X$  and  $Y$  be modules over the same base ring, with distinguished bases  $F$  indexed by  $I$  and  $G$  indexed by  $J$ , respectively.

A module morphism  $\phi$  from  $X$  to  $Y$  is *triangular* if its representing matrix in the distinguished bases of  $X$  and  $Y$  is upper triangular (echelon form).

More precisely,  $\phi$  is *upper triangular* w.r.t. a total order  $<$  on  $J$  if, for any  $j \in J$ , there exists at most one index  $i \in I$  such that the leading support of  $\phi(F_i)$  is  $j$  (see `leading_support()`). We denote by  $r(j)$  this index, setting  $r(j)$  to `None` if it does not exist.

*Lower triangular* morphisms are defined similarly, taking the trailing support instead (see `trailing_support()`).

A triangular morphism is *unitriangular* if all its pivots (i.e. coefficient of  $j$  in each  $\phi(F[r(j)])$ ) are 1.

INPUT:

- `domain` – a module with basis  $X$
- `codomain` – a module with basis  $Y$  (default:  $X$ )
- `category` – a category, as for `ModuleMorphism`
- `triangular` – "upper" or "lower" (default: "upper")

- `unitriangular` – boolean (default: `False`) As a shorthand, one may use `unitriangular="lower"` for `triangular="lower"`, `unitriangular=True`.
- `cmp` – a comparison function on  $J$  (default: the usual comparison function on  $J$ )
- `inverse_on_support` – a function  $J \rightarrow I \cup \{None\}$  implementing  $r$  (default: the identity function). If set to “compute”, the values of  $r(j)$  are precomputed by running through the index set  $I$  of the basis of the domain. This of course requires the domain to be finite dimensional.
- `invertible` – a boolean or `None` (default: `None`); can be set to specify that  $\phi$  is known to be (or not to be) invertible. If the domain and codomain share the same indexing set, this is by default automatically set to `True` if `inverse_on_support` is the identity, or in the finite dimensional case.

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

OUTPUT:

A morphism from  $X$  to  $Y$ .

**Warning:** This class is meant to be used as a complement for a concrete morphism class. In particular, the `__init__()` method focuses on setting up the data structure describing the triangularity of the morphism. It purposely does *not* call `ModuleMorphism.__init__()` which should be called (directly or indirectly) beforehand.

EXAMPLES:

We construct and invert an upper unitriangular module morphism between two free  $\mathbb{Q}$ -modules:

```
sage: I = range(1,200)
sage: X = CombinatorialFreeModule(QQ, I); X.rename("X"); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, I); Y.rename("Y"); y = Y.basis()
sage: ut = Y.sum_of_monomials * divisors # This * is map composition.
sage: phi = X.module_morphism(ut, unitriangular="upper", codomain=Y)
sage: phi(x[2])
B[1] + B[2]
sage: phi(x[6])
B[1] + B[2] + B[3] + B[6]
sage: phi(x[30])
B[1] + B[2] + B[3] + B[5] + B[6] + B[10] + B[15] + B[30]
sage: phi.preimage(y[2])
-B[1] + B[2]
sage: phi.preimage(y[6])
B[1] - B[2] - B[3] + B[6]
sage: phi.preimage(y[30])
-B[1] + B[2] + B[3] + B[5] - B[6] - B[10] - B[15] + B[30]
sage: (phi^-1)(y[30])
-B[1] + B[2] + B[3] + B[5] - B[6] - B[10] - B[15] + B[30]
```

A lower triangular (but not unitriangular) morphism:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def lt(i): return sum(j*x[j] for j in range(i,4))
sage: phi = X.module_morphism(lt, triangular="lower", codomain=X)
```

```

sage: phi(x[2])
2*B[2] + 3*B[3]
sage: phi.preimage(x[2])
1/2*B[2] - 1/2*B[3]
sage: phi(phi.preimage(x[2]))
B[2]

```

Using the `cmp` keyword, we can use triangularity even if the map becomes triangular only after a permutation of the basis:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def ut(i): return (x[1] + x[2] if i == 1 else x[2] + (x[3] if i == 3 else 0))
sage: perm = [0, 2, 1, 3]
sage: phi = X.module_morphism(ut, triangular="upper", codomain=X,
....:                          cmp=lambda a, b: cmp(perm[a], perm[b]))
sage: [phi(x[i]) for i in range(1, 4)]
[B[1] + B[2], B[2], B[2] + B[3]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[B[1] - B[2], B[2], -B[2] + B[3]]

```

The same works in the lower-triangular case:

```

sage: def lt(i): return (x[1] + x[2] + x[3] if i == 2 else x[i])
sage: phi = X.module_morphism(lt, triangular="lower", codomain=X,
....:                          cmp=lambda a, b: cmp(perm[a], perm[b]))
sage: [phi(x[i]) for i in range(1, 4)]
[B[1], B[1] + B[2] + B[3], B[3]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[B[1], -B[1] + B[2] - B[3], B[3]]

```

An injective but not surjective morphism cannot be inverted, but the `inverse_on_support` keyword allows Sage to find a partial inverse:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3, 4, 5]); y = Y.basis()
sage: ult = lambda i: sum( y[j] for j in range(i+1, 6) )
sage: phi = X.module_morphism(ult, unitriangular="lower", codomain=Y,
....:                          inverse_on_support=lambda i: i-1 if i in [2, 3, 4] else None)
sage: phi(x[2])
B[3] + B[4] + B[5]
sage: phi.preimage(y[3])
B[2] - B[3]

```

The `inverse_on_support` keyword can also be used if the bases of the domain and the codomain are identical but one of them has to be permuted in order to render the morphism triangular. For example:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def ut(i):
....:     return (x[3] if i == 1 else x[1] if i == 2
....:             else x[1] + x[2])
sage: def perm(i):
....:     return (2 if i == 1 else 3 if i == 2 else 1)
sage: phi = X.module_morphism(ut, triangular="upper", codomain=X,
....:                          inverse_on_support=perm)
sage: [phi(x[i]) for i in range(1, 4)]
[B[3], B[1], B[1] + B[2]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[B[2], -B[2] + B[3], B[1]]

```



The same works if the permutation induces lower triangularity:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def lt(i):
....:     return (x[3] if i == 1 else x[2] if i == 2
....:             else x[1] + x[2])
sage: def perm(i):
....:     return 4 - i
sage: phi = X.module_morphism(lt, triangular="lower", codomain=X,
....:                          inverse_on_support=perm)
sage: [phi(x[i]) for i in range(1, 4)]
[B[3], B[2], B[1] + B[2]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[-B[2] + B[3], B[2], B[1]]
```

In the finite dimensional case, one can ask Sage to recover `inverse_on_support` by a precomputation:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3, 4]); y = Y.basis()
sage: ut = lambda i: sum( y[j] for j in range(1,i+2) )
sage: phi = X.module_morphism(ut, triangular="upper", codomain=Y,
....:                          inverse_on_support="compute")
sage: for j in Y.basis().keys():
....:     i = phi._inverse_on_support(j)
....:     print j, i, phi(x[i]) if i is not None else None
1 None None
2 1 B[1] + B[2]
3 2 B[1] + B[2] + B[3]
4 3 B[1] + B[2] + B[3] + B[4]
```

The `inverse_on_basis` and `cmp` keywords can be combined:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def ut(i):
....:     return (2*x[2] + 3*x[3] if i == 1
....:             else x[1] + x[2] + x[3] if i == 2
....:             else 4*x[2])
sage: def perm(i):
....:     return (2 if i == 1 else 3 if i == 2 else 1)
sage: perverse_cmp = lambda a, b: cmp((a-2) % 3, (b-2) % 3)
sage: phi = X.module_morphism(ut, triangular="upper", codomain=X,
....:                          inverse_on_support=perm, cmp=perverse_cmp)
sage: [phi(x[i]) for i in range(1, 4)]
[2*B[2] + 3*B[3], B[1] + B[2] + B[3], 4*B[2]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[-1/3*B[1] + B[2] - 1/12*B[3], 1/4*B[3], 1/3*B[1] - 1/6*B[3]]
```

**co\_kernel\_projection**(\*args, \*\*kws)

Deprecated: Use `cokernel_projection()` instead. See [trac ticket #8678](#) for details.

**co\_reduced**(\*args, \*\*kws)

Deprecated: Use `coreduced()` instead. See [trac ticket #8678](#) for details.

**cokernel\_basis\_indices**()

Return the indices of the natural monomial basis of the cokernel of `self`.

INPUT:

- `self` – a triangular morphism over a field or a unitriangular morphism over a ring, with a finite dimensional codomain.

OUTPUT:

A list  $E$  of indices of the basis  $(B_e)_e$  of the codomain of `self` so that  $(B_e)_{e \in E}$  forms a basis of a supplementary of the image set of `self`.

Thinking of this triangular morphism as a row echelon matrix, this returns the complementary of the characteristic columns. Namely  $E$  is the set of indices which do not appear as leading support of some element of the image set of `self`.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(ZZ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [1,2,3,4,5]); y = Y.basis()
sage: uut = lambda i: sum( y[j] for j in range(i+1,6) ) # uni-upper
sage: phi = X.module_morphism(uut, unitriangular="upper", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi.cokernel_basis_indices()
[1, 5]

sage: phi = X.module_morphism(uut, triangular="upper", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi.cokernel_basis_indices()
Traceback (most recent call last):
...
NotImplementedError: cokernel_basis_indices for a triangular but not unitriangular morphism

sage: Y = CombinatorialFreeModule(ZZ, NN); y = Y.basis()
sage: phi = X.module_morphism(uut, unitriangular="upper", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi.cokernel_basis_indices()
Traceback (most recent call last):
...
NotImplementedError: cokernel_basis_indices implemented only for morphisms with a finite dim
```

**cokernel\_projection** (*category=None*)

Return a projection on the co-kernel of `self`.

INPUT:

- `category` – the category of the result

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4,5]); y = Y.basis()
sage: lt = lambda i: sum( y[j] for j in range(i+1,6) ) # lower
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phipro = phi.cokernel_projection()
sage: phipro(y[1] + y[2])
B[1]
sage: all(phipro(phi(x)).is_zero() for x in X.basis())
True
sage: phipro(y[1])
B[1]
sage: phipro(y[4])
-B[5]
sage: phipro(y[5])
B[5]
```

**coreduced** (*y*)

Return  $y$  reduced w.r.t. the image of `self`.

INPUT:

- `self` – a triangular morphism over a field, or a unitriangular morphism over a ring
- $y$  – an element of the codomain of `self`

Suppose that `self` is a morphism from  $X$  to  $Y$ . Then, for any  $y \in Y$ , the call `self.coreduced(y)` returns a normal form for  $y$  in the quotient  $Y/I$  where  $I$  is the image of `self`.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4,5]); y = Y.basis()
sage: ult = lambda i: sum( y[j] for j in range(i+1,6) )
sage: phi = X.module_morphism(ult, unitriangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi(v) for v in X.basis()]
[B[2] + B[3] + B[4] + B[5],
 B[3] + B[4] + B[5],
 B[4] + B[5]]
sage: [phi.coreduced(y[1]-2*y[4])]
[B[1] + 2*B[5]]
sage: [phi.coreduced(v) for v in y]
[B[1], 0, 0, -B[5], B[5]]
```

Now with a non unitriangular morphism:

```
sage: lt = lambda i: sum( j*y[j] for j in range(i+1,6) )
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi(v) for v in X.basis()]
[2*B[2] + 3*B[3] + 4*B[4] + 5*B[5],
 3*B[3] + 4*B[4] + 5*B[5],
 4*B[4] + 5*B[5]]
sage: [phi.coreduced(y[1]-2*y[4])]
[B[1] + 5/2*B[5]]
sage: [phi.coreduced(v) for v in y]
[B[1], 0, 0, -5/4*B[5], B[5]]
```

For general rings, this method is only implemented for unitriangular morphisms:

```
sage: X = CombinatorialFreeModule(ZZ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [1,2,3,4,5]); y = Y.basis()
sage: phi = X.module_morphism(ult, unitriangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi.coreduced(y[1]-2*y[4])]
[B[1] + 2*B[5]]
sage: [phi.coreduced(v) for v in y]
[B[1], 0, 0, -B[5], B[5]]
```

```
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi.coreduced(v) for v in y]
Traceback (most recent call last):
...
```

`NotImplementedError: coreduce for a triangular but not unitriangular morphism over a ring`

---

**Note:** Before [trac ticket #8678](#) this method used to be called `co_reduced`.

---

**preimage**(*f*)

Return the preimage of *f* under self.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3]); y = Y.basis()
sage: lt = lambda i: sum( y[j] for j in range(i,4) ) # uni-lower
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y)
sage: phi.preimage(y[1] + y[2])
B[1] - B[3]
```

The morphism need not be surjective. In the following example, the codomain is of larger dimension than the domain:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3, 4]); y = Y.basis()
sage: lt = lambda i: sum( y[j] for j in range(i,5) )
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y)
sage: phi.preimage(y[1] + y[2])
B[1] - B[3]
```

Here are examples using `inverse_on_support` to handle a morphism that shifts the leading indices by 1:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3, 4, 5]); y = Y.basis()
sage: lt = lambda i: sum( y[j] for j in range(i+1,6) ) # lower
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi(x[1])
B[2] + B[3] + B[4] + B[5]
sage: phi(x[3])
B[4] + B[5]
sage: phi.preimage(y[2] + y[3])
B[1] - B[3]
sage: phi(phi.preimage(y[2] + y[3])) == y[2] + y[3]
True
sage: e1 = x[1] + 3*x[2] + 2*x[3]
sage: phi.preimage(phi(e1)) == e1
True

sage: phi.preimage(y[1])
Traceback (most recent call last):
...
ValueError: B[1] is not in the image
sage: phi.preimage(y[4])
Traceback (most recent call last):
...
ValueError: B[4] is not in the image
```

Over a base ring like  $\mathbb{Z}$ , the morphism need not be surjective even when the dimensions match:

```
sage: X = CombinatorialFreeModule(ZZ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [1, 2, 3]); y = Y.basis()
sage: lt = lambda i: sum( 2* y[j] for j in range(i,4) ) # lower
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y)
sage: phi.preimage(2*y[1] + 2*y[2])
B[1] - B[3]
```

The error message in case of failure could be more specific though:

```
sage: phi.preimage(y[1] + y[2])
Traceback (most recent call last):
...
TypeError: no conversion of this rational to integer
```

### `section()`

Return the section (partial inverse) of `self`.

Return a partial triangular morphism which is a section of `self`. The section morphism raise a `ValueError` if asked to apply on an element which is not in the image of `self`.

#### EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: X.rename('X')
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4,5]); y = Y.basis()
sage: ult = lambda i: sum( y[j] for j in range(i+1,6) ) # uni-lower
sage: phi = X.module_morphism(ult, triangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: ~phi
Traceback (most recent call last):
...
ValueError: Morphism not known to be invertible;
see the invertible option of module_morphism
sage: phiinv = phi.section()
sage: map(phiinv*phi, X.basis().list()) == X.basis().list()
True
sage: phiinv(Y.basis()[1])
Traceback (most recent call last):
...
ValueError: B[1] is not in the image
```

```
class sage.modules.with_basis.morphism.TriangularModuleMorphismByLinearity (domain,
                                                                              on_basis,
                                                                              codomain=None,
                                                                              cat-
                                                                              e-
                                                                              gory=None,
                                                                              **key-
                                                                              words)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphismByLinearity`,  
`sage.modules.with_basis.morphism.TriangularModuleMorphism`

A concrete class for triangular module morphisms obtained by extending a function by linearity.

#### See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismByLinearity` and `TriangularModuleMorphism`.

```
class sage.modules.with_basis.morphism.TriangularModuleMorphismFromFunction (domain,
                                                                              func-
                                                                              tion,
                                                                              codomain=None,
                                                                              cat-
                                                                              e-
                                                                              gory=None,
                                                                              **key-
                                                                              words)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphismFromFunction`,  
`sage.modules.with_basis.morphism.TriangularModuleMorphism`

A concrete class for triangular module morphisms implemented by a function.

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

```
sage.modules.with_basis.morphism.pointwise_inverse_function(f)
```

Return the function  $x \mapsto 1/f(x)$ .

INPUT:

- `f` – a function

EXAMPLES:

```
sage: from sage.modules.with_basis.morphism import pointwise_inverse_function
sage: def f(x): return x
....:
sage: g = pointwise_inverse_function(f)
sage: g(1), g(2), g(3)
(1, 1/2, 1/3)
```

`pointwise_inverse_function()` is an involution:

```
sage: f is pointwise_inverse_function(g)
True
```

---

### Todo

This has nothing to do here!!! Should there be a library for pointwise operations on functions somewhere in Sage?

---

## QUOTIENTS OF MODULES WITH BASIS

```
class sage.modules.with_basis.subquotient.QuotientModuleWithBasis(submodule,
                                                                    category)
```

```
    Bases: sage.combinat.free_module.CombinatorialFreeModule
```

A class for quotients of a module with basis by a submodule.

INPUT:

- `submodule` – a submodule of `self`
- `category` – a category (default: `ModulesWithBasis(submodule.base_ring())`)

`submodule` should be a free submodule admitting a basis in unitriangular echelon form. Typically `submodule` is a `SubmoduleWithBasis` as returned by `Modules.WithBasis.ParentMethods.submodule()`.

The `lift` method should have a method `.cokernel_basis_indices` that computes the indexing set of a subset  $B$  of the basis of `self` that spans some supplementary of `submodule` in `self` (typically the non characteristic columns of the aforementioned echelon form). `submodule` should further implement a `submodule.reduce(x)` method that returns the unique element in the span of  $B$  which is equivalent to  $x$  modulo `submodule`.

This is meant to be constructed via `Modules.WithBasis.FiniteDimensional.ParentMethods.quotient_module`.

This differs from `sage.rings.quotient_ring.QuotientRing` in the following ways:

- `submodule` needs not be an ideal. If it is, the transportation of the ring structure is taken care of by the `Subquotients` categories.
- Thanks to `.cokernel_basis_indices`, we know the indices of a basis of the quotient, and elements are represented directly in the free module spanned by those indices rather than by wrapping elements of the ambient space.

There is room for sharing more code between those two implementations and generalizing them. See [trac ticket #18204](#).

See also:

- `Modules.WithBasis.ParentMethods.submodule()`
- `Modules.WithBasis.FiniteDimensional.ParentMethods.quotient_module()`
- `SubmoduleWithBasis`
- `sage.rings.quotient_ring.QuotientRing`

```
ambient()
```

Return the ambient space of `self`.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.quotient_module((x[0]-x[1], x[1]-x[2]))
sage: Y.ambient() is X
True
```

**lift** (*x*)

Lift *x* to the ambient space of self.

INPUT:

- *x* – an element of self

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.quotient_module((x[0]-x[1], x[1]-x[2])); y = Y.basis()
sage: Y.lift(y[2])
x[2]
```

**retract** (*x*)

Retract an element of the ambient space by projecting it back to self.

INPUT:

- *x* – an element of the ambient space of self

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.quotient_module((x[0]-x[1], x[1]-x[2])); y = Y.basis()
sage: Y.print_options(prefix='y')
sage: Y.retract(x[0])
y[2]
sage: Y.retract(x[1])
y[2]
sage: Y.retract(x[2])
y[2]
```

**class** sage.modules.with\_basis.subquotient.**SubmoduleWithBasis** (*basis*, *ambient*, *category*)

Bases: sage.combinat.free\_module.CombinatorialFreeModule

A base class for submodules of a ModuleWithBasis spanned by a (possibly infinite) basis in echelon form.

INPUT:

- *basis* – a family of elements in echelon form in some module with basis *V*, or data that can be converted into such a family
- *ambient* – the ambient space *V*
- *category* – a category

Further arguments are passed down to CombinatorialFreeModule.

This is meant to be constructed via `Modules.WithBasis.ParentMethods.submodule()`.

See also:

- `Modules.WithBasis.ParentMethods.submodule()`
- `QuotientModuleWithBasis`



**ambient()**

Return the ambient space of self.

**EXAMPLES:**

```
sage: X = CombinatorialFreeModule(QQ, range(3)); x = X.basis()
sage: Y = X.submodule((x[0]-x[1], x[1]-x[2]))
sage: Y.ambient() is X
True
```

**is\_submodule(other)**

Return whether self is a submodule of other.

**INPUT:**

- other – another submodule of the same ambient module, or the ambient module itself

**EXAMPLES:**

```
sage: X = CombinatorialFreeModule(QQ, range(4)); x = X.basis()
sage: F = X.submodule([x[0]-x[1], x[1]-x[2], x[2]-x[3]])
sage: G = X.submodule([x[0]-x[2]])
sage: H = X.submodule([x[0]-x[1], x[2]])
sage: F.is_submodule(X)
True
sage: G.is_submodule(F)
True
sage: H.is_submodule(F)
False
```

**lift()**

The lift (embedding) map from self to the ambient space.

**EXAMPLES:**

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.submodule((x[0]-x[1], x[1]-x[2]), already_echelonized=True); y = Y.basis()
sage: Y.lift
Generic morphism:
  From: Free module generated by {0, 1} over Rational Field
  To:   Free module generated by {0, 1, 2} over Rational Field
sage: [ Y.lift(u) for u in y ]
[x[0] - x[1], x[1] - x[2]]
sage: (y[0] + y[1]).lift()
x[0] - x[2]
```

**reduce()**

The reduce map.

This map reduces elements of the ambient space modulo this submodule.

**EXAMPLES:**

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.submodule((x[0]-x[1], x[1]-x[2]), already_echelonized=True)
sage: Y.reduce
Generic endomorphism of Free module generated by {0, 1, 2} over Rational Field
sage: Y.reduce(x[1])
x[2]
sage: Y.reduce(2*x[0] + x[1])
3*x[2]
```

**TESTS:**

```
sage: all( Y.reduce(u.lift()) == 0 for u in Y.basis() )
True
```

**retract()**

The retract map from the ambient space.

**EXAMPLES:**

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.submodule((x[0]-x[1], x[1]-x[2]), already_echelonized=True)
sage: Y.print_options(prefix='y')
sage: Y.retract
Generic morphism:
  From: Free module generated by {0, 1, 2} over Rational Field
  To:   Free module generated by {0, 1} over Rational Field
sage: Y.retract(x[0] - x[2])
y[0] + y[1]
```

**TESTS:**

```
sage: all( Y.retract(u.lift()) == u for u in Y.basis() )
True
```

## ITERATORS OVER FINITE SUBMODULES OF A $\mathbb{Z}$ -MODULE

We iterate over the elements of a finite  $\mathbb{Z}$ -module. The action of  $\mathbb{Z}$  must be the natural one.

This class is intended to provide optimizations for the `sage.free_module.FreeModule_generic.__iter__()` method.

AUTHORS:

- Thomas Feulner (2012-08-31): initial version
- Punarbasu Purkayastha (2012-11-09): replaced the loop with recursion
- Thomas Feulner (2012-11-09): added functionality to enumerate cosets, `FiniteFieldsubspace_projPoint_iterator`

EXAMPLES:

```
sage: from sage.modules.finite_submodule_iter import FiniteZZsubmodule_iterator
sage: F.<x,y,z> = FreeAlgebra(GF(3),3)
sage: iter = FiniteZZsubmodule_iterator([x,y], [3,3])
sage: list(iter)
[0, x, 2*x, y, x + y, 2*x + y, 2*y, x + 2*y, 2*x + 2*y]
```

There is a specialization for subspaces over finite fields:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator
sage: A = random_matrix(GF(4, 'a'), 5, 100)
sage: iter = FiniteFieldsubspace_iterator(A)
sage: len(list(iter))
1024
```

The module also allows the iteration over cosets:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator
sage: A = random_matrix(GF(4, 'a'), 5, 100)
sage: v = random_vector(GF(4, 'a'), 100)
sage: iter = FiniteFieldsubspace_iterator(A, v)
sage: len(list(iter))
1024
```

TESTS:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator
sage: A = random_matrix(GF(4, 'a'), 5, 100)
sage: iter = FiniteFieldsubspace_iterator(A)
sage: TestSuite(iter).run(skip='_test_pickling')
```

In a second step, we will replace all calls to `__iter__` for finite submodules. This will result in improved running times:

```
sage: A = random_matrix(GF(2), 15, 100)
sage: X = A.row_space()
sage: x = [0 for _ in X] #long time #takes 7.12 seconds
sage: y = [0 for _ in FiniteFieldspace_iterator(A)] # takes 0.05 seconds
sage: sorted(x) == sorted(y) #long time
True
```

**class** `sage.modules.finite_submodule_iter.FiniteFieldspace_iterator`  
Bases: `sage.modules.finite_submodule_iter.FiniteZZsubmodule_iterator`

This class implements an iterator over the subspace of a vector space over a finite field. The subspace is generated by `basis`.

INPUT:

- `basis` – a list of vectors or a matrix with elements over a finite field. If a matrix is provided then it is not checked whether the matrix is full ranked. Similarly, if a list of vectors is provided, then the linear independence of the vectors is not checked.
- `coset_rep` (optional) – a vector in the same ambient space, if one aims to compute a coset of the vector space given by `basis`.
- `immutable` (optional; default: `False`) – set it to `True` to return immutable vectors.

EXAMPLES:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldspace_iterator
sage: A = random_matrix(GF(2), 10, 100)
sage: iter = FiniteFieldspace_iterator(A)
sage: len(list(iter))
1024
sage: X = random_matrix(GF(4, 'a'), 7, 100).row_space()
sage: s = list(X) # long time (5s on sage.math, 2013)
sage: t = list(FiniteFieldspace_iterator(X.basis())) # takes 0.31s
sage: sorted(t) == sorted(s) # long time
True
```

TESTS:

We test whether we get immutable vectors if `immutable=True`:

```
sage: iter = FiniteFieldspace_iterator(A, immutable=True)
sage: c = next(iter)
sage: c.is_immutable()
True
```

**class** `sage.modules.finite_submodule_iter.FiniteFieldspace_projPoint_iterator`  
Bases: `object`

This class implements an iterator over the projective points of a vector space over a finite field. The vector space is generated by `basis` and need not to be equal to the full ambient space.

A projective point (= one dimensional subspace)  $P$  will be represented by a generator  $p$ . To ensure that all  $p$  will be normalized you can set the optional argument `normalize` to `True`.

INPUT:

- `basis` – a list of vectors or a matrix with elements over a finite field. If a matrix is provided then it is not checked whether the matrix is full ranked. Similarly, if a list of vectors is provided, then the linear independence of the vectors is not checked.

- `normalize` (optional; default: `False`) – boolean which indicates if the returned vectors should be normalized, i.e. the first nonzero coordinate is equal to 1.
- `immutable` (optional; default: `False`) – set it to `True` to return immutable vectors.

EXAMPLES:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator, FiniteFieldsubspace_projPoint_iterator
sage: A = random_matrix(GF(4, 'a'), 5, 100)
sage: a = len(list(FiniteFieldsubspace_iterator(A)))
sage: b = len(list(FiniteFieldsubspace_projPoint_iterator(A)))
sage: b == (a-1)/3
True
```

Prove that the option `normalize == True` will only return normalized vectors.

```
sage: all([ x.monic() == x for x in FiniteFieldsubspace_projPoint_iterator(A, True) ]) True
```

TESTS:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_projPoint_iterator
sage: A = MatrixSpace(GF(7), 10, 10).one()
sage: len(list(FiniteFieldsubspace_projPoint_iterator(A[:0]))) #indirect doctest
0
sage: len(list(FiniteFieldsubspace_projPoint_iterator(A[:1]))) #indirect doctest
1
sage: len(list(FiniteFieldsubspace_projPoint_iterator(A[:2]))) #indirect doctest
8
sage: iter = FiniteFieldsubspace_projPoint_iterator(A[:2], immutable=True)
sage: next(iter).is_immutable()
True
```

**next()**

`x.next()` -> the next value, or raise `StopIteration`

**class** `sage.modules.finite_submodule_iter.FiniteZZsubmodule_iterator`

Bases: `object`

Let  $G$  be an abelian group and suppose that  $(g_0, \dots, g_n)$  is a list of elements of  $G$ , whose additive orders are equal to  $m_i$  and  $\sum_{i=0}^n x_i g_i = 0$  for  $x_i \in \mathbf{Z}_{m_i}$  for  $i \in \{0, \dots, n\}$  implies  $x_i = 0$  for all  $i$ .

This class implements an iterator over the  $\mathbf{Z}$ -submodule  $M = \{\sum_{i=0}^n x_i g_i\}$ . If the independence condition from above is not fulfilled, we can still use this iterator to run over the elements. In this case the elements will occur multiple times.

Getting from one element of the submodule to another is performed by one single addition in  $G$ .

INPUT:

- `basis` - the elements  $(g_0, \dots, g_n)$
- `order` (optional) - the additive\_orders  $m_i$  of  $g_i$ .
- `coset_rep` (optional) – an element of  $g$ , if one aims to compute a coset of the  $\mathbf{Z}$ -submodule  $M$ .
- `immutable` (optional; default: `False`) – set it to `True` to return immutable elements. Setting this to `True` makes sense if the elements are vectors. See `FiniteFieldsubspace_iterator` for examples.

EXAMPLES:

```
sage: from sage.modules.finite_submodule_iter import FiniteZZsubmodule_iterator
sage: F.<x,y,z> = FreeAlgebra(GF(3), 3)
sage: iter = FiniteZZsubmodule_iterator([x,y], [3,3])
```

```
sage: list(iter)
[0, x, 2*x, y, x + y, 2*x + y, 2*y, x + 2*y, 2*x + 2*y]
sage: iter = FiniteZZsubmodule_iterator([x,y], [3,3], z)
sage: list(iter)
[z, x + z, 2*x + z, y + z, x + y + z, 2*x + y + z, 2*y + z, x + 2*y + z, 2*x + 2*y + z]
```

**next()**

`x.next()` -> the next value, or raise `StopIteration`

## FREE QUADRATIC MODULES

Sage supports computation with free quadratic modules over an arbitrary commutative ring. Nontrivial functionality is available over  $\mathbf{Z}$  and fields. All free modules over an integral domain are equipped with an embedding in an ambient vector space and an inner product, which you can specify and change.

Create the free module of rank  $n$  over an arbitrary commutative ring  $R$  using the command `FreeModule(R, n)` with a given `inner_product_matrix`.

The following example illustrates the creation of both a vector spaces and a free module over the integers and a submodule of it. Use the functions `FreeModule`, `span` and member functions of free modules to create free modules. “Do not use the `FreeModule_XXX` constructors directly.”

EXAMPLES:

```
sage: M = Matrix(QQ, [[2,1,0],[1,2,1],[0,1,2]])
sage: V = VectorSpace(QQ,3,inner_product_matrix=M)
sage: type(V)
<class 'sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_field_with_category'>
sage: V.inner_product_matrix()
[2 1 0]
[1 2 1]
[0 1 2]
sage: W = V.subspace([[1,2,7],[1,1,0]])
sage: type(W)
<class 'sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_field_with_category'>
sage: W
Quadratic space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -7]
[ 0  1  7]
Inner product matrix:
[2 1 0]
[1 2 1]
[0 1 2]
sage: W.gram_matrix()
[ 100 -104]
[-104  114]
```

TESTS:

```
sage: M = Matrix(QQ, [[2,1,0],[1,2,1],[0,1,2]])
sage: V = VectorSpace(QQ,3,inner_product_matrix = M)
sage: V == loads(dumps(V))
True
sage: W = QuadraticSpace(QQ,3,M)
```

```
sage: W == V
True
```

**AUTHORS:**

- David Kohel (2008-06): First created (based on free\_module.py)

```
sage.modules.free_quadratic_module.FreeQuadraticModule(base_ring, rank, inner_product_matrix,
                                                         sparse=False, inner_product_ring=None)
```

Create the free quadratic module over the given commutative ring of the given rank.

**INPUT:**

- `base_ring` – a commutative ring
- `rank` – a nonnegative integer
- `inner_product_matrix` – the inner product matrix
- `sparse` – bool; (default False)
- `inner_product_ring` – the inner product codomain ring; (default None)

**OUTPUT:**

A free quadratic module (with given inner product matrix).

---

**Note:** In Sage it is the case that there is only one dense and one sparse free ambient quadratic module of rank  $n$  over  $R$  and given inner product matrix.

---

**EXAMPLES:**

```
sage: M1 = FreeQuadraticModule(ZZ, 2, inner_product_matrix=1)
sage: M1 is FreeModule(ZZ, 2, inner_product_matrix=1)
True
sage: M1.inner_product_matrix()
[1 0]
[0 1]
sage: M1 == ZZ^2
True
sage: M1 is ZZ^2
False
sage: M2 = FreeQuadraticModule(ZZ, 2, inner_product_matrix=[1, 2, 3, 4])
sage: M2 is FreeQuadraticModule(ZZ, 2, inner_product_matrix=[1, 2, 3, 4])
True
sage: M2.inner_product_matrix()
[1 2]
[3 4]
sage: M3 = FreeModule(ZZ, 2, inner_product_matrix=[[1, 2], [3, 4]])
sage: M3 is M2
True
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient(base_ring,
                                                                       rank, inner_product_matrix,
                                                                       sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_ambient`, `sage.modules.free_quadratic_module.Free`

Ambient free module over a commutative ring.



```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_domain (base_ring,
                                                                              rank,
                                                                              inner_product_matrix,
                                                                              sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_ambient_domain,`  
`sage.modules.free_quadratic_module.FreeQuadraticModule_ambient`

Ambient free quadratic module over an integral domain.

**ambient\_vector\_space()**

Returns the ambient vector space, which is this free module tensored with its fraction field.

EXAMPLES:

```
sage: M = ZZ^3; M.ambient_vector_space()
Vector space of dimension 3 over Rational Field
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_field (base_field,
                                                                              dimension,
                                                                              inner_product_matrix,
                                                                              sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_ambient_field,`  
`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_field,`  
`sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_pid`

Create the ambient vector space of given dimension over the given field.

INPUT:

- `base_field` – a field
- `dimension` – a non-negative integer
- `sparse` – bool (default: False)

EXAMPLES:

```
sage: VectorSpace(QQ, 3, inner_product_matrix=[[2, 1, 0], [1, 2, 0], [0, 1, 2]])
Ambient quadratic space of dimension 3 over Rational Field
Inner product matrix:
[2 1 0]
[1 2 0]
[0 1 2]
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_pid (base_ring,
                                                                              rank,
                                                                              inner_product_matrix,
                                                                              sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_ambient_pid,`  
`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid,`  
`sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_domain`

Ambient free quadratic module over a principal ideal domain.

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_generic (base_ring,
                                                                    rank,
                                                                    degree, inner_product_matrix,
                                                                    sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_generic`

Base class for all free quadratic modules.

**ambient\_module()**

Return the ambient module associated to this module.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
```

```
sage: M = FreeModule(R,2)
```

```
sage: M.ambient_module()
```

Ambient free module of rank 2 over the integral domain Multivariate Polynomial Ring in x, y

```
sage: V = FreeModule(QQ, 4).span([[1,2,3,4], [1,0,0,0]]); V
```

Vector space of degree 4 and dimension 2 over Rational Field

Basis matrix:

```
[ 1  0  0  0]
```

```
[ 0  1 3/2  2]
```

```
sage: V.ambient_module()
```

Vector space of dimension 4 over Rational Field

**determinant()**

Return the determinant of this free module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3, inner_product_matrix=1)
```

```
sage: M.determinant()
```

1

```
sage: N = M.span([[1,2,3]])
```

```
sage: N.determinant()
```

14

```
sage: P = M.span([[1,2,3], [1,1,1]])
```

```
sage: P.determinant()
```

6

**discriminant()**

Return the discriminant of this free module, defined to be  $(-1)^r$  of the determinant, where  $r = n/2$  ( $n$  even) or  $(n-1)/2$  ( $n$  odd) for a module of rank  $n$ .

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
```

```
sage: M.discriminant()
```

1

```
sage: N = M.span([[1,2,3]])
```

```
sage: N.discriminant()
```

14

```
sage: P = M.span([[1,2,3], [1,1,1]])
```

```
sage: P.discriminant()
```

6

**gram\_matrix()**

Return the gram matrix associated to this free module, defined to be  $G = B \cdot A \cdot B^{\text{transpose}}()$ , where  $A$  is the inner product matrix (induced from the ambient space), and  $B$  the basis matrix.

## EXAMPLES:

```

sage: V = VectorSpace(QQ, 4)
sage: u = V([1/2, 1/2, 1/2, 1/2])
sage: v = V([0, 1, 1, 0])
sage: w = V([0, 0, 1, 1])
sage: M = span([u, v, w], ZZ)
sage: M.inner_product_matrix() == V.inner_product_matrix()
True
sage: L = M.submodule_with_basis([u, v, w])
sage: L.inner_product_matrix() == M.inner_product_matrix()
True
sage: L.gram_matrix()
[1 1 1]
[1 2 1]
[1 1 2]

```

**inner\_product\_matrix()**

Return the inner product matrix associated to this module. By definition this is the inner product matrix of the ambient space, hence may be of degree greater than the rank of the module.

N.B. The inner product does not have to be symmetric (see examples).

TODO: Differentiate the image ring of the inner product from the base ring of the module and/or ambient space. E.g. On an integral module over  $\mathbb{ZZ}$  the inner product pairing could naturally take values in  $\mathbb{ZZ}$ ,  $\mathbb{QQ}$ ,  $\mathbb{RR}$ , or  $\mathbb{CC}$ .

## EXAMPLES:

```

sage: M = FreeModule(ZZ, 3)
sage: M.inner_product_matrix()
[1 0 0]
[0 1 0]
[0 0 1]

```

The inner product does not have to be symmetric or definite:

```

sage: N = FreeModule(ZZ, 2, inner_product_matrix=[[1, -1], [2, 5]])
sage: N.inner_product_matrix()
[ 1 -1]
[ 2  5]
sage: u, v = N.basis()
sage: u.inner_product(v)
-1
sage: v.inner_product(u)
2

```

The inner product matrix is defined with respect to the ambient space.

```

sage: V = QQ^3 sage: u = V([1/2, 1, 1]) sage: v = V([1, 1, 1/2]) sage: M = span([u, v], ZZ)
sage: M.inner_product_matrix() [1 0 0] [0 1 0] [0 0 1] sage: M.inner_product_matrix() ==
V.inner_product_matrix() True sage: M.gram_matrix() [ 1/2 -3/4] [-3/4 13/4]

```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_generic_field(base_field,  
                                                                           di-  
                                                                           men-  
                                                                           sion,  
                                                                           de-  
                                                                           gree,  
                                                                           in-  
                                                                           ner_product_matrix,  
                                                                           sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_generic_field,`  
`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid`

Base class for all free modules over fields.

**span** (*gens, check=True, already\_echelonized=False*)

Return the K-span of the given list of gens, where K is the base field of self. Note that this span is a subspace of the ambient vector space, but need not be a subspace of self.

INPUT:

- gens – list of vectors
- check – bool (default: True): whether or not to coerce entries of gens into base field
- already\_echelonized – bool (default: False): set this if you know the gens are already in echelon form

EXAMPLES:

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
sage: W.span([[1,1,1]])
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 1 1]
```

**span\_of\_basis** (*basis, check=True, already\_echelonized=False*)

Return the free K-module with the given basis, where K is the base field of self. Note that this span is a subspace of the ambient vector space, but need not be a subspace of self.

INPUT:

- basis – list of vectors
- check – bool (default: True): whether or not to coerce entries of gens into base field
- already\_echelonized – bool (default: False): set this if you know the gens are already in echelon form

EXAMPLES:

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
sage: W.span_of_basis([[2,2,2], [3,3,0]])
Vector space of degree 3 and dimension 2 over Finite Field of size 7
User basis matrix:
[2 2 2]
[3 3 0]
```

The basis vectors must be linearly independent or a `ValueError` exception is raised:

```
sage: W.span_of_basis([[2,2,2], [3,3,3]])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid(base_ring,
                                                                           rank,
                                                                           de-
                                                                           gree,
                                                                           in-
                                                                           ner_product_matrix,
                                                                           sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_generic_pid,`  
`sage.modules.free_quadratic_module.FreeQuadraticModule_generic`

Class of all free modules over a PID.

**span** (*gens*, *check=True*, *already\_echelonized=False*)

Return the R-span of the given list of gens, where R is the base ring of self. Note that this span need not be a submodule of self, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R.

EXAMPLES:

```
sage: V = FreeModule(ZZ, 3)
sage: W = V.submodule([V.gen(0)])
sage: W.span([V.gen(1)])
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[0 1 0]
sage: W.submodule([V.gen(1)])
Traceback (most recent call last):
...
ArithmeticError: Argument gens (= [(0, 1, 0)]) does not generate a submodule of self.
```

**span\_of\_basis** (*basis*, *check=True*, *already\_echelonized=False*)

Return the free R-module with the given basis, where R is the base ring of self. Note that this R-module need not be a submodule of self, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: W = M.span_of_basis([M([1,2,3])])
```

Next we create two free **Z**-modules, neither of which is a submodule of *W*:

```
sage: W.span_of_basis([M([2,4,0])]) Free module of degree 3 and rank 1 over Integer Ring
basis matrix: [2 4 0]
```

The following module isn't even in the ambient space:

```
sage: Q = QQ
sage: W.span_of_basis([ Q('1/5')*M([1,2,0]), Q('1/7')*M([1,1,0]) ])
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1/5 2/5 0]
[1/7 1/7 0]
```

Of course the input basis vectors must be linearly independent:

```
sage: W.span_of_basis([ [1,2,0], [2,4,0] ])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.
```

#### `zero_submodule()`

Return the zero submodule of this module.

##### EXAMPLES:

```
sage: V = FreeModule(ZZ,2)
sage: V.zero_submodule()
Free module of degree 2 and rank 0 over Integer Ring
Echelon basis matrix:
[]
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_field(ambient,
                                                                                   gens,
                                                                                   in-
                                                                                   ner_product_matrix,
                                                                                   check=True,
                                                                                   al-
                                                                                   ready_echelonized=False)
    Bases: sage.modules.free_module.FreeModule_submodule_field,
            sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_field
```

An embedded vector subspace with echelonized basis.

##### EXAMPLES:

Since this is an embedded vector subspace with echelonized basis, the `echelon_coordinates()` and `user_coordinates()` agree:

```
sage: V = QQ^3
sage: W = V.span([ [1,2,3], [4,5,6] ])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]

sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.basis_matrix()
(1, 5, 9)

sage: v = V([1,5,9])
sage: W.coordinates(v)
[1, 5]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_pid(ambient,
                                                                           gens,
                                                                           in-
                                                                           ner_product_matrix,
                                                                           check=True,
                                                                           al-
                                                                           ready_echelonized=False)
```

Bases: `sage.modules.free_module.FreeModule_submodule_pid`,  
`sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid`

An  $R$ -submodule of  $K^n$  where  $K$  is the fraction field of a principal ideal domain  $R$ .

#### EXAMPLES:

```
sage: M = ZZ^3
sage: W = M.span_of_basis([[1,2,3],[4,5,19]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  2  3]
[ 4  5 19]
```

We can save and load submodules and elements:

```
sage: loads(W.dumps()) == W
True
sage: v = W.0 + W.1
sage: loads(v.dumps()) == v
True
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_field(ambien
ba-
sis,
in-
ner_pr
check=
ech-
e-
l-
o-
nize=F
ech-
e-
l-
o-
nized_
al-
ready_
```

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_field`,  
`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_field`,  
`sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid`

An embedded vector subspace with a distinguished user basis.

#### EXAMPLES:

```
sage: M = QQ^3; W = M.submodule_with_basis([[1,2,3],[4,5,19]]); W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  2  3]
[ 4  5 19]
```

Since this is an embedded vector subspace with a distinguished user basis possibly different than the echelonized basis, the `echelon_coordinates()` and `user_coordinates()` do not agree:

```
sage: V = QQ^3
sage: W = V.submodule_with_basis([[1,2,3], [4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 2 3]
[4 5 6]

sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.echelonized_basis_matrix()
(1, 5, 9)

sage: v = V([1,5,9])
sage: W.coordinates(v)
[5, -1]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

We can load and save submodules:

```
sage: loads(W.dumps()) == W
True

sage: K.<x> = FractionField(PolynomialRing(QQ, 'x'))
sage: M = K^3; W = M.span_of_basis([[1,1,x]])
sage: loads(W.dumps()) == W
True
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid(ambient,
ba-
sis,
in-
ner_produ
check=Tru
ech-
e-
l-
o-
nize=Fals
ech-
e-
l-
o-
nized_bas
al-
ready_ech
```

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_pid`,  
`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid`

An  $R$ -submodule of  $K^n$  with distinguished basis, where  $K$  is the fraction field of a principal ideal domain  $R$ .

`change_ring(R)`



Return the free module over  $R$  obtained by coercing each element of self into a vector over the fraction field of  $R$ , then taking the resulting  $R$ -module. Raises a `TypeError` if coercion is not possible.

INPUT:

- $R$  – a principal ideal domain

EXAMPLES:

Changing rings preserves the inner product and the user basis:

```
sage: V = QQ^3
sage: W = V.subspace([[2, '1/2', 1]]); W
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[ 1 1/4 1/2]
sage: W.change_ring(GF(7))
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 2 4]

sage: N = FreeModule(ZZ, 2, inner_product_matrix=[[1,-1],[2,5]])
sage: N.inner_product_matrix()
[ 1 -1]
[ 2  5]
sage: Np = N.change_ring(RDF)
sage: Np.inner_product_matrix()
[ 1.0 -1.0]
[ 2.0  5.0]
```

`sage.modules.free_quadratic_module.InnerProductSpace(K, dimension, inner_product_matrix, sparse=False)`

EXAMPLES:

The base can be complicated, as long as it is a field:

```
sage: F.<x> = FractionField(PolynomialRing(ZZ, 'x'))
sage: D = diagonal_matrix([x, x-1, x+1])
sage: V = QuadraticSpace(F, 3, D)
sage: V
Ambient quadratic space of dimension 3 over Fraction Field of Univariate Polynomial Ring in x over
Inner product matrix:
[  x      0      0]
[  0 x - 1      0]
[  0      0 x + 1]
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
```

The base must be a field or a `TypeError` is raised:

```
sage: QuadraticSpace(ZZ, 5, identity_matrix(ZZ, 2))
Traceback (most recent call last):
...
TypeError: Argument K (= Integer Ring) must be a field.
```

```
sage.modules.free_quadratic_module.QuadraticSpace(K, dimension, inner_product_matrix,  
                                                    sparse=False)
```

**EXAMPLES:**

The base can be complicated, as long as it is a field:

```
sage: F.<x> = FractionField(PolynomialRing(ZZ, 'x'))
sage: D = diagonal_matrix([x, x-1, x+1])
sage: V = QuadraticSpace(F, 3, D)
sage: V
Ambient quadratic space of dimension 3 over Fraction Field of Univariate Polynomial Ring in x ov
Inner product matrix:
[  x      0      0]
[  0 x - 1      0]
[  0      0 x + 1]
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
```

The base must be a field or a `TypeError` is raised:

```
sage: QuadraticSpace(ZZ, 5, identity_matrix(ZZ, 2))
Traceback (most recent call last):
...
TypeError: Argument K (= Integer Ring) must be a field.
```

```
sage.modules.free_quadratic_module.is_FreeQuadraticModule(M)
```

Return True if  $M$  is a free quadratic module.

**EXAMPLES:**

```
sage: from sage.modules.free_quadratic_module import is_FreeQuadraticModule
sage: U = FreeModule(QQ, 3)
sage: is_FreeQuadraticModule(U)
False
sage: V = FreeModule(QQ, 3, inner_product_matrix=diagonal_matrix([1, 1, 1]))
sage: is_FreeQuadraticModule(V)
True
sage: W = FreeModule(QQ, 3, inner_product_matrix=diagonal_matrix([2, 3, 3]))
sage: is_FreeQuadraticModule(W)
True
```

## MISCELLANEOUS MODULE-RELATED FUNCTIONS.

AUTHORS:

- William Stein (2007-11-18)

`sage.modules.misc.gram_schmidt(B)`

Return the Gram-Schmidt orthogonalization of the entries in the list `B` of vectors, along with the matrix `mu` of Gram-Schmidt coefficients.

Note that the output vectors need not have unit length. We do this to avoid having to extract square roots.

**Note:** Use of this function is discouraged. It fails on linearly dependent input and its output format is not as natural as it could be. Instead, see `sage.matrix.matrix2.Matrix2.gram_schmidt()` which is safer and more general-purpose.

EXAMPLES:

```
sage: B = [vector([1,2,1/5]), vector([1,2,3]), vector([-1,0,0])]
sage: from sage.modules.misc import gram_schmidt
sage: G, mu = gram_schmidt(B)
sage: G
[(1, 2, 1/5), (-1/9, -2/9, 25/9), (-4/5, 2/5, 0)]
sage: G[0] * G[1]
0
sage: G[0] * G[2]
0
sage: G[1] * G[2]
0
sage: mu
[ 0 0 0]
[ 10/9 0 0]
[-25/126 1/70 0]
sage: a = matrix([])
sage: a.gram_schmidt()
([], [])
sage: a = matrix([[], [], [], []])
sage: a.gram_schmidt()
([], [])
```

Linearly dependent input leads to a zero dot product in a denominator. This shows that Trac #10791 is fixed.

```
sage: from sage.modules.misc import gram_schmidt
sage: V = [vector(ZZ, [1,1]), vector(ZZ, [2,2]), vector(ZZ, [1,2])]
sage: gram_schmidt(V)
Traceback (most recent call last):
...
ValueError: linearly dependent input for module version of Gram-Schmidt
```



## QUOTIENTS OF FINITE RANK FREE MODULES OVER A FIELD.

```
class sage.modules.quotient_module.FreeModule_ambient_field_quotient(domain,
                                                                    sub, quo-
                                                                    tient_matrix,
                                                                    lift_matrix,
                                                                    in-
                                                                    ner_product_matrix=None)
```

Bases: `sage.modules.free_module.FreeModule_ambient_field`

A quotient  $V/W$  of two vector spaces as a vector space.

To obtain  $V$  or  $W$  use `self.V()` and `self.W()`.

EXAMPLES:

```
sage: k.<i> = QuadraticField(-1)
sage: A = k^3; V = A.span([[1,0,i], [2,i,0]])
sage: W = A.span([[3,i,i]])
sage: U = V/W; U
```

Vector space quotient  $V/W$  of dimension 1 over Number Field in  $i$  with defining polynomial  $x^2 + 1$   
V: Vector space of degree 3 and dimension 2 over Number Field in  $i$  with defining polynomial  $x^2 + 1$   
Basis matrix:

```
[ 1  0  i]
[ 0  1 -2]
```

W: Vector space of degree 3 and dimension 1 over Number Field in  $i$  with defining polynomial  $x^2 + 1$   
Basis matrix:

```
[ 1 1/3*i 1/3*i]
```

```
sage: U.V()
```

Vector space of degree 3 and dimension 2 over Number Field in  $i$  with defining polynomial  $x^2 + 1$   
Basis matrix:

```
[ 1  0  i]
[ 0  1 -2]
```

```
sage: U.W()
```

Vector space of degree 3 and dimension 1 over Number Field in  $i$  with defining polynomial  $x^2 + 1$   
Basis matrix:

```
[ 1 1/3*i 1/3*i]
```

```
sage: U.quotient_map()
```

Vector space morphism represented by the matrix:

```
[ 1]
[3*i]
```

Domain: Vector space of degree 3 and dimension 2 over Number Field in  $i$  with defining polynomial  $x^2 + 1$

Basis matrix:

```
[ 1  0  i]
[ 0  1 -2]
```

Codomain: Vector space quotient  $V/W$  of dimension 1 over Number Field in  $i$  with defining polynomial  $x^2 + 1$

V: Vector space of degree 3 and dimension 2 over Number Field in  $i$  with defining polynomial  $x^2 + 1$

Basis matrix:

```
[ 1  0  i]
[ 0  1 -2]
W: Vector space of degree 3 and dimension 1 over Number Field in i with defining polynomial x^2
Basis matrix:
[ 1 1/3*i 1/3*i]
sage: Z = V.quotient(W)
sage: Z == U
True
```

**TESTS:**

```
sage: A = QQ^0; V = A.span([]) # corner case
sage: W = A.span([])
sage: U = V/W

sage: loads(dumps(U)) == U
True
sage: type(loads(dumps(U)))
<class 'sage.modules.quotient_module.FreeModule_ambient_field_quotient_with_category'>
```

**V()**

Given this quotient space  $Q = V/W$ , return  $V$ .

**EXAMPLES:**

```
sage: M = QQ^10 / [range(10), range(2,12)]
sage: M.V()
Vector space of dimension 10 over Rational Field
```

**W()**

Given this quotient space  $Q = V/W$ , return  $W$ .

**EXAMPLES:**

```
sage: M = QQ^10 / [range(10), range(2,12)]
sage: M.W()
Vector space of degree 10 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1 -2 -3 -4 -5 -6 -7 -8]
[ 0  1  2  3  4  5  6  7  8  9]
```

**cover()**

Given this quotient space  $Q = V/W$ , return  $V$ . This is the same as `self.V()`.

**EXAMPLES:**

```
sage: M = QQ^10 / [range(10), range(2,12)]
sage: M.cover()
Vector space of dimension 10 over Rational Field
```

**lift(x)**

Lift element of this quotient  $V/W$  to  $V$  by applying the fixed lift homomorphism.

The lift is a fixed homomorphism.

**EXAMPLES:**

```
sage: M = QQ^3 / [[1,2,3]]
sage: M.lift(M.0)
(1, 0, 0)
sage: M.lift(M.1)
(0, 1, 0)
```

```
(0, 1, 0)
sage: M.lift(M.0 - 2*M.1)
(1, -2, 0)
```

**lift\_map()**

Given this quotient space  $Q = V/W$ , return a fixed choice of linear homomorphism (a section) from  $Q$  to  $V$ .

**EXAMPLES:**

```
sage: M = QQ^3 / [[1,2,3]]
sage: M.lift_map()
Vector space morphism represented by the matrix:
[1 0 0]
[0 1 0]
Domain: Vector space quotient V/W of dimension 2 over Rational Field where
V: Vector space of dimension 3 over Rational Field
W: Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
Codomain: Vector space of dimension 3 over Rational Field
```

**quotient\_map()**

Given this quotient space  $Q = V/W$ , return the natural quotient map from  $V$  to  $Q$ .

**EXAMPLES:**

```
sage: M = QQ^3 / [[1,2,3]]
sage: M.quotient_map()
Vector space morphism represented by the matrix:
[ 1  0]
[ 0  1]
[-1/3 -2/3]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space quotient V/W of dimension 2 over Rational Field where
V: Vector space of dimension 3 over Rational Field
W: Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]

sage: M.quotient_map()( (QQ^3)([1,2,3]) )
(0, 0)
```

**relations()**

Given this quotient space  $Q = V/W$ , return  $W$ . This is the same as `self.W()`.

**EXAMPLES:**

```
sage: M = QQ^10 / [range(10), range(2,12)]
sage: M.relations()
Vector space of degree 10 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1 -2 -3 -4 -5 -6 -7 -8]
[ 0  1  2  3  4  5  6  7  8  9]
```





## DENSE COMPLEX DOUBLE VECTORS USING A NUMPY BACKEND.

### EXAMPLES:

```
sage: v = vector(CDF, [(1,-1), (2,pi), (3,5)])
sage: v
(1.0 - 1.0*I, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: type(v)
<type 'sage.modules.vector_complex_double_dense.Vector_complex_double_dense'>
sage: parent(v)
Vector space of dimension 3 over Complex Double Field
sage: v[0] = 5
sage: v
(5.0, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: loads(dumps(v)) == v
True
```

### TESTS:

```
sage: v = vector(CDF, [2, 2])
sage: v - v
(0.0, 0.0)
sage: (v - v).norm()
0.0
```

### AUTHORS:

– Jason Grout, Oct 2008: switch to NumPy backend, factored out `Vector_double_dense` class

```
class sage.modules.vector_complex_double_dense.Vector_complex_double_dense
    Bases: sage.modules.vector_double_dense.Vector_double_dense
```

Vectors over the Complex Double Field. These are supposed to be fast vector operations using C doubles. Most operations are implemented using numpy which will call the underlying BLAS, if needed, on the system.

**EXAMPLES:** sage: v = vector(CDF,[(1,-1), (2,pi), (3,5)]) sage: v (1.0 - 1.0\*I, 2.0 + 3.141592653589793\*I, 3.0 + 5.0\*I) sage: v\*v # rel tol 1e-15 -21.86960440108936 + 40.56637061435917\*I

```
sage.modules.vector_complex_double_dense.unpickle_v0(parent, entries, degree)
    Create a complex double vector containing the entries.
```

**EXAMPLE:** sage: v = vector(CDF, [1,2,3]) sage: w = sage.modules.vector\_complex\_double\_dense.unpickle\_v0(v.parent(), list(v), v.degree()) sage: v == w True

```
sage.modules.vector_complex_double_dense.unpickle_v1(parent, entries, degree,
                                                    is_mutable=None)
    Create a complex double vector with the given parent, entries, degree, and mutability.
```

**EXAMPLE:** sage: v = vector(CDF, [1,2,3]) sage: w = sage.modules.vector\_complex\_double\_dense.unpickle\_v1(v.parent(),  
list(v), v.degree(), v.is\_mutable()) sage: v == w True

## DENSE VECTORS USING A NUMPY BACKEND.

This serves as a base class for dense vectors over Real Double Field and Complex Double Field

EXAMPLES:

```
sage: v = vector(CDF, [(1,-1), (2,pi), (3,5)])
sage: v
(1.0 - 1.0*I, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: type(v)
<type 'sage.modules.vector_complex_double_dense.Vector_complex_double_dense'>
sage: parent(v)
Vector space of dimension 3 over Complex Double Field
sage: v[0] = 5
sage: v
(5.0, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: loads(dumps(v)) == v
True
sage: v = vector(RDF, [1,2,3,4]); v
(1.0, 2.0, 3.0, 4.0)
sage: loads(dumps(v)) == v
True
```

AUTHORS:

- Jason Grout, Oct 2008: switch to numpy backend, factored out `Vector_double_dense` class
- Josh Kantor
- William Stein

```
class sage.modules.vector_double_dense.Vector_double_dense
    Bases: sage.modules.free_module_element.FreeModuleElement
```

Base class for vectors over the Real Double Field and the Complex Double Field. These are supposed to be fast vector operations using C doubles. Most operations are implemented using numpy which will call the underlying BLAS, if needed, on the system.

This class cannot be instantiated on its own. The numpy vector creation depends on several variables that are set in the subclasses.

EXAMPLES:

```
sage: v = vector(RDF, [1,2,3,4]); v
(1.0, 2.0, 3.0, 4.0)
sage: v*v
30.0
```

**complex\_vector()**

Return the associated complex vector, i.e., this vector but with coefficients viewed as complex numbers.

## EXAMPLES:

```
sage: v = vector(RDF, 4, range(4)); v
(0.0, 1.0, 2.0, 3.0)
sage: v.complex_vector()
(0.0, 1.0, 2.0, 3.0)
sage: v = vector(RDF, 0)
sage: v.complex_vector()
()
```

**fft** (*direction*='forward', *algorithm*='radix2', *inplace*=False)

This performs a fast fourier transform on the vector.

**INPUT:** *direction* – ‘forward’ (default) or ‘backward’

The algorithm and inplace arguments are ignored.

This function is fastest if the vector’s length is a power of 2.

## EXAMPLES:

```
sage: v = vector(CDF, [1+2*I, 2, 3*I, 4])
sage: v.fft()
(7.0 + 5.0*I, 1.0 + 1.0*I, -5.0 + 5.0*I, 1.0 - 3.0*I)
sage: v.fft(direction='backward')
(1.75 + 1.25*I, 0.25 - 0.75*I, -1.25 + 1.25*I, 0.25 + 0.25*I)
sage: v.fft().fft(direction='backward')
(1.0 + 2.0*I, 2.0, 3.0*I, 4.0)
sage: v.fft().parent()
Vector space of dimension 4 over Complex Double Field
sage: v.fft(inplace=True)
sage: v
(7.0 + 5.0*I, 1.0 + 1.0*I, -5.0 + 5.0*I, 1.0 - 3.0*I)

sage: v = vector(RDF, 4, range(4)); v
(0.0, 1.0, 2.0, 3.0)
sage: v.fft()
(6.0, -2.0 + 2.0*I, -2.0, -2.0 - 2.0*I)
sage: v.fft(direction='backward')
(1.5, -0.5 - 0.5*I, -0.5, -0.5 + 0.5*I)
sage: v.fft().fft(direction='backward')
(0.0, 1.0, 2.0, 3.0)
sage: v.fft().parent()
Vector space of dimension 4 over Complex Double Field
sage: v.fft(inplace=True)
Traceback (most recent call last):
...
ValueError: inplace can only be True for CDF vectors
```

**inv\_fft** (*algorithm*='radix2', *inplace*=False)

This performs the inverse fast fourier transform on the vector.

The fourier transform can be done in place using the keyword *inplace*=True

This will be fastest if the vector’s length is a power of 2.

## EXAMPLES:

```
sage: v = vector(CDF, [1, 2, 3, 4])
sage: w = v.fft()
sage: max(v - w.inv_fft()) < 1e-12
True
```

**mean()**

Calculate the arithmetic mean of the vector.

EXAMPLE:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.mean()
4.0
sage: w.mean()
4.0 + 5.0*I
```

**norm(p=2)**

Returns the norm (or related computations) of the vector.

INPUT:

- $p$  - default: 2 - controls which norm is computed, allowable values are any real number and positive and negative infinity. See output discussion for specifics.

OUTPUT:

Returned value is a double precision floating point value in RDF (or an integer when  $p=0$ ). The default value of  $p = 2$  is the “usual” Euclidean norm. For other values:

- $p = \text{Infinity}$  or  $p = \infty$ : the maximum of the absolute values of the entries, where the absolute value of the complex number  $a + bi$  is  $\sqrt{a^2 + b^2}$ .
- $p = -\text{Infinity}$  or  $p = -\infty$ : the minimum of the absolute values of the entries.
- $p = 0$ : the number of nonzero entries in the vector.
- $p$  is any other real number: for a vector  $\vec{x}$  this method computes

$$\left( \sum_i x_i^p \right)^{1/p}$$

For  $p < 0$  this function is not a norm, but the above computation may be useful for other purposes.

ALGORITHM:

Computation is performed by the `norm()` function of the SciPy/NumPy library.

EXAMPLES:

First over the reals.

```
sage: v = vector(RDF, range(9))
sage: v.norm()
14.28285685...
sage: v.norm(p=2)
14.28285685...
sage: v.norm(p=6)
8.744039097...
sage: v.norm(p=Infinity)
8.0
sage: v.norm(p=-oo)
0.0
sage: v.norm(p=0)
8.0
sage: v.norm(p=0.3)
4099.153615...
```

And over the complex numbers.

```
sage: w = vector(CDF, [3-4*I, 0, 5+12*I])
sage: w.norm()
13.9283882...
sage: w.norm(p=2)
13.9283882...
sage: w.norm(p=0)
2.0
sage: w.norm(p=4.2)
13.0555695...
sage: w.norm(p=oo)
13.0
```

Negative values of  $p$  are allowed and will provide the same computation as for positive values. A zero entry in the vector will raise a warning and return zero.

```
sage: v = vector(CDF, range(1,10))
sage: v.norm(p=-3.2)
0.953760808...
sage: w = vector(CDF, [-1,0,1])
sage: w.norm(p=-1.6)
doctest:...: RuntimeWarning: divide by zero encountered in power
0.0
```

Return values are in RDF, or an integer when  $p = 0$ .

```
sage: v = vector(RDF, [1,2,4,8])
sage: v.norm() in RDF
True
sage: v.norm(p=0) in ZZ
True
```

Improper values of  $p$  are caught.

```
sage: w = vector(CDF, [-1,0,1])
sage: w.norm(p='junk')
Traceback (most recent call last):
...
ValueError: vector norm 'p' must be +/- infinity or a real number, not junk
```

**numpy** (*dtype=None*)

Return numpy array corresponding to this vector.

INPUT:

•**dtype** – if specified, the **numpy dtype** of the returned array.

EXAMPLES:

```
sage: v = vector(CDF, 4, range(4))
sage: v.numpy()
array([ 0.+0.j,  1.+0.j,  2.+0.j,  3.+0.j])
sage: v = vector(CDF, 0)
sage: v.numpy()
array([], dtype=complex128)
sage: v = vector(RDF, 4, range(4))
sage: v.numpy()
array([ 0.,  1.,  2.,  3.])
sage: v = vector(RDF, 0)
sage: v.numpy()
array([], dtype=float64)
```

A numpy dtype may be requested manually:

```
sage: import numpy
sage: v = vector(CDF, 3, range(3))
sage: v.numpy()
array([ 0.+0.j,  1.+0.j,  2.+0.j])
sage: v.numpy(dtype=numpy.float64)
array([ 0.,  1.,  2.])
sage: v.numpy(dtype=numpy.float32)
array([ 0.,  1.,  2.], dtype=float32)
```

### **prod()**

Return the product of the entries of self.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.prod()
0.0
sage: w.prod()
57204225.0*I
```

### **standard\_deviation** (*population=True*)

Calculate the standard deviation of entries of the vector.

**INPUT:** *population* – If False, calculate the sample standard deviation.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.standard_deviation()
2.7386127875258306
sage: v.standard_deviation(population=False)
2.581988897471611
sage: w.standard_deviation()
3.872983346207417
sage: w.standard_deviation(population=False)
3.6514837167011076
```

### **stats\_kurtosis()**

Compute the kurtosis of a dataset.

Kurtosis is the fourth central moment divided by the square of the variance. Since we use Fisher's definition, 3.0 is subtracted from the result to give 0.0 for a normal distribution. (Paragraph from the `scipy.stats` docstring.)

EXAMPLE:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.stats_kurtosis()
-1.2300000000000002
sage: w.stats_kurtosis()
-1.2300000000000002
```

### **sum()**

Return the sum of the entries of self.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.sum()
36.0
sage: w.sum()
36.0 + 45.0*I
```

**variance** (*population=True*)

Calculate the variance of entries of the vector.

INPUT:

- *population* – If False, calculate the sample variance.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.variance()
7.5
sage: v.variance(population=False)
6.666666666666667
sage: w.variance()
15.0
sage: w.variance(population=False)
13.333333333333334
```

**zero\_at** (*eps*)

Returns a copy with small entries replaced by zeros.

This is useful for modifying output from algorithms which have large relative errors when producing zero elements, e.g. to create reliable doctests.

INPUT:

- *eps* - cutoff value

OUTPUT:

A modified copy of the vector. Elements smaller than or equal to *eps* are replaced with zeroes. For complex vectors, the real and imaginary parts are considered individually.

EXAMPLES:

```
sage: v = vector(RDF, [1.0, 2.0, 10^-10, 3.0])
sage: v.zero_at(1e-8)
(1.0, 2.0, 0.0, 3.0)
sage: v.zero_at(1e-12)
(1.0, 2.0, 1e-10, 3.0)
```

For complex numbers the real and imaginary parts are considered separately.

```
sage: w = vector(CDF, [10^-6 + 5*I, 5 + 10^-6*I, 5 + 5*I, 10^-6 + 10^-6*I])
sage: w.zero_at(1.0e-4)
(5.0*I, 5.0, 5.0 + 5.0*I, 0.0)
sage: w.zero_at(1.0e-8)
(1e-06 + 5.0*I, 5.0 + 1e-06*I, 5.0 + 5.0*I, 1e-06 + 1e-06*I)
```



## VECTORS WITH INTEGER ENTRIES

AUTHOR:

- William Stein (2007)

EXAMPLES:

```
sage: v = vector(ZZ, [1,2,3,4,5])
sage: v
(1, 2, 3, 4, 5)
sage: 3*v
(3, 6, 9, 12, 15)
sage: v*7
(7, 14, 21, 28, 35)
sage: -v
(-1, -2, -3, -4, -5)
sage: v - v
(0, 0, 0, 0, 0)
sage: v + v
(2, 4, 6, 8, 10)
sage: v * v    # dot product.
55
```

We make a large zero vector:

```
sage: k = ZZ^100000; k
Ambient free module of rank 100000 over the principal ideal domain Integer Ring
sage: v = k(0)
sage: v[:10]
(0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
```

TESTS:

```
sage: v = vector(ZZ, [1,2,3,4])
sage: loads(dumps(v)) == v
True

sage: w = vector(ZZ, [-1,0,0,0])
sage: w.set_immutable()
sage: isinstance(hash(w), int)
True
```

```
class sage.modules.vector_integer_dense.Vector_integer_dense
    Bases: sage.modules.free_module_element.FreeModuleElement

    list (copy=True)
        The list of entries of the vector.
```

INPUT:

- `copy`, ignored optional argument.

EXAMPLES:

```
sage: v = vector([1,2,3,4])
sage: a = v.list(copy=False); a
[1, 2, 3, 4]
sage: a[0] = 0
sage: v
(1, 2, 3, 4)
```

```
sage.modules.vector_integer_dense.unpickle_v0(parent, entries, degree)
```

```
sage.modules.vector_integer_dense.unpickle_v1(parent, entries, degree, is_mutable)
```

## VECTORS WITH ELEMENTS IN $GF(2)$ .

AUTHOR:

- Martin Albrecht (2009-12): initial implementation
- Thomas Feulner (2012-11): added `Vector_mod2_dense.hamming_weight()`

EXAMPLES:

```
sage: VS = GF(2)^3
sage: e = VS.random_element(); e
(1, 0, 0)
sage: f = VS.random_element(); f
(0, 1, 1)
sage: e + f
(1, 1, 1)
```

TESTS:

```
sage: w = vector(GF(2), [-1, 0, 0, 0])
sage: w.set_immutable()
sage: isinstance(hash(w), int)
True
```

```
class sage.modules.vector_mod2_dense.Vector_mod2_dense
    Bases: sage.modules.free_module_element.FreeModuleElement
```

EXAMPLE:

```
sage: VS = VectorSpace(GF(2), 3)
sage: VS((0, 0, 1/3))
(0, 0, 1)
sage: type(_)
<type 'sage.modules.vector_mod2_dense.Vector_mod2_dense'>
sage: VS((0, 0, int(3)))
(0, 0, 1)
sage: VS((0, 0, 3))
(0, 0, 1)
sage: VS((0, 0, GF(2)(1)))
(0, 0, 1)
```

TESTS:

Check that ticket #8601 is fixed:

```
sage: VS = VectorSpace(GF(2), 3)
sage: VS((-1, -2, -3))
(1, 0, 1)
```

```
sage: V = VectorSpace(GF(2), 2)
sage: V([1, 3])
(1, 1)
sage: V([1, -3])
(1, 1)
```

**hamming\_weight()**

Return the number of positions  $i$  such that  $\text{self}[i] \neq 0$ .

EXAMPLES:

```
sage: vector(GF(2), [1, 1, 0]).hamming_weight()
2
```

**list(copy=True)**

Return a list of entries in `self`.

INPUT:

- `copy` - always `True`

EXAMPLE:

```
sage: VS = VectorSpace(GF(2), 10)
sage: e = VS.random_element(); e
(1, 0, 0, 0, 1, 1, 1, 0, 0, 1)
sage: e.list()
[1, 0, 0, 0, 1, 1, 1, 0, 0, 1]
```

**n(\*args, \*\*kwargs)**

Returns a numerical approximation of `self` by calling the `n()` method on all of its entries.

EXAMPLES:

```
sage: v = vector(GF(2), [1, 2, 3])
sage: v.n()
(1.0000000000000000, 0.0000000000000000, 1.0000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: v.n(prec=75)
(1.0000000000000000000000000000000000, 0.0000000000000000000000000000000000, 1.0000000000000000000000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 75 bits of precision
```

`sage.modules.vector_mod2_dense.unpickle_v0(parent, entries, degree, is_mutable)`

EXAMPLE:

```
sage: from sage.modules.vector_mod2_dense import unpickle_v0
sage: VS = VectorSpace(GF(2), 10)
sage: unpickle_v0(VS, [0, 1, 2, 3, 4, 5, 6, 7, 8, 9], 10, 0)
(0, 1, 0, 1, 0, 1, 0, 1, 0, 1)
```

## VECTORS WITH INTEGER MOD N ENTRIES, WITH N SMALL.

EXAMPLES:

```
sage: v = vector(Integers(8), [1, 2, 3, 4, 5])
sage: type(v)
<type 'sage.modules.vector_modn_dense.Vector_modn_dense'>
sage: v
(1, 2, 3, 4, 5)
sage: 3*v
(3, 6, 1, 4, 7)
sage: v*7
(7, 6, 5, 4, 3)
sage: -v
(7, 6, 5, 4, 3)
sage: v - v
(0, 0, 0, 0, 0)
sage: v + v
(2, 4, 6, 0, 2)
sage: v * v
7

sage: v = vector(Integers(8), [1, 2, 3, 4, 5])
sage: u = vector(Integers(8), [1, 2, 3, 4, 4])
sage: v - u
(0, 0, 0, 0, 1)
sage: u - v
(0, 0, 0, 0, 7)

sage: v = vector((Integers(5)(1), 2, 3, 4, 4))
sage: u = vector((Integers(5)(1), 2, 3, 4, 3))
sage: v - u
(0, 0, 0, 0, 1)
sage: u - v
(0, 0, 0, 0, 4)
```

We make a large zero vector:

```
sage: k = Integers(8)^100000; k
Ambient free module of rank 100000 over Ring of integers modulo 8
sage: v = k(0)
sage: v[:10]
(0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
```

We multiply a vector by a matrix:

```
sage: a = (GF(97)^5)(range(5))
sage: m = matrix(GF(97), 5, range(25))
sage: a*m
(53, 63, 73, 83, 93)
```

**TESTS:**

```
sage: v = vector(Integers(8), [1,2,3,4,5])
sage: loads(dumps(v)) == v
True
sage: v = vector(Integers(389), [1,2,3,4,5])
sage: loads(dumps(v)) == v
True
sage: v = vector(Integers(next_prime(10^20)), [1,2,3,4,5])
sage: loads(dumps(v)) == v
True

sage: K = GF(previous_prime(2^31))
sage: v = vector(K, [42]); type(v[0])
<type 'sage.rings.finite_rings.integer_mod.IntegerMod_int64'>
sage: ~v[0]
2096353084

sage: K = GF(next_prime(2^31))
sage: v = vector(K, [42]); type(v[0])
<type 'sage.rings.finite_rings.integer_mod.IntegerMod_gmp'>
sage: ~v[0]
1482786336

sage: w = vector(GF(11), [-1,0,0,0])
sage: w.set_immutable()
sage: isinstance(hash(w), int)
True
```

**AUTHOR:**

- William Stein (2007)

```
class sage.modules.vector_modn_dense.Vector_modn_dense
    Bases: sage.modules.free_module_element.FreeModuleElement
sage.modules.vector_modn_dense.unpickle_v0 (parent, entries, degree, p)
sage.modules.vector_modn_dense.unpickle_v1 (parent, entries, degree, p, is_mutable)
```

## VECTORS WITH RATIONAL ENTRIES.

AUTHOR:

- William Stein (2007)
- Soroosh Yazdani (2007)

EXAMPLES:

```
sage: v = vector(QQ, [1, 2, 3, 4, 5])
sage: v
(1, 2, 3, 4, 5)
sage: 3*v
(3, 6, 9, 12, 15)
sage: v/2
(1/2, 1, 3/2, 2, 5/2)
sage: -v
(-1, -2, -3, -4, -5)
sage: v - v
(0, 0, 0, 0, 0)
sage: v + v
(2, 4, 6, 8, 10)
sage: v * v
55
```

We make a large zero vector:

```
sage: k = QQ^100000; k
Vector space of dimension 100000 over Rational Field
sage: v = k(0)
sage: v[:10]
(0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
```

TESTS:

```
sage: v = vector(QQ, [1, 2/5, -3/8, 4])
sage: loads(dumps(v)) == v
True
```

```
sage: w = vector(QQ, [-1, 0, 0, 0])
sage: w.set_immutable()
sage: isinstance(hash(w), int)
True
```

```
class sage.modules.vector_rational_dense.Vector_rational_dense
    Bases: sage.modules.free_module_element.FreeModuleElement
```

**list** (*copy=True*)

The list of entries of the vector.

INPUT:

- copy*, ignored optional argument.

EXAMPLES:

```
sage: v = vector(QQ, [1, 2, 3, 4])
sage: a = v.list(copy=False); a
[1, 2, 3, 4]
sage: a[0] = 0
sage: v
(1, 2, 3, 4)
```

`sage.modules.vector_rational_dense.unpickle_v0` (*parent, entries, degree*)

`sage.modules.vector_rational_dense.unpickle_v1` (*parent, entries, degree, is\_mutable*)



## DENSE REAL DOUBLE VECTORS USING A NUMPY BACKEND.

**EXAMPLES:** sage: `v = vector(RDF,[1, pi, sqrt(2)])` sage: `v` (1.0, 3.141592653589793, 1.414213562373095)  
sage: `type(v)` <type 'sage.modules.vector\_real\_double\_dense.Vector\_real\_double\_dense'> sage: `parent(v)`  
Vector space of dimension 3 over Real Double Field sage: `v[0] = 5` sage: `v` (5.0, 3.141592653589793,  
1.414213562373095) sage: `loads(dumps(v)) == v` True

### AUTHORS:

– Jason Grout, Oct 2008: switch to numpy backend, factored out `Vector_double_dense` class

**class** `sage.modules.vector_real_double_dense.Vector_real_double_dense`

Bases: `sage.modules.vector_double_dense.Vector_double_dense`

Vectors over the Real Double Field. These are supposed to be fast vector operations using C doubles. Most operations are implemented using numpy which will call the underlying BLAS, if needed, on the system.

**EXAMPLES:** sage: `v = vector(RDF, [1,2,3,4])`; `v` (1.0, 2.0, 3.0, 4.0) sage: `v*v` 30.0

**stats\_skew()**

Computes the skewness of a data set.

For normally distributed data, the skewness should be about 0. A skewness value > 0 means that there is more weight in the left tail of the distribution. (Paragraph from the `scipy.stats` docstring.)

**EXAMPLE:** sage: `v = vector(RDF, range(9))` sage: `v.stats_skew()` 0.0

`sage.modules.vector_real_double_dense.unpickle_v0` (*parent*, *entries*, *degree*)

Create a real double vector containing the entries.

**EXAMPLE:** sage: `v = vector(RDF, [1,2,3])` sage: `w = sage.modules.vector_real_double_dense.unpickle_v0(v.parent(), list(v), v.degree())` sage: `v == w` True

`sage.modules.vector_real_double_dense.unpickle_v1` (*parent*, *entries*, *degree*,  
*is\_mutable=None*)

Create a real double vector with the given parent, entries, degree, and mutability.

**EXAMPLE:** sage: `v = vector(RDF, [1,2,3])` sage: `w = sage.modules.vector_real_double_dense.unpickle_v1(v.parent(), list(v), v.degree(), v.is_mutable())` sage: `v == w` True



## VECTORS OVER THE SYMBOLIC RING.

Implements vectors over the symbolic ring.

AUTHORS:

- Robert Bradshaw (2011-05-25): Added more element-wise simplification methods
- Joris Vankerschaver (2011-05-15): Initial version

EXAMPLES:

```
sage: x, y = var('x, y')
sage: u = vector([sin(x)^2 + cos(x)^2, log(2*y) + log(3*y)]); u
(cos(x)^2 + sin(x)^2, log(3*y) + log(2*y))
sage: type(u)
<class 'sage.modules.vector_symbolic_dense.FreeModule_ambient_field_with_category.element_class'>
sage: u.simplify_full()
(1, log(3*y) + log(2*y))
```

TESTS:

Check that the outcome of arithmetic with symbolic vectors is again a symbolic vector (#11549):

```
sage: v = vector(SR, [1, 2])
sage: w = vector(SR, [sin(x), 0])
sage: type(v)
<class 'sage.modules.vector_symbolic_dense.FreeModule_ambient_field_with_category.element_class'>
sage: type(w)
<class 'sage.modules.vector_symbolic_dense.FreeModule_ambient_field_with_category.element_class'>
sage: type(v + w)
<class 'sage.modules.vector_symbolic_dense.FreeModule_ambient_field_with_category.element_class'>
sage: type(-v)
<class 'sage.modules.vector_symbolic_dense.FreeModule_ambient_field_with_category.element_class'>
sage: type(5*w)
<class 'sage.modules.vector_symbolic_dense.FreeModule_ambient_field_with_category.element_class'>
```

Test pickling/unpickling:

```
sage: u = vector(SR, [sin(x^2)])
sage: loads(dumps(u)) == u
True
```

```
class sage.modules.vector_symbolic_dense.Vector_symbolic_dense
    Bases: sage.modules.free_module_element.FreeModuleElement_generic_dense
    canonicalize_radical(*args, **kws)
```

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.canonicalize_radical()` for optional arguments.

**simplify** (\*args, \*\*kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.simplify()` for optional arguments.

**`simplify_exp(*args, **kws)`**

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.simplify_exp()` for optional arguments.

**`simplify_factorial(*args, **kws)`**

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
```

```
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.simplify_factorial()` for optional arguments.

**simplify\_full**(\*args, \*\*kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.simplify_full()` for optional arguments.

**simplify\_log**(\*args, \*\*kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
```

```

sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See `Expression.simplify_log()` for optional arguments.

### **simplify\_radical**(\*args, \*\*kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```

sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See `Expression.simplify_radical()` for optional arguments.

### **simplify\_rational**(\*args, \*\*kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```

sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)

```

```
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.simplify_rational()` for optional arguments.

**simplify\_trig**(*\*args*, *\*\*kws*)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.simplify_trig()` for optional arguments.

**trig\_expand**(*\*args*, *\*\*kws*)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
```



```

sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See `Expression.expand_trig()` for optional arguments.

**trig\_reduce** (\*args, \*\*kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```

sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)), factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See `Expression.reduce_trig()` for optional arguments.

`sage.modules.vector_symbolic_dense.apply_map` (*phi*)

Returns a function that applies *phi* to its argument.

EXAMPLES:

```

sage: from sage.modules.vector_symbolic_dense import apply_map
sage: v = vector([1, 2, 3])
sage: f = apply_map(lambda x: x+1)
sage: f(v)
(2, 3, 4)

```



## INDICES AND TABLES

- Index
- Module Index
- Search Page



## BIBLIOGRAPHY

- [Mic2010] D. Micciancio, P. Voulgaris. *A Deterministic Single Exponential Time Algorithm for Most Lattice Problems based on Voronoi Cell Computations*. Proceedings of the 42nd ACM Symposium Theory of Computation, 2010.
- [Vit1996] E. Viterbo, E. Biglieri. *Computing the Voronoi Cell of a Lattice: The Diamond-Cutting Algorithm*. IEEE Transactions on Information Theory, 1996.
- [WIKIPEDIA:CROSSPRODUCT] Algebraic Properties of the Cross Product  
[http://en.wikipedia.org/wiki/Cross\\_product](http://en.wikipedia.org/wiki/Cross_product)



## m

- `sage.modules.complex_double_vector`, 151
- `sage.modules.diamond_cutting`, 225
- `sage.modules.fg_pid.fgp_element`, 217
- `sage.modules.fg_pid.fgp_module`, 203
- `sage.modules.fg_pid.fgp_morphism`, 221
- `sage.modules.finite_submodule_iter`, 247
- `sage.modules.free_module`, 5
- `sage.modules.free_module_element`, 71
- `sage.modules.free_module_homspace`, 175
- `sage.modules.free_module_integer`, 61
- `sage.modules.free_module_morphism`, 179
- `sage.modules.free_quadratic_module`, 251
- `sage.modules.matrix_morphism`, 189
- `sage.modules.misc`, 263
- `sage.modules.module`, 1
- `sage.modules.quotient_module`, 265
- `sage.modules.real_double_vector`, 153
- `sage.modules.vector_callable_symbolic_dense`, 155
- `sage.modules.vector_complex_double_dense`, 269
- `sage.modules.vector_double_dense`, 271
- `sage.modules.vector_integer_dense`, 277
- `sage.modules.vector_mod2_dense`, 279
- `sage.modules.vector_modn_dense`, 281
- `sage.modules.vector_rational_dense`, 283
- `sage.modules.vector_real_double_dense`, 285
- `sage.modules.vector_space_homspace`, 157
- `sage.modules.vector_space_morphism`, 161
- `sage.modules.vector_symbolic_dense`, 287
- `sage.modules.with_basis.__init__`, 227
- `sage.modules.with_basis.morphism`, 229
- `sage.modules.with_basis.subquotient`, 243

## t

- `sage.tensor.modules.finite_rank_free_module`, 119





## A

additive\_order() (sage.modules.fg\_pid.fgp\_element.FGP\_Element method), 217  
 additive\_order() (sage.modules.free\_module\_element.FreeModuleElement method), 72  
 alternating\_form() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 130  
 ambient() (sage.modules.with\_basis.subquotient.QuotientModuleWithBasis method), 243  
 ambient() (sage.modules.with\_basis.subquotient.SubmoduleWithBasis method), 244  
 ambient\_module() (sage.modules.free\_module.FreeModule\_ambient method), 9  
 ambient\_module() (sage.modules.free\_module.FreeModule\_generic method), 15  
 ambient\_module() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 50  
 ambient\_module() (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_generic method), 254  
 ambient\_vector\_space() (sage.modules.free\_module.FreeModule\_ambient\_domain method), 13  
 ambient\_vector\_space() (sage.modules.free\_module.FreeModule\_ambient\_field method), 14  
 ambient\_vector\_space() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 50  
 ambient\_vector\_space() (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_ambient\_domain method), 253  
 annihilator() (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 207  
 apply\_map() (in module sage.modules.vector\_symbolic\_dense), 293  
 apply\_map() (sage.modules.free\_module\_element.FreeModuleElement method), 73  
 are\_linearly\_dependent() (sage.modules.free\_module.FreeModule\_generic method), 15  
 automorphism() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 131

## B

base\_extend() (sage.modules.module.Module method), 2  
 base\_field() (sage.modules.free\_module.FreeModule\_ambient\_field method), 15  
 base\_field() (sage.modules.free\_module.FreeModule\_generic method), 16  
 base\_ring() (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 207  
 base\_ring() (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 192  
 bases() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 132  
 basis() (sage.modules.free\_module.FreeModule\_ambient method), 9  
 basis() (sage.modules.free\_module.FreeModule\_generic method), 16  
 basis() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 51  
 basis() (sage.modules.free\_module\_homspace.FreeModuleHomspace method), 176  
 basis() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 132  
 basis\_matrix() (sage.modules.free\_module.FreeModule\_generic method), 16  
 basis\_seq() (in module sage.modules.free\_module), 57  
 BKZ() (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 62

## C

`calculate_voronoi_cell()` (in module `sage.modules.diamond_cutting`), 225

`canonicalize_radical()` (`sage.modules.vector_symbolic_dense.Vector_symbolic_dense` method), 287

`cardinality()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 207

`cardinality()` (`sage.modules.free_module.FreeModule_generic` method), 17

`change_of_basis()` (`sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule` method), 134

`change_ring()` (`sage.modules.free_module.FreeModule_ambient` method), 9

`change_ring()` (`sage.modules.free_module.FreeModule_submodule_with_basis_pid` method), 51

`change_ring()` (`sage.modules.free_module_element.FreeModuleElement` method), 74

`change_ring()` (`sage.modules.free_module_morphism.FreeModuleMorphism` method), 179

`change_ring()` (`sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid` method), 260

`change_ring()` (`sage.modules.module.Module` method), 3

`characteristic_polynomial()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 192

`charpoly()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 192

`closest_vector()` (`sage.modules.free_module_integer.FreeModule_submodule_with_basis_integer` method), 64

`co_kernel_projection()` (`sage.modules.with_basis.morphism.TriangularModuleMorphism` method), 237

`co_reduced()` (`sage.modules.with_basis.morphism.TriangularModuleMorphism` method), 237

`cokernel_basis_indices()` (`sage.modules.with_basis.morphism.TriangularModuleMorphism` method), 237

`cokernel_projection()` (`sage.modules.with_basis.morphism.TriangularModuleMorphism` method), 238

`column()` (`sage.modules.free_module_element.FreeModuleElement` method), 74

`complement()` (`sage.modules.free_module.FreeModule_generic_field` method), 28

`complex_vector()` (`sage.modules.vector_double_dense.Vector_double_dense` method), 271

`ComplexDoubleVectorSpace_class` (class in `sage.modules.free_module`), 7

`conjugate()` (`sage.modules.free_module_element.FreeModuleElement` method), 75

`construction()` (`sage.modules.free_module.FreeModule_generic` method), 18

`construction()` (`sage.modules.free_module.FreeModule_submodule_with_basis_pid` method), 52

`coordinate_module()` (`sage.modules.free_module.FreeModule_generic` method), 18

`coordinate_ring()` (`sage.modules.free_module.FreeModule_generic` method), 19

`coordinate_ring()` (`sage.modules.free_module_element.FreeModuleElement` method), 76

`coordinate_vector()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 208

`coordinate_vector()` (`sage.modules.free_module.FreeModule_ambient` method), 10

`coordinate_vector()` (`sage.modules.free_module.FreeModule_ambient_domain` method), 14

`coordinate_vector()` (`sage.modules.free_module.FreeModule_generic` method), 19

`coordinate_vector()` (`sage.modules.free_module.FreeModule_submodule_field` method), 46

`coordinate_vector()` (`sage.modules.free_module.FreeModule_submodule_pid` method), 47

`coordinate_vector()` (`sage.modules.free_module.FreeModule_submodule_with_basis_pid` method), 52

`coordinates()` (`sage.modules.free_module.ComplexDoubleVectorSpace_class` method), 7

`coordinates()` (`sage.modules.free_module.FreeModule_generic` method), 19

`coordinates()` (`sage.modules.free_module.RealDoubleVectorSpace_class` method), 56

`coreduced()` (`sage.modules.with_basis.morphism.TriangularModuleMorphism` method), 238

`cover()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 209

`cover()` (`sage.modules.quotient_module.FreeModule_ambient_field_quotient` method), 266

`create_key()` (`sage.modules.free_module.FreeModuleFactory` method), 9

`create_object()` (`sage.modules.free_module.FreeModuleFactory` method), 9

`cross_product()` (`sage.modules.free_module_element.FreeModuleElement` method), 77

`cross_product_matrix()` (`sage.modules.free_module_element.FreeModuleElement` method), 78

`curl()` (`sage.modules.free_module_element.FreeModuleElement` method), 79

## D

decomposition() (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 192  
 default\_basis() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 135  
 degree() (sage.modules.free\_module.FreeModule\_generic method), 20  
 degree() (sage.modules.free\_module\_element.FreeModuleElement method), 80  
 denominator() (sage.modules.free\_module.FreeModule\_generic\_pid method), 37  
 denominator() (sage.modules.free\_module\_element.FreeModuleElement method), 80  
 denominator() (sage.modules.free\_module\_element.FreeModuleElement\_generic\_sparse method), 102  
 dense\_module() (sage.modules.free\_module.FreeModule\_generic method), 20  
 dense\_vector() (sage.modules.free\_module\_element.FreeModuleElement method), 80  
 derivative() (sage.modules.free\_module\_element.FreeModuleElement method), 80  
 det() (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 193  
 determinant() (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_generic method), 254  
 DiagonalModuleMorphism (class in sage.modules.with\_basis.morphism), 230  
 diamond\_cut() (in module sage.modules.diamond\_cutting), 225  
 dict() (sage.modules.free\_module\_element.FreeModuleElement method), 81  
 dict() (sage.modules.free\_module\_element.FreeModuleElement\_generic\_sparse method), 102  
 diff() (sage.modules.free\_module\_element.FreeModuleElement method), 81  
 dimension() (sage.modules.free\_module.FreeModule\_generic method), 20  
 direct\_sum() (sage.modules.free\_module.FreeModule\_generic method), 21  
 discriminant() (sage.modules.free\_module.FreeModule\_generic method), 21  
 discriminant() (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 64  
 discriminant() (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_generic method), 254  
 div() (sage.modules.free\_module\_element.FreeModuleElement method), 81  
 dot\_product() (sage.modules.free\_module\_element.FreeModuleElement method), 82  
 dual() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 136  
 dual\_exterior\_power() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 137

## E

echelon\_coordinate\_vector() (sage.modules.free\_module.FreeModule\_ambient method), 10  
 echelon\_coordinate\_vector() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 52  
 echelon\_coordinates() (sage.modules.free\_module.FreeModule\_ambient method), 10  
 echelon\_coordinates() (sage.modules.free\_module.FreeModule\_submodule\_field method), 46  
 echelon\_coordinates() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 53  
 echelon\_to\_user\_matrix() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 54  
 echelonized\_basis() (sage.modules.free\_module.FreeModule\_ambient method), 11  
 echelonized\_basis() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 54  
 echelonized\_basis\_matrix() (sage.modules.free\_module.FreeModule\_ambient method), 11  
 echelonized\_basis\_matrix() (sage.modules.free\_module.FreeModule\_generic method), 21  
 echelonized\_basis\_matrix() (sage.modules.free\_module.FreeModule\_generic\_field method), 29  
 echelonized\_basis\_matrix() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 54  
 eigenspaces() (sage.modules.free\_module\_morphism.FreeModuleMorphism method), 180  
 eigenvalues() (sage.modules.free\_module\_morphism.FreeModuleMorphism method), 181  
 eigenvectors() (sage.modules.free\_module\_morphism.FreeModuleMorphism method), 181  
 Element (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class attribute), 207  
 Element (sage.modules.fg\_pid.fgp\_morphism.FGP\_Homset\_class attribute), 221  
 Element (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule attribute), 130  
 element() (sage.modules.free\_module\_element.FreeModuleElement method), 83  
 element\_class() (in module sage.modules.free\_module), 57  
 endomorphism() (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 137

`endomorphism_ring()` (`sage.modules.module.Module` method), 3

## F

`fcf()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 193

`fft()` (`sage.modules.vector_double_dense.Vector_double_dense` method), 272

`FGP_Element` (class in `sage.modules.fg_pid.fgp_element`), 217

`FGP_Homset()` (in module `sage.modules.fg_pid.fgp_morphism`), 221

`FGP_Homset_class` (class in `sage.modules.fg_pid.fgp_morphism`), 221

`FGP_Module()` (in module `sage.modules.fg_pid.fgp_module`), 206

`FGP_Module_class` (class in `sage.modules.fg_pid.fgp_module`), 206

`FGP_Morphism` (class in `sage.modules.fg_pid.fgp_morphism`), 221

`FiniteFieldsubspace_iterator` (class in `sage.modules.finite_submodule_iter`), 248

`FiniteFieldsubspace_projPoint_iterator` (class in `sage.modules.finite_submodule_iter`), 248

`FiniteRankFreeModule` (class in `sage.tensor.modules.finite_rank_free_module`), 127

`FiniteZZsubmodule_iterator` (class in `sage.modules.finite_submodule_iter`), 249

`free_module()` (`sage.modules.free_module.FreeModule_generic` method), 22

`free_module_element()` (in module `sage.modules.free_module_element`), 103

`FreeModule_ambient` (class in `sage.modules.free_module`), 9

`FreeModule_ambient_domain` (class in `sage.modules.free_module`), 13

`FreeModule_ambient_field` (class in `sage.modules.free_module`), 14

`FreeModule_ambient_field_quotient` (class in `sage.modules.quotient_module`), 265

`FreeModule_ambient_pid` (class in `sage.modules.free_module`), 15

`FreeModule_generic` (class in `sage.modules.free_module`), 15

`FreeModule_generic_field` (class in `sage.modules.free_module`), 28

`FreeModule_generic_pid` (class in `sage.modules.free_module`), 37

`FreeModule_submodule_field` (class in `sage.modules.free_module`), 45

`FreeModule_submodule_pid` (class in `sage.modules.free_module`), 47

`FreeModule_submodule_with_basis_field` (class in `sage.modules.free_module`), 48

`FreeModule_submodule_with_basis_integer` (class in `sage.modules.free_module_integer`), 61

`FreeModule_submodule_with_basis_pid` (class in `sage.modules.free_module`), 49

`FreeModuleElement` (class in `sage.modules.free_module_element`), 72

`FreeModuleElement_generic_dense` (class in `sage.modules.free_module_element`), 100

`FreeModuleElement_generic_sparse` (class in `sage.modules.free_module_element`), 102

`FreeModuleFactory` (class in `sage.modules.free_module`), 7

`FreeModuleHomspace` (class in `sage.modules.free_module_homspace`), 176

`FreeModuleMorphism` (class in `sage.modules.free_module_morphism`), 179

`FreeQuadraticModule()` (in module `sage.modules.free_quadratic_module`), 252

`FreeQuadraticModule_ambient` (class in `sage.modules.free_quadratic_module`), 252

`FreeQuadraticModule_ambient_domain` (class in `sage.modules.free_quadratic_module`), 252

`FreeQuadraticModule_ambient_field` (class in `sage.modules.free_quadratic_module`), 253

`FreeQuadraticModule_ambient_pid` (class in `sage.modules.free_quadratic_module`), 253

`FreeQuadraticModule_generic` (class in `sage.modules.free_quadratic_module`), 253

`FreeQuadraticModule_generic_field` (class in `sage.modules.free_quadratic_module`), 255

`FreeQuadraticModule_generic_pid` (class in `sage.modules.free_quadratic_module`), 257

`FreeQuadraticModule_submodule_field` (class in `sage.modules.free_quadratic_module`), 258

`FreeQuadraticModule_submodule_pid` (class in `sage.modules.free_quadratic_module`), 258

`FreeQuadraticModule_submodule_with_basis_field` (class in `sage.modules.free_quadratic_module`), 259

`FreeQuadraticModule_submodule_with_basis_pid` (class in `sage.modules.free_quadratic_module`), 260

`function()` (`sage.modules.free_module_element.FreeModuleElement_generic_dense` method), 101

## G

[gen\(\) \(sage.modules.fg\\_pid.fgp\\_module.FGP\\_Module\\_class method\)](#), 209  
[gen\(\) \(sage.modules.free\\_module.FreeModule\\_ambient method\)](#), 11  
[gen\(\) \(sage.modules.free\\_module.FreeModule\\_generic method\)](#), 22  
[general\\_linear\\_group\(\) \(sage.tensor.modules.finite\\_rank\\_free\\_module.FiniteRankFreeModule method\)](#), 138  
[gens\(\) \(sage.modules.fg\\_pid.fgp\\_module.FGP\\_Module\\_class method\)](#), 210  
[gens\(\) \(sage.modules.free\\_module.FreeModule\\_generic method\)](#), 22  
[get\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\)](#), 83  
[gram\\_matrix\(\) \(sage.modules.free\\_module.FreeModule\\_generic method\)](#), 22  
[gram\\_matrix\(\) \(sage.modules.free\\_quadratic\\_module.FreeQuadraticModule\\_generic method\)](#), 254  
[gram\\_schmidt\(\) \(in module sage.modules.misc\)](#), 263

## H

[hamming\\_weight\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\)](#), 84  
[hamming\\_weight\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement\\_generic\\_sparse method\)](#), 103  
[hamming\\_weight\(\) \(sage.modules.vector\\_mod2\\_dense.Vector\\_mod2\\_dense method\)](#), 280  
[has\\_canonical\\_map\\_to\(\) \(sage.modules.fg\\_pid.fgp\\_module.FGP\\_Module\\_class method\)](#), 210  
[has\\_user\\_basis\(\) \(sage.modules.free\\_module.FreeModule\\_generic method\)](#), 23  
[has\\_user\\_basis\(\) \(sage.modules.free\\_module.FreeModule\\_submodule\\_field method\)](#), 47  
[has\\_user\\_basis\(\) \(sage.modules.free\\_module.FreeModule\\_submodule\\_pid method\)](#), 48  
[has\\_user\\_basis\(\) \(sage.modules.free\\_module.FreeModule\\_submodule\\_with\\_basis\\_pid method\)](#), 55  
[hermitian\\_inner\\_product\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\)](#), 84  
[HKZ\(\) \(sage.modules.free\\_module\\_integer.FreeModule\\_submodule\\_with\\_basis\\_integer method\)](#), 62  
[hom\(\) \(sage.modules.fg\\_pid.fgp\\_module.FGP\\_Module\\_class method\)](#), 210  
[hom\(\) \(sage.tensor.modules.finite\\_rank\\_free\\_module.FiniteRankFreeModule method\)](#), 139

## I

[identity\(\) \(sage.modules.free\\_module\\_homspace.FreeModuleHomspace method\)](#), 176  
[identity\\_map\(\) \(sage.tensor.modules.finite\\_rank\\_free\\_module.FiniteRankFreeModule method\)](#), 140  
[im\\_gens\(\) \(sage.modules.fg\\_pid.fgp\\_morphism.FGP\\_Morphism method\)](#), 222  
[image\(\) \(sage.modules.fg\\_pid.fgp\\_morphism.FGP\\_Morphism method\)](#), 222  
[image\(\) \(sage.modules.matrix\\_morphism.MatrixMorphism\\_abstract method\)](#), 193  
[index\\_in\(\) \(sage.modules.free\\_module.FreeModule\\_generic\\_pid method\)](#), 38  
[index\\_in\\_saturation\(\) \(sage.modules.free\\_module.FreeModule\\_generic\\_pid method\)](#), 38  
[inner\\_product\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\)](#), 85  
[inner\\_product\\_matrix\(\) \(sage.modules.free\\_module.FreeModule\\_generic method\)](#), 23  
[inner\\_product\\_matrix\(\) \(sage.modules.free\\_quadratic\\_module.FreeQuadraticModule\\_generic method\)](#), 255  
[InnerProductSpace\(\) \(in module sage.modules.free\\_quadratic\\_module\)](#), 261  
[IntegerLattice\(\) \(in module sage.modules.free\\_module\\_integer\)](#), 67  
[integral\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\)](#), 86  
[integrate\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\)](#), 86  
[intersection\(\) \(sage.modules.free\\_module.FreeModule\\_generic\\_field method\)](#), 29  
[intersection\(\) \(sage.modules.free\\_module.FreeModule\\_generic\\_pid method\)](#), 38  
[inv\\_fft\(\) \(sage.modules.vector\\_double\\_dense.Vector\\_double\\_dense method\)](#), 272  
[invariants\(\) \(sage.modules.fg\\_pid.fgp\\_module.FGP\\_Module\\_class method\)](#), 212  
[inverse\(\) \(sage.modules.matrix\\_morphism.MatrixMorphism\\_abstract method\)](#), 194  
[inverse\\_image\(\) \(sage.modules.fg\\_pid.fgp\\_morphism.FGP\\_Morphism method\)](#), 222  
[inverse\\_image\(\) \(sage.modules.free\\_module\\_morphism.FreeModuleMorphism method\)](#), 182  
[irange\(\) \(sage.tensor.modules.finite\\_rank\\_free\\_module.FiniteRankFreeModule method\)](#), 141  
[is\\_ambient\(\) \(sage.modules.free\\_module.FreeModule\\_ambient method\)](#), 12

`is_ambient()` (sage.modules.free\_module.FreeModule\_generic method), 23  
`is_ambient()` (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_field method), 49  
`is_bijective()` (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 196  
`is_dense()` (sage.modules.free\_module.FreeModule\_generic method), 24  
`is_dense()` (sage.modules.free\_module\_element.FreeModuleElement method), 87  
`is_equal_function()` (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 196  
`is_FGP_Module()` (in module sage.modules.fg\_pid.fgp\_module), 215  
`is_finite()` (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 212  
`is_finite()` (sage.modules.free\_module.FreeModule\_generic method), 24  
`is_FreeModule()` (in module sage.modules.free\_module), 57  
`is_FreeModuleElement()` (in module sage.modules.free\_module\_element), 108  
`is_FreeModuleHomspace()` (in module sage.modules.free\_module\_homspace), 177  
`is_FreeModuleMorphism()` (in module sage.modules.free\_module\_morphism), 186  
`is_FreeQuadraticModule()` (in module sage.modules.free\_quadratic\_module), 262  
`is_full()` (sage.modules.free\_module.FreeModule\_generic method), 24  
`is_identity()` (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 197  
`is_immutable()` (sage.modules.free\_module\_element.FreeModuleElement method), 87  
`is_injective()` (sage.modules.matrix\_morphism.MatrixMorphism method), 190  
`is_invertible()` (sage.modules.vector\_space\_morphism.VectorSpaceMorphism method), 167  
`is_MatrixMorphism()` (in module sage.modules.matrix\_morphism), 202  
`is_Module()` (in module sage.modules.module), 3  
`is_mutable()` (sage.modules.free\_module\_element.FreeModuleElement method), 87  
`is_sparse()` (sage.modules.free\_module.FreeModule\_generic method), 24  
`is_sparse()` (sage.modules.free\_module\_element.FreeModuleElement method), 87  
`is_submodule()` (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 212  
`is_submodule()` (sage.modules.free\_module.FreeModule\_generic method), 24  
`is_submodule()` (sage.modules.with\_basis.subquotient.SubmoduleWithBasis method), 245  
`is_subspace()` (sage.modules.free\_module.FreeModule\_generic\_field method), 30  
`is_surjective()` (sage.modules.matrix\_morphism.MatrixMorphism method), 190  
`is_unimodular()` (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 64  
`is_vector()` (sage.modules.free\_module\_element.FreeModuleElement method), 87  
`is_VectorSpace()` (in module sage.modules.module), 3  
`is_VectorSpaceHomspace()` (in module sage.modules.vector\_space\_homspace), 160  
`is_VectorSpaceMorphism()` (in module sage.modules.vector\_space\_morphism), 167  
`is_zero()` (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 198  
`iteritems()` (sage.modules.free\_module\_element.FreeModuleElement method), 88  
`iteritems()` (sage.modules.free\_module\_element.FreeModuleElement\_generic\_sparse method), 103

## J

`jacobi()` (in module sage.modules.diamond\_cutting), 226

## K

`kernel()` (sage.modules.fg\_pid.fgp\_morphism.FGP\_Morphism method), 223  
`kernel()` (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 199

## L

`lift()` (sage.modules.fg\_pid.fgp\_element.FGP\_Element method), 218  
`lift()` (sage.modules.fg\_pid.fgp\_morphism.FGP\_Morphism method), 223  
`lift()` (sage.modules.free\_module\_element.FreeModuleElement method), 88  
`lift()` (sage.modules.free\_module\_morphism.FreeModuleMorphism method), 183



[lift\(\)](#) (sage.modules.quotient\_module.FreeModule\_ambient\_field\_quotient method), 266  
[lift\(\)](#) (sage.modules.with\_basis.subquotient.QuotientModuleWithBasis method), 244  
[lift\(\)](#) (sage.modules.with\_basis.subquotient.SubmoduleWithBasis method), 245  
[lift\\_map\(\)](#) (sage.modules.quotient\_module.FreeModule\_ambient\_field\_quotient method), 267  
[linear\\_combination\\_of\\_basis\(\)](#) (sage.modules.free\_module.FreeModule\_ambient method), 12  
[linear\\_combination\\_of\\_basis\(\)](#) (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 55  
[linear\\_combination\\_of\\_smith\\_form\\_gens\(\)](#) (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 213  
[linear\\_dependence\(\)](#) (sage.modules.free\_module.FreeModule\_generic\_field method), 30  
[linear\\_form\(\)](#) (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 142  
[linear\\_transformation\(\)](#) (in module sage.modules.vector\_space\_morphism), 168  
[list\(\)](#) (sage.modules.free\_module.FreeModule\_generic method), 25  
[list\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement method), 88  
[list\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement\_generic\_dense method), 101  
[list\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement\_generic\_sparse method), 103  
[list\(\)](#) (sage.modules.vector\_integer\_dense.Vector\_integer\_dense method), 277  
[list\(\)](#) (sage.modules.vector\_mod2\_dense.Vector\_mod2\_dense method), 280  
[list\(\)](#) (sage.modules.vector\_rational\_dense.Vector\_rational\_dense method), 283  
[list\\_from\\_positions\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement method), 88  
[LLL\(\)](#) (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 63

## M

[make\\_FreeModuleElement\\_generic\\_dense\(\)](#) (in module sage.modules.free\_module\_element), 108  
[make\\_FreeModuleElement\\_generic\\_dense\\_v1\(\)](#) (in module sage.modules.free\_module\_element), 108  
[make\\_FreeModuleElement\\_generic\\_sparse\(\)](#) (in module sage.modules.free\_module\_element), 108  
[make\\_FreeModuleElement\\_generic\\_sparse\\_v1\(\)](#) (in module sage.modules.free\_module\_element), 108  
[matrix\(\)](#) (sage.modules.free\_module.FreeModule\_generic method), 25  
[matrix\(\)](#) (sage.modules.matrix\_morphism.MatrixMorphism method), 191  
[matrix\(\)](#) (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 199  
[MatrixMorphism](#) (class in sage.modules.matrix\_morphism), 189  
[MatrixMorphism\\_abstract](#) (class in sage.modules.matrix\_morphism), 191  
[mean\(\)](#) (sage.modules.vector\_double\_dense.Vector\_double\_dense method), 272  
[minimal\\_polynomial\(\)](#) (sage.modules.free\_module\_morphism.FreeModuleMorphism method), 184  
[minpoly\(\)](#) (sage.modules.free\_module\_morphism.FreeModuleMorphism method), 184  
[Mod\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement method), 72  
[Module](#) (class in sage.modules.module), 1  
[Module\\_old](#) (class in sage.modules.module), 3  
[ModuleMorphism](#) (class in sage.modules.with\_basis.morphism), 231  
[ModuleMorphismByLinearity](#) (class in sage.modules.with\_basis.morphism), 231  
[ModuleMorphismFromFunction](#) (class in sage.modules.with\_basis.morphism), 232  
[ModuleMorphismFromMatrix](#) (class in sage.modules.with\_basis.morphism), 233  
[monic\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement method), 88

## N

[n\(\)](#) (sage.modules.vector\_mod2\_dense.Vector\_mod2\_dense method), 280  
[next\(\)](#) (sage.modules.finite\_submodule\_iter.FiniteFieldsSubspace\_projPoint\_iterator method), 249  
[next\(\)](#) (sage.modules.finite\_submodule\_iter.FiniteZZsubmodule\_iterator method), 250  
[ngens\(\)](#) (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 213  
[ngens\(\)](#) (sage.modules.free\_module.FreeModule\_generic method), 25  
[nintegral\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement method), 89  
[nintegrate\(\)](#) (sage.modules.free\_module\_element.FreeModuleElement method), 89

`nonembedded_free_module()` (`sage.modules.free_module.FreeModule_generic` method), 26  
`nonzero_positions()` (`sage.modules.free_module_element.FreeModuleElement` method), 89  
`nonzero_positions()` (`sage.modules.free_module_element.FreeModuleElement_generic_sparse` method), 103  
`norm()` (`sage.modules.free_module_element.FreeModuleElement` method), 90  
`norm()` (`sage.modules.vector_double_dense.Vector_double_dense` method), 273  
`normalized()` (`sage.modules.free_module_element.FreeModuleElement` method), 91  
`nullity()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 200  
`numpy()` (`sage.modules.free_module_element.FreeModuleElement` method), 91  
`numpy()` (`sage.modules.vector_double_dense.Vector_double_dense` method), 274

## O

`on_basis()` (`sage.modules.with_basis.morphism.ModuleMorphismByLinearity` method), 232  
`optimized()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 213  
`outer_product()` (`sage.modules.free_module_element.FreeModuleElement` method), 92

## P

`pairwise_product()` (`sage.modules.free_module_element.FreeModuleElement` method), 94  
`plane_inequality()` (in module `sage.modules.diamond_cutting`), 226  
`plot()` (`sage.modules.free_module_element.FreeModuleElement` method), 95  
`plot_step()` (`sage.modules.free_module_element.FreeModuleElement` method), 97  
`pointwise_inverse()` (`sage.modules.with_basis.morphism.PointwiseInverseFunction` method), 234  
`pointwise_inverse_function()` (in module `sage.modules.with_basis.morphism`), 242  
`PointwiseInverseFunction` (class in `sage.modules.with_basis.morphism`), 234  
`preimage()` (`sage.modules.with_basis.morphism.TriangularModuleMorphism` method), 239  
`preimage_representative()` (`sage.modules.free_module_morphism.FreeModuleMorphism` method), 185  
`prepare()` (in module `sage.modules.free_module_element`), 109  
`print_bases()` (`sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule` method), 142  
`prod()` (`sage.modules.vector_double_dense.Vector_double_dense` method), 275  
`pushforward()` (`sage.modules.free_module_morphism.FreeModuleMorphism` method), 186

## Q

`QuadraticSpace()` (in module `sage.modules.free_quadratic_module`), 261  
`quotient()` (`sage.modules.free_module.FreeModule_generic_field` method), 32  
`quotient()` (`sage.modules.free_module.FreeModule_generic_pid` method), 39  
`quotient_abstract()` (`sage.modules.free_module.FreeModule_generic_field` method), 32  
`quotient_map()` (`sage.modules.quotient_module.FreeModule_ambient_field_quotient` method), 267  
`QuotientModuleWithBasis` (class in `sage.modules.with_basis.subquotient`), 243

## R

`random_element()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 214  
`random_element()` (`sage.modules.free_module.FreeModule_ambient` method), 13  
`random_element()` (`sage.modules.free_module.FreeModule_generic` method), 26  
`random_fgp_module()` (in module `sage.modules.fg_pid.fgp_module`), 216  
`random_fgp_morphism_0()` (in module `sage.modules.fg_pid.fgp_module`), 216  
`random_vector()` (in module `sage.modules.free_module_element`), 110  
`rank()` (`sage.modules.free_module.FreeModule_generic` method), 26  
`rank()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 200  
`rank()` (`sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule` method), 143  
`RealDoubleVectorSpace_class` (class in `sage.modules.free_module`), 56  
`reduce()` (`sage.modules.with_basis.subquotient.SubmoduleWithBasis` method), 245



[reduced\\_basis \(sage.modules.free\\_module\\_integer.FreeModule\\_submodule\\_with\\_basis\\_integer attribute\), 65](#)  
[relations\(\) \(sage.modules.fg\\_pid.fgp\\_module.FGP\\_Module\\_class method\), 214](#)  
[relations\(\) \(sage.modules.quotient\\_module.FreeModule\\_ambient\\_field\\_quotient method\), 267](#)  
[restrict\(\) \(sage.modules.matrix\\_morphism.MatrixMorphism\\_abstract method\), 200](#)  
[restrict\\_codomain\(\) \(sage.modules.matrix\\_morphism.MatrixMorphism\\_abstract method\), 201](#)  
[restrict\\_domain\(\) \(sage.modules.matrix\\_morphism.MatrixMorphism\\_abstract method\), 202](#)  
[retract\(\) \(sage.modules.with\\_basis.subquotient.QuotientModuleWithBasis method\), 244](#)  
[retract\(\) \(sage.modules.with\\_basis.subquotient.SubmoduleWithBasis method\), 246](#)  
[row\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\), 97](#)

## S

[sage.modules.complex\\_double\\_vector \(module\), 151](#)  
[sage.modules.diamond\\_cutting \(module\), 225](#)  
[sage.modules.fg\\_pid.fgp\\_element \(module\), 217](#)  
[sage.modules.fg\\_pid.fgp\\_module \(module\), 203](#)  
[sage.modules.fg\\_pid.fgp\\_morphism \(module\), 221](#)  
[sage.modules.finite\\_submodule\\_iter \(module\), 247](#)  
[sage.modules.free\\_module \(module\), 5](#)  
[sage.modules.free\\_module\\_element \(module\), 71](#)  
[sage.modules.free\\_module\\_homspace \(module\), 175](#)  
[sage.modules.free\\_module\\_integer \(module\), 61](#)  
[sage.modules.free\\_module\\_morphism \(module\), 179](#)  
[sage.modules.free\\_quadratic\\_module \(module\), 251](#)  
[sage.modules.matrix\\_morphism \(module\), 189](#)  
[sage.modules.misc \(module\), 263](#)  
[sage.modules.module \(module\), 1](#)  
[sage.modules.quotient\\_module \(module\), 265](#)  
[sage.modules.real\\_double\\_vector \(module\), 153](#)  
[sage.modules.vector\\_callable\\_symbolic\\_dense \(module\), 155](#)  
[sage.modules.vector\\_complex\\_double\\_dense \(module\), 269](#)  
[sage.modules.vector\\_double\\_dense \(module\), 271](#)  
[sage.modules.vector\\_integer\\_dense \(module\), 277](#)  
[sage.modules.vector\\_mod2\\_dense \(module\), 279](#)  
[sage.modules.vector\\_modn\\_dense \(module\), 281](#)  
[sage.modules.vector\\_rational\\_dense \(module\), 283](#)  
[sage.modules.vector\\_real\\_double\\_dense \(module\), 285](#)  
[sage.modules.vector\\_space\\_homspace \(module\), 157](#)  
[sage.modules.vector\\_space\\_morphism \(module\), 161](#)  
[sage.modules.vector\\_symbolic\\_dense \(module\), 287](#)  
[sage.modules.with\\_basis.\\_\\_init\\_\\_ \(module\), 227](#)  
[sage.modules.with\\_basis.morphism \(module\), 229](#)  
[sage.modules.with\\_basis.subquotient \(module\), 243](#)  
[sage.tensor.modules.finite\\_rank\\_free\\_module \(module\), 119](#)  
[saturation\(\) \(sage.modules.free\\_module.FreeModule\\_generic\\_pid method\), 40](#)  
[scale\(\) \(sage.modules.free\\_module.FreeModule\\_generic\\_field method\), 33](#)  
[scale\(\) \(sage.modules.free\\_module.FreeModule\\_generic\\_pid method\), 40](#)  
[section\(\) \(sage.modules.with\\_basis.morphism.TriangularModuleMorphism method\), 241](#)  
[set\(\) \(sage.modules.free\\_module\\_element.FreeModuleElement method\), 98](#)  
[set\\_change\\_of\\_basis\(\) \(sage.tensor.modules.finite\\_rank\\_free\\_module.FiniteRankFreeModule method\), 143](#)  
[set\\_default\\_basis\(\) \(sage.tensor.modules.finite\\_rank\\_free\\_module.FiniteRankFreeModule method\), 144](#)

`set_immutable()` (sage.modules.free\_module\_element.FreeModuleElement method), 98

`shortest_vector()` (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 65

`simplify()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 288

`simplify_exp()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 289

`simplify_factorial()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 289

`simplify_full()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 290

`simplify_log()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 290

`simplify_radical()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 291

`simplify_rational()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 291

`simplify_trig()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 292

`smith_form_gen()` (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 214

`smith_form_gens()` (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 215

`span()` (in module sage.modules.free\_module), 58

`span()` (sage.modules.free\_module.FreeModule\_generic\_field method), 34

`span()` (sage.modules.free\_module.FreeModule\_generic\_pid method), 41

`span()` (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_generic\_field method), 256

`span()` (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_generic\_pid method), 257

`span_of_basis()` (sage.modules.free\_module.FreeModule\_generic\_field method), 34

`span_of_basis()` (sage.modules.free\_module.FreeModule\_generic\_pid method), 41

`span_of_basis()` (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_generic\_field method), 256

`span_of_basis()` (sage.modules.free\_quadratic\_module.FreeQuadraticModule\_generic\_pid method), 257

`sparse_module()` (sage.modules.free\_module.FreeModule\_generic method), 26

`sparse_vector()` (sage.modules.free\_module\_element.FreeModuleElement method), 98

`standard_deviation()` (sage.modules.vector\_double\_dense.Vector\_double\_dense method), 275

`stats_kurtosis()` (sage.modules.vector\_double\_dense.Vector\_double\_dense method), 275

`stats_skew()` (sage.modules.vector\_real\_double\_dense.Vector\_real\_double\_dense method), 285

`submodule()` (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 215

`submodule()` (sage.modules.free\_module.FreeModule\_generic\_pid method), 42

`submodule_with_basis()` (sage.modules.free\_module.FreeModule\_generic\_pid method), 43

`SubmoduleWithBasis` (class in sage.modules.with\_basis.subquotient), 244

`subs()` (sage.modules.free\_module\_element.FreeModuleElement method), 99

`subspace()` (sage.modules.free\_module.FreeModule\_generic\_field method), 35

`subspace_with_basis()` (sage.modules.free\_module.FreeModule\_generic\_field method), 36

`subspaces()` (sage.modules.free\_module.FreeModule\_generic\_field method), 36

`sum()` (sage.modules.vector\_double\_dense.Vector\_double\_dense method), 275

`support()` (sage.modules.free\_module\_element.FreeModuleElement method), 99

`sym_bilinear_form()` (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 144

## T

`tensor()` (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 146

`tensor_from_comp()` (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 147

`tensor_module()` (sage.tensor.modules.finite\_rank\_free\_module.FiniteRankFreeModule method), 147

`tensor_product()` (sage.modules.free\_module\_element.FreeModuleElement method), 99

`test_morphism_0()` (in module sage.modules.fg\_pid.fgp\_module), 216

`trace()` (sage.modules.matrix\_morphism.MatrixMorphism\_abstract method), 202

`TriangularModuleMorphism` (class in sage.modules.with\_basis.morphism), 234

`TriangularModuleMorphismByLinearity` (class in sage.modules.with\_basis.morphism), 241

`TriangularModuleMorphismFromFunction` (class in sage.modules.with\_basis.morphism), 241

`trig_expand()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 292

`trig_reduce()` (sage.modules.vector\_symbolic\_dense.Vector\_symbolic\_dense method), 293

## U

unpickle\_v0() (in module sage.modules.vector\_complex\_double\_dense), 269  
 unpickle\_v0() (in module sage.modules.vector\_integer\_dense), 278  
 unpickle\_v0() (in module sage.modules.vector\_mod2\_dense), 280  
 unpickle\_v0() (in module sage.modules.vector\_modn\_dense), 282  
 unpickle\_v0() (in module sage.modules.vector\_rational\_dense), 284  
 unpickle\_v0() (in module sage.modules.vector\_real\_double\_dense), 285  
 unpickle\_v1() (in module sage.modules.vector\_complex\_double\_dense), 269  
 unpickle\_v1() (in module sage.modules.vector\_integer\_dense), 278  
 unpickle\_v1() (in module sage.modules.vector\_modn\_dense), 282  
 unpickle\_v1() (in module sage.modules.vector\_rational\_dense), 284  
 unpickle\_v1() (in module sage.modules.vector\_real\_double\_dense), 285  
 update\_reduced\_basis() (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 66  
 user\_to\_echelon\_matrix() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 55  
 uses\_ambient\_inner\_product() (sage.modules.free\_module.FreeModule\_generic method), 27

## V

V() (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 207  
 V() (sage.modules.quotient\_module.FreeModule\_ambient\_field\_quotient method), 266  
 variance() (sage.modules.vector\_double\_dense.Vector\_double\_dense method), 276  
 vector() (in module sage.modules.free\_module\_element), 111  
 vector() (sage.modules.fg\_pid.fgp\_element.FGP\_Element method), 218  
 Vector\_callable\_symbolic\_dense (class in sage.modules.vector\_callable\_symbolic\_dense), 155  
 Vector\_complex\_double\_dense (class in sage.modules.vector\_complex\_double\_dense), 269  
 Vector\_double\_dense (class in sage.modules.vector\_double\_dense), 271  
 Vector\_integer\_dense (class in sage.modules.vector\_integer\_dense), 277  
 Vector\_mod2\_dense (class in sage.modules.vector\_mod2\_dense), 279  
 Vector\_modn\_dense (class in sage.modules.vector\_modn\_dense), 282  
 Vector\_rational\_dense (class in sage.modules.vector\_rational\_dense), 283  
 Vector\_real\_double\_dense (class in sage.modules.vector\_real\_double\_dense), 285  
 vector\_space() (sage.modules.free\_module.FreeModule\_ambient\_domain method), 14  
 vector\_space() (sage.modules.free\_module.FreeModule\_generic\_field method), 37  
 vector\_space() (sage.modules.free\_module.FreeModule\_submodule\_with\_basis\_pid method), 56  
 vector\_space\_span() (sage.modules.free\_module.FreeModule\_generic\_pid method), 44  
 vector\_space\_span\_of\_basis() (sage.modules.free\_module.FreeModule\_generic\_pid method), 45  
 Vector\_symbolic\_dense (class in sage.modules.vector\_symbolic\_dense), 287  
 VectorSpace() (in module sage.modules.free\_module), 56  
 VectorSpaceHomspace (class in sage.modules.vector\_space\_homspace), 159  
 VectorSpaceMorphism (class in sage.modules.vector\_space\_morphism), 166  
 volume() (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 66  
 voronoi\_cell() (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 66  
 voronoi\_relevant\_vectors() (sage.modules.free\_module\_integer.FreeModule\_submodule\_with\_basis\_integer method), 67

## W

W() (sage.modules.fg\_pid.fgp\_module.FGP\_Module\_class method), 207  
 W() (sage.modules.quotient\_module.FreeModule\_ambient\_field\_quotient method), 266

## Z

`zero()` (`sage.modules.free_module.FreeModule_generic` method), [27](#)  
`zero()` (`sage.modules.free_module_homspace.FreeModuleHomspace` method), [177](#)  
`zero()` (`sage.tensor.modules.finite_rank_free_module.FiniteRankFreeModule` method), [148](#)  
`zero_at()` (`sage.modules.vector_double_dense.Vector_double_dense` method), [276](#)  
`zero_submodule()` (`sage.modules.free_module.FreeModule_generic_field` method), [37](#)  
`zero_submodule()` (`sage.modules.free_module.FreeModule_generic_pid` method), [45](#)  
`zero_submodule()` (`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid` method), [258](#)  
`zero_subspace()` (`sage.modules.free_module.FreeModule_generic_field` method), [37](#)  
`zero_vector()` (in module `sage.modules.free_module_element`), [116](#)  
`zero_vector()` (`sage.modules.free_module.FreeModule_generic` method), [27](#)