

---

# **Sage Reference Manual: Coding Theory**

***Release 7.2***

**The Sage Development Team**

May 15, 2016



<b>1</b>	<b>Abstract classes, catalogs and databases</b>	<b>1</b>
1.1	Decoder . . . . .	1
1.2	Encoder . . . . .	3
1.3	Index of bounds . . . . .	7
1.4	Index of channels . . . . .	7
1.5	Index of codes . . . . .	8
1.6	Index of decoders . . . . .	10
1.7	Index of encoders . . . . .	10
1.8	Database of two-weight codes . . . . .	10
<b>2</b>	<b>Linear codes and related constructions</b>	<b>13</b>
2.1	Fast binary code routines . . . . .	13
2.2	Generalized Reed-Solomon code . . . . .	22
2.3	Hamming Code . . . . .	37
2.4	Guruswami-Sudan decoder for Generalized Reed-Solomon codes . . . . .	38
2.5	Interpolation algorithms for the Guruswami-Sudan decoder . . . . .	45
2.6	Finding $F[x]$ -roots for polynomials over $F[x][y]$ , with ' $F$ ' is a (finite) field, as used in the Guruswami-Sudan decoding. . . . .	48
2.7	Guruswami-Sudan utility methods . . . . .	49
2.8	Linear code . . . . .	51
2.9	Linear code constructions . . . . .	93
2.10	Binary self-dual codes . . . . .	107
2.11	Guava error-correcting code constructions . . . . .	109
<b>3</b>	<b>Bounds on codes</b>	<b>113</b>
3.1	Bounds for Parameters of Codes . . . . .	113
3.2	Delsarte, a.k.a. Linear Programming (LP), upper bounds . . . . .	119
<b>4</b>	<b>Channels and related constructions</b>	<b>125</b>
4.1	Channels . . . . .	125
<b>5</b>	<b>Source coding</b>	<b>133</b>
5.1	Huffman Encoding . . . . .	133
<b>6</b>	<b>Canonical forms</b>	<b>139</b>
6.1	Canonical forms and automorphism group computation for linear codes over finite fields . . . . .	139
6.2	Canonical forms and automorphisms for linear codes over finite fields . . . . .	146
<b>7</b>	<b>Indices and Tables</b>	<b>151</b>
	<b>Bibliography</b>	<b>153</b>



## ABSTRACT CLASSES, CATALOGS AND DATABASES

### 1.1 Decoder

Representation of an error-correction algorithm for a code.

AUTHORS:

- David Joyner (2009-02-01): initial version
- David Lucas (2015-06-29): abstract class version

**class** `sage.coding.decoder.Decoder` (*code*, *input\_space*, *connected\_encoder\_name*)

Bases: `sage.structure.sage_object.SageObject`

Abstract top-class for *Decoder* objects.

Every decoder class should inherit from this abstract class.

To implement an decoder, you need to:

- inherit from *Decoder*
- call `Decoder.__init__` in the subclass constructor. Example: `super(SubclassName, self).__init__(code, input_space, connected_encoder_name)`. By doing that, your subclass will have all the parameters described above initialized.
- Then, you need to override one of decoding methods, either `decode_to_code()` or `decode_to_message()`. You can also override the optional method `decoding_radius()`.
- By default, comparison of *Decoder* (using methods `__eq__` and `__ne__`) are by memory reference: if you build the same decoder twice, they will be different. If you need something more clever, override `__eq__` and `__ne__` in your subclass.
- As *Decoder* is not designed to be instantiated, it does not have any representation methods. You should implement `__repr__` and `__latex__` methods in the subclass.

**code()**

Returns the code for this *Decoder*.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: D = C.decoder()
sage: D.code()
Linear code of length 7, dimension 4 over Finite Field of size 2
```

**connected\_encoder()**

Returns the connected encoder of `self`.

## EXAMPLES:

```

sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: D = C.decoder()
sage: D.connected_encoder()
Generator matrix-based encoder for Linear code of length 7, dimension 4 over Finite Field of

```

**decode\_to\_code(r)**

Corrects the errors in `r` and returns a codeword.

This is a default implementation which assumes that the method `decode_to_message()` has been implemented, else it returns an exception.

## INPUT:

- `r` – a element of the input space of `self`.

## OUTPUT:

- a vector of `code()`.

## EXAMPLES:

```

sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: word = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
sage: word in C
True
sage: w_err = word + vector(GF(2), (1, 0, 0, 0, 0, 0, 0))
sage: w_err in C
False
sage: D = C.decoder()
sage: D.decode_to_code(w_err)
(1, 1, 0, 0, 1, 1, 0)

```

**decode\_to\_message(r)**

Decodes `r` to the message space of `meth:connected_encoder`.

This is a default implementation, which assumes that the method `decode_to_code()` has been implemented, else it returns an exception.

## INPUT:

- `r` – a element of the input space of `self`.

## OUTPUT:

- a vector of `message_space()`.

## EXAMPLES:

```

sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: word = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
sage: w_err = word + vector(GF(2), (1, 0, 0, 0, 0, 0, 0))
sage: D = C.decoder()
sage: D.decode_to_message(w_err)
(0, 1, 1, 0)

```

**decoder\_type()**

Returns the set of types of `self`. These types describe the nature of `self` and its decoding algorithm.

## EXAMPLES:

```
sage: G = Matrix(GF(2), [[1, 0, 0, 1], [0, 1, 1, 1]])
sage: C = LinearCode(G)
sage: D = C.decoder()
sage: D.decoder_type()
{'complete', 'hard-decision', 'might-error', 'unique'}
```

**decoding\_radius** (\*\*kwargs)

Returns the maximal number of errors that `self` is able to correct.

This is an abstract method and it should be implemented in subclasses.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeSyndromeDecoder(C)
sage: D.decoding_radius()
1
```

**input\_space**()

Returns the input space of `self`.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: D = C.decoder()
sage: D.input_space()
Vector space of dimension 7 over Finite Field of size 2
```

**message\_space**()

Returns the message space of `self`'s `connected_encoder()`.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: D = C.decoder()
sage: D.message_space()
Vector space of dimension 4 over Finite Field of size 2
```

**exception** `sage.coding.decoder.DecodingError`

Bases: `exceptions.Exception`

Special exception class to indicate an error during decoding.

## 1.2 Encoder

Representation of a bijection between a message space and a code.

**class** `sage.coding.encoder.Encoder` (*code*)

Bases: `sage.structure.sage_object.SageObject`

Abstract top-class for *Encoder* objects.

Every encoder class should inherit from this abstract class.

To implement an encoder, you need to:

- inherit from *Encoder*,

- call `Encoder.__init__` in the subclass constructor. Example: `super(SubclassName, self).__init__(code)`. By doing that, your subclass will have its `code` parameter initialized.
- Then, if the message space is a vector space, default implementations of `encode()` and `unencode_nocheck()` methods are provided. These implementations rely on `generator_matrix()` which you need to override to use the default implementations.
- If the message space is not of the form  $F^k$ , where  $F$  is a finite field, you cannot have a generator matrix. In that case, you need to override `encode()`, `unencode_nocheck()` and `message_space()`.
- By default, comparison of `Encoder` (using methods `__eq__` and `__ne__`) are by memory reference: if you build the same encoder twice, they will be different. If you need something more clever, override `__eq__` and `__ne__` in your subclass.
- As `Encoder` is not designed to be instantiated, it does not have any representation methods. You should implement `_repr_` and `_latex_` methods in the subclass.

## REFERENCES:

`code()`

Returns the code for this `Encoder`.

## EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: E = C.encoder()
sage: E.code() == C
True
```

`encode(word)`

Transforms an element of the message space into a codeword.

This is a default implementation which assumes that the message space of the encoder is  $F^k$ , where  $F$  is `sage.coding.linear_code.AbstractLinearCode.base_field()` and  $k$  is `sage.coding.linear_code.AbstractLinearCode.dimension()`. If this is not the case, this method should be overwritten by the subclass.

---

**Note:** `encode()` might be a partial function over `self`'s `message_space()`. One should use the exception `EncodingError` to catch attempts to encode words that are outside of the message space.

---

## INPUT:

- word – a vector of the message space of the `self`.

## OUTPUT:

- a vector of `code()`.

## EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: word = vector(GF(2), (0, 1, 1, 0))
sage: E = codes.encoders.LinearCodeGeneratorMatrixEncoder(C)
sage: E.encode(word)
(1, 1, 0, 0, 1, 1, 0)
```

If `word` is not in the message space of `self`, it will return an exception:

```
sage: word = random_vector(GF(7), 4)
sage: E.encode(word)
```



```
Traceback (most recent call last):
```

```
...
```

```
ValueError: The value to encode must be in Vector space of dimension 4 over Finite Field of
```

### **generator\_matrix()**

Returns a generator matrix of the associated code of `self`.

This is an abstract method and it should be implemented separately. Reimplementing this for each subclass of `Encoder` is not mandatory (as a generator matrix only makes sense when the message space is of the  $F^k$ , where  $F$  is the base field of `code()`).

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: E = C.encoder()
sage: E.generator_matrix()
[1 1 1 0 0 0 0]
[1 0 0 1 1 0 0]
[0 1 0 1 0 1 0]
[1 1 0 1 0 0 1]
```

### **message\_space()**

Returns the ambient space of allowed input to `encode()`. Note that `encode()` is possibly a partial function over the ambient space.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: E = C.encoder()
sage: E.message_space()
Vector space of dimension 4 over Finite Field of size 2
```

### **unencode(c, nocheck=False)**

Returns the message corresponding to the codeword `c`.

This is the inverse of `encode()`.

INPUT:

- `c` – a codeword of `code()`.
- `nocheck` – (default: `False`) checks if `c` is in `code()`. You might set this to `True` to disable the check for saving computation. Note that if `c` is not in `self()` and `nocheck = True`, then the output of `unencode()` is not defined (except that it will be in the message space of `self`).

OUTPUT:

- an element of the message space of `self`

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: c = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
sage: c in C
True
sage: E = codes.encoders.LinearCodeGeneratorMatrixEncoder(C)
sage: E.unencode(c)
(0, 1, 1, 0)
```

## TESTS:

If `nocheck` is set to `False`, and one provides a word which is not in `code()`, `unencode()` will return an error:

```
sage: c = vector(GF(2), (0, 1, 0, 0, 1, 1, 0))
sage: c in C
False
sage: E.unencode(c, False)
Traceback (most recent call last):
...
EncodingError: Given word is not in the code
```

If ones tries to unencode a codeword of a code of dimension 0, it returns the empty vector:

```
sage: G = Matrix(GF(17), [])
sage: C = LinearCode(G)
sage: E = codes.encoders.LinearCodeGeneratorMatrixEncoder(C)
sage: c = C.random_element()
sage: E.unencode(c)
()
```

**unencode\_nocheck(c)**

Returns the message corresponding to `c`.

When `c` is not a codeword, the output is unspecified.

## AUTHORS:

This function is taken from `codinglib` [Nielsen]

## INPUT:

- `c` – a codeword of `code()`.

## OUTPUT:

- an element of the message space of `self`.

## EXAMPLES:

```
sage: G = Matrix(GF(2), [[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: c = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
sage: c in C
True
sage: E = codes.encoders.LinearCodeGeneratorMatrixEncoder(C)
sage: E.unencode_nocheck(c)
(0, 1, 1, 0)
```

Taking a vector that does not belong to `C` will not raise an error but probably just give a non-sensical result:

```
sage: c = vector(GF(2), (1, 1, 0, 0, 1, 1, 1))
sage: c in C
False
sage: E = codes.encoders.LinearCodeGeneratorMatrixEncoder(C)
sage: E.unencode_nocheck(c)
(0, 1, 1, 0)
sage: m = vector(GF(2), (0, 1, 1, 0))
sage: c1 = E.encode(m)
sage: c == c1
False
```

**exception** `sage.coding.encoder.EncodingError`

Bases: `exceptions.Exception`

Special exception class to indicate an error during encoding or unencoding.

## 1.3 Index of bounds

The `codes.bounds` object may be used to access the bounds that Sage can compute.

<code>codesize_upper_bound()</code>	This computes the minimum value of the upper bound using the methods of Singleton, Hamming, Plotkin, and Elias.
<code>dimension_upper_bound()</code>	Returns an upper bound $B(n, d) = B_q(n, d)$ for the dimension of a linear code of length $n$ , minimum distance $d$ over a field of size $q$ . Parameter “algorithm” has the same meaning as in <code>codesize_upper_bound()</code>
<code>elias_bound_asymptotic()</code>	Computes the asymptotic Elias bound for the information rate, provided $0 < \delta < 1 - 1/q$ .
<code>elias_upper_bound()</code>	Returns the Elias upper bound for number of elements in the largest code of minimum distance $d$ in $F_q^n$ . Wraps GAP’s <code>UpperBoundElias</code> .
<code>entropy()</code>	Computes the entropy at $x$ on the $q$ -ary symmetric channel.
<code>gilbert_lower_bound()</code>	Returns lower bound for number of elements in the largest code of minimum distance $d$ in $F_q^n$ .
<code>griesmer_upper_bound()</code>	Returns the Griesmer upper bound for number of elements in the largest code of minimum distance $d$ in $F_q^n$ . Wraps GAP’s <code>UpperBoundGriesmer</code> .
<code>gv_bound_asymptotic()</code>	Computes the asymptotic GV bound for the information rate, $R$ .
<code>gv_info_rate()</code>	GV lower bound for information rate of a $q$ -ary code of length $n$ minimum distance $\delta n$
<code>hamming_bound_asymptotic()</code>	Computes the asymptotic Hamming bound for the information rate.
<code>hamming_upper_bound()</code>	Returns the Hamming upper bound for number of elements in the largest code of minimum distance $d$ in $F_q^n$ . Wraps GAP’s <code>UpperBoundHamming</code> .
<code>mrrwl_bound_asymptotic()</code>	Computes the first asymptotic McEliece-Rumsey-Rodemich-Welsh bound for the information rate, provided $0 < \delta < 1 - 1/q$ .
<code>plotkin_bound_asymptotic()</code>	Computes the asymptotic Plotkin bound for the information rate, provided $0 < \delta < 1 - 1/q$ .
<code>plotkin_upper_bound()</code>	Returns Plotkin upper bound for number of elements in the largest code of minimum distance $d$ in $F_q^n$ .
<code>singleton_bound_asymptotic()</code>	Computes the asymptotic Singleton bound for the information rate.
<code>singleton_upper_bound()</code>	Returns the Singleton upper bound for number of elements in the largest code of minimum distance $d$ in $F_q^n$ . Wraps GAP’s <code>UpperBoundSingleton</code> .
<code>volume_hamming_bound()</code>	Returns number of elements in a Hamming ball of radius $r$ in $F_q^n$ . Agrees with Guava’s <code>SphereContent(n,r,GF(q))</code> .

**Note:** To import these names into the global namespace, use:

```
sage: from sage.coding.bounds_catalog import *
```

## 1.4 Index of channels

The `channels` object may be used to access the codes that Sage can build.

- `channel_constructions.ErrorErasureChannel`
- `channel_constructions.StaticErrorRateChannel`
- `channel_constructions.QarySymmetricChannel`

---

**Note:** To import these names into the global namespace, use:

```
sage: from sage.coding.channels_catalog import *
```

---

## 1.5 Index of codes

The `codes` object may be used to access the codes that Sage can build.

<code>BCHCode()</code>	A ‘Bose-Chaudhuri-Hockenghem code’ (or BCH code for short) is the largest possible cyclic code of length $n$ over field $F=GF(q)$ , whose generator polynomial has zeros (which contain the set) $Z = \{a^b, a^{b+1}, \dots, a^{b+\text{delta}-2}\}$ , where $a$ is a primitive $n^{\text{th}}$ root of unity in the splitting field $GF(q^m)$ , $b$ is an integer $0 \leq b \leq n - \text{delta} + 1$ and $m$ is the multiplicative order of $q$ modulo $n$ . (The integers $b, \dots, b + \text{delta} - 2$ typically lie in the range $1, \dots, n - 1$ .) The integer $\text{delta} \geq 1$ is called the “designed distance”. The length $n$ of the code and the size $q$ of the base field must be relatively prime. The generator polynomial is equal to the least common multiple of the minimal polynomials of the elements of the set $Z$ above.
<code>BinaryGolayCode()</code>	<code>BinaryGolayCode()</code> returns a binary Golay code. This is a perfect $[23,12,7]$ code. It is also (equivalent to) a cyclic code, with generator polynomial $g(x) = 1 + x^2 + x^4 + x^5 + x^6 + x^{10} + x^{11}$ . Extending it yields the extended Golay code (see <code>ExtendedBinaryGolayCode</code> ).
<code>BinaryReedMullerCode()</code>	The binary ‘Reed-Muller code’ with dimension $k$ and order $r$ is a code with length $2^k$ and minimum distance $2^k - r$ (see for example, section 1.10 in <a href="#">[HP]</a> ). By definition, the $r^{\text{th}}$ order binary Reed-Muller code of length $n = 2^m$ , for $0 \leq r \leq m$ , is the set of all vectors $(f(p) \mid p \in GF(2)^m)$ , where $f$ is a multivariate polynomial of degree at most $r$ in $m$ variables.
<code>CyclicCode()</code>	If $g$ is a polynomial over $GF(q)$ which divides $x^n - 1$ then this constructs the code “generated by $g$ ” (ie, the code associated with the principle ideal $gR$ in the ring $R = GF(q)[x]/(x^n - 1)$ in the usual way).
<code>CyclicCodeFromCheckPolynomial()</code>	If $h$ is a polynomial over $GF(q)$ which divides $x^n - 1$ then this constructs the code “generated by $g = (x^n - 1)/h$ ” (ie, the code associated with the principle ideal $gR$ in the ring $R = GF(q)[x]/(x^n - 1)$ in the usual way). The option “ignore” says to ignore the condition that the characteristic of the base field does not divide the length (the usual assumption in the theory of cyclic codes).
<code>DuadicCodeEvenPair()</code>	Constructs the “even pair” of duadic codes associated to the “splitting” (see the docstring for <code>is_a_splitting</code> for the definition) $S_1, S_2$ of $n$ .
<code>DuadicCodeOddPair()</code>	Constructs the “odd pair” of duadic codes associated to the “splitting” $S_1, S_2$ of $n$ .
<code>ExtendedBinaryGolayCode()</code>	<code>ExtendedBinaryGolayCode()</code> returns the extended binary Golay code. This is a perfect $[24,12,8]$ code. This code is self-dual.
<code>ExtendedQuadraticResidueCode()</code>	The extended quadratic residue code (or XQR code) is obtained from a QR code by adding a check bit to the last coordinate. (These codes have very remarkable properties such as large automorphism groups and duality properties - see <a href="#">[HP]</a> , Section 6.6.3-6.6.4.)
<code>ExtendedTernaryGolayCode()</code>	<code>ExtendedTernaryGolayCode</code> returns a ternary Golay code. This is a self-dual perfect $[12,6,6]$ code.
<code>LinearCodeFromCheckMatrix()</code>	A linear $[n,k]$ -code $C$ is uniquely determined by its generator matrix $G$ and check matrix $H$ . We have the following short exact sequence
<code>QuadraticResidueCode()</code>	A quadratic residue code (or QR code) is a cyclic code whose generator polynomial is the product of the polynomials $x - \alpha^i$ ( $\alpha$ is a primitive $n^{\text{th}}$ root of unity; $i$ ranges over the set of quadratic residues modulo $n$ ).
<code>QuadraticResidueCodes()</code>	Quadratic residue codes of a given odd prime length and base ring either don’t exist at all or occur as 4-tuples - a pair of “odd-like” codes and a pair of “even-like” codes. If $n > 2$ is prime then (Theorem 6.6.2 in <a href="#">[HP]</a> ) a QR code exists over $GF(q)$ iff $q$ is a quadratic residue mod $n$ .
<code>QuadraticResidueCodesList()</code>	Quadratic residue codes of a given odd prime length and base ring either don’t exist at all or occur as 4-tuples - a pair of “odd-like” codes and a pair of “even-like” codes. If $n > 2$ is prime then (Theorem 6.6.2 in <a href="#">[HP]</a> ) a QR code exists over $GF(q)$ iff $q$ is a quadratic residue mod $n$ .
<code>QuasiQuadraticResidueCode()</code>	A (binary) quasi-quadratic residue code (or QQR code), as defined by Proposition 2.2 in <a href="#">[BM]</a> , has a generator matrix in the block form $G = (Q, N)$ . Here $Q$ is a $p \times p$ circulant matrix whose top row is $(0, x_1, \dots, x_{p-1})$ , where $x_i = 1$ if and only if $i$ is a quadratic residue mod $p$ , and $N$ is a $p \times p$ circulant matrix whose top row is $(0, y_1, \dots, y_{p-1})$ , where $x_i + y_i = 1$ for all $i$ .
<code>RandomLinearCode()</code>	The method used is to first construct a $k \times n$ matrix using Sage’s <code>random_element</code> method for the <code>MatrixSpace</code> class. The construction is probabilistic but should only fail extremely rarely.
<code>RandomLinearCodeGuerrero()</code>	The method used is to first construct a $k \times n$ matrix of the block form $(I, A)$ , where $I$ is a $k \times k$ identity matrix and $A$ is a $k \times (n - k)$ matrix constructed using random

---

**Note:** To import these names into the global namespace, use:

```
sage: from sage.coding.codes_catalog import *
```

---

## 1.6 Index of decoders

The `codes.decoders` object may be used to access the decoders that Sage can build.

### Generic decoders

- `linear_code.LinearCodeSyndromeDecoder`
- `linear_code.LinearCodeNearestNeighborDecoder`

### Generalized Reed-Solomon code decoders

- `grs.GRSBerlekampWelchDecoder`
- `grs.GRSErrorErasureDecoder`
- `grs.GRSGaoDecoder`
- `grs.GRSKeyEquationSyndromeDecoder`
- `guruswami_sudan.gs_decoder.GRSGuruswamiSudanDecoder`

---

**Note:** To import these names into the global namespace, use:

```
sage: from sage.coding.decoders_catalog import *
```

---

## 1.7 Index of encoders

The `codes.encoders` object may be used to access the encoders that Sage can build.

### Generic encoders

`linear_code.LinearCodeGeneratorMatrixEncoder` `linear_code.LinearCodeParityCheckEncoder`

### Generalized Reed-Solomon code encoders

- `grs.GRSEvaluationVectorEncoder`
- `grs.GRSEvaluationPolynomialEncoder`

---

**Note:** To import these names into the global namespace, use:

```
sage: from sage.coding.encoders_catalog import *
```

---

## 1.8 Database of two-weight codes

This module stores a database of two-weight codes.

$q = 2$	$n = 68$	$k = 8$	$w_1 = 32$	$w_2 = 40$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 2$	$n = 85$	$k = 8$	$w_1 = 40$	$w_2 = 48$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 2$	$n = 70$	$k = 9$	$w_1 = 32$	$w_2 = 40$	Found by Axel Kohnert <a href="#">[Kohnert07]</a> and shared by Alfred Wassermann.
$q = 2$	$n = 73$	$k = 9$	$w_1 = 32$	$w_2 = 40$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 2$	$n = 219$	$k = 9$	$w_1 = 96$	$w_2 = 112$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 2$	$n = 198$	$k = 10$	$w_1 = 96$	$w_2 = 112$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 15$	$k = 4$	$w_1 = 9$	$w_2 = 12$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 55$	$k = 5$	$w_1 = 36$	$w_2 = 45$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 56$	$k = 6$	$w_1 = 36$	$w_2 = 45$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 84$	$k = 6$	$w_1 = 54$	$w_2 = 63$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 98$	$k = 6$	$w_1 = 63$	$w_2 = 72$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 126$	$k = 6$	$w_1 = 81$	$w_2 = 90$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 140$	$k = 6$	$w_1 = 90$	$w_2 = 99$	Found by Axel Kohnert <a href="#">[Kohnert07]</a> and shared by Alfred Wassermann.
$q = 3$	$n = 154$	$k = 6$	$w_1 = 99$	$w_2 = 108$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 3$	$n = 168$	$k = 6$	$w_1 = 108$	$w_2 = 117$	From <a href="#">[Disset00]</a>
$q = 4$	$n = 34$	$k = 4$	$w_1 = 24$	$w_2 = 28$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 4$	$n = 121$	$k = 5$	$w_1 = 88$	$w_2 = 96$	From <a href="#">[Disset00]</a>
$q = 4$	$n = 132$	$k = 5$	$w_1 = 96$	$w_2 = 104$	From <a href="#">[Disset00]</a>
$q = 4$	$n = 143$	$k = 5$	$w_1 = 104$	$w_2 = 112$	From <a href="#">[Disset00]</a>
$q = 5$	$n = 39$	$k = 4$	$w_1 = 30$	$w_2 = 35$	From Bouyukliev and Simonis ( <a href="#">[BS03]</a> , Theorem 4.1)
$q = 5$	$n = 52$	$k = 4$	$w_1 = 40$	$w_2 = 45$	Shared by Eric Chen <a href="#">[ChenDB]</a> .
$q = 5$	$n = 65$	$k = 4$	$w_1 = 50$	$w_2 = 55$	Shared by Eric Chen <a href="#">[ChenDB]</a> .

REFERENCE:

TESTS:

Check the data's consistency:

```
sage: from sage.coding.two_weight_db import data
sage: for code in data:
....:     M = code['M']
....:     assert code['n'] == M.ncols()
```

```
....:     assert code['k'] == M.nrows()
....:     w1,w2 = [w for w,f in enumerate(LinearCode(M).weight_distribution()) if w and f]
....:     assert (code['w1'], code['w2']) == (w1, w2)
```



## LINEAR CODES AND RELATED CONSTRUCTIONS

### 2.1 Fast binary code routines

Some computations with linear binary codes. Fix a basis for  $GF(2)^n$ . A linear binary code is a linear subspace of  $GF(2)^n$ , together with this choice of basis. A permutation  $g \in S_n$  of the fixed basis gives rise to a permutation of the vectors, or words, in  $GF(2)^n$ , sending  $(w_i)$  to  $(w_{g(i)})$ . The permutation automorphism group of the code  $C$  is the set of permutations of the basis that bijectively map  $C$  to itself. Note that if  $g$  is such a permutation, then

$$g(a_i) + g(b_i) = (a_{g(i)} + b_{g(i)}) = g((a_i) + (b_i)).$$

Over other fields, it is also required that the map be linear, which as per above boils down to scalar multiplication. However, over  $GF(2)$ , the only scalars are 0 and 1, so the linearity condition has trivial effect.

AUTHOR:

- Robert L Miller (Oct-Nov 2007)
- compiled code data structure
- union-find based orbit partition
- optimized partition stack class
- NICE-based partition refinement algorithm
- canonical generation function

**class** `sage.coding.binary_code.BinaryCode`

Bases: object

Minimal, but optimized, binary code object.

EXAMPLE:

```
sage: import sage.coding.binary_code
sage: from sage.coding.binary_code import *
sage: M = Matrix(GF(2), [[1,1,1,1]])
sage: B = BinaryCode(M)           # create from matrix
sage: C = BinaryCode(B, 60)      # create using glue
sage: D = BinaryCode(C, 240)
sage: E = BinaryCode(D, 85)
sage: B
Binary [4,1] linear code, generator matrix
[1111]
sage: C
Binary [6,2] linear code, generator matrix
[111100]
[001111]
```

```

sage: D
Binary [8,3] linear code, generator matrix
[11110000]
[00111100]
[00001111]
sage: E
Binary [8,4] linear code, generator matrix
[11110000]
[00111100]
[00001111]
[10101010]

sage: M = Matrix(GF(2), [[1]*32])
sage: B = BinaryCode(M)
sage: B
Binary [32,1] linear code, generator matrix
[11111111111111111111111111111111]

```

**apply\_permutation** (*labeling*)

Apply a column permutation to the code.

INPUT:

- *labeling* – a list permutation of the columns

EXAMPLE:

```

sage: from sage.coding.binary_code import *
sage: B = BinaryCode(codes.ExtendedBinaryGolayCode().generator_matrix())
sage: B
Binary [24,12] linear code, generator matrix
[100000000000101011100011]
[010000000000111110010010]
[001000000000110100101011]
[000100000000110001110110]
[000010000000110011011001]
[000001000000011001101101]
[000000100000001100110111]
[0000000100000101101111000]
[000000001000010110111100]
[000000000100001011011110]
[000000000010000101101111]
[000000000001000010110111]
[000000000000100001011011]
[000000000000010000101101]
[000000000000001000010110]
[000000000000000100001011]
[000000000000000010000101]
[000000000000000001000010]
[000000000000000000100001]
[000000000000000000010000]
[000000000000000000001000]
[000000000000000000000100]
[000000000000000000000010]
[000000000000000000000001]
[000000000000000000000000]
sage: B.apply_permutation(range(11,-1,-1) + range(12, 24))
sage: B
Binary [24,12] linear code, generator matrix
[0000000000001101011100011]
[0000000000010111110010010]
[0000000000100110100101011]
[0000000001000110001110110]
[0000000010000110011011001]
[0000000100000011001101101]
[000000100000001100110111]
[000010000000101101111000]
[00010000000010110111100]
[00100000000010110111110]
[010000000000101110001101]
[10000000000010111000111]

```

**matrix()**

Returns the generator matrix of the BinaryCode, i.e. the code is the rowspace of B.matrix().

EXAMPLE:

```
sage: M = Matrix(GF(2), [[1,1,1,1,0,0],[0,0,1,1,1,1]])
sage: from sage.coding.binary_code import *
sage: B = BinaryCode(M)
sage: B.matrix()
[1 1 1 1 0 0]
[0 0 1 1 1 1]
```

**print\_data()**

Print all data for self.

EXAMPLES:

```
sage: import sage.coding.binary_code
sage: from sage.coding.binary_code import *
sage: M = Matrix(GF(2), [[1,1,1,1]])
sage: B = BinaryCode(M)
sage: C = BinaryCode(B, 60)
sage: D = BinaryCode(C, 240)
sage: E = BinaryCode(D, 85)
sage: B.print_data() # random - actually "print P.print_data()"
ncols: 4
nrows: 1
nwords: 2
radix: 32
basis:
1111
words:
0000
1111
sage: C.print_data() # random - actually "print P.print_data()"
ncols: 6
nrows: 2
nwords: 4
radix: 32
basis:
111100
001111
words:
000000
111100
001111
110011
sage: D.print_data() # random - actually "print P.print_data()"
ncols: 8
nrows: 3
nwords: 8
radix: 32
basis:
11110000
00111100
00001111
words:
00000000
11110000
00111100
```

```
11001100
00001111
11111111
00110011
11000011
sage: E.print_data() # random - actually "print P.print_data()"
ncols: 8
nrows: 4
nwords: 16
radix: 32
basis:
11110000
00111100
00001111
10101010
words:
00000000
11110000
00111100
11001100
00001111
11111111
00110011
11000011
10101010
01011010
10010110
01100110
10100101
01010101
10011001
01101001
```

**put\_in\_std\_form()**

Put the code in binary form, which is defined by an identity matrix on the left, augmented by a matrix of data.

EXAMPLE:

```
sage: from sage.coding.binary_code import *
sage: M = Matrix(GF(2), [[1,1,1,1,0,0],[0,0,1,1,1,1]])
sage: B = BinaryCode(M); B
Binary [6,2] linear code, generator matrix
[111100]
[001111]
sage: B.put_in_std_form(); B
0
Binary [6,2] linear code, generator matrix
[101011]
[010111]
```

**class** sage.coding.binary\_code.**BinaryCodeClassifier**

Bases: object

**generate\_children**(*B*, *n*, *d*=2)

Use canonical augmentation to generate children of the code *B*.

INPUT:

- **B** – a `BinaryCode`
- **n** – limit on the degree of the code
- **d** – test whether new vector has weight divisible by **d**. If **d**==4, this ensures that all doubly-even canonically augmented children are generated.

EXAMPLE:

```
sage: from sage.coding.binary_code import *
sage: BC = BinaryCodeClassifier()
sage: B = BinaryCode(Matrix(GF(2), [[1,1,1,1]]))
sage: BC.generate_children(B, 6, 4)
[
[1 1 1 1 0 0]
[0 1 0 1 1 1]
]
```

---

**Note:** The function `self_orthogonal_binary_codes` makes heavy use of this function.

---

MORE EXAMPLES:

```
sage: soc_iter = self_orthogonal_binary_codes(12, 6, 4)
sage: L = list(soc_iter)
sage: for n in range(0, 13):
....:     s = 'n=%2d : %n'
....:     for k in range(1,7):
....:         s += '%3d %len([C for C in L if C.length() == n and C.dimension() == k])'
....:     print s
n= 0 :      0      0      0      0      0      0
n= 1 :      0      0      0      0      0      0
n= 2 :      0      0      0      0      0      0
n= 3 :      0      0      0      0      0      0
n= 4 :      1      0      0      0      0      0
n= 5 :      0      0      0      0      0      0
n= 6 :      0      1      0      0      0      0
n= 7 :      0      0      1      0      0      0
n= 8 :      1      1      1      1      0      0
n= 9 :      0      0      0      0      0      0
n=10 :      0      1      1      1      0      0
n=11 :      0      0      1      1      0      0
n=12 :      1      2      3      4      2      0
```

**put\_in\_canonical\_form(B)**

Puts the code into canonical form.

Canonical form is obtained by performing row reduction, permuting the pivots to the front so that the generator matrix is of the form: the identity matrix augmented to the right by arbitrary data.

EXAMPLE:

```
sage: from sage.coding.binary_code import *
sage: BC = BinaryCodeClassifier()
sage: B = BinaryCode(codes.ExtendedBinaryGolayCode().generator_matrix())
sage: B.apply_permutation(range(24,-1,-1))
sage: B
Binary [24,12] linear code, generator matrix
[011000111010100000000000]
[001001001111100000000001]
[011010100101100000000010]
```

```

[001101110001100000000100]
[010011011001100000001000]
[010110110011000000010000]
[011101100110000000100000]
[000011110110100001000000]
[000111101101000010000000]
[001111011010000100000000]
[010110001110101000000000]
[011100011101010000000000]
sage: BC.put_in_canonical_form(B)
sage: B
Binary [24,12] linear code, generator matrix
[1000000000000001100111001]
[0100000000000001010001111]
[0010000000000001111010010]
[0001000000000001011010101]
[0000100000000001011001010]
[00000100000000010001101101]
[00000010000000011000110110]
[00000001000000011111001001]
[00000000100000010101110011]
[000000000100010011011110]
[000000000010001011110101]
[000000000001001101110110]
[0000000000001001101101110]
[0000000000000100110110110]

```

**class** sage.coding.binary\_code.**OrbitPartition**

Bases: object

Structure which keeps track of which vertices are equivalent under the part of the automorphism group that has already been seen, during search. Essentially a disjoint-set data structure\*, which also keeps track of the minimum element and size of each cell of the partition, and the size of the partition.

•[http://en.wikipedia.org/wiki/Disjoint-set\\_data\\_structure](http://en.wikipedia.org/wiki/Disjoint-set_data_structure)

**class** sage.coding.binary\_code.**PartitionStack**

Bases: object

Partition stack structure for traversing the search tree during automorphism group computation.

**cmp** (*other*, *CG*)

EXAMPLES:

```

sage: import sage.coding.binary_code
sage: from sage.coding.binary_code import *
sage: M = Matrix(GF(2), [[1,1,1,1,0,0,0,0],[0,0,1,1,1,1,0,0],[0,0,0,0,1,1,1,1],[1,0,1,0,1,0,1,0],
sage: B = BinaryCode(M)
sage: P = PartitionStack(4, 8)
sage: P._refine(0, [[0,0],[1,0]], B)
181
sage: P._split_vertex(0, 1)
0
sage: P._refine(1, [[0,0]], B)
290
sage: P._split_vertex(1, 2)
1
sage: P._refine(2, [[0,1]], B)
463
sage: P._split_vertex(2, 3)
2
sage: P._refine(3, [[0,2]], B)

```

```

1500
sage: P._split_vertex(4, 4)
4
sage: P._refine(4, [[0,4]], B)
1224
sage: P._is_discrete(4)
1
sage: Q = PartitionStack(P)
sage: Q._clear(4)
sage: Q._split_vertex(5, 4)
4
sage: Q._refine(4, [[0,4]], B)
1224
sage: Q._is_discrete(4)
1
sage: Q.cmp(P, B)
0

```

**print\_basis()**

EXAMPLE:

```

sage: import sage.coding.binary_code
sage: from sage.coding.binary_code import *
sage: P = PartitionStack(4, 8)
sage: P._dangerous_dont_use_set_ents_lvls(range(8), range(7)+[-1], [4,7,12,11,1,9,3,0,2,5,6,10])
sage: P
({4},{7},{12},{11},{1},{9},{3},{0},{2},{5},{6},{8},{10},{13},{14},{15})  ({0},{1,2,3,4,5,6,7})
({4},{7},{12},{11},{1},{9},{3},{0},{2},{5},{6},{8},{10},{13},{14},{15})  ({0},{1},{2,3,4,5,6})
({4},{7},{12},{11},{1},{9},{3},{0},{2},{5},{6},{8},{10},{13},{14},{15})  ({0},{1},{2},{3,4,5,6,7})
({4},{7},{12},{11},{1},{9},{3},{0},{2},{5},{6},{8},{10},{13},{14},{15})  ({0},{1},{2},{3},{4,5,6,7})
({4},{7},{12},{11},{1},{9},{3},{0},{2},{5},{6},{8},{10},{13},{14},{15})  ({0},{1},{2},{3},{4},{5,6,7})
({4},{7},{12},{11},{1},{9},{3},{0},{2},{5},{6},{8},{10},{13},{14},{15})  ({0},{1},{2},{3},{4},{5},{6,7})
({4},{7},{12},{11},{1},{9},{3},{0},{2},{5},{6},{8},{10},{13},{14},{15})  ({0},{1},{2},{3},{4},{5},{6},{7})
sage: P._find_basis()
sage: P.print_basis()
basis_locations:
4
8
0
11

```

**print\_data()**

Prints all data for self.

EXAMPLE:

```

sage: import sage.coding.binary_code
sage: from sage.coding.binary_code import *
sage: P = PartitionStack(2, 6)
sage: print P.print_data()
nwords:4
nrows:2
ncols:6
radix:32
wd_ents:
0
1
2
3

```

```
wd_lvls:
12
12
12
-1
col_ents:
0
1
2
3
4
5
col_lvls:
12
12
12
12
12
-1
col_degs:
0
0
0
0
0
0
col_counts:
0
0
0
0
col_output:
0
0
0
0
0
0
wd_degs:
0
0
0
0
wd_counts:
0
0
0
0
0
0
0
0
wd_output:
0
0
0
0
```

```
sage.coding.binary_code.test_expand_to_ortho_basis(B=None)
```



This function is written in pure C for speed, and is tested from this function.

INPUT:

• **B** – a BinaryCode in standard form

OUTPUT:

An array of codewords which represent the expansion of a basis for  $B$  to a basis for  $(B')^\perp$ , where  $B' = B$  if the all-ones vector  $1$  is in  $B$ , otherwise  $B' = \text{extspan}(B, 1)$  (note that this guarantees that all the vectors in the span of the output have even weight).

TESTS:

```
sage: from sage.coding.binary_code import test_expand_to_ortho_basis, BinaryCode
sage: M = Matrix(GF(2), [[1,1,1,1,1,1,0,0,0,0],[0,0,1,1,1,1,1,1,1,1]])
sage: B = BinaryCode(M)
sage: B.put_in_std_form()
0
sage: test_expand_to_ortho_basis(B=B)
INPUT CODE:
Binary [10,2] linear code, generator matrix
[1010001111]
[0101111111]
Expanding to the basis of an orthogonal complement...
Basis:
0010000010
0001000010
0000100001
0000010001
0000001001
```

`sage.coding.binary_code.test_word_perms(t_limit=5.0)`

Tests the WordPermutation structs for at least `t_limit` seconds.

These are structures written in pure C for speed, and are tested from this function, which performs the following tests:

1. **Tests `create_word_perm`, which creates a WordPermutation from a Python** list  $L$  representing a permutation  $i \rightarrow L[i]$ . Takes a random word and permutes it by a random list permutation, and tests that the result agrees with doing it the slow way.
- 1b. **Tests `create_array_word_perm`, which creates a WordPermutation from a C array.** Does the same as above.
2. **Tests `create_comp_word_perm`, which creates a WordPermutation as a composition** of two WordPermutations. Takes a random word and two random permutations, and tests that the result of permuting by the composition is correct.
3. **Tests `create_inv_word_perm` and `create_id_word_perm`, which create a WordPermutation** as the inverse and identity permutations, resp. Takes a random word and a random permutation, and tests that the result permuting by the permutation and its inverse in either order, and permuting by the identity both return the original word.

---

**Note:** The functions `permute_word_by_wp` and `dealloc_word_perm` are implicitly involved in each of the above tests.

---

TESTS:

```
sage: from sage.coding.binary_code import test_word_perms
sage: test_word_perms() # long time (5s on sage.math, 2011)
```

`sage.coding.binary_code.weight_dist(M)`

Computes the weight distribution of the row space of M.

EXAMPLES:

```
sage: from sage.coding.binary_code import weight_dist
sage: M = Matrix(GF(2), [
.....: [1,1,1,1,1,1,1,1,0,0,0,0,0,0,0],
.....: [0,0,0,0,1,1,1,1,1,1,1,0,0,0,0],
.....: [0,0,0,0,0,0,0,0,1,1,1,1,1,1,1],
.....: [0,0,1,1,0,0,1,1,0,0,1,1,0,0,1,1],
.....: [0,1,0,1,0,1,0,1,0,1,0,1,0,1,0,1]])
sage: weight_dist(M)
[1, 0, 0, 0, 0, 0, 0, 0, 30, 0, 0, 0, 0, 0, 0, 1]
sage: M = Matrix(GF(2), [
.....: [1,1,1,1,1,1,1,1,0,0,0,0,0,0,0,0],
.....: [0,0,0,0,0,0,1,1,1,1,1,1,1,0,0,0],
.....: [0,0,0,0,0,1,0,1,0,0,0,1,1,1,1,1],
.....: [0,0,0,1,1,0,0,0,0,1,1,0,1,1,0,1]])
sage: weight_dist(M)
[1, 0, 0, 0, 0, 0, 0, 0, 11, 0, 0, 0, 4, 0, 0, 0]
sage: M=Matrix(GF(2), [
.....: [1,0,0,1,1,1,1,0,0,1,0,0,0,0,0,0],
.....: [0,1,0,0,1,1,1,1,0,0,1,0,0,0,0,0],
.....: [0,0,1,0,0,1,1,1,1,0,0,1,0,0,0,0],
.....: [0,0,0,1,0,0,1,1,1,1,0,0,1,0,0,0],
.....: [0,0,0,0,1,0,0,1,1,1,1,0,0,1,0,0],
.....: [0,0,0,0,0,1,0,0,1,1,1,1,0,0,1,0],
.....: [0,0,0,0,0,0,1,0,0,1,1,1,1,0,0,1],
.....: [0,0,0,0,0,0,0,1,0,0,1,1,1,1,0,0]])
sage: weight_dist(M)
[1, 0, 0, 0, 0, 0, 68, 0, 85, 0, 68, 0, 34, 0, 0, 0]
```

## 2.2 Generalized Reed-Solomon code

Given  $n$  different evaluation points  $\alpha_1, \dots, \alpha_n$  from some finite field  $F$ , and  $n$  column multipliers  $\beta_1, \dots, \beta_n$ , the corresponding GRS code of dimension  $k$  is the set:

$$\{(\beta_1 f(\alpha_1), \dots, \beta_n f(\alpha_n)) \mid f \in F[x], \deg f < k\}$$

This file contains the following elements:

- `GeneralizedReedSolomonCode`, the class for GRS codes
- `GRSEvaluationVectorEncoder`, an encoder with a vectorial message space
- `GRSEvaluationPolynomialEncoder`, an encoder with a polynomial message space
- `GRSBerlekampWelchDecoder`, a decoder which corrects errors using Berlekamp-Welch algorithm
- `GRSGaoDecoder`, a decoder which corrects errors using Gao algorithm
- `GRSErrorErasureDecoder`, a decoder which corrects both errors and erasures
- `GRSKeyEquationSyndromeDecoder`, a decoder which corrects errors using the key equation on syndrome polynomials

```
class sage.coding.grs.GRSBerlekampWelchDecoder (code)
```

Bases: `sage.coding.decoder.Decoder`

Decoder for Generalized Reed-Solomon codes which uses Berlekamp-Welch decoding algorithm to correct errors in codewords.

This algorithm recovers the error locator polynomial by solving a linear system. See [HJ04] pp. 51-52 for details.

REFERENCES:

INPUT:

- `code` – A code associated to this decoder

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSBerlekampWelchDecoder(C)
sage: D
Berlekamp-Welch decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

Actually, we can construct the decoder from `C` directly:

```
sage: D = C.decoder("BerlekampWelch")
sage: D
Berlekamp-Welch decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

```
decode_to_code(r)
```

Corrects the errors in `r` and returns a codeword.

---

**Note:** If the code associated to `self` has the same length as its dimension, `r` will be returned as is.

---

INPUT:

- `r` – a vector of the ambient space of `self.code()`

OUTPUT:

- a vector of `self.code()`

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSBerlekampWelchDecoder(C)
sage: c = C.random_element()
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), D.decoding_radius())
sage: y = Chan(c)
sage: c == D.decode_to_code(y)
True
```

TESTS:

If one tries to decode a word which is too far from any codeword, an exception is raised:

```
sage: e = vector(F, [0, 0, 54, 23, 1, 0, 0, 0, 53, 21, 0, 0, 0, 34, 6, 11, 0, 0, 16, 0, 0, 0, 15])
sage: D.decode_to_code(c + e)
Traceback (most recent call last):
```

```
...
DecodingError: Decoding failed because the number of errors exceeded the decoding radius
```

If one tries to decode something which is not in the ambient space of the code, an exception is raised:

```
sage: D.decode_to_code(42)
Traceback (most recent call last):
...
ValueError: The word to decode has to be in the ambient space of the code
```

The bug detailed in [trac ticket #20340](#) has been fixed:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(59).list()[0:40], 12)
sage: c = C.random_element()
sage: D = C.decoder("BerlekampWelch")
sage: D.decode_to_code(c) == c
True
```

### `decode_to_message(r)`

Decodes  $r$  to an element in message space of `self`.

**Note:** If the code associated to `self` has the same length as its dimension,  $r$  will be unencoded as is. In that case, if  $r$  is not a codeword, the output is unspecified.

INPUT:

- $r$  – a codeword of `self`

OUTPUT:

- a vector of `self` message space

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSBerlekampWelchDecoder(C)
sage: c = C.random_element()
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), D.decoding_radius())
sage: y = Chan(c)
sage: D.connected_encoder().unencode(c) == D.decode_to_message(y)
True
```

TESTS:

If one tries to decode a word which is too far from any codeword, an exception is raised:

```
sage: e = vector(F, [0, 0, 54, 23, 1, 0, 0, 0, 53, 21, 0, 0, 0, 34, 6, 11, 0, 0, 16, 0, 0, 0,
15
sage: D.decode_to_message(c + e)
Traceback (most recent call last):
...
DecodingError: Decoding failed because the number of errors exceeded the decoding radius
```

If one tries to decode something which is not in the ambient space of the code, an exception is raised:

```
sage: D.decode_to_message(42)
Traceback (most recent call last):
...
ValueError: The word to decode has to be in the ambient space of the code
```

The bug detailed in [trac ticket #20340](#) has been fixed:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(59).list()[0:40], 12)
sage: c = C.random_element()
sage: D = C.decoder("BerlekampWelch")
sage: E = D.connected_encoder()
sage: m = E.message_space().random_element()
sage: c = E.encode(m)
sage: D.decode_to_message(c) == m
True
```

### `decoding_radius()`

Returns maximal number of errors that `self` can decode.

OUTPUT:

- the number of errors as an integer

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSBerlekampWelchDecoder(C)
sage: D.decoding_radius()
14
```

**class** `sage.coding.grs.GRSErrorErasureDecoder`(*code*)

Bases: `sage.coding.decoder.Decoder`

Decoder for Generalized Reed-Solomon codes which is able to correct both errors and erasures in codewords.

INPUT:

- `code` – The associated code of this decoder.

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSErrorErasureDecoder(C)
sage: D
Error-Erasure decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

Actually, we can construct the decoder from `C` directly:

```
sage: D = C.decoder("ErrorErasure")
sage: D
Error-Erasure decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

### `decode_to_message`(*word\_and\_erasure\_vector*)

Decode `word_and_erasure_vector` to an element in message space of `self`

INPUT:

- `word_and_erasure_vector` – a tuple whose: - first element is an element of the ambient space of the code - second element is a vector over  $\text{GF}(2)$  whose length is the same as the code's

**Note:** If the code associated to `self` has the same length as its dimension, `r` will be unencoded as is. If

the number of erasures is exactly  $n - k$ , where  $n$  is the length of the code associated to `self` and  $k$  its dimension, `r` will be returned as is. In either case, if `r` is not a codeword, the output is unspecified.

INPUT:

- `word_and_erasure_vector` – a pair of vectors, where first element is a codeword of `self` and second element is a vector of  $\text{GF}(2)$  containing erasure positions

OUTPUT:

- a vector of `self` message space

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSErrorErasureDecoder(C)
sage: c = C.random_element()
sage: n_era = randint(0, C.minimum_distance() - 2)
sage: Chan = channels.ErrorErasureChannel(C.ambient_space(), D.decoding_radius(n_era), n_era)
sage: y = Chan(c)
sage: D.connected_encoder().unencode(c) == D.decode_to_message(y)
True
```

TESTS:

If one tries to decode a word with too many erasures, it returns an exception:

```
sage: Chan = channels.ErrorErasureChannel(C.ambient_space(), 0, C.minimum_distance() + 1)
sage: y = Chan(c)
sage: D.decode_to_message(y)
Traceback (most recent call last):
...
DecodingError: Too many erasures in the received word
```

If one tries to decode something which is not in the ambient space of the code, an exception is raised:

```
sage: D.decode_to_message((42, random_vector(GF(2), C.length())))
Traceback (most recent call last):
...
ValueError: The word to decode has to be in the ambient space of the code
```

If one tries to pass an `erasure_vector` which is not a vector over  $\text{GF}(2)$  of the same length as code's, an exception is raised:

```
sage: D.decode_to_message((C.random_element(), 42))
Traceback (most recent call last):
...
ValueError: The erasure vector has to be a vector over GF(2) of the same length as the code
```

**`decoding_radius`** (*number\_erasures*)

Return maximal number of errors that `self` can decode according to how many erasures it receives

INPUT:

- `number_erasures` – the number of erasures when we try to decode

OUTPUT:

- the number of errors as an integer

EXAMPLES:

```

sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: D = codes.decoders.GRSErrorErasureDecoder(C)
sage: D.decoding_radius(5)
11

```

If we receive too many erasures, it returns an exception as codeword will be impossible to decode:

```

sage: D.decoding_radius(30)
Traceback (most recent call last):
...
ValueError: The number of erasures exceed decoding capability

```

**class** sage.coding.grs.**GRSEvaluationPolynomialEncoder**(code)

Bases: [sage.coding.encoder.Encoder](#)

Encoder for Generalized Reed-Solomon codes which uses evaluation of polynomials to obtain codewords.

INPUT:

- code – The associated code of this encoder.

EXAMPLES:

```

sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: E = codes.encoders.GRSEvaluationPolynomialEncoder(C)
sage: E
Evaluation polynomial-style encoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite F
sage: E.message_space()
Univariate Polynomial Ring in x over Finite Field of size 59

```

Actually, we can construct the encoder from C directly:

```

sage: E = C.encoder("EvaluationPolynomial")
sage: E
Evaluation polynomial-style encoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite F

```

**encode**(p)

Transforms the polynomial p into a codeword of code().

INPUT:

- p – A polynomial from the message space of self of degree less than self.code().dimension().

OUTPUT:

- A codeword in associated code of self

EXAMPLES:

```

sage: F = GF(11)
sage: Fx.<x> = F[]
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: E = C.encoder("EvaluationPolynomial")
sage: p = x^2 + 3*x + 10
sage: c = E.encode(p); c
(10, 3, 9, 6, 5, 6, 9, 3, 10, 8)

```

```
sage: c in C
True
```

If a polynomial of too high degree is given, an error is raised:

```
sage: p = x^10
sage: E.encode(p)
Traceback (most recent call last):
...
ValueError: The polynomial to encode must have degree at most 4
```

If  $p$  is not an element of the proper polynomial ring, an error is raised:

```
sage: Qy.<y> = QQ[]
sage: p = y^2 + 1
sage: E.encode(p)
Traceback (most recent call last):
...
ValueError: The value to encode must be in Univariate Polynomial Ring in x over Finite Field
```

### **message\_space()**

Returns the message space of `self`

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: E = C.encoder("EvaluationPolynomial")
sage: E.message_space()
Univariate Polynomial Ring in x over Finite Field of size 11
```

### **unencode\_nocheck(c)**

Returns the message corresponding to the codeword  $c$ .

Use this method with caution: it does not check if  $c$  belongs to the code, and if this is not the case, the output is unspecified. Instead, use `unencode()`.

INPUT:

- $c$  – A codeword of `code()`.

OUTPUT:

- An polynomial of degree less than `self.code().dimension()`.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: E = C.encoder("EvaluationPolynomial")
sage: c = vector(F, (10, 3, 9, 6, 5, 6, 9, 3, 10, 8))
sage: c in C
True
sage: p = E.unencode_nocheck(c); p
x^2 + 3*x + 10
sage: E.encode(p) == c
True
```

Note that no error is thrown if  $c$  is not a codeword, and that the result is undefined:



```

sage: c = vector(F, (11, 3, 9, 6, 5, 6, 9, 3, 10, 8))
sage: c in C
False
sage: p = E.unencode_nocheck(c); p
6*x^4 + 6*x^3 + 2*x^2
sage: E.encode(p) == c
False

```

**class** `sage.coding.grs.GRSEvaluationVectorEncoder` (*code*)

Bases: `sage.coding.encoder.Encoder`

Encoder for Generalized Reed-Solomon codes which encodes vectors into codewords.

INPUT:

- `code` – The associated code of this encoder.

EXAMPLES:

```

sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[:n], k)
sage: E = codes.encoders.GRSEvaluationVectorEncoder(C)
sage: E
Evaluation vector-style encoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field

```

Actually, we can construct the encoder from `C` directly:

```

sage: E = C.encoder("EvaluationVector")
sage: E
Evaluation vector-style encoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field

```

**generator\_matrix()**

Returns a generator matrix of self

EXAMPLES:

```

sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[:n], k)
sage: E = codes.encoders.GRSEvaluationVectorEncoder(C)
sage: E.generator_matrix()
[1 1 1 1 1 1 1 1 1 1]
[0 1 2 3 4 5 6 7 8 9]
[0 1 4 9 5 3 3 5 9 4]
[0 1 8 5 9 4 7 2 6 3]
[0 1 5 4 3 9 9 3 4 5]

```

**class** `sage.coding.grs.GRSGaoDecoder` (*code*)

Bases: `sage.coding.decoder.Decoder`

Decoder for Generalized Reed-Solomon codes which uses Gao decoding algorithm to correct errors in codewords.

Gao decoding algorithm uses early terminated extended Euclidean algorithm to find the error locator polynomial. See [G02] for details.

REFERENCES:

INPUT:

- `code` – The associated code of this decoder.

## EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSGaoDecoder(C)
sage: D
Gao decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

Actually, we can construct the decoder from C directly:

```
sage: D = C.decoder("Gao")
sage: D
Gao decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

**decode\_to\_code(r)**

Corrects the errors in `r` and returns a codeword.

---

**Note:** If the code associated to `self` has the same length as its dimension, `r` will be returned as is.

---

## INPUT:

- `r` – a vector of the ambient space of `self.code()`

## OUTPUT:

- a vector of `self.code()`

## EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSGaoDecoder(C)
sage: c = C.random_element()
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), D.decoding_radius())
sage: y = Chan(c)
sage: c == D.decode_to_code(y)
True
```

## TESTS:

If one tries to decode a word which is too far from any codeword, an exception is raised:

```
sage: e = vector(F, [0, 0, 54, 23, 1, 0, 0, 0, 53, 21, 0, 0, 0, 34, 6, 11, 0, 0, 16, 0, 0, 0,
15
sage: D.decode_to_code(c + e)
Traceback (most recent call last):
...
DecodingError: Decoding failed because the number of errors exceeded the decoding radius
```

If one tries to decode something which is not in the ambient space of the code, an exception is raised:

```
sage: D.decode_to_code(42)
Traceback (most recent call last):
...
ValueError: The word to decode has to be in the ambient space of the code
```

The bug detailed in [trac ticket #20340](#) has been fixed:

```

sage: C = codes.GeneralizedReedSolomonCode(GF(59).list()[0:40], 12)
sage: c = C.random_element()
sage: D = C.decoder("Gao")
sage: c = C.random_element()
sage: D.decode_to_code(c) == c
True

```

**decode\_to\_message(r)**

Decodes  $r$  to an element in message space of `self`.

**Note:** If the code associated to `self` has the same length as its dimension,  $r$  will be unencoded as is. In that case, if  $r$  is not a codeword, the output is unspecified.

INPUT:

- $r$  – a codeword of `self`

OUTPUT:

- a vector of `self` message space

EXAMPLES:

```

sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[0:n], k)
sage: D = codes.decoders.GRSGaoDecoder(C)
sage: c = C.random_element()
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), D.decoding_radius())
sage: y = Chan(c)
sage: D.connected_encoder().unencode(c) == D.decode_to_message(y)
True

```

TESTS:

If one tries to decode a word which is too far from any codeword, an exception is raised:

```

sage: e = vector(F, [0, 0, 54, 23, 1, 0, 0, 0, 53, 21, 0, 0, 0, 34, 6, 11, 0, 0, 16, 0, 0, 0,
15
sage: D.decode_to_message(c + e)
Traceback (most recent call last):
...
DecodingError: Decoding failed because the number of errors exceeded the decoding radius

```

If one tries to decode something which is not in the ambient space of the code, an exception is raised:

```

sage: D.decode_to_message(42)
Traceback (most recent call last):
...
ValueError: The word to decode has to be in the ambient space of the code

```

The bug detailed in [trac ticket #20340](#) has been fixed:

```

sage: C = codes.GeneralizedReedSolomonCode(GF(59).list()[0:40], 12)
sage: c = C.random_element()
sage: D = C.decoder("Gao")
sage: E = D.connected_encoder()
sage: m = E.message_space().random_element()
sage: c = E.encode(m)

```

```
sage: D.decode_to_message(c) == m
True
```

**decoding\_radius()**

Return maximal number of errors that `self` can decode

OUTPUT:

- the number of errors as an integer

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n], k)
sage: D = codes.decoders.GRSgaoDecoder(C)
sage: D.decoding_radius()
14
```

**class** `sage.coding.grs.GRSKeyEquationSyndromeDecoder`(*code*)

Bases: `sage.coding.decoder.Decoder`

Decoder for Generalized Reed-Solomon codes which uses a Key equation decoding based on the syndrome polynomial to correct errors in codewords.

This algorithm uses early terminated extended euclidean algorithm to solve the key equations, as described in [R06], pp. 183-195.

REFERENCES:

INPUT:

- code* – The associated code of this decoder.

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n+1], k)
sage: D = codes.decoders.GRSKeyEquationSyndromeDecoder(C)
sage: D
Key equation decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

Actually, we can construct the decoder from *C* directly:

```
sage: D = C.decoder("KeyEquationSyndrome")
sage: D
Key equation decoder for [40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

**decode\_to\_code(r)**

Corrects the errors in *r* and returns a codeword.

---

**Note:** If the code associated to `self` has the same length as its dimension, *r* will be returned as is.

---

INPUT:

- r* – a vector of the ambient space of `self.code()`

OUTPUT:

- a vector of `self.code()`

**EXAMPLES:**

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n+1], k)
sage: D = codes.decoders.GRSKeyEquationSyndromeDecoder(C)
sage: c = C.random_element()
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), D.decoding_radius())
sage: y = Chan(c)
sage: c == D.decode_to_code(y)
True
```

**TESTS:**

If one tries to decode a word with too many errors, it returns an exception:

```
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), D.decoding_radius()+1)
sage: y = Chan(c)
sage: D.decode_to_message(y)
Traceback (most recent call last):
...
DecodingError: Decoding failed because the number of errors exceeded the decoding radius
```

If one tries to decode something which is not in the ambient space of the code, an exception is raised:

```
sage: D.decode_to_code(42)
Traceback (most recent call last):
...
ValueError: The word to decode has to be in the ambient space of the code
```

**`decode_to_message(r)`**

Decodes ‘r’ to an element in message space of `self`

---

**Note:** If the code associated to `self` has the same length as its dimension, `r` will be unencoded as is. In that case, if `r` is not a codeword, the output is unspecified.

---

**INPUT:**

- `r` – a codeword of `self`

**OUTPUT:**

- a vector of `self` message space

**EXAMPLES:**

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n+1], k)
sage: D = codes.decoders.GRSKeyEquationSyndromeDecoder(C)
sage: c = C.random_element()
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), D.decoding_radius())
sage: y = Chan(c)
sage: D.connected_encoder().unencode(c) == D.decode_to_message(y)
True
```

**`decoding_radius()`**

Return maximal number of errors that `self` can decode

OUTPUT:

- the number of errors as an integer

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n+1], k)
sage: D = codes.decoders.GRSKeyEquationSyndromeDecoder(C)
sage: D.decoding_radius()
14
```

**class** sage.coding.grs.**GeneralizedReedSolomonCode**(*evaluation\_points*, *dimension*, *column\_multipliers*=None)

Bases: *sage.coding.linear\_code.AbstractLinearCode*

Representation of a Generalized Reed-Solomon code.

INPUT:

- evaluation\_points* – A list of distinct elements of some finite field  $F$ .
- dimension* – The dimension of the resulting code.
- column\_multipliers* – (default: None) List of non-zero elements of  $F$ . All column multipliers are set to 1 if default value is kept.

EXAMPLES:

A Reed-Solomon code can be constructed by taking all non-zero elements of the field as evaluation points, and specifying no column multipliers:

```
sage: F = GF(7)
sage: evalpts = [F(i) for i in range(1,7)]
sage: C = codes.GeneralizedReedSolomonCode(evalpts, 3)
sage: C
[6, 3, 4] Generalized Reed-Solomon Code over Finite Field of size 7
```

More generally, the following is a GRS code where the evaluation points are a subset of the field and includes zero:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n], k)
sage: C
[40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

It is also possible to specify the column multipliers:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: colmults = F.list()[1:n+1]
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n], k, colmults)
sage: C
[40, 12, 29] Generalized Reed-Solomon Code over Finite Field of size 59
```

**column\_multipliers()**

Returns the column multipliers of *self* as a vector.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
```

```

sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.column_multipliers()
(1, 1, 1, 1, 1, 1, 1, 1, 1, 1)

```

**covering\_radius()**

Returns the covering radius of `self`.

The covering radius of a linear code  $C$  is the smallest number  $r$  s.t. any element of the ambient space of  $C$  is at most at distance  $r$  to  $C$ .

As GRS codes are Maximum Distance Separable codes (MDS), their covering radius is always  $d - 1$ , where  $d$  is the minimum distance. This is opposed to random linear codes where the covering radius is computationally hard to determine.

EXAMPLES:

```

sage: F = GF(2^8, 'a')
sage: n, k = 256, 100
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.covering_radius()
156

```

**decode\_to\_message(r)**

Decodes “`r`” to an element in message space of `self`

---

**Note:** If the code associated to `self` has the same length as its dimension, `r` will be unencoded as is. In that case, if `r` is not a codeword, the output is unspecified.

---

INPUT:

- `r` – a codeword of `self`

OUTPUT:

- a vector of `self` message space

EXAMPLES:

```

sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[1:n+1], k)
sage: r = vector(F, (8, 2, 6, 10, 6, 10, 7, 6, 7, 2))
sage: C.decode_to_message(r)
(3, 6, 6, 3, 1)

```

**dual\_code()**

Returns the dual code of `self`, which is also a GRS code.

EXAMPLES:

```

sage: F = GF(59)
sage: colmults = [ F.random_element() for i in range(40) ]
sage: C = codes.GeneralizedReedSolomonCode(F.list()[40], 12, colmults)
sage: Cd = C.dual_code(); Cd
[40, 28, 13] Generalized Reed-Solomon Code over Finite Field of size 59

```

The dual code of the dual code is the original code:

```

sage: C == Cd.dual_code()
True

```

**evaluation\_points()**

Returns the evaluation points of `self` as a vector.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.evaluation_points()
(0, 1, 2, 3, 4, 5, 6, 7, 8, 9)
```

**minimum\_distance()**

Returns the minimum distance of `self`. Since a GRS code is always Maximum-Distance-Separable (MDS), this returns `C.length() - C.dimension() + 1`.

EXAMPLES:

```
sage: F = GF(59)
sage: n, k = 40, 12
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.minimum_distance()
29
```

**multipliers\_product()**

Returns the component-wise product of the column multipliers of `self` with the column multipliers of the dual GRS code.

This is a simple Cramer's rule-like expression on the evaluation points of `self`. Recall that the column multipliers of the dual GRS code is also the column multipliers of the parity check matrix of `self`.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.multipliers_product()
[10, 9, 8, 7, 6, 5, 4, 3, 2, 1]
```

**parity\_check\_matrix()**

Returns the parity check matrix of `self`.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.parity_check_matrix()
[10 9 8 7 6 5 4 3 2 1]
[ 0 9 5 10 2 3 2 10 5 9]
[ 0 9 10 8 8 4 1 4 7 4]
[ 0 9 9 2 10 9 6 6 1 3]
[ 0 9 7 6 7 1 3 9 8 5]
```

**parity\_column\_multipliers()**

Returns the list of column multipliers of `self`'s parity check matrix.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.parity_column_multipliers()
```



```
[10, 9, 8, 7, 6, 5, 4, 3, 2, 1]
```

**weight\_distribution()**

Returns the list whose  $i$ 'th entry is the number of words of weight  $i$  in `self`.

Computing the weight distribution for a GRS code is very fast. Note that for random linear codes, it is computationally hard.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.weight_distribution()
[1, 0, 0, 0, 0, 0, 2100, 6000, 29250, 61500, 62200]
```

**weight\_enumerator()**

Returns the polynomial whose coefficient to  $x^i$  is the number of codewords of weight  $i$  in `self`.

Computing the weight enumerator for a GRS code is very fast. Note that for random linear codes, it is computationally hard.

EXAMPLES:

```
sage: F = GF(11)
sage: n, k = 10, 5
sage: C = codes.GeneralizedReedSolomonCode(F.list()[n], k)
sage: C.weight_enumerator()
62200*x^10 + 61500*x^9 + 29250*x^8 + 6000*x^7 + 2100*x^6 + 1
```

## 2.3 Hamming Code

Given an integer  $r$  and a field  $F$ , such that  $F = GF(q)$ , the  $[n, k, d]$  code with length  $n = \frac{q^r - 1}{q - 1}$ , dimension  $k = \frac{q^r - 1}{q - 1} - r$  and minimum distance  $d = 3$  is called the Hamming Code of order  $r$ .

REFERENCES:

**class** `sage.coding.hamming_code.HammingCode` (*base\_field*, *order*)

Bases: `sage.coding.linear_code.AbstractLinearCode`

Representation of a Hamming code.

INPUT:

- `base_field` – the base field over which `self` is defined.
- `order` – the order of `self`.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(7), 3)
sage: C
[57, 54] Hamming Code over Finite Field of size 7
```

**minimum\_distance()**

Returns the minimum distance of `self`. It is always 3 as `self` is a Hamming Code.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(7), 3)
sage: C.minimum_distance()
3
```

**parity\_check\_matrix()**

Returns a parity check matrix of `self`.

The construction of the parity check matrix in case `self` is not a binary code is not really well documented. Regarding the choice of projective geometry, one might check:

- the note over section 2.3 in [\[R\]](#), pages 47-48
- the dedicated paragraph in [\[HP\]](#), page 30

**EXAMPLES:**

```
sage: C = codes.HammingCode(GF(3), 3)
sage: C.parity_check_matrix()
[1 0 1 1 0 1 0 1 1 1 0 1 1]
[0 1 1 2 0 0 1 1 2 0 1 1 2]
[0 0 0 0 1 1 1 1 1 2 2 2 2]
```

## 2.4 Guruswami-Sudan decoder for Generalized Reed-Solomon codes

**REFERENCES:****AUTHORS:**

- Johan S. R. Nielsen, original implementation (see [\[Nielsen\]](#) for details)
- David Lucas, ported the original implementation in Sage

```
class sage.coding.guruswami_sudan.gs_decoder.GRSGuruswamiSudanDecoder (code,
                                                                    tau=None,
                                                                    param-
                                                                    eters=None,
                                                                    in-
                                                                    terpola-
                                                                    tion_alg=None,
                                                                    root_finder=None)
```

Bases: [sage.coding.decoder.Decoder](#)

The Guruswami-Sudan list-decoding algorithm for decoding Generalized Reed-Solomon codes.

The Guruswami-Sudan algorithm is a polynomial time algorithm to decode beyond half the minimum distance of the code. It can decode up to the Johnson radius which is  $n - \sqrt{n(n-d)}$ , where  $n, d$  is the length, respectively minimum distance of the RS code. See [GS99] for more details. It is a list-decoder meaning that it returns a list of all closest codewords or their corresponding message polynomials. Note that the output of the `decode_to_code` and `decode_to_message` methods are therefore lists.

The algorithm has two free parameters, the list size and the multiplicity, and these determine how many errors the method will correct: generally, higher decoding radius requires larger values of these parameters. To decode all the way to the Johnson radius, one generally needs values in the order of  $O(n^2)$ , while decoding just one error less requires just  $O(n)$ .

This class has static methods for computing choices of parameters given the decoding radius or vice versa.

The Guruswami-Sudan consists of two computationally intensive steps: Interpolation and Root finding, either of which can be completed in multiple ways. This implementation allows choosing the sub-algorithms among currently implemented possibilities, or supplying your own.

INPUT:

- `code` – A code associated to this decoder.
- `tau` – (default: `None`) an integer, the number of errors one wants the Guruswami-Sudan algorithm to correct.
- **parameters** – (default: `None`) a pair of integers, where:
  - the first integer is the multiplicity parameter, and
  - the second integer is the list size parameter.
- `interpolation_alg` – (default: `None`) the interpolation algorithm that will be used. The following possibilities are currently available:
  - "`LinearAlgebra`" – uses a linear system solver.
  - "`LeeOSullivan`" – uses Lee O'Sullivan method based on row reduction of a matrix
  - `None` – one of the above will be chosen based on the size of the code and the parameters.

You can also supply your own function to perform the interpolation. See NOTE section for details on the signature of this function.

- `root_finder` – (default: `None`) the rootfinding algorithm that will be used. The following possibilities are currently available:
  - "`RothRuckenstein`" – uses Roth-Ruckenstein algorithm.
  - `None` – one of the above will be chosen based on the size of the code and the parameters.

You can also supply your own function to perform the interpolation. See NOTE section for details on the signature of this function.

---

**Note:** One has to provide either `tau` or `parameters`. If neither are given, an exception will be raised.

If one provides a function as `root_finder`, its signature has to be: `my_rootfinder(Q, maxd=default_value, precision=default_value)`.  $Q$  will be given as an element of  $F[x][y]$ . The function must return the roots as a list of polynomials over a univariate polynomial ring. See [sage.coding.guruswami\\_sudan.rootfinding.rootfind\\_roth\\_ruckenstein\(\)](#) for an example.

If one provides a function as `interpolation_alg`, its signature has to be: `my_inter(interpolation_points, tau, s_and_l, wy)`. See [sage.coding.guruswami\\_sudan.interpolation.gs\\_interpolation\\_linalg\(\)](#) for an example.

---

#### EXAMPLES:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[1:250], 70)
sage: D = codes.decoders.GRSGuruswamiSudanDecoder(C, tau = 97)
sage: D
```

Guruswami-Sudan decoder for [250, 70, 181] Generalized Reed-Solomon Code over Finite Field of si

One can specify multiplicity and list size instead of `tau`:

```
sage: D = codes.decoders.GRSGuruswamiSudanDecoder(C, parameters = (1,2))
sage: D
Guruswami-Sudan decoder for [250, 70, 181] Generalized Reed-Solomon Code over Finite Field of si
```

One can pass a method as `root_finder` (works also for `interpolation_alg`):

```
sage: from sage.coding.guruswami_sudan.rootfinding import rootfind_roth_ruckenstein
sage: rf = rootfind_roth_ruckenstein
sage: D = codes.decoders.GRSGuruswamiSudanDecoder(C, parameters = (1,2), root_finder = rf)
sage: D
Guruswami-Sudan decoder for [250, 70, 181] Generalized Reed-Solomon Code over Finite Field of si
```

If one wants to use the native Sage algorithms for the root finding step, one can directly pass the string given in the Input block of this class. This works for `interpolation_alg` as well:

```
sage: from sage.coding.guruswami_sudan.rootfinding import rootfind_roth_ruckenstein
sage: rf = rootfind_roth_ruckenstein
sage: D = codes.decoders.GRSGuruswamiSudanDecoder(C, parameters = (1,2), root_finder="RothRuckenstein")
sage: D
Guruswami-Sudan decoder for [250, 70, 181] Generalized Reed-Solomon Code over Finite Field of si
```

Actually, we can construct the decoder from `C` directly:

```
sage: D = C.decoder("GuruswamiSudan", tau = 97)
sage: D
Guruswami-Sudan decoder for [250, 70, 181] Generalized Reed-Solomon Code over Finite Field of si
```

#### `decode_to_code(r)`

Return the list of all codeword within radius `self.decoding_radius()` of the received word `r`.

INPUT:

- `r` – a received word, i.e. a vector in  $F^n$  where  $F$  and  $n$  are the base field respectively length of `self.code()`.

EXAMPLES:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(17).list()[1:15], 6)
sage: D = codes.decoders.GRSGuruswamiSudanDecoder(C, tau=5)
sage: c = vector(GF(17), [3,13,12,0,0,7,5,1,8,11,1,9,4,12,14])
sage: c in C
True
sage: r = vector(GF(17), [3,13,12,0,0,7,5,1,8,11,15,12,14,7,10])
sage: r in C
False
sage: codewords = D.decode_to_code(r)
sage: len(codewords)
2
sage: c in codewords
True
```

#### `decode_to_message(r)`

Decodes `r` to the list of polynomials whose encoding by `self.code()` is within Hamming distance `self.decoding_radius()` of `r`.

INPUT:

- `r` – a received word, i.e. a vector in  $F^n$  where  $F$  and  $n$  are the base field respectively length of `self.code()`.

EXAMPLES:

```

sage: C = codes.GeneralizedReedSolomonCode(GF(17).list()[1:15], 6)
sage: D = codes.decoders.GRSGuruswamiSudanDecoder(C, tau=5)
sage: F.<x> = GF(17)[]
sage: m = 13*x^4 + 7*x^3 + 10*x^2 + 14*x + 3
sage: c = D.connected_encoder().encode(m)
sage: r = vector(GF(17), [3,13,12,0,0,7,5,1,8,11,15,12,14,7,10])
sage: (c-r).hamming_weight()
5
sage: messages = D.decode_to_message(r)
sage: len(messages)
2
sage: m in messages
True

```

**TESTS:**

If one has provided a method as a `root_finder` or a `interpolation_alg` which does not fit the allowed signature, an exception will be raised:

```

sage: C = codes.GeneralizedReedSolomonCode(GF(17).list()[1:15], 6)
sage: D = codes.decoders.GRSGuruswamiSudanDecoder(C, tau=5, root_finder=next_prime)
sage: F.<x> = GF(17)[]
sage: m = 9*x^5 + 10*x^4 + 9*x^3 + 7*x^2 + 15*x + 2
sage: c = D.connected_encoder().encode(m)
sage: r = vector(GF(17), [3,1,4,2,14,1,0,4,13,12,1,16,1,13,15])
sage: m in D.decode_to_message(r)
Traceback (most recent call last):
...
ValueError: The provided root-finding algorithm has a wrong signature. See the documentation

```

**decoding\_radius()**

Returns the maximal number of errors that `self` is able to correct.

**EXAMPLES:**

```

sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[1:250], 70)
sage: D = C.decoder("GuruswamiSudan", tau = 97)
sage: D.decoding_radius()
97

```

An example where `tau` is not one of the inputs to the constructor:

```

sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[1:250], 70)
sage: D = C.decoder("GuruswamiSudan", parameters = (2,4))
sage: D.decoding_radius()
105

```

**static gs\_satisfactory(tau, s, l, C=None, n\_k=None)**

Returns whether input parameters satisfy the governing equation of Guruswami-Sudan.

See [NI3] page 49, definition 3.3 and proposition 3.4 for details.

**INPUT:**

- `tau` – an integer, number of errors one expects Guruswami-Sudan algorithm to correct
- `s` – an integer, multiplicity parameter of Guruswami-Sudan algorithm
- `l` – an integer, list size parameter
- `C` – (default: None) a `GeneralizedReedSolomonCode`

- `n_k` – (default: `None`) a tuple of integers, respectively the length and the dimension of the `GeneralizedReedSolomonCode`

..NOTE:

One has to provide either ```C``` or ```(n, k)```. If none or both are given, an exception will be raised.

EXAMPLES:

```
sage: tau, s, l = 97, 1, 2
sage: n, k = 250, 70
sage: codes.decoders.GRSGuruswamiSudanDecoder.gs_satisfactory(tau, s, l, n_k = (n, k))
True
```

One can also pass a GRS code:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[0:250], 70)
sage: codes.decoders.GRSGuruswamiSudanDecoder.gs_satisfactory(tau, s, l, C = C)
True
```

Another example where `s` and `l` does not satisfy the equation:

```
sage: tau, s, l = 118, 47, 80
sage: codes.decoders.GRSGuruswamiSudanDecoder.gs_satisfactory(tau, s, l, n_k = (n, k))
False
```

If one provides both `C` and `n_k` an exception is returned:

```
sage: tau, s, l = 97, 1, 2
sage: n, k = 250, 70
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[0:250], 70)
sage: codes.decoders.GRSGuruswamiSudanDecoder.gs_satisfactory(tau, s, l, C = C, n_k = (n, k))
Traceback (most recent call last):
...
ValueError: Please provide only the code or its length and dimension
```

Same if one provides none of these:

```
sage: codes.decoders.GRSGuruswamiSudanDecoder.gs_satisfactory(tau, s, l)
Traceback (most recent call last):
...
ValueError: Please provide either the code or its length and dimension
```

**static** `guruswami_sudan_decoding_radius` (`C=None, n_k=None, l=None, s=None`)

Returns the maximal decoding radius of the Guruswami-Sudan decoder and the parameter choices needed for this.

If `s` is set but `l` is not it will return the best decoding radius using this `s` alongside with the required `l`. Vice versa for `l`. If both are set, it returns the decoding radius given this parameter choice.

INPUT:

- `C` – (default: `None`) a `GeneralizedReedSolomonCode`
- `n_k` – (default: `None`) a pair of integers, respectively the length and the dimension of the `GeneralizedReedSolomonCode`
- `s` – (default: `None`) an integer, the multiplicity parameter of Guruswami-Sudan algorithm
- `l` – (default: `None`) an integer, the list size parameter

---

**Note:** One has to provide either `C` or `n_k`. If none or both are given, an exception will be raised.

---

OUTPUT:

• `(tau, (s, 1))` – where

- `tau` is the obtained decoding radius, and
- `s, ell` are the multiplicity parameter, respectively list size parameter giving this radius.

EXAMPLES:

```
sage: n, k = 250, 70
sage: codes.decoders.GRSGuruswamiSudanDecoder.guruswami_sudan_decoding_radius(n_k = (n, k))
(118, (47, 89))
```

One parameter can be restricted at a time:

```
sage: n, k = 250, 70
sage: codes.decoders.GRSGuruswamiSudanDecoder.guruswami_sudan_decoding_radius(n_k = (n, k),
(109, (3, 5))
sage: codes.decoders.GRSGuruswamiSudanDecoder.guruswami_sudan_decoding_radius(n_k = (n, k),
(111, (4, 7))
```

The function can also just compute the decoding radius given the parameters:

```
sage: codes.decoders.GRSGuruswamiSudanDecoder.guruswami_sudan_decoding_radius(n_k = (n, k),
(92, (2, 6))
```

**interpolation\_algorithm()**

Returns the interpolation algorithm that will be used.

Remember that its signature has to be: `my_inter(interpolation_points, tau, s_and_l, wy)`. See [sage.coding.guruswami\\_sudan.interpolation.gs\\_interpolation\\_linalg\(\)](#) for an example.

EXAMPLES:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[0:250], 70)
sage: D = C.decoder("GuruswamiSudan", tau = 97)
sage: D.interpolation_algorithm() #random
<function gs_interpolation_linalg at 0x7f9d55753500>
```

**list\_size()**

Returns the list size parameter of `self`.

EXAMPLES:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[0:250], 70)
sage: D = C.decoder("GuruswamiSudan", tau = 97)
sage: D.list_size()
2
```

**multiplicity()**

Returns the multiplicity parameter of `self`.

EXAMPLES:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[0:250], 70)
sage: D = C.decoder("GuruswamiSudan", tau = 97)
sage: D.multiplicity()
1
```

**parameters()**

Returns the multiplicity and list size parameters of self.

**EXAMPLES:**

```
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[1:250], 70)
sage: D = C.decoder("GuruswamiSudan", tau = 97)
sage: D.parameters()
(1, 2)
```

**static parameters\_given\_tau(tau, C=None, n\_k=None)**

Returns the smallest possible multiplicity and list size given the given parameters of the code and decoding radius.

**INPUT:**

- **tau** – an integer, number of errors one wants the Guruswami-Sudan algorithm to correct
- **C** – (default: None) a GeneralizedReedSolomonCode
- **n\_k** – (default: None) a pair of integers, respectively the length and the dimension of the GeneralizedReedSolomonCode

**OUTPUT:**

- **(s, l)** – a pair of integers, where:
  - s is the multiplicity parameter, and
  - l is the list size parameter.

---

**Note:** One should to provide either C or (n, k). If neither or both are given, an exception will be raised.

---

**EXAMPLES:**

```
sage: tau, n, k = 97, 250, 70
sage: codes.decoders.GRSGuruswamiSudanDecoder.parameters_given_tau(tau, n_k = (n, k))
(1, 2)
```

Another example with a bigger decoding radius:

```
sage: tau, n, k = 118, 250, 70
sage: codes.decoders.GRSGuruswamiSudanDecoder.parameters_given_tau(tau, n_k = (n, k))
(47, 89)
```

Choosing a decoding radius which is too large results in an errors:

```
sage: tau = 200
sage: codes.decoders.GRSGuruswamiSudanDecoder.parameters_given_tau(tau, n_k = (n, k))
Traceback (most recent call last):
...
ValueError: The decoding radius must be less than the Johnson radius (which is 118.66)
```

**rootfinding\_algorithm()**

Returns the rootfinding algorithm that will be used.

Remember that its signature has to be: `my_rootfinder(Q, maxd=default_value, precision=default_value)`. See `sage.coding.guruswami_sudan.rootfinding.rootfind_roth_ruckenstein()` for an example.



## EXAMPLES:

```
sage: C = codes.GeneralizedReedSolomonCode(GF(251).list()[ :250], 70)
sage: D = C.decoder("GuruswamiSudan", tau = 97)
sage: D.rootfinding_algorithm() #random
<function rootfind_roth_ruckenstein at 0x7fea00618848>
```

```
sage.coding.guruswami_sudan.gs_decoder.n_k_params(C, n_k)
```

Internal helper function for the GRS`GuruswamiSudanDecoder` class for allowing to specify either a GRS code  $C$  or the length and dimensions  $n, k$  directly, in all the static functions.

If neither  $C$  or  $n, k$  were specified to those functions, an appropriate error should be raised. Otherwise,  $n, k$  of the code or the supplied tuple directly is returned.

## INPUT:

- $C$  – A GRS code or *None*
- $n_k$  – A tuple  $(n, k)$  being length and dimension of a GRS code, or *None*.

## OUTPUT:

- $n_k$  – A tuple  $(n, k)$  being length and dimension of a GRS code.

## EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.gs_decoder import n_k_params
sage: n_k_params(None, (10, 5))
(10, 5)
sage: C = codes.GeneralizedReedSolomonCode(GF(11).list()[ :10], 5)
sage: n_k_params(C, None)
(10, 5)
sage: n_k_params(None, None)
Traceback (most recent call last):
...
ValueError: Please provide either the code or its length and dimension
sage: n_k_params(C, (12, 2))
Traceback (most recent call last):
...
ValueError: Please provide only the code or its length and dimension
```

## 2.5 Interpolation algorithms for the Guruswami-Sudan decoder

## AUTHORS:

- Johan S. R. Nielsen, original implementation (see [\[Nielsen\]](#) for details)
- David Lucas, ported the original implementation in Sage

```
sage.coding.guruswami_sudan.interpolation.gs_interpolation_lee_osullivan(points,
                                                                           tau,
                                                                           pa-
                                                                           ram-
                                                                           e-
                                                                           ters,
                                                                           wy)
```

Returns an interpolation polynomial  $Q(x, y)$  for the given input using the module-based algorithm of Lee and O'Sullivan.

This algorithm constructs an explicit  $(\ell + 1) \times (\ell + 1)$  polynomial matrix whose rows span the  $\mathbf{F}_q[x]$  module of all interpolation polynomials. It then runs a row reduction algorithm to find a low-shifted degree vector in this row space, corresponding to a low weighted-degree interpolation polynomial.

INPUT:

- **points** – a list of tuples  $(x_i, y_i)$  such that we seek  $Q$  with  $(x_i, y_i)$  being a root of  $Q$  with multiplicity  $s$ .
- **tau** – an integer, the number of errors one wants to decode.
- **parameters** – (default: None) a pair of integers, where:
  - the first integer is the multiplicity parameter of Guruswami-Sudan algorithm and
  - the second integer is the list size parameter.
- **wy** – an integer, the  $y$ -weight, where we seek  $Q$  of low  $(1, wy)$  weighted degree.

EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.interpolation import gs_interpolation_lee_osullivan
sage: F = GF(11)
sage: points = [(F(0), F(2)), (F(1), F(5)), (F(2), F(0)), (F(3), F(4)), (F(4), F(9)) \
, (F(5), F(1)), (F(6), F(9)), (F(7), F(10))]
sage: tau = 1
sage: params = (1, 1)
sage: wy = 1
sage: gs_interpolation_lee_osullivan(points, tau, params, wy)
x^3*y + 2*x^3 - x^2*y + 5*x^2 + 5*x*y - 5*x + 2*y - 4
```

```
sage.coding.guruswami_sudan.interpolation.gs_interpolation_linalg(points, tau,
                                                                    parameters,
                                                                    wy)
```

Compute an interpolation polynomial  $Q(x,y)$  for the Guruswami-Sudan algorithm by solving a linear system of equations.

$Q$  is a bivariate polynomial over the field of the points, such that the polynomial has a zero of multiplicity at least  $s$  at each of the points, where  $s$  is the multiplicity parameter. Furthermore, its  $(1, wy)$ -weighted degree should be less than  $\text{\_interpolation\_max\_weighted\_deg}(n, \text{tau}, \text{wy})$ , where  $n$  is the number of points

INPUT:

- **points** – a list of tuples  $(x_i, y_i)$  such that we seek  $Q$  with  $(x_i, y_i)$  being a root of  $Q$  with multiplicity  $s$ .
- **tau** – an integer, the number of errors one wants to decode.
- **parameters** – (default: None) a pair of integers, where:
  - the first integer is the multiplicity parameter of Guruswami-Sudan algorithm and
  - the second integer is the list size parameter.
- **wy** – an integer, the  $y$ -weight, where we seek  $Q$  of low  $(1, wy)$  weighted degree.

EXAMPLES:

The following parameters arise from Guruswami-Sudan decoding of an  $[6,2,5]$  GRS code over  $F(11)$  with multiplicity 2 and list size 4:

```
sage: from sage.coding.guruswami_sudan.interpolation import gs_interpolation_linalg
sage: F = GF(11)
sage: points = [ (F(x),F(y)) for (x,y) in (0, 5), (1, 1), (2, 4), (3, 6), (4, 3), (5, 3)]
```

```

sage: tau = 3
sage: params = (2, 4)
sage: wy = 1
sage: Q = gs_interpolation_linalg(points, tau, params, wy); Q
4*x^5 - 4*x^4*y - 2*x^2*y^3 - x*y^4 + 3*x^4 - 4*x^2*y^2 + 5*y^4 - x^3 + x^2*y + 5*x*y^2 - 5*y^3

```

We verify that the interpolation polynomial has a zero of multiplicity at least 2 in each point:

```

sage: all( Q(x=a, y=b).is_zero() for (a,b) in points )
True
sage: x,y = Q.parent().gens()
sage: dQdx = Q.derivative(x)
sage: all( dQdx(x=a, y=b).is_zero() for (a,b) in points )
True
sage: dQdy = Q.derivative(y)
sage: all( dQdy(x=a, y=b).is_zero() for (a,b) in points )
True

```

`sage.coding.guruswami_sudan.interpolation.lee_osullivan_module`(*points*, *parameters*, *wy*)

Returns the analytically straight-forward basis for the  $\mathbf{F}_q[x]$  module containing all interpolation polynomials, as according to Lee and O'Sullivan.

The module is constructed in the following way: Let  $R(x)$  be the Lagrange interpolation polynomial through the sought interpolation points  $(x_i, y_i)$ , i.e.  $R(x_i) = y_i$ . Let  $G(x) = \prod_{i=1}^n (x - x_i)$ . Then the  $i$ 'th row of the basis matrix of the module is the coefficient-vector of the following polynomial in  $\mathbf{F}_q[x][y]$ :

$$P_i(x, y) = G(x)^{[i-s]}(y - R(x))^{i-[i-s]}y^{[i-s]},$$

where  $[a]$  for real  $a$  is  $a$  when  $a > 0$  and 0 otherwise. It is easily seen that  $P_i(x, y)$  is an interpolation polynomial, i.e. it is zero with multiplicity at least  $s$  on each of the points  $(x_i, y_i)$ .

INPUT:

- **points** – a list of tuples  $(x_i, y_i)$  such that we seek  $Q$  with  $(x_i, y_i)$  being a root of  $Q$  with multiplicity  $s$ .
- **parameters** – (default: `None`) a pair of integers, where:
  - the first integer is the multiplicity parameter  $s$  of Guruswami-Sudan algorithm and
  - the second integer is the list size parameter.
- **wy** – an integer, the  $y$ -weight, where we seek  $Q$  of low  $(1, wy)$  weighted degree.

EXAMPLES:

```

sage: from sage.coding.guruswami_sudan.interpolation import lee_osullivan_module
sage: F = GF(11)
sage: points = [(F(0), F(2)), (F(1), F(5)), (F(2), F(0)), (F(3), F(4)), (F(4), F(9)) \
, (F(5), F(1)), (F(6), F(9)), (F(7), F(10))]
sage: params = (1, 1)
sage: wy = 1
sage: lee_osullivan_module(points, params, wy)
[x^8 + 5*x^7 + 3*x^6 + 9*x^5 + 4*x^4 + 2*x^3 + 9*x      0]
[10*x^7 + 4*x^6 + 9*x^4 + 7*x^3 + 2*x^2 + 9*x + 9     1]

```

## 2.6 Finding $F[x]$ -roots for polynomials over $F[x][y]$ , with ‘F’ is a (finite) field, as used in the Guruswami-Sudan decoding.

This module contains functions for finding two types of  $F[x]$  roots in a polynomial over  $F[x][y]$ , where  $F$  is a field. Note that if  $F$  is an infinite field, then these functions should work, but no measures are taken to limit coefficient growth. The functions also assume the existence of a root finding procedure in  $F[x]$ .

Given a  $Q(x, y) \in F[x, y]$ , the first type of root are actual  $F[x]$  roots, i.e. polynomials  $f(x) \in F[x]$  such that  $Q(x, f(x)) = 0$ .

The second type of root are modular roots: given  $Q(x, y) \in F[x, y]$  and a precision  $d \in \mathbb{Z}_+$ , then we find all  $f(x) \in F[x]$  such that  $Q(x, f(x)) \equiv 0 \pmod{x^d}$ . Since this set is infinite, we return a succinct description of all such polynomials: this is given as pairs  $(f(x), h)$  such that  $f(x) + g(x)x^h$  is a modular root of  $Q$  for any  $g \in F[x]$ .

AUTHORS:

- Johan S. R. Nielsen, original implementation (see [\[Nielsen\]](#) for details)
- David Lucas, ported the original implementation in Sage

```
sage.coding.guruswami_sudan.rootfinding.rootfind_roth_ruckenstein(Q,
                                                                    maxd=None,
                                                                    preci-
                                                                    sion=None)
```

Returns the list of roots of a bivariate polynomial  $Q$ .

Uses the Roth-Ruckenstein algorithm to find roots or modular roots of a  $Q \in \mathbb{F}[x][y]$  where  $\mathbb{F}$  is a field.

If `precision = None` then actual roots will be found, i.e. all  $f \in \mathbb{F}[x]$  such that  $Q(f) = 0$ . This will be returned as a list of  $\mathbb{F}[x]$  elements.

If `precision = d` for some integer  $d$ , then all  $f \in \mathbb{F}[x]$  such that  $Q(f) \equiv 0 \pmod{x^d}$  will be returned. This set is infinite, and so it will be returned as a list of pairs in  $\mathbb{F}[x] \times \mathbb{Z}_+$ , where  $(f, h)$  denotes that  $Q(f + x^h g) \equiv 0 \pmod{x^d}$  for any  $g \in \mathbb{F}[x]$ .

If `maxd` is given, then find only  $f$  with  $\deg f \leq \text{maxd}$ . In case `precision = d` setting `maxd` means to only find the roots up to precision `maxd`, i.e.  $h \leq \text{maxd}$  in the above; otherwise, this will be naturally bounded at `precision - 1`.

INPUT:

- $Q$  – a bivariate polynomial, represented either over  $F[x, y]$ ,  $F[x][y]$  or  $F[x]$  list.
- `maxd` – (default: `None`) an non-negative integer degree bound, as defined above.
- `precision` – (default: `None`) an integer, as defined above.

EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.rootfinding import rootfind_roth_ruckenstein
sage: F = GF(17)
sage: Px.<x> = F[]
sage: Py.<y> = Px[]
sage: Q = (y - (x**2 + x + 1)) * (y**2 - x + 1) * (y - (x**3 + 4*x + 16))
sage: roots = rootfind_roth_ruckenstein(Q); set(roots)
{x^2 + x + 1, x^3 + 4*x + 16}
sage: Q(roots[0])
0
sage: set(rootfind_roth_ruckenstein(Q, maxd = 2))
{x^2 + x + 1}
sage: modroots = rootfind_roth_ruckenstein(Q, precision = 3); set(modroots)
{(4*x + 16, 3), (x^2 + x + 1, 3), (8*x^2 + 15*x + 4, 3), (9*x^2 + 2*x + 13, 3)}
```

```

sage: (f,h) = modroots[0]
sage: Q(f + x^h * Px.random_element()) % x^3
0
sage: modroots2 = rootfind_roth_ruckenstein(Q, maxd=1, precision = 3); set(modroots2)
{(x + 1, 2), (2*x + 13, 2), (4*x + 16, 2), (15*x + 4, 2)}

```

**TESTS:**

Test that if  $Q = 0$ , then the appropriate response is given

```

sage: F = GF(17) sage: R.<x,y> = F[] sage: rootfind_roth_ruckenstein(R.zero()) ValueError('The
zero polynomial has infinitely many roots.') sage: rootfind_roth_ruckenstein(R.zero(), precision=1)
[(0, 0)]

```

## 2.7 Guruswami-Sudan utility methods

**AUTHORS:**

- Johan S. R. Nielsen, original implementation (see [\[Nielsen\]](#) for details)
- David Lucas, ported the original implementation in Sage

`sage.coding.guruswami_sudan.utils.apply_shifts(M, shifts)`  
 Applies column shifts inplace to the polynomial matrix  $M$ .

This is equivalent to multiplying the  $n$ 'th column of  $M$  with  $x^{\text{shifts}[n]}$ .

**INPUT:**

- $M$  – a polynomial matrix
- `shifts` – a list of non-negative integer shifts

**EXAMPLES:**

```

sage: from sage.coding.guruswami_sudan.utils import apply_shifts
sage: F.<x> = GF(7) []
sage: M = matrix(F, [[2*x^2 + x, 5*x^2 + 2*x + 1, 4*x^2 + x], \
                     [x^2 + 3*x + 3, 5*x^2 + 5*x + 1, 6*x^2 + 5*x + 4], \
                     [5*x^2 + 2*x + 4, 4*x^2 + 2*x, 5*x^2 + x + 2]])
sage: shifts = [1, 2, 3]
sage: apply_shifts(M, shifts)
sage: M
[      2*x^3 + x^2      5*x^4 + 2*x^3 + x^2      4*x^5 + x^4]
[      x^3 + 3*x^2 + 3*x      5*x^4 + 5*x^3 + x^2      6*x^5 + 5*x^4 + 4*x^3]
[      5*x^3 + 2*x^2 + 4*x      4*x^4 + 2*x^3      5*x^5 + x^4 + 2*x^3]

```

`sage.coding.guruswami_sudan.utils.gilt(x)`  
 Returns the greatest integer smaller than  $x$ .

**EXAMPLES:**

```

sage: from sage.coding.guruswami_sudan.utils import gilt
sage: gilt(43)
42

```

It works with any type of numbers (not only integers):

```

sage: gilt(43.041)
43

```

`sage.coding.guruswami_sudan.utils.johnson_radius(n, d)`

Returns the Johnson-radius for the code length  $n$  and the minimum distance  $d$ .

The Johnson radius is defined as  $n - \sqrt{n(n - d)}$ .

INPUT:

- $n$  – an integer, the length of the code
- $d$  – an integer, the minimum distance of the code

EXAMPLES:

```
sage: sage.coding.guruswami_sudan.utils.johnson_radius(250, 181)
-5*sqrt(690) + 250
```

`sage.coding.guruswami_sudan.utils.leading_term(v, shifts=None)`

Returns the term of  $v$  with the highest degree.

This methods can manage shifted degree, by providing `shift` to it.

In case of several positions having the same, highest degree, the term with the right-most position is returned.

INPUT:

- $v$  – a vector of polynomials
- `shifts` – (default: `None`) a list of integer shifts to consider  $v$  under. If `None`, all shifts are considered as 0.

EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.utils import leading_term
sage: F.<x> = GF(7)[]
sage: v = vector(F, [3*x^2 + 3*x + 4, 4*x + 3, 4*x^2 + 4*x + 5, x^2 + 2*x + 5, 3*x^2 + 5*x])
sage: leading_term(v)
3*x^2 + 5*x
```

`sage.coding.guruswami_sudan.utils.ligt(x)`

Returns the least integer greater than  $x$ .

EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.utils import ligt
sage: ligt(41)
42
```

It works with any type of numbers (not only integers):

```
sage: ligt(41.041)
42
```

`sage.coding.guruswami_sudan.utils.polynomial_to_list(p, len)`

Returns  $p$  as a list of its coefficients of length  $len$ .

INPUT:

- $p$  – a polynomial
- $len$  – an integer. If  $len$  is smaller than the degree of  $p$ , the returned list will be of size degree of  $p$ , else it will be of size  $len$ .

EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.utils import polynomial_to_list
sage: F.<x> = GF(41) []
sage: p = 9*x^2 + 8*x + 37
sage: polynomial_to_list(p, 4)
[37, 8, 9, 0]
```

`sage.coding.guruswami_sudan.utils.remove_shifts(M, shifts)`

Removes the shifts inplace to the matrix  $M$  as they were introduced by `apply_shifts()`.

If  $M$  was not earlier called with `apply_shifts()` using the same shifts, then the least significant coefficients of the entries of  $M$ , corresponding to how much we are shifting down, will be lost.

INPUT:

- $M$  – a polynomial matrix
- `shifts` – a list of non-negative integer shifts

EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.utils import remove_shifts
sage: F.<x> = GF(7) []
sage: M = matrix(F, [[2*x^3 + x^2, 5*x^4 + 2*x^3 + x^2, 4*x^5 + x^4], \
                     [x^3 + 3*x^2 + 3*x, 5*x^4 + 5*x^3 + x^2, 6*x^5 + 5*x^4 + 4*x^3], \
                     [5*x^3 + 2*x^2 + 4*x, 4*x^4 + 2*x^3, 5*x^5 + x^4 + 2*x^3]])

sage: shifts = [1, 2, 3]
sage: remove_shifts(M, shifts)
sage: M
[      2*x^2 + x 5*x^2 + 2*x + 1      4*x^2 + x]
[  x^2 + 3*x + 3 5*x^2 + 5*x + 1 6*x^2 + 5*x + 4]
[5*x^2 + 2*x + 4      4*x^2 + 2*x      5*x^2 + x + 2]
```

`sage.coding.guruswami_sudan.utils.solve_degree2_to_integer_range(a, b, c)`

Returns the greatest integer range  $[i_1, i_2]$  such that  $i_1 > x_1$  and  $i_2 < x_2$  where  $x_1, x_2$  are the two zeroes of the equation in  $x$ :  $ax^2 + bx + c = 0$ .

If there is no real solution to the equation, it returns an empty range with negative coefficients.

INPUT:

- $a, b$  and  $c$  – coefficients of a second degree equation,  $a$  being the coefficient of the higher degree term.

EXAMPLES:

```
sage: from sage.coding.guruswami_sudan.utils import solve_degree2_to_integer_range
sage: solve_degree2_to_integer_range(1, -5, 1)
(1, 4)
```

If there is no real solution:

```
sage: solve_degree2_to_integer_range(50, 5, 42)
(-2, -1)
```

## 2.8 Linear code

VERSION: 1.2

Let  $F$  be a finite field. Here, we will denote the finite field with  $q$  elements by  $\mathbf{F}_q$ . A subspace of  $F^n$  (with the standard basis) is called a linear code of length  $n$ . If its dimension is denoted  $k$  then we typically store a basis of  $C$  as a  $k \times n$

matrix, with rows the basis vectors. It is called the generator matrix of  $C$ . The rows of the parity check matrix of  $C$  are a basis for the code,

$$C^* = \{v \in GF(q)^n \mid v \cdot c = 0, \text{ for all } c \in C\},$$

called the dual space of  $C$ .

If  $F = \mathbf{F}_2$  then  $C$  is called a binary code. If  $F = \mathbf{F}_q$  then  $C$  is called a  $q$ -ary code. The elements of a code  $C$  are called codewords.

Let  $C, D$  be linear codes of length  $n$  and dimension  $k$ . There are several notions of equivalence for linear codes:

$C$  and  $D$  are

- permutational equivalent, if there is some permutation  $\pi \in S_n$  such that  $(c_{\pi(0)}, \dots, c_{\pi(n-1)}) \in D$  for all  $c \in C$ .
- linear equivalent, if there is some permutation  $\pi \in S_n$  and a vector  $\phi$  of units of length  $n$  such that  $(c_{\pi(0)}\phi_0^{-1}, \dots, c_{\pi(n-1)}\phi_{n-1}^{-1}) \in D$  for all  $c \in C$ .
- semilinear equivalent, if there is some permutation  $\pi \in S_n$ , a vector  $\phi$  of units of length  $n$  and a field automorphism  $\alpha$  such that  $(\alpha(c_{\pi(0)}\phi_0^{-1}), \dots, \alpha(c_{\pi(n-1)}\phi_{n-1}^{-1})) \in D$  for all  $c \in C$ .

These are group actions. If one of these group elements sends the linear code  $C$  to itself, then we will call it an automorphism. Depending on the group action we will call those groups:

- permutation automorphism group
- monomial automorphism group (every linear Hamming isometry is a monomial transformation of the ambient space, for  $n \geq 3$ )
- automorphism group (every semilinear Hamming isometry is a semimonomial transformation of the ambient space, for  $n \geq 3$ )

This file contains

1. LinearCode class definition; LinearCodeFromVectorspace conversion function,
2. The spectrum (weight distribution), covering\_radius, minimum distance programs (calling Steve Linton's or CJ Tjhal's C programs), characteristic\_function, and several implementations of the Duursma zeta function (sd\_zeta\_polynomial, zeta\_polynomial, zeta\_function, chinen\_polynomial, for example),
3. interface with best\_known\_linear\_code\_www (interface with codetables.de since A. Brouwer's online tables have been disabled), bounds\_minimum\_distance which call tables in GUAVA (updated May 2006) created by Cen Tjhai instead of the online internet tables,
4. generator\_matrix, generator\_matrix\_systematic, information\_set, list, parity\_check\_matrix, decode, dual\_code, extended\_code, shortened, punctured, genus, binomial\_moment, and divisor methods for LinearCode,
5. Boolean-valued functions such as "==" , is\_self\_dual, is\_self\_orthogonal, is\_subcode, is\_permutation\_automorphism, is\_permutation\_equivalent (which interfaces with Robert Miller's partition refinement code),
6. permutation methods: is\_permutation\_automorphism, permutation\_automorphism\_group, permuted\_code, standard\_form, module\_composition\_factors,
7. design-theoretic methods: assmus\_mattson\_designs (implementing Assmus-Mattson Theorem),
8. code constructions, such as HammingCode and ToricCode, are in a separate code\_constructions.py module; in the separate guava.py module, you will find constructions, such as RandomLinearCodeGuava and BinaryReedMullerCode, wrapped from the corresponding GUAVA codes.

EXAMPLES:



```

sage: MS = MatrixSpace(GF(2), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: C.basis()
[(1, 1, 1, 0, 0, 0, 0),
 (1, 0, 0, 1, 1, 0, 0),
 (0, 1, 0, 1, 0, 1, 0),
 (1, 1, 0, 1, 0, 0, 1)]
sage: c = C.basis()[1]
sage: c in C
True
sage: c.nonzero_positions()
[0, 3, 4]
sage: c.support()
[0, 3, 4]
sage: c.parent()
Vector space of dimension 7 over Finite Field of size 2

```

To be added:

1. More wrappers
2. GRS codes and special decoders.
3.  $P^1$  Goppa codes and group actions on  $P^1$  RR space codes.

REFERENCES:

- [HP] W. C. Huffman and V. Pless, Fundamentals of error-correcting codes, Cambridge Univ. Press, 2003.
- [Gu] GUAVA manual, <http://www.gap-system.org/Packages/guava.html>

AUTHORS:

- David Joyner (2005-11-22, 2006-12-03): initial version
- William Stein (2006-01-23): Inclusion in Sage
- David Joyner (2006-01-30, 2006-04): small fixes
- David Joyner (2006-07): added documentation, group-theoretical methods, ToricCode
- David Joyner (2006-08): hopeful latex fixes to documentation, added list and `__iter__` methods to LinearCode and examples, added hamming\_weight function, fixed random method to return a vector, TrivialCode, fixed subtle bug in dual\_code, added galois\_closure method, fixed mysterious bug in permutation\_automorphism\_group (GAP was over-using “G” somehow?)
- David Joyner (2006-08): hopeful latex fixes to documentation, added CyclicCode, best\_known\_linear\_code, bounds\_minimum\_distance, assmus\_mattson\_designs (implementing Assmus-Mattson Theorem).
- David Joyner (2006-09): modified decode syntax, fixed bug in is\_galois\_closed, added LinearCode\_from\_vectorspace, extended\_code, zeta\_function
- Nick Alexander (2006-12-10): factor GUAVA code to guava.py
- David Joyner (2007-05): added methods punctured, shortened, divisor, characteristic\_polynomial, binomial\_moment, support for LinearCode. Completely rewritten zeta\_function (old version is now zeta\_function2) and a new function, LinearCodeFromVectorSpace.
- David Joyner (2007-11): added zeta\_polynomial, weight\_enumerator, chinen\_polynomial; improved best\_known\_code; made some pythonic revisions; added is\_equivalent (for binary codes)
- David Joyner (2008-01): fixed bug in decode reported by Harald Schilly, (with Mike Hansen) added some doctests.

- David Joyner (2008-02): translated `standard_form`, `dual_code` to Python.
- David Joyner (2008-03): translated `punctured`, `shortened`, `extended_code`, `random` (and renamed `random` to `random_element`), deleted `zeta_function2`, `zeta_function3`, added wrapper `automorphism_group_binary_code` to Robert Miller's code), added `direct_sum_code`, `is_subcode`, `is_self_dual`, `is_self_orthogonal`, `redundancy_matrix`, did some alphabetical reorganizing to make the file more readable. Fixed a bug in `permutation_automorphism_group` which caused it to crash.
- David Joyner (2008-03): fixed bugs in `spectrum` and `zeta_polynomial`, which misbehaved over non-prime base rings.
- David Joyner (2008-10): use CJ Tjhal's `MinimumWeight` if `char = 2` or `3` for `min_dist`; add `is_permutation_equivalent` and improve `permutation_automorphism_group` using an interface with Robert Miller's code; added interface with Leon's code for the `spectrum` method.
- David Joyner (2009-02): added native decoding methods (see `module_decoder.py`)
- David Joyner (2009-05): removed dependence on Guava, allowing it to be an option. Fixed errors in some docstrings.
- Kwankyu Lee (2010-01): added methods `generator_matrix_systematic`, `information_set`, and magma interface for linear codes.
- Niles Johnson (2010-08): [trac ticket ##3893](#): `random_element()` should pass on `*args` and `**kwargs`.
- Thomas Feulner (2012-11): [trac ticket #13723](#): deprecation of `hamming_weight()`
- Thomas Feulner (2013-10): added methods to compute a canonical representative and the automorphism group

## TESTS:

```
sage: MS = MatrixSpace(GF(2), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: C == loads(dumps(C))
True
```

```
class sage.coding.linear_code.AbstractLinearCode(base_field,          length,          de-
                                                fault_encoder_name,      de-
                                                fault_decoder_name)
```

Bases: `sage.modules.module.Module`

Abstract class for linear codes.

This class contains all methods that can be used on Linear Codes and on Linear Codes families. So, every Linear Code-related class should inherit from this abstract class.

To implement a linear code, you need to:

- inherit from `AbstractLinearCode`
- call `AbstractLinearCode.__init__` method in the subclass constructor. Example: `super(SubclassName, self).__init__(base_field, length, "EncoderName", "DecoderName")`. By doing that, your subclass will have its `length` parameter initialized and will be properly set as a member of the category framework. You need of course to complete the constructor by adding any additional parameter needed to describe properly the code defined in the subclass.
- fill the dictionary of its encoders in `sage.coding.__init__.py` file. Example: I want to link the encoder `MyEncoderClass` to `MyNewCodeClass` under the name `MyEncoderName`. All I need to do is to write this line in the `__init__.py` file: `MyNewCodeClass._registered_encoders["NameOfMyEncoder"] = MyEncoderClass` and all instances of `MyNewCodeClass` will be able to use instances of `MyEncoderClass`.

•fill the dictionary of its decoders in `sage.coding.__init__` file. Example: I want to link the encoder `MyDecoderClass` to `MyNewCodeClass` under the name `MyDecoderName`. All I need to do is to write this line in the `__init__.py` file:

```
MyNewCodeClass._registered_decoders["NameOfMyDecoder"] =
MyDecoderClass
```

and all instances of `MyNewCodeClass` will be able to use instances of `MyDecoderClass`.

As `AbstractLinearCode` is not designed to be implemented, it does not have any representation methods. You should implement `_repr_` and `_latex_` methods in the subclass.

**Note:** `AbstractLinearCode` has generic implementations of the comparison methods `__cmp__` and `__eq__` which use the generator matrix and are quite slow. In subclasses you are encouraged to override these functions.

**Warning:** The default encoder should always have  $F^k$  as message space, with  $k$  the dimension of the code and  $F$  is the base ring of the code.

A lot of methods of the abstract class rely on the knowledge of a generator matrix. It is thus strongly recommended to set an encoder with a generator matrix implemented as a default encoder.

**add\_decoder** (*name*, *decoder*)

Adds an decoder to the list of registered decoders of `self`.

**Note:** This method only adds `decoder` to `self`, and not to any member of the class of `self`. To know how to add an `sage.coding.decoder.Decoder`, please refer to the documentation of `AbstractLinearCode`.

INPUT:

- `name` – the string name for the decoder
- `decoder` – the class name of the decoder

EXAMPLES:

First of all, we create a (very basic) new decoder:

```
sage: class MyDecoder(sage.coding.decoder.Decoder):
....:     def __init__(self, code):
....:         super(MyDecoder, self).__init__(code)
....:     def _repr_(self):
....:         return "MyDecoder decoder with associated code %s" % self.code()
```

We now create a new code:

```
sage: C = codes.HammingCode(GF(2), 3)
```

We can add our new decoder to the list of available decoders of `C`:

```
sage: C.add_decoder("MyDecoder", MyDecoder)
sage: C.decoders_available()
['MyDecoder', 'Syndrome', 'NearestNeighbor']
```

We can verify that any new code will not know `MyDecoder`:

```
sage: C2 = codes.HammingCode(GF(2), 3)
sage: C2.decoders_available()
['Syndrome', 'NearestNeighbor']
```

## TESTS:

It is impossible to use a name which is in the dictionary of available decoders:

```
sage: C.add_decoder("Syndrome", MyDecoder)
Traceback (most recent call last):
...
ValueError: There is already a registered decoder with this name
```

**add\_encoder** (*name*, *encoder*)

Adds an encoder to the list of registered encoders of *self*.

**Note:** This method only adds encoder to *self*, and not to any member of the class of *self*. To know how to add an [sage.coding.encoder.Encoder](#), please refer to the documentation of [AbstractLinearCode](#).

## INPUT:

- *name* – the string name for the encoder
- *encoder* – the class name of the encoder

## EXAMPLES:

First of all, we create a (very basic) new encoder:

```
sage: class MyEncoder(sage.coding.encoder.Encoder):
....:     def __init__(self, code):
....:         super(MyEncoder, self).__init__(code)
....:     def _repr_(self):
....:         return "MyEncoder encoder with associated code %s" % self.code()
```

We now create a new code:

```
sage: C = codes.HammingCode(GF(2), 3)
```

We can add our new encoder to the list of available encoders of *C*:

```
sage: C.add_encoder("MyEncoder", MyEncoder)
sage: C.encoders_available()
['MyEncoder', 'ParityCheck']
```

We can verify that any new code will not know *MyEncoder*:

```
sage: C2 = codes.HammingCode(GF(2), 3)
sage: C2.encoders_available()
['ParityCheck']
```

## TESTS:

It is impossible to use a name which is in the dictionary of available encoders:

```
sage: C.add_encoder("ParityCheck", MyEncoder)
Traceback (most recent call last):
...
ValueError: There is already a registered encoder with this name
```

**ambient\_space** ()

Returns the ambient vector space of *self*.

## EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.ambient_space()
Vector space of dimension 7 over Finite Field of size 2
```

**assmus\_mattson\_designs** (*t, mode=None*)

Assmus and Mattson Theorem (section 8.4, page 303 of [HP]): Let  $A_0, A_1, \dots, A_n$  be the weights of the codewords in a binary linear  $[n, k, d]$  code  $C$ , and let  $A_0^*, A_1^*, \dots, A_n^*$  be the weights of the codewords in its dual  $[n, n - k, d^*]$  code  $C^*$ . Fix a  $t$ ,  $0 < t < d$ , and let

$$s = |\{i \mid A_i^* \neq 0, 0 < i \leq n - t\}|.$$

Assume  $s \leq d - t$ .

1. If  $A_i \neq 0$  and  $d \leq i \leq n$  then  $C_i = \{c \in C \mid wt(c) = i\}$  holds a simple  $t$ -design.
2. If  $A_i^* \neq 0$  and  $d^* \leq i \leq n - t$  then  $C_i^* = \{c \in C^* \mid wt(c) = i\}$  holds a simple  $t$ -design.

A block design is a pair  $(X, B)$ , where  $X$  is a non-empty finite set of  $v > 0$  elements called points, and  $B$  is a non-empty finite multiset of size  $b$  whose elements are called blocks, such that each block is a non-empty finite multiset of  $k$  points. A design without repeated blocks is called a simple block design. If every subset of points of size  $t$  is contained in exactly  $\lambda$  blocks the block design is called a  $t - (v, k, \lambda)$  design (or simply a  $t$ -design when the parameters are not specified). When  $\lambda = 1$  then the block design is called a  $S(t, k, v)$  Steiner system.

In the Assmus and Mattson Theorem (1),  $X$  is the set  $\{1, 2, \dots, n\}$  of coordinate locations and  $B = \{supp(c) \mid c \in C_i\}$  is the set of supports of the codewords of  $C$  of weight  $i$ . Therefore, the parameters of the  $t$ -design for  $C_i$  are

```
t =      given
v =      n
k =      i    (k not to be confused with dim(C))
b =      Ai
lambda = b*binomial(k,t)/binomial(v,t) (by Theorem 8.1.6,
                                         p 294, in [HP])
```

Setting the `mode="verbose"` option prints out the values of the parameters.

The first example below means that the binary  $[24, 12, 8]$ -code  $C$  has the property that the (support of the) codewords of weight 8 (resp., 12, 16) form a 5-design. Similarly for its dual code  $C^*$  (of course  $C = C^*$  in this case, so this info is extraneous). The test fails to produce 6-designs (ie, the hypotheses of the theorem fail to hold, not that the 6-designs definitely don't exist). The command `assmus_mattson_designs(C, 5, mode="verbose")` returns the same value but prints out more detailed information.

The second example below illustrates the blocks of the  $5-(24, 8, 1)$  design (i.e., the  $S(5, 8, 24)$  Steiner system).

## EXAMPLES:

```
sage: C = codes.ExtendedBinaryGolayCode() # example 1
sage: C.assmus_mattson_designs(5)
['weights from C: ',
 [8, 12, 16, 24],
 'designs from C: ',
 [[5, (24, 8, 1)], [5, (24, 12, 48)], [5, (24, 16, 78)], [5, (24, 24, 1)]]],
['weights from C*: ',
 [8, 12, 16],
 'designs from C*: ',
 [[5, (24, 8, 1)], [5, (24, 12, 48)], [5, (24, 16, 78)]]]
```

```
sage: C.assmus_mattson_designs(6)
0
sage: X = range(24) # example 2
sage: blocks = [c.support() for c in C if c.hamming_weight()==8]; len(blocks)
759
```

REFERENCE:

- [HP] W. C. Huffman and V. Pless, Fundamentals of ECC, Cambridge Univ. Press, 2003.

**automorphism\_group\_gens** (*equivalence*='semilinear')Return generators of the automorphism group of `self`.

INPUT:

- equivalence (optional) – which defines the acting group, either
  - permutational
  - linear
  - semilinear

OUTPUT:

- generators of the automorphism group of self
- the order of the automorphism group of self

EXAMPLES:

[illegible]

```
base field()
```

Return the base field of `self`.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0], [1,0,0,1,1,0,0], [0,1,0,1,0,1,0], [1,0,1,0,1,0,0], [0,0,1,0,0,1,1], [0,1,1,0,0,0,1], [1,0,0,0,1,1,0]])
sage: C = LinearCode(G)
sage: C.base_field()
Finite Field of size 2
```

**basis ()**

Returns a basis of *self*.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.basis()
[(1, 0, 0, 0, 0, 1, 1), (0, 1, 0, 0, 1, 0, 1), (0, 0, 1, 0, 1, 1, 0), (0, 0, 0, 1, 1, 1, 1)]
```

**binomial\_moment** (*i*)

Returns the *i*-th binomial moment of the  $[n, k, d]_q$ -code *C*:

$$B_i(C) = \sum_{S, |S|=i} \frac{q^{k_S} - 1}{q - 1}$$

where  $k_S$  is the dimension of the shortened code  $C_{J-S}$ ,  $J = [1, 2, \dots, n]$ . (The normalized binomial moment is  $b_i(C) = \binom{n}{i}^{-1} B_i(C)$ .) In other words,  $C_{J-S}$  is isomorphic to the subcode of *C* of codewords supported on *S*.

## EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.binomial_moment(2)
0
sage: C.binomial_moment(4)      # long time
35
```

**Warning:** This is slow.

## REFERENCE:

- I. Duursma, “Combinatorics of the two-variable zeta function”, Finite fields and applications, 109-136, Lecture Notes in Comput. Sci., 2948, Springer, Berlin, 2004.

**canonical\_representative** (*equivalence*=‘semilinear’)

Compute a canonical orbit representative under the action of the semimonomial transformation group.

See [sage.coding.codecan.autgroup\\_can\\_label](#) for more details, for example if you would like to compute a canonical form under some more restrictive notion of equivalence, i.e. if you would like to restrict the permutation group to a Young subgroup.

## INPUT:

- equivalence* (optional) – which defines the acting group, either
  - permutational
  - linear
  - semilinear

## OUTPUT:

- a canonical representative of *self*
- a semimonomial transformation mapping *self* onto its representative

## EXAMPLES:

```
sage: F.<z> = GF(4)
sage: C = codes.HammingCode(F, 3)
sage: CanRep, transp = C.canonical_representative()
```

Check that the transporter element is correct:

```
sage: LinearCode(transp*C.generator_matrix()) == CanRep
True
```

Check if an equivalent code has the same canonical representative:

```
sage: f = F.hom([z**2])
sage: C_iso = LinearCode(C.generator_matrix().apply_map(f))
sage: CanRep_iso, _ = C_iso.canonical_representative()
sage: CanRep_iso == CanRep
True
```

Since applying the Frobenius automorphism could be extended to an automorphism of  $C$ , the following must also yield True:

```
sage: CanRep1, _ = C.canonical_representative("linear")
sage: CanRep2, _ = C_iso.canonical_representative("linear")
sage: CanRep2 == CanRep1
True
```

### **cardinality()**

Return the size of this code.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.cardinality()
16
sage: len(C)
16
```

### **characteristic()**

Returns the characteristic of the base ring of *self*.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.characteristic()
2
```

### **characteristic\_polynomial()**

Returns the characteristic polynomial of a linear code, as defined in van Lint's text [vL].

EXAMPLES:

```
sage: C = codes.ExtendedBinaryGolayCode()
sage: C.characteristic_polynomial()
-4/3*x^3 + 64*x^2 - 2816/3*x + 4096
```

REFERENCES:

- van Lint, Introduction to coding theory, 3rd ed., Springer-Verlag GTM, 86, 1999.

### **check\_mat(\*args, \*\*kws)**

Deprecated: Use `parity_check_matrix()` instead. See [trac ticket #17973](#) for details.

### **chinen\_polynomial()**

Returns the Chinen zeta polynomial of the code.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.chinen_polynomial() # long time
1/5*(2*sqrt(2)*t^3 + 2*sqrt(2)*t^2 + 2*t^2 + sqrt(2)*t + 2*t + 1)/(sqrt(2) + 1)
```



```
sage: C = codes.TernaryGolayCode()
sage: C.chinen_polynomial()          # long time
1/7*(3*sqrt(3)*t^3 + 3*sqrt(3)*t^2 + 3*t^2 + sqrt(3)*t + 3*t + 1)/(sqrt(3) + 1)
```

This last output agrees with the corresponding example given in Chinen’s paper below.

#### REFERENCES:

- Chinen, K. “An abundance of invariant polynomials satisfying the Riemann hypothesis”, April 2007 preprint.

#### **covering\_radius()**

Wraps Guava’s `CoveringRadius` command.

The covering radius of a linear code  $C$  is the smallest number  $r$  with the property that each element  $v$  of the ambient vector space of  $C$  has at most a distance  $r$  to the code  $C$ . So for each vector  $v$  there must be an element  $c$  of  $C$  with  $d(v, c) \leq r$ . A binary linear code with reasonable small covering radius is often referred to as a covering code.

For example, if  $C$  is a perfect code, the covering radius is equal to  $t$ , the number of errors the code can correct, where  $d = 2t + 1$ , with  $d$  the minimum distance of  $C$ .

#### EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 5)
sage: C.covering_radius()          # optional - gap_packages (Guava package)
1
```

#### **decode(right, algorithm='syndrome')**

Corrects the errors in `right` and returns a codeword.

##### INPUT:

- `right` – a vector of the same length as `self` over the base field of `self`
- `algorithm` – (default: 'syndrome') Name of the decoding algorithm which will be used to decode `right`. Can be 'syndrome' or 'nearest\_neighbor'.

---

**Note:** This is a deprecated method which will soon be removed from Sage. Please use `decode_to_code()` instead.

---

#### **decode\_to\_code(word, decoder\_name=None, \*\*kwargs)**

Corrects the errors in `word` and returns a codeword.

##### INPUT:

- `word` – a vector of the same length as `self` over the base field of `self`
- `decoder_name` – (default: None) Name of the decoder which will be used to decode `word`. The default decoder of `self` will be used if default value is kept.
- `kwargs` – all additional arguments are forwarded to `decoder()`

##### OUTPUT:

- A vector of `self`.

#### EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: word = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
```

```
sage: w_err = word + vector(GF(2), (1, 0, 0, 0, 0, 0, 0))
sage: C.decode_to_code(w_err)
(1, 1, 0, 0, 1, 1, 0)
```

It is possible to manually choose the decoder amongst the list of the available ones:

```
sage: C.decoders_available()
['Syndrome', 'NearestNeighbor']
sage: C.decode_to_code(w_err, 'NearestNeighbor')
(1, 1, 0, 0, 1, 1, 0)
```

**decode\_to\_message** (*word*, *decoder\_name=None*, *\*\*kwargs*)

Correct the errors in word and decodes it to the message space.

INPUT:

- *word* – a vector of the same length as *self* over the base field of *self*
- *decoder\_name* – (default: None) Name of the decoder which will be used to decode *word*. The default decoder of *self* will be used if default value is kept.
- *kwargs* – all additional arguments are forwarded to *decoder()*

OUTPUT:

- A vector of the message space of *self*.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: word = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
sage: C.decode_to_message(word)
(0, 1, 1, 0)
```

It is possible to manually choose the decoder amongst the list of the available ones:

```
sage: C.decoders_available()
['Syndrome', 'NearestNeighbor']
sage: C.decode_to_message(word, 'NearestNeighbor')
(0, 1, 1, 0)
```

**decoder** (*decoder\_name=None*, *\*\*kwargs*)

Return a decoder of *self*.

INPUT:

- *decoder\_name* – (default: None) name of the decoder which will be returned. The default decoder of *self* will be used if default value is kept.
- *kwargs* – all additional arguments will be forwarded to the constructor of the decoder that will be returned by this method

OUTPUT:

- a decoder object

Besides creating the decoder and returning it, this method also stores the decoder in a cache. With this behaviour, each decoder will be created at most one time for *self*.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
```

```
sage: C.decoder()
Syndrome decoder for Linear code of length 7, dimension 4 over Finite Field of size 2 handling
```

If the name of a decoder which is not known by `self` is passed, an exception will be raised:

```
sage: C.decoders_available()
['Syndrome', 'NearestNeighbor']
sage: C.decoder('Try')
Traceback (most recent call last):
...
ValueError: Passed Decoder name not known
```

### **decoders\_available** (*classes=False*)

Returns a list of the available decoders' names for `self`.

INPUT:

- `classes` – (default: `False`) if `classes` is set to `True`, it also returns the decoders' classes associated with the decoders' names.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: C.decoders_available()
['Syndrome', 'NearestNeighbor']

sage: C.decoders_available(True)
{'NearestNeighbor': <class 'sage.coding.linear_code.LinearCodeNearestNeighborDecoder'>,
 'Syndrome': <class 'sage.coding.linear_code.LinearCodeSyndromeDecoder'>}
```

### **dimension** ()

Returns the dimension of this code.

EXAMPLES:

```
sage: G = matrix(GF(2), [[1,0,0],[1,1,0]])
sage: C = LinearCode(G)
sage: C.dimension()
2
```

### **direct\_sum** (*other*)

Returns the code given by the direct sum of the codes `self` and `other`, which must be linear codes defined over the same base ring.

EXAMPLES:

```
sage: C1 = codes.HammingCode(GF(2), 3)
sage: C2 = C1.direct_sum(C1); C2
Linear code of length 14, dimension 8 over Finite Field of size 2
sage: C3 = C1.direct_sum(C2); C3
Linear code of length 21, dimension 12 over Finite Field of size 2
```

### **divisor** ()

Returns the divisor of a code, which is the smallest integer  $d_0 > 0$  such that each  $A_i > 0$  iff  $i$  is divisible by  $d_0$ .

EXAMPLES:

```
sage: C = codes.ExtendedBinaryGolayCode()
sage: C.divisor() # Type II self-dual
```

```

4
sage: C = codes.QuadraticResidueCodeEvenPair(17, GF(2))[0]
sage: C.divisor()
2

```

**dual\_code()**Returns the dual code  $C^\perp$  of the code  $C$ ,

$$C^\perp = \{v \in V \mid v \cdot c = 0, \forall c \in C\}.$$

EXAMPLES:

```

sage: C = codes.HammingCode(GF(2), 3)
sage: C.dual_code()
Linear code of length 7, dimension 3 over Finite Field of size 2
sage: C = codes.HammingCode(GF(4, 'a'), 3)
sage: C.dual_code()
Linear code of length 21, dimension 3 over Finite Field in a of size 2^2

```

**encode** (*word*, *encoder\_name=None*, *\*\*kwargs*)

Transforms an element of a message space into a codeword.

INPUT:

- *word* – a vector of a message space of the code.
- *encoder\_name* – (default: None) Name of the encoder which will be used to encode *word*. The default encoder of *self* will be used if default value is kept.
- *kwargs* – all additional arguments are forwarded to the construction of the encoder that is used.

---

**Note:** The default encoder always has  $F^k$  as message space, with  $k$  the dimension of *self* and  $F$  the base ring of *self*.

---

OUTPUT:

- a vector of *self*.

EXAMPLES:

```

sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: word = vector((0, 1, 1, 0))
sage: C.encode(word)
(1, 1, 0, 0, 1, 1, 0)

```

It is possible to manually choose the encoder amongst the list of the available ones:

```

sage: C.encoders_available()
['GeneratorMatrix']
sage: word = vector((0, 1, 1, 0))
sage: C.encode(word, 'GeneratorMatrix')
(1, 1, 0, 0, 1, 1, 0)

```

**encoder** (*encoder\_name=None*, *\*\*kwargs*)Returns an encoder of *self*.

The returned encoder provided by this method is cached.

This methods creates a new instance of the encoder subclass designated by `encoder_name`. While it is also possible to do the same by directly calling the subclass' constructor, it is strongly advised to use this method to take advantage of the caching mechanism.

INPUT:

- `encoder_name` – (default: None) name of the encoder which will be returned. The default encoder of `self` will be used if default value is kept.
- `kwargs` – all additional arguments are forwarded to the constructor of the encoder this method will return.

OUTPUT:

- an Encoder object.

---

**Note:** The default encoder always has  $F^k$  as message space, with  $k$  the dimension of `self` and  $F$  the base ring of `self`.

---

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: C.encoder()
Generator matrix-based encoder for Linear code of length 7, dimension 4 over Finite Field of
```

We check that the returned encoder is cached:

```
sage: C.encoder.is_in_cache()
True
```

If the name of an encoder which is not known by `self` is passed, an exception will be raised:

```
sage: C.encoders_available()
['GeneratorMatrix']
sage: C.encoder('NonExistingEncoder')
Traceback (most recent call last):
...
ValueError: Passed Encoder name not known
```

**encoders\_available** (*classes=False*)

Returns a list of the available encoders' names for `self`.

INPUT:

- `classes` – (default: False) if `classes` is set to True, it also returns the encoders' classes associated with the encoders' names.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: C.encoders_available()
['GeneratorMatrix']

sage: C.encoders_available(True)
{'GeneratorMatrix':
<class 'sage.coding.linear_code.LinearCodeGeneratorMatrixEncoder'>}
```

**extended\_code** ()

If `self` is a linear code of length  $n$  defined over  $F$  then this returns the code of length  $n + 1$  where the

last digit  $c_n$  satisfies the check condition  $c_0 + \dots + c_n = 0$ . If `self` is an  $[n, k, d]$  binary code then the extended code  $C^\vee$  is an  $[n+1, k, d^\vee]$  code, where  $d^\vee = d$  (if  $d$  is even) and  $d^\vee = d+1$  (if  $d$  is odd).

EXAMPLES:

```
sage: C = codes.HammingCode(GF(4, 'a'), 3)
sage: C
[21, 18] Hamming Code over Finite Field in a of size 2^2
sage: Cx = C.extended_code()
sage: Cx
Linear code of length 22, dimension 18 over Finite Field in a of size 2^2
```

**galois\_closure** ( $F_0$ )

If `self` is a linear code defined over  $F$  and  $F_0$  is a subfield with Galois group  $G = \text{Gal}(F/F_0)$  then this returns the  $G$ -module  $C^-$  containing  $C$ .

EXAMPLES:

```
sage: C = codes.HammingCode(GF(4, 'a'), 3)
sage: Cc = C.galois_closure(GF(2))
sage: C; Cc
[21, 18] Hamming Code over Finite Field in a of size 2^2
Linear code of length 21, dimension 20 over Finite Field in a of size 2^2
sage: c = C.basis()[2]
sage: V = VectorSpace(GF(4, 'a'), 21)
sage: c2 = V([x^2 for x in c.list()])
sage: c2 in C
False
sage: c2 in Cc
True
```

**gen\_mat** (\*args, \*\*kws)

Deprecated: Use `generator_matrix()` instead. See [trac ticket #17973](#) for details.

**gen\_mat\_systematic** (\*args, \*\*kws)

Deprecated: Use `generator_matrix_systematic()` instead. See [trac ticket #17973](#) for details.

**generator\_matrix** (encoder\_name=None, \*\*kwargs)

Returns a generator matrix of `self`.

INPUT:

- `encoder_name` – (default: None) name of the encoder which will be used to compute the generator matrix. The default encoder of `self` will be used if default value is kept.
- `kwargs` – all additional arguments are forwarded to the construction of the encoder that is used.

EXAMPLES:

```
sage: G = matrix(GF(3), 2, [1, -1, 1, -1, 1, 1])
sage: code = LinearCode(G)
sage: code.generator_matrix()
[1 2 1]
[2 1 1]
```

**generator\_matrix\_systematic** ()

Return a systematic generator matrix of the code.

A generator matrix of a code is called systematic if it contains a set of columns forming an identity matrix.

EXAMPLES:

```

sage: G = matrix(GF(3), 2, [1, -1, 1, -1, 1, 1])
sage: code = LinearCode(G)
sage: code.generator_matrix()
[1 2 1]
[2 1 1]
sage: code.generator_matrix_systematic()
[1 2 0]
[0 0 1]

```

**gens()**

Returns the generators of this code as a list of vectors.

**EXAMPLES:**

```

sage: C = codes.HammingCode(GF(2), 3)
sage: C.gens()
[(1, 0, 0, 0, 0, 1, 1), (0, 1, 0, 0, 1, 0, 1), (0, 0, 1, 0, 1, 1, 0), (0, 0, 0, 1, 1, 1, 1)]

```

**genus()**

Returns the “Duursma genus” of the code,  $\gamma_C = n + 1 - k - d$ .

**EXAMPLES:**

```

sage: C1 = codes.HammingCode(GF(2), 3); C1
[7, 4] Hamming Code over Finite Field of size 2
sage: C1.genus()
1
sage: C2 = codes.HammingCode(GF(4, "a"), 2); C2
[5, 3] Hamming Code over Finite Field in a of size 2^2
sage: C2.genus()
0

```

Since all Hamming codes have minimum distance 3, these computations agree with the definition,  $n + 1 - k - d$ .

**information\_set()**

Return an information set of the code.

Return value of this method is cached.

A set of column positions of a generator matrix of a code is called an information set if the corresponding columns form a square matrix of full rank.

**OUTPUT:**

- Information set of a systematic generator matrix of the code.

**EXAMPLES:**

```

sage: G = matrix(GF(3), 2, [1, -1, 0, -1, 1, 1])
sage: code = LinearCode(G)
sage: code.generator_matrix_systematic()
[1 2 0]
[0 0 1]
sage: code.information_set()
(0, 2)

```

**is\_galois\_closed()**

Checks if `self` is equal to its Galois closure.

**EXAMPLES:**

```
sage: C = codes.HammingCode(GF(4, "a"), 3)
sage: C.is_galois_closed()
False
```

**is\_permutation\_automorphism(*g*)**

Returns 1 if  $g$  is an element of  $S_n$  ( $n = \text{length of self}$ ) and if  $g$  is an automorphism of self.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(3), 3)
sage: g = SymmetricGroup(13).random_element()
sage: C.is_permutation_automorphism(g)
0
sage: MS = MatrixSpace(GF(2), 4, 8)
sage: G = MS([[1, 0, 0, 0, 1, 1, 1, 0], [0, 1, 1, 1, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 1], [0, 0, 0, 0, 0, 1, 0, 0]])
sage: C = LinearCode(G)
sage: S8 = SymmetricGroup(8)
sage: g = S8("(2, 3)")
sage: C.is_permutation_automorphism(g)
1
sage: g = S8("(1, 2, 3, 4)")
sage: C.is_permutation_automorphism(g)
0
```

**is\_permutation\_equivalent(*other*, *algorithm=None*)**

Returns True if self and other are permutation equivalent codes and False otherwise.

The `algorithm="verbose"` option also returns a permutation (if True) sending self to other.

Uses Robert Miller's double coset partition refinement work.

EXAMPLES:

```
sage: P.<x> = PolynomialRing(GF(2), "x")
sage: g = x^3+x+1
sage: C1 = codes.CyclicCodeFromGeneratingPolynomial(7, g); C1
Linear code of length 7, dimension 4 over Finite Field of size 2
sage: C2 = codes.HammingCode(GF(2), 3); C2
[7, 4] Hamming Code over Finite Field of size 2
sage: C1.is_permutation_equivalent(C2)
True
sage: C1.is_permutation_equivalent(C2, algorithm="verbose")
(True, (3, 4) (5, 7, 6))
sage: C1 = codes.RandomLinearCode(10, 5, GF(2))
sage: C2 = codes.RandomLinearCode(10, 5, GF(3))
sage: C1.is_permutation_equivalent(C2)
False
```

**is\_projective()**

Test whether the code is projective.

A linear code  $C$  over a field is called *projective* when its dual  $C^\perp$  has minimum weight  $\geq 3$ , i.e. when no two coordinate positions of  $C$  are linearly independent (cf. definition 3 from [BS11] or 9.8.1 from [BH12]).

EXAMPLE:

```
sage: C = codes.BinaryGolayCode()
sage: C.is_projective()
True
```



```
sage: C.dual_code().minimum_distance()
8
```

A non-projective code:

```
sage: C = codes.LinearCode(matrix(GF(2), [[1,0,1],[1,1,1]]))
sage: C.is_projective()
False
```

REFERENCE:

**is\_self\_dual()**

Returns True if the code is self-dual (in the usual Hamming inner product) and False otherwise.

EXAMPLES:

```
sage: C = codes.ExtendedBinaryGolayCode()
sage: C.is_self_dual()
True
sage: C = codes.HammingCode(GF(2), 3)
sage: C.is_self_dual()
False
```

**is\_self\_orthogonal()**

Returns True if this code is self-orthogonal and False otherwise.

A code is self-orthogonal if it is a subcode of its dual.

EXAMPLES:

```
sage: C = codes.ExtendedBinaryGolayCode()
sage: C.is_self_orthogonal()
True
sage: C = codes.HammingCode(GF(2), 3)
sage: C.is_self_orthogonal()
False
sage: C = codes.QuasiQuadraticResidueCode(11) # optional - gap_packages (Guava package)
sage: C.is_self_orthogonal() # optional - gap_packages (Guava package)
True
```

**is\_subcode(other)**

Returns True if self is a subcode of other.

EXAMPLES:

```
sage: C1 = codes.HammingCode(GF(2), 3)
sage: G1 = C1.generator_matrix()
sage: G2 = G1.matrix_from_rows([0,1,2])
sage: C2 = LinearCode(G2)
sage: C2.is_subcode(C1)
True
sage: C1.is_subcode(C2)
False
sage: C3 = C1.extended_code()
sage: C1.is_subcode(C3)
False
sage: C4 = C1.punctured([1])
sage: C4.is_subcode(C1)
False
sage: C5 = C1.shortened([1])
sage: C5.is_subcode(C1)
```

```

False
sage: C1 = codes.HammingCode(GF(9, "z"), 3)
sage: G1 = C1.generator_matrix()
sage: G2 = G1.matrix_from_rows([0, 1, 2])
sage: C2 = LinearCode(G2)
sage: C2.is_subcode(C1)
True

```

**length()**

Returns the length of this code.

**EXAMPLES:**

```

sage: C = codes.HammingCode(GF(2), 3)
sage: C.length()
7

```

**list()**

Return a list of all elements of this linear code.

**EXAMPLES:**

```

sage: C = codes.HammingCode(GF(2), 3)
sage: Clist = C.list()
sage: Clist[5]; Clist[5] in C
(1, 0, 1, 0, 1, 0, 1)
True

```

**minimum\_distance** (*algorithm=None*)

Returns the minimum distance of this linear code.

By default, this uses a GAP kernel function (in C and not part of Guava) written by Steve Linton. If `algorithm="guava"` is set and  $q$  is 2 or 3 then this uses a very fast program written in C written by CJ Tjhal. (This is much faster, except in some small examples.)

Raises a `ValueError` in case there is no non-zero vector in this linear code.

The minimum distance of the code is stored once it has been computed or provided during the initialization of `LinearCode`. If `algorithm` is `None` and the stored value of minimum distance is found, then the stored value will be returned without recomputing the minimum distance again.

**INPUT:**

- `algorithm` - Method to be used, `None`, `"gap"`, or `"guava"` (default: `None`).

**OUTPUT:**

- Integer, minimum distance of this code

**EXAMPLES:**

```

sage: MS = MatrixSpace(GF(3), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: C.minimum_distance()
3

```

Once the minimum distance has been computed, it's value is stored. Hence the following command will return the value instantly, without further computations.:

```

sage: C.minimum_distance()
3

```

If algorithm is provided, then the minimum distance will be recomputed even if there is a stored value from a previous run.:

```
sage: C.minimum_distance(algorithm="gap")
3
sage: C.minimum_distance(algorithm="guava") # optional - gap_packages (Guava package)
3
```

Another example.:

```
sage: C = codes.HammingCode(GF(4,"a"), 2); C
[5, 3] Hamming Code over Finite Field in a of size 2^2
sage: C.minimum_distance()
3
```

TESTS:

```
sage: C = codes.RandomLinearCode(5, 2, GF(4,"a"))
sage: C.minimum_distance(algorithm='something')
Traceback (most recent call last):
...
ValueError: The algorithm argument must be one of None, 'gap' or 'guava'; got 'something'
```

**module\_composition\_factors(gp)**

Prints the GAP record of the Meataxe composition factors module in Meataxe notation. This uses GAP but not Guava.

EXAMPLES:

```
sage: MS = MatrixSpace(GF(2), 4, 8)
sage: G = MS([[1, 0, 0, 0, 1, 1, 1, 0], [0, 1, 1, 1, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 1], [0, 0, 0, 0, 0, 1, 0, 0]])
sage: C = LinearCode(G)
sage: gp = C.permutation_automorphism_group()
```

Now type “C.module\_composition\_factors(gp)” to get the record printed.

**parity\_check\_matrix()**

Returns the parity check matrix of self.

The parity check matrix of a linear code  $C$  corresponds to the generator matrix of the dual code of  $C$ .

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: Cperp = C.dual_code()
sage: C; Cperp
[7, 4] Hamming Code over Finite Field of size 2
Linear code of length 7, dimension 3 over Finite Field of size 2
sage: C.generator_matrix()
[1 0 0 0 0 1 1]
[0 1 0 0 1 0 1]
[0 0 1 0 1 1 0]
[0 0 0 1 1 1 1]
sage: C.parity_check_matrix()
[1 0 1 0 1 0 1]
[0 1 1 0 0 1 1]
[0 0 0 1 1 1 1]
sage: Cperp.parity_check_matrix()
[1 0 0 0 0 1 1]
[0 1 0 0 1 0 1]
[0 0 1 0 1 1 0]
[0 0 0 1 1 1 1]
```

```
sage: Cperp.generator_matrix()
[1 0 1 0 1 0 1]
[0 1 1 0 0 1 1]
[0 0 0 1 1 1 1]
```

### **permutation\_automorphism\_group** (*algorithm='partition'*)

If  $C$  is an  $[n, k, d]$  code over  $F$ , this function computes the subgroup  $\text{Aut}(C) \subset S_n$  of all permutation automorphisms of  $C$ . The binary case always uses the (default) partition refinement algorithm of Robert Miller.

Note that if the base ring of  $C$  is  $GF(2)$  then this is the full automorphism group. Otherwise, you could use `automorphism_group_gens()` to compute generators of the full automorphism group.

INPUT:

- **algorithm** - If "gap" then GAP's MatrixAutomorphism function (written by Thomas Breuer) is used. The implementation combines an idea of mine with an improvement suggested by Cary Huffman. If "gap+verbose" then code-theoretic data is printed out at several stages of the computation. If "partition" then the (default) partition refinement algorithm of Robert Miller is used. Finally, if "codecan" then the partition refinement algorithm of Thomas Feulner is used, which also computes a canonical representative of self (call `canonical_representative()` to access it).

OUTPUT:

- Permutation automorphism group

EXAMPLES:

```
sage: MS = MatrixSpace(GF(2), 4, 8)
sage: G = MS([[1, 0, 0, 0, 1, 1, 1, 0], [0, 1, 1, 1, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 1], [0, 0, 0, 0, 0, 1, 0, 0]])
sage: C = LinearCode(G)
sage: C
Linear code of length 8, dimension 4 over Finite Field of size 2
sage: G = C.permutation_automorphism_group()
sage: G.order()
144
sage: GG = C.permutation_automorphism_group("codecan")
sage: GG == G
True
```

A less easy example involves showing that the permutation automorphism group of the extended ternary Golay code is the Mathieu group  $M_{11}$ .

```
sage: C = codes.ExtendedTernaryGolayCode()
sage: M11 = MathieuGroup(11)
sage: M11.order()
7920
sage: G = C.permutation_automorphism_group() # long time (6s on sage.math, 2011)
sage: G.is_isomorphic(M11) # long time
True
sage: GG = C.permutation_automorphism_group("codecan") # long time
sage: GG == G # long time
True
```

Other examples:

```
sage: C = codes.ExtendedBinaryGolayCode()
sage: G = C.permutation_automorphism_group()
sage: G.order()
244823040
```

```

sage: C = codes.HammingCode(GF(2), 5)
sage: G = C.permutation_automorphism_group()
sage: G.order()
9999360
sage: C = codes.HammingCode(GF(3), 2); C
[4, 2] Hamming Code over Finite Field of size 3
sage: C.permutation_automorphism_group(algorithm="partition")
Permutation Group with generators [(1,3,4)]
sage: C = codes.HammingCode(GF(4,"z"), 2); C
[5, 3] Hamming Code over Finite Field in z of size 2^2
sage: G = C.permutation_automorphism_group(algorithm="partition"); G
Permutation Group with generators [(1,3)(4,5), (1,4)(3,5)]
sage: GG = C.permutation_automorphism_group(algorithm="codecan") # long time
sage: GG == G # long time
True
sage: C.permutation_automorphism_group(algorithm="gap") # optional - gap_packages (Guava pa
Permutation Group with generators [(1,3)(4,5), (1,4)(3,5)]
sage: C = codes.TernaryGolayCode()
sage: C.permutation_automorphism_group(algorithm="gap") # optional - gap_packages (Guava pa
Permutation Group with generators [(3,4)(5,7)(6,9)(8,11), (3,5,8)(4,11,7)(6,9,10), (2,3)(4,6)

```

However, the option `algorithm="gap+verbose"`, will print out:

```

Minimum distance: 5 Weight distribution: [1, 0, 0, 0, 0, 132, 132,
0, 330, 110, 0, 24]

```

```

Using the 132 codewords of weight 5 Supergroup size: 39916800

```

in addition to the output of `C.permutation_automorphism_group(algorithm="gap")`.

#### **permuted\_code(p)**

Returns the permuted code, which is equivalent to `self` via the column permutation `p`.

EXAMPLES:

```

sage: C = codes.HammingCode(GF(2), 3)
sage: G = C.permutation_automorphism_group(); G
Permutation Group with generators [(4,5)(6,7), (4,6)(5,7), (2,3)(6,7), (2,4)(3,5), (1,2)(5,6)]
sage: g = G("(2,3)(6,7)")
sage: Cg = C.permuted_code(g)
sage: Cg
Linear code of length 7, dimension 4 over Finite Field of size 2
sage: C.generator_matrix() == Cg.generator_matrix_systematic()
True

```

#### **punctured(L)**

Returns the code punctured at the positions  $L$ ,  $L \subset \{1, 2, \dots, n\}$ . If this code  $C$  is of length  $n$  in  $\text{GF}(q)$  then the code  $C^L$  obtained from  $C$  by puncturing at the positions in  $L$  is the code of length  $n - |L|$  consisting of codewords of  $C$  which have their  $i$ -th coordinate deleted if  $i \in L$  and left alone if  $i \notin L$ :

$$C^L = \{(c_{i_1}, \dots, c_{i_N}) \mid (c_1, \dots, c_n) \in C\},$$

where  $\{1, 2, \dots, n\} - T = \{i_1, \dots, i_N\}$ . In particular, if  $L = \{j\}$  then  $C^L$  is simply the code obtained from  $C$  by deleting the  $j$ -th coordinate of each codeword. The code  $C^L$  is called the punctured code at  $L$ . The dimension of  $C^L$  can decrease if  $|L| > d - 1$ .

INPUT:

- $L$  - Subset of  $\{1, \dots, n\}$ , where  $n$  is the length of `self`

OUTPUT:

- Linear code, the punctured code described above

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.punctured([1,2])
Linear code of length 5, dimension 4 over Finite Field of size 2
```

**random\_element** (\*args, \*\*kws)

Returns a random codeword; passes other positional and keyword arguments to `random_element()` method of vector space.

OUTPUT:

- Random element of the vector space of this code

EXAMPLES:

```
sage: C = codes.HammingCode(GF(4, 'a'), 3)
sage: C.random_element() # random test
(1, 0, 0, a + 1, 1, a, a, a + 1, a + 1, 1, 1, 0, a + 1, a, 0, a, a, 0, a, a, 1)
```

Passes extra positional or keyword arguments through:

```
sage: C.random_element(prob=.5, distribution='1/n') # random test
(1, 0, a, 0, 0, 0, 0, 0, a + 1, 0, 0, 0, 0, 0, 0, 0, 0, a + 1, a + 1, 1, 0, 0)
```

TESTS:

Test that the codeword returned is immutable (see [trac ticket #16469](#)):

```
sage: c = C.random_element()
sage: c.is_immutable()
True
```

Test that codeword returned has the same parent as any non-random codeword (see [trac ticket #19653](#)):

```
sage: C = codes.RandomLinearCode(10, 4, GF(16, 'a'))
sage: c1 = C.random_element()
sage: c2 = C[1]
sage: c1.parent() == c2.parent()
True
```

**redundancy\_matrix** (C)

If C is a linear  $[n,k,d]$  code then this function returns a  $k \times (n - k)$  matrix A such that  $G = (I, A)$  generates a code (in standard form) equivalent to C. If C is already in standard form and  $G = (I, A)$  is its generator matrix then this function simply returns that A.

OUTPUT:

- Matrix, the redundancy matrix

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.generator_matrix()
[1 0 0 0 0 1 1]
[0 1 0 0 1 0 1]
[0 0 1 0 1 1 0]
[0 0 0 1 1 1 1]
sage: C.redundancy_matrix()
[0 1 1]
```

```

[1 0 1]
[1 1 0]
[1 1 1]
sage: C.standard_form()[0].generator_matrix()
[1 0 0 0 0 1 1]
[0 1 0 0 1 0 1]
[0 0 1 0 1 1 0]
[0 0 0 1 1 1 1]
sage: C = codes.HammingCode(GF(3), 2)
sage: C.generator_matrix()
[1 0 1 1]
[0 1 1 2]
sage: C.redundancy_matrix()
[1 1]
[1 2]

```

**sd\_duursma\_data**(*C*, *i*)

Returns the Duursma data  $v$  and  $m$  of this formally s.d. code  $C$  and the type number  $i$  in (1,2,3,4). Does *not* check if this code is actually sd.

INPUT:

- $i$  - Type number

OUTPUT:

- Pair  $(v, m)$  as in Duursma [D]

REFERENCES:

EXAMPLES:

```

sage: MS = MatrixSpace(GF(2), 2, 4)
sage: G = MS([1, 1, 0, 0, 0, 0, 1, 1])
sage: C = LinearCode(G)
sage: C == C.dual_code() # checks that C is self dual
True
sage: for i in [1, 2, 3, 4]: print C.sd_duursma_data(i)
[2, -1]
[2, -3]
[2, -2]
[2, -1]

```

**sd\_duursma\_q**(*C*, *i*, *d0*)

INPUT:

- $C$  - sd code; does *not* check if  $C$  is actually an sd code
- $i$  - Type number, one of 1,2,3,4
- $d0$  - Divisor, the smallest integer such that each  $A_i > 0$  iff  $i$  is divisible by  $d0$

OUTPUT:

- Coefficients  $q_0, q_1, \dots$  of  $q(T)$  as in Duursma [D]

REFERENCES:

- [D] - I. Duursma, “Extremal weight enumerators and ultraspherical polynomials”

EXAMPLES:

```

sage: C1 = codes.HammingCode(GF(2), 3)
sage: C2 = C1.extended_code(); C2
Linear code of length 8, dimension 4 over Finite Field of size 2
sage: C2.is_self_dual()
True
sage: C2.sd_duursma_q(1,1)
2/5*T^2 + 2/5*T + 1/5
sage: C2.sd_duursma_q(3,1)
3/5*T^4 + 1/5*T^3 + 1/15*T^2 + 1/15*T + 1/15

```

**sd\_zeta\_polynomial** (*C*, *typ=1*)

Returns the Duursma zeta function of a self-dual code using the construction in [D].

INPUT:

- *typ* - Integer, type of this s.d. code; one of 1,2,3, or 4 (default: 1)

OUTPUT:

- Polynomial

EXAMPLES:

```

sage: C1 = codes.HammingCode(GF(2), 3)
sage: C2 = C1.extended_code(); C2
Linear code of length 8, dimension 4 over Finite Field of size 2
sage: C2.is_self_dual()
True
sage: C2.sd_zeta_polynomial()
2/5*T^2 + 2/5*T + 1/5
sage: C2.zeta_polynomial()
2/5*T^2 + 2/5*T + 1/5
sage: P = C2.sd_zeta_polynomial(); P(1)
1
sage: F.<z> = GF(4, "z")
sage: MS = MatrixSpace(F, 3, 6)
sage: G = MS([[1,0,0,1,z,z],[0,1,0,z,1,z],[0,0,1,z,z,1]])
sage: C = LinearCode(G) # the "hexacode"
sage: C.sd_zeta_polynomial(4)
1

```

It is a general fact about Duursma zeta polynomials that  $P(1) = 1$ .

REFERENCES:

- [D] I. Duursma, “Extremal weight enumerators and ultraspherical polynomials”

**shortened** (*L*)

Returns the code shortened at the positions *L*, where  $L \subset \{1, 2, \dots, n\}$ .

Consider the subcode  $C(L)$  consisting of all codewords  $c \in C$  which satisfy  $c_i = 0$  for all  $i \in L$ . The punctured code  $C(L)^L$  is called the shortened code on *L* and is denoted  $C_L$ . The code constructed is actually only isomorphic to the shortened code defined in this way.

By Theorem 1.5.7 in [HP],  $C_L$  is  $((C^\perp)^L)^\perp$ . This is used in the construction below.

INPUT:

- *L* - Subset of  $\{1, \dots, n\}$ , where *n* is the length of this code

OUTPUT:

- Linear code, the shortened code described above



## EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.shortened([1,2])
Linear code of length 5, dimension 2 over Finite Field of size 2
```

**spectrum**(algorithm=None)

Returns the spectrum of self as a list.

The default algorithm uses a GAP kernel function (in C) written by Steve Linton.

## INPUT:

- algorithm-None, "gap", "leon", or "binary"; defaults to "gap" except in the binary case. If "gap" then uses the GAP function, if "leon" then uses Jeffrey Leon's software via Guava, and if "binary" then uses Sage native Cython code
- List, the spectrum

The optional algorithm ("leon") may create a stack smashing error and a traceback but should return the correct answer. It appears to run much faster than the GAP algorithm in some small examples and much slower than the GAP algorithm in other larger examples.

## EXAMPLES:

```
sage: MS = MatrixSpace(GF(2), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: C.spectrum()
[1, 0, 0, 7, 7, 0, 0, 1]
sage: F.<z> = GF(2^2, "z")
sage: C = codes.HammingCode(F, 2); C
[5, 3] Hamming Code over Finite Field in z of size 2^2
sage: C.spectrum()
[1, 0, 0, 30, 15, 18]
sage: C = codes.HammingCode(GF(2), 3); C
[7, 4] Hamming Code over Finite Field of size 2
sage: C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C.spectrum(algorithm="gap")
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C.spectrum(algorithm="binary")
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C = codes.HammingCode(GF(3), 3); C
[13, 10] Hamming Code over Finite Field of size 3
sage: C.spectrum() == C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
True
sage: C = codes.HammingCode(GF(5), 2); C
[6, 4] Hamming Code over Finite Field of size 5
sage: C.spectrum() == C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
True
sage: C = codes.HammingCode(GF(7), 2); C
[8, 6] Hamming Code over Finite Field of size 7
sage: C.spectrum() == C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
True
```

**standard\_form**()

Returns the standard form of this linear code.

An  $[n, k]$  linear code with generator matrix  $G$  in standard form is the row-reduced echelon form of  $G$  is  $(I, A)$ , where  $I$  denotes the  $k \times k$  identity matrix and  $A$  is a  $k \times (n - k)$  block. This method returns a

pair  $(C, p)$  where  $C$  is a code permutation equivalent to `self` and  $p$  in  $S_n$ , with  $n$  the length of  $C$ , is the permutation sending `self` to  $C$ . This does not call GAP.

Thanks to Frank Luebeck for (the GAP version of) this code.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.generator_matrix()
[1 0 0 0 0 1 1]
[0 1 0 0 1 0 1]
[0 0 1 0 1 1 0]
[0 0 0 1 1 1 1]
sage: Cs, p = C.standard_form()
sage: p
()
sage: MS = MatrixSpace(GF(3), 3, 7)
sage: G = MS([[1, 0, 0, 0, 1, 1, 0], [0, 1, 0, 1, 0, 1, 0], [0, 0, 0, 0, 0, 0, 1]])
sage: C = LinearCode(G)
sage: Cs, p = C.standard_form()
sage: p
(3, 7)
sage: Cs.generator_matrix()
[1 0 0 0 1 1 0]
[0 1 0 1 0 1 0]
[0 0 1 0 0 0 0]
```

**support()**

Returns the set of indices  $j$  where  $A_j$  is nonzero, where  $\text{spectrum}(\text{self}) = [A_0, A_1, \dots, A_n]$ .

OUTPUT:

- List of integers

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.spectrum()
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C.support()
[0, 3, 4, 7]
```

**syndrome(r)**

Returns the syndrome of  $r$ .

The syndrome of  $r$  is the result of  $H \times r$  where  $H$  is the parity check matrix of `self`. If  $r$  belongs to `self`, its syndrome equals to the zero vector.

INPUT:

- $r$  – a vector of the same length as `self`

OUTPUT:

- a column vector

EXAMPLES:

```
sage: MS = MatrixSpace(GF(2), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: r = vector(GF(2), (1, 0, 1, 0, 1, 0, 1))
sage: r in C
True
```

```
sage: C.syndrome(r)
(0, 0, 0)
```

If `r` is not a codeword, its syndrome is not equal to zero:

```
sage: r = vector(GF(2), (1, 0, 1, 0, 1, 1, 1))
sage: r in C
False
sage: C.syndrome(r)
(0, 1, 1)
```

Syndrome computation works fine on bigger fields:

```
sage: C = codes.RandomLinearCode(12, 4, GF(59))
sage: r = C.random_element()
sage: C.syndrome(r)
(0, 0, 0, 0, 0, 0, 0, 0, 0)
```

**unencode** (*c*, *encoder\_name=None*, *nocheck=False*, *\*\*kwargs*)

Returns the message corresponding to *c*.

This is the inverse of `encode()`.

INPUT:

- *c* – a codeword of `self`.
- *encoder\_name* – (default: `None`) name of the decoder which will be used to decode `word`. The default decoder of `self` will be used if default value is kept.
- *nocheck* – (default: `False`) checks if *c* is in `self`. You might set this to `True` to disable the check for saving computation. Note that if *c* is not in `self` and *nocheck* = `True`, then the output of `unencode()` is not defined (except that it will be in the message space of `self`).
- *kwargs* – all additional arguments are forwarded to the construction of the encoder that is used.

OUTPUT:

- an element of the message space of *encoder\_name* of `self`.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: c = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
sage: C.unencode(c)
(0, 1, 1, 0)
```

**weight\_distribution** (*algorithm=None*)

Returns the spectrum of `self` as a list.

The default algorithm uses a GAP kernel function (in C) written by Steve Linton.

INPUT:

- *algorithm* – `None`, "gap", "leon", or "binary"; defaults to "gap" except in the binary case. If "gap" then uses the GAP function, if "leon" then uses Jeffrey Leon's software via Guava, and if "binary" then uses Sage native Cython code
- List, the spectrum

The optional algorithm ("leon") may create a stack smashing error and a traceback but should return the correct answer. It appears to run much faster than the GAP algorithm in some small examples and much slower than the GAP algorithm in other larger examples.

EXAMPLES:

```
sage: MS = MatrixSpace(GF(2), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: C.spectrum()
[1, 0, 0, 7, 7, 0, 0, 1]
sage: F.<z> = GF(2^2, "z")
sage: C = codes.HammingCode(F, 2); C
[5, 3] Hamming Code over Finite Field in z of size 2^2
sage: C.spectrum()
[1, 0, 0, 30, 15, 18]
sage: C = codes.HammingCode(GF(2), 3); C
[7, 4] Hamming Code over Finite Field of size 2
sage: C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C.spectrum(algorithm="gap")
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C.spectrum(algorithm="binary")
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C = codes.HammingCode(GF(3), 3); C
[13, 10] Hamming Code over Finite Field of size 3
sage: C.spectrum() == C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
True
sage: C = codes.HammingCode(GF(5), 2); C
[6, 4] Hamming Code over Finite Field of size 5
sage: C.spectrum() == C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
True
sage: C = codes.HammingCode(GF(7), 2); C
[8, 6] Hamming Code over Finite Field of size 7
sage: C.spectrum() == C.spectrum(algorithm="leon") # optional - gap_packages (Guava package)
True
```

**weight\_enumerator** (names='xy', name2=None)

Returns the weight enumerator of the code.

INPUT:

- names - String of length 2, containing two variable names (default: "xy"). Alternatively, it can be a variable name or a string, or a tuple of variable names or strings.
- name2 - string or symbolic variable (default: None). If name2 is provided then it is assumed that names contains only one variable.

OUTPUT:

- Polynomial over  $\mathbb{Q}$

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.weight_enumerator()
x^7 + 7*x^4*y^3 + 7*x^3*y^4 + y^7
sage: C.weight_enumerator(names="st")
s^7 + 7*s^4*t^3 + 7*s^3*t^4 + t^7
sage: (var1, var2) = var('var1, var2')
sage: C.weight_enumerator((var1, var2))
var1^7 + 7*var1^4*var2^3 + 7*var1^3*var2^4 + var2^7
```

```
sage: C.weight_enumerator(var1, var2)
var1^7 + 7*var1^4*var2^3 + 7*var1^3*var2^4 + var2^7
```

**zero()**

Returns the zero vector of self.

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.zero()
(0, 0, 0, 0, 0, 0, 0)
sage: C.sum() # indirect doctest
(0, 0, 0, 0, 0, 0, 0)
sage: C.sum((C.gens())) # indirect doctest
(1, 1, 1, 1, 1, 1, 1)
```

**zeta\_function(name='T')**

Returns the Duursma zeta function of the code.

INPUT:

- name - String, variable name (default: "T")

OUTPUT:

- Element of  $\mathbb{Q}(T)$

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.zeta_function()
(2/5*T^2 + 2/5*T + 1/5)/(2*T^2 - 3*T + 1)
```

**zeta\_polynomial(name='T')**

Returns the Duursma zeta polynomial of this code.

Assumes that the minimum distances of this code and its dual are greater than 1. Prints a warning to stdout otherwise.

INPUT:

- name - String, variable name (default: "T")

OUTPUT:

- Polynomial over  $\mathbb{Q}$

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3)
sage: C.zeta_polynomial()
2/5*T^2 + 2/5*T + 1/5
sage: C = best_known_linear_code(6,3,GF(2)) # optional - gap_packages (Guava package)
sage: C.minimum_distance() # optional - gap_packages (Guava package)
3
sage: C.zeta_polynomial() # optional - gap_packages (Guava package)
2/5*T^2 + 2/5*T + 1/5
sage: C = codes.HammingCode(GF(2), 4)
sage: C.zeta_polynomial()
16/429*T^6 + 16/143*T^5 + 80/429*T^4 + 32/143*T^3 + 30/143*T^2 + 2/13*T + 1/13
sage: F.<z> = GF(4, "z")
sage: MS = MatrixSpace(F, 3, 6)
sage: G = MS([[1, 0, 0, 1, z, z], [0, 1, 0, z, 1, z], [0, 0, 1, z, z, 1]])
```

```
sage: C = LinearCode(G) # the "hexacode"
sage: C.zeta_polynomial()
1
```

## REFERENCES:

- I. Duursma, “From weight enumerators to zeta functions”, in Discrete Applied Mathematics, vol. 111, no. 1-2, pp. 55-73, 2001.

**class** sage.coding.linear\_code.**LinearCode**(generator, d=None)

Bases: [sage.coding.linear\\_code.AbstractLinearCode](#)

Linear codes over a finite field or finite ring, represented using a generator matrix.

This class should be used for arbitrary and unstructured linear codes. This means that basic operations on the code, such as the computation of the minimum distance, will use generic, slow algorithms.

If you are looking for constructing a code from a more specific family, see if the family has been implemented by investigating *codes*. < tab >. These more specific classes use properties particular to that family to allow faster algorithms, and could also have family-specific methods.

See [Wikipedia article Linear\\_code](#) for more information on unstructured linear codes.

## INPUT:

- generator – a generator matrix over a finite field (G can be defined over a finite ring but the matrices over that ring must have certain attributes, such as rank); or a code over a finite field
- d – (optional, default: None) the minimum distance of the code

---

**Note:** The veracity of the minimum distance d, if provided, is not checked.

---

## EXAMPLES:

```
sage: MS = MatrixSpace(GF(2), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: C
Linear code of length 7, dimension 4 over Finite Field of size 2
sage: C.base_ring()
Finite Field of size 2
sage: C.dimension()
4
sage: C.length()
7
sage: C.minimum_distance()
3
sage: C.spectrum()
[1, 0, 0, 7, 7, 0, 0, 1]
sage: C.weight_distribution()
[1, 0, 0, 7, 7, 0, 0, 1]
```

The minimum distance of the code, if known, can be provided as an optional parameter.:

```
sage: C = LinearCode(G, d=3)
sage: C.minimum_distance()
3
```

Another example.:

```

sage: MS = MatrixSpace(GF(5), 4, 7)
sage: G = MS([[1, 1, 1, 0, 0, 0, 0], [1, 0, 0, 1, 1, 0, 0], [0, 1, 0, 1, 0, 1, 0], [1, 1, 0, 1, 0, 0, 1]])
sage: C = LinearCode(G)
sage: C
Linear code of length 7, dimension 4 over Finite Field of size 5

```

Providing a code as the parameter in order to “forget” its structure (see [trac ticket #20198](#)):

```

sage: C = codes.GeneralizedReedSolomonCode(GF(23).list(), 12)
sage: LinearCode(C)
Linear code of length 23, dimension 12 over Finite Field of size 23

```

Another example:

```

sage: C = codes.HammingCode(GF(7), 3)
sage: C
[57, 54] Hamming Code over Finite Field of size 7
sage: LinearCode(C)
Linear code of length 57, dimension 54 over Finite Field of size 7

```

#### AUTHORS:

- David Joyner (11-2005)
- Charles Prior (03-2016): [trac ticket #20198](#), `LinearCode` from a code

**generator\_matrix** (*encoder\_name=None*, *\*\*kwargs*)

Returns a generator matrix of self.

#### INPUT:

- encoder\_name* – (default: None) name of the encoder which will be used to compute the generator matrix. `self._generator_matrix` will be returned if default value is kept.
- kwargs* – all additional arguments are forwarded to the construction of the encoder that is used.

#### EXAMPLES:

```

sage: G = matrix(GF(3), 2, [1, -1, 1, -1, 1, 1])
sage: code = LinearCode(G)
sage: code.generator_matrix()
[1 2 1]
[2 1 1]

```

`sage.coding.linear_code.LinearCodeFromVectorSpace` (*V*, *d=None*)

Simply converts a vector subspace  $V$  of  $GF(q)^n$  into a *LinearCode*.

#### INPUT:

- V* – The vector space
- d* – (Optional, default: None) the minimum distance of the code, if known. This is an optional parameter.

---

**Note:** The veracity of the minimum distance *d*, if provided, is not checked.

---

#### EXAMPLES:

```

sage: V = VectorSpace(GF(2), 8)
sage: L = V.subspace([[1, 1, 1, 1, 0, 0, 0, 0], [0, 0, 0, 0, 1, 1, 1, 1]])
sage: C = LinearCodeFromVectorSpace(L)
sage: C.generator_matrix()

```

```
[1 1 1 1 0 0 0 0]
[0 0 0 0 1 1 1 1]
sage: C.minimum_distance()
4
```

Here, we provide the minimum distance of the code.:

```
sage: C = LinearCodeFromVectorSpace(L, d=4)
sage: C.minimum_distance()
4
```

**class** `sage.coding.linear_code.LinearCodeGeneratorMatrixEncoder` (*code*)

Bases: `sage.coding.encoder.Encoder`

Encoder based on `generator_matrix` for Linear codes.

This is the default encoder of a generic linear code, and should never be used for other codes than `LinearCode`.

INPUT:

- `code` – The associated `LinearCode` of this encoder.

**generator\_matrix** ()

Returns a generator matrix of the associated code of `self`.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: E = codes.encoders.LinearCodeGeneratorMatrixEncoder(C)
sage: E.generator_matrix()
[1 1 1 0 0 0 0]
[1 0 0 1 1 0 0]
[0 1 0 1 0 1 0]
[1 1 0 1 0 0 1]
```

**class** `sage.coding.linear_code.LinearCodeNearestNeighborDecoder` (*code*)

Bases: `sage.coding.decoder.Decoder`

Construct a decoder for Linear Codes. This decoder will decode to the nearest codeword found.

INPUT:

- `code` – A code associated to this decoder

**decode\_to\_code** (*r*)

Corrects the errors in `word` and returns a codeword.

INPUT:

- `r` – a codeword of `self`

OUTPUT:

- a vector of `self`'s message space

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeNearestNeighborDecoder(C)
sage: word = vector(GF(2), (1, 1, 0, 0, 1, 1, 0))
sage: w_err = word + vector(GF(2), (1, 0, 0, 0, 0, 0, 0))
sage: D.decode_to_code(w_err)
(1, 1, 0, 0, 1, 1, 0)
```



**decoding\_radius()**

Return maximal number of errors `self` can decode.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeNearestNeighborDecoder(C)
sage: D.decoding_radius()
1
```

**class** `sage.coding.linear_code.LinearCodeParityCheckEncoder`(*code*)

Bases: `sage.coding.encoder.Encoder`

Encoder based on `parity_check_matrix()` for Linear codes.

It constructs the generator matrix through the parity check matrix.

INPUT:

- `code` – The associated code of this encoder.

**generator\_matrix()**

Returns a generator matrix of the associated code of `self`.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: E = codes.encoders.LinearCodeParityCheckEncoder(C)
sage: E.generator_matrix()
[1 0 0 0 0 1 1]
[0 1 0 0 1 0 1]
[0 0 1 0 1 1 0]
[0 0 0 1 1 1 1]
```

**class** `sage.coding.linear_code.LinearCodeSyndromeDecoder`(*code*, *maximum\_error\_weight=None*)

Bases: `sage.coding.decoder.Decoder`

Constructs a decoder for Linear Codes based on syndrome lookup table.

The decoding algorithm works as follows:

- First, a lookup table is built by computing the syndrome of every error pattern of weight up to `maximum_error_weight`.
- Then, whenever one tries to decode a word `r`, the syndrome of `r` is computed. The corresponding error pattern is recovered from the pre-computed lookup table.
- Finally, the recovered error pattern is subtracted from `r` to recover the original word.

`maximum_error_weight` need never exceed the covering radius of the code, since there are then always lower-weight errors with the same syndrome. If one sets `maximum_error_weight` to a value greater than the covering radius, then the covering radius will be determined while building the lookup-table. This lower value is then returned if you query `decoding_radius` after construction.

If `maximum_error_weight` is left unspecified or set to a number at least the covering radius of the code, this decoder is complete, i.e. it decodes every vector in the ambient space.

NOTE:

Constructing the lookup table takes time exponential in the length of the code and the size of the code's base field. Afterwards, the individual decodings are fast.

INPUT:

- `code` – A code associated to this decoder
- `maximum_error_weight` – (default: None) the maximum number of errors to look for when building the table. An error is raised if it is set greater than  $n - k$ , since this is an upper bound on the covering radius on any linear code. If `maximum_error_weight` is kept unspecified, it will be set to  $n - k$ , where  $n$  is the length of `code` and  $k$  its dimension.

EXAMPLES:

```
sage: G = Matrix(GF(3), [[1,0,0,1,0,1,0,1,2],[0,1,0,2,2,0,1,1,0],[0,0,1,0,2,2,2,1,2]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeSyndromeDecoder(C)
sage: D
Syndrome decoder for Linear code of length 9, dimension 3 over Finite Field of size 3 handling e
```

If one wants to correct up to a lower number of errors, one can do as follows:

```
sage: D = codes.decoders.LinearCodeSyndromeDecoder(C, maximum_error_weight=2)
sage: D
Syndrome decoder for Linear code of length 9, dimension 3 over Finite Field of size 3 handling e
```

If one checks the list of types of this decoder before constructing it, one will notice it contains the keyword `dynamic`. Indeed, the behaviour of the syndrome decoder depends on the maximum error weight one wants to handle, and how it compares to the minimum distance and the covering radius of code. In the following examples, we illustrate this property by computing different instances of syndrome decoder for the same code.

We choose the following linear code, whose covering radius equals to 4 and minimum distance to 5 (half the minimum distance is 2):

```
sage: G = matrix(GF(5), [[1, 0, 0, 0, 0, 4, 3, 0, 3, 1, 0],
.....:                  [0, 1, 0, 0, 0, 3, 2, 2, 3, 2, 1],
.....:                  [0, 0, 1, 0, 0, 1, 3, 0, 1, 4, 1],
.....:                  [0, 0, 0, 1, 0, 3, 4, 2, 2, 3, 3],
.....:                  [0, 0, 0, 0, 1, 4, 2, 3, 2, 2, 1]])
sage: C = LinearCode(G)
```

In the following examples, we illustrate how the choice of `maximum_error_weight` influences the types of the instance of syndrome decoder, alongside with its decoding radius.

We build a first syndrome decoder, and pick a `maximum_error_weight` smaller than both the covering radius and half the minimum distance:

```
sage: D = C.decoder("Syndrome", maximum_error_weight = 1)
sage: D.decoder_type()
{'always-succeed', 'bounded_distance', 'hard-decision', 'unique'}
sage: D.decoding_radius()
1
```

In that case, we are sure the decoder will always succeed. It is also a bounded distance decoder.

We now build another syndrome decoder, and this time, `maximum_error_weight` is chosen to be bigger than half the minimum distance, but lower than the covering radius:

```
sage: D = C.decoder("Syndrome", maximum_error_weight = 3)
sage: D.decoder_type()
{'bounded_distance', 'hard-decision', 'might-error', 'unique'}
```

```
sage: D.decoding_radius()
3
```

Here, we still get a bounded distance decoder. But because we have a maximum error weight bigger than half the minimum distance, we know it might return a codeword which was not the original codeword.

And now, we build a third syndrome decoder, whose `maximum_error_weight` is bigger than both the covering radius and half the minimum distance:

```
sage: D = C.decoder("Syndrome", maximum_error_weight = 5)
sage: D.decoder_type()
{'complete', 'hard-decision', 'might-error', 'unique'}
sage: D.decoding_radius()
4
```

In that case, the decoder might still return an unexpected codeword, but it is now complete. Note the decoding radius is equal to 4: it was determined while building the syndrome lookup table that any error with weight more than 4 will be decoded incorrectly. That is because the covering radius for the code is 4.

The minimum distance and the covering radius are both determined while computing the syndrome lookup table. They user did not explicitly ask to compute these on the code `C`. The dynamic typing of the syndrome decoder might therefore seem slightly surprising, but in the end is quite informative.

#### `decode_to_code(r)`

Corrects the errors in `word` and returns a codeword.

INPUT:

- `r` – a codeword of `self`

OUTPUT:

- a vector of `self`'s message space

EXAMPLES:

```
sage: G = Matrix(GF(3), [
....:   [1, 0, 0, 0, 2, 2, 1, 1],
....:   [0, 1, 0, 0, 0, 0, 1, 1],
....:   [0, 0, 1, 0, 2, 0, 0, 2],
....:   [0, 0, 0, 1, 0, 2, 0, 1]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeSyndromeDecoder(C, maximum_error_weight = 2)
sage: Chan = channels.StaticErrorRateChannel(C.ambient_space(), 2)
sage: c = C.random_element()
sage: r = Chan(c)
sage: c == D.decode_to_code(r)
True
```

#### `decoding_radius()`

Returns the maximal number of errors a received word can have and for which `self` is guaranteed to return a most likely codeword.

EXAMPLES:

```
sage: G = Matrix(GF(3), [[1,0,0,1,0,1,0,1,2],[0,1,0,2,2,0,1,1,0],[0,0,1,0,2,2,2,1,2]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeSyndromeDecoder(C)
sage: D.decoding_radius()
4
```

**maximum\_error\_weight()**

Returns the maximal number of errors a received word can have and for which `self` is guaranteed to return a most likely codeword.

Same as `self.decoding_radius`.

EXAMPLES:

```
sage: G = Matrix(GF(3), [[1,0,0,1,0,1,0,1,2],[0,1,0,2,2,0,1,1,0],[0,0,1,0,2,2,2,1,2]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeSyndromeDecoder(C)
sage: D.maximum_error_weight()
4
```

**syndrome\_table()**

Returns the syndrome lookup table of `self`.

EXAMPLES:

```
sage: G = Matrix(GF(2), [[1,1,1,0,0,0,0],[1,0,0,1,1,0,0],[0,1,0,1,0,1,0],[1,1,0,1,0,0,1]])
sage: C = LinearCode(G)
sage: D = codes.decoders.LinearCodeSyndromeDecoder(C)
sage: D.syndrome_table()
{(0, 0, 0): (0, 0, 0, 0, 0, 0, 0),
 (1, 0, 0): (1, 0, 0, 0, 0, 0, 0),
 (0, 1, 0): (0, 1, 0, 0, 0, 0, 0),
 (1, 1, 0): (0, 0, 1, 0, 0, 0, 0),
 (0, 0, 1): (0, 0, 0, 1, 0, 0, 0),
 (1, 0, 1): (0, 0, 0, 0, 1, 0, 0),
 (0, 1, 1): (0, 0, 0, 0, 0, 1, 0),
 (1, 1, 1): (0, 0, 0, 0, 0, 0, 1)}
```

**sage.coding.linear\_code.best\_known\_linear\_code(n, k, F)**

Returns the best known (as of 11 May 2006) linear code of length `n`, dimension `k` over field `F`. The function uses the tables described in `bounds_minimum_distance` to construct this code.

This does not require an internet connection.

EXAMPLES:

```
sage: best_known_linear_code(10,5,GF(2)) # long time; optional - gap_packages (Guava package)
Linear code of length 10, dimension 5 over Finite Field of size 2
sage: gap.eval("C:=BestKnownLinearCode(10,5,GF(2))") # long time; optional - gap_packages (G
'a linear [10,5,4]2..4 shortened code'
```

This means that best possible binary linear code of length 10 and dimension 5 is a code with minimum distance 4 and covering radius somewhere between 2 and 4. Use `bounds_minimum_distance(10, 5, GF(2))` for further details.

**sage.coding.linear\_code.best\_known\_linear\_code\_www(n, k, F, verbose=False)**

Explains the construction of the best known linear code over `GF(q)` with length `n` and dimension `k`, courtesy of the `www` page <http://www.codetables.de/>.

INPUT:

- `n` - Integer, the length of the code
- `k` - Integer, the dimension of the code
- `F` - Finite field, of order 2, 3, 4, 5, 7, 8, or 9
- `verbose` - Bool (default: False)

OUTPUT:

- Text about why the bounds are as given

EXAMPLES:

```
sage: L = best_known_linear_code_www(72, 36, GF(2)) # optional - internet
sage: print L                                     # optional - internet
Construction of a linear code
[72,36,15] over GF(2):
[1]: [73, 36, 16] Cyclic Linear Code over GF(2)
      CyclicCode of length 73 with generating polynomial x^37 + x^36 + x^34 +
x^33 + x^32 + x^27 + x^25 + x^24 + x^22 + x^21 + x^19 + x^18 + x^15 + x^11 +
x^10 + x^8 + x^7 + x^5 + x^3 + 1
[2]: [72, 36, 15] Linear Code over GF(2)
      Puncturing of [1] at 1

last modified: 2002-03-20
```

This function raises an `IOError` if an error occurs downloading data or parsing it. It raises a `ValueError` if the `q` input is invalid.

AUTHORS:

- Steven Sivek (2005-11-14)
- David Joyner (2008-03)

`sage.coding.linear_code.bounds_minimum_distance(n, k, F)`

Calculates a lower and upper bound for the minimum distance of an optimal linear code with word length  $n$  and dimension  $k$  over the field  $F$ .

The function returns a record with the two bounds and an explanation for each bound. The function `Display` can be used to show the explanations.

The values for the lower and upper bound are obtained from a table constructed by Cen Tjhai for GUAVA, derived from the table of Brouwer. See <http://www.codetables.de/> for the most recent data. These tables contain lower and upper bounds for  $q = 2$  (when  $n \leq 257$ ),  $q = 3$  (when  $n \leq 243$ ),  $q = 4$  ( $n \leq 256$ ). (Current as of 11 May 2006.) For codes over other fields and for larger word lengths, trivial bounds are used.

This does not require an internet connection. The format of the output is a little non-intuitive. Try `bounds_minimum_distance(10, 5, GF(2))` for an example.

This function requires optional GAP package (Guava).

EXAMPLES:

```
sage: print bounds_minimum_distance(10, 5, GF(2)) # optional - gap_packages (Guava package)
rec(
  construction :=
    [ <Operation "ShortenedCode">,
      [
        [ <Operation "UUVCode">,
          [
            [ <Operation "DualCode">,
              [ [ <Operation "RepetitionCode">, [ 8, 2 ] ] ] ],
            [ <Operation "UUVCode">,
              [
                [ <Operation "DualCode">,
                  [ [ <Operation "RepetitionCode">, [ 4, 2 ] ] ] ],
                  [ <Operation "RepetitionCode">, [ 4, 2 ] ] ] ]
              ], [ 1, 2, 3, 4, 5, 6 ] ] ],
      ], [ 1, 2, 3, 4, 5, 6 ] ] ],
  k := 5,
```

```
lowerBound := 4,
lowerBoundExplanation := ...
n := 10,
q := 2,
references := rec(
),
upperBound := 4,
upperBoundExplanation := ... )
```

`sage.coding.linear_code.code2leon(C)`

Writes a file in Sage's temp directory representing the code `C`, returning the absolute path to the file. This is the Sage translation of the `GuavaToLeon` command in Guava's `codefun.gi` file.

INPUT:

- `C` - a linear code (over  $\text{GF}(p)$ ,  $p < 11$ )

OUTPUT:

- Absolute path to the file written

EXAMPLES:

```
sage: C = codes.HammingCode(GF(2), 3); C
[7, 4] Hamming Code over Finite Field of size 2
sage: file_loc = sage.coding.linear_code.code2leon(C)
sage: f = open(file_loc); print f.read()
LIBRARY code;
code=seq(2,4,7,seq(
1,0,0,0,0,1,1,
0,1,0,0,1,0,1,
0,0,1,0,1,1,0,
0,0,0,1,1,1,1
));
FINISH;
sage: f.close()
```

`sage.coding.linear_code.min_wt_vec_gap(Gmat, n, k, F, algorithm=None)`

Returns a minimum weight vector of the code generated by `Gmat`.

Uses C programs written by Steve Linton in the kernel of GAP, so is fairly fast. The option `algorithm="guava"` requires Guava. The default algorithm requires GAP but not Guava.

INPUT:

- `Gmat` - String representing a GAP generator matrix  $G$  of a linear code
- `n` - Length of the code generated by  $G$
- `k` - Dimension of the code generated by  $G$
- `F` - Base field

OUTPUT:

- Minimum weight vector of the code generated by `Gmat`

REMARKS:

- The code in the default case allows one (for free) to also compute the message vector  $m$  such that  $mG = v$ , and the (minimum) distance, as a triple. however, this output is not implemented.

- The binary case can presumably be done much faster using Robert Miller's code (see the docstring for the spectrum method). This is also not (yet) implemented.

## EXAMPLES:

```
sage: Gstr = "Z(2)*[[1,1,1,0,0,0,0], [1,0,0,1,1,0,0], [0,1,0,1,0,1,0], [1,1,0,1,0,0,1]]"
sage: sage.coding.linear_code.min_wt_vec_gap(Gstr,7,4,GF(2))
(0, 1, 0, 1, 0, 1, 0)
```

This output is different but still a minimum weight vector:

```
sage: sage.coding.linear_code.min_wt_vec_gap(Gstr,7,4,GF(2),algorithm="guava") # optional - guava
(0, 0, 1, 0, 1, 1, 0)
```

Here Gstr is a generator matrix of the Hamming [7,4,3] binary code.

## TESTS:

We check that [trac ticket #18480](#) is fixed:

```
sage: codes.HammingCode(GF(2), 2).minimum_distance()
3
```

## AUTHORS:

- David Joyner (11-2005)

```
sage.coding.linear_code.self_orthogonal_binary_codes(n, k, b=2, parent=None,
                                                    BC=None, equal=False,
                                                    in_test=None)
```

Returns a Python iterator which generates a complete set of representatives of all permutation equivalence classes of self-orthogonal binary linear codes of length in  $[1..n]$  and dimension in  $[1..k]$ .

## INPUT:

- n - Integer, maximal length
- k - Integer, maximal dimension
- b - Integer, requires that the generators all have weight divisible by b (if b=2, all self-orthogonal codes are generated, and if b=4, all doubly even codes are generated). Must be an even positive integer.
- parent - Used in recursion (default: None)
- BC - Used in recursion (default: None)
- equal - If True generates only  $[n, k]$  codes (default: False)
- in\_test - Used in recursion (default: None)

## EXAMPLES:

Generate all self-orthogonal codes of length up to 7 and dimension up to 3:

```
sage: for B in self_orthogonal_binary_codes(7,3):
...     print B
...
Linear code of length 2, dimension 1 over Finite Field of size 2
Linear code of length 4, dimension 2 over Finite Field of size 2
Linear code of length 6, dimension 3 over Finite Field of size 2
Linear code of length 4, dimension 1 over Finite Field of size 2
Linear code of length 6, dimension 2 over Finite Field of size 2
Linear code of length 6, dimension 2 over Finite Field of size 2
Linear code of length 7, dimension 3 over Finite Field of size 2
Linear code of length 6, dimension 1 over Finite Field of size 2
```

Generate all doubly-even codes of length up to 7 and dimension up to 3:

```
sage: for B in self_orthogonal_binary_codes(7,3,4):
...     print B; print B.generator_matrix()
...
Linear code of length 4, dimension 1 over Finite Field of size 2
[1 1 1 1]
Linear code of length 6, dimension 2 over Finite Field of size 2
[1 1 1 1 0 0]
[0 1 0 1 1 1]
Linear code of length 7, dimension 3 over Finite Field of size 2
[1 0 1 1 0 1 0]
[0 1 0 1 1 1 0]
[0 0 1 0 1 1 1]
```

Generate all doubly-even codes of length up to 7 and dimension up to 2:

```
sage: for B in self_orthogonal_binary_codes(7,2,4):
...     print B; print B.generator_matrix()
...
Linear code of length 4, dimension 1 over Finite Field of size 2
[1 1 1 1]
Linear code of length 6, dimension 2 over Finite Field of size 2
[1 1 1 1 0 0]
[0 1 0 1 1 1]
```

Generate all self-orthogonal codes of length equal to 8 and dimension equal to 4:

```
sage: for B in self_orthogonal_binary_codes(8, 4, equal=True):
...     print B; print B.generator_matrix()
...
Linear code of length 8, dimension 4 over Finite Field of size 2
[1 0 0 1 0 0 0 0]
[0 1 0 0 1 0 0 0]
[0 0 1 0 0 1 0 0]
[0 0 0 0 0 0 1 1]
Linear code of length 8, dimension 4 over Finite Field of size 2
[1 0 0 1 1 0 1 0]
[0 1 0 1 1 1 0 0]
[0 0 1 0 1 1 1 0]
[0 0 0 1 0 1 1 1]
```

Since all the codes will be self-orthogonal, b must be divisible by 2:

```
sage: list(self_orthogonal_binary_codes(8, 4, 1, equal=True))
Traceback (most recent call last):
...
ValueError: b (1) must be a positive even integer.
```

sage.coding.linear\_code.wtdist\_gap(Gmat, n, F)

INPUT:

- Gmat - String representing a GAP generator matrix G of a linear code
- n - Integer greater than 1, representing the number of columns of G (i.e., the length of the linear code)
- F - Finite field (in Sage), base field the code

OUTPUT:

- Spectrum of the associated code

EXAMPLES:



```
sage: Gstr = 'Z(2)*[[1,1,1,0,0,0,0], [1,0,0,1,1,0,0], [0,1,0,1,0,1,0], [1,1,0,1,0,0,1]]'
sage: F = GF(2)
sage: sage.coding.linear_code.wtdist_gap(Gstr, 7, F)
[1, 0, 0, 7, 7, 0, 0, 1]
```

Here `Gstr` is a generator matrix of the Hamming [7,4,3] binary code.

ALGORITHM:

Uses C programs written by Steve Linton in the kernel of GAP, so is fairly fast.

AUTHORS:

•David Joyner (2005-11)

## 2.9 Linear code constructions

This file contains constructions of error-correcting codes which are pure Python/Sage and not obtained from wrapping GUAVA functions. The GUAVA wrappers are in `guava.py`.

All codes available here can be accessed through the `codes` object:

```
sage: codes.HammingCode(GF(2), 3)
[7, 4] Hamming Code over Finite Field of size 2
```

Let  $F$  be a finite field with  $q$  elements. Here's a constructive definition of a cyclic code of length  $n$ .

1. Pick a monic polynomial  $g(x) \in F[x]$  dividing  $x^n - 1$ . This is called the generating polynomial of the code.
2. For each polynomial  $p(x) \in F[x]$ , compute  $p(x)g(x) \pmod{x^n - 1}$ . Denote the answer by  $c_0 + c_1x + \dots + c_{n-1}x^{n-1}$ .
3.  $\mathbf{c} = (c_0, c_1, \dots, c_{n-1})$  is a codeword in  $C$ . Every codeword in  $C$  arises in this way (from some  $p(x)$ ).

The polynomial notation for the code is to call  $c_0 + c_1x + \dots + c_{n-1}x^{n-1}$  the codeword (instead of  $(c_0, c_1, \dots, c_{n-1})$ ). The polynomial  $h(x) = (x^n - 1)/g(x)$  is called the check polynomial of  $C$ .

Let  $n$  be a positive integer relatively prime to  $q$  and let  $\alpha$  be a primitive  $n$ -th root of unity. Each generator polynomial  $g$  of a cyclic code  $C$  of length  $n$  has a factorization of the form

$$g(x) = (x - \alpha^{k_1}) \dots (x - \alpha^{k_r}),$$

where  $\{k_1, \dots, k_r\} \subset \{0, \dots, n-1\}$ . The numbers  $\alpha^{k_i}$ ,  $1 \leq i \leq r$ , are called the zeros of the code  $C$ . Many families of cyclic codes (such as BCH codes and the quadratic residue codes) are defined using properties of the zeros of  $C$ .

- **BCHCode** - A 'Bose-Chaudhuri-Hocckenghem code' (or BCH code for short) is the largest possible cyclic code of length  $n$  over field  $F = \text{GF}(q)$ , whose generator polynomial has zeros (which contain the set)  $Z = \{a^i \mid i \in C_b \cup \dots C_{b+\text{delta}-2}\}$ , where  $a$  is a primitive  $n^{\text{th}}$  root of unity in the splitting field  $GF(q^m)$ ,  $b$  is an integer  $0 \leq b \leq n - \text{delta} + 1$  and  $m$  is the multiplicative order of  $q$  modulo  $n$ . The default here is  $b = 0$  (unlike Guava, which has default  $b = 1$ ). Here  $C_k$  are the cyclotomic codes.
- **BinaryGolayCode**, **ExtendedBinaryGolayCode**, **TernaryGolayCode**, **ExtendedTernaryGolayCode** the well-known "extremal" Golay codes, [http://en.wikipedia.org/wiki/Golay\\_code](http://en.wikipedia.org/wiki/Golay_code)
- **cyclic codes** - **CyclicCodeFromGeneratingPolynomial** (= **CyclicCode**), **CyclicCodeFromCheckPolynomial**, [http://en.wikipedia.org/wiki/Cyclic\\_code](http://en.wikipedia.org/wiki/Cyclic_code)
- **DuadicCodeEvenPair**, **DuadicCodeOddPair**: Constructs the "even (resp. odd) pair" of duadic codes associated to the "splitting"  $S_1, S_2$  of  $n$ . This is a special type of cyclic code whose generator is determined by  $S_1, S_2$ . See chapter 6 in [HP].

- `HammingCode` - the well-known Hamming code, [http://en.wikipedia.org/wiki/Hamming\\_code](http://en.wikipedia.org/wiki/Hamming_code)
- `LinearCodeFromCheckMatrix` - for specifying the code using the check matrix instead of the generator matrix.
- `QuadraticResidueCodeEvenPair`, `QuadraticResidueCodeOddPair`: Quadratic residue codes of a given odd prime length and base ring either don't exist at all or occur as 4-tuples - a pair of "odd-like" codes and a pair of "even-like" codes. If  $n \equiv 1 \pmod{4}$  is prime then (Theorem 6.6.2 in [HP]) a QR code exists over  $\text{GF}(q)$  iff  $q$  is a quadratic residue mod  $n$ . Here they are constructed as "even-like" duadic codes associated the splitting  $(Q, N) \pmod{n}$ , where  $Q$  is the set of non-zero quadratic residues and  $N$  is the non-residues. `QuadraticResidueCode` (a special case) and `ExtendedQuadraticResidueCode` are included as well.
- `RandomLinearCode` - Repeatedly applies Sage's `random_element` applied to the ambient `MatrixSpace` of the generator matrix until a full rank matrix is found.
- `ReedSolomonCode` - Given a finite field  $F$  of order  $q$ , let  $n$  and  $k$  be chosen such that  $1 \leq k \leq n \leq q$ . Pick  $n$  distinct elements of  $F$ , denoted  $\{x_1, x_2, \dots, x_n\}$ . Then, the codewords are obtained by evaluating every polynomial in  $F[x]$  of degree less than  $k$  at each  $x_i$ .
- `ToricCode` - Let  $P$  denote a list of lattice points in  $\mathbb{Z}^d$  and let  $T$  denote a listing of all points in  $(F^x)^d$ . Put  $n = |T|$  and let  $k$  denote the dimension of the vector space of functions  $V = \text{Span}\{x^e \mid e \in P\}$ . The associated toric code  $C$  is the evaluation code which is the image of the evaluation map  $\text{eval}_T : V \rightarrow F^n$ , where  $x^e$  is the multi-index notation.
- `WalshCode` - a binary linear  $[2^m, m, 2^{m-1}]$  code related to Hadamard matrices. [http://en.wikipedia.org/wiki/Walsh\\_code](http://en.wikipedia.org/wiki/Walsh_code)

## REFERENCES:

## AUTHOR:

- David Joyner (2007-05): initial version
- " (2008-02): added cyclic codes, Hamming codes
- " (2008-03): added BCH code, `LinearCodeFromCheckmatrix`, `ReedSolomonCode`, `WalshCode`, `DuadicCodeEvenPair`, `DuadicCodeOddPair`, QR codes (even and odd)
- " (2008-09) fix for bug in `BCHCode` reported by F. Voloch
- " (2008-10) small docstring changes to `WalshCode` and `walsh_matrix`

## 2.9.1 Functions

`sage.coding.code_constructions.BCHCode(n, delta, F, b=0)`

A 'Bose-Chaudhuri-Hocenghem code' (or BCH code for short) is the largest possible cyclic code of length  $n$  over field  $F = \text{GF}(q)$ , whose generator polynomial has zeros (which contain the set)  $Z = \{a^b, a^{b+1}, \dots, a^{b+\text{delta}-2}\}$ , where  $a$  is a primitive  $n^{\text{th}}$  root of unity in the splitting field  $\text{GF}(q^m)$ ,  $b$  is an integer  $0 \leq b \leq n - \text{delta} + 1$  and  $m$  is the multiplicative order of  $q$  modulo  $n$ . (The integers  $b, \dots, b + \text{delta} - 2$  typically lie in the range  $1, \dots, n - 1$ .) The integer  $\text{delta} \geq 1$  is called the "designed distance". The length  $n$  of the code and the size  $q$  of the base field must be relatively prime. The generator polynomial is equal to the least common multiple of the minimal polynomials of the elements of the set  $Z$  above.

Special cases are  $b=1$  (resulting codes are called 'narrow-sense' BCH codes), and  $n = q^m - 1$  (known as 'primitive' BCH codes).

It may happen that several values of  $\text{delta}$  give rise to the same BCH code. The largest one is called the Bose distance of the code. The true minimum distance,  $d$ , of the code is greater than or equal to the Bose distance, so  $d \geq \text{delta}$ .

## EXAMPLES:

```

sage: FF.<a> = GF(3^2, "a")
sage: x = PolynomialRing(FF, "x").gen()
sage: L = [b.minpoly() for b in [a, a^2, a^3]]; g = LCM(L)
sage: f = x^(8)-1
sage: g.divides(f)
True
sage: C = codes.CyclicCode(8, g); C
Linear code of length 8, dimension 4 over Finite Field of size 3
sage: C.minimum_distance()
4
sage: C = codes.BCHCode(8, 3, GF(3), 1); C
Linear code of length 8, dimension 4 over Finite Field of size 3
sage: C.minimum_distance()
4
sage: C = codes.BCHCode(8, 3, GF(3)); C
Linear code of length 8, dimension 5 over Finite Field of size 3
sage: C.minimum_distance()
3
sage: C = codes.BCHCode(26, 5, GF(5), b=1); C
Linear code of length 26, dimension 10 over Finite Field of size 5

```

sage.coding.code\_constructions.**BinaryGolayCode()**

BinaryGolayCode() returns a binary Golay code. This is a perfect  $[23, 12, 7]$  code. It is also (equivalent to) a cyclic code, with generator polynomial  $g(x) = 1 + x^2 + x^4 + x^5 + x^6 + x^{10} + x^{11}$ . Extending it yields the extended Golay code (see ExtendedBinaryGolayCode).

EXAMPLE:

```

sage: C = codes.BinaryGolayCode()
sage: C
Linear code of length 23, dimension 12 over Finite Field of size 2
sage: C.minimum_distance()
7
sage: C.minimum_distance(algorithm='gap') # long time, check d=7
7

```

AUTHORS:

- David Joyner (2007-05)

sage.coding.code\_constructions.**CyclicCode**( $n, g, \text{ignore}=\text{True}$ )

If  $g$  is a polynomial over  $\text{GF}(q)$  which divides  $x^n - 1$  then this constructs the code “generated by  $g$ ” (ie, the code associated with the principle ideal  $gR$  in the ring  $R = \text{GF}(q)[x]/(x^n - 1)$  in the usual way).

The option “ignore” says to ignore the condition that (a) the characteristic of the base field does not divide the length (the usual assumption in the theory of cyclic codes), and (b)  $g$  must divide  $x^n - 1$ . If  $\text{ignore}=\text{True}$ , instead of returning an error, a code generated by  $\text{gcd}(x^n - 1, g)$  is created.

EXAMPLES:

```

sage: P.<x> = PolynomialRing(GF(3), "x")
sage: g = x-1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(4, g); C
Linear code of length 4, dimension 3 over Finite Field of size 3
sage: P.<x> = PolynomialRing(GF(4, "a"), "x")
sage: g = x^3+1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(9, g); C
Linear code of length 9, dimension 6 over Finite Field in a of size 2^2
sage: P.<x> = PolynomialRing(GF(2), "x")
sage: g = x^3+x+1

```

```

sage: C = codes.CyclicCodeFromGeneratingPolynomial(7,g); C
Linear code of length 7, dimension 4 over Finite Field of size 2
sage: C.generator_matrix()
[1 1 0 1 0 0 0]
[0 1 1 0 1 0 0]
[0 0 1 1 0 1 0]
[0 0 0 1 1 0 1]
sage: g = x+1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(4,g); C
Linear code of length 4, dimension 3 over Finite Field of size 2
sage: C.generator_matrix()
[1 1 0 0]
[0 1 1 0]
[0 0 1 1]

```

On the other hand, `CyclicCodeFromPolynomial(4,x)` will produce a `ValueError` including a traceback error message: “ $x$  must divide  $x^4 - 1$ ”. You will also get a `ValueError` if you type

```

sage: P.<x> = PolynomialRing(GF(4,"a"), "x")
sage: g = x^2+1

```

followed by `CyclicCodeFromGeneratingPolynomial(6,g)`. You will also get a `ValueError` if you type

```

sage: P.<x> = PolynomialRing(GF(3), "x")
sage: g = x^2-1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(5,g); C
Linear code of length 5, dimension 4 over Finite Field of size 3

```

followed by `C = CyclicCodeFromGeneratingPolynomial(5,g,False)`, with a traceback message including “ $x^2 + 2$  must divide  $x^5 - 1$ ”.

`sage.coding.code_constructions.CyclicCodeFromCheckPolynomial` ( $n, h, ignore=True$ )

If  $h$  is a polynomial over  $\text{GF}(q)$  which divides  $x^n - 1$  then this constructs the code “generated by  $g = (x^n - 1)/h$ ” (ie, the code associated with the principle ideal  $gR$  in the ring  $R = \text{GF}(q)[x]/(x^n - 1)$  in the usual way). The option “ignore” says to ignore the condition that the characteristic of the base field does not divide the length (the usual assumption in the theory of cyclic codes).

EXAMPLES:

```

sage: P.<x> = PolynomialRing(GF(3), "x")
sage: C = codes.CyclicCodeFromCheckPolynomial(4,x + 1); C
Linear code of length 4, dimension 1 over Finite Field of size 3
sage: C = codes.CyclicCodeFromCheckPolynomial(4,x^3 + x^2 + x + 1); C
Linear code of length 4, dimension 3 over Finite Field of size 3
sage: C.generator_matrix()
[2 1 0 0]
[0 2 1 0]
[0 0 2 1]

```

`sage.coding.code_constructions.CyclicCodeFromGeneratingPolynomial` ( $n, g, ignore=True$ )

If  $g$  is a polynomial over  $\text{GF}(q)$  which divides  $x^n - 1$  then this constructs the code “generated by  $g$ ” (ie, the code associated with the principle ideal  $gR$  in the ring  $R = \text{GF}(q)[x]/(x^n - 1)$  in the usual way).

The option “ignore” says to ignore the condition that (a) the characteristic of the base field does not divide the length (the usual assumption in the theory of cyclic codes), and (b)  $g$  must divide  $x^n - 1$ . If `ignore=True`, instead of returning an error, a code generated by  $\gcd(x^n - 1, g)$  is created.

EXAMPLES:

```

sage: P.<x> = PolynomialRing(GF(3), "x")
sage: g = x-1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(4,g); C
Linear code of length 4, dimension 3 over Finite Field of size 3
sage: P.<x> = PolynomialRing(GF(4, "a"), "x")
sage: g = x^3+1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(9,g); C
Linear code of length 9, dimension 6 over Finite Field in a of size 2^2
sage: P.<x> = PolynomialRing(GF(2), "x")
sage: g = x^3+x+1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(7,g); C
Linear code of length 7, dimension 4 over Finite Field of size 2
sage: C.generator_matrix()
[1 1 0 1 0 0 0]
[0 1 1 0 1 0 0]
[0 0 1 1 0 1 0]
[0 0 0 1 1 0 1]
sage: g = x+1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(4,g); C
Linear code of length 4, dimension 3 over Finite Field of size 2
sage: C.generator_matrix()
[1 1 0 0]
[0 1 1 0]
[0 0 1 1]

```

On the other hand, `CyclicCodeFromPolynomial(4,x)` will produce a `ValueError` including a traceback error message: “ $x$  must divide  $x^4 - 1$ ”. You will also get a `ValueError` if you type

```

sage: P.<x> = PolynomialRing(GF(4, "a"), "x")
sage: g = x^2+1

```

followed by `CyclicCodeFromGeneratingPolynomial(6,g)`. You will also get a `ValueError` if you type

```

sage: P.<x> = PolynomialRing(GF(3), "x")
sage: g = x^2-1
sage: C = codes.CyclicCodeFromGeneratingPolynomial(5,g); C
Linear code of length 5, dimension 4 over Finite Field of size 3

```

followed by `C = CyclicCodeFromGeneratingPolynomial(5,g,False)`, with a traceback message including “ $x^2 + 2$  must divide  $x^5 - 1$ ”.

`sage.coding.code_constructions.DuadicCodeEvenPair` ( $F, S1, S2$ )

Constructs the “even pair” of duadic codes associated to the “splitting” (see the docstring for `is_a_splitting` for the definition)  $S1, S2$  of  $n$ .

**Warning:** Maybe the splitting should be associated to a sum of  $q$ -cyclotomic cosets mod  $n$ , where  $q$  is a prime.

#### EXAMPLES:

```

sage: from sage.coding.code_constructions import is_a_splitting
sage: n = 11; q = 3
sage: C = Zmod(n).cyclotomic_cosets(q); C
[[0], [1, 3, 4, 5, 9], [2, 6, 7, 8, 10]]
sage: S1 = C[1]
sage: S2 = C[2]
sage: is_a_splitting(S1, S2, 11)
True

```

```
sage: codes.DuadicCodeEvenPair(GF(q), S1, S2)
(Linear code of length 11, dimension 5 over Finite Field of size 3,
 Linear code of length 11, dimension 5 over Finite Field of size 3)
```

sage.coding.code\_constructions.**DuadicCodeOddPair**( $F, S1, S2$ )  
Constructs the “odd pair” of duadic codes associated to the “splitting”  $S1, S2$  of  $n$ .

**Warning:** Maybe the splitting should be associated to a sum of  $q$ -cyclotomic cosets mod  $n$ , where  $q$  is a prime.

#### EXAMPLES:

```
sage: from sage.coding.code_constructions import is_a_splitting
sage: n = 11; q = 3
sage: C = Zmod(n).cyclotomic_cosets(q); C
[[0], [1, 3, 4, 5, 9], [2, 6, 7, 8, 10]]
sage: S1 = C[1]
sage: S2 = C[2]
sage: is_a_splitting(S1, S2, 11)
True
sage: codes.DuadicCodeOddPair(GF(q), S1, S2)
(Linear code of length 11, dimension 6 over Finite Field of size 3,
 Linear code of length 11, dimension 6 over Finite Field of size 3)
```

This is consistent with Theorem 6.1.3 in [HP].

sage.coding.code\_constructions.**ExtendedBinaryGolayCode**()  
ExtendedBinaryGolayCode() returns the extended binary Golay code. This is a perfect [24,12,8] code. This code is self-dual.

#### EXAMPLES:

```
sage: C = codes.ExtendedBinaryGolayCode()
sage: C
Linear code of length 24, dimension 12 over Finite Field of size 2
sage: C.minimum_distance()
8
sage: C.minimum_distance(algorithm='gap') # long time, check d=8
8
```

#### AUTHORS:

- David Joyner (2007-05)

sage.coding.code\_constructions.**ExtendedQuadraticResidueCode**( $n, F$ )  
The extended quadratic residue code (or XQR code) is obtained from a QR code by adding a check bit to the last coordinate. (These codes have very remarkable properties such as large automorphism groups and duality properties - see [HP], Section 6.6.3-6.6.4.)

#### INPUT:

- $n$  - an odd prime
- $F$  - a finite prime field  $F$  whose order must be a quadratic residue modulo  $n$ .

OUTPUT: Returns an extended quadratic residue code.

#### EXAMPLES:

```
sage: C1 = codes.QuadraticResidueCode(7, GF(2))
sage: C2 = C1.extended_code()
```

```

sage: C3 = codes.ExtendedQuadraticResidueCode(7, GF(2)); C3
Linear code of length 8, dimension 4 over Finite Field of size 2
sage: C2 == C3
True
sage: C = codes.ExtendedQuadraticResidueCode(17, GF(2))
sage: C
Linear code of length 18, dimension 9 over Finite Field of size 2
sage: C3 = codes.QuadraticResidueCodeOddPair(7, GF(2))[0]
sage: C3x = C3.extended_code()
sage: C4 = codes.ExtendedQuadraticResidueCode(7, GF(2))
sage: C3x == C4
True

```

AUTHORS:

•David Joyner (07-2006)

sage.coding.code\_constructions.**ExtendedTernaryGolayCode**()

ExtendedTernaryGolayCode returns a ternary Golay code. This is a self-dual perfect [12,6,6] code.

EXAMPLES:

```

sage: C = codes.ExtendedTernaryGolayCode()
sage: C
Linear code of length 12, dimension 6 over Finite Field of size 3
sage: C.minimum_distance()
6
sage: C.minimum_distance(algorithm='gap') # long time, check d=6
6

```

AUTHORS:

•David Joyner (11-2005)

sage.coding.code\_constructions.**LinearCodeFromCheckMatrix**(H)

A linear [n,k]-code C is uniquely determined by its generator matrix G and check matrix H. We have the following short exact sequence

$$0 \rightarrow \mathbf{F}^k \xrightarrow{G} \mathbf{F}^n \xrightarrow{H} \mathbf{F}^{n-k} \rightarrow 0.$$

(“Short exact” means (a) the arrow  $G$  is injective, i.e.,  $G$  is a full-rank  $k \times n$  matrix, (b) the arrow  $H$  is surjective, and (c)  $\text{image}(G) = \text{kernel}(H)$ .)

EXAMPLES:

```

sage: C = codes.HammingCode(GF(2), 3)
sage: H = C.parity_check_matrix(); H
[1 0 1 0 1 0 1]
[0 1 1 0 0 1 1]
[0 0 0 1 1 1 1]
sage: Gh = codes.LinearCodeFromCheckMatrix(H).generator_matrix()
sage: Gc = C.generator_matrix_systematic()
sage: Gh == Gc
True
sage: C = codes.HammingCode(GF(3), 2)
sage: H = C.parity_check_matrix(); H
[1 0 1 1]
[0 1 1 2]
sage: Gh = codes.LinearCodeFromCheckMatrix(H).generator_matrix()
sage: Gc = C.generator_matrix_systematic()
sage: Gh == Gc

```

```

True
sage: C = codes.RandomLinearCode(10,5,GF(4,"a"))
sage: H = C.parity_check_matrix()
sage: codes.LinearCodeFromCheckMatrix(H) == C
True

```

sage.coding.code\_constructions.**QuadraticResidueCode**( $n, F$ )

A quadratic residue code (or QR code) is a cyclic code whose generator polynomial is the product of the polynomials  $x - \alpha^i$  ( $\alpha$  is a primitive  $n^{\text{th}}$  root of unity;  $i$  ranges over the set of quadratic residues modulo  $n$ ).

See QuadraticResidueCodeEvenPair and QuadraticResidueCodeOddPair for a more general construction.

INPUT:

- $n$  - an odd prime
- $F$  - a finite prime field  $F$  whose order must be a quadratic residue modulo  $n$ .

OUTPUT: Returns a quadratic residue code.

EXAMPLES:

```

sage: C = codes.QuadraticResidueCode(7,GF(2))
sage: C
Linear code of length 7, dimension 4 over Finite Field of size 2
sage: C = codes.QuadraticResidueCode(17,GF(2))
sage: C
Linear code of length 17, dimension 9 over Finite Field of size 2
sage: C1 = codes.QuadraticResidueCodeOddPair(7,GF(2))[0]
sage: C2 = codes.QuadraticResidueCode(7,GF(2))
sage: C1 == C2
True
sage: C1 = codes.QuadraticResidueCodeOddPair(17,GF(2))[0]
sage: C2 = codes.QuadraticResidueCode(17,GF(2))
sage: C1 == C2
True

```

AUTHORS:

- David Joyner (11-2005)

sage.coding.code\_constructions.**QuadraticResidueCodeEvenPair**( $n, F$ )

Quadratic residue codes of a given odd prime length and base ring either don't exist at all or occur as 4-tuples - a pair of "odd-like" codes and a pair of "even-like" codes. If  $n > 2$  is prime then (Theorem 6.6.2 in [HP]) a QR code exists over  $GF(q)$  iff  $q$  is a quadratic residue mod  $n$ .

They are constructed as "even-like" duadic codes associated the splitting  $(Q,N) \bmod n$ , where  $Q$  is the set of non-zero quadratic residues and  $N$  is the non-residues.

EXAMPLES:

```

sage: codes.QuadraticResidueCodeEvenPair(17,GF(13))
(Linear code of length 17, dimension 8 over Finite Field of size 13,
 Linear code of length 17, dimension 8 over Finite Field of size 13)
sage: codes.QuadraticResidueCodeEvenPair(17,GF(2))
(Linear code of length 17, dimension 8 over Finite Field of size 2,
 Linear code of length 17, dimension 8 over Finite Field of size 2)
sage: codes.QuadraticResidueCodeEvenPair(13,GF(9,"z"))
(Linear code of length 13, dimension 6 over Finite Field in z of size 3^2,
 Linear code of length 13, dimension 6 over Finite Field in z of size 3^2)
sage: C1,C2 = codes.QuadraticResidueCodeEvenPair(7,GF(2))
sage: C1.is_self_orthogonal()

```



```

True
sage: C2.is_self_orthogonal()
True
sage: C3 = codes.QuadraticResidueCodeOddPair(17, GF(2)) [0]
sage: C4 = codes.QuadraticResidueCodeEvenPair(17, GF(2)) [1]
sage: C3 == C4.dual_code()
True

```

This is consistent with Theorem 6.6.9 and Exercise 365 in [HP].

#### TESTS:

```

sage: codes.QuadraticResidueCodeEvenPair(14, Zmod(4))
Traceback (most recent call last):
...
ValueError: the argument F must be a finite field
sage: codes.QuadraticResidueCodeEvenPair(14, GF(2))
Traceback (most recent call last):
...
ValueError: the argument n must be an odd prime
sage: codes.QuadraticResidueCodeEvenPair(5, GF(2))
Traceback (most recent call last):
...
ValueError: the order of the finite field must be a quadratic residue modulo n

```

sage.coding.code\_constructions.**QuadraticResidueCodeOddPair**( $n, F$ )

Quadratic residue codes of a given odd prime length and base ring either don't exist at all or occur as 4-tuples - a pair of "odd-like" codes and a pair of "even-like" codes. If  $n \equiv 2$  is prime then (Theorem 6.6.2 in [HP]) a QR code exists over  $\text{GF}(q)$  iff  $q$  is a quadratic residue mod  $n$ .

They are constructed as "odd-like" duadic codes associated the splitting  $(Q, N) \bmod n$ , where  $Q$  is the set of non-zero quadratic residues and  $N$  is the non-residues.

#### EXAMPLES:

```

sage: codes.QuadraticResidueCodeOddPair(17, GF(13))
(Linear code of length 17, dimension 9 over Finite Field of size 13,
 Linear code of length 17, dimension 9 over Finite Field of size 13)
sage: codes.QuadraticResidueCodeOddPair(17, GF(2))
(Linear code of length 17, dimension 9 over Finite Field of size 2,
 Linear code of length 17, dimension 9 over Finite Field of size 2)
sage: codes.QuadraticResidueCodeOddPair(13, GF(9, "z"))
(Linear code of length 13, dimension 7 over Finite Field in z of size 3^2,
 Linear code of length 13, dimension 7 over Finite Field in z of size 3^2)
sage: C1 = codes.QuadraticResidueCodeOddPair(17, GF(2)) [1]
sage: C1x = C1.extended_code()
sage: C2 = codes.QuadraticResidueCodeOddPair(17, GF(2)) [0]
sage: C2x = C2.extended_code()
sage: C2x.spectrum(); C1x.spectrum()
[1, 0, 0, 0, 0, 0, 102, 0, 153, 0, 153, 0, 102, 0, 0, 0, 0, 1]
[1, 0, 0, 0, 0, 0, 102, 0, 153, 0, 153, 0, 102, 0, 0, 0, 0, 1]
sage: C2x == C1x.dual_code()
True
sage: C3 = codes.QuadraticResidueCodeOddPair(7, GF(2)) [0]
sage: C3x = C3.extended_code()
sage: C3x.spectrum()
[1, 0, 0, 0, 14, 0, 0, 0, 1]
sage: C3x.is_self_dual()
True

```

This is consistent with Theorem 6.6.14 in [HP].

TESTS:

```
sage: codes.QuadraticResidueCodeOddPair(9, GF(2))
Traceback (most recent call last):
...
ValueError: the argument n must be an odd prime
```

sage.coding.code\_constructions.**RandomLinearCode**( $n, k, F$ )

The method used is to first construct a  $k \times n$  matrix using Sage's random\_element method for the MatrixSpace class. The construction is probabilistic but should only fail extremely rarely.

INPUT: Integers  $n, k$ , with  $n > k$ , and a finite field  $F$

OUTPUT: Returns a “random” linear code with length  $n$ , dimension  $k$  over field  $F$ .

EXAMPLES:

```
sage: C = codes.RandomLinearCode(30, 15, GF(2))
sage: C
Linear code of length 30, dimension 15 over Finite Field of size 2
sage: C = codes.RandomLinearCode(10, 5, GF(4, 'a'))
sage: C
Linear code of length 10, dimension 5 over Finite Field in a of size 2^2
```

AUTHORS:

•David Joyner (2007-05)

sage.coding.code\_constructions.**ReedSolomonCode**( $n, k, F, pts=None$ )

sage.coding.code\_constructions.**TernaryGolayCode**()

TernaryGolayCode returns a ternary Golay code. This is a perfect [11,6,5] code. It is also equivalent to a cyclic code, with generator polynomial  $g(x) = 2 + x^2 + 2x^3 + x^4 + x^5$ .

EXAMPLES:

```
sage: C = codes.TernaryGolayCode()
sage: C
Linear code of length 11, dimension 6 over Finite Field of size 3
sage: C.minimum_distance()
5
sage: C.minimum_distance(algorithm='gap') # long time, check d=5
5
```

AUTHORS:

•David Joyner (2007-5)

sage.coding.code\_constructions.**ToricCode**( $P, F$ )

Let  $P$  denote a list of lattice points in  $\mathbf{Z}^d$  and let  $T$  denote the set of all points in  $(F^x)^d$  (ordered in some fixed way). Put  $n = |T|$  and let  $k$  denote the dimension of the vector space of functions  $V = \text{Span}\{x^e \mid e \in P\}$ . The associated toric code  $C$  is the evaluation code which is the image of the evaluation map

$$\text{eval}_T : V \rightarrow F^n,$$

where  $x^e$  is the multi-index notation ( $x = (x_1, \dots, x_d)$ ,  $e = (e_1, \dots, e_d)$ , and  $x^e = x_1^{e_1} \dots x_d^{e_d}$ ), where  $\text{eval}_T(f(x)) = (f(t_1), \dots, f(t_n))$ , and where  $T = \{t_1, \dots, t_n\}$ . This function returns the toric codes discussed in [JJ].

INPUT:

• $P$  - all the integer lattice points in a polytope defining the toric variety.

• $F$  - a finite field.

OUTPUT: Returns toric code with length  $n$  = , dimension  $k$  over field  $F$ .

EXAMPLES:

```
sage: C = codes.ToricCode([[0,0],[1,0],[2,0],[0,1],[1,1]],GF(7))
sage: C
Linear code of length 36, dimension 5 over Finite Field of size 7
sage: C.minimum_distance()
24
sage: C = codes.ToricCode([[-2,-2],[-1,-2],[-1,-1],[-1,0],[0,-1],[0,0],[0,1],[1,-1],[1,0]],GF(5))
sage: C
Linear code of length 16, dimension 9 over Finite Field of size 5
sage: C.minimum_distance()
6
sage: C = codes.ToricCode([ [0,0],[1,1],[1,2],[1,3],[1,4],[2,1],[2,2],[2,3],[3,1],[3,2],[4,1]],GF(8))
sage: C
Linear code of length 49, dimension 11 over Finite Field in a of size 2^3
```

This is in fact a  $[49,11,28]$  code over  $GF(8)$ . If you type next `C.minimum_distance()` and wait overnight (!), you should get 28.

AUTHOR:

•David Joyner (07-2006)

REFERENCES:

`sage.coding.code_constructions.TrivialCode( $F, n$ )`

`sage.coding.code_constructions.WalshCode( $m$ )`

Returns the binary Walsh code of length  $2^m$ . The matrix of codewords correspond to a Hadamard matrix. This is a (constant rate) binary linear  $[2^m, m, 2^{m-1}]$  code.

EXAMPLES:

```
sage: C = codes.WalshCode(4); C
Linear code of length 16, dimension 4 over Finite Field of size 2
sage: C = codes.WalshCode(3); C
Linear code of length 8, dimension 3 over Finite Field of size 2
sage: C.spectrum()
[1, 0, 0, 0, 7, 0, 0, 0, 0]
sage: C.minimum_distance()
4
sage: C.minimum_distance(algorithm='gap') # check d=2^(m-1)
4
```

REFERENCES:

•[http://en.wikipedia.org/wiki/Hadamard\\_matrix](http://en.wikipedia.org/wiki/Hadamard_matrix)

•[http://en.wikipedia.org/wiki/Walsh\\_code](http://en.wikipedia.org/wiki/Walsh_code)

`sage.coding.code_constructions.is_a_splitting( $S1, S2, n, return\_automorphism=False$ )`

Check whether  $(S1, S2)$  is a splitting of  $\mathbf{Z}/n\mathbf{Z}$ .

A splitting of  $R = \mathbf{Z}/n\mathbf{Z}$  is a pair of subsets of  $R$  which is a partition of  $R \setminus \{0\}$  and such that there exists an element  $r$  of  $R$  such that  $rS_1 = S_2$  and  $rS_2 = S_1$  (where  $rS$  is the point-wise multiplication of the elements of  $S$  by  $r$ ).

Splittings are useful for computing idempotents in the quotient ring  $Q = GF(q)[x]/(x^n - 1)$ .

INPUT:

- $S_1, S_2$  – disjoint sublists partitioning  $[1, 2, \dots, n-1]$
- $n$  (integer)
- `return_automorphism` (boolean) – whether to return the automorphism exchanging  $S_1$  and  $S_2$ .

OUTPUT:

If `return_automorphism` is `False` (default) the function returns boolean values.

Otherwise, it returns a pair  $(b, r)$  where  $b$  is a boolean indicating whether  $S_1, S_2$  is a splitting of  $n$ , and  $r$  is such that  $rS_1 = S_2$  and  $rS_2 = S_1$  (if  $b$  is `False`,  $r$  is equal to `None`).

EXAMPLES:

```
sage: from sage.coding.code_constructions import is_a_splitting
sage: is_a_splitting([1,2],[3,4],5)
True
sage: is_a_splitting([1,2],[3,4],5,return_automorphism=True)
(True, 4)

sage: is_a_splitting([1,3],[2,4,5,6],7)
False
sage: is_a_splitting([1,3,4],[2,5,6],7)
False

sage: for P in SetPartitions(6,[3,3]):
....:     res, aut= is_a_splitting(P[0],P[1],7,return_automorphism=True)
....:     if res:
....:         print aut, P[0], P[1]
6 {1, 2, 3} {4, 5, 6}
3 {1, 2, 4} {3, 5, 6}
6 {1, 3, 5} {2, 4, 6}
6 {1, 4, 5} {2, 3, 6}
```

We illustrate now how to find idempotents in quotient rings:

```
sage: n = 11; q = 3
sage: C = Zmod(n).cyclotomic_cosets(q); C
[[0], [1, 3, 4, 5, 9], [2, 6, 7, 8, 10]]
sage: S1 = C[1]
sage: S2 = C[2]
sage: is_a_splitting(S1,S2,11)
True
sage: F = GF(q)
sage: P.<x> = PolynomialRing(F, "x")
sage: I = Ideal(P, [x^n-1])
sage: Q.<x> = QuotientRing(P,I)
sage: i1 = -sum([x^i for i in S1]); i1
2*x^9 + 2*x^5 + 2*x^4 + 2*x^3 + 2*x
sage: i2 = -sum([x^i for i in S2]); i2
2*x^10 + 2*x^8 + 2*x^7 + 2*x^6 + 2*x^2
sage: i1^2 == i1
True
sage: i2^2 == i2
True
sage: (1-i1)^2 == 1-i1
True
sage: (1-i2)^2 == 1-i2
True
```

We return to dealing with polynomials (rather than elements of quotient rings), so we can construct cyclic codes:

```

sage: P.<x> = PolynomialRing(F, "x")
sage: i1 = -sum([x^i for i in S1])
sage: i2 = -sum([x^i for i in S2])
sage: i1_sqrd = (i1^2).quo_rem(x^n-1)[1]
sage: i1_sqrd == i1
True
sage: i2_sqrd = (i2^2).quo_rem(x^n-1)[1]
sage: i2_sqrd == i2
True
sage: C1 = codes.CyclicCodeFromGeneratingPolynomial(n, i1)
sage: C2 = codes.CyclicCodeFromGeneratingPolynomial(n, 1-i2)
sage: C1.dual_code() == C2
True

```

This is a special case of Theorem 6.4.3 in [HP].

sage.coding.code\_constructions.lift2smallest\_field(a)

INPUT: a is an element of a finite field GF(q)

OUTPUT: the element b of the smallest subfield F of GF(q) for which F(b)=a.

EXAMPLES:

```

sage: from sage.coding.code_constructions import lift2smallest_field
sage: FF.<z> = GF(3^4, "z")
sage: a = z^10
sage: lift2smallest_field(a)
(2*z + 1, Finite Field in z of size 3^2)
sage: a = z^40
sage: lift2smallest_field(a)
(2, Finite Field of size 3)

```

AUTHORS:

•John Cremona

sage.coding.code\_constructions.lift2smallest\_field2(a)

INPUT: a is an element of a finite field GF(q) OUTPUT: the element b of the smallest subfield F of GF(q) for which F(b)=a.

EXAMPLES:

```

sage: from sage.coding.code_constructions import lift2smallest_field2
sage: FF.<z> = GF(3^4, "z")
sage: a = z^40
sage: lift2smallest_field2(a)
(2, Finite Field of size 3)
sage: FF.<z> = GF(2^4, "z")
sage: a = z^15
sage: lift2smallest_field2(a)
(1, Finite Field of size 2)

```

**Warning:** Since coercion (the FF(b) step) has a bug in it, this *only works* in the case when you *know* F is a prime field.

AUTHORS:

•David Joyner

```
sage.coding.code_constructions.permutation_action(g, v)
```

Returns permutation of rows  $g \cdot v$ . Works on lists, matrices, sequences and vectors (by permuting coordinates). The code requires switching from  $i$  to  $i+1$  (and back again) since the SymmetricGroup is, by convention, the symmetric group on the “letters”  $1, 2, \dots, n$  (not  $0, 1, \dots, n-1$ ).

EXAMPLES:

```
sage: V = VectorSpace(GF(3), 5)
sage: v = V([0, 1, 2, 0, 1])
sage: G = SymmetricGroup(5)
sage: g = G([(1, 2, 3)])
sage: permutation_action(g, v)
(1, 2, 0, 0, 1)
sage: g = G([()])
sage: permutation_action(g, v)
(0, 1, 2, 0, 1)
sage: g = G([(1, 2, 3, 4, 5)])
sage: permutation_action(g, v)
(1, 2, 0, 1, 0)
sage: L = Sequence([1, 2, 3, 4, 5])
sage: permutation_action(g, L)
[2, 3, 4, 5, 1]
sage: MS = MatrixSpace(GF(3), 3, 7)
sage: A = MS([[1, 0, 0, 0, 1, 1, 0], [0, 1, 0, 1, 0, 1, 0], [0, 0, 0, 0, 0, 0, 1]])
sage: S5 = SymmetricGroup(5)
sage: g = S5([(1, 2, 3)])
sage: A
[1 0 0 0 1 1 0]
[0 1 0 1 0 1 0]
[0 0 0 0 0 0 1]
sage: permutation_action(g, A)
[0 1 0 1 0 1 0]
[0 0 0 0 0 0 1]
[1 0 0 0 1 1 0]
```

It also works on lists and is a “left action”:

```
sage: v = [0, 1, 2, 0, 1]
sage: G = SymmetricGroup(5)
sage: g = G([(1, 2, 3)])
sage: gv = permutation_action(g, v); gv
[1, 2, 0, 0, 1]
sage: permutation_action(g, v) == g(v)
True
sage: h = G([(3, 4)])
sage: gv = permutation_action(g, v)
sage: hgv = permutation_action(h, gv)
sage: hgv == permutation_action(h*g, v)
True
```

AUTHORS:

•David Joyner, licensed under the GPL v2 or greater.

```
sage.coding.code_constructions.walsh_matrix(m0)
```

This is the generator matrix of a Walsh code. The matrix of codewords correspond to a Hadamard matrix.

EXAMPLES:

```
sage: walsh_matrix(2)
[0 0 1 1]
```

```

[0 1 0 1]
sage: walsh_matrix(3)
[0 0 0 0 1 1 1 1]
[0 0 1 1 0 0 1 1]
[0 1 0 1 0 1 0 1]
sage: C = LinearCode(walsh_matrix(4)); C
Linear code of length 16, dimension 4 over Finite Field of size 2
sage: C.spectrum()
[1, 0, 0, 0, 0, 0, 0, 0, 15, 0, 0, 0, 0, 0, 0, 0]

```

This last code has minimum distance 8.

#### REFERENCES:

- [http://en.wikipedia.org/wiki/Hadamard\\_matrix](http://en.wikipedia.org/wiki/Hadamard_matrix)

## 2.10 Binary self-dual codes

This module implements functions useful for studying binary self-dual codes. The main function is `self_dual_codes_binary`, which is a case-by-case list of entries, each represented by a Python dictionary.

Format of each entry: a Python dictionary with keys “order autgp”, “spectrum”, “code”, “Comment”, “Type”, where

- “code” - a sd code C of length n, dim n/2, over GF(2)
- “order autgp” - order of the permutation automorphism group of C
- “Type” - the type of C (which can be “I” or “II”, in the binary case)
- “spectrum” - the spectrum [A0,A1,...,An]
- “Comment” - possibly an empty string.

Python dictionaries were used since they seemed to be both human-readable and allow others to update the database easiest.

- The following double for loop can be time-consuming but should be run once in awhile for testing purposes. It should only print True and have no trace-back errors:

```

for n in [4,6,8,10,12,14,16,18,20,22]:
    C = self_dual_codes_binary(n); m = len(C.keys())
    for i in range(m):
        C0 = C["%s"%n]["%s"%i]["code"]
        print n, ' ', i, ' ', C["%s"%n]["%s"%i]["spectrum"] == C0.spectrum()
        print C0 == C0.dual_code()
        G = C0.automorphism_group_binary_code()
        print C["%s"%n]["%s"%i]["order autgp"] == G.order()

```

- To check if the “Riemann hypothesis” holds, run the following code:

```

R = PolynomialRing(CC, "T")
T = R.gen()
for n in [4,6,8,10,12,14,16,18,20,22]:
    C = self_dual_codes_binary(n); m = len(C["%s"%n].keys())
    for i in range(m):
        C0 = C["%s"%n]["%s"%i]["code"]
        if C0.minimum_distance() > 2:
            f = R(C0.sd_zeta_polynomial())
            print n, i, [z[0].abs() for z in f.roots()]

```

You should get lists of numbers equal to 0.707106781186548.

Here's a rather naive construction of self-dual codes in the binary case:

For even  $m$ , let  $A_m$  denote the  $m \times m$  matrix over  $\text{GF}(2)$  given by adding the all 1's matrix to the identity matrix (in  $\text{MatrixSpace}(\text{GF}(2), m, m)$  of course). If  $M_1, \dots, M_r$  are square matrices, let  $\text{diag}(M_1, M_2, \dots, M_r)$  denote the "block diagonal" matrix with the  $M_i$ 's on the diagonal and 0's elsewhere. Let  $C(m_1, \dots, m_r, s)$  denote the linear code with generator matrix having block form  $G = (I, A)$ , where  $A = \text{diag}(A_{m_1}, A_{m_2}, \dots, A_{m_r}, I_s)$ , for some (even)  $m_i$ 's and  $s$ , where  $m_1 + m_2 + \dots + m_r + s = n/2$ . Note: Such codes  $C(m_1, \dots, m_r, s)$  are SD.

SD codes not of this form will be called (for the purpose of documenting the code below) "exceptional". Except when  $n$  is "small", most sd codes are exceptional (based on a counting argument and table 9.1 in the Huffman+Pless [HP], page 347).

#### AUTHORS:

- David Joyner (2007-08-11)

#### REFERENCES:

- [HP] W. C. Huffman, V. Pless, Fundamentals of Error-Correcting Codes, Cambridge Univ. Press, 2003.
- [P] V. Pless, "A classification of self-orthogonal codes over  $\text{GF}(2)$ ", Discrete Math 3 (1972) 209-246.

`sage.coding.sd_codes.I2(n)`

`sage.coding.sd_codes.MS(n)`

For internal use; returns the  $\text{floor}(n/2) \times n$  matrix space over  $\text{GF}(2)$ .

#### EXAMPLES:

```
sage: import sage.coding.sd_codes as sd_codes
sage: sd_codes.MS(2)
Full MatrixSpace of 1 by 2 dense matrices over Finite Field of size 2
sage: sd_codes.MS(3)
Full MatrixSpace of 1 by 3 dense matrices over Finite Field of size 2
sage: sd_codes.MS(8)
Full MatrixSpace of 4 by 8 dense matrices over Finite Field of size 2
```

`sage.coding.sd_codes.MS2(n)`

For internal use; returns the  $\text{floor}(n/2) \times \text{floor}(n/2)$  matrix space over  $\text{GF}(2)$ .

#### EXAMPLES:

```
sage: import sage.coding.sd_codes as sd_codes
sage: sd_codes.MS2(8)
Full MatrixSpace of 4 by 4 dense matrices over Finite Field of size 2
```

`sage.coding.sd_codes.matA(n)`

For internal use; returns a list of square matrices over  $\text{GF}(2)$  ( $a_{ij}$ ) of sizes  $0 \times 0, 1 \times 1, \dots, n \times n$  which are of the form  $(a_{ij} = 1) + (a_{ij} = \delta_{ij})$ .

#### EXAMPLES:

```
sage: import sage.coding.sd_codes as sd_codes
sage: sd_codes.matA(4)
[
      [0 1 1]
      [0 1]  [1 0 1]
  [], [0], [1 0], [1 1 0]
]
```



`sage.coding.sd_codes.matId(n)`

For internal use; returns a list of identity matrices over GF(2) of sizes  $(\text{floor}(n/2)-j) \times (\text{floor}(n/2)-j)$  for  $j = 0 \dots (\text{floor}(n/2)-1)$ .

EXAMPLES:

```
sage: import sage.coding.sd_codes as sd_codes
sage: sd_codes.matId(6)
[
  [1 0 0]
  [0 1 0]  [1 0]
  [0 0 1], [0 1], [1]
]
```

`sage.coding.sd_codes.self_dual_codes_binary(n)`

Returns the dictionary of inequivalent sd codes of length  $n$ .

For  $n=4$  even, returns the sd codes of a given length, up to (perm) equivalence, the (perm) aut gp, and the type.

The number of inequiv “diagonal” sd binary codes in the database of length  $n$  is (“diagonal” is defined by the conjecture above) is the same as the restricted partition number of  $n$ , where only integers from the set 1,4,6,8,... are allowed. This is the coefficient of  $x^n$  in the series expansion  $(1-x)^{-1} \prod_{2 \leq j} (1-x^{2j})^{-1}$ . Typing the command `f = (1-x)*prod([(1-x(2*j))(-1) for j in range(2,18)])` into Sage, we obtain for the coeffs of  $x^4, x^6, \dots$  [1, 1, 2, 2, 3, 3, 5, 5, 7, 7, 11, 11, 15, 15, 22, 22, 30, 30, 42, 42, 56, 56, 77, 77, 101, 101, 135, 135, 176, 176, 231] These numbers grow too slowly to account for all the sd codes (see Huffman+Pless’ Table 9.1, referenced above). In fact, in Table 9.10 of [HP], the number  $B_n$  of inequivalent sd binary codes of length  $n$  is given:

n	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30
B_n	1	1	1	2	2	3	4	7	9	16	25	55	103	261	731

According to <http://oeis.org/classic/A003179>, the next 2 entries are: 3295, 24147.

EXAMPLES:

```
sage: C = self_dual_codes_binary(10)
sage: C["10"]["0"]["code"] == C["10"]["0"]["code"].dual_code()
True
sage: C["10"]["1"]["code"] == C["10"]["1"]["code"].dual_code()
True
sage: len(C["10"].keys()) # number of inequiv sd codes of length 10
2
sage: C = self_dual_codes_binary(12)
sage: C["12"]["0"]["code"] == C["12"]["0"]["code"].dual_code()
True
sage: C["12"]["1"]["code"] == C["12"]["1"]["code"].dual_code()
True
sage: C["12"]["2"]["code"] == C["12"]["2"]["code"].dual_code()
True
```

## 2.11 Guava error-correcting code constructions

This module only contains Guava wrappers (Guava is an optional GAP package).

AUTHORS:

- David Joyner (2005-11-22, 2006-12-03): initial version
- Nick Alexander (2006-12-10): factor GUAVA code to guava.py

- David Joyner (2007-05): removed Golay codes, toric and trivial codes and placed them in `code_constructions`; renamed `RandomLinearCode` to `RandomLinearCodeGuava`
- David Joyner (2008-03): removed QR, XQR, cyclic and ReedSolomon codes
- David Joyner (2009-05): added “optional package” comments, fixed some docstrings to to be sphinx compatible

### 2.11.1 Functions

`sage.coding.guava.BinaryReedMullerCode(r, k)`

The binary ‘Reed-Muller code’ with dimension  $k$  and order  $r$  is a code with length  $2^k$  and minimum distance  $2^k - r$  (see for example, section 1.10 in [HP]). By definition, the  $r^{\text{th}}$  order binary Reed-Muller code of length  $n = 2^m$ , for  $0 \leq r \leq m$ , is the set of all vectors  $(f(p) \mid p \in GF(2)^m)$ , where  $f$  is a multivariate polynomial of degree at most  $r$  in  $m$  variables.

INPUT:

- $r, k$  – positive integers with  $2^k > r$ .

OUTPUT:

Returns the binary ‘Reed-Muller code’ with dimension  $k$  and order  $r$ .

EXAMPLE:

```
sage: C = codes.BinaryReedMullerCode(2,4); C # optional - gap_packages (Guava package)
Linear code of length 16, dimension 11 over Finite Field of size 2
sage: C.minimum_distance() # optional - gap_packages (Guava package)
4
sage: C.generator_matrix() # optional - gap_packages (Guava package)
[1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1]
[0 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1]
[0 0 0 0 1 1 1 1 0 0 0 0 1 1 1 1]
[0 0 1 1 0 0 1 1 0 0 1 1 0 0 1 1]
[0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1]
[0 0 0 0 0 0 0 0 0 0 0 0 1 1 1 1]
[0 0 0 0 0 0 0 0 0 1 1 0 0 1 1]
[0 0 0 0 0 0 0 0 0 1 0 1 0 1 0 1]
[0 0 0 0 0 0 1 1 0 0 0 0 0 0 1 1]
[0 0 0 0 0 1 0 1 0 0 0 0 0 1 0 1]
[0 0 0 1 0 0 0 1 0 0 0 1 0 0 0 1]
```

AUTHOR: David Joyner (11-2005)

`sage.coding.guava.QuasiQuadraticResidueCode(p)`

A (binary) quasi-quadratic residue code (or QQR code), as defined by Proposition 2.2 in [BM], has a generator matrix in the block form  $G = (Q, N)$ . Here  $Q$  is a  $p \times p$  circulant matrix whose top row is  $(0, x_1, \dots, x_{p-1})$ , where  $x_i = 1$  if and only if  $i$  is a quadratic residue mod  $p$ , and  $N$  is a  $p \times p$  circulant matrix whose top row is  $(0, y_1, \dots, y_{p-1})$ , where  $x_i + y_i = 1$  for all  $i$ .

INPUT:

- $p$  – a prime  $> 2$ .

OUTPUT:

Returns a QQR code of length  $2p$ .

EXAMPLES:

```
sage: C = codes.QuasiQuadraticResidueCode(11); C # optional - gap_packages (Guava package)
Linear code of length 22, dimension 11 over Finite Field of size 2
```

## REFERENCES:

These are self-orthogonal in general and self-dual when  $p \equiv 3 \pmod{4}$ .

AUTHOR: David Joyner (11-2005)

`sage.coding.guava.RandomLinearCodeGuava` ( $n, k, F$ )

The method used is to first construct a  $k \times n$  matrix of the block form  $(I, A)$ , where  $I$  is a  $k \times k$  identity matrix and  $A$  is a  $k \times (n - k)$  matrix constructed using random elements of  $F$ . Then the columns are permuted using a randomly selected element of the symmetric group  $S_n$ .

## INPUT:

•  $n, k$  – integers with  $n > k > 1$ .

## OUTPUT:

Returns a “random” linear code with length  $n$ , dimension  $k$  over field  $F$ .

## EXAMPLES:

```
sage: C = codes.RandomLinearCodeGuava(30,15,GF(2)); C      # optional - gap_packages (Guava pack
Linear code of length 30, dimension 15 over Finite Field of size 2
sage: C = codes.RandomLinearCodeGuava(10,5,GF(4,'a')); C    # optional - gap_packages (Guava p
Linear code of length 10, dimension 5 over Finite Field in a of size 2^2
```

AUTHOR: David Joyner (11-2005)



## BOUNDS ON CODES

### 3.1 Bounds for Parameters of Codes

This module provided some upper and lower bounds for the parameters of codes.

AUTHORS:

- David Joyner (2006-07): initial implementation.
- William Stein (2006-07): minor editing of docs and code (fixed bug in `elias_bound_asymp`)
- David Joyner (2006-07): fixed `dimension_upper_bound` to return an integer, added example to `elias_bound_asymp`.
- ” (2009-05): removed all calls to Guava but left it as an option.
- Dima Pasechnik (2012-10): added LP bounds.

Let  $F$  be a finite field (we denote the finite field with  $q$  elements by  $\mathbf{F}_q$ ). A subset  $C$  of  $V = F^n$  is called a code of length  $n$ . A subspace of  $V$  (with the standard basis) is called a linear code of length  $n$ . If its dimension is denoted  $k$  then we typically store a basis of  $C$  as a  $k \times n$  matrix (the rows are the basis vectors). If  $F = \mathbf{F}_2$  then  $C$  is called a binary code. If  $F$  has  $q$  elements then  $C$  is called a  $q$ -ary code. The elements of a code  $C$  are called codewords. The information rate of  $C$  is

$$R = \frac{\log_q |C|}{n},$$

where  $|C|$  denotes the number of elements of  $C$ . If  $\mathbf{v} = (v_1, v_2, \dots, v_n)$ ,  $\mathbf{w} = (w_1, w_2, \dots, w_n)$  are vectors in  $V = F^n$  then we define

$$d(\mathbf{v}, \mathbf{w}) = |\{i \mid 1 \leq i \leq n, v_i \neq w_i\}|$$

to be the Hamming distance between  $\mathbf{v}$  and  $\mathbf{w}$ . The function  $d : V \times V \rightarrow \mathbf{N}$  is called the Hamming metric. The weight of a vector (in the Hamming metric) is  $d(\mathbf{v}, \mathbf{0})$ . The minimum distance of a linear code is the smallest non-zero weight of a codeword in  $C$ . The relatively minimum distance is denoted

$$\delta = d/n.$$

A linear code with length  $n$ , dimension  $k$ , and minimum distance  $d$  is called an  $[n, k, d]_q$ -code and  $n, k, d$  are called its parameters. A (not necessarily linear) code  $C$  with length  $n$ , size  $M = |C|$ , and minimum distance  $d$  is called an  $(n, M, d)_q$ -code (using parentheses instead of square brackets). Of course,  $k = \log_q(M)$  for linear codes.

What is the “best” code of a given length? Let  $F$  be a finite field with  $q$  elements. Let  $A_q(n, d)$  denote the largest  $M$  such that there exists a  $(n, M, d)$  code in  $F^n$ . Let  $B_q(n, d)$  (also denoted  $A_q^{lin}(n, d)$ ) denote the largest  $k$  such that there exists a  $[n, k, d]$  code in  $F^n$ . (Of course,  $A_q(n, d) \geq B_q(n, d)$ .) Determining  $A_q(n, d)$  and  $B_q(n, d)$  is one of the main problems in the theory of error-correcting codes.

These quantities related to solving a generalization of the childhood game of “20 questions”.

GAME: Player 1 secretly chooses a number from 1 to  $M$  ( $M$  is large but fixed). Player 2 asks a series of “yes/no questions” in an attempt to determine that number. Player 1 may lie at most  $e$  times ( $e \geq 0$  is fixed). What is the minimum number of “yes/no questions” Player 2 must ask to (always) be able to correctly determine the number Player 1 chose?

If feedback is not allowed (the only situation considered here), call this minimum number  $g(M, e)$ .

Lemma: For fixed  $e$  and  $M$ ,  $g(M, e)$  is the smallest  $n$  such that  $A_2(n, 2e + 1) \geq M$ .

Thus, solving the solving a generalization of the game of “20 questions” is equivalent to determining  $A_2(n, d)$ ! Using Sage, you can determine the best known estimates for this number in 2 ways:

1. **Indirectly, using `best_known_linear_code_www(n, k, F)`**, which connects to the website <http://www.codetables.de> by Markus Grassl;
2. **`codesize_upper_bound(n,d,q)`, `dimension_upper_bound(n,d,q)`, and `best_known_linear_code(n, k, F)`.**

The output of `best_known_linear_code()`, `best_known_linear_code_www()`, or `dimension_upper_bound()` would give only special solutions to the GAME because the bounds are applicable to only linear codes. The output of `codesize_upper_bound()` would give the best possible solution, that may belong to a linear or nonlinear code.

This module implements:

- `codesize_upper_bound(n,d,q)`, for the best known (as of May, 2006) upper bound  $A(n,d)$  for the size of a code of length  $n$ , minimum distance  $d$  over a field of size  $q$ .
- `dimension_upper_bound(n,d,q)`, an upper bound  $B(n, d) = B_q(n, d)$  for the dimension of a linear code of length  $n$ , minimum distance  $d$  over a field of size  $q$ .
- `gilbert_lower_bound(n,q,d)`, a lower bound for number of elements in the largest code of min distance  $d$  in  $\mathbb{F}_q^n$ .
- `gv_info_rate(n,delta,q)`,  $\log_q(GLB)/n$ , where GLB is the Gilbert lower bound and  $\delta = d/n$ .
- `gv_bound_asymp(delta,q)`, asymptotic analog of Gilbert lower bound.
- `plotkin_upper_bound(n,q,d)`
- `plotkin_bound_asymp(delta,q)`, asymptotic analog of Plotkin bound.
- `griesmer_upper_bound(n,q,d)`
- `elias_upper_bound(n,q,d)`
- `elias_bound_asymp(delta,q)`, asymptotic analog of Elias bound.
- `hamming_upper_bound(n,q,d)`
- `hamming_bound_asymp(delta,q)`, asymptotic analog of Hamming bound.
- `singleton_upper_bound(n,q,d)`
- `singleton_bound_asymp(delta,q)`, asymptotic analog of Singleton bound.
- `mrrw1_bound_asymp(delta,q)`, “first” asymptotic McEliece-Rumsey-Rodemich-Welsh bound for the information rate.
- Delsarte (a.k.a. Linear Programming (LP)) upper bounds.

PROBLEM: In this module we shall typically either (a) seek bounds on  $k$ , given  $n$ ,  $d$ ,  $q$ , (b) seek bounds on  $R$ ,  $\delta$ ,  $q$  (assuming  $n$  is “infinity”).

TODO:

- Johnson bounds for binary codes.

- `mrrw2_bound_asymp(delta,q)`, “second” asymptotic McEliese-Rumsey-Rodemich-Welsh bound for the information rate.

## REFERENCES:

- C. Huffman, V. Pless, Fundamentals of error-correcting codes, Cambridge Univ. Press, 2003.

`sage.coding.code_bounds.codesize_upper_bound(n, d, q, algorithm=None)`

This computes the minimum value of the upper bound using the methods of Singleton, Hamming, Plotkin, and Elias.

If `algorithm="gap"` then this returns the best known upper bound  $A(n, d) = A_q(n, d)$  for the size of a code of length  $n$ , minimum distance  $d$  over a field of size  $q$ . The function first checks for trivial cases (like  $d=1$  or  $n=d$ ), and if the value is in the built-in table. Then it calculates the minimum value of the upper bound using the algorithms of Singleton, Hamming, Johnson, Plotkin and Elias. If the code is binary,  $A(n, 2\ell-1) = A(n+1, 2\ell)$ , so the function takes the minimum of the values obtained from all algorithms for the parameters  $(n, 2\ell-1)$  and  $(n+1, 2\ell)$ . This wraps GUAVA's (i.e. GAP's package Guava) `UpperBound(n, d, q)`.

If `algorithm="LP"` then this returns the Delsarte (a.k.a. Linear Programming) upper bound.

## EXAMPLES:

```
sage: codes.bounds.codesize_upper_bound(10, 3, 2)
93
sage: codes.bounds.codesize_upper_bound(24, 8, 2, algorithm="LP")
4096
sage: codes.bounds.codesize_upper_bound(10, 3, 2, algorithm="gap") # optional - gap_packages (Guava)
85
sage: codes.bounds.codesize_upper_bound(11, 3, 4, algorithm=None)
123361
sage: codes.bounds.codesize_upper_bound(11, 3, 4, algorithm="gap") # optional - gap_packages (Guava)
123361
sage: codes.bounds.codesize_upper_bound(11, 3, 4, algorithm="LP")
109226
```

`sage.coding.code_bounds.dimension_upper_bound(n, d, q, algorithm=None)`

Returns an upper bound  $B(n, d) = B_q(n, d)$  for the dimension of a linear code of length  $n$ , minimum distance  $d$  over a field of size  $q$ . Parameter “algorithm” has the same meaning as in `codesize_upper_bound()`

## EXAMPLES:

```
sage: codes.bounds.dimension_upper_bound(10, 3, 2)
6
sage: codes.bounds.dimension_upper_bound(30, 15, 4)
13
sage: codes.bounds.dimension_upper_bound(30, 15, 4, algorithm="LP")
12
```

`sage.coding.code_bounds.elias_bound_asymp(delta, q)`

Computes the asymptotic Elias bound for the information rate, provided  $0 < \delta < 1 - 1/q$ .

## EXAMPLES:

```
sage: codes.bounds.elias_bound_asymp(1/4, 2)
0.39912396330...
```

`sage.coding.code_bounds.elias_upper_bound(n, q, d, algorithm=None)`

Returns the Elias upper bound for number of elements in the largest code of minimum distance  $d$  in  $\mathbb{F}_q^n$ . Wraps GAP's `UpperBoundElias`.

## EXAMPLES:

```

sage: codes.bounds.elias_upper_bound(10, 2, 3)
232
sage: codes.bounds.elias_upper_bound(10, 2, 3, algorithm="gap") # optional - gap_packages (Guava p
232

```

`sage.coding.code_bounds.entropy(x, q=2)`  
 Computes the entropy at  $x$  on the  $q$ -ary symmetric channel.

INPUT:

- $x$  - real number in the interval  $[0, 1]$ .
- $q$  - (default: 2) integer greater than 1. This is the base of the logarithm.

EXAMPLES:

```

sage: codes.bounds.entropy(0, 2)
0
sage: codes.bounds.entropy(1/5, 4)
1/5*log(3)/log(4) - 4/5*log(4/5)/log(4) - 1/5*log(1/5)/log(4)
sage: codes.bounds.entropy(1, 3)
log(2)/log(3)

```

Check that values not within the limits are properly handled:

```

sage: codes.bounds.entropy(1.1, 2)
Traceback (most recent call last):
...
ValueError: The entropy function is defined only for x in the interval [0, 1]
sage: codes.bounds.entropy(1, 1)
Traceback (most recent call last):
...
ValueError: The value q must be an integer greater than 1

```

`sage.coding.code_bounds.entropy_inverse(x, q=2)`  
 Find the inverse of the  $q$ -ary entropy function at the point  $x$ .

INPUT:

- $x$  - real number in the interval  $[0, 1]$ .
- $q$  - (default: 2) integer greater than 1. This is the base of the logarithm.

OUTPUT:

Real number in the interval  $[0, 1 - 1/q]$ . The function has multiple values if we include the entire interval  $[0, 1]$ ; hence only the values in the above interval is returned.

EXAMPLES:

```

sage: from sage.coding.code_bounds import entropy_inverse
sage: entropy_inverse(0.1)
0.012986862055848683
sage: entropy_inverse(1)
1/2
sage: entropy_inverse(0, 3)
0
sage: entropy_inverse(1, 3)
2/3

```

`sage.coding.code_bounds.gilbert_lower_bound(n, q, d)`  
 Returns lower bound for number of elements in the largest code of minimum distance  $d$  in  $\mathbb{F}_q^n$ .



## EXAMPLES:

```
sage: codes.bounds.gilbert_lower_bound(10,2,3)
128/7
```

```
sage.coding.code_bounds.griesmer_upper_bound(n,q,d,algorithm=None)
```

Returns the Griesmer upper bound for number of elements in the largest code of minimum distance  $d$  in  $\mathbb{F}_q^n$ . Wraps GAP's UpperBoundGriesmer.

## EXAMPLES:

```
sage: codes.bounds.griesmer_upper_bound(10,2,3)
128
sage: codes.bounds.griesmer_upper_bound(10,2,3,algorithm="gap") # optional - gap_packages (Guava)
```

```
sage.coding.code_bounds.gv_bound_async(delta,q)
```

Computes the asymptotic GV bound for the information rate,  $R$ .

## EXAMPLES:

```
sage: RDF(codes.bounds.gv_bound_async(1/4,2))
0.18872187554086...
sage: f = lambda x: codes.bounds.gv_bound_async(x,2)
sage: plot(f,0,1)
Graphics object consisting of 1 graphics primitive
```

```
sage.coding.code_bounds.gv_info_rate(n,delta,q)
```

GV lower bound for information rate of a  $q$ -ary code of length  $n$  minimum distance  $\delta n$

## EXAMPLES:

```
sage: RDF(codes.bounds.gv_info_rate(100,1/4,3)) # abs tol 1e-15
0.36704992608261894
```

```
sage.coding.code_bounds.hamming_bound_async(delta,q)
```

Computes the asymptotic Hamming bound for the information rate.

## EXAMPLES:

```
sage: RDF(codes.bounds.hamming_bound_async(1/4,2))
0.456435556800...
sage: f = lambda x: codes.bounds.hamming_bound_async(x,2)
sage: plot(f,0,1)
Graphics object consisting of 1 graphics primitive
```

```
sage.coding.code_bounds.hamming_upper_bound(n,q,d)
```

Returns the Hamming upper bound for number of elements in the largest code of minimum distance  $d$  in  $\mathbb{F}_q^n$ . Wraps GAP's UpperBoundHamming.

The Hamming bound (also known as the sphere packing bound) returns an upper bound on the size of a code of length  $n$ , minimum distance  $d$ , over a field of size  $q$ . The Hamming bound is obtained by dividing the contents of the entire space  $\mathbb{F}_q^n$  by the contents of a ball with radius  $\lfloor (d-1)/2 \rfloor$ . As all these balls are disjoint, they can never contain more than the whole vector space.

$$M \leq \frac{q^n}{V(n,e)},$$

where  $M$  is the maximum number of codewords and  $V(n,e)$  is equal to the contents of a ball of radius  $e$ . This bound is useful for small values of  $d$ . Codes for which equality holds are called perfect.

## EXAMPLES:

```
sage: codes.bounds.hamming_upper_bound(10, 2, 3)
93
```

```
sage.coding.code_bounds.mrrwl_bound_asymp(delta, q)
```

Computes the first asymptotic McEliece-Rumsey-Rodemich-Welsh bound for the information rate, provided  $0 < \delta < 1 - 1/q$ .

EXAMPLES:

```
sage: codes.bounds.mrrwl_bound_asymp(1/4, 2) # abs tol 4e-16
0.3545789026652697
```

```
sage.coding.code_bounds.plotkin_bound_asymp(delta, q)
```

Computes the asymptotic Plotkin bound for the information rate, provided  $0 < \delta < 1 - 1/q$ .

EXAMPLES:

```
sage: codes.bounds.plotkin_bound_asymp(1/4, 2)
1/2
```

```
sage.coding.code_bounds.plotkin_upper_bound(n, q, d, algorithm=None)
```

Returns Plotkin upper bound for number of elements in the largest code of minimum distance  $d$  in  $\mathbb{F}_q^n$ .

The `algorithm="gap"` option wraps Guava's `UpperBoundPlotkin`.

EXAMPLES:

```
sage: codes.bounds.plotkin_upper_bound(10, 2, 3)
192
sage: codes.bounds.plotkin_upper_bound(10, 2, 3, algorithm="gap") # optional - gap_packages (Guava)
192
```

```
sage.coding.code_bounds.singleton_bound_asymp(delta, q)
```

Computes the asymptotic Singleton bound for the information rate.

EXAMPLES:

```
sage: codes.bounds.singleton_bound_asymp(1/4, 2)
3/4
sage: f = lambda x: codes.bounds.singleton_bound_asymp(x, 2)
sage: plot(f, 0, 1)
Graphics object consisting of 1 graphics primitive
```

```
sage.coding.code_bounds.singleton_upper_bound(n, q, d)
```

Returns the Singleton upper bound for number of elements in the largest code of minimum distance  $d$  in  $\mathbb{F}_q^n$ . Wraps GAP's `UpperBoundSingleton`.

This bound is based on the shortening of codes. By shortening an  $(n, M, d)$  code  $d-1$  times, an  $(n-d+1, M, 1)$  code results, with  $M \leq q^n - d + 1$ . Thus

$$M \leq q^{n-d+1}.$$

Codes that meet this bound are called maximum distance separable (MDS).

EXAMPLES:

```
sage: codes.bounds.singleton_upper_bound(10, 2, 3)
256
```

```
sage.coding.code_bounds.volume_hamming(n, q, r)
```

Returns number of elements in a Hamming ball of radius  $r$  in  $\mathbb{F}_q^n$ . Agrees with Guava's `SphereContent(n,r,GF(q))`.

## EXAMPLES:

```
sage: codes.bounds.volume_hamming(10,2,3)
176
```

## 3.2 Delsarte, a.k.a. Linear Programming (LP), upper bounds

This module provides LP upper bounds for the parameters of codes. The exact LP solver PPL is used by default, ensuring that no rounding/overflow problems occur.

## AUTHORS:

- Dmitrii V. (Dima) Pasechnik (2012-10): initial implementation. Minor fixes (2015)

```
sage.coding.delsarte_bounds.Kravchuk(n, q, l, x, check=True)
```

Compute  $K_{n,q}^l(x)$ , the Krawtchouk (a.k.a. Kravchuk) polynomial.

See [Wikipedia article Kravchuk polynomials](#); It is defined by the generating function  $(1 + (q - 1)z)^{n-x}(1 - z)^x = \sum_l K_l^{n,q}(x)z^l$  and is equal to

$$K_l^{n,q}(x) = \sum_{j=0}^l (-1)^j (q - 1)^{(l-j)} \binom{x}{j} \binom{n-x}{l-j},$$

## INPUT:

- $n, q, x$  – arbitrary numbers
- $l$  – a nonnegative integer
- `check` – check the input for correctness. `True` by default. Otherwise, pass it as it is. Use `check=False` at your own risk.

## EXAMPLES:

```
sage: Krawtchouk(24,2,5,4)
2224
sage: Krawtchouk(12300,4,5,6)
567785569973042442072
```

## TESTS:

check that the bug reported on [trac ticket #19561](#) is fixed:

```
sage: Krawtchouk(3,2,3,3)
-1
sage: Krawtchouk(int(3),int(2),int(3),int(3))
-1
sage: Krawtchouk(int(3),int(2),int(3),int(3),check=False)
-5
sage: Kravchuk(24,2,5,4)
2224
```

## other unusual inputs

```
sage: Krawtchouk(sqrt(5),1-I*sqrt(3),3,55.3).n()
211295.892797... + 1186.42763...*I
sage: Krawtchouk(-5/2,7*I,3,-1/10)
480053/250*I - 357231/400
sage: Krawtchouk(1,1,-1,1)
Traceback (most recent call last):
```

```
...
ValueError: l must be a nonnegative integer
sage: Krawtchouk(1,1,3/2,1)
Traceback (most recent call last):
...
TypeError: no conversion of this rational to integer
```

sage.coding.delsarte\_bounds.**Krawtchouk**(*n, q, l, x, check=True*)  
 Compute  $K^{\{n, q\}_l}(x)$ , the Krawtchouk (a.k.a. Kravchuk) polynomial.

See [Wikipedia article Kravchuk polynomials](#); It is defined by the generating function  $(1 + (q - 1)z)^{n-x}(1 - z)^x = \sum_l K_l^{n,q}(x)z^l$  and is equal to

$$K_l^{n,q}(x) = \sum_{j=0}^l (-1)^j (q-1)^{(l-j)} \binom{x}{j} \binom{n-x}{l-j},$$

INPUT:

- *n, q, x* – arbitrary numbers
- *l* – a nonnegative integer
- *check* – check the input for correctness. `True` by default. Otherwise, pass it as it is. Use `check=False` at your own risk.

EXAMPLES:

```
sage: Krawtchouk(24,2,5,4)
2224
sage: Krawtchouk(12300,4,5,6)
567785569973042442072
```

TESTS:

check that the bug reported on [trac ticket #19561](#) is fixed:

```
sage: Krawtchouk(3,2,3,3)
-1
sage: Krawtchouk(int(3),int(2),int(3),int(3))
-1
sage: Krawtchouk(int(3),int(2),int(3),int(3),check=False)
-5
sage: Kravchuk(24,2,5,4)
2224
```

other unusual inputs

```
sage: Krawtchouk(sqrt(5),1-I*sqrt(3),3,55.3).n()
211295.892797... + 1186.42763...*I
sage: Krawtchouk(-5/2,7*I,3,-1/10)
480053/250*I - 357231/400
sage: Krawtchouk(1,1,-1,1)
Traceback (most recent call last):
...
ValueError: l must be a nonnegative integer
sage: Krawtchouk(1,1,3/2,1)
Traceback (most recent call last):
...
TypeError: no conversion of this rational to integer
```

```
sage.coding.delsarte_bounds.delsarte_bound_additive_hamming_space(n, d, q,
                                                                    d_star=1,
                                                                    q_base=0,
                                                                    re-
                                                                    turn_data=False,
                                                                    solver='PPL',
                                                                    isinte-
                                                                    ger=False)
```

Find a modified Delsarte bound on additive codes in Hamming space  $H_{q^n}$  of minimal distance  $d$

Find the Delsarte LP bound on  $F_{\{q\_base\}}$ -dimension of additive codes in Hamming space  $H_{q^n}$  of minimal distance  $d$  with minimal distance of the dual code at least  $d\_star$ . If  $q\_base$  is set to non-zero, then  $q$  is a power of  $q\_base$ , and the code is, formally, linear over  $F_{\{q\_base\}}$ . Otherwise it is assumed that  $q\_base==q$ .

INPUT:

- $n$  – the code length
- $d$  – the (lower bound on) minimal distance of the code
- $q$  – the size of the alphabet
- $d\_star$  – the (lower bound on) minimal distance of the dual code; only makes sense for additive codes.
- $q\_base$  – if 0, the code is assumed to be linear. Otherwise,  $q=q\_base^m$  and the code is linear over  $F_{\{q\_base\}}$ .
- $return\_data$  – if True, return a triple  $(W, LP, bound)$ , where  $W$  is a weights vector, and  $LP$  the Delsarte bound LP; both of them are Sage LP data.  $W$  need not be a weight distribution of a code, or, if  $isinteger==False$ , even have integer entries.
- $solver$  – the LP/ILP solver to be used. Defaults to PPL. It is arbitrary precision, thus there will be no rounding errors. With other solvers (see `MixedIntegerLinearProgram` for the list), you are on your own!
- $isinteger$  – if True, uses an integer programming solver (ILP), rather than an LP solver. Can be very slow if set to True.

EXAMPLES:

The bound on dimension of linear  $F_2$ -codes of length 11 and minimal distance 6:

```
sage: delsarte_bound_additive_hamming_space(11, 6, 2)
3
sage: a,p,val=delsarte_bound_additive_hamming_space(11, 6, 2,
sage: [j for i,j in p.get_values(a).iteritems()])
[1, 0, 0, 0, 0, 0, 0, 5, 2, 0, 0, 0, 0]
```

The bound on the dimension of linear  $F_4$ -codes of length 11 and minimal distance 3:

```
sage: delsarte_bound_additive_hamming_space(11, 3, 4)
8
```

The bound on the  $F_2$ -dimension of additive  $F_4$ -codes of length 11 and minimal distance 3:

```
sage: delsarte_bound_additive_hamming_space(11, 3, 4, q_base=2)
16
```

Such a  $d\_star$  is not possible:

```
sage: delsarte_bound_additive_hamming_space(11, 3, 4, d_star=9)
Solver exception: PPL : There is no feasible solution
False
```

## TESTS:

```

sage: a,p,x=delsarte_bound_additive_hamming_space(19,15,7,return_data=True,isinteger=True)
sage: [j for i,j in p.get_values(a).iteritems()]
[1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 307, 0, 0, 1, 34]
sage: delsarte_bound_additive_hamming_space(19,15,7,solver='glpk')
3
sage: delsarte_bound_additive_hamming_space(19,15,7,isinteger=True,solver='glpk')
3

```

`sage.coding.delsarte_bounds.delsarte_bound_hamming_space` (*n*, *d*, *q*, *return\_data=False*, *solver='PPL'*, *isinteger=False*)

Find the Delsarte bound <sup>1</sup> on codes in Hamming space  $H_{q^n}$  of minimal distance *d*

## INPUT:

- *n* – the code length
- *d* – the (lower bound on) minimal distance of the code
- *q* – the size of the alphabet
- **return\_data** – if **True**, return a triple (**W**, **LP**, **bound**), where **W** is a weights vector, and **LP** the Delsarte upper bound LP; both of them are Sage LP data. **W** need not be a weight distribution of a code.
- **solver** – the LP/ILP solver to be used. Defaults to **PPL**. It is arbitrary precision, thus there will be no rounding errors. With other solvers (see `MixedIntegerLinearProgram` for the list), you are on your own!
- **isinteger** – if **True**, uses an integer programming solver (ILP), rather than an LP solver. Can be very slow if set to **True**.

## EXAMPLES:

The bound on the size of the  $F_2$ -codes of length 11 and minimal distance 6:

```

sage: delsarte_bound_hamming_space(11, 6, 2)
12
sage: a, p, val = delsarte_bound_hamming_space(11, 6, 2, return_data=True)
sage: [j for i,j in p.get_values(a).iteritems()]
[1, 0, 0, 0, 0, 0, 0, 11, 0, 0, 0, 0]

```

The bound on the size of the  $F_2$ -codes of length 24 and minimal distance 8, i.e. parameters of the extended binary Golay code:

```

sage: a,p,x=delsarte_bound_hamming_space(24,8,2,return_data=True)
sage: x
4096
sage: [j for i,j in p.get_values(a).iteritems()]
[1, 0, 0, 0, 0, 0, 0, 0, 759, 0, 0, 0, 2576, 0, 0, 0, 759, 0, 0, 0, 0, 0, 0, 0, 1]

```

The bound on the size of  $F_4$ -codes of length 11 and minimal distance 3:

```

sage: delsarte_bound_hamming_space(11,3,4)
327680/3

```

<sup>1</sup> P. Delsarte, An algebraic approach to the association schemes of coding theory, Philips Res. Rep., Suppl., vol. 10, 1973.

An improvement of a known upper bound (150) from <http://www.win.tue.nl/~aeb/codes/binary-1.html>

```
sage: a,p,x= delsarte_bound_hamming_space(23,10,2,return_data=True,isinteger=True); x # long time
148
sage: [j for i,j in p.get_values(a).iteritems()] # long time
[1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 95, 0, 2, 0, 36, 0, 14, 0, 0, 0, 0, 0, 0]
```

Note that a usual LP, without integer variables, won't do the trick

```
sage: delsarte_bound_hamming_space(23,10,2).n(20)
151.86
```

Such an input is invalid:

```
sage: delsarte_bound_hamming_space(11,3,-4)
Solver exception: PPL : There is no feasible solution
False
```

REFERENCES:





## CHANNELS AND RELATED CONSTRUCTIONS

### 4.1 Channels

Given an input space and an output space, a channel takes element from the input space (the message) and transforms it into an element of the output space (the transmitted message).

In Sage, Channels simulate error-prone transmission over communication channels, and we borrow the nomenclature from communication theory, such as “transmission” and “positions” as the elements of transmitted vectors. Transmission can be achieved with two methods:

- `Channel.transmit()`. Considering a channel `Chan` and a message `msg`, transmitting `msg` with `Chan` can be done this way:

```
Chan.transmit(msg)
```

It can also be written in a more convenient way:

```
Chan(msg)
```

- `transmit_unsafe()`. This does the exact same thing as `transmit()` except that it does not check if `msg` belongs to the input space of `Chan`:

```
Chan.transmit_unsafe(msg)
```

This is useful in e.g. an inner-loop of a long simulation as a lighter-weight alternative to `Channel.transmit()`.

This file contains the following elements:

- `Channel`, the abstract class for Channels
- `StaticErrorRateChannel`, which creates a specific number of errors in each transmitted message
- `ErrorErasureChannel`, which creates a specific number of errors and a specific number of erasures in each transmitted message

**class** `sage.coding.channel_constructions.Channel(input_space, output_space)`

Bases: `sage.structure.sage_object.SageObject`

Abstract top-class for Channel objects.

All channel objects must inherit from this class. To implement a channel subclass, one should do the following:

- inherit from this class,
- call the super constructor,
- override `transmit_unsafe()`.

While not being mandatory, it might be useful to reimplement representation methods (`_repr_` and `_latex_`).

This abstract class provides the following parameters:

- `input_space` – the space of the words to transmit
- `output_space` – the space of the transmitted words

**`input_space()`**

Returns the input space of `self`.

EXAMPLES:

```
sage: n_err = 2
sage: Chan = channels.StaticErrorRateChannel(GF(59)^6, n_err)
sage: Chan.input_space()
Vector space of dimension 6 over Finite Field of size 59
```

**`output_space()`**

Returns the output space of `self`.

EXAMPLES:

```
sage: n_err = 2
sage: Chan = channels.StaticErrorRateChannel(GF(59)^6, n_err)
sage: Chan.output_space()
Vector space of dimension 6 over Finite Field of size 59
```

**`transmit(message)`**

Returns `message`, modified accordingly with the algorithm of the channel it was transmitted through.

Checks if `message` belongs to the input space, and returns an exception if not. Note that `message` itself is never modified by the channel.

INPUT:

- `message` – a vector

OUTPUT:

- a vector of the output space of `self`

EXAMPLES:

```
sage: F = GF(59)^6
sage: n_err = 2
sage: Chan = channels.StaticErrorRateChannel(F, n_err)
sage: msg = F((4, 8, 15, 16, 23, 42))
sage: set_random_seed(10)
sage: Chan.transmit(msg)
(4, 8, 4, 16, 23, 53)
```

We can check that the input `msg` is not modified:

```
sage: msg
(4, 8, 15, 16, 23, 42)
```

If we transmit a vector which is not in the input space of `self`:

```
sage: n_err = 2
sage: Chan = channels.StaticErrorRateChannel(GF(59)^6, n_err)
sage: msg = (4, 8, 15, 16, 23, 42)
sage: Chan.transmit(msg)
Traceback (most recent call last):
```

```
...
TypeError: Message must be an element of the input space for the given channel
```

**Note:** One can also call directly `Chan(message)`, which does the same as `Chan.transmit(message)`

**transmit\_unsafe**(*message*)

Returns *message*, modified accordingly with the algorithm of the channel it was transmitted through.

This method does not check if *message* belongs to the input space of “self”.

This is an abstract method which should be reimplemented in all the subclasses of `Channel`.

**class** `sage.coding.channel_constructions.ErrorErasureChannel` (*space*, *number\_errors*, *number\_erasures*)

Bases: `sage.coding.channel_constructions.Channel`

Channel which adds errors and erases several positions in any message it transmits.

The output space of this channel is a Cartesian product between its input space and a `VectorSpace` of the same dimension over `GF(2)`

INPUT:

- *space* – the input and output space
- *number\_errors* – the number of errors created in each transmitted message. It can be either an integer or a tuple. If an tuple is passed as an argument, the number of errors will be a random integer between the two bounds of this tuple.
- *number\_erasures* – the number of erasures created in each transmitted message. It can be either an integer or a tuple. If an tuple is passed as an argument, the number of erasures will be a random integer between the two bounds of this tuple.

EXAMPLES:

We construct a `ErrorErasureChannel` which adds 2 errors and 2 erasures to any transmitted message:

```
sage: n_err, n_era = 2, 2
sage: Chan = channels.ErrorErasureChannel(GF(59)^40, n_err, n_era)
sage: Chan
Error-and-erasure channel creating 2 errors and 2 erasures
of input space Vector space of dimension 40 over Finite Field of size 59
and output space The Cartesian product of (Vector space of dimension 40
over Finite Field of size 59, Vector space of dimension 40 over Finite Field of size 2)
```

We can also pass the number of errors and erasures as a couple of integers:

```
sage: n_err, n_era = (1, 10), (1, 10)
sage: Chan = channels.ErrorErasureChannel(GF(59)^40, n_err, n_era)
sage: Chan
Error-and-erasure channel creating between 1 and 10 errors and
between 1 and 10 erasures of input space Vector space of dimension 40
over Finite Field of size 59 and output space The Cartesian product of
(Vector space of dimension 40 over Finite Field of size 59,
Vector space of dimension 40 over Finite Field of size 2)
```

**number\_erasures**()

Returns the number of erasures created by *self*.

EXAMPLES:

```

sage: n_err, n_era = 0, 3
sage: Chan = channels.ErrorErasureChannel(GF(59)^6, n_err, n_era)
sage: Chan.number_erasures()
(3, 3)

```

**number\_errors()**

Returns the number of errors created by self.

**EXAMPLES:**

```

sage: n_err, n_era = 3, 0
sage: Chan = channels.ErrorErasureChannel(GF(59)^6, n_err, n_era)
sage: Chan.number_errors()
(3, 3)

```

**transmit\_unsafe(message)**

Returns message with as many errors as self.\_number\_errors in it, and as many erasures as self.\_number\_erasures in it.

If self.\_number\_errors was passed as an tuple for the number of errors, it will pick a random integer between the bounds of the tuple and use it as the number of errors. It does the same with self.\_number\_erasures.

All erased positions are set to 0 in the transmitted message. It is guaranteed that the erasures and the errors will never overlap: the received message will always contains exactly as many errors and erasures as expected.

This method does not check if message belongs to the input space of “self”.

**INPUT:**

- message – a vector

**OUTPUT:**

- a couple of vectors, namely:
  - the transmitted message, which is message with erroneous and erased positions
  - the erasure vector, which contains 1 at the erased positions of the transmitted message , 0 elsewhere.

**EXAMPLES:**

```

sage: F = GF(59)^11
sage: n_err, n_era = 2, 2
sage: Chan = channels.ErrorErasureChannel(F, n_err, n_era)
sage: msg = F((3, 14, 15, 9, 26, 53, 58, 9, 7, 9, 3))
sage: set_random_seed(10)
sage: Chan.transmit_unsafe(msg)
((31, 0, 15, 9, 38, 53, 58, 9, 0, 9, 3), (0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0))

```

**class** sage.coding.channel\_constructions.**QarySymmetricChannel**(space, epsilon)

Bases: [sage.coding.channel\\_constructions.Channel](#)

The q-ary symmetric, memoryless communication channel.

Given an alphabet  $\Sigma$  with  $|\Sigma| = q$  and an error probability  $\epsilon$ , a q-ary symmetric channel sends an element of  $\Sigma$  into the same element with probability  $1 - \epsilon$ , and any one of the other  $q - 1$  elements with probability  $\frac{\epsilon}{q-1}$ . This implementation operates over vectors in  $\Sigma^n$ , and “transmits” each element of the vector independently in the above manner.

Though  $\Sigma$  is usually taken to be a finite field, this implementation allows any structure for which Sage can represent  $\Sigma^n$  and for which  $\Sigma$  has a `random_element()` method. However, beware that if  $\Sigma$  is infinite, errors will not be uniformly distributed (since `random_element()` does not draw uniformly at random).

The input space and the output space of this channel are the same:  $\Sigma^n$ .

INPUT:

- `space` – the input and output space of the channel. It has to be  $GF(q)^n$  for some finite field  $GF(q)$ .
- `epsilon` – the transmission error probability of the individual elements.

EXAMPLES:

We construct a `QarySymmetricChannel` which corrupts 30% of all transmitted symbols:

```
sage: epsilon = 0.3
sage: Chan = channels.QarySymmetricChannel(GF(59)^50, epsilon)
sage: Chan
q-ary symmetric channel with error probability 0.3000000000000000,
of input and output space Vector space of dimension 50 over Finite Field of size 59
```

**`error_probability()`**

Returns the error probability of a single symbol transmission of `self`.

EXAMPLES:

```
sage: epsilon = 0.3
sage: Chan = channels.QarySymmetricChannel(GF(59)^50, epsilon)
sage: Chan.error_probability()
0.3000000000000000
```

**`probability_of_at_most_t_errors(t)`**

Returns the probability `self` has to return at most `t` errors.

INPUT:

- `t` – an integer

EXAMPLES:

```
sage: epsilon = 0.3
sage: Chan = channels.QarySymmetricChannel(GF(59)^50, epsilon)
sage: Chan.probability_of_at_most_t_errors(20)
0.952236164579467
```

**`probability_of_exactly_t_errors(t)`**

Returns the probability `self` has to return exactly `t` errors.

INPUT:

- `t` – an integer

EXAMPLES:

```
sage: epsilon = 0.3
sage: Chan = channels.QarySymmetricChannel(GF(59)^50, epsilon)
sage: Chan.probability_of_exactly_t_errors(15)
0.122346861835401
```

**`transmit_unsafe(message)`**

Returns `message` where each of the symbols has been changed to another from the alphabet with probability `error_probability()`.

This method does not check if `message` belongs to the input space of “`self`”.

INPUT:

- message – a vector

EXAMPLES:

```
sage: F = GF(59)^11
sage: epsilon = 0.3
sage: Chan = channels.QarySymmetricChannel(F, epsilon)
sage: msg = F((3, 14, 15, 9, 26, 53, 58, 9, 7, 9, 3))
sage: set_random_seed(10)
sage: Chan.transmit_unsafe(msg)
(3, 14, 15, 53, 12, 53, 58, 9, 55, 9, 3)
```

**class** sage.coding.channel\_constructions.**StaticErrorRateChannel** (*space*, *number\_errors*)

Bases: *sage.coding.channel\_constructions.Channel*

Channel which adds a static number of errors to each message it transmits.

The input space and the output space of this channel are the same.

INPUT:

- space – the space of both input and output
- number\_errors – the number of errors added to each transmitted message It can be either an integer or a tuple. If a tuple is passed as argument, the number of errors will be a random integer between the two bounds of the tuple.

EXAMPLES:

We construct a StaticErrorRateChannel which adds 2 errors to any transmitted message:

```
sage: n_err = 2
sage: Chan = channels.StaticErrorRateChannel(GF(59)^40, n_err)
sage: Chan
Static error rate channel creating 2 errors, of input and output space
Vector space of dimension 40 over Finite Field of size 59
```

We can also pass a tuple for the number of errors:

```
sage: n_err = (1, 10)
sage: Chan = channels.StaticErrorRateChannel(GF(59)^40, n_err)
sage: Chan
Static error rate channel creating between 1 and 10 errors,
of input and output space Vector space of dimension 40 over Finite Field of size 59
```

**number\_errors()**

Returns the number of errors created by self.

EXAMPLES:

```
sage: n_err = 3
sage: Chan = channels.StaticErrorRateChannel(GF(59)^6, n_err)
sage: Chan.number_errors()
(3, 3)
```

**transmit\_unsafe** (*message*)

Returns message with as many errors as self.\_number\_errors in it.

If self.\_number\_errors was passed as a tuple for the number of errors, it will pick a random integer between the bounds of the tuple and use it as the number of errors.

This method does not check if `message` belongs to the input space of “self”.

INPUT:

- `message` – a vector

OUTPUT:

- a vector of the output space

EXAMPLES:

```
sage: F = GF(59)^6
sage: n_err = 2
sage: Chan = channels.StaticErrorRateChannel(F, n_err)
sage: msg = F((4, 8, 15, 16, 23, 42))
sage: set_random_seed(10)
sage: Chan.transmit_unsafe(msg)
(4, 8, 4, 16, 23, 53)
```

This checks that trac #19863 is fixed:

```
sage: V = VectorSpace(GF(2), 1000)
sage: Chan = channels.StaticErrorRateChannel(V, 367)
sage: c = V.random_element()
sage: (c - Chan(c)).hamming_weight()
367
```

`sage.coding.channel_constructions.format_interval(t)`

Returns a formatted string representation of `t`.

This method should be called by any representation function in Channel classes.

---

**Note:** This is a helper function, which should only be used when implementing new channels.

---

INPUT:

- `t` – a list or a tuple

OUTPUT:

- a string

TESTS:

```
sage: from sage.coding.channel_constructions import format_interval
sage: t = (5, 5)
sage: format_interval(t)
'5'

sage: t = (2, 10)
sage: format_interval(t)
'between 2 and 10'
```

`sage.coding.channel_constructions.random_error_vector(n, F, error_positions)`

Return a vector of length `n` over `F` filled with random non-zero coefficients at the positions given by `error_positions`.

---

**Note:** This is a helper function, which should only be used when implementing new channels.

---

INPUT:

- $n$  – the length of the vector
- $F$  – the field over which the vector is defined
- `error_positions` – the non-zero positions of the vector

OUTPUT:

- a vector of  $F$

AUTHORS:

This function is taken from `codinglib` (<https://bitbucket.org/jsrn/codinglib/>) and was written by Johan Nielsen.

EXAMPLES:

```
sage: from sage.coding.channel_constructions import random_error_vector
sage: random_error_vector(5, GF(2), [1, 3])
(0, 1, 0, 1, 0)
```



## SOURCE CODING

### 5.1 Huffman Encoding

This module implements functionalities relating to Huffman encoding and decoding.

AUTHOR:

- Nathann Cohen (2010-05): initial version.

#### 5.1.1 Classes and functions

**class** `sage.coding.source_coding.huffman.Huffman` (*source*)

Bases: `sage.structure.sage_object.SageObject`

This class implements the basic functionalities of Huffman codes.

It can build a Huffman code from a given string, or from the information of a dictionary associating to each key (the elements of the alphabet) a weight (most of the time, a probability value or a number of occurrences).

INPUT:

- *source* – can be either
  - A string from which the Huffman encoding should be created.
  - A dictionary that associates to each symbol of an alphabet a numeric value. If we consider the frequency of each alphabetic symbol, then *source* is considered as the frequency table of the alphabet with each numeric (non-negative integer) value being the number of occurrences of a symbol. The numeric values can also represent weights of the symbols. In that case, the numeric values are not necessarily integers, but can be real numbers.

In order to construct a Huffman code for an alphabet, we use exactly one of the following methods:

1. Let *source* be a string of symbols over an alphabet and feed *source* to the constructor of this class. Based on the input string, a frequency table is constructed that contains the frequency of each unique symbol in *source*. The alphabet in question is then all the unique symbols in *source*. A significant implication of this is that any subsequent string that we want to encode must contain only symbols that can be found in *source*.
2. Let *source* be the frequency table of an alphabet. We can feed this table to the constructor of this class. The table *source* can be a table of frequencies or a table of weights.

Examples:

```
sage: from sage.coding.source_coding.huffman import Huffman, frequency_table
sage: h1 = Huffman("There once was a french fry")
sage: for letter, code in h1.encoding_table().iteritems():
```

```

...     print ""+ letter + " : " + code
'a' : 0111
' ' : 00
'c' : 1010
'e' : 100
'f' : 1011
'h' : 1100
'o' : 11100
'n' : 1101
's' : 11101
'r' : 010
'T' : 11110
'w' : 11111
'y' : 0110

```

We can obtain the same result by “training” the Huffman code with the following table of frequency:

```

sage: ft = frequency_table("There once was a french fry"); ft
{' ': 5,
 'T': 1,
 'a': 2,
 'c': 2,
 'e': 4,
 'f': 2,
 'h': 2,
 'n': 2,
 'o': 1,
 'r': 3,
 's': 1,
 'w': 1,
 'y': 1}
sage: h2 = Huffman(ft)

```

Once h1 has been trained, and hence possesses an encoding table, it is possible to obtain the Huffman encoding of any string (possibly the same) using this code:

```

sage: encoded = h1.encode("There once was a french fry"); encoded
'111101100100010100001110011011010100001111011111010001110010110101001101101011000010110100110

```

We can decode the above encoded string in the following way:

```

sage: h1.decode(encoded)
'There once was a french fry'

```

Obviously, if we try to decode a string using a Huffman instance which has been trained on a different sample (and hence has a different encoding table), we are likely to get some random-looking string:

```

sage: h3 = Huffman("There once were two french fries")
sage: h3.decode(encoded)
' wehnefetrhft ne ewrowrirTc'

```

This does not look like our original string.

Instead of using frequency, we can assign weights to each alphabetic symbol:

```

sage: from sage.coding.source_coding.huffman import Huffman
sage: T = {"a":45, "b":13, "c":12, "d":16, "e":9, "f":5}
sage: H = Huffman(T)
sage: L = ["deaf", "bead", "fab", "bee"]
sage: E = []

```

```

sage: for e in L:
...     E.append(H.encode(e))
...     print E[-1]
...
111110101100
10111010111
11000101
10111011101
sage: D = []
sage: for e in E:
...     D.append(H.decode(e))
...     print D[-1]
...
deaf
bead
fab
bee
sage: D == L
True

```

**decode** (*string*)

Decode the given string using the current encoding table.

INPUT:

- string – a string of Huffman encodings.

OUTPUT:

- The Huffman decoding of string.

EXAMPLES:

This is how a string is encoded and then decoded:

```

sage: from sage.coding.source_coding.huffman import Huffman
sage: str = "Sage is my most favorite general purpose computer algebra system"
sage: h = Huffman(str)
sage: encoded = h.encode(str); encoded
'0000011010001010101100001110101001110010101001101101110011110111001011010000101101111100000
sage: h.decode(encoded)
'Sage is my most favorite general purpose computer algebra system'

```

TESTS:

Of course, the string one tries to decode has to be a binary one. If not, an exception is raised:

```

sage: h.decode('I clearly am not a binary string')
Traceback (most recent call last):
...
ValueError: Input must be a binary string.

```

**encode** (*string*)

Encode the given string based on the current encoding table.

INPUT:

- string – a string of symbols over an alphabet.

OUTPUT:

- A Huffman encoding of string.

## EXAMPLES:

This is how a string is encoded and then decoded:

```
sage: from sage.coding.source_coding.huffman import Huffman
sage: str = "Sage is my most favorite general purpose computer algebra system"
sage: h = Huffman(str)
sage: encoded = h.encode(str); encoded
'000001101000101010110000111010100111001010100110110111001111011100101101000010110111100000
sage: h.decode(encoded)
'Sage is my most favorite general purpose computer algebra system'
```

**encoding\_table()**

Returns the current encoding table.

INPUT:

- None.

OUTPUT:

- A dictionary associating an alphabetic symbol to a Huffman encoding.

## EXAMPLES:

```
sage: from sage.coding.source_coding.huffman import Huffman
sage: str = "Sage is my most favorite general purpose computer algebra system"
sage: h = Huffman(str)
sage: T = sorted(h.encoding_table().items())
sage: for symbol, code in T:
...     print symbol, code
...
      101
S 00000
a 1101
b 110001
c 110000
e 010
f 110010
g 0001
i 10000
l 10011
m 0011
n 110011
o 0110
p 0010
r 1111
s 1110
t 0111
u 10001
v 00001
y 10010
```

**tree()**

Returns the Huffman tree corresponding to the current encoding.

INPUT:

- None.

OUTPUT:

- The binary tree representing a Huffman code.

## EXAMPLES:

```

sage: from sage.coding.source_coding.huffman import Huffman
sage: str = "Sage is my most favorite general purpose computer algebra system"
sage: h = Huffman(str)
sage: T = h.tree(); T
Digraph on 39 vertices
sage: T.show(figsize=[20,20])

```

```
sage.coding.source_coding.huffman.frequency_table(string)
```

Return the frequency table corresponding to the given string.

## INPUT:

- `string` – a string of symbols over some alphabet.

## OUTPUT:

- A table of frequency of each unique symbol in `string`. If `string` is an empty string, return an empty table.

## EXAMPLES:

The frequency table of a non-empty string:

```

sage: from sage.coding.source_coding.huffman import frequency_table
sage: str = "Stop counting my characters!"
sage: T = sorted(frequency_table(str).items())
sage: for symbol, code in T:
...     print symbol, code
...
3
! 1
S 1
a 2
c 3
e 1
g 1
h 1
i 1
m 1
n 2
o 2
p 1
r 2
s 1
t 3
u 1
y 1

```

The frequency of an empty string:

```

sage: frequency_table("")
{}

```



## CANONICAL FORMS

## 6.1 Canonical forms and automorphism group computation for linear codes over finite fields

We implemented the algorithm described in [Feu2009] which computes the unique semilinearly isometric code (canonical form) in the equivalence class of a given linear code  $C$ . Furthermore, this algorithm will return the automorphism group of  $C$ , too.

The algorithm should be started via a further class `LinearCodeAutGroupCanLabel`. This class removes duplicated columns (up to multiplications by units) and zero columns. Hence, we can suppose that the input for the algorithm developed here is a set of points in  $PG(k-1, q)$ .

The implementation is based on the class `sage.groups.perm_gps.partn_ref2.refinement_generic.PartitionRef`. See the description of this algorithm in `sage.groups.perm_gps.partn_ref2.refinement_generic`. In the language given there, we have to implement the group action of  $G = (GL(k, q) \times \mathbb{F}_q^{*n}) \rtimes Aut(\mathbb{F}_q)$  on the set  $X = (\mathbb{F}_q^k)^n$  of  $k \times n$  matrices over  $\mathbb{F}_q$  (with the above restrictions).

The derived class here implements the stabilizers  $G_{\Pi^{(I)}(x)}$  of the projections  $\Pi^{(I)}(x)$  of  $x$  to the coordinates specified in the sequence  $I$ . Furthermore, we implement the inner minimization, i.e. the computation of a canonical form of the projection  $\Pi^{(I)}(x)$  under the action of  $G_{\Pi^{(I-1)}(x)}$ . Finally, we provide suitable homomorphisms of group actions for the refinements and methods to compute the applied group elements in  $G \rtimes S_n$ .

The algorithm also uses Jeffrey Leon's idea of maintaining an invariant set of codewords which is computed in the beginning, see `_init_point_hyperplane_incidence()`. An example for such a set is the set of all codewords of weight  $\leq w$  for some uniquely defined  $w$ . In our case, we interpret the codewords as a set of hyperplanes (via the corresponding information word) and compute invariants of the bipartite, colored derived subgraph of the point-hyperplane incidence graph, see `PartitionRefinementLinearCode._point_refine()` and `PartitionRefinementLinearCode._hyp_refine()`.

Since we are interested in subspaces (linear codes) instead of matrices, our group elements returned in `PartitionRefinementLinearCode.get_transporter()` and `PartitionRefinementLinearCode.get_autom_gens()` will be elements in the group  $(\mathbb{F}_q^{*n} \rtimes Aut(\mathbb{F}_q)) \rtimes S_n = (\mathbb{F}_q^{*n} \rtimes (Aut(\mathbb{F}_q) \times S_n))$ .

AUTHORS:

- Thomas Feulner (2012-11-15): initial version

REFERENCES:

[Feu2009]

EXAMPLES:

Get the canonical form of the Simplex code:

```

sage: from sage.coding.codecan.codecan import PartitionRefinementLinearCode
sage: mat = codes.HammingCode(GF(3), 3).dual_code().generator_matrix()
sage: P = PartitionRefinementLinearCode(mat.ncols(), mat)
sage: cf = P.get_canonical_form(); cf
[1 0 0 0 0 1 1 1 1 1 1 1]
[0 1 0 1 1 0 0 1 1 2 2 1]
[0 0 1 1 2 1 2 1 2 1 2 0]

```

The transporter element is a group element which maps the input to its canonical form:

```

sage: cf.echelon_form() == (P.get_transporter() * mat).echelon_form()
True

```

The automorphism group of the input, i.e. the stabilizer under this group action, is returned by generators:

```

sage: P.get_autom_order_permutation() == GL(3, GF(3)).order() / (len(GF(3)) - 1)
True
sage: A = P.get_autom_gens()
sage: all( [(a*mat).echelon_form() == mat.echelon_form() for a in A])
True

```

**class** sage.coding.codecan.codecan.InnerGroup

Bases: object

This class implements the stabilizers  $G_{\Pi(I)(x)}$  described in sage.groups.perm\_gps.partn\_ref2.refinement\_generators with  $G = (GL(k, q) \times \mathbf{F}_q^n) \rtimes \text{Aut}(\mathbf{F}_q)$ .

Those stabilizers can be stored as triples:

- rank - an integer in  $\{0, \dots, k\}$
- row\_partition - a partition of  $\{0, \dots, k-1\}$  with discrete cells for all integers  $i \geq \text{rank}$ .
- frob\_pow an integer in  $\{0, \dots, r-1\}$  if  $q = p^r$

The group  $G_{\Pi(I)(x)}$  contains all elements  $(A, \varphi, \alpha) \in G$ , where

- $A$  is a  $2 \times 2$  blockmatrix, whose upper left matrix is a  $k \times k$  diagonal matrix whose entries  $A_{i,i}$  are constant on the cells of the partition row\_partition. The lower left matrix is zero. And the right part is arbitrary.
- The support of the columns given by  $i \in I$  intersect exactly one cell of the partition. The entry  $\varphi_i$  is equal to the entries of the corresponding diagonal entry of  $A$ .
- $\alpha$  is a power of  $\tau^{\text{frob\_pow}}$ , where  $\tau$  denotes the Frobenius automorphism of the finite field  $\mathbf{F}_q$ .

See [Feu2009] for more details.

**column\_blocks** (mat)

Let mat be a matrix which is stabilized by self having no zero columns. We know that for each column of mat there is a uniquely defined cell in self.row\_partition having a nontrivial intersection with the support of this particular column.

This function returns a partition (as list of lists) of the columns indices according to the partition of the rows given by self.

EXAMPLES:

```

sage: from sage.coding.codecan.codecan import InnerGroup
sage: I = InnerGroup(3)
sage: mat = Matrix(GF(3), [[0,1,0],[1,0,0],[0,0,1]])
sage: I.column_blocks(mat)
[[1], [0], [2]]

```



**get\_frob\_pow()**

Return the power of the Frobenius automorphism which generates the corresponding component of `self`.

EXAMPLES:

```
sage: from sage.coding.codecan.codecan import InnerGroup
sage: I = InnerGroup(10)
sage: I.get_frob_pow()
1
```

`sage.coding.codecan.codecan.OP_represent` (*n*, *merges*, *perm*)

Demonstration and testing.

TESTS:

```
sage: from sage.groups.perm_gps.partn_ref.automorphism_group_canonical_label import OP_represent
sage: OP_represent(9, [(0,1), (2,3), (3,4)], [1,2,0,4,3,6,7,5,8])
Allocating OrbitPartition...
Allocation passed.
Checking that each element reports itself as its root.
Each element reports itself as its root.
Merging:
Merged 0 and 1.
Merged 2 and 3.
Merged 3 and 4.
Done merging.
Finding:
0 -> 0, root: size=2, mcr=0, rank=1
1 -> 0
2 -> 2, root: size=3, mcr=2, rank=1
3 -> 2
4 -> 2
5 -> 5, root: size=1, mcr=5, rank=0
6 -> 6, root: size=1, mcr=6, rank=0
7 -> 7, root: size=1, mcr=7, rank=0
8 -> 8, root: size=1, mcr=8, rank=0
Allocating array to test merge_perm.
Allocation passed.
Merging permutation: [1, 2, 0, 4, 3, 6, 7, 5, 8]
Done merging.
Finding:
0 -> 0, root: size=5, mcr=0, rank=2
1 -> 0
2 -> 0
3 -> 0
4 -> 0
5 -> 5, root: size=3, mcr=5, rank=1
6 -> 5
7 -> 5
8 -> 8, root: size=1, mcr=8, rank=0
Deallocating OrbitPartition.
Done.
```

`sage.coding.codecan.codecan.PS_represent` (*partition*, *splits*)

Demonstration and testing.

TESTS:

```

sage: from sage.groups.perm_gps.partn_ref.automorphism_group_canonical_label import PS_represent
sage: PS_represent([[6],[3,4,8,7],[1,9,5],[0,2]], [6,1,8,2])
Allocating PartitionStack...
Allocation passed:
(0 1 2 3 4 5 6 7 8 9)
Checking that entries are in order and correct level.
Everything seems in order, deallocating.
Deallocated.
Creating PartitionStack from partition [[6], [3, 4, 8, 7], [1, 9, 5], [0, 2]].
PartitionStack's data:
entries -> [6, 3, 4, 8, 7, 1, 9, 5, 0, 2]
levels -> [0, 10, 10, 10, 0, 10, 10, 0, 10, -1]
depth = 0, degree = 10
(6|3 4 8 7|1 9 5|0 2)
Checking PS_is_discrete:
False
Checking PS_num_cells:
4
Checking PS_is_mcr, min cell reps are:
[6, 3, 1, 0]
Checking PS_is_fixed, fixed elements are:
[6]
Copying PartitionStack:
(6|3 4 8 7|1 9 5|0 2)
Checking for consistency.
Everything is consistent.
Clearing copy:
(0 3 4 8 7 1 9 5 6 2)
Splitting point 6 from original:
0
(6|3 4 8 7|1 9 5|0 2)
Splitting point 1 from original:
5
(6|3 4 8 7|1|5 9|0 2)
Splitting point 8 from original:
1
(6|8|3 4 7|1|5 9|0 2)
Splitting point 2 from original:
8
(6|8|3 4 7|1|5 9|2|0)
Getting permutation from PS2->PS:
[6, 1, 0, 8, 3, 9, 2, 7, 4, 5]
Finding first smallest:
Minimal element is 5, bitset is:
0000010001
Finding element 1:
Location is: 5
Bitset is:
0100000000
Deallocating PartitionStacks.
Done.

```

**class** sage.coding.codecan.codecan.**PartitionRefinementLinearCode**

Bases: sage.groups.perm\_gps.partn\_ref2.refinement\_generic.PartitionRefinement\_generic

See [sage.coding.codecan.codecan](#).

EXAMPLES:

```

sage: from sage.coding.codecan.codecan import PartitionRefinementLinearCode
sage: mat = codes.HammingCode(GF(3), 3).dual_code().generator_matrix()
sage: P = PartitionRefinementLinearCode(mat.ncols(), mat)
sage: cf = P.get_canonical_form(); cf
[1 0 0 0 0 1 1 1 1 1 1 1]
[0 1 0 1 1 0 0 1 1 2 2 1 2]
[0 0 1 1 2 1 2 1 2 1 2 0 0]

```

```

sage: cf.echelon_form() == (P.get_transporter() * mat).echelon_form()
True

```

```

sage: P.get_autom_order_permutation() == GL(3, GF(3)).order() / (len(GF(3))-1)
True
sage: A = P.get_autom_gens()
sage: all( [(a*mat).echelon_form() == mat.echelon_form() for a in A])
True

```

**get\_autom\_gens()**

Return generators of the automorphism group of the initial matrix.

**EXAMPLES:**

```

sage: from sage.coding.codecan.codecan import PartitionRefinementLinearCode
sage: mat = codes.HammingCode(GF(3), 3).dual_code().generator_matrix()
sage: P = PartitionRefinementLinearCode(mat.ncols(), mat)
sage: A = P.get_autom_gens()
sage: all( [(a*mat).echelon_form() == mat.echelon_form() for a in A])
True

```

**get\_autom\_order\_inner\_stabilizer()**

Return the order of the stabilizer of the initial matrix under the action of the inner group  $G$ .

**EXAMPLES:**

```

sage: from sage.coding.codecan.codecan import PartitionRefinementLinearCode
sage: mat = codes.HammingCode(GF(3), 3).dual_code().generator_matrix()
sage: P = PartitionRefinementLinearCode(mat.ncols(), mat)
sage: P.get_autom_order_inner_stabilizer()
2
sage: mat2 = Matrix(GF(4, 'a'), [[1,0,1], [0,1,1]])
sage: P2 = PartitionRefinementLinearCode(mat2.ncols(), mat2)
sage: P2.get_autom_order_inner_stabilizer()
6

```

**get\_canonical\_form()**

Return the canonical form for this matrix.

**EXAMPLES:**

```

sage: from sage.coding.codecan.codecan import PartitionRefinementLinearCode
sage: mat = codes.HammingCode(GF(3), 3).dual_code().generator_matrix()
sage: P1 = PartitionRefinementLinearCode(mat.ncols(), mat)
sage: CF1 = P1.get_canonical_form()
sage: s = SemimonomialTransformationGroup(GF(3), mat.ncols()).an_element()
sage: P2 = PartitionRefinementLinearCode(mat.ncols(), s*mat)
sage: CF1 == P2.get_canonical_form()
True

```

**get\_transporter()**

Return the transporter element, mapping the initial matrix to its canonical form.

## EXAMPLES:

```

sage: from sage.coding.codecan.codecan import PartitionRefinementLinearCode
sage: mat = codes.HammingCode(GF(3), 3).dual_code().generator_matrix()
sage: P = PartitionRefinementLinearCode(mat.ncols(), mat)
sage: CF = P.get_canonical_form()
sage: t = P.get_transporter()
sage: (t*mat).echelon_form() == CF.echelon_form()
True

```

```

sage.coding.codecan.codecan.SC_test_list_perms(L, n, limit, gap, limit_complain,
                                              test_contains)

```

Test that the permutation group generated by list perms in L of degree n is of the correct order, by comparing with GAP. Don't test if the group is of size greater than limit.

## TESTS:

```

sage: from sage.groups.perm_gps.partn_ref.automorphism_group_canonical_label import SC_test_list_perms
sage: limit = 10^7
sage: def test_Sn_on_m_points(n, m, gap, contains):
...     perm1 = [1,0] + range(m)[2:]
...     perm2 = [(i+1)%n for i in range(n)] + range(m)[n:]
...     SC_test_list_perms([perm1, perm2], m, limit, gap, 0, contains)
sage: for i in range(2,9):
...     test_Sn_on_m_points(i,i,1,0)
sage: for i in range(2,9):
...     test_Sn_on_m_points(i,i,0,1)
sage: for i in range(2,9):
...     test_Sn_on_m_points(i,i,1,1) # long time
sage: test_Sn_on_m_points(8,8,1,1)
sage: def test_stab_chain_fns_1(n, gap, contains):
...     perm1 = sum([[2*i+1,2*i] for i in range(n)], [])
...     perm2 = [(i+1)%(2*n) for i in range(2*n)]
...     SC_test_list_perms([perm1, perm2], 2*n, limit, gap, 0, contains)
sage: for n in range(1,11):
...     test_stab_chain_fns_1(n, 1, 0)
sage: for n in range(1,11):
...     test_stab_chain_fns_1(n, 0, 1)
sage: for n in range(1,9):
...     test_stab_chain_fns_1(n, 1, 1) # long time
sage: test_stab_chain_fns_1(11, 1, 1)
sage: def test_stab_chain_fns_2(n, gap, contains):
...     perms = []
...     for p,e in factor(n):
...         perm1 = [(p*(i//p)) + ((i+1)%p) for i in range(n)]
...         perms.append(perm1)
...     SC_test_list_perms(perms, n, limit, gap, 0, contains)
sage: for n in range(2,11):
...     test_stab_chain_fns_2(n, 1, 0)
sage: for n in range(2,11):
...     test_stab_chain_fns_2(n, 0, 1)
sage: for n in range(2,11):
...     test_stab_chain_fns_2(n, 1, 1) # long time
sage: test_stab_chain_fns_2(11, 1, 1)
sage: def test_stab_chain_fns_3(n, gap, contains):
...     perm1 = [(-i)%n for i in range(n)]
...     perm2 = [(i+1)%n for i in range(n)]
...     SC_test_list_perms([perm1, perm2], n, limit, gap, 0, contains)
sage: for n in range(2,20):
...     test_stab_chain_fns_3(n, 1, 0)

```

```

sage: for n in range(2,20):
...     test_stab_chain_fns_3(n, 0, 1)
sage: for n in range(2,14):
...     test_stab_chain_fns_3(n, 1, 1) # long time
sage: test_stab_chain_fns_3(20, 1, 1)
sage: def test_stab_chain_fns_4(n, g, gap, contains):
...     perms = []
...     for _ in range(g):
...         perm = range(n)
...         shuffle(perm)
...         perms.append(perm)
...     SC_test_list_perms(perms, n, limit, gap, 0, contains)
sage: for n in range(4,9):
...     test_stab_chain_fns_4(n, 1, 1, 0) # long time
...     test_stab_chain_fns_4(n, 2, 1, 0) # long time
...     test_stab_chain_fns_4(n, 2, 1, 0) # long time
...     test_stab_chain_fns_4(n, 2, 1, 0) # long time
...     test_stab_chain_fns_4(n, 2, 1, 0) # long time
...     test_stab_chain_fns_4(n, 3, 1, 0) # long time
sage: for n in range(4,9):
...     test_stab_chain_fns_4(n, 1, 0, 1)
...     for j in range(6):
...         test_stab_chain_fns_4(n, 2, 0, 1)
...     test_stab_chain_fns_4(n, 3, 0, 1)
sage: for n in range(4,8):
...     test_stab_chain_fns_4(n, 1, 1, 1) # long time
...     test_stab_chain_fns_4(n, 2, 1, 1) # long time
...     test_stab_chain_fns_4(n, 2, 1, 1) # long time
...     test_stab_chain_fns_4(n, 3, 1, 1) # long time
sage: test_stab_chain_fns_4(8, 2, 1, 1)
sage: def test_stab_chain_fns_5(n, gap, contains):
...     perms = []
...     m = n//3
...     perm1 = range(2*m)
...     shuffle(perm1)
...     perm1 += range(2*m,n)
...     perm2 = range(m,n)
...     shuffle(perm2)
...     perm2 = range(m) + perm2
...     SC_test_list_perms([perm1, perm2], n, limit, gap, 0, contains)
sage: for n in [4..9]:
...     for _ in range(2):
...         test_stab_chain_fns_5(n, 1, 0) # long time
sage: for n in [4..8]:
...     test_stab_chain_fns_5(n, 0, 1) # long time
sage: for n in [4..9]:
...     test_stab_chain_fns_5(n, 1, 1) # long time
sage: def random_perm(x):
...     shuffle(x)
...     return x
sage: def test_stab_chain_fns_6(m,n,k, gap, contains):
...     perms = []
...     for i in range(k):
...         perm = sum([random_perm(range(i*(n//m),min(n, (i+1)*(n//m)))) for i in range(m)], [])
...         perms.append(perm)
...     SC_test_list_perms(perms, m*(n//m), limit, gap, 0, contains)
sage: for m in range(2,9):
...     for n in range(m,3*m):

```

```

...         for k in range(1,3):
...             test_stab_chain_fns_6(m,n,k, 1, 0) # long time
sage: for m in range(2,10):
...     for n in range(m,4*m):
...         for k in range(1,3):
...             test_stab_chain_fns_6(m,n,k, 0, 1)
sage: test_stab_chain_fns_6(10,20,2, 1, 1)
sage: test_stab_chain_fns_6(8,16,2, 1, 1)
sage: test_stab_chain_fns_6(6,36,2, 1, 1)
sage: test_stab_chain_fns_6(4,40,3, 1, 1)
sage: test_stab_chain_fns_6(4,40,2, 1, 1)
sage: def test_stab_chain_fns_7(n, cop, gap, contains):
...     perms = []
...     for i in range(0,n//2,2):
...         p = range(n)
...         p[i] = i+1
...         p[i+1] = i
...     if cop:
...         perms.append([c for c in p])
...     else:
...         perms.append(p)
...     SC_test_list_perms(perms, n, limit, gap, 0, contains)
sage: for n in [6..14]:
...     test_stab_chain_fns_7(n, 1, 1, 0)
...     test_stab_chain_fns_7(n, 0, 1, 0)
sage: for n in [6..30]:
...     test_stab_chain_fns_7(n, 1, 0, 1)
...     test_stab_chain_fns_7(n, 0, 0, 1)
sage: for n in [6..14]:
...     test_stab_chain_fns_7(n, 1, 1, 1) # long time
...     test_stab_chain_fns_7(n, 0, 1, 1) # long time
sage: test_stab_chain_fns_7(20, 1, 1, 1)
sage: test_stab_chain_fns_7(20, 0, 1, 1)

```

## 6.2 Canonical forms and automorphisms for linear codes over finite fields

We implemented the algorithm described in [Feu2009] which computes, a unique code (canonical form) in the equivalence class of a given linear code  $C \leq \mathbf{F}_q^n$ . Furthermore, this algorithm will return the automorphism group of  $C$ , too. You will find more details about the algorithm in the documentation of the class `LinearCodeAutGroupCanLabel`.

The equivalence of codes is modeled as a group action by the group  $G = \mathbf{F}_q^{*n} \rtimes (\text{Aut}(\mathbf{F}_q) \times S_n)$  on the set of subspaces of  $\mathbf{F}_q^n$ . The group  $G$  will be called the semimonomial group of degree  $n$ .

The algorithm is started by initializing the class `LinearCodeAutGroupCanLabel`. When the object gets available, all computations are already finished and you can access the relevant data using the member functions:

- `get_canonical_form()`
- `get_transporter()`
- `get_autom_gens()`

People do also use some weaker notions of equivalence, namely **permutational** equivalence and monomial equivalence (**linear** isometries). These can be seen as the subgroups  $S_n$  and  $\mathbf{F}_q^{*n} \rtimes S_n$  of  $G$ . If you are interested in one of

these notions, you can just pass the optional parameter `algorithm_type`.

A second optional parameter `P` allows you to restrict the group of permutations  $S_n$  to a subgroup which respects the coloring given by `P`.

AUTHORS:

- Thomas Feulner (2012-11-15): initial version

REFERENCES:

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(3), 3).dual_code()
sage: P = LinearCodeAutGroupCanLabel(C)
sage: P.get_canonical_form().generator_matrix()
[1 0 0 0 0 1 1 1 1 1 1 1]
[0 1 0 1 1 0 0 1 1 2 2 1]
[0 0 1 1 2 1 2 1 2 1 2 0]
sage: LinearCode(P.get_transporter()*C.generator_matrix()) == P.get_canonical_form()
True
sage: A = P.get_autom_gens()
sage: all([ LinearCode(a*C.generator_matrix()) == C for a in A])
True
sage: P.get_autom_order() == GL(3, GF(3)).order()
True
```

If the dimension of the dual code is smaller, we will work on this code:

```
sage: C2 = codes.HammingCode(GF(3), 3)
sage: P2 = LinearCodeAutGroupCanLabel(C2)
sage: P2.get_canonical_form().parity_check_matrix() == P.get_canonical_form().generator_matrix()
True
```

There is a specialization of this algorithm to pass a coloring on the coordinates. This is just a list of lists, telling the algorithm which columns do share the same coloring:

```
sage: C = codes.HammingCode(GF(4, 'a'), 3).dual_code()
sage: P = LinearCodeAutGroupCanLabel(C, P=[ [0], [1], range(2, C.length()) ])
sage: P.get_autom_order()
864
sage: A = [a.get_perm() for a in P.get_autom_gens()]
sage: H = SymmetricGroup(21).subgroup(A)
sage: H.orbits()
[[1], [2], [3, 5, 4], [6, 10, 13, 20, 17, 9, 8, 11, 18, 15, 14, 16, 12, 19, 21, 7]]
```

We can also restrict the group action to linear isometries:

```
sage: P = LinearCodeAutGroupCanLabel(C, algorithm_type="linear")
sage: P.get_autom_order() == GL(3, GF(4, 'a')).order()
True
```

and to the action of the symmetric group only:

```
sage: P = LinearCodeAutGroupCanLabel(C, algorithm_type="permutational")
sage: P.get_autom_order() == C.permutation_automorphism_group().order()
True
```

```
class sage.coding.codecan.autgroup_can_label.LinearCodeAutGroupCanLabel (C,
                                                                    P=None,
                                                                    algo-
                                                                    rithm_type='semilinear')
```

Canonical representatives and automorphism group computation for linear codes over finite fields.

There are several notions of equivalence for linear codes: Let  $C, D$  be linear codes of length  $n$  and dimension  $k$ .  $C$  and  $D$  are said to be

- permutational equivalent, if there is some permutation  $\pi \in S_n$  such that  $(c_{\pi(0)}, \dots, c_{\pi(n-1)}) \in D$  for all  $c \in C$ .
- linear equivalent, if there is some permutation  $\pi \in S_n$  and a vector  $\phi \in \mathbb{F}_q^{*n}$  of units of length  $n$  such that  $(c_{\pi(0)}\phi_0^{-1}, \dots, c_{\pi(n-1)}\phi_{n-1}^{-1}) \in D$  for all  $c \in C$ .
- semilinear equivalent, if there is some permutation  $\pi \in S_n$ , a vector  $\phi$  of units of length  $n$  and a field automorphism  $\alpha$  such that  $(\alpha(c_{\pi(0)})\phi_0^{-1}, \dots, \alpha(c_{\pi(n-1)})\phi_{n-1}^{-1}) \in D$  for all  $c \in C$ .

These are group actions. This class provides an algorithm that will compute a unique representative  $D$  in the orbit of the given linear code  $C$ . Furthermore, the group element  $g$  with  $g * C = D$  and the automorphism group of  $C$  will be computed as well.

There is also the possibility to restrict the permutational part of this action to a Young subgroup of  $S_n$ . This could be achieved by passing a partition  $P$  (as a list of lists) of the set  $\{0, \dots, n-1\}$ . This is an option which is also available in the computation of a canonical form of a graph, see `sage.graphs.generic_graph.GenericGraph.canonical_label()`.

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(3), 3).dual_code()
sage: P = LinearCodeAutGroupCanLabel(C)
sage: P.get_canonical_form().generator_matrix()
[1 0 0 0 0 1 1 1 1 1 1 1]
[0 1 0 1 1 0 0 1 1 2 2 1]
[0 0 1 1 2 1 2 1 2 1 2 0]
sage: LinearCode(P.get_transporter()*C.generator_matrix()) == P.get_canonical_form()
True
sage: a = P.get_autom_gens()[0]
sage: (a*C.generator_matrix()).echelon_form() == C.generator_matrix().echelon_form()
True
sage: P.get_autom_order() == GL(3, GF(3)).order()
True
```

**get\_PGgammaL\_gens()**

Return the set of generators translated to the group  $P\Gamma L(k, q)$ .

There is a geometric point of view of code equivalence. A linear code is identified with the multiset of points in the finite projective geometry  $PG(k-1, q)$ . The equivalence of codes translates to the natural action of  $P\Gamma L(k, q)$ . Therefore, we may interpret the group as a subgroup of  $P\Gamma L(k, q)$  as well.

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(4, 'a'), 3).dual_code()
sage: A = LinearCodeAutGroupCanLabel(C).get_PGgammaL_gens()
sage: Gamma = C.generator_matrix()
sage: N = [ x.monic() for x in Gamma.columns() ]
sage: all([ (g[0]*n).apply_map(g[1]).monic() in N for n in N for g in A])
True
```



**get\_PGgammaL\_order()**

Return the size of the automorphism group as a subgroup of  $PTL(k, q)$ .

There is a geometric point of view of code equivalence. A linear code is identified with the multiset of points in the finite projective geometry  $PG(k-1, q)$ . The equivalence of codes translates to the natural action of  $PTL(k, q)$ . Therefore, we may interpret the group as a subgroup of  $PTL(k, q)$  as well.

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(4, 'a'), 3).dual_code()
sage: LinearCodeAutGroupCanLabel(C).get_PGgammaL_order() == GL(3, GF(4, 'a')).order()*2/3
True
```

**get\_autom\_gens()**

Return a generating set for the automorphism group of the code.

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(2), 3).dual_code()
sage: A = LinearCodeAutGroupCanLabel(C).get_autom_gens()
sage: Gamma = C.generator_matrix().echelon_form()
sage: all([(g*Gamma).echelon_form() == Gamma for g in A])
True
```

**get\_autom\_order()**

Return the size of the automorphism group of the code.

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(2), 3).dual_code()
sage: LinearCodeAutGroupCanLabel(C).get_autom_order()
168
```

**get\_canonical\_form()**

Return the canonical orbit representative we computed.

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(3), 3).dual_code()
sage: CF1 = LinearCodeAutGroupCanLabel(C).get_canonical_form()
sage: s = SemimonomialTransformationGroup(GF(3), C.length()).an_element()
sage: C2 = LinearCode(s*C.generator_matrix())
sage: CF2 = LinearCodeAutGroupCanLabel(C2).get_canonical_form()
sage: CF1 == CF2
True
```

**get\_transporter()**

Return the element which maps the code to its canonical form.

EXAMPLES:

```
sage: from sage.coding.codecan.autgroup_can_label import LinearCodeAutGroupCanLabel
sage: C = codes.HammingCode(GF(2), 3).dual_code()
sage: P = LinearCodeAutGroupCanLabel(C)
sage: g = P.get_transporter()
sage: D = P.get_canonical_form()
sage: (g*C.generator_matrix()).echelon_form() == D.generator_matrix().echelon_form()
True
```



## INDICES AND TABLES

- Index
- Module Index
- Search Page



## BIBLIOGRAPHY

- [Nielsen] Johan S. R. Nielsen, (<https://bitbucket.org/jsrn/codinglib/>)
- [BS03] I. Bouyukliev and J. Simonis, Some new results on optimal codes over  $F_5$ , Designs, Codes and Cryptography 30, no. 1 (2003): 97-111, [http://www.moi.math.bas.bg/moiuser/~iliya/pdf\\_site/gf5srev.pdf](http://www.moi.math.bas.bg/moiuser/~iliya/pdf_site/gf5srev.pdf),
- [ChenDB] Eric Chen, Online database of two-weight codes, <http://moodle.tec.hkr.se/~chen/research/2-weight-codes/search.php>
- [Kohnert07] A. Kohnert, Constructing two-weight codes with prescribed groups of automorphisms, Discrete applied mathematics 155, no. 11 (2007): 1451-1457. <http://linearcodes.uni-bayreuth.de/twoweight/>
- [Disset00] L. Dissett, Combinatorial and computational aspects of finite geometries, 2000, <https://tspace.library.utoronto.ca/bitstream/1807/14575/1/NQ49844.pdf>
- [HJ04] Tom Hoeholdt and Joern Justesen, A Course In Error-Correcting Codes, EMS, 2004
- [G02] Shuhong Gao, A new algorithm for decoding Reed-Solomon Codes, January 31, 2002
- [R06] Ron Roth, Introduction to Coding Theory, Cambridge University Press, 2006
- [R] Introduction to Coding Theory, Ron Roth, Cambridge University Press, 2006
- [GS99] Venkatesan Guruswami and Madhu Sudan, Improved Decoding of Reed-Solomon Codes and Algebraic-Geometric Codes, 1999
- [N13] Johan S. R. Nielsen, List Decoding of Algebraic Codes, Ph.D. Thesis, Technical University of Denmark, 2013
- [BS11] E. Byrne and A. Sneyd, On the Parameters of Codes with Two Homogeneous Weights. WCC 2011-Workshop on coding and cryptography, pp. 81-90. 2011. <https://hal.inria.fr/inria-00607341/document>
- [D] I. Duursma, "Extremal weight enumerators and ultraspherical polynomials"
- [HP] W. C. Huffman, V. Pless, Fundamentals of Error-Correcting Codes, Cambridge Univ. Press, 2003.
- [J] D. Joyner, Toric codes over finite fields, Applicable Algebra in Engineering, Communication and Computing, 15, (2004), p. 63-79.
- [BM] Bazzi and Mitter, {it Some constructions of codes from group actions}, (preprint March 2003, available on Mitter's MIT website).
- [Jresidue] D. Joyner, {it On quadratic residue codes and hyperelliptic curves}, (preprint 2006)
- [Feu2009] T. Feulner. The Automorphism Groups of Linear Codes and Canonical Representatives of Their Semilinear Isometry Classes. Advances in Mathematics of Communications 3 (4), pp. 363-383, Nov 2009



**C**

- `sage.coding.binary_code`, 13
- `sage.coding.bounds_catalog`, 7
- `sage.coding.channel_constructions`, 125
- `sage.coding.channels_catalog`, 7
- `sage.coding.code_bounds`, 113
- `sage.coding.code_constructions`, 93
- `sage.coding.codecan.autgroup_can_label`, 146
- `sage.coding.codecan.codecan`, 139
- `sage.coding.codes_catalog`, 8
- `sage.coding.decoder`, 1
- `sage.coding.decoders_catalog`, 10
- `sage.coding.delsarte_bounds`, 119
- `sage.coding.encoder`, 3
- `sage.coding.encoders_catalog`, 10
- `sage.coding.grs`, 22
- `sage.coding.guava`, 109
- `sage.coding.guruswami_sudan.gs_decoder`, 38
- `sage.coding.guruswami_sudan.interpolation`, 45
- `sage.coding.guruswami_sudan.rootfinding`, 48
- `sage.coding.guruswami_sudan.utils`, 49
- `sage.coding.hamming_code`, 37
- `sage.coding.linear_code`, 51
- `sage.coding.sd_codes`, 107
- `sage.coding.source_coding.huffman`, 133
- `sage.coding.two_weight_db`, 10





## A

AbstractLinearCode (class in sage.coding.linear\_code), 54  
 add\_decoder() (sage.coding.linear\_code.AbstractLinearCode method), 55  
 add\_encoder() (sage.coding.linear\_code.AbstractLinearCode method), 56  
 ambient\_space() (sage.coding.linear\_code.AbstractLinearCode method), 56  
 apply\_permutation() (sage.coding.binary\_code.BinaryCode method), 14  
 apply\_shifts() (in module sage.coding.guruswami\_sudan.utils), 49  
 assmus\_mattson\_designs() (sage.coding.linear\_code.AbstractLinearCode method), 57  
 automorphism\_group\_gens() (sage.coding.linear\_code.AbstractLinearCode method), 58

## B

base\_field() (sage.coding.linear\_code.AbstractLinearCode method), 58  
 basis() (sage.coding.linear\_code.AbstractLinearCode method), 58  
 BCHCode() (in module sage.coding.code\_constructions), 94  
 best\_known\_linear\_code() (in module sage.coding.linear\_code), 88  
 best\_known\_linear\_code\_www() (in module sage.coding.linear\_code), 88  
 BinaryCode (class in sage.coding.binary\_code), 13  
 BinaryCodeClassifier (class in sage.coding.binary\_code), 16  
 BinaryGolayCode() (in module sage.coding.code\_constructions), 95  
 BinaryReedMullerCode() (in module sage.coding.guava), 110  
 binomial\_moment() (sage.coding.linear\_code.AbstractLinearCode method), 59  
 bounds\_minimum\_distance() (in module sage.coding.linear\_code), 89

## C

canonical\_representative() (sage.coding.linear\_code.AbstractLinearCode method), 59  
 cardinality() (sage.coding.linear\_code.AbstractLinearCode method), 60  
 Channel (class in sage.coding.channel\_constructions), 125  
 characteristic() (sage.coding.linear\_code.AbstractLinearCode method), 60  
 characteristic\_polynomial() (sage.coding.linear\_code.AbstractLinearCode method), 60  
 check\_mat() (sage.coding.linear\_code.AbstractLinearCode method), 60  
 chinen\_polynomial() (sage.coding.linear\_code.AbstractLinearCode method), 60  
 cmp() (sage.coding.binary\_code.PartitionStack method), 18  
 code() (sage.coding.decoder.Decoder method), 1  
 code() (sage.coding.encoder.Encoder method), 4  
 code2leon() (in module sage.coding.linear\_code), 90  
 codesize\_upper\_bound() (in module sage.coding.code\_bounds), 115  
 column\_blocks() (sage.coding.codecan.codecan.InnerGroup method), 140

`column_multipliers()` (sage.coding.grs.GeneralizedReedSolomonCode method), 34  
`connected_encoder()` (sage.coding.decoder.Decoder method), 1  
`covering_radius()` (sage.coding.grs.GeneralizedReedSolomonCode method), 35  
`covering_radius()` (sage.coding.linear\_code.AbstractLinearCode method), 61  
`CyclicCode()` (in module sage.coding.code\_constructions), 95  
`CyclicCodeFromCheckPolynomial()` (in module sage.coding.code\_constructions), 96  
`CyclicCodeFromGeneratingPolynomial()` (in module sage.coding.code\_constructions), 96

## D

`decode()` (sage.coding.linear\_code.AbstractLinearCode method), 61  
`decode()` (sage.coding.source\_coding.huffman.Huffman method), 135  
`decode_to_code()` (sage.coding.decoder.Decoder method), 2  
`decode_to_code()` (sage.coding.grs.GRSBerlekampWelchDecoder method), 23  
`decode_to_code()` (sage.coding.grs.GRSGaoDecoder method), 30  
`decode_to_code()` (sage.coding.grs.GRSKeyEquationSyndromeDecoder method), 32  
`decode_to_code()` (sage.coding.guruswami\_sudan.gs\_decoder.GRSGuruswamiSudanDecoder method), 40  
`decode_to_code()` (sage.coding.linear\_code.AbstractLinearCode method), 61  
`decode_to_code()` (sage.coding.linear\_code.LinearCodeNearestNeighborDecoder method), 84  
`decode_to_code()` (sage.coding.linear\_code.LinearCodeSyndromeDecoder method), 87  
`decode_to_message()` (sage.coding.decoder.Decoder method), 2  
`decode_to_message()` (sage.coding.grs.GeneralizedReedSolomonCode method), 35  
`decode_to_message()` (sage.coding.grs.GRSBerlekampWelchDecoder method), 24  
`decode_to_message()` (sage.coding.grs.GRSErrorErasureDecoder method), 25  
`decode_to_message()` (sage.coding.grs.GRSGaoDecoder method), 31  
`decode_to_message()` (sage.coding.grs.GRSKeyEquationSyndromeDecoder method), 33  
`decode_to_message()` (sage.coding.guruswami\_sudan.gs\_decoder.GRSGuruswamiSudanDecoder method), 40  
`decode_to_message()` (sage.coding.linear\_code.AbstractLinearCode method), 62  
`Decoder` (class in sage.coding.decoder), 1  
`decoder()` (sage.coding.linear\_code.AbstractLinearCode method), 62  
`decoder_type()` (sage.coding.decoder.Decoder method), 2  
`decoders_available()` (sage.coding.linear\_code.AbstractLinearCode method), 63  
`decoding_radius()` (sage.coding.decoder.Decoder method), 3  
`decoding_radius()` (sage.coding.grs.GRSBerlekampWelchDecoder method), 25  
`decoding_radius()` (sage.coding.grs.GRSErrorErasureDecoder method), 26  
`decoding_radius()` (sage.coding.grs.GRSGaoDecoder method), 32  
`decoding_radius()` (sage.coding.grs.GRSKeyEquationSyndromeDecoder method), 33  
`decoding_radius()` (sage.coding.guruswami\_sudan.gs\_decoder.GRSGuruswamiSudanDecoder method), 41  
`decoding_radius()` (sage.coding.linear\_code.LinearCodeNearestNeighborDecoder method), 85  
`decoding_radius()` (sage.coding.linear\_code.LinearCodeSyndromeDecoder method), 87  
`DecodingError`, 3  
`delsarte_bound_additive_hamming_space()` (in module sage.coding.delsarte\_bounds), 120  
`delsarte_bound_hamming_space()` (in module sage.coding.delsarte\_bounds), 122  
`dimension()` (sage.coding.linear\_code.AbstractLinearCode method), 63  
`dimension_upper_bound()` (in module sage.coding.code\_bounds), 115  
`direct_sum()` (sage.coding.linear\_code.AbstractLinearCode method), 63  
`divisor()` (sage.coding.linear\_code.AbstractLinearCode method), 63  
`DuadicCodeEvenPair()` (in module sage.coding.code\_constructions), 97  
`DuadicCodeOddPair()` (in module sage.coding.code\_constructions), 98  
`dual_code()` (sage.coding.grs.GeneralizedReedSolomonCode method), 35  
`dual_code()` (sage.coding.linear\_code.AbstractLinearCode method), 64

## E

[elias\\_bound\\_asymp\(\)](#) (in module `sage.coding.code_bounds`), 115  
[elias\\_upper\\_bound\(\)](#) (in module `sage.coding.code_bounds`), 115  
[encode\(\)](#) (`sage.coding.encoder.Encoder` method), 4  
[encode\(\)](#) (`sage.coding.grs.GRSEvaluationPolynomialEncoder` method), 27  
[encode\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 64  
[encode\(\)](#) (`sage.coding.source_coding.huffman.Huffman` method), 135  
[Encoder](#) (class in `sage.coding.encoder`), 3  
[encoder\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 64  
[encoders\\_available\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 65  
[encoding\\_table\(\)](#) (`sage.coding.source_coding.huffman.Huffman` method), 136  
[EncodingError](#), 6  
[entropy\(\)](#) (in module `sage.coding.code_bounds`), 116  
[entropy\\_inverse\(\)](#) (in module `sage.coding.code_bounds`), 116  
[error\\_probability\(\)](#) (`sage.coding.channel_constructions.QarySymmetricChannel` method), 129  
[ErrorErasureChannel](#) (class in `sage.coding.channel_constructions`), 127  
[evaluation\\_points\(\)](#) (`sage.coding.grs.GeneralizedReedSolomonCode` method), 35  
[extended\\_code\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 65  
[ExtendedBinaryGolayCode\(\)](#) (in module `sage.coding.code_constructions`), 98  
[ExtendedQuadraticResidueCode\(\)](#) (in module `sage.coding.code_constructions`), 98  
[ExtendedTernaryGolayCode\(\)](#) (in module `sage.coding.code_constructions`), 99

## F

[format\\_interval\(\)](#) (in module `sage.coding.channel_constructions`), 131  
[frequency\\_table\(\)](#) (in module `sage.coding.source_coding.huffman`), 137

## G

[galois\\_closure\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 66  
[gen\\_mat\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 66  
[gen\\_mat\\_systematic\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 66  
[GeneralizedReedSolomonCode](#) (class in `sage.coding.grs`), 34  
[generate\\_children\(\)](#) (`sage.coding.binary_code.BinaryCodeClassifier` method), 16  
[generator\\_matrix\(\)](#) (`sage.coding.encoder.Encoder` method), 5  
[generator\\_matrix\(\)](#) (`sage.coding.grs.GRSEvaluationVectorEncoder` method), 29  
[generator\\_matrix\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 66  
[generator\\_matrix\(\)](#) (`sage.coding.linear_code.LinearCode` method), 83  
[generator\\_matrix\(\)](#) (`sage.coding.linear_code.LinearCodeGeneratorMatrixEncoder` method), 84  
[generator\\_matrix\(\)](#) (`sage.coding.linear_code.LinearCodeParityCheckEncoder` method), 85  
[generator\\_matrix\\_systematic\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 66  
[gens\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 67  
[genus\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 67  
[get\\_autom\\_gens\(\)](#) (`sage.coding.codecan.autgroup_can_label.LinearCodeAutGroupCanLabel` method), 149  
[get\\_autom\\_gens\(\)](#) (`sage.coding.codecan.codecan.PartitionRefinementLinearCode` method), 143  
[get\\_autom\\_order\(\)](#) (`sage.coding.codecan.autgroup_can_label.LinearCodeAutGroupCanLabel` method), 149  
[get\\_autom\\_order\\_inner\\_stabilizer\(\)](#) (`sage.coding.codecan.codecan.PartitionRefinementLinearCode` method), 143  
[get\\_canonical\\_form\(\)](#) (`sage.coding.codecan.autgroup_can_label.LinearCodeAutGroupCanLabel` method), 149  
[get\\_canonical\\_form\(\)](#) (`sage.coding.codecan.codecan.PartitionRefinementLinearCode` method), 143  
[get\\_frob\\_pow\(\)](#) (`sage.coding.codecan.codecan.InnerGroup` method), 141  
[get\\_PGgammaL\\_gens\(\)](#) (`sage.coding.codecan.autgroup_can_label.LinearCodeAutGroupCanLabel` method), 148  
[get\\_PGgammaL\\_order\(\)](#) (`sage.coding.codecan.autgroup_can_label.LinearCodeAutGroupCanLabel` method), 148

`get_transporter()` (sage.coding.codecan.autgroup\_can\_label.LinearCodeAutGroupCanLabel method), 149  
`get_transporter()` (sage.coding.codecan.codecan.PartitionRefinementLinearCode method), 143  
`gilbert_lower_bound()` (in module sage.coding.code\_bounds), 116  
`gilt()` (in module sage.coding.guruswami\_sudan.utils), 49  
`griesmer_upper_bound()` (in module sage.coding.code\_bounds), 117  
`GRSBerlekampWelchDecoder` (class in sage.coding.grs), 23  
`GRSErrorErasureDecoder` (class in sage.coding.grs), 25  
`GRSEvaluationPolynomialEncoder` (class in sage.coding.grs), 27  
`GRSEvaluationVectorEncoder` (class in sage.coding.grs), 29  
`GRSGaoDecoder` (class in sage.coding.grs), 29  
`GRSGuruswamiSudanDecoder` (class in sage.coding.guruswami\_sudan.gs\_decoder), 38  
`GRSKeyEquationSyndromeDecoder` (class in sage.coding.grs), 32  
`gs_interpolation_lee_osullivan()` (in module sage.coding.guruswami\_sudan.interpolation), 45  
`gs_interpolation_linalg()` (in module sage.coding.guruswami\_sudan.interpolation), 46  
`gs_satisfactory()` (sage.coding.guruswami\_sudan.gs\_decoder.GRSGuruswamiSudanDecoder static method), 41  
`guruswami_sudan_decoding_radius()` (sage.coding.guruswami\_sudan.gs\_decoder.GRSGuruswamiSudanDecoder static method), 42  
`gv_bound_asymp()` (in module sage.coding.code\_bounds), 117  
`gv_info_rate()` (in module sage.coding.code\_bounds), 117

## H

`hamming_bound_asymp()` (in module sage.coding.code\_bounds), 117  
`hamming_upper_bound()` (in module sage.coding.code\_bounds), 117  
`HammingCode` (class in sage.coding.hamming\_code), 37  
`Huffman` (class in sage.coding.source\_coding.huffman), 133

## I

`I2()` (in module sage.coding.sd\_codes), 108  
`information_set()` (sage.coding.linear\_code.AbstractLinearCode method), 67  
`InnerGroup` (class in sage.coding.codecan.codecan), 140  
`input_space()` (sage.coding.channel\_constructions.Channel method), 126  
`input_space()` (sage.coding.decoder.Decoder method), 3  
`interpolation_algorithm()` (sage.coding.guruswami\_sudan.gs\_decoder.GRSGuruswamiSudanDecoder method), 43  
`is_a_splitting()` (in module sage.coding.code\_constructions), 103  
`is_galois_closed()` (sage.coding.linear\_code.AbstractLinearCode method), 67  
`is_permutation_automorphism()` (sage.coding.linear\_code.AbstractLinearCode method), 68  
`is_permutation_equivalent()` (sage.coding.linear\_code.AbstractLinearCode method), 68  
`is_projective()` (sage.coding.linear\_code.AbstractLinearCode method), 68  
`is_self_dual()` (sage.coding.linear\_code.AbstractLinearCode method), 69  
`is_self_orthogonal()` (sage.coding.linear\_code.AbstractLinearCode method), 69  
`is_subcode()` (sage.coding.linear\_code.AbstractLinearCode method), 69

## J

`johnson_radius()` (in module sage.coding.guruswami\_sudan.utils), 49

## K

`Kravchuk()` (in module sage.coding.delsarte\_bounds), 119  
`Krawtchouk()` (in module sage.coding.delsarte\_bounds), 120

## L

`leading_term()` (in module sage.coding.guruswami\_sudan.utils), 50

[lee\\_osullivan\\_module\(\)](#) (in module `sage.coding.guruswami_sudan.interpolation`), 47  
[length\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 70  
[lift2smallest\\_field\(\)](#) (in module `sage.coding.code_constructions`), 105  
[lift2smallest\\_field2\(\)](#) (in module `sage.coding.code_constructions`), 105  
[ligt\(\)](#) (in module `sage.coding.guruswami_sudan.utils`), 50  
[LinearCode](#) (class in `sage.coding.linear_code`), 82  
[LinearCodeAutGroupCanLabel](#) (class in `sage.coding.codecan.autgroup_can_label`), 147  
[LinearCodeFromCheckMatrix\(\)](#) (in module `sage.coding.code_constructions`), 99  
[LinearCodeFromVectorSpace\(\)](#) (in module `sage.coding.linear_code`), 83  
[LinearCodeGeneratorMatrixEncoder](#) (class in `sage.coding.linear_code`), 84  
[LinearCodeNearestNeighborDecoder](#) (class in `sage.coding.linear_code`), 84  
[LinearCodeParityCheckEncoder](#) (class in `sage.coding.linear_code`), 85  
[LinearCodeSyndromeDecoder](#) (class in `sage.coding.linear_code`), 85  
[list\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 70  
[list\\_size\(\)](#) (`sage.coding.guruswami_sudan.gs_decoder.GRSGuruswamiSudanDecoder` method), 43

## M

[matA\(\)](#) (in module `sage.coding.sd_codes`), 108  
[matId\(\)](#) (in module `sage.coding.sd_codes`), 108  
[matrix\(\)](#) (`sage.coding.binary_code.BinaryCode` method), 14  
[maximum\\_error\\_weight\(\)](#) (`sage.coding.linear_code.LinearCodeSyndromeDecoder` method), 87  
[message\\_space\(\)](#) (`sage.coding.decoder.Decoder` method), 3  
[message\\_space\(\)](#) (`sage.coding.encoder.Encoder` method), 5  
[message\\_space\(\)](#) (`sage.coding.grs.GRSEvaluationPolynomialEncoder` method), 28  
[min\\_wt\\_vec\\_gap\(\)](#) (in module `sage.coding.linear_code`), 90  
[minimum\\_distance\(\)](#) (`sage.coding.grs.GeneralizedReedSolomonCode` method), 36  
[minimum\\_distance\(\)](#) (`sage.coding.hamming_code.HammingCode` method), 37  
[minimum\\_distance\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 70  
[module\\_composition\\_factors\(\)](#) (`sage.coding.linear_code.AbstractLinearCode` method), 71  
[mrrw1\\_bound\\_asymp\(\)](#) (in module `sage.coding.code_bounds`), 118  
[MS\(\)](#) (in module `sage.coding.sd_codes`), 108  
[MS2\(\)](#) (in module `sage.coding.sd_codes`), 108  
[multiplicity\(\)](#) (`sage.coding.guruswami_sudan.gs_decoder.GRSGuruswamiSudanDecoder` method), 43  
[multipliers\\_product\(\)](#) (`sage.coding.grs.GeneralizedReedSolomonCode` method), 36

## N

[n\\_k\\_params\(\)](#) (in module `sage.coding.guruswami_sudan.gs_decoder`), 45  
[number\\_erasures\(\)](#) (`sage.coding.channel_constructions.ErrorErasureChannel` method), 127  
[number\\_errors\(\)](#) (`sage.coding.channel_constructions.ErrorErasureChannel` method), 128  
[number\\_errors\(\)](#) (`sage.coding.channel_constructions.StaticErrorRateChannel` method), 130

## O

[OP\\_represent\(\)](#) (in module `sage.coding.codecan.codecan`), 141  
[OrbitPartition](#) (class in `sage.coding.binary_code`), 18  
[output\\_space\(\)](#) (`sage.coding.channel_constructions.Channel` method), 126

## P

[parameters\(\)](#) (`sage.coding.guruswami_sudan.gs_decoder.GRSGuruswamiSudanDecoder` method), 44  
[parameters\\_given\\_tau\(\)](#) (`sage.coding.guruswami_sudan.gs_decoder.GRSGuruswamiSudanDecoder` static method), 44

`parity_check_matrix()` (sage.coding.grs.GeneralizedReedSolomonCode method), 36  
`parity_check_matrix()` (sage.coding.hamming\_code.HammingCode method), 38  
`parity_check_matrix()` (sage.coding.linear\_code.AbstractLinearCode method), 71  
`parity_column_multipliers()` (sage.coding.grs.GeneralizedReedSolomonCode method), 36  
`PartitionRefinementLinearCode` (class in sage.coding.codecan.codecan), 142  
`PartitionStack` (class in sage.coding.binary\_code), 18  
`permutation_action()` (in module sage.coding.code\_constructions), 105  
`permutation_automorphism_group()` (sage.coding.linear\_code.AbstractLinearCode method), 72  
`permuted_code()` (sage.coding.linear\_code.AbstractLinearCode method), 73  
`plotkin_bound_asymp()` (in module sage.coding.code\_bounds), 118  
`plotkin_upper_bound()` (in module sage.coding.code\_bounds), 118  
`polynomial_to_list()` (in module sage.coding.guruswami\_sudan.utils), 50  
`print_basis()` (sage.coding.binary\_code.PartitionStack method), 19  
`print_data()` (sage.coding.binary\_code.BinaryCode method), 15  
`print_data()` (sage.coding.binary\_code.PartitionStack method), 19  
`probability_of_at_most_t_errors()` (sage.coding.channel\_constructions.QarySymmetricChannel method), 129  
`probability_of_exactly_t_errors()` (sage.coding.channel\_constructions.QarySymmetricChannel method), 129  
`PS_represent()` (in module sage.coding.codecan.codecan), 141  
`punctured()` (sage.coding.linear\_code.AbstractLinearCode method), 73  
`put_in_canonical_form()` (sage.coding.binary\_code.BinaryCodeClassifier method), 17  
`put_in_std_form()` (sage.coding.binary\_code.BinaryCode method), 16

## Q

`QarySymmetricChannel` (class in sage.coding.channel\_constructions), 128  
`QuadraticResidueCode()` (in module sage.coding.code\_constructions), 100  
`QuadraticResidueCodeEvenPair()` (in module sage.coding.code\_constructions), 100  
`QuadraticResidueCodeOddPair()` (in module sage.coding.code\_constructions), 101  
`QuasiQuadraticResidueCode()` (in module sage.coding.guava), 110

## R

`random_element()` (sage.coding.linear\_code.AbstractLinearCode method), 74  
`random_error_vector()` (in module sage.coding.channel\_constructions), 131  
`RandomLinearCode()` (in module sage.coding.code\_constructions), 102  
`RandomLinearCodeGuava()` (in module sage.coding.guava), 111  
`redundancy_matrix()` (sage.coding.linear\_code.AbstractLinearCode method), 74  
`ReedSolomonCode()` (in module sage.coding.code\_constructions), 102  
`remove_shifts()` (in module sage.coding.guruswami\_sudan.utils), 51  
`rootfind_roth_ruckenstein()` (in module sage.coding.guruswami\_sudan.rootfinding), 48  
`rootfinding_algorithm()` (sage.coding.guruswami\_sudan.gs\_decoder.GRSGuruswamiSudanDecoder method), 44

## S

`sage.coding.binary_code` (module), 13  
`sage.coding.bounds_catalog` (module), 7  
`sage.coding.channel_constructions` (module), 125  
`sage.coding.channels_catalog` (module), 7  
`sage.coding.code_bounds` (module), 113  
`sage.coding.code_constructions` (module), 93  
`sage.coding.codecan.autgroup_can_label` (module), 146  
`sage.coding.codecan.codecan` (module), 139  
`sage.coding.codes_catalog` (module), 8



[sage.coding.decoder \(module\)](#), 1  
[sage.coding.decoders\\_catalog \(module\)](#), 10  
[sage.coding.delsarte\\_bounds \(module\)](#), 119  
[sage.coding.encoder \(module\)](#), 3  
[sage.coding.encoders\\_catalog \(module\)](#), 10  
[sage.coding.grs \(module\)](#), 22  
[sage.coding.guava \(module\)](#), 109  
[sage.coding.guruswami\\_sudan.gs\\_decoder \(module\)](#), 38  
[sage.coding.guruswami\\_sudan.interpolation \(module\)](#), 45  
[sage.coding.guruswami\\_sudan.rootfinding \(module\)](#), 48  
[sage.coding.guruswami\\_sudan.utils \(module\)](#), 49  
[sage.coding.hamming\\_code \(module\)](#), 37  
[sage.coding.linear\\_code \(module\)](#), 51  
[sage.coding.sd\\_codes \(module\)](#), 107  
[sage.coding.source\\_coding.huffman \(module\)](#), 133  
[sage.coding.two\\_weight\\_db \(module\)](#), 10  
[SC\\_test\\_list\\_perms\(\)](#) (in module [sage.coding.codecan.codecan](#)), 144  
[sd\\_duursma\\_data\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 75  
[sd\\_duursma\\_q\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 75  
[sd\\_zeta\\_polynomial\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 76  
[self\\_dual\\_codes\\_binary\(\)](#) (in module [sage.coding.sd\\_codes](#)), 109  
[self\\_orthogonal\\_binary\\_codes\(\)](#) (in module [sage.coding.linear\\_code](#)), 91  
[shortened\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 76  
[singleton\\_bound\\_asymp\(\)](#) (in module [sage.coding.code\\_bounds](#)), 118  
[singleton\\_upper\\_bound\(\)](#) (in module [sage.coding.code\\_bounds](#)), 118  
[solve\\_degree2\\_to\\_integer\\_range\(\)](#) (in module [sage.coding.guruswami\\_sudan.utils](#)), 51  
[spectrum\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 77  
[standard\\_form\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 77  
[StaticErrorRateChannel](#) (class in [sage.coding.channel\\_constructions](#)), 130  
[support\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 78  
[syndrome\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 78  
[syndrome\\_table\(\)](#) ([sage.coding.linear\\_code.LinearCodeSyndromeDecoder](#) method), 88

## T

[TernaryGolayCode\(\)](#) (in module [sage.coding.code\\_constructions](#)), 102  
[test\\_expand\\_to\\_ortho\\_basis\(\)](#) (in module [sage.coding.binary\\_code](#)), 20  
[test\\_word\\_perms\(\)](#) (in module [sage.coding.binary\\_code](#)), 21  
[ToricCode\(\)](#) (in module [sage.coding.code\\_constructions](#)), 102  
[transmit\(\)](#) ([sage.coding.channel\\_constructions.Channel](#) method), 126  
[transmit\\_unsafe\(\)](#) ([sage.coding.channel\\_constructions.Channel](#) method), 127  
[transmit\\_unsafe\(\)](#) ([sage.coding.channel\\_constructions.ErrorErasureChannel](#) method), 128  
[transmit\\_unsafe\(\)](#) ([sage.coding.channel\\_constructions.QarySymmetricChannel](#) method), 129  
[transmit\\_unsafe\(\)](#) ([sage.coding.channel\\_constructions.StaticErrorRateChannel](#) method), 130  
[tree\(\)](#) ([sage.coding.source\\_coding.huffman.Huffman](#) method), 136  
[TrivialCode\(\)](#) (in module [sage.coding.code\\_constructions](#)), 103

## U

[unencode\(\)](#) ([sage.coding.encoder.Encoder](#) method), 5  
[unencode\(\)](#) ([sage.coding.linear\\_code.AbstractLinearCode](#) method), 79  
[unencode\\_nocheck\(\)](#) ([sage.coding.encoder.Encoder](#) method), 6

`unencode_nocheck()` (`sage.coding.grs.GRSEvaluationPolynomialEncoder` method), [28](#)

## V

`volume_hamming()` (in module `sage.coding.code_bounds`), [118](#)

## W

`walsh_matrix()` (in module `sage.coding.code_constructions`), [106](#)

`WalshCode()` (in module `sage.coding.code_constructions`), [103](#)

`weight_dist()` (in module `sage.coding.binary_code`), [22](#)

`weight_distribution()` (`sage.coding.grs.GeneralizedReedSolomonCode` method), [37](#)

`weight_distribution()` (`sage.coding.linear_code.AbstractLinearCode` method), [79](#)

`weight_enumerator()` (`sage.coding.grs.GeneralizedReedSolomonCode` method), [37](#)

`weight_enumerator()` (`sage.coding.linear_code.AbstractLinearCode` method), [80](#)

`wtldist_gap()` (in module `sage.coding.linear_code`), [92](#)

## Z

`zero()` (`sage.coding.linear_code.AbstractLinearCode` method), [81](#)

`zeta_function()` (`sage.coding.linear_code.AbstractLinearCode` method), [81](#)

`zeta_polynomial()` (`sage.coding.linear_code.AbstractLinearCode` method), [81](#)