
Sage Reference Manual: Fixed and Arbitrary Precision Numerical Fields

Release 6.6

The Sage Development Team

April 18, 2015

CONTENTS

1	Double Precision Real Numbers	3
2	Arbitrary Precision Real Numbers	25
3	Arbitrary Precision Real Intervals	69
4	Field of Arbitrary Precision Real Number Intervals	103
5	File: sage/rings/real_interval_absolute.pyx (starting at line 1)	105
6	These classes are very lazy, in the sense that it doesn't really do anything	111
7	Double Precision Complex Numbers	121
8	Field of Arbitrary Precision Complex Numbers	139
9	Arbitrary Precision Complex Numbers	145
10	Arbitrary Precision Complex Numbers using GNU MPC	163
11	Field of Arbitrary Precision Complex Intervals	179
12	Arbitrary Precision Complex Intervals	185
13	Indices and Tables	193

Sage supports two optimized fixed precision fields for numerical computation, the real double (`RealDoubleField`) and complex double fields (`ComplexDoubleField`). Sage also supports arbitrary precision real (`RealField`) and complex fields (`ComplexField`), and real and complex interval arithmetic (`RealIntervalField` and `ComplexIntervalField`).

Real and complex double elements are optimized implementations that use the GNU Scientific Library for arithmetic and some special functions. Arbitrary precision real and complex numbers are implemented using the MPFR library, which builds on GMP. (Note that Sage doesn't currently use the MPC library.) The interval arithmetic field is implemented using the MPFI library.

In many cases the PARI C-library is used to compute special functions when implementations aren't otherwise available.

DOUBLE PRECISION REAL NUMBERS

EXAMPLES:

We create the real double vector space of dimension 3:

```
sage: V = RDF^3; V
Vector space of dimension 3 over Real Double Field
```

Notice that this space is unique:

```
sage: V is RDF^3
True
sage: V is FreeModule(RDF, 3)
True
sage: V is VectorSpace(RDF, 3)
True
```

Also, you can instantly create a space of large dimension:

```
sage: V = RDF^10000
```

TESTS:

Test NumPy conversions:

```
sage: RDF(1).__array_interface__
{'typestr': '=f8'}
sage: import numpy
sage: numpy.array([RDF.pi()]).dtype
dtype('float64')
```

```
class sage.rings.real_double.RealDoubleElement
    Bases: sage.structure.element.FieldElement
```

An approximation to a real number using double precision floating point numbers. Answers derived from calculations with such approximations may differ from what they would be if those calculations were performed with true real numbers. This is due to the rounding errors inherent to finite precision calculations.

```
NaN()
Return Not-a-Number NaN.
```

EXAMPLES:

```
sage: RDF.NaN()
NaN
```

abs()

Returns the absolute value of `self`.

EXAMPLES:

```
sage: RDF(1e10).abs()
10000000000.0
sage: RDF(-1e10).abs()
10000000000.0
```

acosh()

Return the hyperbolic inverse cosine of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/2
sage: i = q.cosh(); i
2.5091784786580567
sage: abs(i.acosh()-q) < 1e-15
True
```

agm(*other*)

Return the arithmetic-geometric mean of `self` and `other`. The arithmetic-geometric mean is the common limit of the sequences u_n and v_n , where u_0 is `self`, v_0 is `other`, u_{n+1} is the arithmetic mean of u_n and v_n , and v_{n+1} is the geometric mean of u_n and v_n . If any operand is negative, the return value is NaN.

EXAMPLES:

```
sage: a = RDF(1.5)
sage: b = RDF(2.3)
sage: a.agm(b)
1.8786484558146697
```

The arithmetic-geometric mean always lies between the geometric and arithmetic mean:

```
sage: sqrt(a*b) < a.agm(b) < (a+b)/2
True
```

algdep(*n*)

Return a polynomial of degree at most n which is approximately satisfied by this number.

Note: The resulting polynomial need not be irreducible, and indeed usually won't be if this number is a good approximation to an algebraic number of degree less than n .

ALGORITHM:

Uses the PARI C-library `algdep` command.

EXAMPLE:

```
sage: r = sqrt(RDF(2)); r
1.4142135623730951
sage: r.algebraic_dependency(5)
x^2 - 2
```

algebraic_dependency(*n*)

Return a polynomial of degree at most n which is approximately satisfied by this number.

Note: The resulting polynomial need not be irreducible, and indeed usually won't be if this number is a good approximation to an algebraic number of degree less than n .

ALGORITHM:

Uses the PARI C-library `algdep` command.

EXAMPLE:

```
sage: r = sqrt(RDF(2)); r
1.4142135623730951
sage: r.algebraic_dependency(5)
x^2 - 2
```

arccos()

Return the inverse cosine of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/3
sage: i = q.cos()
sage: i.arccos() == q
True
```

arcsin()

Return the inverse sine of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/5
sage: i = q.sin()
sage: i.arcsin() == q
True
```

arcsinh()

Return the hyperbolic inverse sine of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/2
sage: i = q.sinh(); i
2.3012989023072947
sage: abs(i.arcsinh()-q) < 1e-15
True
```

arctan()

Return the inverse tangent of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/5
sage: i = q.tan()
sage: i.arctan() == q
True
```

arctanh()

Return the hyperbolic inverse tangent of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/2
sage: i = q.tanh(); i
0.9171523356672744
sage: i.arctanh() - q # rel tol 1
4.440892098500626e-16
```

ceil()

Return the ceiling of `self`.

EXAMPLES:

```
sage: RDF(2.99).ceil()
3
sage: RDF(2.00).ceil()
2
sage: RDF(-5/2).ceil()
-2
```

ceiling()

Return the ceiling of `self`.

EXAMPLES:

```
sage: RDF(2.99).ceil()
3
sage: RDF(2.00).ceil()
2
sage: RDF(-5/2).ceil()
-2
```

conjugate()

Returns the complex conjugate of this real number, which is the real number itself.

EXAMPLES:

```
sage: RDF(4).conjugate()
4.0
```

cos()

Return the cosine of `self`.

EXAMPLES:

```
sage: t=RDF.pi()/2
sage: t.cos()
6.123233995736757e-17
```

cosh()

Return the hyperbolic cosine of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/12
sage: q.cosh()
1.0344656400955106
```

coth()

Return the hyperbolic cotangent of `self`.

EXAMPLES:

```
sage: RDF(pi).coth()
1.003741873197321
sage: CDF(pi).coth()
1.0037418731973213
```

csch()

Return the hyperbolic cosecant of `self`.

EXAMPLES:

```
sage: RDF(pi).csch()
0.08658953753004694
sage: CDF(pi).csch() # rel tol 1e-15
0.08658953753004696
```

cube_root()

Return the cubic root (defined over the real numbers) of `self`.

EXAMPLES:

```
sage: r = RDF(125.0); r.cube_root()
5.000000000000001
sage: r = RDF(-119.0)
sage: r.cube_root()^3 - r # rel tol 1
-1.4210854715202004e-14
```

erf()

Return the value of the error function on `self`.

EXAMPLES:

```
sage: RDF(6).erf()
1.0
```

exp()

Return e^{self} .

EXAMPLES:

```
sage: r = RDF(0.0)
sage: r.exp()
1.0

sage: r = RDF('32.3')
sage: a = r.exp(); a
106588847274864.47
sage: a.log()
32.3

sage: r = RDF('-32.3')
sage: r.exp()
9.381844588498685e-15

sage: RDF(1000).exp()
+infinity
```

exp10()

Return 10^{self} .

EXAMPLES:

```
sage: r = RDF(0.0)
sage: r.exp10()
1.0

sage: r = RDF(32.0)
sage: r.exp10()
1.0000000000000069e+32
```

```
sage: r = RDF(-32.3)
sage: r.exp10()
5.011872336272702e-33
```

exp2()

Return 2^{self} .

EXAMPLES:

```
sage: r = RDF(0.0)
sage: r.exp2()
1.0
```

```
sage: r = RDF(32.0)
sage: r.exp2()
4294967295.9999967
```

```
sage: r = RDF(-32.3)
sage: r.exp2()
1.8911724825302065e-10
```

floor()

Return the floor of `self`.

EXAMPLES:

```
sage: RDF(2.99).floor()
2
sage: RDF(2.00).floor()
2
sage: RDF(-5/2).floor()
-3
```

frac()

Return a real number in $(-1, 1)$. It satisfies the relation: $x = x.\text{trunc}() + x.\text{frac}()$

EXAMPLES:

```
sage: RDF(2.99).frac()
0.99000000000000002
sage: RDF(2.50).frac()
0.5
sage: RDF(-2.79).frac()
-0.79
```

gamma()

Return the value of the Euler gamma function on `self`.

EXAMPLES:

```
sage: RDF(6).gamma()
120.0
sage: RDF(1.5).gamma() # rel tol 1e-15
0.8862269254527584
```

hypot(*other*)

Computes the value $\sqrt{s^2 + o^2}$ where s is `self` and o is `other` in such a way as to avoid overflow.

EXAMPLES:

```
sage: x = RDF(4e300); y = RDF(3e300);
sage: x.hypot(y)
5e+300
sage: sqrt(x^2+y^2) # overflow
+infinity
```

imag()

Return the imaginary part of this number, which is zero.

EXAMPLES:

```
sage: a = RDF(3)
sage: a.imag()
0.0
```

integer_part()

If in decimal this number is written $n.d\text{ef}g$, returns n .

EXAMPLES:

```
sage: r = RDF('-1.6')
sage: a = r.integer_part(); a
-1
sage: type(a)
<type 'sage.rings.integer.Integer'>
sage: r = RDF(0.0/0.0)
sage: a = r.integer_part()
Traceback (most recent call last):
...
TypeError: Attempt to get integer part of NaN
```

is_NaN()

Check if self is NaN.

EXAMPLES:

```
sage: RDF(1).is_NaN()
False
sage: a = RDF(0)/RDF(0)
sage: a.is_NaN()
True
```

is_infinity()

Check if self is ∞ .

EXAMPLES:

```
sage: a = RDF(2); b = RDF(0)
sage: (a/b).is_infinity()
True
sage: (b/a).is_infinity()
False
```

is_integer()

Return True if this number is a integer

EXAMPLES:

```
sage: RDF(3.5).is_integer()
False
sage: RDF(3).is_integer()
True
```

is_negative_infinity()

Check if self is $-\infty$.

EXAMPLES:

```
sage: a = RDF(2)/RDF(0)
sage: a.is_negative_infinity()
False
sage: a = RDF(-3)/RDF(0)
sage: a.is_negative_infinity()
True
```

is_positive_infinity()

Check if self is $+\infty$.

EXAMPLES:

```
sage: a = RDF(1)/RDF(0)
sage: a.is_positive_infinity()
True
sage: a = RDF(-1)/RDF(0)
sage: a.is_positive_infinity()
False
```

is_square()

Return whether or not this number is a square in this field. For the real numbers, this is `True` if and only if self is non-negative.

EXAMPLES:

```
sage: RDF(3.5).is_square()
True
sage: RDF(0).is_square()
True
sage: RDF(-4).is_square()
False
```

log (base=None)

Return the logarithm.

INPUT:

- `base` – integer or `None` (default). The base of the logarithm. If `None` is specified, the base is e (the so-called natural logarithm).

OUTPUT:

The logarithm of self. If self is positive, a double floating point number. Infinity if self is zero. A imaginary complex floating point number if self is negative.

EXAMPLES:

```
sage: RDF(2).log()
0.6931471805599453
sage: RDF(2).log(2)
1.0
sage: RDF(2).log(pi)
0.6055115613982801
sage: RDF(2).log(10)
0.30102999566398114
sage: RDF(2).log(1.5)
```

```

1.7095112913514547
sage: RDF(0).log()
-infinity
sage: RDF(-1).log()
3.141592653589793*I
sage: RDF(-1).log(2) # rel tol 1e-15
4.532360141827194*I

```

TESTS:

Make sure that we can take the log of small numbers accurately and the fix doesn't break preexisting values (trac ticket #12557):

```

sage: R = RealField(128)
sage: def check_error(x):
....:     x = RDF(x)
....:     log_RDF = x.log()
....:     log_RR = R(x).log()
....:     diff = R(log_RDF) - log_RR
....:     if abs(diff) < log_RDF.ulp():
....:         return True
....:     print "logarithm check failed for %s (diff = %s ulp)"%
....:     return False
sage: all( check_error(2^x) for x in range(-100,100) )
True
sage: all( check_error(x) for x in srange(0.01, 2.00, 0.01) )
True
sage: all( check_error(x) for x in srange(0.99, 1.01, 0.001) )
True
sage: RDF(1.000000001).log()
1.000000082240371e-09
sage: RDF(1e-17).log()
-39.14394658089878
sage: RDF(1e-50).log()
-115.12925464970229

```

`log10()`

Return log to the base 10 of self.

EXAMPLES:

```

sage: r = RDF('16.0'); r.log10()
1.2041199826559246
sage: r.log() / RDF(log(10))
1.2041199826559246
sage: r = RDF('39.9'); r.log10()
1.6009728956867482

```

`log2()`

Return log to the base 2 of self.

EXAMPLES:

```

sage: r = RDF(16.0)
sage: r.log2()
4.0

sage: r = RDF(31.9); r.log2()
4.995484518877507

```

logpi()

Return log to the base π of self.

EXAMPLES:

```
sage: r = RDF(16); r.logpi()
2.4220462455931204
sage: r.log() / RDF(log(pi))
2.4220462455931204
sage: r = RDF('39.9'); r.logpi()
3.2203023346075152
```

multiplicative_order()

Returns n such that $\text{self}^n == 1$.

Only ± 1 have finite multiplicative order.

EXAMPLES:

```
sage: RDF(1).multiplicative_order()
1
sage: RDF(-1).multiplicative_order()
2
sage: RDF(3).multiplicative_order()
+Infinity
```

nan()

Return Not-a-Number NaN.

EXAMPLES:

```
sage: RDF.NaN()
NaN
```

nth_root(n)

Return the n^{th} root of self.

INPUT:

- n – an integer

OUTPUT:

The output is a complex double if self is negative and n is even, otherwise it is a real double.

EXAMPLES:

```
sage: r = RDF(-125.0); r.nth_root(3)
-5.000000000000001
sage: r.nth_root(5)
-2.6265278044037674
sage: RDF(-2).nth_root(5)^5 # rel tol 1e-15
-2.000000000000001
sage: RDF(-1).nth_root(5)^5
-1.0
sage: RDF(3).nth_root(10)^10
2.999999999999982
sage: RDF(-1).nth_root(2)
6.123233995736757e-17 + 1.0*I
sage: RDF(-1).nth_root(4)
0.7071067811865476 + 0.7071067811865475*I
```


prec()

Return the precision of this number in bits.

Always returns 53.

EXAMPLES:

```
sage: RDF(0).prec()
53
```

real()

Return self - we are already real.

EXAMPLES:

```
sage: a = RDF(3)
sage: a.real()
3.0
```

restrict_angle()

Return a number congruent to self mod 2π that lies in the interval $(-\pi, \pi]$.

Specifically, it is the unique $x \in (-\pi, \pi]$ such that $\text{self} = x + 2\pi n$ for some $n \in \mathbb{Z}$.

EXAMPLES:

```
sage: RDF(pi).restrict_angle()
3.141592653589793
sage: RDF(pi + 1e-10).restrict_angle()
-3.1415926534897936
sage: RDF(1+10^10*pi).restrict_angle()
0.9999977606...
```

round()

Given real number x , rounds up if fractional part is greater than 0.5, rounds down if fractional part is less than 0.5.

EXAMPLES:

```
sage: RDF(0.49).round()
0
sage: a=RDF(0.51).round(); a
1
```

sech()

Return the hyperbolic secant of self.

EXAMPLES:

```
sage: RDF(pi).sech()
0.08626673833405443
sage: CDF(pi).sech()
0.08626673833405443
```

sign()

Returns -1, 0, or 1 if self is negative, zero, or positive; respectively.

EXAMPLES:

```
sage: RDF(-1.5).sign()
-1
sage: RDF(0).sign()
0
```

```
sage: RDF(2.5).sign()
1
```

sign_mantissa_exponent()

Return the sign, mantissa, and exponent of `self`.

In Sage (as in MPFR), floating-point numbers of precision p are of the form $sm2^{e-p}$, where $s \in \{-1, 1\}$, $2^{p-1} \leq m < 2^p$, and $-2^{30}+1 \leq e \leq 2^{30}-1$; plus the special values $+0$, -0 , $+\infty$, $-\infty$, and NaN (which stands for Not-a-Number).

This function returns s , m , and $e - p$. For the special values:

- $+0$ returns $(1, 0, 0)$
- -0 returns $(-1, 0, 0)$
- the return values for $+\infty$, $-\infty$, and NaN are not specified.

EXAMPLES:

```
sage: a = RDF(exp(1.0)); a
2.718281828459045
sage: sign,mantissa,exponent = RDF(exp(1.0)).sign_mantissa_exponent()
sage: sign,mantissa,exponent
(1, 6121026514868073, -51)
sage: sign*mantissa*(2**exponent) == a
True
```

The mantissa is always a nonnegative number:

```
sage: RDF(-1).sign_mantissa_exponent()
(-1, 4503599627370496, -52)
```

TESTS:

```
sage: RDF('+0').sign_mantissa_exponent()
(1, 0, 0)
sage: RDF('-0').sign_mantissa_exponent()
(-1, 0, 0)
```

sin()

Return the sine of `self`.

EXAMPLES:

```
sage: RDF(2).sin()
0.9092974268256817
```

sincos()

Return a pair consisting of the sine and cosine of `self`.

EXAMPLES:

```
sage: t = RDF.pi()/6
sage: t.sincos()
(0.49999999999999994, 0.8660254037844387)
```

sinh()

Return the hyperbolic sine of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/12
sage: q.sinh()
0.26480022760227073
```

sqrt (*extend=True, all=False*)

The square root function.

INPUT:

- *extend* – bool (default: True); if True, return a square root in a complex field if necessary if *self* is negative; otherwise raise a `ValueError`.
- *all* – bool (default: False); if True, return a list of all square roots.

EXAMPLES:

```
sage: r = RDF(4.0)
sage: r.sqrt()
2.0
sage: r.sqrt()^2 == r
True
```

```
sage: r = RDF(4344)
sage: r.sqrt()
65.90902821313632
sage: r.sqrt()^2 - r
0.0
```

```
sage: r = RDF(-2.0)
sage: r.sqrt()
1.4142135623730951*I
```

```
sage: RDF(2).sqrt(all=True)
[1.4142135623730951, -1.4142135623730951]
sage: RDF(0).sqrt(all=True)
[0.0]
sage: RDF(-2).sqrt(all=True)
[1.4142135623730951*I, -1.4142135623730951*I]
```

str ()

Return the informal string representation of *self*.

EXAMPLES:

```
sage: a = RDF('4.5'); a.str()
'4.5'
sage: a = RDF('49203480923840.2923904823048'); a.str()
'4.92034809238e+13'
sage: a = RDF(1)/RDF(0); a.str()
'+infinity'
sage: a = -RDF(1)/RDF(0); a.str()
'-infinity'
sage: a = RDF(0)/RDF(0); a.str()
'NaN'
```

We verify consistency with RR (mpfr reals):

```
sage: str(RR(RDF(1)/RDF(0))) == str(RDF(1)/RDF(0))
True
sage: str(RR(-RDF(1)/RDF(0))) == str(-RDF(1)/RDF(0))
True
```

```
sage: str(RR(RDF(0)/RDF(0))) == str(RDF(0)/RDF(0))
True
```

tan()

Return the tangent of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/3
sage: q.tan()
1.7320508075688767
sage: q = RDF.pi()/6
sage: q.tan()
0.5773502691896256
```

tanh()

Return the hyperbolic tangent of `self`.

EXAMPLES:

```
sage: q = RDF.pi()/12
sage: q.tanh()
0.25597778924568454
```

trunc()

Truncates this number (returns integer part).

EXAMPLES:

```
sage: RDF(2.99).trunc()
2
sage: RDF(-2.00).trunc()
-2
sage: RDF(0.00).trunc()
0
```

ulp()

Returns the unit of least precision of `self`, which is the weight of the least significant bit of `self`. This is always a strictly positive number. It is also the gap between this number and the closest number with larger absolute value that can be represented.

EXAMPLES:

```
sage: a = RDF(pi)
sage: a.ulp()
4.440892098500626e-16
sage: b = a + a.ulp()
```

Adding or subtracting an ulp always gives a different number:

```
sage: a + a.ulp() == a
False
sage: a - a.ulp() == a
False
sage: b + b.ulp() == b
False
sage: b - b.ulp() == b
False
```

Since the default rounding mode is round-to-nearest, adding or subtracting something less than half an ulp always gives the same number, unless the result has a smaller ulp. The latter can only happen if the input

number is (up to sign) exactly a power of 2:

```
sage: a - a.ulp()/3 == a
True
sage: a + a.ulp()/3 == a
True
sage: b - b.ulp()/3 == b
True
sage: b + b.ulp()/3 == b
True
sage: c = RDF(1)
sage: c - c.ulp()/3 == c
False
sage: c.ulp()
2.220446049250313e-16
sage: (c - c.ulp()).ulp()
1.1102230246251565e-16
```

The ulp is always positive:

```
sage: RDF(-1).ulp()
2.220446049250313e-16
```

The ulp of zero is the smallest positive number in RDF:

```
sage: RDF(0).ulp()
5e-324
sage: RDF(0).ulp()/2
0.0
```

Some special values:

```
sage: a = RDF(1)/RDF(0); a
+infinity
sage: a.ulp()
+infinity
sage: (-a).ulp()
+infinity
sage: a = RDF('nan')
sage: a.ulp() is a
True
```

The ulp method works correctly with small numbers:

```
sage: u = RDF(0).ulp()
sage: u.ulp() == u
True
sage: x = u * (2^52-1) # largest denormal number
sage: x.ulp() == u
True
sage: x = u * 2^52 # smallest normal number
sage: x.ulp() == u
True
```

zeta()

Return the Riemann zeta function evaluated at this real number.

Note: PARI is vastly more efficient at computing the Riemann zeta function. See the example below for how to use it.

EXAMPLES:

```
sage: RDF(2).zeta() # rel tol 1e-15
1.6449340668482269
sage: RDF.pi()^2/6
1.6449340668482264
sage: RDF(-2).zeta()
0.0
sage: RDF(1).zeta()
+infinity
```

`sage.rings.real_double.RealDoubleField()`
Return the unique instance of the `real double field`.

EXAMPLES:

```
sage: RealDoubleField() is RealDoubleField()
True
```

class `sage.rings.real_double.RealDoubleField_class`

Bases: `sage.rings.ring.Field`

An approximation to the field of real numbers using double precision floating point numbers. Answers derived from calculations in this approximation may differ from what they would be if those calculations were performed in the true field of real numbers. This is due to the rounding errors inherent to finite precision calculations.

EXAMPLES:

```
sage: RR == RDF
False
sage: RDF == RealDoubleField() # RDF is the shorthand
True

sage: RDF(1)
1.0
sage: RDF(2/3)
0.6666666666666666
```

A `TypeError` is raised if the coercion doesn't make sense:

```
sage: RDF(QQ['x'].0)
Traceback (most recent call last):
...
TypeError: cannot coerce nonconstant polynomial to float
sage: RDF(QQ['x'](3))
3.0
```

One can convert back and forth between double precision real numbers and higher-precision ones, though of course there may be loss of precision:

```
sage: a = RealField(200)(2).sqrt(); a
1.4142135623730950488016887242096980785696718753769480731767
sage: b = RDF(a); b
1.4142135623730951
sage: a.parent()(b)
1.4142135623730951454746218587388284504413604736328125000000
sage: a.parent()(b) == b
True
sage: b == RR(a)
True
```

`NaN()`

Return Not-a-Number NaN.

EXAMPLES:

```
sage: RDF.NaN()
NaN
```

algebraic_closure()

Return the algebraic closure of `self`, i.e., the complex double field.

EXAMPLES:

```
sage: RDF.algebraic_closure()
Complex Double Field
```

characteristic()

Returns 0, since the field of real numbers has characteristic 0.

EXAMPLES:

```
sage: RDF.characteristic()
0
```

complex_field()

Return the complex field with the same precision as `self`, i.e., the complex double field.

EXAMPLES:

```
sage: RDF.complex_field()
Complex Double Field
```

construction()

Returns the functorial construction of `self`, namely, completion of the rational numbers with respect to the prime at ∞ .

Also preserves other information that makes this field unique (i.e. the Real Double Field).

EXAMPLES:

```
sage: c, S = RDF.construction(); S
Rational Field
sage: RDF == c(S)
True
```

euler_constant()

Return Euler's gamma constant to double precision.

EXAMPLES:

```
sage: RDF.euler_constant()
0.5772156649015329
```

factorial(n)

Return the factorial of the integer n as a real number.

EXAMPLES:

```
sage: RDF.factorial(100)
9.332621544394415e+157
```

gen(n=0)

Return the generator of the real double field.

EXAMPLES:

```
sage: RDF.0
1.0
sage: RDF.gens()
(1.0,)
```

is_exact()
Returns `False`, because doubles are not exact.

EXAMPLE:

```
sage: RDF.is_exact()
False
```

is_finite()
Return `False`, since the field of real numbers is not finite.

Technical note: There exists an upper bound on the double representation.

EXAMPLES:

```
sage: RDF.is_finite()
False
```

log2()
Return $\log(2)$ to the precision of this field.

EXAMPLES:

```
sage: RDF.log2()
0.6931471805599453
sage: RDF(2).log()
0.6931471805599453
```

name()
The name of `self`.

EXAMPLES:

```
sage: RDF.name()
'RealDoubleField'
```

nan()
Return Not-a-Number NaN.

EXAMPLES:

```
sage: RDF.NaN()
NaN
```

ngens()
Return the number of generators which is always 1.

EXAMPLES:

```
sage: RDF.ngens()
1
```

pi()
Returns π to double-precision.

EXAMPLES:


```
sage: RDF.pi()
3.141592653589793
sage: RDF.pi().sqrt()/2
0.8862269254527579
```

prec()

Return the precision of this real double field in bits.

Always returns 53.

EXAMPLES:

```
sage: RDF.precision()
53
```

precision()

Return the precision of this real double field in bits.

Always returns 53.

EXAMPLES:

```
sage: RDF.precision()
53
```

random_element(min=-1, max=1)

Return a random element of this real double field in the interval $[\min, \max]$.

EXAMPLES:

```
sage: RDF.random_element()
0.7369454235661859
sage: RDF.random_element(min=100, max=110)
102.8159473516245
```

to_prec(prec)

Return the real field to the specified precision. As doubles have fixed precision, this will only return a real double field if `prec` is exactly 53.

EXAMPLES:

```
sage: RDF.to_prec(52)
Real Field with 52 bits of precision
sage: RDF.to_prec(53)
Real Double Field
```

zeta(n=2)

Return an n -th root of unity in the real field, if one exists, or raise a `ValueError` otherwise.

EXAMPLES:

```
sage: RDF.zeta()
-1.0
sage: RDF.zeta(1)
1.0
sage: RDF.zeta(5)
Traceback (most recent call last):
...
ValueError: No 5th root of unity in self
```

class `sage.rings.real_double.ToRDF`

Bases: `sage.categories.morphism.Morphism`

Fast morphism from anything with a `__float__` method to an RDF element.

EXAMPLES:

```
sage: f = RDF.coerce_map_from(ZZ); f
Native morphism:
  From: Integer Ring
  To:   Real Double Field
sage: f(4)
4.0
sage: f = RDF.coerce_map_from(QQ); f
Native morphism:
  From: Rational Field
  To:   Real Double Field
sage: f(1/2)
0.5
sage: f = RDF.coerce_map_from(int); f
Native morphism:
  From: Set of Python objects of type 'int'
  To:   Real Double Field
sage: f(3r)
3.0
sage: f = RDF.coerce_map_from(float); f
Native morphism:
  From: Set of Python objects of type 'float'
  To:   Real Double Field
sage: f(3.5)
3.5
```

`sage.rings.real_double.is_RealDoubleElement(x)`
Check if `x` is an element of the real double field.

EXAMPLE:

```
sage: from sage.rings.real_double import is_RealDoubleElement
sage: is_RealDoubleElement(RDF(3))
True
sage: is_RealDoubleElement(RIF(3))
False
```

`sage.rings.real_double.is_RealDoubleField(x)`
Returns True if `x` is the field of real double precision numbers.

EXAMPLES:

```
sage: from sage.rings.real_double import is_RealDoubleField
sage: is_RealDoubleField(RDF)
True
sage: is_RealDoubleField(RealField(53))
False
```

`sage.rings.real_double.pool_stats()`
Statistics for the real double pool.

EXAMPLES:

We first pull all elements from the pool (making sure it is empty to illustrate how the pool works):

```
sage: from sage.rings.real_double import time_alloc_list, pool_stats
sage: L = time_alloc_list(50)
sage: pool_stats()
Used pool 0 / 0 times
```

```
Pool contains 0 / 50 items
```

During the operation (in this example, addition), we end up with two temporary elements. After completion of the operation, they are added to the pool:

```
sage: RDF(2.1) + RDF(2.2)
4.3000000000000001
sage: pool_stats()
Used pool 0 / 0 times
Pool contains 2 / 50 items
```

Next when we call `time_alloc_list()`, the “created” elements are actually pulled from the pool:

```
sage: time_alloc_list(3)
[2.2, 2.1, 0.0]
```

Note that the number of objects left in the pool depends on the garbage collector:

```
sage: pool_stats()
Used pool 0 / 0 times
Pool contains 1 / 50 items
```

```
sage.rings.real_double.time_alloc(n)
Allocate n RealDoubleElement instances.
```

EXAMPLES:

Since this does not store anything in a python object, the created elements will not be sent to the garbage collector. Therefore they remain in the pool:

```
sage: from sage.rings.real_double import time_alloc, pool_stats
sage: pool_stats()
Used pool 0 / 0 times
Pool contains 7 / 50 items
sage: time_alloc(25)
sage: pool_stats()
Used pool 0 / 0 times
Pool contains 7 / 50 items
```

```
sage.rings.real_double.time_alloc_list(n)
Allocate a list of length n of RealDoubleElement instances.
```

EXAMPLES:

During the operation (in this example, addition), we end up with two temporary elements. After completion of the operation, they are added to the pool:

```
sage: from sage.rings.real_double import time_alloc_list
sage: RDF(2.1) + RDF(2.2)
4.3000000000000001
```

Next when we call `time_alloc_list()`, the “created” elements are actually pulled from the pool:

```
sage: time_alloc_list(2)
[2.2, 2.1]
```


ARBITRARY PRECISION REAL NUMBERS

AUTHORS:

- Kyle Schalm (2005-09)
- William Stein: bug fixes, examples, maintenance
- Didier Deshommes (2006-03-19): examples
- David Harvey (2006-09-20): compatibility with `Element._parent`
- William Stein (2006-10): default printing truncates to avoid base-2 rounding confusing (fix suggested by Bill Hart)
- Didier Deshommes: special constructor for QD numbers
- Paul Zimmermann (2008-01): added new functions from mpfr-2.3.0, replaced some, e.g., `sech = 1/cosh`, by their original mpfr version.
- Carl Witty (2008-02): define floating-point rank and associated functions; add some documentation
- Robert Bradshaw (2009-09): decimal literals, optimizations
- Jeroen Demeyer (2012-05-27): set the MPFR exponent range to the maximal possible value ([trac ticket #13033](#))
- Travis Scrimshaw (2012-11-02): Added doctests for full coverage

This is a binding for the MPFR arbitrary-precision floating point library.

We define a class `RealField`, where each instance of `RealField` specifies a field of floating-point numbers with a specified precision and rounding mode. Individual floating-point numbers are of `RealNumber`.

In Sage (as in MPFR), floating-point numbers of precision p are of the form $sm2^{e-p}$, where $s \in \{-1, 1\}$, $2^{p-1} \leq m < 2^p$, and $-2^B + 1 \leq e \leq 2^B - 1$ where $B = 30$ on 32-bit systems and $B = 62$ on 64-bit systems; additionally, there are the special values `+0`, `-0`, `+infinity`, `-infinity` and `NaN` (which stands for Not-a-Number).

Operations in this module which are direct wrappers of MPFR functions are “correctly rounded”; we briefly describe what this means. Assume that you could perform the operation exactly, on real numbers, to get a result r . If this result can be represented as a floating-point number, then we return that number.

Otherwise, the result r is between two floating-point numbers. For the directed rounding modes (round to plus infinity, round to minus infinity, round to zero), we return the floating-point number in the indicated direction from r . For round to nearest, we return the floating-point number which is nearest to r .

This leaves one case unspecified: in round to nearest mode, what happens if r is exactly halfway between the two nearest floating-point numbers? In that case, we round to the number with an even mantissa (the mantissa is the number m in the representation above).

Consider the ordered set of floating-point numbers of precision p . (Here we identify `+0` and `-0`, and ignore `NaN`.) We can give a bijection between these floating-point numbers and a segment of the integers, where 0 maps to 0 and

adjacent floating-point numbers map to adjacent integers. We call the integer corresponding to a given floating-point number the “floating-point rank” of the number. (This is not standard terminology; I just made it up.)

EXAMPLES:

A difficult conversion:

```
sage: RR(sys.maxsize)
9.22337203685478e18      # 64-bit
2.14748364700000e9      # 32-bit
```

TESTS:

```
sage: -1e30
-1.000000000000000e30
sage: hex(-1. + 2^-52)
'-0xf.fffffffffffffp-4'
```

Make sure we don't have a new field for every new literal:

```
sage: parent(2.0) is parent(2.0)
True
sage: RealField(100, rnd='RNDZ') is RealField(100, rnd='RNDD')
False
sage: RealField(100, rnd='RNDZ') is RealField(100, rnd='RNDZ')
True
```

```
class sage.rings.real_mpf.QQtoRR
Bases: sage.categories.map.Map
```

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```
sage: Map(Hom(QQ, ZZ, Rings()))
Generic map:
  From: Rational Field
  To:   Integer Ring
```

Using domain and codomain:

```
sage: Map(QQ['x'], SymmetricGroup(6))
Generic map:
  From: Univariate Polynomial Ring in x over Rational Field
  To:   Symmetric group of order 6! as a permutation group
```

```
class sage.rings.real_mpf.RRtoRR
Bases: sage.categories.map.Map
```

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

```
From: Rational Field
To: Integer Ring
```

Using domain and codomain:

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

```
From: Univariate Polynomial Ring in x over Rational Field
To: Symmetric group of order 6! as a permutation group
```

section()

EXAMPLES:

```
sage: from sage.rings.real_mpfr import RRtoRR
```

```
sage: R10 = RealField(10)
```

```
sage: R100 = RealField(100)
```

```
sage: f = RRtoRR(R100, R10)
```

```
sage: f.section()
```

Generic map:

```
From: Real Field with 10 bits of precision
To: Real Field with 100 bits of precision
```

```
sage.rings.real_mpfr.RealField(prec=53, sci_not=0, rnd='RNDN')
```

RealField(prec, sci_not, rnd):

INPUT:

- **prec** – (integer) precision; default = 53 **prec** is the number of bits used to represent the mantissa of a floating-point number. The precision can be any integer between `mpfr_prec_min()` and `mpfr_prec_max()`. In the current implementation, `mpfr_prec_min()` is equal to 2.
- **sci_not** – (default: False) if True, always display using scientific notation; if False, display using scientific notation only for very large or very small numbers
- **rnd** – (string) the rounding mode:
 - 'RNDN' – (default) round to nearest (ties go to the even number): Knuth says this is the best choice to prevent “floating point drift”
 - 'RNDD' – round towards minus infinity
 - 'RNDZ' – round towards zero
 - 'RNDU' – round towards plus infinity

EXAMPLES:

```
sage: RealField(10)
```

Real Field with 10 bits of precision

```
sage: RealField()
```

Real Field with 53 bits of precision

```
sage: RealField(100000)
```

Real Field with 100000 bits of precision

Here we show the effect of rounding:

```
sage: R17d = RealField(17, rnd='RNDD')
sage: a = R17d(1)/R17d(3); a.exact_rational()
87381/262144
sage: R17u = RealField(17, rnd='RNDU')
sage: a = R17u(1)/R17u(3); a.exact_rational()
43691/131072
```

Note: The default precision is 53, since according to the MPFR manual: ‘mpfr should be able to exactly reproduce all computations with double-precision machine floating-point numbers (double type in C), except the default exponent range is much wider and subnormal numbers are not implemented.’

class `sage.rings.real_mpfr.RealField_class`

Bases: `sage.rings.ring.Field`

An approximation to the field of real numbers using floating point numbers with any specified precision. Answers derived from calculations in this approximation may differ from what they would be if those calculations were performed in the true field of real numbers. This is due to the rounding errors inherent to finite precision calculations.

See the documentation for the module `sage.rings.real_mpfr` for more details.

algebraic_closure()

Return the algebraic closure of `self`, i.e., the complex field with the same precision.

EXAMPLES:

```
sage: RR.algebraic_closure()
Complex Field with 53 bits of precision
sage: RR.algebraic_closure() is CC
True
sage: RealField(100, rnd='RNDD').algebraic_closure()
Complex Field with 100 bits of precision
sage: RealField(100).algebraic_closure()
Complex Field with 100 bits of precision
```

catalan_constant()

Returns Catalan’s constant to the precision of this field.

EXAMPLES:

```
sage: RealField(100).catalan_constant()
0.91596559417721901505460351493
```

characteristic()

Returns 0, since the field of real numbers has characteristic 0.

EXAMPLES:

```
sage: RealField(10).characteristic()
0
```

complex_field()

Return complex field of the same precision.

EXAMPLES:

```
sage: RR.complex_field()
Complex Field with 53 bits of precision
sage: RR.complex_field() is CC
True
```



```
sage: RealField(100, rnd='RNDD').complex_field()
Complex Field with 100 bits of precision
sage: RealField(100).complex_field()
Complex Field with 100 bits of precision
```

```
construction()
```

Return the functorial construction of `self`, namely, completion of the rational numbers with respect to the prime at ∞ .

Also preserves other information that makes this field unique (e.g. precision, rounding, print mode).

EXAMPLES:

```
sage: R = RealField(100, rnd='RNDU')
sage: c, S = R.construction(); S
Rational Field
sage: R == c(S)
True
```

`euler_constant()`

Returns Euler's gamma constant to the precision of this field.

EXAMPLES:

```
sage: RealField(100).euler_constant()
0.57721566490153286060651209008
```

factorial (n)

Return the factorial of the integer n as a real number.

EXAMPLES:

```
sage: RR.factorial(0)
1.0000000000000000
sage: RR.factorial(1000000)
8.26393168833124e55565708
sage: RR.factorial(-1)
Traceback (most recent call last):
...
ArithmeticError: n must be nonnegative
```

gen ($i=0$)

Return the `i`-th generator of `self`.

EXAMPLES:

[illegible]

gens ()

Return a list of generators.

EXAMPLE:

```
sage: RR.gens()
[1.000000000000000]
```

is_exact()

Return `False`, since a real field (represented using finite precision) is not exact.

EXAMPLE:

```
sage: RR.is_exact()
False
sage: RealField(100).is_exact()
False
```

is_finite()

Return `False`, since the field of real numbers is not finite.

EXAMPLES:

```
sage: RealField(10).is_finite()
False
```

log2()

Return $\log(2)$ (i.e., the natural log of 2) to the precision of this field.

EXAMPLES:

```
sage: R=RealField(100)
sage: R.log2()
0.69314718055994530941723212146
sage: R(2).log()
0.69314718055994530941723212146
```

name()

Return the name of `self`, which encodes the precision and rounding convention.

EXAMPLES:

```
sage: RR.name()
'RealField53_0'
sage: RealField(100, rnd='RNDU').name()
'RealField100_2'
```

ngens()

Return the number of generators.

EXAMPLES:

```
sage: RR.ngens()
1
```

pi()

Return π to the precision of this field.

EXAMPLES:

```
sage: R = RealField(100)
sage: R.pi()
3.1415926535897932384626433833
sage: R.pi().sqrt()/2
0.88622692545275801364908374167
sage: R = RealField(150)
sage: R.pi().sqrt()/2
0.88622692545275801364908374167057259139877473
```

prec()

Return the precision of `self`.

EXAMPLES:

```
sage: RR.precision()
53
sage: RealField(20).precision()
20
```

precision()

Return the precision of self.

EXAMPLES:

```
sage: RR.precision()
53
sage: RealField(20).precision()
20
```

random_element (*min=-1, max=1, distribution=None*)

Return a uniformly distributed random number between min and max (default -1 to 1).

Warning: The argument `distribution` is ignored—the random number is from the uniform distribution.

EXAMPLES:

```
sage: RealField(100).random_element(-5, 10)
-1.7093633198207765227646362966
sage: RealField(10).random_element()
-0.11
```

TESTS:

```
sage: RealField(31).random_element()
-0.676162510
sage: RealField(32).random_element()
0.689774422
sage: RealField(33).random_element()
0.396496861
sage: RealField(63).random_element()
-0.339980711116375371
sage: RealField(64).random_element()
-0.0453049884016705260
sage: RealField(65).random_element()
-0.5926714709589708137
sage: RealField(10).random_element()
0.23
sage: RealField(10).random_element()
-0.41
sage: RR.random_element()
-0.0420335212948924
sage: RR.random_element()
-0.616678906367394
```

rounding_mode()

Return the rounding mode.

EXAMPLES:

```
sage: RR.rounding_mode()
'RNDN'
sage: RealField(20, rnd='RNDZ').rounding_mode()
```

```
'RNDZ'
sage: RealField(20, rnd='RNDU').rounding_mode()
'RNDU'
sage: RealField(20, rnd='RNDZ').rounding_mode()
'RNDZ'
```

scientific_notation (*status=None*)

Set or return the scientific notation printing flag. If this flag is `True` then real numbers with this space as parent print using scientific notation.

INPUT:

- `status` – boolean optional flag

EXAMPLES:

```
sage: RR.scientific_notation()
False
sage: elt = RR(0.2512); elt
0.2512000000000000
sage: RR.scientific_notation(True)
sage: elt
2.512000000000000e-1
sage: RR.scientific_notation()
True
sage: RR.scientific_notation(False)
sage: elt
0.2512000000000000
sage: R = RealField(20, sci_not=1)
sage: R.scientific_notation()
True
sage: R(0.2512)
2.5120e-1
```

to_prec (*prec*)

Return the real field that is identical to `self`, except that it has the specified precision.

EXAMPLES:

```
sage: RR.to_prec(212)
Real Field with 212 bits of precision
sage: R = RealField(30, rnd="RNDZ")
sage: R.to_prec(300)
Real Field with 300 bits of precision and rounding RNDZ
```

zeta (*n=2*)

Return an n -th root of unity in the real field, if one exists, or raise a `ValueError` otherwise.

EXAMPLES:

```
sage: R = RealField()
sage: R.zeta()
-1.0000000000000000
sage: R.zeta(1)
1.0000000000000000
sage: R.zeta(5)
Traceback (most recent call last):
...
ValueError: No 5th root of unity in self
```

class `sage.rings.real_mpfr.RealLiteral`
 Bases: `sage.rings.real_mpfr.RealNumber`

Real literals are created in parsing and provide a way to allow casting into higher precision rings.

base

literal

class `sage.rings.real_mpfr.RealNumber`
 Bases: `sage.structure.element.RingElement`

A floating point approximation to a real number using any specified precision. Answers derived from calculations with such approximations may differ from what they would be if those calculations were performed with true real numbers. This is due to the rounding errors inherent to finite precision calculations.

The approximation is printed to slightly fewer digits than its internal precision, in order to avoid confusing roundoff issues that occur because numbers are stored internally in binary.

agm (*other*)
 Return the arithmetic-geometric mean of *self* and *other*.

The arithmetic-geometric mean is the common limit of the sequences u_n and v_n , where u_0 is *self*, v_0 is *other*, u_{n+1} is the arithmetic mean of u_n and v_n , and v_{n+1} is the geometric mean of u_n and v_n . If any operand is negative, the return value is NaN.

INPUT:

- right – another real number

OUTPUT:

- the AGM of *self* and *other*

EXAMPLES:

```
sage: a = 1.5
sage: b = 2.5
sage: a.agm(b)
1.96811775182478
sage: RealField(200)(a).agm(b)
1.9681177518247777389894630877503739489139488203685819712291
sage: a.agm(100)
28.1189391225320
```

The AGM always lies between the geometric and arithmetic mean:

```
sage: sqrt(a*b) < a.agm(b) < (a+b)/2
True
```

It is, of course, symmetric:

```
sage: b.agm(a)
1.96811775182478
```

and satisfies the relation $AGM(ra, rb) = rAGM(a, b)$:

```
sage: (2*a).agm(2*b) / 2
1.96811775182478
sage: (3*a).agm(3*b) / 3
1.96811775182478
```

It is also related to the elliptic integral

$$\int_0^{\pi/2} \frac{d\theta}{\sqrt{1 - m \sin^2 \theta}}.$$

```
sage: m = (a-b)^2/(a+b)^2
sage: E = numerical_integral(1/sqrt(1-m*sin(x)^2), 0, RR.pi()/2)[0]
sage: RR.pi()/4 * (a+b)/E
1.96811775182478
```

TESTS:

```
sage: 1.5.agm(0)
0.0000000000000000
```

algdep(*n*)

Return a polynomial of degree at most *n* which is approximately satisfied by this number.

Note: The resulting polynomial need not be irreducible, and indeed usually won't be if this number is a good approximation to an algebraic number of degree less than *n*.

ALGORITHM:

Uses the PARI C-library algdep command.

EXAMPLE:

```
sage: r = sqrt(2.0); r
1.41421356237310
sage: r.algebraic_dependency(5)
x^2 - 2
```

algebraic_dependency(*n*)

Return a polynomial of degree at most *n* which is approximately satisfied by this number.

Note: The resulting polynomial need not be irreducible, and indeed usually won't be if this number is a good approximation to an algebraic number of degree less than *n*.

ALGORITHM:

Uses the PARI C-library algdep command.

EXAMPLE:

```
sage: r = sqrt(2.0); r
1.41421356237310
sage: r.algebraic_dependency(5)
x^2 - 2
```

arccos()

Return the inverse cosine of *self*.

EXAMPLES:

```
sage: q = RR.pi()/3
sage: i = q.cos()
sage: i.arccos() == q
True
```

arccosh()

Return the hyperbolic inverse cosine of *self*.

EXAMPLES:

```
sage: q = RR.pi()/2
sage: i = q.cosh() ; i
2.50917847865806
sage: q == i.arccosh()
True
```

arccoth()

Return the inverse hyperbolic cotangent of *self*.

EXAMPLES:

```
sage: q = RR.pi()/5
sage: i = q.coth()
sage: i.arccoth() == q
True
```

arccsch()

Return the inverse hyperbolic cosecant of *self*.

EXAMPLES:

```
sage: i = RR.pi()/5
sage: q = i.csch()
sage: q.arccsch() == i
True
```

arcsech()

Return the inverse hyperbolic secant of *self*.

EXAMPLES:

```
sage: i = RR.pi()/3
sage: q = i.sech()
sage: q.arcsech() == i
True
```

arcsin()

Return the inverse sine of *self*.

EXAMPLES:

```
sage: q = RR.pi()/5
sage: i = q.sin()
sage: i.arcsin() == q
True
sage: i.arcsin() - q
0.0000000000000000
```

arcsinh()

Return the hyperbolic inverse sine of *self*.

EXAMPLES:

```
sage: q = RR.pi()/7
sage: i = q.sinh() ; i
0.464017630492991
sage: i.arcsinh() - q
0.0000000000000000
```

arctan()

Return the inverse tangent of *self*.

EXAMPLES:

```
sage: q = RR.pi()/5
sage: i = q.tan()
sage: i.arctan() == q
True
```

arctanh()

Return the hyperbolic inverse tangent of self.

EXAMPLES:

```
sage: q = RR.pi()/7
sage: i = q.tanh() ; i
0.420911241048535
sage: i.arctanh() - q
0.0000000000000000
```

ceil()

Return the ceiling of self.

EXAMPLES:

```
sage: (2.99).ceil()
3
sage: (2.00).ceil()
2
sage: (2.01).ceil()
3

sage: ceil(10^16 * 1.0)
10000000000000000
sage: ceil(10^17 * 1.0)
100000000000000000
sage: ceil(RR(+infinity))
Traceback (most recent call last):
...
ValueError: Calling ceil() on infinity or NaN
```

ceiling()

Return the ceiling of self.

EXAMPLES:

```
sage: (2.99).ceil()
3
sage: (2.00).ceil()
2
sage: (2.01).ceil()
3

sage: ceil(10^16 * 1.0)
10000000000000000
sage: ceil(10^17 * 1.0)
100000000000000000
sage: ceil(RR(+infinity))
Traceback (most recent call last):
...
ValueError: Calling ceil() on infinity or NaN
```

conjugate()

EXAMPLES:

cos ()

EXAMPLES:

cosh ()

EXAMPLES:

cot ()

EXAMPLES:

coth ()

EXAMPLES:

csc ()

EXAMPLES:

csch()

EXAMPLES:

cube_root()

EXAMPLES:

```
sage: r = 125.0; r.cube_root()
5.000000000000000
sage: r = -119.0
sage: r.cube_root()^3 - r      # illustrates precision loss
-1.42108547152020e-14
```

eint()

Returns the exponential integral of this number.

EXAMPLES:

```
sage: r = 1.0
sage: r.eint()
1.89511781635594
```

```
sage: r = -1.0
sage: r.eint()
NaN
```

epsilon (*field=None*)

Returns $\text{abs}(\text{self})$ divided by 2^b where b is the precision in bits of self . Equivalently, return $\text{abs}(\text{self})$ multiplied by the `ulp()` of 1.

This is a scale-invariant version of `ulp()` and it lies in $[u/2, u)$ where u is $\text{self.ulp}()$ (except in the case of zero or underflow).

INPUT:

- `field` – `RealField` used as parent of the result. If not specified, use `parent(self)`.

OUTPUT:

```
field(self.abs() / 2^self.precision())
```

EXAMPLES:

```
sage: RR(2^53).epsilon()
1.000000000000000
sage: RR(0).epsilon()
0.000000000000000
sage: a = RR.pi()
sage: a.epsilon()
3.48786849800863e-16
sage: a.ulp()/2, a.ulp()
(2.22044604925031e-16, 4.44089209850063e-16)
sage: a / 2^a.precision()
3.48786849800863e-16
sage: (-a).epsilon()
3.48786849800863e-16
```

We use a different field:

```
sage: a = RealField(256).pi()
sage: a.epsilon()
2.713132368784788677624750042896586252980746500631892201656843478528498954308e-77
sage: e = a.epsilon(RealField(64))
sage: e
2.71313236878478868e-77
sage: parent(e)
Real Field with 64 bits of precision
sage: e = a.epsilon(QQ)
Traceback (most recent call last):
```

```
...
TypeError: field argument must be a RealField
```

Special values:

```
sage: RR('nan').epsilon()
NaN
sage: parent(RR('nan').epsilon(RealField(42)))
Real Field with 42 bits of precision
sage: RR('+Inf').epsilon()
+infinity
sage: RR('-Inf').epsilon()
+infinity
```

erf()

Return the value of the error function on `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).erf()
0.995322265018953
sage: R(6).erf()
1.000000000000000
```

erfc()

Return the value of the complementary error function on `self`, i.e., $1 - \text{erf}(\text{self})$.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).erfc()
0.00467773498104727
sage: R(6).erfc()
2.15197367124989e-17
```

exact_rational()

Returns the exact rational representation of this floating-point number.

EXAMPLES:

```
sage: RR(0).exact_rational()
0
sage: RR(1/3).exact_rational()
6004799503160661/18014398509481984
sage: RR(37/16).exact_rational()
37/16
sage: RR(3^60).exact_rational()
42391158275216203520420085760
sage: RR(3^60).exact_rational() - 3^60
6125652559
sage: RealField(5)(-pi).exact_rational()
-25/8
```

TESTS:

```
sage: RR('nan').exact_rational()
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number
sage: RR('-infinity').exact_rational()
```

```
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number
```

exp()

Return e^{self} .

EXAMPLES:

```
sage: r = 0.0
sage: r.exp()
1.0000000000000000

sage: r = 32.3
sage: a = r.exp(); a
1.06588847274864e14
sage: a.log()
32.3000000000000000

sage: r = -32.3
sage: r.exp()
9.38184458849869e-15
```

exp10()

Return 10^{self} .

EXAMPLES:

```
sage: r = 0.0
sage: r.exp10()
1.0000000000000000

sage: r = 32.0
sage: r.exp10()
1.0000000000000000e32

sage: r = -32.3
sage: r.exp10()
5.01187233627276e-33
```

exp2()

Return 2^{self} .

EXAMPLES:

```
sage: r = 0.0
sage: r.exp2()
1.0000000000000000

sage: r = 32.0
sage: r.exp2()
4.294967296000000e9

sage: r = -32.3
sage: r.exp2()
1.89117248253021e-10
```

expm1()

Return $e^{\text{self}} - 1$, avoiding cancellation near 0.

EXAMPLES:

```

sage: r = 1.0
sage: r.expm1()
1.71828182845905

sage: r = 1e-16
sage: exp(r)-1
0.0000000000000000
sage: r.expm1()
1.0000000000000000e-16

```

floor()

Return the floor of `self`.

EXAMPLES:

```

sage: R = RealField()
sage: (2.99).floor()
2
sage: (2.00).floor()
2
sage: floor(RR(-5/2))
-3
sage: floor(RR(+infinity))
Traceback (most recent call last):
...
ValueError: Calling floor() on infinity or NaN

```

fp_rank()

Returns the floating-point rank of this number. That is, if you list the floating-point numbers of this precision in order, and number them starting with $0.0 \rightarrow 0$ and extending the list to positive and negative infinity, returns the number corresponding to this floating-point number.

EXAMPLES:

```

sage: RR(0).fp_rank()
0
sage: RR(0).nextabove().fp_rank()
1
sage: RR(0).nextbelow().nextbelow().fp_rank()
-2
sage: RR(1).fp_rank()
4835703278458516698824705 # 32-bit
20769187434139310514121985316880385 # 64-bit
sage: RR(-1).fp_rank()
-4835703278458516698824705 # 32-bit
-20769187434139310514121985316880385 # 64-bit
sage: RR(1).fp_rank() - RR(1).nextbelow().fp_rank()
1
sage: RR(-infinity).fp_rank()
-9671406552413433770278913 # 32-bit
-41538374868278621023740371006390273 # 64-bit
sage: RR(-infinity).fp_rank() - RR(-infinity).nextabove().fp_rank()
-1

```

fp_rank_delta(other)

Return the floating-point rank delta between `self` and `other`. That is, if the return value is positive, this is the number of times you have to call `.nextabove()` to get from `self` to `other`.

EXAMPLES:

```
sage: [x.fp_rank_delta(x.nextabove()) for x in
...      (RR(-infinity), -1.0, 0.0, 1.0, RR(pi), RR(infinity))]
[1, 1, 1, 1, 1, 0]
```

In the 2-bit floating-point field, one subsegment of the floating-point numbers is: 1, 1.5, 2, 3, 4, 6, 8, 12, 16, 24, 32

```
sage: R2 = RealField(2)
sage: R2(1).fp_rank_delta(R2(2))
2
sage: R2(2).fp_rank_delta(R2(1))
-2
sage: R2(1).fp_rank_delta(R2(1048576))
40
sage: R2(24).fp_rank_delta(R2(4))
-5
sage: R2(-4).fp_rank_delta(R2(-24))
-5
```

There are lots of floating-point numbers around 0:

```
sage: R2(-1).fp_rank_delta(R2(1))
4294967298      # 32-bit
18446744073709551618 # 64-bit
```

frac()

Return a real number such that `self = self.trunc() + self.frac()`. The return value will also satisfy `-1 < self.frac() < 1`.

EXAMPLES:

```
sage: (2.99).frac()
0.9900000000000000
sage: (2.50).frac()
0.5000000000000000
sage: (-2.79).frac()
-0.7900000000000000
sage: (-2.79).trunc() + (-2.79).frac()
-2.7900000000000000
```

gamma()

Return the value of the Euler gamma function on `self`.

EXAMPLES:

```
sage: R = RealField()
sage: R(6).gamma()
120.00000000000000
sage: R(1.5).gamma()
0.886226925452758
```

hex()

Return a hexadecimal floating-point representation of `self`, in the style of C99 hexadecimal floating-point constants.

EXAMPLES:

```
sage: RR(-1/3).hex()
'-0x5.5555555555554p-4'
sage: Reals(100)(123.456e789).hex()
'0xf.721008e90630c8da88f44dd2p+2624'
```

```
sage: (-0.).hex()
'-0x0p+0'
```

```
sage: [(a.hex(), float(a).hex()) for a in [.5, 1., 2., 16.]]
[('0x8p-4', '0x1.0000000000000p-1'),
 ('0x1p+0', '0x1.0000000000000p+0'),
 ('0x2p+0', '0x1.0000000000000p+1'),
 ('0x1p+4', '0x1.0000000000000p+4')]
```

Special values:

```
sage: [RR(s).hex() for s in ['+inf', '-inf', 'nan']]
['inf', '-inf', 'nan']
```

imag()

Return the imaginary part of `self`.

(Since `self` is a real number, this simply returns exactly 0.)

EXAMPLES:

```
sage: RR.pi().imag()
0
sage: RealField(100)(2).imag()
0
```

integer_part()

If in decimal this number is written `n.defg`, returns `n`.

OUTPUT: a Sage Integer

EXAMPLE:

```
sage: a = 119.41212
sage: a.integer_part()
119
sage: a = -123.4567
sage: a.integer_part()
-123
```

A big number with no decimal point:

```
sage: a = RR(10^17); a
1.000000000000000e17
sage: a.integer_part()
100000000000000000
```

is_NaN()

Return True if `self` is Not-a-Number NaN.

EXAMPLES:

```
sage: a = RR(0) / RR(0); a
NaN
sage: a.is_NaN()
True
```

is_infinity()

Return True if `self` is ∞ and False otherwise.

EXAMPLES:

```
sage: a = RR('1.494') / RR(0); a
+infinity
sage: a.is_infinity()
True
sage: a = -RR('1.494') / RR(0); a
-infinity
sage: a.is_infinity()
True
sage: RR(1.5).is_infinity()
False
sage: RR('nan').is_infinity()
False
```

is_integer()

Return True if this number is a integer.

EXAMPLES:

```
sage: RR(1).is_integer()
True
sage: RR(0.1).is_integer()
False
```

is_negative_infinity()

Return True if self is $-\infty$.

EXAMPLES:

```
sage: a = RR('1.494') / RR(0); a
+infinity
sage: a.is_negative_infinity()
False
sage: a = -RR('1.494') / RR(0); a
-infinity
sage: RR(1.5).is_negative_infinity()
False
sage: a.is_negative_infinity()
True
```

is_positive_infinity()

Return True if self is $+\infty$.

EXAMPLES:

```
sage: a = RR('1.494') / RR(0); a
+infinity
sage: a.is_positive_infinity()
True
sage: a = -RR('1.494') / RR(0); a
-infinity
sage: RR(1.5).is_positive_infinity()
False
sage: a.is_positive_infinity()
False
```

is_real()

Return True if self is real (of course, this always returns True for a finite element of a real field).

EXAMPLES:


```
sage: RR(1).is_real()
True
sage: RR('-100').is_real()
True
```

is_square()

Return whether or not this number is a square in this field. For the real numbers, this is `True` if and only if `self` is non-negative.

EXAMPLES:

```
sage: r = 3.5
sage: r.is_square()
True
sage: r = 0.0
sage: r.is_square()
True
sage: r = -4.0
sage: r.is_square()
False
```

is_unit()

Return `True` if `self` is a unit (has a multiplicative inverse) and `False` otherwise.

EXAMPLES:

```
sage: RR(1).is_unit()
True
sage: RR('0').is_unit()
False
sage: RR('-0').is_unit()
False
sage: RR('nan').is_unit()
False
sage: RR('inf').is_unit()
False
sage: RR('-inf').is_unit()
False
```

j0()

Return the value of the Bessel J function of order 0 at `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).j0()
0.223890779141236
```

j1()

Return the value of the Bessel J function of order 1 at `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).j1()
0.576724807756873
```

jn(n)

Return the value of the Bessel J function of order n at `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).jn(3)
0.128943249474402
sage: R(2).jn(-17)
-2.65930780516787e-15
```

log (*base=None*)

Return the logarithm of self to the base.

EXAMPLES:

```
sage: R = RealField()
sage: R(2).log()
0.693147180559945
sage: log(RR(2))
0.693147180559945
sage: log(RR(2), "e")
0.693147180559945
sage: log(RR(2), e)
0.693147180559945

sage: r = R(-1); r.log()
3.14159265358979*I
sage: log(RR(-1), e)
3.14159265358979*I
sage: r.log(2)
4.53236014182719*I
```

For the error value NaN (Not A Number), log will return NaN:

```
sage: r = R(NaN); r.log()
NaN
```

log10 ()

Return log to the base 10 of self.

EXAMPLES:

```
sage: r = 16.0; r.log10()
1.20411998265592
sage: r.log() / log(10.0)
1.20411998265592

sage: r = 39.9; r.log10()
1.60097289568675

sage: r = 0.0
sage: r.log10()
-infinity

sage: r = -1.0
sage: r.log10()
1.36437635384184*I
```

log1p ()

Return log base e of $1 + \text{self}$.

EXAMPLES:

```
sage: r = 15.0; r.loglp()
2.77258872223978
sage: (r+1).log()
2.77258872223978
```

For small values, this is more accurate than computing $\log(1 + \text{self})$ directly, as it avoids cancellation issues:

```
sage: r = 3e-10
sage: r.loglp()
2.99999999955000e-10
sage: (1+r).log()
3.00000024777111e-10
sage: r100 = RealField(100)(r)
sage: (1+r100).log()
2.9999999995500000000978021372e-10
```

For small values, this is more accurate than computing $\log(1 + \text{self})$ directly, as it avoid cancelation issues:

```
sage: r = 3e-10
sage: r.loglp()
2.99999999955000e-10
sage: (1+r).log()
3.00000024777111e-10
sage: r100 = RealField(100)(r)
sage: (1+r100).log()
2.9999999995500000000978021372e-10
```

```
sage: r = 38.9; r.loglp()
3.68637632389582
```

```
sage: r = -1.0
sage: r.loglp()
-infinity
```

```
sage: r = -2.0
sage: r.loglp()
3.14159265358979*I
```

log2()

Return log to the base 2 of self.

EXAMPLES:

```
sage: r = 16.0
sage: r.log2()
4.00000000000000
```

```
sage: r = 31.9; r.log2()
4.99548451887751
```

```
sage: r = 0.0
sage: r.log2()
-infinity
```

```
sage: r = -3.0; r.log2()
1.58496250072116 + 4.53236014182719*I
```

log_gamma()

Return the logarithm of gamma of `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(6).log_gamma()
4.78749174278205
sage: R(1e10).log_gamma()
2.20258509288811e11
```

`multiplicative_order()`

Return the multiplicative order of `self`.

EXAMPLES:

```
sage: RR(1).multiplicative_order()
1
sage: RR(-1).multiplicative_order()
2
sage: RR(3).multiplicative_order()
+Infinity
```

`nearby_rational(max_error=None, max_denominator=None)`

Find a rational near to `self`. Exactly one of `max_error` or `max_denominator` must be specified.

If `max_error` is specified, then this returns the simplest rational in the range `[self-max_error .. self+max_error]`. If `max_denominator` is specified, then this returns the rational closest to `self` with denominator at most `max_denominator`. (In case of ties, we pick the simpler rational.)

EXAMPLES:

```
sage: (0.333).nearby_rational(max_error=0.001)
1/3
sage: (0.333).nearby_rational(max_error=1)
0
sage: (-0.333).nearby_rational(max_error=0.0001)
-257/772

sage: (0.333).nearby_rational(max_denominator=100)
1/3
sage: RR(1/3 + 1/1000000).nearby_rational(max_denominator=2999999)
777780/2333333
sage: RR(1/3 + 1/1000000).nearby_rational(max_denominator=3000000)
1000003/3000000
sage: (-0.333).nearby_rational(max_denominator=1000)
-333/1000
sage: RR(3/4).nearby_rational(max_denominator=2)
1
sage: RR(pi).nearby_rational(max_denominator=120)
355/113
sage: RR(pi).nearby_rational(max_denominator=10000)
355/113
sage: RR(pi).nearby_rational(max_denominator=100000)
312689/99532
sage: RR(pi).nearby_rational(max_denominator=1)
3
sage: RR(-3.5).nearby_rational(max_denominator=1)
-3
```

TESTS:

```

sage: RR('nan').nearby_rational(max_denominator=1000)
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number
sage: RR('nan').nearby_rational(max_error=0.01)
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number
sage: RR(oo).nearby_rational(max_denominator=1000)
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number
sage: RR(oo).nearby_rational(max_error=0.01)
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number

```

nextabove()

Return the next floating-point number larger than self.

EXAMPLES:

```

sage: RR('-infinity').nextabove()
-2.09857871646739e323228496      # 32-bit
-5.87565378911159e1388255822130839282 # 64-bit
sage: RR(0).nextabove()
2.38256490488795e-323228497      # 32-bit
8.50969131174084e-1388255822130839284 # 64-bit
sage: RR('+infinity').nextabove()
+infinity
sage: RR(-sqrt(2)).str(truncate=False)
'-1.4142135623730951'
sage: RR(-sqrt(2)).nextabove().str(truncate=False)
'-1.4142135623730949'

```

nextbelow()

Return the next floating-point number smaller than self.

EXAMPLES:

```

sage: RR('-infinity').nextbelow()
-infinity
sage: RR(0).nextbelow()
-2.38256490488795e-323228497      # 32-bit
-8.50969131174084e-1388255822130839284 # 64-bit
sage: RR('+infinity').nextbelow()
2.09857871646739e323228496      # 32-bit
5.87565378911159e1388255822130839282 # 64-bit
sage: RR(-sqrt(2)).str(truncate=False)
'-1.4142135623730951'
sage: RR(-sqrt(2)).nextbelow().str(truncate=False)
'-1.4142135623730954'

```

nexttoward(*other*)

Return the floating-point number adjacent to self which is closer to other. If self or other is NaN, returns NaN; if self equals other, returns self.

EXAMPLES:

```

sage: (1.0).nexttoward(2).str(truncate=False)
'1.000000000000000002'
sage: (1.0).nexttoward(RR('-infinity')).str(truncate=False)
'0.999999999999999989'
sage: RR(infinity).nexttoward(0)
2.09857871646739e323228496          # 32-bit
5.87565378911159e1388255822130839282 # 64-bit
sage: RR(pi).str(truncate=False)
'3.1415926535897931'
sage: RR(pi).nexttoward(22/7).str(truncate=False)
'3.1415926535897936'
sage: RR(pi).nexttoward(21/7).str(truncate=False)
'3.1415926535897927'

```

nth_root (*n*, *algorithm*=0)

Return an n^{th} root of self.

INPUT:

- *n* – A positive number, rounded down to the nearest integer. Note that *n* should be less than `'sys.maxsize'`.
- *algorithm* – Set this to 1 to call mpfr directly, set this to 2 to use interval arithmetic and logarithms, or leave it at the default of 0 to choose the algorithm which is estimated to be faster.

AUTHORS:

- Carl Witty (2007-10)

EXAMPLES:

```

sage: R = RealField()
sage: R(8).nth_root(3)
2.0000000000000000
sage: R(8).nth_root(3.7)      # illustrate rounding down
2.0000000000000000
sage: R(-8).nth_root(3)
-2.0000000000000000
sage: R(0).nth_root(3)
0.0000000000000000
sage: R(32).nth_root(-1)
Traceback (most recent call last):
...
ValueError: n must be positive
sage: R(32).nth_root(1.0)
32.0000000000000000
sage: R(4).nth_root(4)
1.41421356237310
sage: R(4).nth_root(40)
1.03526492384138
sage: R(4).nth_root(400)
1.00347174850950
sage: R(4).nth_root(4000)
1.00034663365385
sage: R(4).nth_root(4000000)
1.00000034657365
sage: R(-27).nth_root(3)
-3.0000000000000000
sage: R(-4).nth_root(3999999)
-1.00000034657374

```

Note that for negative numbers, any even root throws an exception:

```
sage: R(-2).nth_root(6)
Traceback (most recent call last):
...
ValueError: taking an even root of a negative number
```

The n^{th} root of 0 is defined to be 0, for any n :

```
sage: R(0).nth_root(6)
0.0000000000000000
sage: R(0).nth_root(7)
0.0000000000000000
```

TESTS:

The old and new algorithms should give exactly the same results in all cases:

```
sage: def check(x, n):
...     answers = []
...     for sign in (1, -1):
...         if is_even(n) and sign == -1:
...             continue
...         for rounding in ('RNDN', 'RNDD', 'RNDU', 'RNDZ'):
...             fld = RealField(x.prec(), rnd=rounding)
...             fx = fld(sign * x)
...             alg_mpfr = fx.nth_root(n, algorithm=1)
...             alg_mpfi = fx.nth_root(n, algorithm=2)
...             assert(alg_mpfr == alg_mpfi)
...             if sign == 1: answers.append(alg_mpfr)
...     return answers
```

Check some perfect powers (and nearby numbers):

```
sage: check(16.0, 4)
[2.000000000000000, 2.000000000000000, 2.000000000000000, 2.000000000000000]
sage: check((16.0).nextabove(), 4)
[2.000000000000000, 2.000000000000000, 2.000000000000001, 2.000000000000000]
sage: check((16.0).nextbelow(), 4)
[2.000000000000000, 1.999999999999999, 2.000000000000000, 1.999999999999999]
sage: check(((9.0 * 256)^7), 7)
[2304.000000000000, 2304.000000000000, 2304.000000000000, 2304.000000000000]
sage: check(((9.0 * 256)^7).nextabove(), 7)
[2304.000000000000, 2304.000000000000, 2304.000000000001, 2304.000000000000]
sage: check(((9.0 * 256)^7).nextbelow(), 7)
[2304.000000000000, 2303.999999999999, 2304.000000000000, 2303.999999999999]
sage: check(((5.0 / 512)^17), 17)
[0.00976562500000000, 0.00976562500000000, 0.00976562500000000, 0.00976562500000000]
sage: check(((5.0 / 512)^17).nextabove(), 17)
[0.00976562500000000, 0.00976562500000000, 0.00976562500000001, 0.00976562500000000]
sage: check(((5.0 / 512)^17).nextbelow(), 17)
[0.00976562500000000, 0.00976562499999999, 0.00976562500000000, 0.00976562499999999]
```

And check some non-perfect powers:

```
sage: check(2.0, 3)
[1.25992104989487, 1.25992104989487, 1.25992104989488, 1.25992104989487]
sage: check(2.0, 4)
[1.18920711500272, 1.18920711500272, 1.18920711500273, 1.18920711500272]
sage: check(2.0, 5)
[1.14869835499704, 1.14869835499703, 1.14869835499704, 1.14869835499703]
```

And some different precisions:

```
sage: check(RealField(20)(22/7), 19)
[1.0621, 1.0621, 1.0622, 1.0621]
sage: check(RealField(200)(e), 4)
[1.2840254166877414840734205680624364583362808652814630892175, 1.284025416687741484073420568
```

Check that [trac ticket #12105](#) is fixed:

```
sage: RealField(53)(0.05).nth_root(7 * 10^8)
0.999999995720382
```

```
prec()
```

Return the precision of `self`.

EXAMPLES:

```
sage: RR(1.0).precision()
53
sage: RealField(101)(-1).precision()
101
```

```
precision()
```

Return the precision of `self`.

EXAMPLES:

```
sage: RR(1.0).precision()
53
sage: RealField(101)(-1).precision()
101
```

real()

Return the real part of `self`.

(Since `self` is a real number, this simply returns `self`.)

EXAMPLES:

[illegible]

round()

Rounds `self` to the nearest integer. The rounding mode of the parent field has no effect on this function.

EXAMPLES:

```
sage: RR(0.49).round()
0
sage: RR(0.5).round()
1
sage: RR(-0.49).round()
0
sage: RR(-0.5).round()
-1
```

sec ()

Returns the secant of this number

EXAMPLES:


```
sage: RealField(100)(2).sec()
-2.4029979617223809897546004014
```

sech()

Return the hyperbolic secant of `self`.

EXAMPLES:

```
sage: RealField(100)(2).sech()
0.26580222883407969212086273982
```

sign()

Return +1 if `self` is positive, -1 if `self` is negative, and 0 if `self` is zero.

EXAMPLES:

```
sage: R=RealField(100)
sage: R(-2.4).sign()
-1
sage: R(2.1).sign()
1
sage: R(0).sign()
0
```

sign_mantissa_exponent()

Return the sign, mantissa, and exponent of `self`.

In Sage (as in MPFR), floating-point numbers of precision p are of the form $sm2^{e-p}$, where $s \in \{-1, 1\}$, $2^{p-1} \leq m < 2^p$, and $-2^{30}+1 \leq e \leq 2^{30}-1$; plus the special values $+0$, -0 , $+\infty$, $-\infty$, and NaN (which stands for Not-a-Number).

This function returns s , m , and $e - p$. For the special values:

- $+0$ returns $(1, 0, 0)$ (analogous to IEEE-754; note that MPFR actually stores the exponent as “smallest exponent possible”)
- -0 returns $(-1, 0, 0)$ (analogous to IEEE-754; note that MPFR actually stores the exponent as “smallest exponent possible”)
- the return values for $+\infty$, $-\infty$, and NaN are not specified.

EXAMPLES:

```
sage: R = RealField(53)
sage: a = R(exp(1.0)); a
2.71828182845905
sage: sign, mantissa, exponent = R(exp(1.0)).sign_mantissa_exponent()
sage: sign, mantissa, exponent
(1, 6121026514868073, -51)
sage: sign*mantissa*(2**exponent) == a
True
```

The mantissa is always a nonnegative number (see [trac ticket #14448](#)):

```
sage: RR(-1).sign_mantissa_exponent()
(-1, 4503599627370496, -52)
```

We can also calculate this also using p -adic valuations:

```
sage: a = R(exp(1.0))
sage: b = a.exact_rational()
sage: valuation, unit = b.val_unit(2)
```

```

sage: (b/abs(b), unit, valuation)
(1, 6121026514868073, -51)
sage: a.sign_mantissa_exponent()
(1, 6121026514868073, -51)

```

TESTS:

```

sage: R('+0').sign_mantissa_exponent()
(1, 0, 0)
sage: R('-0').sign_mantissa_exponent()
(-1, 0, 0)

```

`simplest_rational()`

Return the simplest rational which is equal to `self` (in the Sage sense). Recall that Sage defines the equality operator by coercing both sides to a single type and then comparing; thus, this finds the simplest rational which (when coerced to this `RealField`) is equal to `self`.

Given rationals a/b and c/d (both in lowest terms), the former is simpler if $b < d$ or if $b = d$ and $|a| < |c|$.

The effect of rounding modes is slightly counter-intuitive. Consider the case of round-toward-minus-infinity. This rounding is performed when coercing a rational to a floating-point number; so the `simplest_rational()` of a round-to-minus-infinity number will be either exactly equal to or slightly larger than the number.

EXAMPLES:

```

sage: RRd = RealField(53, rnd='RNDD')
sage: RRz = RealField(53, rnd='RNDZ')
sage: RRu = RealField(53, rnd='RNDU')
sage: def check(x):
...     rx = x.simplest_rational()
...     assert(x == rx)
...     return rx
sage: RRd(1/3) < RRu(1/3)
True
sage: check(RRd(1/3))
1/3
sage: check(RRu(1/3))
1/3
sage: check(RRz(1/3))
1/3
sage: check(RR(1/3))
1/3
sage: check(RRd(-1/3))
-1/3
sage: check(RRu(-1/3))
-1/3
sage: check(RRz(-1/3))
-1/3
sage: check(RR(-1/3))
-1/3
sage: check(RealField(20)(pi))
355/113
sage: check(RR(pi))
245850922/78256779
sage: check(RR(2).sqrt())
131836323/93222358
sage: check(RR(1/2^210))
1/1645504557321205859467264516194506011931735427766374553794641921

```

```

sage: check(RR(2^210))
1645504557321205950811116849375918117252433820865891134852825088
sage: (RR(17).sqrt()).simplest_rational()^2 - 17
-1/348729667233025
sage: (RR(23).cube_root()).simplest_rational()^3 - 23
-1404915133/264743395842039084891584
sage: RRd5 = RealField(5, rnd='RNDD')
sage: RRu5 = RealField(5, rnd='RNDU')
sage: RR5 = RealField(5)
sage: below1 = RR5(1).nextbelow()
sage: check(RRd5(below1))
31/32
sage: check(RRu5(below1))
16/17
sage: check(below1)
21/22
sage: below1.exact_rational()
31/32
sage: above1 = RR5(1).nextabove()
sage: check(RRd5(above1))
10/9
sage: check(RRu5(above1))
17/16
sage: check(above1)
12/11
sage: above1.exact_rational()
17/16
sage: check(RR(1234))
1234
sage: check(RR5(1234))
1185
sage: check(RR5(1184))
1120
sage: RRd2 = RealField(2, rnd='RNDD')
sage: RRu2 = RealField(2, rnd='RNDU')
sage: RR2 = RealField(2)
sage: check(RR2(8))
7
sage: check(RRd2(8))
8
sage: check(RRu2(8))
7
sage: check(RR2(13))
11
sage: check(RRd2(13))
12
sage: check(RRu2(13))
13
sage: check(RR2(16))
14
sage: check(RRd2(16))
16
sage: check(RRu2(16))
13
sage: check(RR2(24))
21
sage: check(RRu2(24))
17

```

```
sage: check(RR2(-24))
-21
sage: check(RRu2(-24))
-24
```

TESTS:

```
sage: RR('nan').simplest_rational()
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number
sage: RR('-infinity').simplest_rational()
Traceback (most recent call last):
...
ValueError: Cannot convert NaN or infinity to rational number
```

sin()

Return the sine of self.

EXAMPLES:

```
sage: R = RealField(100)
sage: R(2).sin()
0.90929742682568169539601986591
```

sincos()

Return a pair consisting of the sine and cosine of self.

EXAMPLES:

```
sage: R = RealField()
sage: t = R.pi()/6
sage: t.sincos()
(0.5000000000000000, 0.866025403784439)
```

sinh()

Return the hyperbolic sine of self.

EXAMPLES:

```
sage: q = RR.pi()/12
sage: q.sinh()
0.264800227602271
```

sqrt (*extend=True, all=False*)

The square root function.

INPUT:

- **extend** – bool (default: True); if True, return a square root in a complex field if necessary if self is negative; otherwise raise a ValueError
- **all** – bool (default: False); if True, return a list of all square roots.

EXAMPLES:

```
sage: r = -2.0
sage: r.sqrt()
1.41421356237310*I

sage: r = 4.0
sage: r.sqrt()
```

```

2.0000000000000000
sage: r.sqrt()^2 == r
True

sage: r = 4344
sage: r.sqrt()
2*sqrt(1086)

sage: r = 4344.0
sage: r.sqrt()^2 == r
True
sage: r.sqrt()^2 - r
0.0000000000000000

sage: r = -2.0
sage: r.sqrt()
1.41421356237310*I

```

str (*base=10, no_sci=None, e=None, truncate=1, skip_zeroes=0*)
 Return a string representation of self.

INPUT:

- *base* – base for output
- *no_sci* – if 2, never print using scientific notation; if 1 or True, print using scientific notation only for very large or very small numbers; if 0 or False always print with scientific notation; if None (the default), print how the parent prints.
- *e* – symbol used in scientific notation; defaults to ‘e’ for base=10, and ‘@’ otherwise
- *truncate* – if True, round off the last digits in printing to lessen confusing base-2 roundoff issues.
- *skip_zeroes* – if True, skip trailing zeroes in mantissa

EXAMPLES:

```

sage: a = 61/3.0; a
20.3333333333333
sage: a.str(truncate=False)
'20.33333333333332'
sage: a.str(2)
'10100.010101010101010101010101010101010101010101'
sage: a.str(no_sci=False)
'2.03333333333333e1'
sage: a.str(16, no_sci=False)
'1.45555555555555@1'
sage: b = 2.0^99
sage: b.str()
'6.33825300114115e29'
sage: b.str(no_sci=False)
'6.33825300114115e29'
sage: b.str(no_sci=True)
'6.33825300114115e29'
sage: c = 2.0^100
sage: c.str()
'1.26765060022823e30'
sage: c.str(no_sci=False)
'1.26765060022823e30'
sage: c.str(no_sci=True)
'1.26765060022823e30'

```

```
sage: c.str(no_sci=2)
'1267650600228230000000000000000000.'
sage: 0.5^53
1.11022302462516e-16
sage: 0.5^54
5.55111512312578e-17
sage: (0.01).str()
'0.0100000000000000'
sage: (0.01).str(skip_zeroes=True)
'0.01'
sage: (-10.042).str()
'-10.0420000000000'
sage: (-10.042).str(skip_zeroes=True)
'-10.042'
sage: (389.0).str(skip_zeroes=True)
'389.'
```

Test various bases:

```
sage: print (65536.0).str(base=2)
1.00000000000000000000000000000000000000000000000e16
sage: print (65536.0).str(base=36)
1ekg.00000000
sage: print (65536.0).str(base=62)
H32.0000000
sage: print (65536.0).str(base=63)
Traceback (most recent call last):
...
ValueError: base (=63) must be an integer between 2 and 62
```

tan()

Return the tangent of `self`.

EXAMPLES:

```
sage: q = RR.pi()/3
sage: q.tan()
1.73205080756888
sage: q = RR.pi()/6
sage: q.tan()
0.577350269189626
```

tanh ()

Return the hyperbolic tangent of `self`.

EXAMPLES:

```
sage: q = RR.pi()/11
sage: q.tanh()
0.278079429295850
```

trunc()

Truncate self.

EXAMPLES:

```
sage: (2.99).trunc()  
2  
sage: (-0.00).trunc()  
0
```

```
sage: (0.00).trunc()
0
```

ulp (*field=None*)

Returns the unit of least precision of `self`, which is the weight of the least significant bit of `self`. This is always a strictly positive number. It is also the gap between this number and the closest number with larger absolute value that can be represented.

INPUT:

- `field` – `RealField` used as parent of the result. If not specified, use `parent(self)`.

Note: The `ulp` of zero is defined as the smallest representable positive number. For extremely small numbers, underflow occurs and the output is also the smallest representable positive number (the rounding mode is ignored, this computation is done by rounding towards +infinity).

See also:

`epsilon()` for a scale-invariant version of this.

EXAMPLES:

```
sage: a = 1.0
sage: a.ulp()
2.22044604925031e-16
sage: (-1.5).ulp()
2.22044604925031e-16
sage: a + a.ulp() == a
False
sage: a + a.ulp()/2 == a
True

sage: a = RealField(500).pi()
sage: b = a + a.ulp()
sage: (a+b)/2 in [a,b]
True
```

The `ulp` of zero is the smallest non-zero number:

```
sage: a = RR(0).ulp()
sage: a
2.38256490488795e-323228497 # 32-bit
8.50969131174084e-1388255822130839284 # 64-bit
sage: a.fp_rank()
1
```

The `ulp` of very small numbers results in underflow, so the smallest non-zero number is returned instead:

```
sage: a.ulp() == a
True
```

We use a different field:

```
sage: a = RealField(256).pi()
sage: a.ulp()
3.454467422037777850154540745120159828446400145774512554009481388067436721265e-77
sage: e = a.ulp(RealField(64))
sage: e
3.45446742203777785e-77
sage: parent(e)
```

```
Real Field with 64 bits of precision
sage: e = a.ulp(QQ)
Traceback (most recent call last):
...
TypeError: field argument must be a RealField
```

For infinity and NaN, we get back positive infinity and NaN:

```
sage: a = RR(infinity)
sage: a.ulp()
+infinity
sage: (-a).ulp()
+infinity
sage: a = RR('nan')
sage: a.ulp()
NaN
sage: parent(RR('nan').ulp(RealField(42)))
Real Field with 42 bits of precision
```

y0()

Return the value of the Bessel Y function of order 0 at `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).y0()
0.510375672649745
```

y1()

Return the value of the Bessel Y function of order 1 at `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).y1()
-0.107032431540938
```

yn(n)

Return the value of the Bessel Y function of order n at `self`.

EXAMPLES:

```
sage: R = RealField(53)
sage: R(2).yn(3)
-1.12778377684043
sage: R(2).yn(-17)
7.09038821729481e12
```

zeta()

Return the Riemann zeta function evaluated at this real number.

Note: PARI is vastly more efficient at computing the Riemann zeta function. See the example below for how to use it.

EXAMPLES:

```
sage: R = RealField()
sage: R(2).zeta()
1.64493406684823
sage: R.pi()^2/6
```



```

1.64493406684823
sage: R(-2).zeta()
0.0000000000000000
sage: R(1).zeta()
+infinity

```

Computing zeta using PARI is much more efficient in difficult cases. Here's how to compute zeta with at least a given precision:

```

sage: z = pari(2).zeta(precision=53); z
1.64493406684823
sage: pari(2).zeta(precision=128).python().prec()
128
sage: pari(2).zeta(precision=65).python().prec()
128                                     # 64-bit
96                                     # 32-bit

```

Note that the number of bits of precision in the constructor only effects the internal precision of the pari number, which is rounded up to the nearest multiple of 32 or 64. To increase the number of digits that gets displayed you must use `pari.set_real_precision`.

```

sage: type(z)
<type 'sage.libs.pari.gen.gen'>
sage: R(z)
1.64493406684823

```

class `sage.rings.real_mpfr.ZZtoRR`
 Bases: `sage.categories.map.Map`

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```

sage: Map(Hom(QQ, ZZ, Rings()))
Generic map:
  From: Rational Field
  To:   Integer Ring

```

Using domain and codomain:

```

sage: Map(QQ['x'], SymmetricGroup(6))
Generic map:
  From: Univariate Polynomial Ring in x over Rational Field
  To:   Symmetric group of order 6! as a permutation group

```

`sage.rings.real_mpfr.create_RealField(prec=53, type='MPFR', rnd='RNDN', sci_not=0)`
 Create a real field with given precision, type, rounding mode and scientific notation.

Some options are ignored for certain types (RDF for example).

INPUT:

- `prec` – a positive integer
- `type` – type of real field:

- ‘RDF’ – the Sage real field corresponding to native doubles
- ‘Interval’ – real fields implementing interval arithmetic
- ‘RLF’ – the real lazy field
- ‘MPFR’ – floating point real numbers implemented using the MPFR library
- `rnd` – rounding mode:
 - ‘RNDN’ – round to nearest
 - ‘RNDZ’ – round toward zero
 - ‘RNDD’ – round down
 - ‘RNDU’ – round up
- `sci_not` – boolean, whether to use scientific notation for printing

OUTPUT:

the appropriate real field

EXAMPLES:

```
sage: from sage.rings.real_mpfr import create_RealField
sage: create_RealField(30)
Real Field with 30 bits of precision
sage: create_RealField(20, 'RDF') # ignores precision
Real Double Field
sage: create_RealField(60, 'Interval')
Real Interval Field with 60 bits of precision
sage: create_RealField(40, 'RLF') # ignores precision
Real Lazy Field
```

```
sage.rings.real_mpfr.create_RealNumber(s, base=10, pad=0, rnd='RNDN', min_prec=53)
```

Return the real number defined by the string `s` as an element of `RealField(prec=n)`, where `n` potentially has slightly more (controlled by `pad`) bits than given by `s`.

INPUT:

- `s` – a string that defines a real number (or something whose string representation defines a number)
- `base` – an integer between 2 and 62
- `pad` – an integer = 0.
- `rnd` – rounding mode:
 - ‘RNDN’ – round to nearest
 - ‘RNDZ’ – round toward zero
 - ‘RNDD’ – round down
 - ‘RNDU’ – round up
- `min_prec` – number will have at least this many bits of precision, no matter what.

EXAMPLES:

```
sage: RealNumber('2.3') # indirect doctest
2.3000000000000000
sage: RealNumber(10)
10.0000000000000000
sage: RealNumber('1.0000000000000000000000000000000000000000000000000')
1.0000000000000000000000000000000000000000000000000
```

[illegible]

We can use various bases:

```
sage: RealNumber("10101e2", base=2)
84.00000000000000
sage: RealNumber("deadbeef", base=16)
3.735928559000000e9
sage: RealNumber("deadbeefxxx", base=16)
Traceback (most recent call last):
...
TypeError: Unable to convert x (=‘deadbeefxxx’) to real number.
sage: RealNumber("z", base=36)
35.00000000000000
sage: RealNumber("AAA", base=37)
14070.0000000000
sage: RealNumber("aaa", base=37)
50652.0000000000
sage: RealNumber("3.4", base="foo")
Traceback (most recent call last):
...
TypeError: an integer is required
sage: RealNumber("3.4", base=63)
Traceback (most recent call last):
...
ValueError: base (=63) must be an integer between 2 and 62
```

The rounding mode is respected in all cases:

```
sage: RealNumber("1.5", rnd="RNDU").parent()
Real Field with 53 bits of precision and rounding RNDU
sage: RealNumber("1.5000000000000000000000000000000000", rnd="RNDU").parent()
Real Field with 130 bits of precision and rounding RNDU
```

TESTS:

[illegible]

Make sure we've rounded up $\log(10, 2)$ enough to guarantee sufficient precision ([trac ticket #10164](#)):

```
sage: ks = 5*10**5, 10**6
sage: all(RealNumber("1." + "0"*k + "1")-1 > 0 for k in ks)
True
```

```
class sage.rings.real_mpfr.double_torR
  Bases: sage.categories.map.Map
```

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

From: Rational Field

To: Integer Ring

Using domain and codomain:

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

From: Univariate Polynomial Ring in x over Rational Field

To: Symmetric group of order 6! as a permutation group

```
class sage.rings.real_mpfr.int_toRR
```

Bases: sage.categories.map.Map

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

From: Rational Field

To: Integer Ring

Using domain and codomain:

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

From: Univariate Polynomial Ring in x over Rational Field

To: Symmetric group of order 6! as a permutation group

```
sage.rings.real_mpfr.is_RealField(x)
```

Returns True if x is technically of a Python real field type.

EXAMPLES:

```
sage: sage.rings.real_mpfr.is_RealField(RR)
```

True

```
sage: sage.rings.real_mpfr.is_RealField(CC)
```

False

```
sage.rings.real_mpfr.is_RealNumber(x)
```

Return True if x is of type `RealNumber`, meaning that it is an element of the MPFR real field with some precision.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import is_RealNumber
```

```
sage: is_RealNumber(2.5)
```

True

```
sage: is_RealNumber(float(2.3))
```

```
False
sage: is_RealNumber(RDF(2))
False
sage: is_RealNumber(pi)
False
```

`sage.rings.real_mpfr.mpfr_get_exp_max()`
Return the current maximal exponent for MPFR numbers.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import mpfr_get_exp_max
sage: mpfr_get_exp_max()
1073741823          # 32-bit
4611686018427387903 # 64-bit
sage: 0.5 << mpfr_get_exp_max()
1.04928935823369e323228496          # 32-bit
2.93782689455579e1388255822130839282 # 64-bit
sage: 0.5 << (mpfr_get_exp_max()+1)
+infinity
```

`sage.rings.real_mpfr.mpfr_get_exp_max_max()`
Get the maximal value allowed for `mpfr_set_exp_max()`.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import mpfr_get_exp_max_max, mpfr_set_exp_max
sage: mpfr_get_exp_max_max()
1073741823          # 32-bit
4611686018427387903 # 64-bit
```

This is really the maximal value allowed:

```
sage: mpfr_set_exp_max(mpfr_get_exp_max_max() + 1)
Traceback (most recent call last):
...
OverflowError: bad value for mpfr_set_exp_max()
```

`sage.rings.real_mpfr.mpfr_get_exp_min()`
Return the current minimal exponent for MPFR numbers.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import mpfr_get_exp_min
sage: mpfr_get_exp_min()
-1073741823          # 32-bit
-4611686018427387903 # 64-bit
sage: 0.5 >> (-mpfr_get_exp_min())
2.38256490488795e-323228497          # 32-bit
8.50969131174084e-1388255822130839284 # 64-bit
sage: 0.5 >> (-mpfr_get_exp_min()+1)
0.0000000000000000
```

`sage.rings.real_mpfr.mpfr_get_exp_min_min()`
Get the minimal value allowed for `mpfr_set_exp_min()`.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import mpfr_get_exp_min_min, mpfr_set_exp_min
sage: mpfr_get_exp_min_min()
```

```
-1073741823          # 32-bit
-4611686018427387903 # 64-bit
```

This is really the minimal value allowed:

```
sage: mpfr_set_exp_min(mpfr_get_exp_min_min() - 1)
Traceback (most recent call last):
...
OverflowError: bad value for mpfr_set_exp_min()
```

sage.rings.real_mpfr.**mpfr_prec_max**()

TESTS:

```
sage: from sage.rings.real_mpfr import mpfr_prec_max
sage: mpfr_prec_max()
2147483391
sage: R = RealField(2^31-257)
sage: R
Real Field with 2147483391 bits of precision
sage: R = RealField(2^31-256)
Traceback (most recent call last):
...
ValueError: prec (=2147483392) must be >= 2 and <= 2147483391
```

sage.rings.real_mpfr.**mpfr_prec_min**()

Return the mpfr variable MPFR_PREC_MIN.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import mpfr_prec_min
sage: mpfr_prec_min()
2
sage: R = RealField(2)
sage: R(2) + R(1)
3.0
sage: R(4) + R(1)
4.0
sage: R = RealField(1)
Traceback (most recent call last):
...
ValueError: prec (=1) must be >= 2 and <= 2147483391
```

sage.rings.real_mpfr.**mpfr_set_exp_max**(e)

Set the maximal exponent for MPFR numbers.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import mpfr_get_exp_max, mpfr_set_exp_max
sage: old = mpfr_get_exp_max()
sage: mpfr_set_exp_max(1000)
sage: 0.5 << 1000
5.35754303593134e300
sage: 0.5 << 1001
+infinity
sage: mpfr_set_exp_max(old)
sage: 0.5 << 1001
1.07150860718627e301
```

sage.rings.real_mpfr.**mpfr_set_exp_min**(e)

Set the minimal exponent for MPFR numbers.

EXAMPLES:

```
sage: from sage.rings.real_mpfr import mpfr_get_exp_min, mpfr_set_exp_min
sage: old = mpfr_get_exp_min()
sage: mpfr_set_exp_min(-1000)
sage: 0.5 >> 1000
4.66631809251609e-302
sage: 0.5 >> 1001
0.0000000000000000
sage: mpfr_set_exp_min(old)
sage: 0.5 >> 1001
2.33315904625805e-302
```


ARBITRARY PRECISION REAL INTERVALS

AUTHORS:

- Carl Witty (2007-01-21): based on `real_mpf_r.pyx`; changed it to use `mpfi` rather than `mpfr`.
- William Stein (2007-01-24): modifications and clean up and docs, etc.
- Niles Johnson (2010-08): [trac ticket #3893](#): `random_element()` should pass on `*args` and `**kwargs`.
- Travis Scrimshaw (2012-10-20): Fixing scientific notation output to fix [trac ticket #13634](#).
- Travis Scrimshaw (2012-11-02): Added doctests for full coverage

This is a straightforward binding to the MPFI library; it may be useful to refer to its documentation for more details.

An interval is represented as a pair of floating-point numbers a and b (where $a \leq b$) and is printed as a standard floating-point number with a question mark (for instance, `3.1416?`). The question mark indicates that the preceding digit may have an error of ± 1 . These floating-point numbers are implemented using MPFR (the same as the `RealNumber` elements of `RealField_class`).

There is also an alternate method of printing, where the interval prints as `[a .. b]` (for instance, `[3.1415 .. 3.1416]`).

The interval represents the set $\{x : a \leq x \leq b\}$ (so if $a = b$, then the interval represents that particular floating-point number). The endpoints can include positive and negative infinity, with the obvious meaning. It is also possible to have a NaN (Not-a-Number) interval, which is represented by having either endpoint be NaN.

PRINTING:

There are two styles for printing intervals: ‘brackets’ style and ‘question’ style (the default).

In question style, we print the “known correct” part of the number, followed by a question mark. The question mark indicates that the preceding digit is possibly wrong by ± 1 .

```
sage: RIF(sqrt(2))
1.414213562373095?
```

However, if the interval is precise (its lower bound is equal to its upper bound) and equal to a not-too-large integer, then we just print that integer.

```
sage: RIF(0)
0
sage: RIF(654321)
654321
```

```
sage: RIF(123, 125)
124.?
sage: RIF(123, 126)
1.3?e2
```

As we see in the last example, question style can discard almost a whole digit's worth of precision. We can reduce this by allowing “error digits”: an error following the question mark, that gives the maximum error of the digit(s) before the question mark. If the error is absent (which it always is in the default printing), then it is taken to be 1.

```
sage: RIF(123, 126).str(error_digits=1)
'125.?2'
sage: RIF(123, 127).str(error_digits=1)
'125.?2'
sage: v = RIF(-e, pi); v
0.?e1
sage: v.str(error_digits=1)
'1.?4'
sage: v.str(error_digits=5)
'0.2117?29300'
```

Error digits also sometimes let us indicate that the interval is actually equal to a single floating-point number:

```
sage: RIF(54321/256)
212.191406250000000?
sage: RIF(54321/256).str(error_digits=1)
'212.191406250000000?0'
```

In brackets style, intervals are printed with the left value rounded down and the right rounded up, which is conservative, but in some ways unsatisfying.

Consider a 3-bit interval containing exactly the floating-point number 1.25. In round-to-nearest or round-down, this prints as 1.2; in round-up, this prints as 1.3. The straightforward options, then, are to print this interval as `[1.2 .. 1.2]` (which does not even contain the true value, 1.25), or to print it as `[1.2 .. 1.3]` (which gives the impression that the upper and lower bounds are not equal, even though they really are). Neither of these is very satisfying, but we have chosen the latter.

```
sage: R = RealIntervalField(3)
sage: a = R(1.25)
sage: a.str(style='brackets')
'[1.2 .. 1.3]'
sage: a == 1.25
True
sage: a == 2
False
```

COMPARISONS:

Comparison operations (`==`, `!=`, `<`, `<=`, `>`, `>=`) return `True` if every value in the first interval has the given relation to every value in the second interval. The `cmp(a, b)` function works differently; it compares two intervals lexicographically. (However, the behavior is not specified if given a non-interval and an interval.)

This convention for comparison operators has good and bad points. The good:

- Expected transitivity properties hold (if $a > b$ and $b == c$, then $a > c$; etc.)
- if $a > b$, then `cmp(a, b) == 1`; if $a == b$, then `cmp(a, b) == 0`; if $a < b$, then `cmp(a, b) == -1`
- $a == 0$ is true if the interval contains only the floating-point number 0; similarly for $a == 1$
- $a > 0$ means something useful (that every value in the interval is greater than 0)

The bad:

- Trichotomy fails to hold: there are values (a, b) such that none of $a < b$, $a == b$, or $a > b$ are true

- It is not the case that if $\text{cmp}(a, b) == 0$ then $a == b$, or that if $\text{cmp}(a, b) == 1$ then $a > b$, or that if $\text{cmp}(a, b) == -1$ then $a < b$
- There are values a and b such that $a \leq b$ but neither $a < b$ nor $a == b$ hold.

Note: Intervals a and b overlap iff $\text{not}(a \neq b)$.

EXAMPLES:

```
sage: 0 < RIF(1, 2)
True
sage: 0 == RIF(0)
True
sage: not(0 == RIF(0, 1))
True
sage: not(0 != RIF(0, 1))
True
sage: 0 <= RIF(0, 1)
True
sage: not(0 < RIF(0, 1))
True
sage: cmp(RIF(0), RIF(0, 1))
-1
sage: cmp(RIF(0, 1), RIF(0))
1
sage: cmp(RIF(0, 1), RIF(1))
-1
sage: cmp(RIF(0, 1), RIF(0, 1))
0
```

Comparison with infinity is defined through coercion to the infinity ring where semi-infinite intervals are sent to their central value (plus or minus infinity); This implements the above convention for inequalities:

```
sage: InfinityRing.has_coerce_map_from(RIF)
True
sage: -oo < RIF(-1, 1) < oo
True
sage: -oo < RIF(0, oo) <= oo
True
sage: -oo <= RIF(-oo, -1) < oo
True
```

Comparison by equality shows what the semi-infinite intervals actually coerce to:

```
sage: RIF(1, oo) == oo
True
sage: RIF(-oo, -1) == -oo
True
```

For lack of a better value in the infinity ring, the doubly infinite interval coerces to plus infinity:

```
sage: RIF(-oo, oo) == oo
True
```

`sage.rings.real_mpfi.RealInterval` (*s*, *upper=None*, *base=10*, *pad=0*, *min_prec=53*)

Return the real number defined by the string *s* as an element of `RealIntervalField(prec=n)`, where *n* potentially has slightly more (controlled by *pad*) bits than given by *s*.

INPUT:

class `sage.rings.real_mpf.RealIntervalFieldElement`

Bases: `sage.structure.element.RingElement`

A real number interval.

absolute_diameter()

The diameter of this interval (for $[a..b]$, this is $b - a$), rounded upward, as a `RealNumber`.

EXAMPLES:

```
sage: RIF(1, pi).absolute_diameter()
2.14159265358979
```

alea()

Return a floating-point number picked at random from the interval.

EXAMPLES:

```
sage: RIF(1, 2).alea() # random
1.34696133696137
```

algdep(*n*)

Returns a polynomial of degree at most n which is approximately satisfied by `self`.

Note: The returned polynomial need not be irreducible, and indeed usually won't be if `self` is a good approximation to an algebraic number of degree less than n .

Pari needs to know the number of “known good bits” in the number; we automatically get that from the interval width.

ALGORITHM:

Uses the PARI C-library `algdep` command.

EXAMPLES:

```
sage: r = sqrt(RIF(2)); r
1.414213562373095?
sage: r.algdep(5)
x^2 - 2
```

If we compute a wrong, but precise, interval, we get a wrong answer:

```
sage: r = sqrt(RealIntervalField(200)(2)) + (1/2)^40; r
1.414213562374004543503461652447613117632171875376948073176680?
sage: r.algdep(5)
7266488*x^5 + 22441629*x^4 - 90470501*x^3 + 23297703*x^2 + 45778664*x + 13681026
```

But if we compute an interval that includes the number we mean, we're much more likely to get the right answer, even if the interval is very imprecise:

```
sage: r = r.union(sqrt(2.0))
sage: r.algdep(5)
x^2 - 2
```

Even on this extremely imprecise interval we get an answer which is technically correct:

```
sage: RIF(-1, 1).algdep(5)
x
```

arccos()

Return the inverse cosine of `self`.

EXAMPLES:

```
sage: q = RIF.pi()/3; q
1.047197551196598?
sage: i = q.cos(); i
0.5000000000000000?
sage: q2 = i.arccos(); q2
1.047197551196598?
sage: q == q2
False
sage: q != q2
False
sage: q2.lower() == q.lower()
False
sage: q - q2
0.?e-15
sage: q in q2
True
```

arccosh()

Return the hyperbolic inverse cosine of `self`.

EXAMPLES:

```
sage: q = RIF.pi()/2
sage: i = q.arccosh() ; i
1.023227478547551?
```

arccoth()

Return the inverse hyperbolic cotangent of `self`.

EXAMPLES:

```
sage: RealIntervalField(100)(2).arccoth()
0.549306144334054845697622618462?
sage: (2.0).arccoth()
0.549306144334055
```

arccsch()

Return the inverse hyperbolic cosecant of `self`.

EXAMPLES:

```
sage: RealIntervalField(100)(2).arccsch()
0.481211825059603447497758913425?
sage: (2.0).arccsch()
0.481211825059603
```

arcsech()

Return the inverse hyperbolic secant of `self`.

EXAMPLES:

```
sage: RealIntervalField(100)(0.5).arcsech()
1.316957896924816708625046347308?
sage: (0.5).arcsech()
1.31695789692482
```

arcsin()

Return the inverse sine of `self`.

EXAMPLES:

```
sage: q = RIF.pi()/5; q
0.6283185307179587?
sage: i = q.sin(); i
0.587785252292474?
sage: q2 = i.arcsin(); q2
0.628318530717959?
sage: q == q2
False
sage: q != q2
False
sage: q2.lower() == q.lower()
False
sage: q - q2
0.?e-15
sage: q in q2
True
```

arcsinh()

Return the hyperbolic inverse sine of self.

EXAMPLES:

```
sage: q = RIF.pi()/7
sage: i = q.sinh(); i
0.464017630492991?
sage: i.arcsinh() - q
0.?e-15
```

arctan()

Return the inverse tangent of self.

EXAMPLES:

```
sage: q = RIF.pi()/5; q
0.6283185307179587?
sage: i = q.tan(); i
0.726542528005361?
sage: q2 = i.arctan(); q2
0.628318530717959?
sage: q == q2
False
sage: q != q2
False
sage: q2.lower() == q.lower()
False
sage: q - q2
0.?e-15
sage: q in q2
True
```

arctanh()

Return the hyperbolic inverse tangent of self.

EXAMPLES:

```
sage: q = RIF.pi()/7
sage: i = q.tanh(); i
0.420911241048535?
sage: i.arctanh() - q
0.?e-15
```

bisection()

Returns the bisection of `self` into two intervals of half the size whose union is `self` and intersection is `center()`.

EXAMPLES:

```
sage: a, b = RIF(1,2).bisection()
sage: a.lower(), a.upper()
(1.000000000000000, 1.500000000000000)
sage: b.lower(), b.upper()
(1.500000000000000, 2.000000000000000)

sage: I = RIF(e, pi)
sage: a, b = I.bisection()
sage: a.intersection(b) == I.center()
True
sage: a.union(b).endpoints() == I.endpoints()
True
```

ceil()

Return the ceiling of `self`.

OUTPUT:

integer

EXAMPLES:

```
sage: (2.99).ceil()
3
sage: (2.00).ceil()
2
sage: (2.01).ceil()
3
sage: R = RealIntervalField(30)
sage: a = R(-9.5, -11.3); a.str(style='brackets')
'[-11.3000000012 .. -9.5000000000]'
sage: a.floor().str(style='brackets')
'[-12.0000000000 .. -10.0000000000]'
sage: a.ceil()
-10.?
sage: ceil(a).str(style='brackets')
'[-11.0000000000 .. -9.0000000000]'
```

ceiling()

Return the ceiling of `self`.

OUTPUT:

integer

EXAMPLES:

```
sage: (2.99).ceil()
3
sage: (2.00).ceil()
2
sage: (2.01).ceil()
3
sage: R = RealIntervalField(30)
sage: a = R(-9.5, -11.3); a.str(style='brackets')
'[-11.3000000012 .. -9.5000000000]'
```



```
sage: a.floor().str(style='brackets')
'[-12.000000000 .. -10.000000000]'
sage: a.ceil()
-10.?
sage: ceil(a).str(style='brackets')
'[-11.000000000 .. -9.000000000]'
```

center()

Compute the center of the interval $[a..b]$ which is $(a+b)/2$.

EXAMPLES:

```
sage: RIF(1, 2).center()
1.500000000000000
```

contains_zero()

Return True if self is an interval containing zero.

EXAMPLES:

```
sage: RIF(0).contains_zero()
True
sage: RIF(1, 2).contains_zero()
False
sage: RIF(-1, 1).contains_zero()
True
sage: RIF(-1, 0).contains_zero()
True
```

cos()

Return the cosine of self.

EXAMPLES:

```
sage: t=RIF(pi)/2
sage: t.cos()
0.?e-15
sage: t.cos().str(style='brackets')
'[-1.6081226496766367e-16 .. 6.1232339957367661e-17]'
sage: t.cos().cos()
0.999999999999999?
```

TESTS:

This looped forever with an earlier version of MPFI, but now it works:

```
sage: RIF(-1, 1).cos().str(style='brackets')
'[0.54030230586813965 .. 1.0000000000000000]'
```

cosh()

Return the hyperbolic cosine of self.

EXAMPLES:

```
sage: q = RIF.pi()/12
sage: q.cosh()
1.034465640095511?
```

cot()

Return the cotangent of self.

EXAMPLES:

```
sage: RealIntervalField(100)(2).cot()  
-0.457657554360285763750277410432?
```

coth()

Return the hyperbolic cotangent of self.

EXAMPLES:

```
sage: RealIntervalField(100)(2).coth()  
1.03731472072754809587780976477?
```

csc()

Return the cosecant of self.

EXAMPLES:

```
sage: RealIntervalField(100)(2).csc()  
1.099750170294616466756697397026?
```

csch()

Return the hyperbolic cosecant of self.

EXAMPLES:

```
sage: RealIntervalField(100)(2).csch()  
0.275720564771783207758351482163?
```

diameter()

If 0 is in self, then return `absolute_diameter()`, otherwise return `relative_diameter()`.

EXAMPLES:

```
sage: RIF(1, 2).diameter()  
0.6666666666666667  
sage: RIF(1, 2).absolute_diameter()  
1.0000000000000000  
sage: RIF(1, 2).relative_diameter()  
0.6666666666666667  
sage: RIF(pi).diameter()  
1.41357985842823e-16  
sage: RIF(pi).absolute_diameter()  
4.44089209850063e-16  
sage: RIF(pi).relative_diameter()  
1.41357985842823e-16  
sage: (RIF(pi) - RIF(3, 22/7)).diameter()  
0.142857142857144  
sage: (RIF(pi) - RIF(3, 22/7)).absolute_diameter()  
0.142857142857144  
sage: (RIF(pi) - RIF(3, 22/7)).relative_diameter()  
2.03604377705518
```

endpoints(rnd=None)

Return the lower and upper endpoints of self.

EXAMPLES:

```
sage: RIF(1, 2).endpoints()  
(1.0000000000000000, 2.0000000000000000)  
sage: RIF(pi).endpoints()  
(3.14159265358979, 3.14159265358980)  
sage: a = CIF(RIF(1, 2), RIF(3, 4))
```

```
sage: a.real().endpoints()
(1.000000000000000, 2.000000000000000)
```

As with `lower()` and `upper()`, a rounding mode is accepted:

```
sage: RIF(1,2).endpoints('RNDD')[0].parent()
Real Field with 53 bits of precision and rounding RNDD
```

exp()

Returns e^{self}

EXAMPLES:

```
sage: r = RIF(0.0)
sage: r.exp()
1

sage: r = RIF(32.3)
sage: a = r.exp(); a
1.065888472748645?e14
sage: a.log()
32.30000000000000?

sage: r = RIF(-32.3)
sage: r.exp()
9.38184458849869?e-15
```

exp2()

Returns 2^{self}

EXAMPLES:

```
sage: r = RIF(0.0)
sage: r.exp2()
1

sage: r = RIF(32.0)
sage: r.exp2()
4294967296

sage: r = RIF(-32.3)
sage: r.exp2()
1.891172482530207?e-10
```

factorial()

Return the factorial evaluated on `self`.

EXAMPLES:

```
sage: RIF(5).factorial()
120
sage: RIF(2.3,5.7).factorial()
1.?e3
sage: RIF(2.3).factorial()
2.683437381955768?
```

Recover the factorial as integer:

```
sage: f = RealIntervalField(200)(50).factorial()
sage: f
3.0414093201713378043612608166064768844377641568960512000000000?e64
```

```
sage: f.unique_integer()
30414093201713378043612608166064768844377641568960512000000000000
sage: 50.factorial()
30414093201713378043612608166064768844377641568960512000000000000
```

floor()

Return the floor of `self`.

EXAMPLES:

[illegible]

`fp_rank_diameter()`

Computes the diameter of this interval in terms of the “floating-point rank”.

The floating-point rank is the number of floating-point numbers (of the current precision) contained in the given interval, minus one. An `fp_rank_diameter` of 0 means that the interval is exact; an `fp_rank_diameter` of 1 means that the interval is as tight as possible, unless the number you're trying to represent is actually exactly representable as a floating-point number.

EXAMPLES:

```
sage: RIF(pi).fp_rank_diameter()
1
sage: RIF(12345).fp_rank_diameter()
0
sage: RIF(-sqrt(2)).fp_rank_diameter()
1
sage: RIF(5/8).fp_rank_diameter()
0
sage: RIF(5/7).fp_rank_diameter()
1
sage: a = RIF(pi)^12345; a
2.06622879260?e6137
sage: a.fp_rank_diameter()
30524
sage: (RIF(sqrt(2)) - RIF(sqrt(2))).fp_rank_diameter()
9671406088542672151117826 # 32-bit
41538374868278620559869609387229186 # 64-bit
```

Just because we have the best possible interval, doesn't mean the interval is actually small:

```

sage: a = RIF(pi)^12345678901234567890; a
[2.0985787164673874e323228496 .. +infinity] # 32-bit
[5.8756537891115869e1388255822130839282 .. +infinity] # 64-bit
sage: a.fp_rank_diameter()
1

```

gamma()

Return the gamma function evaluated on self.

EXAMPLES:

```

sage: RIF(1).gamma()
1
sage: RIF(5).gamma()
24
sage: a = RIF(3,4).gamma(); a
1.7e1
sage: a.lower(), a.upper()
(2.000000000000000, 6.000000000000000)
sage: RIF(-1/2).gamma()
-3.54490770181104?
sage: gamma(-1/2).n(100) in RIF(-1/2).gamma()
True
sage: 0 in (RealField(2000)(-19/3).gamma() - RealIntervalField(1000)(-19/3).gamma())
True
sage: gamma(RIF(100))
9.33262154439442?e155
sage: gamma(RIF(-10000/3))
1.31280781451?e-10297

```

Verify the result contains the local minima:

```

sage: 0.88560319441088 in RIF(1, 2).gamma()
True
sage: 0.88560319441088 in RIF(0.25, 4).gamma()
True
sage: 0.88560319441088 in RIF(1.4616, 1.46164).gamma()
True

sage: (-0.99).gamma()
-100.436954665809
sage: (-0.01).gamma()
-100.587197964411
sage: RIF(-0.99, -0.01).gamma().upper()
-1.60118039970055

```

Correctly detects poles:

```

sage: gamma(RIF(-3/2, -1/2))
[-infinity .. +infinity]

```

intersection(other)

Return the intersection of two intervals. If the intervals do not overlap, raises a ValueError.

EXAMPLES:

```

sage: RIF(1, 2).intersection(RIF(1.5, 3)).str(style='brackets')
'[1.500000000000000 .. 2.000000000000000]'
sage: RIF(1, 2).intersection(RIF(4/3, 5/3)).str(style='brackets')
'[1.333333333333332 .. 1.666666666666666]'

```

```
sage: RIF(1, 2).intersection(RIF(3, 4))
Traceback (most recent call last):
...
ValueError: intersection of non-overlapping intervals
```

is_NaN()

Check to see if self is Not-a-Number NaN.

EXAMPLES:

```
sage: a = RIF(0) / RIF(0.0, 0.00); a
[.. NaN ..]
sage: a.is_NaN()
True
```

is_exact()

Return whether this real interval is exact (i.e. contains exactly one real value).

EXAMPLES:

```
sage: RIF(3).is_exact()
True
sage: RIF(2*pi).is_exact()
False
```

is_int()

Checks to see whether this interval includes exactly one integer.

OUTPUT:

If this contains exactly one integer, it returns the tuple (True, n), where n is that integer; otherwise, this returns (False, None).

EXAMPLES:

```
sage: a = RIF(0.8, 1.5)
sage: a.is_int()
(True, 1)
sage: a = RIF(1.1, 1.5)
sage: a.is_int()
(False, None)
sage: a = RIF(1, 2)
sage: a.is_int()
(False, None)
sage: a = RIF(-1.1, -0.9)
sage: a.is_int()
(True, -1)
sage: a = RIF(0.1, 1.9)
sage: a.is_int()
(True, 1)
sage: RIF(+infinity, +infinity).is_int()
(False, None)
```

log(base='e')

Return the logarithm of self to the given base.

EXAMPLES:

```
sage: R = RealIntervalField()
sage: r = R(2); r.log()
0.6931471805599453?
```

```
sage: r = R(-2); r.log()
0.6931471805599453? + 3.141592653589794?*I
```

log10()

Return log to the base 10 of self.

EXAMPLES:

```
sage: r = RIF(16.0); r.log10()
1.204119982655925?
sage: r.log() / log(10.0)
1.204119982655925?
```

```
sage: r = RIF(39.9); r.log10()
1.600972895686749?
```

```
sage: r = RIF(0.0)
sage: r.log10()
[-infinity .. -infinity]
```

```
sage: r = RIF(-1.0)
sage: r.log10()
1.364376353841841?*I
```

log2()

Return log to the base 2 of self.

EXAMPLES:

```
sage: r = RIF(16.0)
sage: r.log2()
4
```

```
sage: r = RIF(31.9); r.log2()
4.995484518877507?
```

```
sage: r = RIF(0.0, 2.0)
sage: r.log2()
[-infinity .. 1.0000000000000000]
```

lower(rnd=None)

Return the lower bound of this interval

INPUT:

- **rnd** – (string) the rounding mode
 - ‘RNDN’ – round to nearest
 - ‘RNDD’ – (default) round towards minus infinity
 - ‘RNDZ’ – round towards zero
 - ‘RNDU’ – round towards plus infinity

The rounding mode does not affect the value returned as a floating-point number, but it does control which variety of `RealField` the returned number is in, which affects printing and subsequent operations.

EXAMPLES:

```
sage: R = RealIntervalField(13)
sage: R.pi().lower().str(truncate=False)
'3.1411'
```

```

sage: x = R(1.2, 1.3); x.str(style='brackets')
'[1.1999 .. 1.3001]'
sage: x.lower()
1.19
sage: x.lower('RNDU')
1.20
sage: x.lower('RNDN')
1.20
sage: x.lower('RNDZ')
1.19
sage: x.lower().parent()
Real Field with 13 bits of precision and rounding RNDD
sage: x.lower('RNDU').parent()
Real Field with 13 bits of precision and rounding RNDU
sage: x.lower() == x.lower('RNDU')
True

```

magnitude()

The largest absolute value of the elements of the interval.

EXAMPLES:

```

sage: RIF(-2, 1).magnitude()
2.000000000000000
sage: RIF(-1, 2).magnitude()
2.000000000000000

```

max(*_others)

Return an interval containing the maximum of self and the arguments.

EXAMPLES:

```

sage: RIF(-1, 1).max(0).endpoints()
(0.0000000000000000, 1.0000000000000000)
sage: RIF(-1, 1).max(RIF(2, 3)).endpoints()
(2.0000000000000000, 3.0000000000000000)
sage: RIF(-1, 1).max(RIF(-100, 100)).endpoints()
(-1.0000000000000000, 100.00000000000000)
sage: RIF(-1, 1).max(RIF(-100, 100), RIF(5, 10)).endpoints()
(5.0000000000000000, 100.00000000000000)

```

Note that if the maximum is one of the given elements, that element will be returned.

```

sage: a = RIF(-1, 1)
sage: b = RIF(2, 3)
sage: c = RIF(3, 4)
sage: c.max(a, b) is c
True
sage: b.max(a, c) is c
True
sage: a.max(b, c) is c
True

```

It might also be convenient to call the method as a function:

```

sage: from sage.rings.real_mpfi import RealIntervalFieldElement
sage: RealIntervalFieldElement.max(a, b, c) is c
True
sage: elements = [a, b, c]
sage: RealIntervalFieldElement.max(*elements) is c

```


True

The generic max does not always do the right thing:

```
sage: max(0, RIF(-1, 1))
0
sage: max(RIF(-1, 1), RIF(-100, 100)).endpoints()
(-1.0000000000000000, 1.0000000000000000)
```

See also:

`min()`

TESTS:

```
sage: a.max('x')
Traceback (most recent call last):
...
TypeError: Unable to convert number to real interval.
```

mignitude()

The smallest absolute value of the elements of the interval.

EXAMPLES:

```
sage: RIF(-2, 1).mignitude()
0.0000000000000000
sage: RIF(-2, -1).mignitude()
1.0000000000000000
sage: RIF(3, 4).mignitude()
3.0000000000000000
```

min(*_others)

Return an interval containing the minimum of `self` and the arguments.

EXAMPLES:

```
sage: a = RIF(-1, 1).min(0).endpoints()
sage: a[0] == -1.0 and a[1].abs() == 0.0 # in MPFI, the sign of 0.0 is not specified
True
sage: RIF(-1, 1).min(pi).endpoints()
(-1.0000000000000000, 1.0000000000000000)
sage: RIF(-1, 1).min(RIF(-100, 100)).endpoints()
(-100.00000000000000, 1.0000000000000000)
sage: RIF(-1, 1).min(RIF(-100, 0)).endpoints()
(-100.00000000000000, 0.0000000000000000)
sage: RIF(-1, 1).min(RIF(-100, 2), RIF(-200, -3)).endpoints()
(-200.00000000000000, -3.0000000000000000)
```

Note that if the minimum is one of the given elements, that element will be returned.

```
sage: a = RIF(-1, 1)
sage: b = RIF(2, 3)
sage: c = RIF(3, 4)
sage: c.min(a, b) is a
True
sage: b.min(a, c) is a
True
sage: a.min(b, c) is a
True
```

It might also be convenient to call the method as a function:

```
sage: from sage.rings.real_mpfi import RealIntervalFieldElement
sage: RealIntervalFieldElement.min(a, b, c) is a
True
sage: elements = [a, b, c]
sage: RealIntervalFieldElement.min(*elements) is a
True
```

The generic min does not always do the right thing:

```
sage: min(0, RIF(-1, 1))
0
sage: min(RIF(-1, 1), RIF(-100, 100)).endpoints()
(-1.000000000000000, 1.000000000000000)
```

See also:

```
max()
```

TESTS:

```
sage: a.min('x')
Traceback (most recent call last):
...
TypeError: Unable to convert number to real interval.
```

multiplicative_order()

Return n such that $\text{self}^n == 1$.

Only ± 1 have finite multiplicative order.

EXAMPLES:

```
sage: RIF(1).multiplicative_order()
1
sage: RIF(-1).multiplicative_order()
2
sage: RIF(3).multiplicative_order()
+Infinity
```

overlaps(*other*)

Return True if self and other are intervals with at least one value in common. For intervals a and b, we have $a.\text{overlaps}(b)$ iff not $(a \neq b)$.

EXAMPLES:

```
sage: RIF(0, 1).overlaps(RIF(1, 2))
True
sage: RIF(1, 2).overlaps(RIF(0, 1))
True
sage: RIF(0, 1).overlaps(RIF(2, 3))
False
sage: RIF(2, 3).overlaps(RIF(0, 1))
False
sage: RIF(0, 3).overlaps(RIF(1, 2))
True
sage: RIF(0, 2).overlaps(RIF(1, 3))
True
```

prec()

Returns the precision of self.

EXAMPLES:

```
sage: RIF(2.1).precision()
53
sage: RealIntervalField(200)(2.1).precision()
200
```

precision()

Returns the precision of self.

EXAMPLES:

```
sage: RIF(2.1).precision()
53
sage: RealIntervalField(200)(2.1).precision()
200
```

psi()

Return the digamma function evaluated on self.

INPUT:

None.

OUTPUT:

A `RealIntervalFieldElement`.

This uses the optional `arb` library. You may have to install it via `sage -i arb`.

EXAMPLES:

```
sage: psi_1 = RIF(1).psi() # optional - arb
sage: psi_1 # optional - arb
-0.577215664901533?
sage: psi_1.overlaps(-RIF.euler_constant()) # optional - arb
True
```

real()

Return the real part of self.

(Since self is a real number, this simply returns self.)

EXAMPLES:

```
sage: RIF(1.2465).real() == RIF(1.2465)
True
```

relative_diameter()

The relative diameter of this interval (for $[a..b]$, this is $(b - a)/((a + b)/2)$), rounded upward, as a `RealNumber`.

EXAMPLES:

```
sage: RIF(1, pi).relative_diameter()
1.03418797197910
```

sec()

Return the secant of this number.

EXAMPLES:

```
sage: RealIntervalField(100)(2).sec()
-2.40299796172238098975460040142?
```

sech()

Return the hyperbolic secant of self.

EXAMPLES:

```
sage: RealIntervalField(100)(2).sech()
0.265802228834079692120862739820?
```

simplest_rational (*low_open=False, high_open=False*)

Return the simplest rational in this interval. Given rationals a/b and c/d (both in lowest terms), the former is simpler if $b < d$ or if $b = d$ and $|a| < |c|$.

If optional parameters `low_open` or `high_open` are `True`, then treat this as an open interval on that end.

EXAMPLES:

```
sage: RealIntervalField(10)(pi).simplest_rational()
22/7
sage: RealIntervalField(20)(pi).simplest_rational()
355/113
sage: RIF(0.123, 0.567).simplest_rational()
1/2
sage: RIF(RR(1/3).nextabove(), RR(3/7)).simplest_rational()
2/5
sage: RIF(1234/567).simplest_rational()
1234/567
sage: RIF(-8765/432).simplest_rational()
-8765/432
sage: RIF(-1.234, 0.003).simplest_rational()
0
sage: RIF(RR(1/3)).simplest_rational()
6004799503160661/18014398509481984
sage: RIF(RR(1/3)).simplest_rational(high_open=True)
Traceback (most recent call last):
...
ValueError: simplest_rational() on open, empty interval
sage: RIF(1/3, 1/2).simplest_rational()
1/2
sage: RIF(1/3, 1/2).simplest_rational(high_open=True)
1/3
sage: phi = ((RealIntervalField(500)(5).sqrt() + 1)/2)
sage: phi.simplest_rational() == fibonacci(362)/fibonacci(361)
True
```

sin()

Return the sine of self.

EXAMPLES:

```
sage: R = RealIntervalField(100)
sage: R(2).sin()
0.909297426825681695396019865912?
```

sinh()

Return the hyperbolic sine of self.

EXAMPLES:

```
sage: q = RIF.pi()/12
sage: q.sinh()
0.2648002276022707?
```

sqrt()

Return a square root of `self`. Raises an error if `self` is nonpositive.

If you use `square_root()` then an interval will always be returned (though it will be NaN if `self` is nonpositive).

EXAMPLES:

```
sage: r = RIF(4.0)
sage: r.sqrt()
2
sage: r.sqrt()^2 == r
True

sage: r = RIF(4344)
sage: r.sqrt()
65.90902821313633?
sage: r.sqrt()^2 == r
False
sage: r in r.sqrt()^2
True
sage: r.sqrt()^2 - r
0.?e-11
sage: (r.sqrt()^2 - r).str(style='brackets')
'[-9.0949470177292824e-13 .. 1.8189894035458565e-12]'
```

```
sage: r = RIF(-2.0)
sage: r.sqrt()
Traceback (most recent call last):
...
ValueError: self (=-2) is not >= 0

sage: r = RIF(-2, 2)
sage: r.sqrt()
Traceback (most recent call last):
...
ValueError: self (=0.?e1) is not >= 0
```

square()

Return the square of `self`.

Note: Squaring an interval is different than multiplying it by itself, because the square can never be negative.

EXAMPLES:

```
sage: RIF(1, 2).square().str(style='brackets')
'[1.0000000000000000 .. 4.0000000000000000]'
```

```
sage: RIF(-1, 1).square().str(style='brackets')
'[0.0000000000000000 .. 1.0000000000000000]'
```

```
sage: (RIF(-1, 1) * RIF(-1, 1)).str(style='brackets')
'[-1.0000000000000000 .. 1.0000000000000000]'
```

square_root()

Return a square root of `self`. An interval will always be returned (though it will be NaN if `self` is nonpositive).

EXAMPLES:

```
sage: r = RIF(-2.0)
sage: r.square_root()
[... NaN ...]
sage: r.sqrt()
Traceback (most recent call last):
...
ValueError: self (=-2) is not >= 0
```

str (*base=10, style=None, no_sci=None, e=None, error_digits=None*)

Return a string representation of self.

INPUT:

- *base* – base for output
- *style* – The printing style; either 'brackets' or 'question' (or None, to use the current default).
- *no_sci* – if True do not print using scientific notation; if False print with scientific notation; if None (the default), print how the parent prints.
- *e* – symbol used in scientific notation
- *error_digits* – The number of digits of error to print, in 'question' style.

We support two different styles of printing; 'question' style and 'brackets' style. In question style (the default), we print the “known correct” part of the number, followed by a question mark:

```
sage: RIF(pi).str()
'3.141592653589794?'
sage: RIF(pi, 22/7).str()
'3.142?'
sage: RIF(pi, 22/7).str(style='question')
'3.142?'
```

However, if the interval is precisely equal to some integer that's not too large, we just return that integer:

```
sage: RIF(-42).str()
'-42'
sage: RIF(0).str()
'0'
sage: RIF(12^5).str(base=3)
'110122100000'
```

Very large integers, however, revert to the normal question-style printing:

```
sage: RIF(3^7).str()
'2187'
sage: RIF(3^7 * 2^256).str()
'2.5323729916201052?e80'
```

In brackets style, we print the lower and upper bounds of the interval within brackets:

```
sage: RIF(237/16).str(style='brackets')
'[14.812500000000000 .. 14.812500000000000]'
```

Note that the lower bound is rounded down, and the upper bound is rounded up. So even if the lower and upper bounds are equal, they may print differently. (This is done so that the printed representation of the interval contains all the numbers in the internal binary interval.)

For instance, we find the best 10-bit floating point representation of $1/3$:

```
sage: RR10 = RealField(10)
sage: RR(RR10(1/3))
0.333496093750000
```

And we see that the point interval containing only this floating-point number prints as a wider decimal interval, that does contain the number:

```
sage: RIF10 = RealIntervalField(10)
sage: RIF10(RR10(1/3)).str(style='brackets')
'[0.33349 .. 0.33350]'
```

We always use brackets style for NaN and infinities:

```
sage: RIF(pi, infinity)
[3.1415926535897931 .. +infinity]
sage: RIF(NaN)
[.. NaN ..]
```

Let's take a closer, formal look at the question style. In its full generality, a number printed in the question style looks like:

MANTISSA ?ERROR eEXPONENT

(without the spaces). The “eEXPONENT” part is optional; if it is missing, then the exponent is 0. (If the base is greater than 10, then the exponent separator is “@” instead of “e”.)

The “ERROR” is optional; if it is missing, then the error is 1.

The mantissa is printed in base b , and always contains a decimal point (also known as a radix point, in bases other than 10). (The error and exponent are always printed in base 10.)

We define the “precision” of a floating-point printed representation to be the positional value of the last digit of the mantissa. For instance, in $2.7?e5$, the precision is 10^4 ; in $8.?$, the precision is 10^0 ; and in $9.35?$ the precision is 10^{-2} . This precision will always be 10^k for some k (or, for an arbitrary base b , b^k).

Then the interval is contained in the interval:

$$\text{mantissa} \cdot b^{\text{exponent}} - \text{error} \cdot b^k \dots \text{mantissa} \cdot b^{\text{exponent}} + \text{error} \cdot b^k$$

To control the printing, we can specify a maximum number of error digits. The default is 0, which means that we do not print an error at all (so that the error is always the default, 1).

Now, consider the precisions needed to represent the endpoints (this is the precision that would be produced by `v.lower().str(no_sci=False, truncate=False)`). Our result is no more precise than the less precise endpoint, and is sufficiently imprecise that the error can be represented with the given number of decimal digits. Our result is the most precise possible result, given these restrictions. When there are two possible results of equal precision and with the same error width, then we pick the one which is farther from zero. (For instance, `RIF(0, 123)` with two error digits could print as $61.?62$ or $62.?62$. We prefer the latter because it makes it clear that the interval is known not to be negative.)

EXAMPLES:

```
sage: a = RIF(59/27); a
2.185185185185186?
sage: a.str()
'2.185185185185186?'
sage: a.str(style='brackets')
'[2.1851851851851851 .. 2.1851851851851856]'
```

```
sage: a.str(16)
'2.2f684bda12f69?'
```

```
sage: a.str(no_sci=False)
'2.185185185185186?e0'
sage: pi_appr = RIF(pi, 22/7)
sage: pi_appr.str(style='brackets')
'[3.1415926535897931 .. 3.1428571428571433]'
sage: pi_appr.str()
'3.142?'
sage: pi_appr.str(error_digits=1)
'3.1422?7'
sage: pi_appr.str(error_digits=2)
'3.14223?64'
sage: pi_appr.str(base=36)
'3.6?'
sage: RIF(NaN)
[.. NaN ..]
sage: RIF(pi, infinity)
[3.1415926535897931 .. +infinity]
sage: RIF(-infinity, pi)
[-infinity .. 3.1415926535897936]
sage: RealIntervalField(210)(3).sqrt()
1.732050807568877293527446341505872366942805253810380628055806980?
sage: RealIntervalField(210)(RIF(3).sqrt())
1.732050807568878?
sage: RIF(3).sqrt()
1.732050807568878?
sage: RIF(0, 3^-150)
1.?e-71
```

TESTS:

Check that [trac ticket #13634](#) is fixed:

```
sage: RIF(0.025)
0.025000000000000002?
sage: RIF.scientific_notation(True)
sage: RIF(0.025)
2.5000000000000002?e-2
sage: RIF.scientific_notation(False)
sage: RIF(0.025)
0.025000000000000002?
```

tan()

Return the tangent of self.

EXAMPLES:

```
sage: q = RIF.pi()/3
sage: q.tan()
1.732050807568877?
sage: q = RIF.pi()/6
sage: q.tan()
0.577350269189626?
```

tanh()

Return the hyperbolic tangent of self.

EXAMPLES:

```
sage: q = RIF.pi()/11
sage: q.tanh()
```



```
0.2780794292958503?
```

`union(other)`

Return the union of two intervals, or of an interval and a real number (more precisely, the convex hull).

EXAMPLES:

```
sage: RIF(1, 2).union(RIF(pi, 22/7)).str(style='brackets')
'[1.0000000000000000 .. 3.1428571428571433]'
sage: RIF(1, 2).union(pi).str(style='brackets')
'[1.0000000000000000 .. 3.1415926535897936]'
sage: RIF(1).union(RIF(0, 2)).str(style='brackets')
'[0.0000000000000000 .. 2.0000000000000000]'
sage: RIF(1).union(RIF(-1)).str(style='brackets')
'[-1.0000000000000000 .. 1.0000000000000000]'
```

`unique_ceil()`

Returns the unique ceiling of this interval, if it is well defined, otherwise raises a `ValueError`.

OUTPUT:

- an integer.

EXAMPLES:

```
sage: RIF(pi).unique_ceil()
4
sage: RIF(100*pi).unique_ceil()
315
sage: RIF(100, 200).unique_ceil()
Traceback (most recent call last):
...
ValueError: interval does not have a unique ceil
```

`unique_floor()`

Returns the unique floor of this interval, if it is well defined, otherwise raises a `ValueError`.

OUTPUT:

- an integer.

EXAMPLES:

```
sage: RIF(pi).unique_floor()
3
sage: RIF(100*pi).unique_floor()
314
sage: RIF(100, 200).unique_floor()
Traceback (most recent call last):
...
ValueError: interval does not have a unique floor
```

`unique_integer()`

Return the unique integer in this interval, if there is exactly one, otherwise raises a `ValueError`.

EXAMPLES:

```
sage: RIF(pi).unique_integer()
Traceback (most recent call last):
...
ValueError: interval contains no integer
sage: RIF(pi, pi+1).unique_integer()
```

```
4
sage: RIF(pi, pi+2).unique_integer()
Traceback (most recent call last):
...
ValueError: interval contains more than one integer
sage: RIF(100).unique_integer()
100
```

unique_round()

Returns the unique round (nearest integer) of this interval, if it is well defined, otherwise raises a ValueError.

OUTPUT:

•an integer.

EXAMPLES:

```
sage: RIF(pi).unique_round()
3
sage: RIF(1000*pi).unique_round()
3142
sage: RIF(100, 200).unique_round()
Traceback (most recent call last):
...
ValueError: interval does not have a unique round (nearest integer)
sage: RIF(1.2, 1.7).unique_round()
Traceback (most recent call last):
...
ValueError: interval does not have a unique round (nearest integer)
sage: RIF(0.7, 1.2).unique_round()
1
sage: RIF(-pi).unique_round()
-3
sage: (RIF(4.5).unique_round(), RIF(-4.5).unique_round())
(5, -5)
```

TESTS:

```
sage: RIF(-1/2, -1/3).unique_round()
Traceback (most recent call last):
...
ValueError: interval does not have a unique round (nearest integer)
sage: RIF(-1/2, 1/3).unique_round()
Traceback (most recent call last):
...
ValueError: interval does not have a unique round (nearest integer)
sage: RIF(-1/3, 1/3).unique_round()
0
sage: RIF(-1/2, 0).unique_round()
Traceback (most recent call last):
...
ValueError: interval does not have a unique round (nearest integer)
sage: RIF(1/2).unique_round()
1
sage: RIF(-1/2).unique_round()
-1
```

```
sage: RIF(0).unique_round()
0
```

upper (*rnd=None*)

Return the upper bound of *self*

INPUT:

- *rnd* – (string) the rounding mode
 - ‘RNDN’ – round to nearest
 - ‘RNDD’ – (default) round towards minus infinity
 - ‘RNDZ’ – round towards zero
 - ‘RNDU’ – round towards plus infinity

The rounding mode does not affect the value returned as a floating-point number, but it does control which variety of `RealField` the returned number is in, which affects printing and subsequent operations.

EXAMPLES:

```
sage: R = RealIntervalField(13)
sage: R.pi().upper().str(truncate=False)
'3.1417'

sage: R = RealIntervalField(13)
sage: x = R(1.2, 1.3); x.str(style='brackets')
'[1.1999 .. 1.3001]'
sage: x.upper()
1.31
sage: x.upper('RNDU')
1.31
sage: x.upper('RNDN')
1.30
sage: x.upper('RNDD')
1.30
sage: x.upper('RNDZ')
1.30
sage: x.upper().parent()
Real Field with 13 bits of precision and rounding RNDU
sage: x.upper('RNDD').parent()
Real Field with 13 bits of precision and rounding RNDD
sage: x.upper() == x.upper('RNDD')
True
```

class `sage.rings.real_mpfi.RealIntervalField_class`

Bases: `sage.rings.ring.Field`

Class of the real interval field.

INPUT:

- *prec* – (integer) precision; default = 53 *prec* is the number of bits used to represent the mantissa of a floating-point number. The precision can be any integer between `mpfr_prec_min()` and `mpfr_prec_max()`. In the current implementation, `mpfr_prec_min()` is equal to 2.
- *sci_not* – (default: `False`) whether or not to display using scientific notation

EXAMPLES:

```
sage: RealIntervalField(10)
Real Interval Field with 10 bits of precision
sage: RealIntervalField()
Real Interval Field with 53 bits of precision
sage: RealIntervalField(100000)
Real Interval Field with 100000 bits of precision
```

Note: The default precision is 53, since according to the GMP manual: ‘mpfr should be able to exactly reproduce all computations with double-precision machine floating-point numbers (double type in C), except the default exponent range is much wider and subnormal numbers are not implemented.’

EXAMPLES:

Creation of elements.

First with default precision. First we coerce elements of various types, then we coerce intervals:

```
sage: RIF = RealIntervalField(); RIF
Real Interval Field with 53 bits of precision
sage: RIF(3)
3
sage: RIF(RIF(3))
3
sage: RIF(pi)
3.141592653589794?
sage: RIF(RealField(53)('1.5'))
1.5000000000000000?
sage: RIF(-2/19)
-0.1052631578947369?
sage: RIF(-3939)
-3939
sage: RIF(-3939r)
-3939
sage: RIF('1.5')
1.5000000000000000?
sage: R200 = RealField(200)
sage: RIF(R200.pi())
3.141592653589794?
```

The base must be explicitly specified as a named parameter:

```
sage: RIF('101101', base=2)
45
sage: RIF('+infinity')
[+infinity .. +infinity]
sage: RIF('[1..3]').str(style='brackets')
'[1.0000000000000000 .. 3.0000000000000000]'
```

Next we coerce some 2-tuples, which define intervals:

```
sage: RIF((-1.5, -1.3))
-1.4?
sage: RIF((RDF('-1.5'), RDF('-1.3'))
-1.4?
sage: RIF((1/3, 2/3)).str(style='brackets')
'[0.3333333333333333 .. 0.6666666666666667]'
```

The extra parentheses aren't needed:

```

sage: RIF(1/3, 2/3).str(style='brackets')
'[0.33333333333333331 .. 0.66666666666666675]'
sage: RIF((1, 2)).str(style='brackets')
'[1.0000000000000000 .. 2.0000000000000000]'
sage: RIF((1r, 2r)).str(style='brackets')
'[1.0000000000000000 .. 2.0000000000000000]'
sage: RIF((pi, e)).str(style='brackets')
'[2.7182818284590455 .. 3.1415926535897932]'

```

Values which can be represented as an exact floating-point number (of the precision of this RealIntervalField) result in a precise interval, where the lower bound is equal to the upper bound (even if they print differently). Other values typically result in an interval where the lower and upper bounds are adjacent floating-point numbers.

```

sage: def check(x):
...     return (x, x.lower() == x.upper())
sage: check(RIF(pi))
(3.141592653589794?, False)
sage: check(RIF(RR(pi)))
(3.1415926535897932?, True)
sage: check(RIF(1.5))
(1.5000000000000000?, True)
sage: check(RIF('1.5'))
(1.5000000000000000?, True)
sage: check(RIF(0.1))
(0.10000000000000001?, True)
sage: check(RIF(1/10))
(0.10000000000000000?, False)
sage: check(RIF('0.1'))
(0.10000000000000000?, False)

```

Similarly, when specifying both ends of an interval, the lower end is rounded down and the upper end is rounded up:

```

sage: outward = RIF(1/10, 7/10); outward.str(style='brackets')
'[0.09999999999999991 .. 0.70000000000000007]'
sage: nearest = RIF(RR(1/10), RR(7/10)); nearest.str(style='brackets')
'[0.10000000000000000 .. 0.69999999999999996]'
sage: nearest.lower() - outward.lower()
1.38777878078144e-17
sage: outward.upper() - nearest.upper()
1.11022302462516e-16

```

Some examples with a real interval field of higher precision:

```

sage: R = RealIntervalField(100)
sage: R(3)
3
sage: R(R(3))
3
sage: R(pi)
3.14159265358979323846264338328?
sage: R(-2/19)
-0.1052631578947368421052631578948?
sage: R(e, pi).str(style='brackets')
'[2.7182818284590452353602874713512 .. 3.1415926535897932384626433832825]'

```

TESTS:

```
sage: RIF._lower_field() is RealField(53, rnd='RNDD')
True
sage: RIF._upper_field() is RealField(53, rnd='RNDU')
True
sage: RIF._middle_field() is RR
True
sage: TestSuite(RIF).run()
```

characteristic()

Returns 0, since the field of real numbers has characteristic 0.

EXAMPLES:

```
sage: RealIntervalField(10).characteristic()
0
```

complex_field()

Return complex field of the same precision.

EXAMPLES:

```
sage: RIF.complex_field()
Complex Interval Field with 53 bits of precision
```

construction()

Returns the functorial construction of `self`, namely, completion of the rational numbers with respect to the prime at ∞ , and the note that this is an interval field.

Also preserves other information that makes this field unique (e.g. precision, print mode).

EXAMPLES:

```
sage: R = RealIntervalField(123)
sage: c, S = R.construction(); S
Rational Field
sage: R == c(S)
True
```

euler_constant()

Returns Euler's gamma constant to the precision of this field.

EXAMPLES:

```
sage: RealIntervalField(100).euler_constant()
0.577215664901532860606512090083?
```

gen(i=0)

Return the i -th generator of `self`.

EXAMPLES:

```
sage: RIF.gen(0)
1
sage: RIF.gen(1)
Traceback (most recent call last):
...
IndexError: self has only one generator
```

gens()

Return a list of generators.

EXAMPLE:

```
sage: RIF.gens()  
[1]
```

is_exact()

Returns whether or not this field is exact, which is always False.

EXAMPLES:

```
sage: RIF.is_exact()  
False
```

is_finite()

Return False, since the field of real numbers is not finite.

EXAMPLES:

```
sage: RealIntervalField(10).is_finite()  
False
```

log2()

Returns $\log(2)$ to the precision of this field.

EXAMPLES:

```
sage: R=RealIntervalField(100)  
sage: R.log2()  
0.693147180559945309417232121458?  
sage: R(2).log()  
0.693147180559945309417232121458?
```

name()

Return the name of self.

EXAMPLES:

```
sage: RIF.name()  
'IntervalRealIntervalField53'  
sage: RealIntervalField(200).name()  
'IntervalRealIntervalField200'
```

ngens()

Return the number of generators of self, which is 1.

EXAMPLES:

```
sage: RIF.ngens()  
1
```

pi()

Returns π to the precision of this field.

EXAMPLES:

```
sage: R = RealIntervalField(100)  
sage: R.pi()  
3.14159265358979323846264338328?  
sage: R.pi().sqrt()/2  
0.88622692545275801364908374167?  
sage: R = RealIntervalField(150)  
sage: R.pi().sqrt()/2  
0.886226925452758013649083741670572591398774728?
```

prec()

Return the precision of this field (in bits).

EXAMPLES:

```
sage: RIF.precision()
53
sage: RealIntervalField(200).precision()
200
```

precision()

Return the precision of this field (in bits).

EXAMPLES:

```
sage: RIF.precision()
53
sage: RealIntervalField(200).precision()
200
```

random_element(*args, **kws)

Return a random element of self. Any arguments or keywords are passed onto the random element function in real field.

By default, this is uniformly distributed in $[-1, 1]$.

EXAMPLES:

```
sage: RIF.random_element()
0.15363619378561300?
sage: RIF.random_element()
-0.50298737524751780?
sage: RIF.random_element(-100, 100)
60.958996432224126?
```

Passes extra positional or keyword arguments through:

```
sage: RIF.random_element(min=0, max=100)
2.5572702830891970?
sage: RIF.random_element(min=-100, max=0)
-1.5803457307118123?
```

scientific_notation(status=None)

Set or return the scientific notation printing flag.

If this flag is True then real numbers with this space as parent print using scientific notation.

INPUT:

- status – boolean optional flag

EXAMPLES:

```
sage: RIF(0.025)
0.025000000000000002?
sage: RIF.scientific_notation(True)
sage: RIF(0.025)
2.5000000000000002?e-2
sage: RIF.scientific_notation(False)
sage: RIF(0.025)
0.025000000000000002?
```


to_prec (*prec*)

Returns a real interval field to the given precision.

EXAMPLES:

```
sage: RIF.to_prec(200)
Real Interval Field with 200 bits of precision
sage: RIF.to_prec(20)
Real Interval Field with 20 bits of precision
sage: RIF.to_prec(53) is RIF
True
```

zeta (*n=2*)

Return an n -th root of unity in the real field, if one exists, or raise a `ValueError` otherwise.

EXAMPLES:

```
sage: R = RealIntervalField()
sage: R.zeta()
-1
sage: R.zeta(1)
1
sage: R.zeta(5)
Traceback (most recent call last):
...
ValueError: No 5th root of unity in self
```

`sage.rings.real_mpfi.is_RealIntervalField(x)`

Check if x is a `RealIntervalField_class`.

EXAMPLES:

```
sage: sage.rings.real_mpfi.is_RealIntervalField(RIF)
True
sage: sage.rings.real_mpfi.is_RealIntervalField(RealIntervalField(200))
True
```

`sage.rings.real_mpfi.is_RealIntervalFieldElement(x)`

Check if x is a `RealIntervalFieldElement`.

EXAMPLES:

```
sage: sage.rings.real_mpfi.is_RealIntervalFieldElement(RIF(2.2))
True
sage: sage.rings.real_mpfi.is_RealIntervalFieldElement(RealIntervalField(200)(2.2))
True
```


FIELD OF ARBITRARY PRECISION REAL NUMBER INTERVALS

```
sage.rings.real_interval_field.is_RealIntervalField(x)  
Check if x is a RealIntervalField_class.
```

EXAMPLES:

```
sage: from sage.rings.real_interval_field import is_RealIntervalField as is_RIF  
sage: is_RIF(RIF)  
True
```

```
sage.rings.real_interval_field.is_RealIntervalFieldElement(x)  
Check if x is a RealIntervalFieldElement.
```

EXAMPLES:

```
sage: from sage.rings.real_interval_field import is_RealIntervalFieldElement as is_RIFE  
sage: is_RIFE(RIF(2.5))  
True
```


FILE: SAGE/RINGS/REAL_INTERVAL_ABSOLUTE.PYX (STARTING AT LINE 1)

```
class sage.rings.real_interval_absolute.Factory
    Bases: sage.structure.factory.UniqueFactory
```

INPUT:

- `name` – string. A name in the global namespace referring to self or a fully qualified path name to self, which is used to locate the factory on unpickling.

EXAMPLES:

```
sage: from sage.structure.factory import UniqueFactory
sage: fake_factory = UniqueFactory('ZZ')
sage: loads(dumps(fake_factory))
Integer Ring
sage: fake_factory = UniqueFactory('sage.rings.all.QQ')
sage: loads(dumps(fake_factory))
Rational Field
```

create_key (*prec*)

The only piece of data is the precision.

TESTS:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: RealIntervalAbsoluteField.create_key(1000)
1000
```

create_object (*version*, *prec*)

Ensures uniqueness.

TESTS:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: RealIntervalAbsoluteField(23) is RealIntervalAbsoluteField(23) # indirect doctest
True
```

```
class sage.rings.real_interval_absolute.MpfrOp
    Bases: object
```

This class is used to endow absolute real interval field elements with all the methods of (relative) real interval field elements.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(100)
```

```
sage: R(1).sin()
0.841470984807896506652502321631?
```

class sage.rings.real_interval_absolute.**RealIntervalAbsoluteElement**
Bases: sage.structure.element.FieldElement

Create a `RealIntervalAbsoluteElement`.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(50)
sage: R(1)
1
sage: R(1/3)
0.33333333333333334?
sage: R(1.3)
1.3000000000000000?
sage: R(pi)
3.141592653589794?
sage: R((11, 12))
12.?
sage: R((11, 11.00001))
11.00001?

sage: R100 = RealIntervalAbsoluteField(100)
sage: R(R100((5, 6)))
6.?
sage: R100(R((5, 6)))
6.?
```

abs()

Return the absolute value of self.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(100)
sage: R(1/3).abs()
0.3333333333333333333333333333333333333333333333333333333333333333334?
sage: R(-1/3).abs()
0.3333333333333333333333333333333333333333333333333333333333333333334?
sage: R((-1/3, 1/2)).abs()
1.?
sage: R((-1/3, 1/2)).abs().endpoints()
(0, 1/2)
sage: R((-3/2, 1/2)).abs().endpoints()
(0, 3/2)
```

absolute_diameter()

Return the diameter self.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10)
sage: R(1/4).absolute_diameter()
0
sage: a = R(pi)
sage: a.absolute_diameter()
1/1024
```

```
sage: a.upper() - a.lower()
1/1024
```

contains_zero()

Return whether `self` contains zero.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10)
sage: R(10).contains_zero()
False
sage: R((10, 11)).contains_zero()
False
sage: R((0, 11)).contains_zero()
True
sage: R((-10, 11)).contains_zero()
True
sage: R((-10, -1)).contains_zero()
False
sage: R((-10, 0)).contains_zero()
True
sage: R(pi).contains_zero()
False
```

diameter()

Return the diameter `self`.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10)
sage: R(1/4).absolute_diameter()
0
sage: a = R(pi)
sage: a.absolute_diameter()
1/1024
sage: a.upper() - a.lower()
1/1024
```

endpoints()

Return the left and right endpoints of `self`, as a tuple.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10)
sage: R(1/4).endpoints()
(1/4, 1/4)
sage: R((1, 2)).endpoints()
(1, 2)
```

is_negative()

Return whether `self` is definitely negative.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(100)
sage: R(10).is_negative()
False
```

```
sage: R((10,11)).is_negative()
False
sage: R((0,11)).is_negative()
False
sage: R((-10,11)).is_negative()
False
sage: R((-10,-1)).is_negative()
True
sage: R(pi).is_negative()
False
```

is_positive()

Return whether `self` is definitely positive.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10)
sage: R(10).is_positive()
True
sage: R((10,11)).is_positive()
True
sage: R((0,11)).is_positive()
False
sage: R((-10,11)).is_positive()
False
sage: R((-10,-1)).is_positive()
False
sage: R(pi).is_positive()
True
```

lower()

Return the lower bound of `self`.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(50)
sage: R(1/4).lower()
1/4
```

midpoint()

Return the midpoint of `self`.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(100)
sage: R(1/4).midpoint()
1/4
sage: R(pi).midpoint()
7964883625991394727376702227905/2535301200456458802993406410752
sage: R(pi).midpoint().n()
3.14159265358979
```

mpfi_prec()

Return the precision needed to represent this value as an mpfi interval.

EXAMPLES:


```

sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10)
sage: R(10).mpfi_prec()
14
sage: R(1000).mpfi_prec()
20

```

sqrt()

Return the square root of self.

EXAMPLES:

```

sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(100)
sage: R(2).sqrt()
1.414213562373095048801688724210?
sage: R((4, 9)).sqrt().endpoints()
(2, 3)

```

upper()

Return the upper bound of self.

EXAMPLES:

```

sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(50)
sage: R(1/4).upper()
1/4

```

`sage.rings.real_interval_absolute.RealIntervalAbsoluteField(*args, **kws)`

This field is similar to the `RealIntervalField` except instead of truncating everything to a fixed relative precision, it maintains a fixed absolute precision.

Note that unlike the standard real interval field, elements in this field can have different size and experience coefficient blowup. On the other hand, it avoids precision loss on addition and subtraction. This is useful for, e.g., series computations for special functions.

EXAMPLES:

```

sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10); R
Real Interval Field with absolute precision 2^-10
sage: R(3/10)
0.300?
sage: R(1000003/10)
100000.300?
sage: R(1e100) + R(1) - R(1e100)
1

```

class `sage.rings.real_interval_absolute.RealIntervalAbsoluteField_class`

Bases: `sage.rings.ring.Field`

This field is similar to the `RealIntervalField` except instead of truncating everything to a fixed relative precision, it maintains a fixed absolute precision.

Note that unlike the standard real interval field, elements in this field can have different size and experience coefficient blowup. On the other hand, it avoids precision loss on addition and subtraction. This is useful for, e.g., series computations for special functions.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(10); R
Real Interval Field with absolute precision 2^-10
sage: R(3/10)
0.300?
sage: R(1000003/10)
100000.300?
sage: R(1e100) + R(1) - R(1e100)
1
```

absprec()

Returns the absolute precision of self.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import RealIntervalAbsoluteField
sage: R = RealIntervalAbsoluteField(100)
sage: R.absprec()
100
sage: RealIntervalAbsoluteField(5).absprec()
5
```

`sage.rings.real_interval_absolute.shift_ceil(x, shift)`

Return $x/2^s$ where s is the value of `shift`, rounded towards $+\infty$. For internal use.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import shift_ceil
sage: shift_ceil(15, 2)
4
sage: shift_ceil(-15, 2)
-3
sage: shift_ceil(32, 2)
8
sage: shift_ceil(-32, 2)
-8
```

`sage.rings.real_interval_absolute.shift_floor(x, shift)`

Return $x/2^s$ where s is the value of `shift`, rounded towards $-\infty$. For internal use.

EXAMPLES:

```
sage: from sage.rings.real_interval_absolute import shift_floor
sage: shift_floor(15, 2)
3
sage: shift_floor(-15, 2)
-4
```

but simply sits between exact rings of characteristic 0 and the real numbers. The values are actually computed when they are cast into a field of fixed precision.

`sage.rings.real_lazy.ComplexLazyField()`
Returns the lazy complex field.

There is only one lazy complex field:

```
class sage.rings.real_lazy.ComplexLazyField_class
  Bases: sage.rings.real_lazy.LazyField
```

For more information, see the documentation of the [RLF](#).

[illegible]

```
sage: TestSuite(CLF).run(skip=["_test_prod"])
```

is due to (acceptable?) numerical noise:


```

0.6234898018587335? + 0.7818314824680299?*I
sage: ComplexField(150)(a) # indirect doctest
0.6234898018587335052500488400423981063227473 + 0.78183148246802980870844452667405775023233
sage: a = LazyAlgebraic(CLF, QQ['x'].0^2-7, -2.0)
sage: RR(a)
-2.64575131106459
sage: RR(a)^2
7.000000000000000

```

class `sage.rings.real_lazy.LazyBinop`
 Bases: `sage.rings.real_lazy.LazyFieldElement`

A lazy element representing a binary (usually arithmetic) operation between two other lazy elements.

EXAMPLES:

```

sage: from sage.rings.real_lazy import LazyBinop
sage: a = LazyBinop(RLF, 2, 1/3, operator.add)
sage: a
2.3333333333333334?
sage: Reals(200)(a)
2.333333333333333333333333333333333333333333333333333333333333333333

```

depth()

Return the depth of `self` as an arithmetic expression.

This is the maximum number of dependent intermediate expressions when evaluating `self`, and is used to determine the precision needed to get the final result to the desired number of bits.

It is equal to the maximum of the right and left depths, plus one.

EXAMPLES:

```

sage: from sage.rings.real_lazy import LazyBinop
sage: a = LazyBinop(RLF, 6, 8, operator.mul)
sage: a.depth()
1
sage: b = LazyBinop(RLF, 2, a, operator.sub)
sage: b.depth()
2

```

eval(R)

Convert the operands to elements of `R`, then perform the operation on them.

EXAMPLES:

```

sage: from sage.rings.real_lazy import LazyBinop
sage: a = LazyBinop(RLF, 6, 8, operator.add)
sage: a.eval(RR)
14.000000000000000

```

A bit absurd:

```

sage: a.eval(str)
'68'

```

class `sage.rings.real_lazy.LazyConstant`
 Bases: `sage.rings.real_lazy.LazyFieldElement`

This class represents a real or complex constant (such as `pi` or `I`).

TESTS:

```

sage: a = RLF.pi(); a
3.141592653589794?
sage: RealField(300)(a)
3.14159265358979323846264338327950288419716939937510582097494459230781640628620899862803482

sage: from sage.rings.real_lazy import LazyConstant
sage: a = LazyConstant(RLF, 'euler_constant')
sage: RealField(200)(a)
0.57721566490153286060651209008240243104215933593992359880577

```

eval(*R*)

Convert *self* into an element of *R*.

EXAMPLES:

```

sage: from sage.rings.real_lazy import LazyConstant
sage: a = LazyConstant(RLF, 'e')
sage: RDF(a) # indirect doctest
2.718281828459045
sage: a = LazyConstant(CLF, 'I')
sage: CC(a)
1.000000000000000*I

```

class sage.rings.real_lazy.**LazyField**

Bases: sage.rings.ring.Field

The base class for lazy real fields.

Warning: LazyField uses `__getattr__()`, to implement:

```

sage: CLF.pi
3.141592653589794?

```

I (NT, 20/04/2012) did not manage to have `__getattr__` call `Parent.__getattr__()` in case of failure; hence we can't use this `__getattr__` trick for extension types to recover the methods from categories. Therefore, at this point, no concrete subclass of this class should be an extension type (which is probably just fine):

```

sage: RLF.__class__
<class 'sage.rings.real_lazy.RealLazyField_class_with_category'>
sage: CLF.__class__
<class 'sage.rings.real_lazy.ComplexLazyField_class_with_category'>

```

algebraic_closure()

Returns the algebraic closure of *self*, i.e., the complex lazy field.

EXAMPLES:

```

sage: RLF.algebraic_closure()
Complex Lazy Field

sage: CLF.algebraic_closure()
Complex Lazy Field

```

interval_field(*prec=None*)

Abstract method to create the corresponding interval field.

TESTS:

```
sage: RLF.interval_field() # indirect doctest
Real Interval Field with 53 bits of precision
```

```
class sage.rings.real_lazy.LazyFieldElement
Bases: sage.structure.element.FieldElement
```

INPUT:

- parent - a SageObject

approx()

Returns self as an element of an interval field.

EXAMPLES:

```
sage: CLF(1/6).approx()
0.16666666666666667?
sage: CLF(1/6).approx().parent()
Complex Interval Field with 53 bits of precision
```

When the absolute value is involved, the result might be real:

```
sage: z = exp(CLF(1 + I/2)); z
2.38551673095914? + 1.303213729686996?*I
sage: r = z.abs(); r
2.71828182845905?
sage: parent(z.approx())
Complex Interval Field with 53 bits of precision
sage: parent(r.approx())
Real Interval Field with 53 bits of precision
```

depth()

Abstract method for returning the depth of self as an arithmetic expression.

This is the maximum number of dependent intermediate expressions when evaluating self, and is used to determine the precision needed to get the final result to the desired number of bits.

It is equal to the maximum of the right and left depths, plus one.

EXAMPLES:

```
sage: from sage.rings.real_lazy import LazyBinop
sage: a = LazyBinop(RLF, 6, 8, operator.mul)
sage: a.depth()
1
```

eval(R)

Abstract method for converting self into an element of R.

EXAMPLES:

```
sage: a = RLF(12)
sage: a.eval(ZZ)
12
```

```
class sage.rings.real_lazy.LazyNamedUnop
Bases: sage.rings.real_lazy.LazyUnop
```

This class is used to represent the many named methods attached to real numbers, and is instantiated by the `__getattr__` method of `LazyElements`.

EXAMPLES:

```
sage: from sage.rings.real_lazy import LazyNamedUnop
sage: a = LazyNamedUnop(RLF, 1, 'arcsin')
sage: RR(a)
1.57079632679490
sage: a = LazyNamedUnop(RLF, 9, 'log', extra_args=(3,))
sage: RR(a)
2.000000000000000
```

approx ()

Does something reasonable with functions that are not defined on the interval fields.

TESTS:

```
sage: from sage.rings.real_lazy import LazyNamedUnop
sage: LazyNamedUnop(RLF, 8, 'sqrt') # indirect doctest
2.828427124746190?
```

$$\mathbf{eval}(R)$$

Convert `self` into an element of R .

TESTS:

[illegible]

Now for some extra arguments:

```
sage: a = RLF(100)
sage: a.log(10)
2
sage: float(a.log(10))
2.0
```

```
class sage.rings.real_lazy.LazyUnop
```

Bases: sage.rings.real_lazy.LazyFieldElement

Represents a unevaluated single function of one variable.

EXAMPLES:

```
sage: from sage.rings.real_lazy import LazyUnop
sage: a = LazyUnop(RLF, 3, sqrt); a
1.732050807568878?
sage: a._arg
3
sage: a._op
<function sqrt at ...>
sage: Reals(100)(a)
1.7320508075688772935274463415
sage: Reals(100)(a)^2
3.000000000000000000000000000000
```

depth ()

Return the depth of `self` as an arithmetic expression.

This is the maximum number of dependent intermediate expressions when evaluating `self`, and is used to determine the precision needed to get the final result to the desired number of bits.

It is equal to one more than the depth of its operand.

EXAMPLES:

```
sage: from sage.rings.real_lazy import LazyUnop
sage: a = LazyUnop(RLF, 3, sqrt)
sage: a.depth()
1
sage: b = LazyUnop(RLF, a, sin)
sage: b.depth()
2
```

eval(*R*)

Convert `self` into an element of *R*.

EXAMPLES:

```
sage: from sage.rings.real_lazy import LazyUnop
sage: a = LazyUnop(RLF, 3, sqrt)
sage: a.eval(ZZ)
sqrt(3)
```

class `sage.rings.real_lazy.LazyWrapper`

Bases: `sage.rings.real_lazy.LazyFieldElement`

A lazy element that simply wraps an element of another ring.

EXAMPLES:

```
sage: from sage.rings.real_lazy import LazyWrapper
sage: a = LazyWrapper(RLF, 3)
sage: a._value
3
```

depth()

Returns the depth of `self` as an expression, which is always 0.

EXAMPLES:

```
sage: RLF(4).depth()
0
```

eval(*R*)

Convert `self` into an element of *R*.

EXAMPLES:

```
sage: a = RLF(12)
sage: a.eval(ZZ)
12
sage: a.eval(ZZ).parent()
Integer Ring
```

class `sage.rings.real_lazy.LazyWrapperMorphism`

Bases: `sage.categories.morphism.Morphism`

This morphism coerces elements from anywhere into lazy rings by creating a wrapper element (as fast as possible).

gen (*i=0*)

Return the *i*-th generator of `self`.

EXAMPLES:

```
sage: RLF.gen()  
1
```

interval_field (*prec=None*)

Returns the interval field that represents the same mathematical field as `self`.

EXAMPLES:

```
sage: RLF.interval_field()  
Real Interval Field with 53 bits of precision  
sage: RLF.interval_field(200)  
Real Interval Field with 200 bits of precision
```

`sage.rings.real_lazy`.**make_element** (*parent, *args*)

Create an element of `parent`.

EXAMPLES:

```
sage: a = RLF(pi) + RLF(sqrt(1/2)) # indirect doctest  
sage: loads(dumps(a)) == a  
True
```


DOUBLE PRECISION COMPLEX NUMBERS

Sage supports arithmetic using double-precision complex numbers. A double-precision complex number is a complex number $x + I*y$ with x, y 64-bit (8 byte) floating point numbers (double precision).

The field `ComplexDoubleField` implements the field of all double-precision complex numbers. You can refer to this field by the shorthand `CDF`. Elements of this field are of type `ComplexDoubleElement`. If x and y are coercible to doubles, you can create a complex double element using `ComplexDoubleElement(x, y)`. You can coerce more general objects z to complex doubles by typing either `ComplexDoubleField(x)` or `CDF(x)`.

EXAMPLES:

```
sage: ComplexDoubleField()
Complex Double Field
sage: CDF
Complex Double Field
sage: type(CDF.0)
<type 'sage.rings.complex_double.ComplexDoubleElement'>
sage: ComplexDoubleElement(sqrt(2), 3)
1.4142135623730951 + 3.0*I
sage: parent(CDF(-2))
Complex Double Field

sage: CC == CDF
False
sage: CDF is ComplexDoubleField()      # CDF is the shorthand
True
sage: CDF == ComplexDoubleField()
True
```

The underlying arithmetic of complex numbers is implemented using functions and macros in GSL (the GNU Scientific Library), and should be very fast. Also, all standard complex trig functions, log, exponents, etc., are implemented using GSL, and are also robust and fast. Several other special functions, e.g. eta, gamma, incomplete gamma, etc., are implemented using the PARI C library.

AUTHORS:

- William Stein (2006-09): first version
- Travis Scrimshaw (2012-10-18): Added doctests to get full coverage
- Jeroen Demeyer (2013-02-27): fixed all PARI calls ([trac ticket #14082](#))

```
class sage.rings.complex_double.ComplexDoubleElement
    Bases: sage.structure.element.FieldElement
```

An approximation to a complex number using double precision floating point numbers. Answers derived from calculations with such approximations may differ from what they would be if those calculations were performed

with true complex numbers. This is due to the rounding errors inherent to finite precision calculations.

abs()

This function returns the magnitude $|z|$ of the complex number z .

See also:

- `norm()`

EXAMPLES:

```
sage: CDF(2, 3).abs()
3.605551275463989
```

abs2()

This function returns the squared magnitude $|z|^2$ of the complex number z , otherwise known as the complex norm.

See also:

- `norm()`

EXAMPLES:

```
sage: CDF(2, 3).abs2()
13.0
```

agm(right, algorithm='optimal')

Return the Arithmetic-Geometric Mean (AGM) of `self` and `right`.

INPUT:

- `right` (complex) – another complex number
- `algorithm` (string, default "optimal") – the algorithm to use (see below).

OUTPUT:

(complex) A value of the AGM of `self` and `right`. Note that this is a multi-valued function, and the algorithm used affects the value returned, as follows:

- `'pari'`: Call the `agm` function from the `pari` library.
- `'optimal'`: Use the AGM sequence such that at each stage (a, b) is replaced by $(a_1, b_1) = ((a + b)/2, \pm\sqrt{ab})$ where the sign is chosen so that $|a_1 - b_1| \leq |a_1 + b_1|$, or equivalently $\Re(b_1/a_1) \geq 0$. The resulting limit is maximal among all possible values.
- `'principal'`: Use the AGM sequence such that at each stage (a, b) is replaced by $(a_1, b_1) = ((a + b)/2, \pm\sqrt{ab})$ where the sign is chosen so that $\Re(b_1/a_1) \geq 0$ (the so-called principal branch of the square root).

EXAMPLES:

```
sage: i = CDF(I)
sage: (1+i).agm(2-i) # rel tol 1e-15
1.6278054848727064 + 0.1368275483973686*I
```

An example to show that the returned value depends on the algorithm parameter:

```
sage: a = CDF(-0.95, -0.65)
sage: b = CDF(0.683, 0.747)
sage: a.agm(b, algorithm='optimal')
-0.3715916523517613 + 0.31989466020683*I
```

```

sage: a.agm(b, algorithm='principal') # rel tol 1e-15
0.33817546298618006 - 0.013532696956540503*I
sage: a.agm(b, algorithm='pari')
-0.37159165235176134 + 0.31989466020683005*I

```

Some degenerate cases:

```

sage: CDF(0).agm(a)
0.0
sage: a.agm(0)
0.0
sage: a.agm(-a)
0.0

```

algdep(*n*)

Returns a polynomial of degree at most n which is approximately satisfied by this complex number. Note that the returned polynomial need not be irreducible, and indeed usually won't be if z is a good approximation to an algebraic number of degree less than n .

ALGORITHM: Uses the PARI C-library algdep command.

EXAMPLES:

```

sage: z = (1/2)*(1 + RDF(sqrt(3)) *CDF(0)); z
0.5 + 0.8660254037844387*I
sage: p = z.algdep(5); p
x^3 + 1
sage: p.factor()
(x + 1) * (x^2 - x + 1)
sage: abs(z^2 - z + 1) < 1e-14
True

sage: CDF(0,2).algdep(10)
x^2 + 4
sage: CDF(1,5).algdep(2)
x^2 - 2*x + 26

```

arccos(*z*)

This function returns the complex arccosine of the complex number z , $\arccos(z)$. The branch cuts are on the real axis, less than -1 and greater than 1.

EXAMPLES:

```

sage: CDF(1,1).arccos()
0.9045568943023814 - 1.0612750619050357*I

```

arccosh(*z*)

This function returns the complex hyperbolic arccosine of the complex number z , $\arccosh(z)$. The branch cut is on the real axis, less than 1.

EXAMPLES:

```

sage: CDF(1,1).arccosh()
1.0612750619050357 + 0.9045568943023814*I

```

arccot(*z*)

This function returns the complex arccotangent of the complex number z , $\arccot(z) = \arctan(1/z)$.

EXAMPLES:

```
sage: CDF(1,1).arccot() # rel tol 1e-15
0.5535743588970452 - 0.4023594781085251*I
```

arccoth()

This function returns the complex hyperbolic arccotangent of the complex number z , $\operatorname{arccoth}(z) = \operatorname{arctanh}(1/z)$.

EXAMPLES:

```
sage: CDF(1,1).arccoth() # rel tol 1e-15
0.4023594781085251 - 0.5535743588970452*I
```

arccsc()

This function returns the complex arccosecant of the complex number z , $\operatorname{arccsc}(z) = \arcsin(1/z)$.

EXAMPLES:

```
sage: CDF(1,1).arccsc() # rel tol 1e-15
0.45227844715119064 - 0.5306375309525178*I
```

arccsch()

This function returns the complex hyperbolic arccosecant of the complex number z , $\operatorname{arccsch}(z) = \arcsin(1/z)$.

EXAMPLES:

```
sage: CDF(1,1).arccsch() # rel tol 1e-15
0.5306375309525178 - 0.45227844715119064*I
```

arcsec()

This function returns the complex arcsecant of the complex number z , $\operatorname{arcsec}(z) = \arccos(1/z)$.

EXAMPLES:

```
sage: CDF(1,1).arcsec() # rel tol 1e-15
1.118517879643706 + 0.5306375309525178*I
```

arcsech()

This function returns the complex hyperbolic arcsecant of the complex number z , $\operatorname{arcsech}(z) = \operatorname{arccosh}(1/z)$.

EXAMPLES:

```
sage: CDF(1,1).arcsech() # rel tol 1e-15
0.5306375309525176 - 1.118517879643706*I
```

arcsin()

This function returns the complex arcsine of the complex number z , $\operatorname{arcsin}(z)$. The branch cuts are on the real axis, less than -1 and greater than 1.

EXAMPLES:

```
sage: CDF(1,1).arcsin()
0.6662394324925152 + 1.0612750619050357*I
```

arcsinh()

This function returns the complex hyperbolic arcsine of the complex number z , $\operatorname{arcsinh}(z)$. The branch cuts are on the imaginary axis, below $-i$ and above i .

EXAMPLES:


```
sage: CDF(1,1).arcsinh()
1.0612750619050357 + 0.6662394324925152*I
```

arctan()

This function returns the complex arctangent of the complex number z , $\arctan(z)$. The branch cuts are on the imaginary axis, below $-i$ and above i .

EXAMPLES:

```
sage: CDF(1,1).arctan()
1.0172219678978514 + 0.4023594781085251*I
```

arctanh()

This function returns the complex hyperbolic arctangent of the complex number z , $\operatorname{arctanh}(z)$. The branch cuts are on the real axis, less than -1 and greater than 1 .

EXAMPLES:

```
sage: CDF(1,1).arctanh()
0.4023594781085251 + 1.0172219678978514*I
```

arg()

This function returns the argument of `self`, the complex number z , denoted by $\arg(z)$, where $-\pi < \arg(z) \leq \pi$.

EXAMPLES:

```
sage: CDF(1,0).arg()
0.0
sage: CDF(0,1).arg()
1.5707963267948966
sage: CDF(0,-1).arg()
-1.5707963267948966
sage: CDF(-1,0).arg()
3.141592653589793
```

argument()

This function returns the argument of the `self`, the complex number z , in the interval $-\pi < \arg(z) \leq \pi$.

EXAMPLES:

```
sage: CDF(6).argument()
0.0
sage: CDF(i).argument()
1.5707963267948966
sage: CDF(-1).argument()
3.141592653589793
sage: CDF(-1 - 0.000001*i).argument()
-3.1415916535897934
```

conj()

This function returns the complex conjugate of the complex number z :

$$\bar{z} = x - iy.$$

EXAMPLES:

```
sage: z = CDF(2,3); z.conj()
2.0 - 3.0*I
```

conjugate()

This function returns the complex conjugate of the complex number z :

$$\bar{z} = x - iy.$$

EXAMPLES:

```
sage: z = CDF(2,3); z.conjugate()
2.0 - 3.0*I
```

cos()

This function returns the complex cosine of the complex number z :

$$\cos(z) = \frac{e^{iz} + e^{-iz}}{2}$$

EXAMPLES:

```
sage: CDF(1,1).cos()
0.8337300251311491 - 0.9888977057628651*I
```

cosh()

This function returns the complex hyperbolic cosine of the complex number z :

$$\cosh(z) = \frac{e^z + e^{-z}}{2}.$$

EXAMPLES:

```
sage: CDF(1,1).cosh()
0.8337300251311491 + 0.9888977057628651*I
```

cot()

This function returns the complex cotangent of the complex number z :

$$\cot(z) = \frac{1}{\tan(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).cot() # rel tol 1e-15
0.21762156185440268 - 0.8680141428959249*I
```

coth()

This function returns the complex hyperbolic cotangent of the complex number z :

$$\coth(z) = \frac{1}{\tanh(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).coth() # rel tol 1e-15
0.8680141428959249 - 0.21762156185440268*I
```

csc()

This function returns the complex cosecant of the complex number z :

$$\csc(z) = \frac{1}{\sin(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).csc() # rel tol 1e-15
0.6215180171704284 - 0.30393100162842646*I
```

csch()

This function returns the complex hyperbolic cosecant of the complex number z :

$$\operatorname{csch}(z) = \frac{1}{\sinh(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).csch() # rel tol 1e-15
0.30393100162842646 - 0.6215180171704284*I
```

dilog()

Returns the principal branch of the dilogarithm of x , i.e., analytic continuation of the power series

$$\log_2(x) = \sum_{n \geq 1} x^n / n^2.$$

EXAMPLES:

```
sage: CDF(1,2).dilog()
-0.059474798673809476 + 2.0726479717747566*I
sage: CDF(10000000,10000000).dilog()
-134.411774490731 + 38.79396299904504*I
```

eta(omit_frac=0)

Return the value of the Dedekind η function on self.

INPUT:

- `self` - element of the upper half plane (if not, raises a `ValueError`).
- `omit_frac` - (bool, default: `False`), if `True`, omit the $e^{\pi iz/12}$ factor.

OUTPUT: a complex double number

ALGORITHM: Uses the PARI C library.

The η function is

$$\eta(z) = e^{\pi iz/12} \prod_{n=1}^{\infty} (1 - e^{2\pi inz})$$

EXAMPLES:

We compute a few values of `eta()`:

```
sage: CDF(0,1).eta()
0.7682254223260566
sage: CDF(1,1).eta()
0.7420487758365647 + 0.1988313702299107*I
sage: CDF(25,1).eta()
0.7420487758365647 + 0.1988313702299107*I
```

`eta()` works even if the inputs are large:

```
sage: CDF(0, 10^15).eta()
0.0
sage: CDF(10^15, 0.1).eta() # abs tol 1e-10
-0.115342592727 - 0.19977923088*I
```

We compute a few values of `eta()`, but with the fractional power of e omitted:

```
sage: CDF(0,1).eta(True)
0.9981290699259585
```

We compute `eta()` to low precision directly from the definition:

```
sage: z = CDF(1,1); z.eta()
0.7420487758365647 + 0.1988313702299107*I
sage: i = CDF(0,1); pi = CDF(pi)
sage: exp(pi * i * z / 12) * prod([1-exp(2*pi*i*n*z) for n in range(1,10)])
0.7420487758365647 + 0.19883137022991068*I
```

The optional argument allows us to omit the fractional part:

```
sage: z.eta(omit_frac=True)
0.9981290699259585
sage: pi = CDF(pi)
sage: prod([1-exp(2*pi*i*n*z) for n in range(1,10)]) # abs tol 1e-12
0.998129069926 + 4.59084695545e-19*I
```

We illustrate what happens when z is not in the upper half plane:

```
sage: z = CDF(1)
sage: z.eta()
Traceback (most recent call last):
...
ValueError: value must be in the upper half plane
```

You can also use functional notation:

```
sage: z = CDF(1,1)
sage: eta(z)
0.7420487758365647 + 0.1988313702299107*I
```

`exp()`

This function returns the complex exponential of the complex number z , $\exp(z)$.

EXAMPLES:

```
sage: CDF(1,1).exp()
1.4686939399158851 + 2.2873552871788423*I
```

We numerically verify a famous identity to the precision of a double:

```
sage: z = CDF(0, 2*pi); z
6.283185307179586*I
sage: exp(z) # rel tol 1e-4
1.0 - 2.4492935982947064e-16*I
```

`gamma()`

Return the gamma function $\Gamma(z)$ evaluated at `self`, the complex number z .

EXAMPLES:

```
sage: CDF(5,0).gamma()
24.0
sage: CDF(1,1).gamma()
0.49801566811835607 - 0.15494982830181067*I
sage: CDF(0).gamma()
Infinity
sage: CDF(-1,0).gamma()
Infinity
```

gamma_inc(t)

Return the incomplete gamma function evaluated at this complex number.

EXAMPLES:

```
sage: CDF(1,1).gamma_inc(CDF(2,3))
0.0020969148636468277 - 0.059981913655449706*I
sage: CDF(1,1).gamma_inc(5)
-0.001378130936215849 + 0.006519820023119819*I
sage: CDF(2,0).gamma_inc(CDF(1,1))
0.7070920963459381 - 0.4203536409598115*I
```

imag()

Return the imaginary part of this complex double.

EXAMPLES:

```
sage: a = CDF(3,-2)
sage: a.imag()
-2.0
sage: a.imag_part()
-2.0
```

imag_part()

Return the imaginary part of this complex double.

EXAMPLES:

```
sage: a = CDF(3,-2)
sage: a.imag()
-2.0
sage: a.imag_part()
-2.0
```

is_infinity()

Check if self is ∞ .

EXAMPLES:

```
sage: CDF(1, 2).is_infinity()
False
sage: CDF(0, oo).is_infinity()
True
```

is_integer()

Returns True if this number is a integer

EXAMPLES:

```
sage: CDF(0.5).is_integer()
False
sage: CDF(1).is_integer()
False
sage: CDF(2).is_integer()
True
```

is_negative_infinity()

Check if self is $-\infty$.

EXAMPLES:

```
sage: CDF(1, 2).is_negative_infinity()
False
sage: CDF(-oo, 0).is_negative_infinity()
True
sage: CDF(0, -oo).is_negative_infinity()
False
```

is_positive_infinity()

Check if self is $+\infty$.

EXAMPLES:

```
sage: CDF(1, 2).is_positive_infinity()
False
sage: CDF(oo, 0).is_positive_infinity()
True
sage: CDF(0, oo).is_positive_infinity()
False
```

is_square()

This function always returns True as \mathbf{C} is algebraically closed.

EXAMPLES:

```
sage: CDF(-1).is_square()
True
```

log (base=None)

This function returns the complex natural logarithm to the given base of the complex number z , $\log(z)$. The branch cut is the negative real axis.

INPUT:

- base - default: e , the base of the natural logarithm

EXAMPLES:

```
sage: CDF(1, 1).log()
0.34657359027997264 + 0.7853981633974483*I
```

This is the only example different from the GSL:

```
sage: CDF(0, 0).log()
-infinity
```

log10()

This function returns the complex base-10 logarithm of the complex number z , $\log_{10}(z)$.

The branch cut is the negative real axis.

EXAMPLES:

```
sage: CDF(1, 1).log10()
0.15051499783199057 + 0.3410940884604603*I
```

log_b(b)

This function returns the complex base- b logarithm of the complex number z , $\log_b(z)$. This quantity is computed as the ratio $\log(z)/\log(b)$.

The branch cut is the negative real axis.

EXAMPLES:

```
sage: CDF(1,1).log_b(10) # rel tol 1e-15
0.15051499783199057 + 0.3410940884604603*I
```

logabs()

This function returns the natural logarithm of the magnitude of the complex number z , $\log |z|$.

This allows for an accurate evaluation of $\log |z|$ when $|z|$ is close to 1. The direct evaluation of $\log(\text{abs}(z))$ would lead to a loss of precision in this case.

EXAMPLES:

```
sage: CDF(1.1,0.1).logabs()
0.09942542937258267
sage: log(abs(CDF(1.1,0.1)))
0.09942542937258259

sage: log(abs(ComplexField(200)(1.1,0.1)))
0.099425429372582595066319157757531449594489450091985182495705
```

norm()

This function returns the squared magnitude $|z|^2$ of the complex number z , otherwise known as the complex norm. If $c = a + bi$ is a complex number, then the norm of c is defined as the product of c and its complex conjugate:

$$\text{norm}(c) = \text{norm}(a + bi) = c \cdot \bar{c} = a^2 + b^2.$$

The norm of a complex number is different from its absolute value. The absolute value of a complex number is defined to be the square root of its norm. A typical use of the complex norm is in the integral domain $\mathbb{Z}[i]$ of Gaussian integers, where the norm of each Gaussian integer $c = a + bi$ is defined as its complex norm.

See also:

- `abs()`
- `abs2()`
- `sage.misc.functional.norm()`
- `sage.rings.complex_number.ComplexNumber.norm()`

EXAMPLES:

```
sage: CDF(2,3).norm()
13.0
```

nth_root(n, all=False)

The n -th root function.

INPUT:

- `all` – bool (default: False); if True, return a list of all n -th roots.

EXAMPLES:

```
sage: a = CDF(125)
sage: a.nth_root(3)
5.000000000000001
sage: a = CDF(10, 2)
sage: [r^5 for r in a.nth_root(5, all=True)] # rel tol 1e-14
[9.999999999999998 + 2.0*I, 9.999999999999993 + 2.000000000000002*I, 9.999999999999996 + 1.999999999999999*I, 9.999999999999998 - 2.0*I, 9.999999999999993 - 2.000000000000002*I]
```

```
sage: abs(sum(a.nth_root(111, all=True))) # rel tol 0.1
1.1057313523818259e-13
```

prec()

Returns the precision of this number (to be more similar to `ComplexNumber`). Always returns 53.

EXAMPLES:

```
sage: CDF(0).prec()
53
```

real()

Return the real part of this complex double.

EXAMPLES:

```
sage: a = CDF(3,-2)
sage: a.real()
3.0
sage: a.real_part()
3.0
```

real_part()

Return the real part of this complex double.

EXAMPLES:

```
sage: a = CDF(3,-2)
sage: a.real()
3.0
sage: a.real_part()
3.0
```

sec()

This function returns the complex secant of the complex number z :

$$\sec(z) = \frac{1}{\cos(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).sec() # rel tol 1e-15
0.4983370305551868 + 0.591083841721045*I
```

sech()

This function returns the complex hyperbolic secant of the complex number z :

$$\operatorname{sech}(z) = \frac{1}{\cosh(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).sech() # rel tol 1e-15
0.4983370305551868 - 0.591083841721045*I
```

sin()

This function returns the complex sine of the complex number z :

$$\sin(z) = \frac{e^{iz} - e^{-iz}}{2i}.$$

EXAMPLES:


```
sage: CDF(1,1).sin()
1.2984575814159773 + 0.6349639147847361*I
```

sinh()

This function returns the complex hyperbolic sine of the complex number z :

$$\sinh(z) = \frac{e^z - e^{-z}}{2}.$$

EXAMPLES:

```
sage: CDF(1,1).sinh()
0.6349639147847361 + 1.2984575814159773*I
```

sqrt (*all=False*, ***kws*)

The square root function.

INPUT:

- *all* - bool (default: False); if True, return a list of all square roots.

If *all* is False, the branch cut is the negative real axis. The result always lies in the right half of the complex plane.

EXAMPLES:

We compute several square roots:

```
sage: a = CDF(2,3)
sage: b = a.sqrt(); b # rel tol 1e-15
1.6741492280355401 + 0.8959774761298381*I
sage: b^2 # rel tol 1e-15
2.0 + 3.0*I
sage: a^(1/2)
1.6741492280355401 + 0.895977476129838*I
```

We compute the square root of -1:

```
sage: a = CDF(-1)
sage: a.sqrt()
1.0*I
```

We compute all square roots:

```
sage: CDF(-2).sqrt(all=True)
[1.4142135623730951*I, -1.4142135623730951*I]
sage: CDF(0).sqrt(all=True)
[0.0]
```

tan()

This function returns the complex tangent of the complex number z :

$$\tan(z) = \frac{\sin(z)}{\cos(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).tan()
0.27175258531951174 + 1.0839233273386946*I
```

tanh()

This function returns the complex hyperbolic tangent of the complex number z :

$$\tanh(z) = \frac{\sinh(z)}{\cosh(z)}.$$

EXAMPLES:

```
sage: CDF(1,1).tanh()
1.0839233273386946 + 0.27175258531951174*I
```

zeta()

Return the Riemann zeta function evaluated at this complex number.

EXAMPLES:

```
sage: z = CDF(1, 1)
sage: z.zeta()
0.5821580597520036 - 0.9268485643308071*I
sage: zeta(z)
0.5821580597520036 - 0.9268485643308071*I
sage: zeta(CDF(1))
Infinity
```

```
sage.rings.complex_double.ComplexDoubleField()
```

Returns the field of double precision complex numbers.

EXAMPLE:

```
sage: ComplexDoubleField()
Complex Double Field
sage: ComplexDoubleField() is CDF
True
```

```
class sage.rings.complex_double.ComplexDoubleField_class
```

Bases: sage.rings.ring.Field

An approximation to the field of complex numbers using double precision floating point numbers. Answers derived from calculations in this approximation may differ from what they would be if those calculations were performed in the true field of complex numbers. This is due to the rounding errors inherent to finite precision calculations.

ALGORITHM:

Arithmetic is done using GSL (the GNU Scientific Library).

algebraic_closure()

Returns the algebraic closure of `self`, i.e., the complex double field.

EXAMPLES:

```
sage: CDF.algebraic_closure()
Complex Double Field
```

characteristic()

Return the characteristic of the complex double field, which is 0.

EXAMPLES:

```
sage: CDF.characteristic()
0
```

construction()

Returns the functorial construction of `self`, namely, algebraic closure of the real double field.

EXAMPLES:

```
sage: c, S = CDF.construction(); S
Real Double Field
sage: CDF == c(S)
True
```

gen($n=0$)

Return the generator of the complex double field.

EXAMPLES:

```
sage: CDF.0
1.0*I
sage: CDF.gen(0)
1.0*I
```

is_exact()

Returns whether or not this field is exact, which is always `False`.

EXAMPLES:

```
sage: CDF.is_exact()
False
```

ngens()

The number of generators of this complex field as an \mathbf{R} -algebra.

There is one generator, namely `sqrt(-1)`.

EXAMPLES:

```
sage: CDF.ngens()
1
```

pi()

Returns π as a double precision complex number.

EXAMPLES:

```
sage: CDF.pi()
3.141592653589793
```

prec()

Return the precision of this complex double field (to be more similar to `ComplexField`). Always returns 53.

EXAMPLES:

```
sage: CDF.prec()
53
```

precision()

Return the precision of this complex double field (to be more similar to `ComplexField`). Always returns 53.

EXAMPLES:

```
sage: CDF.prec()
53
```

random_element (*xmin=-1, xmax=1, ymin=-1, ymax=1*)

Return a random element of this complex double field with real and imaginary part bounded by *xmin*, *xmax*, *ymin*, *ymax*.

EXAMPLES:

```
sage: CDF.random_element()
-0.43681052967509904 + 0.7369454235661859*I
sage: CDF.random_element(-10,10,-10,10)
-7.088740263015161 - 9.54135400334003*I
sage: CDF.random_element(-10^20,10^20,-2,2)
-7.587654737635711e+19 + 0.925549022838656*I
```

real_double_field()

The real double field, which you may view as a subfield of this complex double field.

EXAMPLES:

```
sage: CDF.real_double_field()
Real Double Field
```

to_prec (*prec*)

Returns the complex field to the specified precision. As doubles have fixed precision, this will only return a complex double field if *prec* is exactly 53.

EXAMPLES:

```
sage: CDF.to_prec(53)
Complex Double Field
sage: CDF.to_prec(250)
Complex Field with 250 bits of precision
```

zeta (*n=2*)

Return a primitive *n*-th root of unity in this CDF, for $n \geq 1$.

INPUT:

- *n* – a positive integer (default: 2)

OUTPUT: a complex *n*-th root of unity.

EXAMPLES:

```
sage: CDF.zeta(7) # rel tol 1e-15
0.6234898018587336 + 0.7818314824680298*I
sage: CDF.zeta(1)
1.0
sage: CDF.zeta()
-1.0
sage: CDF.zeta() == CDF.zeta(2)
True

sage: CDF.zeta(0.5)
Traceback (most recent call last):
...
ValueError: n must be a positive integer
sage: CDF.zeta(0)
Traceback (most recent call last):
...
ValueError: n must be a positive integer
sage: CDF.zeta(-1)
Traceback (most recent call last):
```

```
...
ValueError: n must be a positive integer
```

class `sage.rings.complex_double.FloatToCDF`

Bases: `sage.categories.morphism.Morphism`

Fast morphism from anything with a `__float__` method to an RDF element.

EXAMPLES:

```
sage: f = CDF.coerce_map_from(ZZ); f
Native morphism:
  From: Integer Ring
  To:   Complex Double Field
sage: f(4)
4.0
sage: f = CDF.coerce_map_from(QQ); f
Native morphism:
  From: Rational Field
  To:   Complex Double Field
sage: f(1/2)
0.5
sage: f = CDF.coerce_map_from(int); f
Native morphism:
  From: Set of Python objects of type 'int'
  To:   Complex Double Field
sage: f(3r)
3.0
sage: f = CDF.coerce_map_from(float); f
Native morphism:
  From: Set of Python objects of type 'float'
  To:   Complex Double Field
sage: f(3.5)
3.5
```

`sage.rings.complex_double.is_ComplexDoubleElement(x)`

Return True if `x` is a `ComplexDoubleElement`.

EXAMPLES:

```
sage: from sage.rings.complex_double import is_ComplexDoubleElement
sage: is_ComplexDoubleElement(0)
False
sage: is_ComplexDoubleElement(CDF(0))
True
```

`sage.rings.complex_double.is_ComplexDoubleField(x)`

Return True if `x` is the complex double field.

EXAMPLE:

```
sage: from sage.rings.complex_double import is_ComplexDoubleField
sage: is_ComplexDoubleField(CDF)
True
sage: is_ComplexDoubleField(ComplexField(53))
False
```


FIELD OF ARBITRARY PRECISION COMPLEX NUMBERS

AUTHORS:

- William Stein (2006-01-26): complete rewrite
- Niles Johnson (2010-08): [trac ticket #3893](#): `random_element()` should pass on `*args` and `**kwargs`.
- Travis Scrimshaw (2012-10-18): Added documentation for full coverage.

```
sage.rings.complex_field.ComplexField(prec=53, names=None)
```

Return the complex field with real and imaginary parts having *prec bits* of precision.

EXAMPLES:

```
sage: ComplexField()
Complex Field with 53 bits of precision
sage: ComplexField(100)
Complex Field with 100 bits of precision
sage: ComplexField(100).base_ring()
Real Field with 100 bits of precision
sage: i = ComplexField(200).gen()
sage: i^2
-1.0000000000000000000000000000000000000000000000000000000
```

```
class sage.rings.complex_field.ComplexField_class (prec=53)
```

Bases: sage.rings.ring.Field

An approximation to the field of complex numbers using floating point numbers with any specified precision. Answers derived from calculations in this approximation may differ from what they would be if those calculations were performed in the true field of complex numbers. This is due to the rounding errors inherent to finite precision calculations.

EXAMPLES:

```
sage: C = ComplexField(); C
Complex Field with 53 bits of precision
sage: Q = RationalField()
sage: C(1/3)
0.3333333333333333
sage: C(1/3, 2)
0.3333333333333333 + 2.000000000000000*I
sage: C(RR.pi())
3.14159265358979
sage: C(RR.log2(), RR.pi())
0.693147180559945 + 3.14159265358979*I
```

We can also coerce rational numbers and integers into `C`, but coercing a polynomial will raise an exception:

```
sage: Q = RationalField()
sage: C(1/3)
0.3333333333333333
sage: S = PolynomialRing(Q, 'x')
sage: C(S.gen())
Traceback (most recent call last):
...
TypeError: unable to coerce to a ComplexNumber: <type 'sage.rings.polynomial.polynomial_rational
```

This illustrates precision:

[illegible]

We can load and save complex numbers and the complex field:

```
sage: loads(z.dumps()) == z
True
sage: loads(CC.dumps()) == CC
True
sage: k = ComplexField(100)
sage: loads(dumps(k)) == k
True
```

This illustrates basic properties of a complex field:

```
sage: CC = ComplexField(200)
sage: CC.is_field()
True
sage: CC.characteristic()
0
sage: CC.precision()
200
sage: CC.variable_name()
'I'
sage: CC == ComplexField(200)
True
sage: CC == ComplexField(53)
False
sage: CC == 1.1
False
```

`algebraic_closure()`

Return the algebraic closure of `self` (which is itself).

EXAMPLES:

```
sage: CC
Complex Field with 53 bits of precision
sage: CC.algebraic_closure()
Complex Field with 53 bits of precision
sage: CC = ComplexField(1000)
sage: CC.algebraic_closure() is CC
True
```


characteristic()

Return the characteristic of \mathbb{C} , which is 0.

EXAMPLES:

```
sage: ComplexField().characteristic()
0
```

construction()

Returns the functorial construction of `self`, namely the algebraic closure of the real field with the same precision.

EXAMPLES:

```
sage: c, S = CC.construction(); S
Real Field with 53 bits of precision
sage: CC == c(S)
True
```

gen(*n=0*)

Return the generator of the complex field.

EXAMPLES:

```
sage: ComplexField().gen(0)
1.000000000000000*I
```

is_exact()

Return whether or not this field is exact, which is always `False`.

EXAMPLES:

```
sage: ComplexField().is_exact()
False
```

is_field(*proof=True*)

Return `True` since the complex numbers are a field.

EXAMPLES:

```
sage: CC.is_field()
True
```

is_finite()

Return `False` since there are infinite number of complex numbers.

EXAMPLES:

```
sage: CC.is_finite()
False
```

ngens()

The number of generators of this complex field as an \mathbb{R} -algebra.

There is one generator, namely $\sqrt{-1}$.

EXAMPLES:

```
sage: ComplexField().ngens()
1
```

pi()

Returns π as a complex number.

EXAMPLES:

```
sage: ComplexField().pi()
3.14159265358979
sage: ComplexField(100).pi()
3.1415926535897932384626433833
```

prec()

Return the precision of this complex field.

EXAMPLES:

```
sage: ComplexField().prec()
53
sage: ComplexField(15).prec()
15
```

precision()

Return the precision of this complex field.

EXAMPLES:

```
sage: ComplexField().prec()
53
sage: ComplexField(15).prec()
15
```

random_element (*component_max=1, *args, **kws*)

Returns a uniformly distributed random number inside a square centered on the origin (by default, the square $[-1, 1] \times [-1, 1]$).

Passes additional arguments and keywords to underlying real field.

EXAMPLES:

```
sage: [CC.random_element() for _ in range(5)]
[0.153636193785613 - 0.502987375247518*I,
 0.609589964322241 - 0.948854594338216*I,
 0.968393085385764 - 0.148483595843485*I,
 -0.908976099636549 + 0.126219184235123*I,
 0.461226845462901 - 0.0420335212948924*I]
sage: CC6 = ComplexField(6)
sage: [CC6.random_element(2^-20) for _ in range(5)]
[-5.4e-7 - 3.3e-7*I, 2.1e-7 + 8.0e-7*I, -4.8e-7 - 8.6e-7*I, -6.0e-8 + 2.7e-7*I, 6.0e-8 + 1.8e-7*I]
sage: [CC6.random_element(pi^20) for _ in range(5)]
[6.7e8 - 5.4e8*I, -9.4e8 + 5.0e9*I, 1.2e9 - 2.7e8*I, -2.3e9 - 4.0e9*I, 7.7e9 + 1.2e9*I]
```

Passes extra positional or keyword arguments through:

```
sage: [CC.random_element(distribution='1/n') for _ in range(5)]
[-0.900931453455899 - 0.932172283929307*I,
 0.327862582226912 + 0.828104487111727*I,
 0.246299162813240 + 0.588214960163442*I,
 0.892970599589521 - 0.266744694790704*I,
 0.878458776600692 - 0.905641181799996*I]
```

scientific_notation (*status=None*)

Set or return the scientific notation printing flag.

If this flag is `True` then complex numbers with this space as parent print using scientific notation.

EXAMPLES:

```

sage: C = ComplexField()
sage: C((0.025, 2))
0.02500000000000000 + 2.000000000000000*I
sage: C.scientific_notation(True)
sage: C((0.025, 2))
2.500000000000000e-2 + 2.000000000000000e0*I
sage: C.scientific_notation(False)
sage: C((0.025, 2))
0.02500000000000000 + 2.000000000000000*I

```

to_prec (*prec*)

Returns the complex field to the specified precision.

EXAMPLES:

```

sage: CC.to_prec(10)
Complex Field with 10 bits of precision
sage: CC.to_prec(100)
Complex Field with 100 bits of precision

```

zeta (*n=2*)

Return a primitive *n*-th root of unity.

INPUT:

- *n* - an integer (default: 2)

OUTPUT: a complex *n*-th root of unity.

EXAMPLES:

```

sage: C = ComplexField()
sage: C.zeta(2)
-1.000000000000000
sage: C.zeta(5)
0.309016994374947 + 0.951056516295154*I

```

`sage.rings.complex_field.is_ComplexField(x)`

Check if *x* is a complex field.

EXAMPLES:

```

sage: from sage.rings.complex_field import is_ComplexField as is_CF
sage: is_CF(ComplexField())
True
sage: is_CF(ComplexField(12))
True
sage: is_CF(CC)
True

```

`sage.rings.complex_field.late_import()`

Import the objects/modules after build (when needed).

TESTS:

```

sage: sage.rings.complex_field.late_import()

```


ARBITRARY PRECISION COMPLEX NUMBERS

AUTHORS:

- William Stein (2006-01-26): complete rewrite
- Joel B. Mohler (2006-12-16): naive rewrite into pyrex
- William Stein(2007-01): rewrite of Mohler's rewrite
- Vincent Delecroix (2010-01): plot function
- Travis Scrimshaw (2012-10-18): Added documentation for full coverage

class `sage.rings.complex_number.CCtoCDF`

Bases: `sage.categories.map.Map`

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

```
From: Rational Field
To: Integer Ring
```

Using domain and codomain:

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

```
From: Univariate Polynomial Ring in x over Rational Field
To: Symmetric group of order 6! as a permutation group
```

class `sage.rings.complex_number.ComplexNumber`

Bases: `sage.structure.element.FieldElement`

A floating point approximation to a complex number using any specified precision. Answers derived from calculations with such approximations may differ from what they would be if those calculations were performed with true complex numbers. This is due to the rounding errors inherent to finite precision calculations.

EXAMPLES:

```
sage: I = CC.0
```

```
sage: b = 1.5 + 2.5*I
```

```
sage: loads(b.dumps()) == b
True
```

`additive_order()`

Return the additive order of `self`.

EXAMPLES:

```
sage: CC(0).additive_order()
1
sage: CC.gen().additive_order()
+Infinity
```

`agm(right, algorithm='optimal')`

Return the Arithmetic-Geometric Mean (AGM) of `self` and `right`.

INPUT:

- `right` (complex) – another complex number
- `algorithm` (string, default “optimal”) – the algorithm to use (see below).

OUTPUT:

(complex) A value of the AGM of `self` and `right`. Note that this is a multi-valued function, and the algorithm used affects the value returned, as follows:

- “**pari**”: Call the `sgm` function from the `pari` library.
- “**optimal**”: Use the AGM sequence such that at each stage (a, b) is replaced by $(a_1, b_1) = ((a + b)/2, \pm\sqrt{ab})$ where the sign is chosen so that $|a_1 - b_1| \leq |a_1 + b_1|$, or equivalently $\Re(b_1/a_1) \geq 0$. The resulting limit is maximal among all possible values.
- “**principal**”: Use the AGM sequence such that at each stage (a, b) is replaced by $(a_1, b_1) = ((a + b)/2, \pm\sqrt{ab})$ where the sign is chosen so that $\Re(b_1) \geq 0$ (the so-called principal branch of the square root).

The values $AGM(a, 0)$, $AGM(0, a)$, and $AGM(a, -a)$ are all taken to be 0.

EXAMPLES:

```
sage: a = CC(1, 1)
sage: b = CC(2, -1)
sage: a.agm(b)
1.62780548487271 + 0.136827548397369*I
sage: a.agm(b, algorithm="optimal")
1.62780548487271 + 0.136827548397369*I
sage: a.agm(b, algorithm="principal")
1.62780548487271 + 0.136827548397369*I
sage: a.agm(b, algorithm="pari")
1.62780548487271 + 0.136827548397369*I
```

An example to show that the returned value depends on the algorithm parameter:

```
sage: a = CC(-0.95, -0.65)
sage: b = CC(0.683, 0.747)
sage: a.agm(b, algorithm="optimal")
-0.371591652351761 + 0.319894660206830*I
sage: a.agm(b, algorithm="principal")
0.338175462986180 - 0.0135326969565405*I
sage: a.agm(b, algorithm="pari")
-0.371591652351761 + 0.319894660206830*I
sage: a.agm(b, algorithm="optimal").abs()
```

```
0.490319232466314
sage: a.agm(b, algorithm="principal").abs()
0.338446122230459
sage: a.agm(b, algorithm="pari").abs()
0.490319232466314
```

TESTS:

An example which came up in testing:

```
sage: I = CC(I)
sage: a = 0.501648970493109 + 1.11877240294744*I
sage: b = 1.05946309435930 + 1.05946309435930*I
sage: a.agm(b)
0.774901870587681 + 1.10254945079875*I

sage: a = CC(-0.32599972608379413, 0.60395514542928641)
sage: b = CC(0.6062314525690593, 0.1425693337776659)
sage: a.agm(b)
0.199246281325876 + 0.478401702759654*I
sage: a.agm(-a)
0.0000000000000000

sage: a.agm(0)
0.0000000000000000

sage: CC(0).agm(a)
0.0000000000000000
```

Consistency:

[illegible]algdep (*n*, ****kws**)

Returns a polynomial of degree at most n which is approximately satisfied by this complex number. Note that the returned polynomial need not be irreducible, and indeed usually won't be if z is a good approximation to an algebraic number of degree less than n .

ALGORITHM: Uses the PARI C-library `algdep` command.

INPUT: Type `algdep?` at the top level prompt. All additional parameters are passed onto the top-level `algdep` command.

EXAMPLE:

```
sage: C = ComplexField()
sage: z = (1/2)*(1 + sqrt(3.0) *C.0); z
0.5000000000000000 + 0.866025403784439*I
sage: p = z.algdep(5); p
x^3 + 1
sage: p.factor()
(x + 1) * (x^2 - x + 1)
sage: z^2 - z + 1
1.11022302462516e-16
```

algebraic_dependency(*n*)

Returns a polynomial of degree at most n which is approximately satisfied by this complex number. Note that the returned polynomial need not be irreducible, and indeed usually won't be if z is a good approximation to an algebraic number of degree less than n .

ALGORITHM: Uses the PARI C-library `algdep` command.

INPUT: Type `algdep?` at the top level prompt. All additional parameters are passed onto the top-level `algdep` command.

EXAMPLE:

```
sage: C = ComplexField()
sage: z = (1/2)*(1 + sqrt(3.0) *C.0); z
0.5000000000000000 + 0.866025403784439*I
sage: p = z.algebraic_dependency(5); p
x^3 + 1
sage: p.factor()
(x + 1) * (x^2 - x + 1)
sage: z^2 - z + 1
1.11022302462516e-16
```

arccos()

Return the arccosine of `self`.

EXAMPLES:

```
sage: (1+CC(I)).arccos()
0.904556894302381 - 1.06127506190504*I
```

arccosh()

Return the hyperbolic arccosine of `self`.

EXAMPLES:

```
sage: (1+CC(I)).arccosh()
1.06127506190504 + 0.904556894302381*I
```

arccoth()

Return the hyperbolic arccotangent of `self`.

EXAMPLES:

```
sage: ComplexField(100)(1,1).arccoth()
0.40235947810852509365018983331 - 0.55357435889704525150853273009*I
```

arccsch()

Return the hyperbolic arccosecant of `self`.

EXAMPLES:

```
sage: ComplexField(100)(1,1).arccsch()
0.53063753095251782601650945811 - 0.45227844715119068206365839783*I
```

arcsech()

Return the hyperbolic arcsecant of `self`.

EXAMPLES:

```
sage: ComplexField(100)(1,1).arcsech()
0.53063753095251782601650945811 - 1.1185178796437059371676632938*I
```

arcsin()

Return the arcsine of `self`.

EXAMPLES:

```
sage: (1+CC(I)).arcsin()  
0.666239432492515 + 1.06127506190504*I
```

arcsinh()

Return the hyperbolic arcsine of `self`.

EXAMPLES:

```
sage: (1+CC(I)).arcsinh()  
1.06127506190504 + 0.666239432492515*I
```

arctan()

Return the arctangent of `self`.

EXAMPLES:

```
sage: (1+CC(I)).arctan()  
1.01722196789785 + 0.402359478108525*I
```

arctanh()

Return the hyperbolic arctangent of `self`.

EXAMPLES:

```
sage: (1+CC(I)).arctanh()  
0.402359478108525 + 1.01722196789785*I
```

arg()

See `argument()`.

EXAMPLES:

```
sage: i = CC.0  
sage: (i^2).arg()  
3.14159265358979
```

argument()

The argument (angle) of the complex number, normalized so that $-\pi < \theta \leq \pi$.

EXAMPLES:

```
sage: i = CC.0  
sage: (i^2).argument()  
3.14159265358979  
sage: (1+i).argument()  
0.785398163397448  
sage: i.argument()  
1.57079632679490  
sage: (-i).argument()  
-1.57079632679490  
sage: (RR('-0.001') - i).argument()  
-1.57179632646156
```

conjugate()

Return the complex conjugate of this complex number.

EXAMPLES:

```
sage: i = CC.0  
sage: (1+i).conjugate()  
1.000000000000000 - 1.000000000000000*I
```

cos()Return the cosine of `self`.

EXAMPLES:

```
sage: (1+CC(I)).cos()
0.833730025131149 - 0.988897705762865*I
```

cosh()Return the hyperbolic cosine of `self`.

EXAMPLES:

```
sage: (1+CC(I)).cosh()
0.833730025131149 + 0.988897705762865*I
```

cotan()Return the cotangent of `self`.

EXAMPLES:

```
sage: (1+CC(I)).cotan()
0.217621561854403 - 0.868014142895925*I
sage: i = ComplexField(200).0
sage: (1+i).cotan()
0.21762156185440268136513424360523807352075436916785404091068 - 0.86801414289592494863584920
sage: i = ComplexField(220).0
sage: (1+i).cotan()
0.21762156185440268136513424360523807352075436916785404091068124239 - 0.86801414289592494863
```

coth()Return the hyperbolic cotangent of `self`.

EXAMPLES:

```
sage: ComplexField(100)(1,1).coth()
0.86801414289592494863584920892 - 0.21762156185440268136513424361*I
```

csc()Return the cosecant of `self`.

EXAMPLES:

```
sage: ComplexField(100)(1,1).csc()
0.62151801717042842123490780586 - 0.30393100162842645033448560451*I
```

csch()Return the hyperbolic cosecant of `self`.

EXAMPLES:

```
sage: ComplexField(100)(1,1).csch()
0.30393100162842645033448560451 - 0.62151801717042842123490780586*I
```

dilog()Returns the complex dilogarithm of `self`.

The complex dilogarithm, or Spence's function, is defined by

$$Li_2(z) = - \int_0^z \frac{\log|1-\zeta|}{\zeta} d(\zeta) = \sum_{k=1}^{\infty} \frac{z^k}{k}$$

Note that the series definition can only be used for $|z| < 1$.

EXAMPLES:

```
sage: a = ComplexNumber(1,0)
sage: a.dilog()
1.64493406684823
sage: float(pi^2/6)
1.6449340668482262

sage: b = ComplexNumber(0,1)
sage: b.dilog()
-0.205616758356028 + 0.915965594177219*I

sage: c = ComplexNumber(0,0)
sage: c.dilog()
0.0000000000000000
```

eta (*omit_frac=False*)

Return the value of the Dedekind η function on `self`, intelligently computed using $\mathrm{SL}(2, \mathbb{Z})$ transformations.

The η function is

$$\eta(z) = e^{\pi iz/12} \prod_{n=1}^{\infty} (1 - e^{2\pi inz})$$

INPUT:

- `self` – element of the upper half plane (if not, raises a `ValueError`).
- `omit_frac` – (bool, default: `False`), if `True`, omit the $e^{\pi iz/12}$ factor.

OUTPUT: a complex number

ALGORITHM: Uses the PARI C library.

EXAMPLES:

First we compute $\eta(1+i)$:

```
sage: i = CC.0
sage: z = 1+i; z.eta()
0.742048775836565 + 0.198831370229911*I
```

We compute eta to low precision directly from the definition:

```
sage: z = 1 + i; z.eta()
0.742048775836565 + 0.198831370229911*I
sage: pi = CC(pi) # otherwise we will get a symbolic result.
sage: exp(pi * i * z / 12) * prod([1-exp(2*pi*i*n*z) for n in range(1,10)])
0.742048775836565 + 0.198831370229911*I
```

The optional argument allows us to omit the fractional part:

```
sage: z = 1 + i
sage: z.eta(omit_frac=True)
0.998129069925959
sage: prod([1-exp(2*pi*i*n*z) for n in range(1,10)])
0.998129069925958 + 4.59099857829247e-19*I
```

We illustrate what happens when z is not in the upper half plane:

```
sage: z = CC(1)
sage: z.eta()
```

```
Traceback (most recent call last):
...
ValueError: value must be in the upper half plane
```

You can also use functional notation:

```
sage: eta(1+CC(I))
0.742048775836565 + 0.198831370229911*I
```

exp()

Compute e^z or $\exp(z)$.

EXAMPLES:

```
sage: i = ComplexField(300).0
sage: z = 1 + i
sage: z.exp()
1.46869393991588515713896759732660426132695673662900872279767567631093696585951213872272450
```

gamma()

Return the Gamma function evaluated at this complex number.

EXAMPLES:

```
sage: i = ComplexField(30).0
sage: (1+i).gamma()
0.49801567 - 0.15494983*I
```

TESTS:

```
sage: CC(0).gamma()
Infinity
```

```
sage: CC(-1).gamma()
Infinity
```

gamma_inc(t)

Return the incomplete Gamma function evaluated at this complex number.

EXAMPLES:

```
sage: C, i = ComplexField(30).objgen()
sage: (1+i).gamma_inc(2 + 3*i) # abs tol 2e-10
0.0020969149 - 0.059981914*I
sage: (1+i).gamma_inc(5)
-0.0013781309 + 0.0065198200*I
sage: C(2).gamma_inc(1 + i)
0.70709210 - 0.42035364*I
sage: CC(2).gamma_inc(5)
0.0404276819945128
```

TESTS:

Check that [trac ticket #7099](#) is fixed:

```
sage: C = ComplexField(400)
sage: C(2 + I).gamma_inc(C(3 + I)) # abs tol 1e-120
0.121515644664508695525971545977439666159749344176962379708992904126499444842886620664991650
```

imag()

Return imaginary part of self.

[illegible]

Return imaginary part of self.

[illegible]

```
sage: CC(1.23*i).is_imaginary()
True
sage: CC(1+i).is_imaginary()
False
```

```
sage: CC(1, 2).is_infinity()
False
sage: CC(0, oo).is_infinity()
True
```

```
sage: CC(3).is_integer()
True
sage: CC(1,2).is_integer()
False
```

153

```
True
sage: CC(0, -oo).is_negative_infinity()
False
```

is_positive_infinity()

Check if self is $+\infty$.

EXAMPLES:

```
sage: CC(1, 2).is_positive_infinity()
False
sage: CC(oo, 0).is_positive_infinity()
True
sage: CC(0, oo).is_positive_infinity()
False
```

is_real()

Return True if self is real, i.e. has imaginary part zero.

EXAMPLES:

```
sage: CC(1.23).is_real()
True
sage: CC(1+i).is_real()
False
```

is_square()

This function always returns true as \mathbb{C} is algebraically closed.

EXAMPLES:

```
sage: a = ComplexNumber(2,1)
sage: a.is_square()
True
```

\mathbb{C} is algebraically closed, hence every element is a square:

```
sage: b = ComplexNumber(5)
sage: b.is_square()
True
```

log (base=None)

Complex logarithm of z with branch chosen as follows: Write $z = \rho e^{i\theta}$ with $-\pi < \theta \leq \pi$. Then $\log(z) = \log(\rho) + i\theta$.

Warning: Currently the real log is computed using floats, so there is potential precision loss.

EXAMPLES:

```
sage: a = ComplexNumber(2,1)
sage: a.log()
0.804718956217050 + 0.463647609000806*I
sage: log(a.abs())
0.804718956217050
sage: a.argument()
0.463647609000806

sage: b = ComplexNumber(float(exp(42)), 0)
sage: b.log()
41.99999999999971
```

```
sage: c = ComplexNumber(-1,0)
sage: c.log()
3.14159265358979*I
```

The option of a base is included for compatibility with other logs:

```
sage: c = ComplexNumber(-1,0)
sage: c.log(2)
4.53236014182719*I
```

If either component (real or imaginary) of the complex number is NaN (not a number), log will return the complex NaN:

```
sage: c = ComplexNumber(NaN,2)
sage: c.log()
NaN - NaN*I
```

multiplicative_order()

Return the multiplicative order of this complex number, if known, or raise a `NotImplementedError`.

EXAMPLES:

```
sage: C.<i> = ComplexField()
sage: i.multiplicative_order()
4
sage: C(1).multiplicative_order()
1
sage: C(-1).multiplicative_order()
2
sage: C(i^2).multiplicative_order()
2
sage: C(-i).multiplicative_order()
4
sage: C(2).multiplicative_order()
+Infinity
sage: w = (1+sqrt(-3.0))/2; w
0.5000000000000000 + 0.866025403784439*I
sage: abs(w)
1.0000000000000000
sage: w.multiplicative_order()
Traceback (most recent call last):
...
NotImplementedError: order of element not known
```

norm()

Returns the norm of this complex number.

If $c = a + bi$ is a complex number, then the norm of c is defined as the product of c and its complex conjugate:

$$\text{norm}(c) = \text{norm}(a + bi) = c \cdot \bar{c} = a^2 + b^2.$$

The norm of a complex number is different from its absolute value. The absolute value of a complex number is defined to be the square root of its norm. A typical use of the complex norm is in the integral domain $\mathbf{Z}[i]$ of Gaussian integers, where the norm of each Gaussian integer $c = a + bi$ is defined as its complex norm.

See also:

- `sage.misc.functional.norm()`

```
•sage.rings.complex_double.ComplexDoubleElement.norm()
```

EXAMPLES:

This indeed acts as the square function when the imaginary component of `self` is equal to zero:

```
sage: a = ComplexNumber(2,1)
sage: a.norm()
5.000000000000000
sage: b = ComplexNumber(4.2,0)
sage: b.norm()
17.640000000000000
sage: b^2
17.640000000000000
```

nth_root (*n*, *all=False*)

The *n*-th root function.

INPUT:

- all* - bool (default: False); if True, return a list of all *n*-th roots.

EXAMPLES:

```
sage: a = CC(27)
sage: a.nth_root(3)
3.000000000000000
sage: a.nth_root(3, all=True)
[3.000000000000000, -1.500000000000000 + 2.59807621135332*I, -1.500000000000000 - 2.59807621135332*I]
sage: a = ComplexField(20)(2,1)
sage: [r^7 for r in a.nth_root(7, all=True)]
[2.0000 + 1.0000*I, 2.0000 + 1.0000*I, 2.0000 + 1.0000*I, 2.0000 + 1.0000*I, 2.0000 + 1.0000*I, 2.0000 + 1.0000*I, 2.0000 + 1.0000*I]
```

plot (***kargs*)

Plots this complex number as a point in the plane

The accepted options are the ones of `point2d()`. Type `point2d.options` to see all options.

Note: Just wraps the `sage.plot.point.point2d` method

EXAMPLES:

You can either use the indirect:

```
sage: z = CC(0,1)
sage: plot(z)
Graphics object consisting of 1 graphics primitive
```

or the more direct:

```
sage: z = CC(0,1)
sage: z.plot()
Graphics object consisting of 1 graphics primitive
```

prec ()

Return precision of this complex number.

EXAMPLES:

```
sage: i = ComplexField(2000).0
sage: i.prec()
2000
```



```
sage: (1+CC(I)).tanh()
1.08392332733869 + 0.271752585319512*I
```

zeta()

Return the Riemann zeta function evaluated at this complex number.

EXAMPLES:

```
sage: i = ComplexField(30).gen()
sage: z = 1 + i
sage: z.zeta()
0.58215806 - 0.92684856*I
sage: zeta(z)
0.58215806 - 0.92684856*I

sage: CC(1).zeta()
Infinity
```

class sage.rings.complex_number.RRtoCC

Bases: sage.categories.map.Map

EXAMPLES:

```
sage: from sage.rings.complex_number import RRtoCC
sage: RRtoCC(RR, CC)
Natural map:
  From: Real Field with 53 bits of precision
  To:   Complex Field with 53 bits of precision
```

sage.rings.complex_number.**cmp_abs**(a, b)

Returns -1, 0, or 1 according to whether $|a|$ is less than, equal to, or greater than $|b|$.

Optimized for non-close numbers, where the ordering can be determined by examining exponents.

EXAMPLES:

```
sage: from sage.rings.complex_number import cmp_abs
sage: cmp_abs(CC(5), CC(1))
1
sage: cmp_abs(CC(5), CC(4))
1
sage: cmp_abs(CC(5), CC(5))
0
sage: cmp_abs(CC(5), CC(6))
-1
sage: cmp_abs(CC(5), CC(100))
-1
sage: cmp_abs(CC(-100), CC(1))
1
sage: cmp_abs(CC(-100), CC(100))
0
sage: cmp_abs(CC(-100), CC(1000))
-1
sage: cmp_abs(CC(1,1), CC(1))
1
sage: cmp_abs(CC(1,1), CC(2))
-1
sage: cmp_abs(CC(1,1), CC(1,0.99999))
1
sage: cmp_abs(CC(1,1), CC(1,-1))
```

```
0
sage: cmp_abs(CC(0), CC(1))
-1
sage: cmp_abs(CC(1), CC(0))
1
sage: cmp_abs(CC(0), CC(0))
0
sage: cmp_abs(CC(2,1), CC(1,2))
0
```

[illegible]

Return the complex number defined by the strings `s_real` and `s_imag` as an element of `ComplexField(prec=n)`, where n potentially has slightly more (controlled by `pad`) bits than given by `s`.

INPUT:

- `s_real` – a string that defines a real number (or something whose string representation defines a number)
- `s_imag` – a string that defines a real number (or something whose string representation defines a number)
- `pad` – an integer at least 0.
- `min_prec` – number will have at least this many bits of precision, no matter what.

EXAMPLES:

[illegible]

TESTS:

Make sure we've rounded up $\log(10, 2)$ enough to guarantee sufficient precision ([trac ticket #10164](#)):

```
sage: s = "1." + "0"*10**6 + "1"
sage: sage.rings.complex_number.create_ComplexNumber(s,0).real()-1 == 0
False
sage: sage.rings.complex_number.create_ComplexNumber(0,s).imag()-1 == 0
False
```

```
sage.rings.complex number.is ComplexNumber(x)
```

Returns `True` if `x` is a complex number. In particular, if `x` is of the `ComplexNumber` type.

EXAMPLES:

```
sage: from sage.rings.complex_number import is_ComplexNumber
sage: a = ComplexNumber(1,2); a
1.0000000000000000 + 2.0000000000000000*I
```

```
sage: is_ComplexNumber(a)
True
sage: b = ComplexNumber(1); b
1.0000000000000000
sage: is_ComplexNumber(b)
True
```

Note that the global element `I` is of type `SymbolicConstant`. However, elements of the class `ComplexField_class` are of type `ComplexNumber`:

```
sage: c = 1 + 2*I
sage: is_ComplexNumber(c)
False
sage: d = CC(1 + 2*I)
sage: is_ComplexNumber(d)
True
```

`sage.rings.complex_number.make_ComplexNumber0(fld, mult_order, re, im)`
Create a complex number for pickling.

EXAMPLES:

```
sage: a = CC(1 + I)
sage: loads(dumps(a)) == a # indirect doctest
True
```

`sage.rings.complex_number.set_global_complex_round_mode(n)`
Set the global complex rounding mode.

Warning: Do not call this function explicitly. The default rounding mode is `n = 0`.

EXAMPLES:

```
sage: sage.rings.complex_number.set_global_complex_round_mode(0)
```


ARBITRARY PRECISION COMPLEX NUMBERS USING GNU MPC

This is a binding for the MPC arbitrary-precision floating point library. It is adapted from `real_mpfr.pyx` and `complex_number.pyx`.

We define a class `MPCComplexField`, where each instance of `MPCComplexField` specifies a field of floating-point complex numbers with a specified precision shared by the real and imaginary part and a rounding mode stating the rounding mode directions specific to real and imaginary parts.

Individual floating-point numbers are of class `MPCComplexNumber`.

For floating-point representation and rounding mode description see the documentation for the `sage.rings.real_mpfr`.

AUTHORS:

- Philippe Theveny (2008-10-13): initial version.
- Alex Ghitza (2008-11): cache, generators, random element, and many doctests.
- Yann Laigle-Chapuy (2010-01): improves compatibility with CC, updates.
- Jeroen Demeyer (2012-02): reformat documentation, make MPC a standard package.
- Travis Scrimshaw (2012-10-18): Added doctests for full coverage.

EXAMPLES:

```
sage: MPC = MPCComplexField(42)
sage: a = MPC(12, '15.64E+32'); a
12.00000000000 + 1.564000000000e33*I
sage: a * a * a * a
5.98338564121e132 - 1.83633318912e101*I
sage: a + 1
13.00000000000 + 1.564000000000e33*I
sage: a / 3
4.00000000000 + 5.21333333333e32*I
sage: MPC("infinity + NaN *I")
+infinity + NaN*I
```

```
class sage.rings.complex_mpc.CCtoMPC
    Bases: sage.categories.map.Map
```

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

From: Rational Field

To: Integer Ring

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

From: Univariate Polynomial Ring in x over Rational Field

To: Symmetric group of order $6!$ as a permutation group

Bases: `sage.categories.map.Map`

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

```
sage: from sage.categories.map import Map
```

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

From: Rational Field

To: Integer Ring

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

From: Univariate Polynomial Ring in x over Rational Field

To: Symmetric group of order $6!$ as a permutation group

Return the complex field with real and imaginary parts having *prec bits* of precision.

```
sage: MPComplexField()
```

Complex Field with 53 bits of precision

```
sage: MPComplexField(100)
```

Complex Field with 100 bits of precision

```
sage: MPComplexField(100).base_ring()
```

Real Field with 100 bits of precision

```
sage: i = MPComplexField(200).gen()
```

```
sage: i^2
```

[illegible]

Bases: sage.rings.ring.Field

Initialize self.

INPUT:

- **prec** – (integer) precision; default = 53

prec is the number of bits used to represent the mantissa of both the real and imaginary part of complex floating-point number.

- **rnd** – (string) the rounding mode; default = 'RNDNN'

Rounding mode is of the form 'RNDxy' where *x* and *y* are the rounding mode for respectively the real and imaginary parts and are one of:

- 'N' for rounding to nearest
- 'Z' for rounding towards zero
- 'U' for rounding towards plus infinity
- 'D' for rounding towards minus infinity

For example, 'RNDZU' indicates to round the real part towards zero, and the imaginary part towards plus infinity.

EXAMPLES:

```
sage: MPComplexField(17)
Complex Field with 17 bits of precision
sage: MPComplexField()
Complex Field with 53 bits of precision
sage: MPComplexField(1042, 'RNDDZ')
Complex Field with 1042 bits of precision and rounding RNDDZ
```

ALGORITHMS: Computations are done using the MPC library.

characteristic()

Return 0, since the field of complex numbers has characteristic 0.

EXAMPLES:

```
sage: MPComplexField(42).characteristic()
0
```

gen(*n*=0)

Return the generator of this complex field over its real subfield.

EXAMPLES:

```
sage: MPComplexField(34).gen()
1.000000000*I
```

is_exact()

Returns whether or not this field is exact, which is always False.

EXAMPLES:

```
sage: MPComplexField(42).is_exact()
False
```

is_finite()

Return False, since the field of complex numbers is not finite.

EXAMPLES:

```
sage: MPComplexField(17).is_finite()
False
```

name()

Return the name of the complex field.

EXAMPLES:

```
sage: C = MPComplexField(10, 'RNDNZ'); C.name()
'MPComplexField10_RNDNZ'
```

ngens()

Return 1, the number of generators of this complex field over its real subfield.

EXAMPLES:

```
sage: MPComplexField(34).ngens()
1
```

prec()

Return the precision of this field of complex numbers.

EXAMPLES:

```
sage: MPComplexField().prec()
53
sage: MPComplexField(22).prec()
22
```

random_element(min=0, max=1)

Return a random complex number, uniformly distributed with real and imaginary parts between min and max (default 0 to 1).

EXAMPLES:

```
sage: MPComplexField(100).random_element(-5, 10) # random
1.9305310520925994224072377281 + 0.94745292506956219710477444855*I
sage: MPComplexField(10).random_element() # random
0.12 + 0.23*I
```

rounding_mode()

Return rounding modes used for each part of a complex number.

EXAMPLES:

```
sage: MPComplexField().rounding_mode()
'RNDNN'
sage: MPComplexField(rnd='RNDZU').rounding_mode()
'RNDZU'
```

rounding_mode_imag()

Return rounding mode used for the imaginary part of complex number.

EXAMPLES:

```
sage: MPComplexField(rnd='RNDZU').rounding_mode_imag()
'RNDU'
```

rounding_mode_real()

Return rounding mode used for the real part of complex number.

EXAMPLES:

```
sage: MPComplexField(rnd='RNDZU').rounding_mode_real()
'RNDZ'
```

class `sage.rings.complex_mpc.MPCComplexNumber`
 Bases: `sage.structure.element.FieldElement`

A floating point approximation to a complex number using any specified precision common to both real and imaginary part.

agm (*right*, *algorithm*='optimal')

Returns the algebraic geometric mean of self and right.

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: u = MPC(1, 4)
sage: v = MPC(-2, 5)
sage: u.agm(v, algorithm="pari")
-0.410522769709397 + 4.60061063922097*I
sage: u.agm(v, algorithm="principal")
1.24010691168158 - 0.472193567796433*I
sage: u.agm(v, algorithm="optimal")
-0.410522769709397 + 4.60061063922097*I
```

algebraic_dependency (*n*, ***kws*)

Returns a polynomial of degree at most *n* which is approximately satisfied by this complex number. Note that the returned polynomial need not be irreducible, and indeed usually won't be if *z* is a good approximation to an algebraic number of degree less than *n*.

ALGORITHM: Uses the PARI C-library `algdep` command.

INPUT: Type `algdep?` at the top level prompt. All additional parameters are passed onto the top-level `algdep` command.

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: z = (1/2)*(1 + sqrt(3.0) * MPC.0); z
0.500000000000000 + 0.866025403784439*I
sage: p = z.algebraic_dependency(5)
sage: p.factor()
(x + 1) * (x^2 - x + 1)^2
sage: z^2 - z + 1
1.11022302462516e-16
```

algebraic_dependency (*n*, ***kws*)

Returns a polynomial of degree at most *n* which is approximately satisfied by this complex number. Note that the returned polynomial need not be irreducible, and indeed usually won't be if *z* is a good approximation to an algebraic number of degree less than *n*.

ALGORITHM: Uses the PARI C-library `algdep` command.

INPUT: Type `algdep?` at the top level prompt. All additional parameters are passed onto the top-level `algdep` command.

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: z = (1/2)*(1 + sqrt(3.0) * MPC.0); z
0.500000000000000 + 0.866025403784439*I
sage: p = z.algebraic_dependency(5)
sage: p.factor()
(x + 1) * (x^2 - x + 1)^2
sage: z^2 - z + 1
1.11022302462516e-16
```

arccos()

Return the arccosine of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
sage: arccos(u)
1.11692611683177 - 2.19857302792094*I
```

arccosh()

Return the hyperbolic arccos of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
sage: arccosh(u)
2.19857302792094 + 1.11692611683177*I
```

arccoth()

Return the hyperbolic arccotangent of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(100)
sage: MPC(1,1).arccoth()
0.40235947810852509365018983331 - 0.55357435889704525150853273009*I
```

arccsch()

Return the hyperbolic arcsine of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(100)
sage: MPC(1,1).arccsch()
0.53063753095251782601650945811 - 0.45227844715119068206365839783*I
```

arcsech()

Return the hyperbolic arcsecant of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(100)
sage: MPC(1,1).arcsech()
0.53063753095251782601650945811 - 1.1185178796437059371676632938*I
```

arcsin()

Return the arcsine of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
sage: arcsin(u)
0.453870209963122 + 2.19857302792094*I
```

arcsinh()

Return the hyperbolic arcsine of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
```

```
sage: arcsinh(u)
2.18358521656456 + 1.09692154883014*I
```

arctan()

Return the arctangent of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(-2, 4)
sage: arctan(u)
-1.46704821357730 + 0.200586618131234*I
```

arctanh()

Return the hyperbolic arctangent of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
sage: arctanh(u)
0.0964156202029962 + 1.37153510396169*I
```

argument()

The argument (angle) of the complex number, normalized so that $-\pi < \theta \leq \pi$.

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: i = MPC.0
sage: (i^2).argument()
3.14159265358979
sage: (1+i).argument()
0.785398163397448
sage: i.argument()
1.57079632679490
sage: (-i).argument()
-1.57079632679490
sage: (RR('-0.001') - i).argument()
-1.57179632646156
```

conjugate()

Return the complex conjugate of this complex number:

$$\text{conjugate}(a + ib) = a - ib.$$

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: i = MPC(0, 1)
sage: (1+i).conjugate()
1.000000000000000 - 1.000000000000000*I
```

cos()

Return the cosine of this complex number:

$$\cos(a + ib) = \cos a \cosh b - i \sin a \sinh b.$$

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
sage: cos(u)
-11.3642347064011 - 24.8146514856342*I
```

cosh()

Return the hyperbolic cosine of this complex number:

$$\cosh(a + ib) = \cosh a \cos b + i \sinh a \sin b.$$

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
sage: cosh(u)
-2.45913521391738 - 2.74481700679215*I
```

cotan()

Return the cotangent of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(53)
sage: (1+MPC(I)).cotan()
0.217621561854403 - 0.868014142895925*I
sage: i = MPComplexField(200).0
sage: (1+i).cotan()
0.21762156185440268136513424360523807352075436916785404091068 - 0.86801414289592494863584920
sage: i = MPComplexField(220).0
sage: (1+i).cotan()
0.21762156185440268136513424360523807352075436916785404091068124239 - 0.86801414289592494863
```

coth()

Return the hyperbolic cotangent of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(100)
sage: MPC(1,1).coth()
0.86801414289592494863584920892 - 0.21762156185440268136513424361*I
```

csc()

Return the cosecant of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(100)
sage: MPC(1,1).csc()
0.62151801717042842123490780586 - 0.30393100162842645033448560451*I
```

csch()

Return the hyperbolic cosecant of this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(100)
sage: MPC(1,1).csch()
0.30393100162842645033448560451 - 0.62151801717042842123490780586*I
```

dilog()

Return the complex dilogarithm of `self`.

The complex dilogarithm, or Spence's function, is defined by

$$Li_2(z) = - \int_0^z \frac{\log|1-\zeta|}{\zeta} d(\zeta) = \sum_{k=1}^{\infty} \frac{z^k}{k^2}.$$

Note that the series definition can only be used for $|z| < 1$.

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: a = MPC(1, 0)
sage: a.dilog()
1.64493406684823
sage: float(pi^2/6)
1.6449340668482262

sage: b = MPC(0, 1)
sage: b.dilog()
-0.205616758356028 + 0.915965594177219*I

sage: c = MPC(0, 0)
sage: c.dilog()
0
```

eta (*omit_frac=False*)

Return the value of the Dedekind η function on `self`, intelligently computed using $\mathrm{SL}(2, \mathbf{Z})$ transformations.

The η function is

$$\eta(z) = e^{\pi iz/12} \prod_{n=1}^{\infty} (1 - e^{2\pi inz})$$

INPUT:

- `self` - element of the upper half plane (if not, raises a `ValueError`).
- `omit_frac` - (bool, default: `False`), if `True`, omit the $e^{\pi iz/12}$ factor.

OUTPUT: a complex number

ALGORITHM: Uses the PARI C library.

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: i = MPC(0, 1)
sage: z = 1+i; z.eta()
0.742048775836565 + 0.198831370229911*I
```

exp ()

Return the exponential of this complex number:

$$\exp(a + ib) = \exp(a)(\cos b + i \sin b).$$

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: u = MPC(2, 4)
sage: exp(u)
-4.82980938326939 - 5.59205609364098*I
```

gamma ()

Return the Gamma function evaluated at this complex number.

EXAMPLES:

```
sage: MPC = MPComplexField(30)
```

```
sage: i = MPC.0
```

```
sage: (1+i).gamma()
```

$$0.49801567 - 0.15494983 \cdot i$$

TESTS:

```
sage: MPC(0).gamma()
```

Infinity

```
sage: MPC(-1).gamma()
```

Infinity

$$\gamma_{\text{inc}}(t)$$

Return the incomplete Gamma function evaluated at this complex number.

EXAMPLES:

```
sage: C, i = MPComplexField(30).objgen()
```

```
sage: (1+i).gamma_inc(2 + 3*i) # abs tol 2e-10
```

$$0.0020969149 - 0.059981914 \cdot I$$

```
sage: (1+i).gamma_inc(5)
```

$$-0.0013781309 + 0.0065198200 \cdot i$$

```
sage: C(2).gamma_inc(1 + i)
```

$$0.70709210 - 0.42035364 * i$$

`imag()`

Return imaginary part of self.

EXAMPLES:

```
sage: C = MPComplexField(100)
```

```
sage: z = C(2, 3)
```

```
sage: x = z.imag(); x
```

3.00000000000000000000000000000000

```
sage: x.parent()
```

Real Field with 100 bits of precision

```
is_imaginary()
```

Return True if self is imaginary, i.e. has real part zero.

EXAMPLES:

```
sage: C200 = MPComplexField(200)
```

```
sage: C200(1.23*i).is_imaginary()
```

True

```
sage: C200(1+i).is_imaginary()
```

False

is_real()

Return True if self is real, i.e. has imaginary part zero.

EXAMPLES:

```
sage: C200 = MPCComplexField(200)
```

```
sage: C200(1.23).is_real()
```

True


```
sage: C200(1+i).is_real()
False
```

is_square()

This function always returns true as \mathbb{C} is algebraically closed.

EXAMPLES:

```
sage: C200 = MPComplexField(200)
sage: a = C200(2, 1)
sage: a.is_square()
True
```

\mathbb{C} is algebraically closed, hence every element is a square:

```
sage: b = C200(5)
sage: b.is_square()
True
```

log()

Return the logarithm of this complex number with the branch cut on the negative real axis:

$$\log(z) = \log|z| + i \arg(z).$$

EXAMPLES:

```
sage: MPC = MPComplexField()
sage: u = MPC(2, 4)
sage: log(u)
1.49786613677700 + 1.10714871779409*I
```

norm()

Return the norm of a complex number, rounded with the rounding mode of the real part. The norm is the square of the absolute value:

$$\text{norm}(a + ib) = a^2 + b^2.$$

OUTPUT:

A floating-point number in the real field of the real part (same precision, same rounding mode).

EXAMPLES:

This indeed acts as the square function when the imaginary component of self is equal to zero:

```
sage: MPC = MPComplexField()
sage: a = MPC(2, 1)
sage: a.norm()
5.000000000000000
sage: b = MPC(4.2, 0)
sage: b.norm()
17.640000000000000
sage: b^2
17.640000000000000
```

nth_root(n, all=False)

The n -th root function.

INPUT:

- `all` - bool (default: False); if True, return a list of all n -th roots.

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: a = MPC(27)
sage: a.nth_root(3)
3.000000000000000
sage: a.nth_root(3, all=True)
[3.000000000000000, -1.500000000000000 + 2.59807621135332*I, -1.500000000000000 - 2.59807621135332*I]
```

```
prec()
```

Return precision of this complex number.

EXAMPLES:

```
sage: i = MPComplexField(2000).0
sage: i.prec()
2000
```

real()

Return the real part of `self`.

EXAMPLES:

[illegible]

sec ()

Return the secant of this complex number.

EXAMPLES:

```
sage: MPC = MPCComplexField(100)
sage: MPC(1, 1).sec()
0.49833703055518678521380589177 + 0.59108384172104504805039169297*I
```

sech ()

Return the hyperbolic secant of this complex number.

EXAMPLES:

```
sage: MPC = MPCComplexField(100)
sage: MPC(1,1).sech()
0.49833703055518678521380589177 - 0.59108384172104504805039169297*I
```

sin()

Return the sine of this complex number:

$$\sin(a + ib) = \sin a \cosh b + i \cos x \sinh b.$$

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: u = MPC(2, 4)
sage: sin(u)
24.8313058489464 - 11.35661271112182*I
```

sinh ()


```
sage: MPC = MPCComplexField()
sage: u = MPC(-2, 4)
sage: tan(u)
0.000507980623470039 + 1.00043851320205*I
```

tanh()

Return the hyperbolic tangent of this complex number:

$$\tanh(a + ib) = (\sinh 2a + i \sin 2b) / (\cosh 2a + \cos 2b).$$

EXAMPLES:

```
sage: MPC = MPCComplexField()
sage: u = MPC(2, 4)
sage: tanh(u)
1.00468231219024 + 0.0364233692474037*I
```

zeta()

Return the Riemann zeta function evaluated at this complex number.

EXAMPLES:

```
sage: i = MPCComplexField(30).gen()
sage: z = 1 + i
sage: z.zeta()
0.58215806 - 0.92684856*I
```

class sage.rings.complex_mpc.MPctoMPC

Bases: sage.categories.map.Map

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

From: Rational Field

To: Integer Ring

Using domain and codomain:

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

From: Univariate Polynomial Ring in x over Rational Field

To: Symmetric group of order 6! as a permutation group

section()**EXAMPLES:**

```
sage: from sage.rings.complex_mpc import *
sage: C10 = MPCComplexField(10)
sage: C100 = MPCComplexField(100)
sage: f = MPctoMPC(C100, C10)
sage: f.section()
Generic map:
```

```

From: Complex Field with 10 bits of precision
To:   Complex Field with 100 bits of precision

```

class `sage.rings.complex_mpc.MPFRtoMPC`

Bases: `sage.categories.map.Map`

INPUT:

There can be one or two arguments of this init method. If it is one argument, it must be a hom space. If it is two arguments, it must be two parent structures that will be domain and codomain of the map-to-be-created.

TESTS:

```
sage: from sage.categories.map import Map
```

Using a hom space:

```
sage: Map(Hom(QQ, ZZ, Rings()))
```

Generic map:

```

From: Rational Field
To:   Integer Ring

```

Using domain and codomain:

```
sage: Map(QQ['x'], SymmetricGroup(6))
```

Generic map:

```

From: Univariate Polynomial Ring in x over Rational Field
To:   Symmetric group of order 6! as a permutation group

```

`sage.rings.complex_mpc.late_import()`

Import the objects/modules after build (when needed).

TESTS:

```
sage: sage.rings.complex_mpc.late_import()
```

`sage.rings.complex_mpc.split_complex_string(string, base=10)`

Split and return in that order the real and imaginary parts of a complex in a string.

This is an internal function.

EXAMPLES:

```
sage: sage.rings.complex_mpc.split_complex_string('123.456e789')
('123.456e789', None)
```

```
sage: sage.rings.complex_mpc.split_complex_string('123.456e789*I')
(None, '123.456e789')
```

```
sage: sage.rings.complex_mpc.split_complex_string('123.+456e789*I')
('123.', '+456e789')
```

```
sage: sage.rings.complex_mpc.split_complex_string('123.456e789', base=2)
(None, None)
```


FIELD OF ARBITRARY PRECISION COMPLEX INTERVALS

AUTHORS:

- William Stein wrote `complex_field.py`.
- William Stein (2006-01-26): complete rewrite

Then `complex_field.py` was copied to `complex_interval_field.py` and heavily modified:

- Carl Witty (2007-10-24): rewrite for intervals
- Niles Johnson (2010-08): [trac ticket #3893](#): `random_element()` should pass on `*args` and `**kwds`.
- Travis Scrimshaw (2012-10-18): Added documentation to get full coverage.

Note: The `ComplexIntervalField` differs from `ComplexField` in that `ComplexIntervalField` only gives the digits with exact precision, then a `?` signifying that that digit can have an error of ± 1 .

```
sage.rings.complex_interval_field.ComplexIntervalField(prec=53, names=None)
```

Return the complex interval field with real and imaginary parts having `prec` bits of precision.

EXAMPLES:

```
sage: ComplexIntervalField()
Complex Interval Field with 53 bits of precision
sage: ComplexIntervalField(100)
Complex Interval Field with 100 bits of precision
sage: ComplexIntervalField(100).base_ring()
Real Interval Field with 100 bits of precision
sage: i = ComplexIntervalField(200).gen()
sage: i^2
-1
sage: i^i
0.207879576350761908546955619834978770033877841631769608075136?
```

```
class sage.rings.complex_interval_field.ComplexIntervalField_class(prec=53)
```

Bases: `sage.rings.ring.Field`

The field of complex (interval) numbers.

EXAMPLES:

```
sage: C = ComplexIntervalField(); C
Complex Interval Field with 53 bits of precision
sage: Q = RationalField()
sage: C(1/3)
0.33333333333333334?
sage: C(1/3, 2)
0.33333333333333334? + 2*I
```

We can also coerce rational numbers and integers into \mathbb{C} , but coercing a polynomial will raise an exception:

```
sage: Q = RationalField()
sage: C(1/3)
0.3333333333333334?
sage: S = PolynomialRing(Q, 'x')
sage: C(S.gen())
Traceback (most recent call last):
...
TypeError: unable to coerce to a ComplexIntervalFieldElement
```

This illustrates precision:

```
sage: CIF = ComplexIntervalField(10); CIF(1/3, 2/3)
0.334? + 0.667?*I
sage: CIF
Complex Interval Field with 10 bits of precision
sage: CIF = ComplexIntervalField(100); CIF
Complex Interval Field with 100 bits of precision
sage: z = CIF(1/3, 2/3); z
0.33333333333333333333333333333334? + 0.6666666666666666666666666666667?*I
```

We can load and save complex numbers and the complex interval field:

```
sage: cmp.loads(z.dumps()), z
0
sage: loads(CIF.dumps()) == CIF
True
sage: k = ComplexIntervalField(100)
sage: loads(dumps(k)) == k
True
```

This illustrates basic properties of a complex (interval) field:

```
sage: CIF = ComplexIntervalField(200)
sage: CIF.is_field()
True
sage: CIF.characteristic()
0
sage: CIF.precision()
200
sage: CIF.variable_name()
'I'
sage: CIF == ComplexIntervalField(200)
True
sage: CIF == ComplexIntervalField(53)
False
sage: CIF == 1.1
False
sage: CIF = ComplexIntervalField(53)

sage: CIF.category()
Category of fields
sage: TestSuite(CIF).run()
```

characteristic()

Return the characteristic of the complex (interval) field, which is 0.

EXAMPLES:


```
sage: CIF.characteristic()
0
```

gen(*n=0*)
Return the generator of the complex (interval) field.

EXAMPLES:

```
sage: CIF.0
1*I
sage: CIF.gen(0)
1*I
```

is_exact()
The complex interval field is not exact.

EXAMPLES:

```
sage: CIF.is_exact()
False
```

is_field(*proof=True*)
Return True, since the complex numbers are a field.

EXAMPLES:

```
sage: CIF.is_field()
True
```

is_finite()
Return False, since the complex numbers are infinite.

EXAMPLES:

```
sage: CIF.is_finite()
False
```

ngens()
The number of generators of this complex (interval) field as an \mathbf{R} -algebra.
There is one generator, namely $\sqrt{-1}$.

EXAMPLES:

```
sage: CIF.ngens()
1
```

pi()
Returns π as an element in the complex (interval) field.

EXAMPLES:

```
sage: ComplexIntervalField(100).pi()
3.14159265358979323846264338328?
```

prec()
Returns the precision of `self` (in bits).

EXAMPLES:

```
sage: CIF.prec()
53
sage: ComplexIntervalField(200).prec()
200
```

precision()

Returns the precision of `self` (in bits).

EXAMPLES:

```
sage: CIF.prec()
53
sage: ComplexIntervalField(200).prec()
200
```

random_element(*args, **kws)

Create a random element of `self`.

This simply chooses the real and imaginary part randomly, passing arguments and keywords to the underlying real interval field.

EXAMPLES:

```
sage: CIF.random_element()
0.15363619378561300? - 0.50298737524751780?*I
sage: CIF.random_element(10, 20)
18.047949821611205? + 10.255727028308920?*I
```

Passes extra positional or keyword arguments through:

```
sage: CIF.random_element(max=0, min=-5)
-0.079017286535590259? - 2.8712089896087117?*I
```

scientific_notation(status=None)

Set or return the scientific notation printing flag.

If this flag is `True` then complex numbers with this space as parent print using scientific notation.

EXAMPLES:

```
sage: CIF((0.025, 2))
0.025000000000000002? + 2*I
sage: CIF.scientific_notation(True)
sage: CIF((0.025, 2))
2.5000000000000002?e-2 + 2*I
sage: CIF.scientific_notation(False)
sage: CIF((0.025, 2))
0.025000000000000002? + 2*I
```

to_prec(prec)

Returns a complex interval field with the given precision.

EXAMPLES:

```
sage: CIF.to_prec(150)
Complex Interval Field with 150 bits of precision
sage: CIF.to_prec(15)
Complex Interval Field with 15 bits of precision
sage: CIF.to_prec(53) is CIF
True
```

zeta(n=2)

Return a primitive n -th root of unity.

Todo

Implement `ComplexIntervalFieldElement` multiplicative order and set this output to have multiplicative order n .

INPUT:

- n – an integer (default: 2)

OUTPUT:

A complex n -th root of unity.

EXAMPLES:

```
sage: CIF.zeta(2)
```

```
-1
```

```
sage: CIF.zeta(5)
```

```
0.309016994374948? + 0.9510565162951536?*I
```

```
sage.rings.complex_interval_field.is_ComplexIntervalField(x)
```

Check if x is a `ComplexIntervalField`.

EXAMPLES:

```
sage: from sage.rings.complex_interval_field import is_ComplexIntervalField as is_CIF
```

```
sage: is_CIF(CIF)
```

```
True
```

```
sage: is_CIF(CC)
```

```
False
```

```
sage.rings.complex_interval_field.late_import()
```

Import the objects/modules after build (when needed).

TESTS:

```
sage: sage.rings.complex_interval_field.late_import()
```


ARBITRARY PRECISION COMPLEX INTERVALS

This is a simple complex interval package, using intervals which are axis-aligned rectangles in the complex plane. It has very few special functions, and it does not use any special tricks to keep the size of the intervals down.

AUTHORS:

These authors wrote `complex_number.pyx`:

- William Stein (2006-01-26): complete rewrite
- Joel B. Mohler (2006-12-16): naive rewrite into pyrex
- William Stein(2007-01): rewrite of Mohler's rewrite

Then `complex_number.pyx` was copied to `complex_interval.pyx` and heavily modified:

- Carl Witty (2007-10-24): rewrite to become a complex interval package
- Travis Scrimshaw (2012-10-18): Added documentation to get full coverage.

Todo

Implement `ComplexIntervalFieldElement` multiplicative order similar to `ComplexNumber` multiplicative order with `_set_multiplicative_order(n)` and `ComplexNumber.multiplicative_order()` methods.

```
class sage.rings.complex_interval.ComplexIntervalFieldElement
    Bases: sage.structure.element.FieldElement
```

A complex interval.

EXAMPLES:

```
sage: I = CIF.gen()
sage: b = 1.5 + 2.5*I
sage: TestSuite(b).run()
```

`arg()`

Same as `argument()`.

EXAMPLES:

```
sage: i = CIF.0
sage: (i^2).arg()
3.141592653589794?
```

`argument()`

The argument (angle) of the complex number, normalized so that $-\pi < \theta.lower() \leq \pi$.

We raise a `ValueError` if the interval strictly contains 0, or if the interval contains only 0.

Warning: We do not always use the standard branch cut for argument! If the interval crosses the negative real axis, then the argument will be an interval whose lower bound is less than π and whose upper bound is more than π ; in effect, we move the branch cut away from the interval.

EXAMPLES:

```
sage: i = CIF.0
sage: (i^2).argument()
3.141592653589794?
sage: (1+i).argument()
0.785398163397449?
sage: i.argument()
1.570796326794897?
sage: (-i).argument()
-1.570796326794897?
sage: (RR('-0.001') - i).argument()
-1.571796326461564?
sage: CIF(2).argument()
0
sage: CIF(-2).argument()
3.141592653589794?
```

Here we see that if the interval crosses the negative real axis, then the argument can exceed π , and we violate the standard interval guarantees in the process:

```
sage: CIF(-2, RIF(-0.1, 0.1)).argument().str(style='brackets')
'[3.0916342578678501 .. 3.1915510493117365]'
sage: CIF(-2, -0.1).argument()
-3.091634257867851?
```

bisection()

Returns the bisection of `self` into four intervals whose union is `self` and intersection is `center()`.

EXAMPLES:

```
sage: z = CIF(RIF(2, 3), RIF(-5, -4))
sage: z.bisection()
(3.? - 5.?*I, 3.? - 5.?*I, 3.? - 5.?*I, 3.? - 5.?*I)
sage: for z in z.bisection():
...     print z.real().endpoints(), z.imag().endpoints()
(2.000000000000000, 2.500000000000000) (-5.000000000000000, -4.500000000000000)
(2.500000000000000, 3.000000000000000) (-5.000000000000000, -4.500000000000000)
(2.000000000000000, 2.500000000000000) (-4.500000000000000, -4.000000000000000)
(2.500000000000000, 3.000000000000000) (-4.500000000000000, -4.000000000000000)

sage: z = CIF(RIF(sqrt(2), sqrt(3)), RIF(e, pi))
sage: a, b, c, d = z.bisection()
sage: a.intersection(b).intersection(c).intersection(d) == CIF(z.center())
True

sage: zz = a.union(b).union(c).union(d)
sage: zz.real().endpoints() == z.real().endpoints()
True
sage: zz.imag().endpoints() == z.imag().endpoints()
True
```

center()

Returns the closest floating-point approximation to the center of the interval.

EXAMPLES:

```
sage: CIF(RIF(1, 2), RIF(3, 4)).center()
1.500000000000000 + 3.500000000000000*I
```

conjugate()

Return the complex conjugate of this complex number.

EXAMPLES:

```
sage: i = CIF.0
sage: (1+i).conjugate()
1 - 1*I
```

contains_zero()

Returns True if self is an interval containing zero.

EXAMPLES:

```
sage: CIF(0).contains_zero()
True
sage: CIF(RIF(-1, 1), 1).contains_zero()
False
```

crosses_log_branch_cut()

Returns True if this interval crosses the standard branch cut for `log()` (and hence for exponentiation) and for argument. (Recall that this branch cut is infinitesimally below the negative portion of the real axis.)

EXAMPLES:

```
sage: z = CIF(1.5, 2.5) - CIF(0, 2.5000000000000001); z
1.500000000000000? + -1.?e-15*I
sage: z.crosses_log_branch_cut()
False
sage: CIF(-2, RIF(-0.1, 0.1)).crosses_log_branch_cut()
True
```

diameter()

Returns a somewhat-arbitrarily defined “diameter” for this interval.

The diameter of an interval is the maximum of the diameter of the real and imaginary components, where diameter on a real interval is defined as absolute diameter if the interval contains zero, and relative diameter otherwise.

EXAMPLES:

```
sage: CIF(RIF(-1, 1), RIF(13, 17)).diameter()
2.000000000000000
sage: CIF(RIF(-0.1, 0.1), RIF(13, 17)).diameter()
0.2666666666666667
sage: CIF(RIF(-1, 1), 15).diameter()
2.000000000000000
```

exp()

Compute e^z or $\exp(z)$ where z is the complex number self.

EXAMPLES:

```
sage: i = ComplexIntervalField(300).0
sage: z = 1 + i
sage: z.exp()
1.46869393991588515713896759732660426132695673662900872279767567631093696585951213872272450?
```

imag()

Return imaginary part of self.

EXAMPLES:

```
sage: i = ComplexIntervalField(100).0
sage: z = 2 + 3*i
sage: x = z.imag(); x
3
sage: x.parent()
Real Interval Field with 100 bits of precision
```

intersection(other)

Returns the intersection of the two complex intervals self and other.

EXAMPLES:

```
sage: CIF(RIF(1, 3), RIF(1, 3)).intersection(CIF(RIF(2, 4), RIF(2, 4))).str(style='brackets')
'[2.0000000000000000 .. 3.0000000000000000] + [2.0000000000000000 .. 3.0000000000000000]*I'
sage: CIF(RIF(1, 2), RIF(1, 3)).intersection(CIF(RIF(3, 4), RIF(2, 4)))
Traceback (most recent call last):
...
ValueError: intersection of non-overlapping intervals
```

is_exact()

Returns whether this complex interval is exact (i.e. contains exactly one complex value).

EXAMPLES:

```
sage: CIF(3).is_exact()
True
sage: CIF(0, 2).is_exact()
True
sage: CIF(-4, 0).sqrt().is_exact()
True
sage: CIF(-5, 0).sqrt().is_exact()
False
sage: CIF(0, 2*pi).is_exact()
False
sage: CIF(e).is_exact()
False
sage: CIF(1e100).is_exact()
True
sage: (CIF(1e100) + 1).is_exact()
False
```

is_square()This function always returns True as \mathbb{C} is algebraically closed.

EXAMPLES:

```
sage: CIF(2, 1).is_square()
True
```

log(base=None)Complex logarithm of z .

Warning: This does always not use the standard branch cut for complex log! See the docstring for `argument()` to see what we do instead.

EXAMPLES:


```

sage: a = CIF(RIF(3, 4), RIF(13, 14))
sage: a.log().str(style='brackets')
'[2.5908917751460420 .. 2.6782931373360067] + [1.2722973952087170 .. 1.3597029935721503]*I'
sage: a.log().exp().str(style='brackets')
'[2.7954667135098274 .. 4.2819545928390213] + [12.751682453911920 .. 14.237018048974635]*I'
sage: a in a.log().exp()
True

```

If the interval crosses the negative real axis, then we don't use the standard branch cut (and we violate the interval guarantees):

```

sage: CIF(-3, RIF(-1/4, 1/4)).log().str(style='brackets')
'[1.0986122886681095 .. 1.1020725100903968] + [3.0584514217013518 .. 3.2247338854782349]*I'
sage: CIF(-3, -1/4).log()
1.102072510090397? - 3.058451421701352?*I

```

Usually if an interval contains zero, we raise an exception:

```

sage: CIF(RIF(-1, 1), RIF(-1, 1)).log()
Traceback (most recent call last):
...
ValueError: Can't take the argument of interval strictly containing zero

```

But we allow the exact input zero:

```

sage: CIF(0).log()
[-infinity .. -infinity]

```

If a base is passed from another function, we can accommodate this:

```

sage: CIF(-1, 1).log(2)
0.5000000000000000? + 3.399270106370396?*I

```

norm()

Returns the norm of this complex number.

If $c = a + bi$ is a complex number, then the norm of c is defined as the product of c and its complex conjugate:

$$\text{extnorm}(c) = \text{extnorm}(a + bi) = c \cdot \bar{c} = a^2 + b^2.$$

The norm of a complex number is different from its absolute value. The absolute value of a complex number is defined to be the square root of its norm. A typical use of the complex norm is in the integral domain $\mathbf{Z}[i]$ of Gaussian integers, where the norm of each Gaussian integer $c = a + bi$ is defined as its complex norm.

See also:

- `sage.rings.complex_double.ComplexDoubleElement.norm()`

EXAMPLES:

```

sage: CIF(2, 1).norm()
5
sage: CIF(1, -2).norm()
5

```

overlaps(other)

Returns True if self and other are intervals with at least one value in common.

EXAMPLES:

```

sage: CIF(0).overlaps(CIF(RIF(0, 1), RIF(-1, 0)))
True
sage: CIF(1).overlaps(CIF(1, 1))
False

```

plot (*pointsize=10, **kws*)

Plot a complex interval as a rectangle.

EXAMPLES:

```

sage: sum(plot(CIF(RIF(1/k, 1/k), RIF(-k, k))) for k in [1..10])
Graphics object consisting of 20 graphics primitives

```

Exact and nearly exact points are still visible:

```

sage: plot(CIF(pi, 1), color='red') + plot(CIF(1, e), color='purple') + plot(CIF(-1, -1))
Graphics object consisting of 6 graphics primitives

```

A demonstration that $z \mapsto z^2$ acts chaotically on $|z| = 1$:

```

sage: z = CIF(0, 2*pi/1000).exp()
sage: g = Graphics()
sage: for i in range(40):
...     z = z^2
...     g += z.plot(color=(1./(40-i), 0, 1))
...
sage: g
Graphics object consisting of 80 graphics primitives

```

prec ()

Return precision of this complex number.

EXAMPLES:

```

sage: i = ComplexIntervalField(2000).0
sage: i.prec()
2000

```

real ()

Return real part of self.

EXAMPLES:

```

sage: i = ComplexIntervalField(100).0
sage: z = 2 + 3*i
sage: x = z.real(); x
2
sage: x.parent()
Real Interval Field with 100 bits of precision

```

sqrt (*all=False, **kws*)

The square root function.

Warning: We approximate the standard branch cut along the negative real axis, with `sqrt(-r^2)` = `i*r` for positive real `r`; but if the interval crosses the negative real axis, we pick the root with positive imaginary component for the entire interval.

INPUT:

- `all` – bool (default: `False`); if `True`, return a list of all square roots.

- `s_imag` – a string that defines a real number (or something whose string representation defines a number)
- `pad` – an integer at least 0.
- `min_prec` – number will have at least this many bits of precision, no matter what.

EXAMPLES:

```
sage: ComplexIntervalFieldElement('2.3')
2.3000000000000000?
sage: ComplexIntervalFieldElement('2.3','1.1')
2.3000000000000000? + 1.1000000000000000*I
sage: ComplexIntervalFieldElement(10)
10
sage: ComplexIntervalFieldElement(10,10)
10 + 10*I
sage: ComplexIntervalFieldElement(1.0000000000000000000000000000,2)
1 + 2*I
sage: ComplexIntervalFieldElement(1,2.000000000000000000000000)
1 + 2*I
sage: ComplexIntervalFieldElement(1.234567890123456789012345, 5.43210987654321987654321)
1.234567890123456789012350? + 5.4321098765432198765432000?*I
```

TESTS:

Make sure we've rounded up $\log(10, 2)$ enough to guarantee sufficient precision ([trac ticket #10164](#)). This is a little tricky because at the time of writing, we don't support intervals long enough to trip the error. However, at least we can make sure that we either do it correctly or fail noisily:

```
sage: c_CIFE = sage.rings.complex_interval.create_ComplexIntervalFieldElement
sage: for kp in range(2,6):
...     s = '1.' + '0'*10**kp + '1'
...     try:
...         assert c_CIFE(s,0).real()-1 != 0
...         assert c_CIFE(0,s).imag()-1 != 0
...     except TypeError:
...         pass
```

`sage.rings.complex_interval.is_ComplexIntervalFieldElement(x)`
Check if `x` is a `ComplexIntervalFieldElement`.

EXAMPLES:

```
sage: from sage.rings.complex_interval import is_ComplexIntervalFieldElement as is_CIFE
sage: is_CIFE(CIF(2))
True
sage: is_CIFE(CC(2))
False
```

`sage.rings.complex_interval.make_ComplexIntervalFieldElement0` (*fld, re, im*)
Construct a `ComplexIntervalFieldElement` for pickling.

TESTS:

```
sage: a = CIF(1 + I)
sage: loads(dumps(a)) == a # indirect doctest
True
```

INDICES AND TABLES

- Index
- Module Index
- Search Page

r

`sage.rings.complex_double`, 121
`sage.rings.complex_field`, 139
`sage.rings.complex_interval`, 185
`sage.rings.complex_interval_field`, 179
`sage.rings.complex_mpc`, 163
`sage.rings.complex_number`, 145
`sage.rings.real_double`, 3
`sage.rings.real_interval_absolute`, 105
`sage.rings.real_interval_field`, 103
`sage.rings.real_lazy`, 111
`sage.rings.real_mpfi`, 69
`sage.rings.real_mpfr`, 25

A

`abs()` (sage.rings.complex_double.ComplexDoubleElement method), 122
`abs()` (sage.rings.real_double.RealDoubleElement method), 3
`abs()` (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 106
`abs2()` (sage.rings.complex_double.ComplexDoubleElement method), 122
`absolute_diameter()` (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 106
`absolute_diameter()` (sage.rings.real_mpf.RealIntervalFieldElement method), 73
`absprec()` (sage.rings.real_interval_absolute.RealIntervalAbsoluteField_class method), 110
`acosh()` (sage.rings.real_double.RealDoubleElement method), 4
`additive_order()` (sage.rings.complex_number.ComplexNumber method), 146
`agm()` (sage.rings.complex_double.ComplexDoubleElement method), 122
`agm()` (sage.rings.complex_mpc.MPCComplexNumber method), 167
`agm()` (sage.rings.complex_number.ComplexNumber method), 146
`agm()` (sage.rings.real_double.RealDoubleElement method), 4
`agm()` (sage.rings.real_mpfr.RealNumber method), 33
`alea()` (sage.rings.real_mpf.RealIntervalFieldElement method), 73
`algdep()` (sage.rings.complex_double.ComplexDoubleElement method), 123
`algdep()` (sage.rings.complex_number.ComplexNumber method), 147
`algdep()` (sage.rings.real_double.RealDoubleElement method), 4
`algdep()` (sage.rings.real_mpf.RealIntervalFieldElement method), 73
`algdep()` (sage.rings.real_mpfr.RealNumber method), 34
`algebraic_closure()` (sage.rings.complex_double.ComplexDoubleField_class method), 134
`algebraic_closure()` (sage.rings.complex_field.ComplexField_class method), 140
`algebraic_closure()` (sage.rings.real_double.RealDoubleField_class method), 19
`algebraic_closure()` (sage.rings.real_lazy.LazyField method), 114
`algebraic_closure()` (sage.rings.real_mpfr.RealField_class method), 28
`algebraic_dependancy()` (sage.rings.complex_mpc.MPCComplexNumber method), 167
`algebraic_dependancy()` (sage.rings.complex_number.ComplexNumber method), 147
`algebraic_dependency()` (sage.rings.complex_mpc.MPCComplexNumber method), 167
`algebraic_dependency()` (sage.rings.real_double.RealDoubleElement method), 4
`algebraic_dependency()` (sage.rings.real_mpfr.RealNumber method), 34
`approx()` (sage.rings.real_lazy.LazyFieldElement method), 115
`approx()` (sage.rings.real_lazy.LazyNamedUnop method), 116
`arccos()` (sage.rings.complex_double.ComplexDoubleElement method), 123
`arccos()` (sage.rings.complex_mpc.MPCComplexNumber method), 167
`arccos()` (sage.rings.complex_number.ComplexNumber method), 148
`arccos()` (sage.rings.real_double.RealDoubleElement method), 5

`arccos()` (sage.rings.real_mpf.RealIntervalFieldElement method), 73
`arccos()` (sage.rings.real_mpfr.RealNumber method), 34
`arccosh()` (sage.rings.complex_double.ComplexDoubleElement method), 123
`arccosh()` (sage.rings.complex_mpc.MPCComplexNumber method), 168
`arccosh()` (sage.rings.complex_number.ComplexNumber method), 148
`arccosh()` (sage.rings.real_mpf.RealIntervalFieldElement method), 74
`arccosh()` (sage.rings.real_mpfr.RealNumber method), 34
`arccot()` (sage.rings.complex_double.ComplexDoubleElement method), 123
`arccoth()` (sage.rings.complex_double.ComplexDoubleElement method), 124
`arccoth()` (sage.rings.complex_mpc.MPCComplexNumber method), 168
`arccoth()` (sage.rings.complex_number.ComplexNumber method), 148
`arccoth()` (sage.rings.real_mpf.RealIntervalFieldElement method), 74
`arccoth()` (sage.rings.real_mpfr.RealNumber method), 35
`arccsc()` (sage.rings.complex_double.ComplexDoubleElement method), 124
`arccsch()` (sage.rings.complex_double.ComplexDoubleElement method), 124
`arccsch()` (sage.rings.complex_mpc.MPCComplexNumber method), 168
`arccsch()` (sage.rings.complex_number.ComplexNumber method), 148
`arccsch()` (sage.rings.real_mpf.RealIntervalFieldElement method), 74
`arccsch()` (sage.rings.real_mpfr.RealNumber method), 35
`arcsec()` (sage.rings.complex_double.ComplexDoubleElement method), 124
`arcsech()` (sage.rings.complex_double.ComplexDoubleElement method), 124
`arcsech()` (sage.rings.complex_mpc.MPCComplexNumber method), 168
`arcsech()` (sage.rings.complex_number.ComplexNumber method), 148
`arcsech()` (sage.rings.real_mpf.RealIntervalFieldElement method), 74
`arcsech()` (sage.rings.real_mpfr.RealNumber method), 35
`arcsin()` (sage.rings.complex_double.ComplexDoubleElement method), 124
`arcsin()` (sage.rings.complex_mpc.MPCComplexNumber method), 168
`arcsin()` (sage.rings.complex_number.ComplexNumber method), 148
`arcsin()` (sage.rings.real_double.RealDoubleElement method), 5
`arcsin()` (sage.rings.real_mpf.RealIntervalFieldElement method), 74
`arcsin()` (sage.rings.real_mpfr.RealNumber method), 35
`arcsinh()` (sage.rings.complex_double.ComplexDoubleElement method), 124
`arcsinh()` (sage.rings.complex_mpc.MPCComplexNumber method), 168
`arcsinh()` (sage.rings.complex_number.ComplexNumber method), 149
`arcsinh()` (sage.rings.real_double.RealDoubleElement method), 5
`arcsinh()` (sage.rings.real_mpf.RealIntervalFieldElement method), 75
`arcsinh()` (sage.rings.real_mpfr.RealNumber method), 35
`arctan()` (sage.rings.complex_double.ComplexDoubleElement method), 125
`arctan()` (sage.rings.complex_mpc.MPCComplexNumber method), 169
`arctan()` (sage.rings.complex_number.ComplexNumber method), 149
`arctan()` (sage.rings.real_double.RealDoubleElement method), 5
`arctan()` (sage.rings.real_mpf.RealIntervalFieldElement method), 75
`arctan()` (sage.rings.real_mpfr.RealNumber method), 35
`arctanh()` (sage.rings.complex_double.ComplexDoubleElement method), 125
`arctanh()` (sage.rings.complex_mpc.MPCComplexNumber method), 169
`arctanh()` (sage.rings.complex_number.ComplexNumber method), 149
`arctanh()` (sage.rings.real_double.RealDoubleElement method), 5
`arctanh()` (sage.rings.real_mpf.RealIntervalFieldElement method), 75
`arctanh()` (sage.rings.real_mpfr.RealNumber method), 36
`arg()` (sage.rings.complex_double.ComplexDoubleElement method), 125

arg() (sage.rings.complex_interval.ComplexIntervalFieldElement method), 185
 arg() (sage.rings.complex_number.ComplexNumber method), 149
 argument() (sage.rings.complex_double.ComplexDoubleElement method), 125
 argument() (sage.rings.complex_interval.ComplexIntervalFieldElement method), 185
 argument() (sage.rings.complex_mpc.MPCComplexNumber method), 169
 argument() (sage.rings.complex_number.ComplexNumber method), 149

B

base (sage.rings.real_mpfr.RealLiteral attribute), 33
 bisection() (sage.rings.complex_interval.ComplexIntervalFieldElement method), 186
 bisection() (sage.rings.real_mpfir.RealIntervalFieldElement method), 75

C

catalan_constant() (sage.rings.real_mpfr.RealField_class method), 28
 CCtoCDF (class in sage.rings.complex_number), 145
 CCtoMPC (class in sage.rings.complex_mpc), 163
 ceil() (sage.rings.real_double.RealDoubleElement method), 5
 ceil() (sage.rings.real_mpfir.RealIntervalFieldElement method), 76
 ceil() (sage.rings.real_mpfr.RealNumber method), 36
 ceiling() (sage.rings.real_double.RealDoubleElement method), 6
 ceiling() (sage.rings.real_mpfir.RealIntervalFieldElement method), 76
 ceiling() (sage.rings.real_mpfr.RealNumber method), 36
 center() (sage.rings.complex_interval.ComplexIntervalFieldElement method), 186
 center() (sage.rings.real_mpfir.RealIntervalFieldElement method), 77
 characteristic() (sage.rings.complex_double.ComplexDoubleField_class method), 134
 characteristic() (sage.rings.complex_field.ComplexField_class method), 140
 characteristic() (sage.rings.complex_interval_field.ComplexIntervalField_class method), 180
 characteristic() (sage.rings.complex_mpc.MPCComplexField_class method), 165
 characteristic() (sage.rings.real_double.RealDoubleField_class method), 19
 characteristic() (sage.rings.real_mpfir.RealIntervalField_class method), 98
 characteristic() (sage.rings.real_mpfr.RealField_class method), 28
 cmp_abs() (in module sage.rings.complex_number), 159
 complex_field() (sage.rings.real_double.RealDoubleField_class method), 19
 complex_field() (sage.rings.real_mpfir.RealIntervalField_class method), 98
 complex_field() (sage.rings.real_mpfr.RealField_class method), 28
 ComplexDoubleElement (class in sage.rings.complex_double), 121
 ComplexDoubleField() (in module sage.rings.complex_double), 134
 ComplexDoubleField_class (class in sage.rings.complex_double), 134
 ComplexField() (in module sage.rings.complex_field), 139
 ComplexField_class (class in sage.rings.complex_field), 139
 ComplexIntervalField() (in module sage.rings.complex_interval_field), 179
 ComplexIntervalField_class (class in sage.rings.complex_interval_field), 179
 ComplexIntervalFieldElement (class in sage.rings.complex_interval), 185
 ComplexLazyField() (in module sage.rings.real_lazy), 111
 ComplexLazyField_class (class in sage.rings.real_lazy), 111
 ComplexNumber (class in sage.rings.complex_number), 145
 conj() (sage.rings.complex_double.ComplexDoubleElement method), 125
 conjugate() (sage.rings.complex_double.ComplexDoubleElement method), 125
 conjugate() (sage.rings.complex_interval.ComplexIntervalFieldElement method), 187
 conjugate() (sage.rings.complex_mpc.MPCComplexNumber method), 169

`conjugate()` (sage.rings.complex_number.ComplexNumber method), 149
`conjugate()` (sage.rings.real_double.RealDoubleElement method), 6
`conjugate()` (sage.rings.real_mpfr.RealNumber method), 36
`construction()` (sage.rings.complex_double.ComplexDoubleField_class method), 134
`construction()` (sage.rings.complex_field.ComplexField_class method), 141
`construction()` (sage.rings.real_double.RealDoubleField_class method), 19
`construction()` (sage.rings.real_lazy.ComplexLazyField_class method), 112
`construction()` (sage.rings.real_lazy.RealLazyField_class method), 118
`construction()` (sage.rings.real_mpmf.RealIntervalField_class method), 98
`construction()` (sage.rings.real_mpfr.RealField_class method), 29
`contains_zero()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 187
`contains_zero()` (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 107
`contains_zero()` (sage.rings.real_mpmf.RealIntervalFieldElement method), 77
`cos()` (sage.rings.complex_double.ComplexDoubleElement method), 126
`cos()` (sage.rings.complex_mpc.MPCComplexNumber method), 169
`cos()` (sage.rings.complex_number.ComplexNumber method), 149
`cos()` (sage.rings.real_double.RealDoubleElement method), 6
`cos()` (sage.rings.real_mpmf.RealIntervalFieldElement method), 77
`cos()` (sage.rings.real_mpfr.RealNumber method), 37
`cosh()` (sage.rings.complex_double.ComplexDoubleElement method), 126
`cosh()` (sage.rings.complex_mpc.MPCComplexNumber method), 170
`cosh()` (sage.rings.complex_number.ComplexNumber method), 150
`cosh()` (sage.rings.real_double.RealDoubleElement method), 6
`cosh()` (sage.rings.real_mpmf.RealIntervalFieldElement method), 77
`cosh()` (sage.rings.real_mpfr.RealNumber method), 37
`cot()` (sage.rings.complex_double.ComplexDoubleElement method), 126
`cot()` (sage.rings.real_mpmf.RealIntervalFieldElement method), 77
`cot()` (sage.rings.real_mpfr.RealNumber method), 37
`cotan()` (sage.rings.complex_mpc.MPCComplexNumber method), 170
`cotan()` (sage.rings.complex_number.ComplexNumber method), 150
`coth()` (sage.rings.complex_double.ComplexDoubleElement method), 126
`coth()` (sage.rings.complex_mpc.MPCComplexNumber method), 170
`coth()` (sage.rings.complex_number.ComplexNumber method), 150
`coth()` (sage.rings.real_double.RealDoubleElement method), 6
`coth()` (sage.rings.real_mpmf.RealIntervalFieldElement method), 78
`coth()` (sage.rings.real_mpfr.RealNumber method), 37
`create_ComplexIntervalFieldElement()` (in module sage.rings.complex_interval), 191
`create_ComplexNumber()` (in module sage.rings.complex_number), 160
`create_key()` (sage.rings.real_interval_absolute.Factory method), 105
`create_object()` (sage.rings.real_interval_absolute.Factory method), 105
`create_RealField()` (in module sage.rings.real_mpfr), 61
`create_RealNumber()` (in module sage.rings.real_mpfr), 62
`crosses_log_branch_cut()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 187
`csc()` (sage.rings.complex_double.ComplexDoubleElement method), 126
`csc()` (sage.rings.complex_mpc.MPCComplexNumber method), 170
`csc()` (sage.rings.complex_number.ComplexNumber method), 150
`csc()` (sage.rings.real_mpmf.RealIntervalFieldElement method), 78
`csc()` (sage.rings.real_mpfr.RealNumber method), 37
`csch()` (sage.rings.complex_double.ComplexDoubleElement method), 127
`csch()` (sage.rings.complex_mpc.MPCComplexNumber method), 170

csch() (sage.rings.complex_number.ComplexNumber method), 150
 csch() (sage.rings.real_double.RealDoubleElement method), 6
 csch() (sage.rings.real_mpfi.RealIntervalFieldElement method), 78
 csch() (sage.rings.real_mpfr.RealNumber method), 37
 cube_root() (sage.rings.real_double.RealDoubleElement method), 7
 cube_root() (sage.rings.real_mpfr.RealNumber method), 37

D

depth() (sage.rings.real_lazy.LazyBinop method), 113
 depth() (sage.rings.real_lazy.LazyFieldElement method), 115
 depth() (sage.rings.real_lazy.LazyUnop method), 116
 depth() (sage.rings.real_lazy.LazyWrapper method), 117
 diameter() (sage.rings.complex_interval.ComplexIntervalFieldElement method), 187
 diameter() (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 107
 diameter() (sage.rings.real_mpfi.RealIntervalFieldElement method), 78
 dilog() (sage.rings.complex_double.ComplexDoubleElement method), 127
 dilog() (sage.rings.complex_mpc.MPCComplexNumber method), 170
 dilog() (sage.rings.complex_number.ComplexNumber method), 150
 double_toRR (class in sage.rings.real_mpfr), 63

E

eint() (sage.rings.real_mpfr.RealNumber method), 38
 endpoints() (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 107
 endpoints() (sage.rings.real_mpfi.RealIntervalFieldElement method), 78
 epsilon() (sage.rings.real_mpfr.RealNumber method), 38
 erf() (sage.rings.real_double.RealDoubleElement method), 7
 erf() (sage.rings.real_mpfr.RealNumber method), 39
 erfc() (sage.rings.real_mpfr.RealNumber method), 39
 eta() (sage.rings.complex_double.ComplexDoubleElement method), 127
 eta() (sage.rings.complex_mpc.MPCComplexNumber method), 171
 eta() (sage.rings.complex_number.ComplexNumber method), 151
 euler_constant() (sage.rings.real_double.RealDoubleField_class method), 19
 euler_constant() (sage.rings.real_mpfi.RealIntervalField_class method), 98
 euler_constant() (sage.rings.real_mpfr.RealField_class method), 29
 eval() (sage.rings.real_lazy.LazyAlgebraic method), 112
 eval() (sage.rings.real_lazy.LazyBinop method), 113
 eval() (sage.rings.real_lazy.LazyConstant method), 114
 eval() (sage.rings.real_lazy.LazyFieldElement method), 115
 eval() (sage.rings.real_lazy.LazyNamedUnop method), 116
 eval() (sage.rings.real_lazy.LazyUnop method), 117
 eval() (sage.rings.real_lazy.LazyWrapper method), 117
 exact_rational() (sage.rings.real_mpfr.RealNumber method), 39
 exp() (sage.rings.complex_double.ComplexDoubleElement method), 128
 exp() (sage.rings.complex_interval.ComplexIntervalFieldElement method), 187
 exp() (sage.rings.complex_mpc.MPCComplexNumber method), 171
 exp() (sage.rings.complex_number.ComplexNumber method), 152
 exp() (sage.rings.real_double.RealDoubleElement method), 7
 exp() (sage.rings.real_mpfi.RealIntervalFieldElement method), 79
 exp() (sage.rings.real_mpfr.RealNumber method), 40
 exp10() (sage.rings.real_double.RealDoubleElement method), 7

`exp10()` (sage.rings.real_mpfr.RealNumber method), 40
`exp2()` (sage.rings.real_double.RealDoubleElement method), 8
`exp2()` (sage.rings.real_mpf. RealIntervalFieldElement method), 79
`exp2()` (sage.rings.real_mpfr.RealNumber method), 40
`expm1()` (sage.rings.real_mpfr.RealNumber method), 40

F

`factorial()` (sage.rings.real_double.RealDoubleField_class method), 19
`factorial()` (sage.rings.real_mpf. RealIntervalFieldElement method), 79
`factorial()` (sage.rings.real_mpfr.RealField_class method), 29
`Factory` (class in sage.rings.real_interval_absolute), 105
`FloatToCDF` (class in sage.rings.complex_double), 137
`floor()` (sage.rings.real_double.RealDoubleElement method), 8
`floor()` (sage.rings.real_mpf. RealIntervalFieldElement method), 80
`floor()` (sage.rings.real_mpfr.RealNumber method), 41
`fp_rank()` (sage.rings.real_mpfr.RealNumber method), 41
`fp_rank_delta()` (sage.rings.real_mpfr.RealNumber method), 41
`fp_rank_diameter()` (sage.rings.real_mpf. RealIntervalFieldElement method), 80
`frac()` (sage.rings.real_double.RealDoubleElement method), 8
`frac()` (sage.rings.real_mpfr.RealNumber method), 42

G

`gamma()` (sage.rings.complex_double.ComplexDoubleElement method), 128
`gamma()` (sage.rings.complex_mpc.MPCComplexNumber method), 171
`gamma()` (sage.rings.complex_number.ComplexNumber method), 152
`gamma()` (sage.rings.real_double.RealDoubleElement method), 8
`gamma()` (sage.rings.real_mpf. RealIntervalFieldElement method), 81
`gamma()` (sage.rings.real_mpfr.RealNumber method), 42
`gamma_inc()` (sage.rings.complex_double.ComplexDoubleElement method), 129
`gamma_inc()` (sage.rings.complex_mpc.MPCComplexNumber method), 172
`gamma_inc()` (sage.rings.complex_number.ComplexNumber method), 152
`gen()` (sage.rings.complex_double.ComplexDoubleField_class method), 135
`gen()` (sage.rings.complex_field.ComplexField_class method), 141
`gen()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 181
`gen()` (sage.rings.complex_mpc.MPCComplexField_class method), 165
`gen()` (sage.rings.real_double.RealDoubleField_class method), 19
`gen()` (sage.rings.real_lazy.ComplexLazyField_class method), 112
`gen()` (sage.rings.real_lazy.RealLazyField_class method), 118
`gen()` (sage.rings.real_mpf. RealIntervalField_class method), 98
`gen()` (sage.rings.real_mpfr.RealField_class method), 29
`gens()` (sage.rings.real_mpf. RealIntervalField_class method), 98
`gens()` (sage.rings.real_mpfr.RealField_class method), 29

H

`hex()` (sage.rings.real_mpfr.RealNumber method), 42
`hypot()` (sage.rings.real_double.RealDoubleElement method), 8

I

`imag()` (sage.rings.complex_double.ComplexDoubleElement method), 129
`imag()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 187

`imag()` (sage.rings.complex_mpc.MPCComplexNumber method), 172
`imag()` (sage.rings.complex_number.ComplexNumber method), 152
`imag()` (sage.rings.real_double.RealDoubleElement method), 9
`imag()` (sage.rings.real_mpfr.RealNumber method), 43
`imag_part()` (sage.rings.complex_double.ComplexDoubleElement method), 129
`imag_part()` (sage.rings.complex_number.ComplexNumber method), 153
`int_toRR` (class in sage.rings.real_mpfr), 64
`integer_part()` (sage.rings.real_double.RealDoubleElement method), 9
`integer_part()` (sage.rings.real_mpfr.RealNumber method), 43
`INTEGERtoMPC` (class in sage.rings.complex_mpc), 164
`intersection()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 188
`intersection()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 81
`interval_field()` (sage.rings.real_lazy.ComplexLazyField_class method), 112
`interval_field()` (sage.rings.real_lazy.LazyField method), 114
`interval_field()` (sage.rings.real_lazy.RealLazyField_class method), 119
`is_ComplexDoubleElement()` (in module sage.rings.complex_double), 137
`is_ComplexDoubleField()` (in module sage.rings.complex_double), 137
`is_ComplexField()` (in module sage.rings.complex_field), 143
`is_ComplexIntervalField()` (in module sage.rings.complex_interval_field), 183
`is_ComplexIntervalFieldElement()` (in module sage.rings.complex_interval), 192
`is_ComplexNumber()` (in module sage.rings.complex_number), 160
`is_exact()` (sage.rings.complex_double.ComplexDoubleField_class method), 135
`is_exact()` (sage.rings.complex_field.ComplexField_class method), 141
`is_exact()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 188
`is_exact()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 181
`is_exact()` (sage.rings.complex_mpc.MPCComplexField_class method), 165
`is_exact()` (sage.rings.real_double.RealDoubleField_class method), 20
`is_exact()` (sage.rings.real_mpfi.RealIntervalField_class method), 99
`is_exact()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 82
`is_exact()` (sage.rings.real_mpfr.RealField_class method), 29
`is_field()` (sage.rings.complex_field.ComplexField_class method), 141
`is_field()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 181
`is_finite()` (sage.rings.complex_field.ComplexField_class method), 141
`is_finite()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 181
`is_finite()` (sage.rings.complex_mpc.MPCComplexField_class method), 165
`is_finite()` (sage.rings.real_double.RealDoubleField_class method), 20
`is_finite()` (sage.rings.real_mpfi.RealIntervalField_class method), 99
`is_finite()` (sage.rings.real_mpfr.RealField_class method), 30
`is_imaginary()` (sage.rings.complex_mpc.MPCComplexNumber method), 172
`is_imaginary()` (sage.rings.complex_number.ComplexNumber method), 153
`is_infinity()` (sage.rings.complex_double.ComplexDoubleElement method), 129
`is_infinity()` (sage.rings.complex_number.ComplexNumber method), 153
`is_infinity()` (sage.rings.real_double.RealDoubleElement method), 9
`is_infinity()` (sage.rings.real_mpfr.RealNumber method), 43
`is_int()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 82
`is_integer()` (sage.rings.complex_double.ComplexDoubleElement method), 129
`is_integer()` (sage.rings.complex_number.ComplexNumber method), 153
`is_integer()` (sage.rings.real_double.RealDoubleElement method), 9
`is_integer()` (sage.rings.real_mpfr.RealNumber method), 44
`is_NaN()` (sage.rings.real_double.RealDoubleElement method), 9

`is_NaN()` (`sage.rings.real_mprf.RealIntervalFieldElement` method), 82
`is_NaN()` (`sage.rings.real_mprf.RealNumber` method), 43
`is_negative()` (`sage.rings.real_interval_absolute.RealIntervalAbsoluteElement` method), 107
`is_negative_infinity()` (`sage.rings.complex_double.ComplexDoubleElement` method), 129
`is_negative_infinity()` (`sage.rings.complex_number.ComplexNumber` method), 153
`is_negative_infinity()` (`sage.rings.real_double.RealDoubleElement` method), 10
`is_negative_infinity()` (`sage.rings.real_mprf.RealNumber` method), 44
`is_positive()` (`sage.rings.real_interval_absolute.RealIntervalAbsoluteElement` method), 108
`is_positive_infinity()` (`sage.rings.complex_double.ComplexDoubleElement` method), 130
`is_positive_infinity()` (`sage.rings.complex_number.ComplexNumber` method), 154
`is_positive_infinity()` (`sage.rings.real_double.RealDoubleElement` method), 10
`is_positive_infinity()` (`sage.rings.real_mprf.RealNumber` method), 44
`is_real()` (`sage.rings.complex_mpc.MPCComplexNumber` method), 172
`is_real()` (`sage.rings.complex_number.ComplexNumber` method), 154
`is_real()` (`sage.rings.real_mprf.RealNumber` method), 44
`is_RealDoubleElement()` (in module `sage.rings.real_double`), 22
`is_RealDoubleField()` (in module `sage.rings.real_double`), 22
`is_RealField()` (in module `sage.rings.real_mprf`), 64
`is_RealIntervalField()` (in module `sage.rings.real_interval_field`), 103
`is_RealIntervalField()` (in module `sage.rings.real_mprf`), 101
`is_RealIntervalFieldElement()` (in module `sage.rings.real_interval_field`), 103
`is_RealIntervalFieldElement()` (in module `sage.rings.real_mprf`), 101
`is_RealNumber()` (in module `sage.rings.real_mprf`), 64
`is_square()` (`sage.rings.complex_double.ComplexDoubleElement` method), 130
`is_square()` (`sage.rings.complex_interval.ComplexIntervalFieldElement` method), 188
`is_square()` (`sage.rings.complex_mpc.MPCComplexNumber` method), 173
`is_square()` (`sage.rings.complex_number.ComplexNumber` method), 154
`is_square()` (`sage.rings.real_double.RealDoubleElement` method), 10
`is_square()` (`sage.rings.real_mprf.RealNumber` method), 45
`is_unit()` (`sage.rings.real_mprf.RealNumber` method), 45

J

`j0()` (`sage.rings.real_mprf.RealNumber` method), 45
`j1()` (`sage.rings.real_mprf.RealNumber` method), 45
`jn()` (`sage.rings.real_mprf.RealNumber` method), 45

L

`late_import()` (in module `sage.rings.complex_field`), 143
`late_import()` (in module `sage.rings.complex_interval_field`), 183
`late_import()` (in module `sage.rings.complex_mpc`), 177
`LazyAlgebraic` (class in `sage.rings.real_lazy`), 112
`LazyBinop` (class in `sage.rings.real_lazy`), 113
`LazyConstant` (class in `sage.rings.real_lazy`), 113
`LazyField` (class in `sage.rings.real_lazy`), 114
`LazyFieldElement` (class in `sage.rings.real_lazy`), 115
`LazyNamedUnop` (class in `sage.rings.real_lazy`), 115
`LazyUnop` (class in `sage.rings.real_lazy`), 116
`LazyWrapper` (class in `sage.rings.real_lazy`), 117
`LazyWrapperMorphism` (class in `sage.rings.real_lazy`), 117
`literal` (`sage.rings.real_mprf.RealLiteral` attribute), 33

[log\(\)](#) (sage.rings.complex_double.ComplexDoubleElement method), 130
[log\(\)](#) (sage.rings.complex_interval.ComplexIntervalFieldElement method), 188
[log\(\)](#) (sage.rings.complex_mpc.MPCComplexNumber method), 173
[log\(\)](#) (sage.rings.complex_number.ComplexNumber method), 154
[log\(\)](#) (sage.rings.real_double.RealDoubleElement method), 10
[log\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 82
[log\(\)](#) (sage.rings.real_mpfr.RealNumber method), 46
[log10\(\)](#) (sage.rings.complex_double.ComplexDoubleElement method), 130
[log10\(\)](#) (sage.rings.real_double.RealDoubleElement method), 11
[log10\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 83
[log10\(\)](#) (sage.rings.real_mpfr.RealNumber method), 46
[log1p\(\)](#) (sage.rings.real_mpfr.RealNumber method), 46
[log2\(\)](#) (sage.rings.real_double.RealDoubleElement method), 11
[log2\(\)](#) (sage.rings.real_double.RealDoubleField_class method), 20
[log2\(\)](#) (sage.rings.real_mpfi.RealIntervalField_class method), 99
[log2\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 83
[log2\(\)](#) (sage.rings.real_mpfr.RealField_class method), 30
[log2\(\)](#) (sage.rings.real_mpfr.RealNumber method), 47
[log_b\(\)](#) (sage.rings.complex_double.ComplexDoubleElement method), 130
[log_gamma\(\)](#) (sage.rings.real_mpfr.RealNumber method), 47
[logabs\(\)](#) (sage.rings.complex_double.ComplexDoubleElement method), 131
[logpi\(\)](#) (sage.rings.real_double.RealDoubleElement method), 11
[lower\(\)](#) (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 108
[lower\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 83

M

[magnitude\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 84
[make_ComplexIntervalFieldElement0\(\)](#) (in module sage.rings.complex_interval), 192
[make_ComplexNumber0\(\)](#) (in module sage.rings.complex_number), 161
[make_element\(\)](#) (in module sage.rings.real_lazy), 119
[max\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 84
[midpoint\(\)](#) (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 108
[mignitude\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 85
[min\(\)](#) (sage.rings.real_mpfi.RealIntervalFieldElement method), 85
[MPCComplexField\(\)](#) (in module sage.rings.complex_mpc), 164
[MPCComplexField_class](#) (class in sage.rings.complex_mpc), 164
[MPCComplexNumber](#) (class in sage.rings.complex_mpc), 166
[MPCtoMPC](#) (class in sage.rings.complex_mpc), 176
[mpfi_prec\(\)](#) (sage.rings.real_interval_absolute.RealIntervalAbsoluteElement method), 108
[mpfr_get_exp_max\(\)](#) (in module sage.rings.real_mpfr), 65
[mpfr_get_exp_max_max\(\)](#) (in module sage.rings.real_mpfr), 65
[mpfr_get_exp_min\(\)](#) (in module sage.rings.real_mpfr), 65
[mpfr_get_exp_min_min\(\)](#) (in module sage.rings.real_mpfr), 65
[mpfr_prec_max\(\)](#) (in module sage.rings.real_mpfr), 66
[mpfr_prec_min\(\)](#) (in module sage.rings.real_mpfr), 66
[mpfr_set_exp_max\(\)](#) (in module sage.rings.real_mpfr), 66
[mpfr_set_exp_min\(\)](#) (in module sage.rings.real_mpfr), 66
[MpfrOp](#) (class in sage.rings.real_interval_absolute), 105
[MPFRtoMPC](#) (class in sage.rings.complex_mpc), 177
[multiplicative_order\(\)](#) (sage.rings.complex_number.ComplexNumber method), 155

`multiplicative_order()` (sage.rings.real_double.RealDoubleElement method), 12
`multiplicative_order()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 86
`multiplicative_order()` (sage.rings.real_mpfr.RealNumber method), 48

N

`name()` (sage.rings.complex_mpc.MPCComplexField_class method), 165
`name()` (sage.rings.real_double.RealDoubleField_class method), 20
`name()` (sage.rings.real_mpfi.RealIntervalField_class method), 99
`name()` (sage.rings.real_mpfr.RealField_class method), 30
`NaN()` (sage.rings.real_double.RealDoubleElement method), 3
`nan()` (sage.rings.real_double.RealDoubleElement method), 12
`NaN()` (sage.rings.real_double.RealDoubleField_class method), 18
`nan()` (sage.rings.real_double.RealDoubleField_class method), 20
`nearby_rational()` (sage.rings.real_mpfr.RealNumber method), 48
`nextabove()` (sage.rings.real_mpfr.RealNumber method), 49
`nextbelow()` (sage.rings.real_mpfr.RealNumber method), 49
`nexttoward()` (sage.rings.real_mpfr.RealNumber method), 49
`ngens()` (sage.rings.complex_double.ComplexDoubleField_class method), 135
`ngens()` (sage.rings.complex_field.ComplexField_class method), 141
`ngens()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 181
`ngens()` (sage.rings.complex_mpc.MPCComplexField_class method), 166
`ngens()` (sage.rings.real_double.RealDoubleField_class method), 20
`ngens()` (sage.rings.real_mpfi.RealIntervalField_class method), 99
`ngens()` (sage.rings.real_mpfr.RealField_class method), 30
`norm()` (sage.rings.complex_double.ComplexDoubleElement method), 131
`norm()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 189
`norm()` (sage.rings.complex_mpc.MPCComplexNumber method), 173
`norm()` (sage.rings.complex_number.ComplexNumber method), 155
`nth_root()` (sage.rings.complex_double.ComplexDoubleElement method), 131
`nth_root()` (sage.rings.complex_mpc.MPCComplexNumber method), 173
`nth_root()` (sage.rings.complex_number.ComplexNumber method), 156
`nth_root()` (sage.rings.real_double.RealDoubleElement method), 12
`nth_root()` (sage.rings.real_mpfr.RealNumber method), 50

O

`overlaps()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 189
`overlaps()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 86

P

`pi()` (sage.rings.complex_double.ComplexDoubleField_class method), 135
`pi()` (sage.rings.complex_field.ComplexField_class method), 141
`pi()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 181
`pi()` (sage.rings.real_double.RealDoubleField_class method), 20
`pi()` (sage.rings.real_mpfi.RealIntervalField_class method), 99
`pi()` (sage.rings.real_mpfr.RealField_class method), 30
`plot()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 190
`plot()` (sage.rings.complex_number.ComplexNumber method), 156
`pool_stats()` (in module sage.rings.real_double), 22
`prec()` (sage.rings.complex_double.ComplexDoubleElement method), 132
`prec()` (sage.rings.complex_double.ComplexDoubleField_class method), 135

`prec()` (sage.rings.complex_field.ComplexField_class method), 142
`prec()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 190
`prec()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 181
`prec()` (sage.rings.complex_mpc.MPCComplexField_class method), 166
`prec()` (sage.rings.complex_mpc.MPCComplexNumber method), 174
`prec()` (sage.rings.complex_number.ComplexNumber method), 156
`prec()` (sage.rings.real_double.RealDoubleElement method), 12
`prec()` (sage.rings.real_double.RealDoubleField_class method), 21
`prec()` (sage.rings.real_mpfi.RealIntervalField_class method), 99
`prec()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 86
`prec()` (sage.rings.real_mpfr.RealField_class method), 30
`prec()` (sage.rings.real_mpfr.RealNumber method), 52
`precision()` (sage.rings.complex_double.ComplexDoubleField_class method), 135
`precision()` (sage.rings.complex_field.ComplexField_class method), 142
`precision()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 182
`precision()` (sage.rings.real_double.RealDoubleField_class method), 21
`precision()` (sage.rings.real_mpfi.RealIntervalField_class method), 100
`precision()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 87
`precision()` (sage.rings.real_mpfr.RealField_class method), 31
`precision()` (sage.rings.real_mpfr.RealNumber method), 52
`psi()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 87

Q

`QQtoRR` (class in sage.rings.real_mpfr), 26

R

`random_element()` (sage.rings.complex_double.ComplexDoubleField_class method), 135
`random_element()` (sage.rings.complex_field.ComplexField_class method), 142
`random_element()` (sage.rings.complex_interval_field.ComplexIntervalField_class method), 182
`random_element()` (sage.rings.complex_mpc.MPCComplexField_class method), 166
`random_element()` (sage.rings.real_double.RealDoubleField_class method), 21
`random_element()` (sage.rings.real_mpfi.RealIntervalField_class method), 100
`random_element()` (sage.rings.real_mpfr.RealField_class method), 31
`real()` (sage.rings.complex_double.ComplexDoubleElement method), 132
`real()` (sage.rings.complex_interval.ComplexIntervalFieldElement method), 190
`real()` (sage.rings.complex_mpc.MPCComplexNumber method), 174
`real()` (sage.rings.complex_number.ComplexNumber method), 156
`real()` (sage.rings.real_double.RealDoubleElement method), 13
`real()` (sage.rings.real_mpfi.RealIntervalFieldElement method), 87
`real()` (sage.rings.real_mpfr.RealNumber method), 52
`real_double_field()` (sage.rings.complex_double.ComplexDoubleField_class method), 136
`real_part()` (sage.rings.complex_double.ComplexDoubleElement method), 132
`real_part()` (sage.rings.complex_number.ComplexNumber method), 157
`RealDoubleElement` (class in sage.rings.real_double), 3
`RealDoubleField()` (in module sage.rings.real_double), 18
`RealDoubleField_class` (class in sage.rings.real_double), 18
`RealField()` (in module sage.rings.real_mpfr), 27
`RealField_class` (class in sage.rings.real_mpfr), 28
`RealInterval()` (in module sage.rings.real_mpfi), 71
`RealIntervalAbsoluteElement` (class in sage.rings.real_interval_absolute), 106

`RealIntervalAbsoluteField()` (in module `sage.rings.real_interval_absolute`), 109
`RealIntervalAbsoluteField_class` (class in `sage.rings.real_interval_absolute`), 109
`RealIntervalField()` (in module `sage.rings.real_mpfi`), 72
`RealIntervalField_class` (class in `sage.rings.real_mpfi`), 95
`RealIntervalFieldElement` (class in `sage.rings.real_mpfi`), 72
`RealLazyField()` (in module `sage.rings.real_lazy`), 118
`RealLazyField_class` (class in `sage.rings.real_lazy`), 118
`RealLiteral` (class in `sage.rings.real_mpfr`), 32
`RealNumber` (class in `sage.rings.real_mpfr`), 33
`relative_diameter()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 87
`restrict_angle()` (`sage.rings.real_double.RealDoubleElement` method), 13
`round()` (`sage.rings.real_double.RealDoubleElement` method), 13
`round()` (`sage.rings.real_mpfr.RealNumber` method), 52
`rounding_mode()` (`sage.rings.complex_mpc.MPCComplexField_class` method), 166
`rounding_mode()` (`sage.rings.real_mpfr.RealField_class` method), 31
`rounding_mode_imag()` (`sage.rings.complex_mpc.MPCComplexField_class` method), 166
`rounding_mode_real()` (`sage.rings.complex_mpc.MPCComplexField_class` method), 166
`RRtoCC` (class in `sage.rings.complex_number`), 159
`RRtoRR` (class in `sage.rings.real_mpfr`), 26

S

`sage.rings.complex_double` (module), 121
`sage.rings.complex_field` (module), 139
`sage.rings.complex_interval` (module), 185
`sage.rings.complex_interval_field` (module), 179
`sage.rings.complex_mpc` (module), 163
`sage.rings.complex_number` (module), 145
`sage.rings.real_double` (module), 3
`sage.rings.real_interval_absolute` (module), 105
`sage.rings.real_interval_field` (module), 103
`sage.rings.real_lazy` (module), 111
`sage.rings.real_mpfi` (module), 69
`sage.rings.real_mpfr` (module), 25
`scientific_notation()` (`sage.rings.complex_field.ComplexField_class` method), 142
`scientific_notation()` (`sage.rings.complex_interval_field.ComplexIntervalField_class` method), 182
`scientific_notation()` (`sage.rings.real_mpfi.RealIntervalField_class` method), 100
`scientific_notation()` (`sage.rings.real_mpfr.RealField_class` method), 32
`sec()` (`sage.rings.complex_double.ComplexDoubleElement` method), 132
`sec()` (`sage.rings.complex_mpc.MPCComplexNumber` method), 174
`sec()` (`sage.rings.complex_number.ComplexNumber` method), 157
`sec()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 87
`sec()` (`sage.rings.real_mpfr.RealNumber` method), 52
`sech()` (`sage.rings.complex_double.ComplexDoubleElement` method), 132
`sech()` (`sage.rings.complex_mpc.MPCComplexNumber` method), 174
`sech()` (`sage.rings.complex_number.ComplexNumber` method), 157
`sech()` (`sage.rings.real_double.RealDoubleElement` method), 13
`sech()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 87
`sech()` (`sage.rings.real_mpfr.RealNumber` method), 53
`section()` (`sage.rings.complex_mpc.MPCtoMPC` method), 176
`section()` (`sage.rings.real_mpfr.RRtoRR` method), 27

[set_global_complex_round_mode\(\)](#) (in module `sage.rings.complex_number`), 161
[shift_ceil\(\)](#) (in module `sage.rings.real_interval_absolute`), 110
[shift_floor\(\)](#) (in module `sage.rings.real_interval_absolute`), 110
[sign\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 13
[sign\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 53
[sign_mantissa_exponent\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 14
[sign_mantissa_exponent\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 53
[simplest_rational\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 88
[simplest_rational\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 54
[sin\(\)](#) (`sage.rings.complex_double.ComplexDoubleElement` method), 132
[sin\(\)](#) (`sage.rings.complex_mpc.MPCComplexNumber` method), 174
[sin\(\)](#) (`sage.rings.complex_number.ComplexNumber` method), 157
[sin\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 14
[sin\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 88
[sin\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 56
[sincos\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 14
[sincos\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 56
[sinh\(\)](#) (`sage.rings.complex_double.ComplexDoubleElement` method), 133
[sinh\(\)](#) (`sage.rings.complex_mpc.MPCComplexNumber` method), 174
[sinh\(\)](#) (`sage.rings.complex_number.ComplexNumber` method), 157
[sinh\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 14
[sinh\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 88
[sinh\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 56
[split_complex_string\(\)](#) (in module `sage.rings.complex_mpc`), 177
[sqr\(\)](#) (`sage.rings.complex_mpc.MPCComplexNumber` method), 175
[sqrt\(\)](#) (`sage.rings.complex_double.ComplexDoubleElement` method), 133
[sqrt\(\)](#) (`sage.rings.complex_interval.ComplexIntervalFieldElement` method), 190
[sqrt\(\)](#) (`sage.rings.complex_mpc.MPCComplexNumber` method), 175
[sqrt\(\)](#) (`sage.rings.complex_number.ComplexNumber` method), 157
[sqrt\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 15
[sqrt\(\)](#) (`sage.rings.real_interval_absolute.RealIntervalAbsoluteElement` method), 109
[sqrt\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 89
[sqrt\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 56
[square\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 89
[square_root\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 89
[str\(\)](#) (`sage.rings.complex_interval.ComplexIntervalFieldElement` method), 191
[str\(\)](#) (`sage.rings.complex_mpc.MPCComplexNumber` method), 175
[str\(\)](#) (`sage.rings.complex_number.ComplexNumber` method), 158
[str\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 15
[str\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 90
[str\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 57

T

[tan\(\)](#) (`sage.rings.complex_double.ComplexDoubleElement` method), 133
[tan\(\)](#) (`sage.rings.complex_mpc.MPCComplexNumber` method), 175
[tan\(\)](#) (`sage.rings.complex_number.ComplexNumber` method), 158
[tan\(\)](#) (`sage.rings.real_double.RealDoubleElement` method), 16
[tan\(\)](#) (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 92
[tan\(\)](#) (`sage.rings.real_mpfr.RealNumber` method), 58
[tanh\(\)](#) (`sage.rings.complex_double.ComplexDoubleElement` method), 133

`tanh()` (`sage.rings.complex_mpc.MPCComplexNumber` method), 176
`tanh()` (`sage.rings.complex_number.ComplexNumber` method), 158
`tanh()` (`sage.rings.real_double.RealDoubleElement` method), 16
`tanh()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 92
`tanh()` (`sage.rings.real_mpfr.RealNumber` method), 58
`time_alloc()` (in module `sage.rings.real_double`), 23
`time_alloc_list()` (in module `sage.rings.real_double`), 23
`to_prec()` (`sage.rings.complex_double.ComplexDoubleField_class` method), 136
`to_prec()` (`sage.rings.complex_field.ComplexField_class` method), 143
`to_prec()` (`sage.rings.complex_interval_field.ComplexIntervalField_class` method), 182
`to_prec()` (`sage.rings.real_double.RealDoubleField_class` method), 21
`to_prec()` (`sage.rings.real_mpfi.RealIntervalField_class` method), 100
`to_prec()` (`sage.rings.real_mpfr.RealField_class` method), 32
`ToRDF` (class in `sage.rings.real_double`), 21
`trunc()` (`sage.rings.real_double.RealDoubleElement` method), 16
`trunc()` (`sage.rings.real_mpfr.RealNumber` method), 58

U

`ulp()` (`sage.rings.real_double.RealDoubleElement` method), 16
`ulp()` (`sage.rings.real_mpfr.RealNumber` method), 59
`union()` (`sage.rings.complex_interval.ComplexIntervalFieldElement` method), 191
`union()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 93
`unique_ceil()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 93
`unique_floor()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 93
`unique_integer()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 93
`unique_round()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 94
`upper()` (`sage.rings.real_interval_absolute.RealIntervalAbsoluteElement` method), 109
`upper()` (`sage.rings.real_mpfi.RealIntervalFieldElement` method), 95

Y

`y0()` (`sage.rings.real_mpfr.RealNumber` method), 60
`y1()` (`sage.rings.real_mpfr.RealNumber` method), 60
`yn()` (`sage.rings.real_mpfr.RealNumber` method), 60

Z

`zeta()` (`sage.rings.complex_double.ComplexDoubleElement` method), 134
`zeta()` (`sage.rings.complex_double.ComplexDoubleField_class` method), 136
`zeta()` (`sage.rings.complex_field.ComplexField_class` method), 143
`zeta()` (`sage.rings.complex_interval_field.ComplexIntervalField_class` method), 182
`zeta()` (`sage.rings.complex_mpc.MPCComplexNumber` method), 176
`zeta()` (`sage.rings.complex_number.ComplexNumber` method), 159
`zeta()` (`sage.rings.real_double.RealDoubleElement` method), 17
`zeta()` (`sage.rings.real_double.RealDoubleField_class` method), 21
`zeta()` (`sage.rings.real_mpfi.RealIntervalField_class` method), 101
`zeta()` (`sage.rings.real_mpfr.RealField_class` method), 32
`zeta()` (`sage.rings.real_mpfr.RealNumber` method), 60
`ZZtoRR` (class in `sage.rings.real_mpfr`), 61