
Sage Reference Manual: Power Series Rings

Release 6.10

The Sage Development Team

December 21, 2015

CONTENTS

1	Power Series Rings	1
2	Power Series	13
3	Power Series Methods	29
4	Multivariate Power Series Rings	35
5	Multivariate Power Series	43
6	Laurent Series Rings	63
7	Laurent Series	69
8	Indices and Tables	79

POWER SERIES RINGS

Power series rings are constructed in the standard Sage fashion. See also *Multivariate Power Series Rings*.

EXAMPLES:

Construct rings and elements:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: R.random_element(6) # random
-4 - 1/2*t^2 - 1/95*t^3 + 1/2*t^4 - 12*t^5 + O(t^6)

sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: p = -t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + R.O(6); p
-t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + O(t, u, v)^6
sage: p in R
True
```

The default precision is specified at construction, but does not bound the precision of created elements.

```
sage: R.<t> = PowerSeriesRing(QQ, default_prec=5)
sage: R.random_element(6) # random
1/2 - 1/4*t + 2/3*t^2 - 5/2*t^3 + 2/3*t^5 + O(t^6)
```

Construct univariate power series from a list of coefficients:

```
sage: S = R([1, 3, 5, 7]); S
1 + 3*t + 5*t^2 + 7*t^3
```

An iterated example:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: S.<t2> = PowerSeriesRing(R)
sage: S
Power Series Ring in t2 over Power Series Ring in t over Integer Ring
sage: S.base_ring()
Power Series Ring in t over Integer Ring
```

Sage can compute with power series over the symbolic ring.

```
sage: K.<t> = PowerSeriesRing(SR, default_prec=5)
sage: a, b, c = var('a,b,c')
sage: f = a + b*t + c*t^2 + O(t^3)
sage: f*f
a^2 + 2*a*b*t + (b^2 + 2*a*c)*t^2 + O(t^3)
sage: f = sqrt(2) + sqrt(3)*t + O(t^3)
```

```
sage: f^2
2 + 2*sqrt(3)*sqrt(2)*t + 3*t^2 + O(t^3)
```

Elements are first coerced to constants in `base_ring`, then coerced into the `PowerSeriesRing`:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: f = Mod(2, 3) * t; (f, f.parent())
(2*t, Power Series Ring in t over Ring of integers modulo 3)
```

We make a sparse power series.

```
sage: R.<x> = PowerSeriesRing(QQ, sparse=True); R
Sparse Power Series Ring in x over Rational Field
sage: f = 1 + x^1000000
sage: g = f*f
sage: g.degree()
2000000
```

We make a sparse Laurent series from a power series generator:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: latex(-2/3*(1/t^3) + 1/t + 3/5*t^2 + O(t^5))
\frac{-\frac{2}{3}}{t^3} + \frac{1}{t} + \frac{3}{5}t^2 + O(t^5)
sage: S = parent(1/t); S
Sparse Laurent Series Ring in t over Rational Field
```

AUTHORS:

- William Stein: the code
- Jeremy Cho (2006-05-17): some examples (above)
- Niles Johnson (2010-09): implement multivariate power series
- Simon King (2012-08): use category and coercion framework, [trac ticket #13412](#)

TESTS:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: R is loads(dumps(R))
True
sage: TestSuite(R).run()

sage: R.<x> = PowerSeriesRing(QQ, sparse=True)
sage: R is loads(dumps(R))
True
sage: TestSuite(R).run()

sage: M = PowerSeriesRing(QQ, 't,u,v,w', default_prec=20)
sage: M is loads(dumps(M))
True
sage: TestSuite(M).run()
```

```
sage.rings.power_series_ring.PowerSeriesRing(base_ring, name=None, arg2=None,
                                              names=None, sparse=False, de-
                                              fault_prec=None, order='negdeglex',
                                              num_gens=None)
```

Create a univariate or multivariate power series ring over a given (commutative) base ring.

INPUT:

- `base_ring` - a commutative ring
- `name, names` - name(s) of the indeterminate
- **`default_prec` - the default precision used if an exact object must** be changed to an approximate object in order to do an arithmetic operation. If left as `None`, it will be set to the global default (20) in the univariate case, and 12 in the multivariate case.
- `sparse` - (default: `False`) whether power series are represented as sparse objects.
- `order` - (default: `negdeglex`) term ordering, for multivariate case
- `num_gens` - number of generators, for multivariate case

There is a unique power series ring over each base ring with given variable name. Two power series over the same base ring with different variable names are not equal or isomorphic.

EXAMPLES (Univariate):

```
sage: R = PowerSeriesRing(QQ, 'x'); R
Power Series Ring in x over Rational Field

sage: S = PowerSeriesRing(QQ, 'y'); S
Power Series Ring in y over Rational Field

sage: R = PowerSeriesRing(QQ, 10)
Traceback (most recent call last):
...
ValueError: variable name '10' does not start with a letter

sage: S = PowerSeriesRing(QQ, 'x', default_prec = 15); S
Power Series Ring in x over Rational Field
sage: S.default_prec()
15
```

EXAMPLES (Multivariate) See also *Multivariate Power Series Rings*:

```
sage: R = PowerSeriesRing(QQ, 't,u,v'); R
Multivariate Power Series Ring in t, u, v over Rational Field

sage: N = PowerSeriesRing(QQ, 'w', num_gens=5); N
Multivariate Power Series Ring in w0, w1, w2, w3, w4 over Rational Field
```

Number of generators can be specified before variable name without using keyword:

```
sage: M = PowerSeriesRing(QQ, 4, 'k'); M
Multivariate Power Series Ring in k0, k1, k2, k3 over Rational Field
```

Multivariate power series can be constructed using angle bracket or double square bracket notation:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ, 't,u,v'); R
Multivariate Power Series Ring in t, u, v over Rational Field

sage: ZZ[['s,t,u']]
Multivariate Power Series Ring in s, t, u over Integer Ring
```

Sparse multivariate power series ring:

```
sage: M = PowerSeriesRing(QQ, 4, 'k', sparse=True); M
Sparse Multivariate Power Series Ring in k0, k1, k2, k3 over
Rational Field
```

Power series ring over polynomial ring:

```
sage: H = PowerSeriesRing(PolynomialRing(ZZ, 3, 'z'), 4, 'f'); H
Multivariate Power Series Ring in f0, f1, f2, f3 over Multivariate
Polynomial Ring in z0, z1, z2 over Integer Ring
```

Power series ring over finite field:

```
sage: S = PowerSeriesRing(GF(65537), 'x, y'); S
Multivariate Power Series Ring in x, y over Finite Field of size
65537
```

Power series ring with many variables:

```
sage: R = PowerSeriesRing(ZZ, ['x%s'%p for p in primes(100)]); R
Multivariate Power Series Ring in x2, x3, x5, x7, x11, x13, x17, x19,
x23, x29, x31, x37, x41, x43, x47, x53, x59, x61, x67, x71, x73, x79,
x83, x89, x97 over Integer Ring
```

•Use `inject_variables()` to make the variables available for interactive use.

```
sage: R.inject_variables()
Defining x2, x3, x5, x7, x11, x13, x17, x19, x23, x29, x31, x37,
x41, x43, x47, x53, x59, x61, x67, x71, x73, x79, x83, x89, x97

sage: f = x47 + 3*x11*x29 - x19 + R.O(3)
sage: f in R
True
```

Variable ordering determines how series are displayed:

```
sage: T.<a,b> = PowerSeriesRing(ZZ, order='deglex'); T
Multivariate Power Series Ring in a, b over Integer Ring
sage: T.term_order()
Degree lexicographic term order
sage: p = - 2*b^6 + a^5*b^2 + a^7 - b^2 - a*b^3 + T.O(9); p
a^7 + a^5*b^2 - 2*b^6 - a*b^3 - b^2 + O(a, b)^9

sage: U = PowerSeriesRing(ZZ, 'a,b', order='negdeglex'); U
Multivariate Power Series Ring in a, b over Integer Ring
sage: U.term_order()
Negative degree lexicographic term order
sage: U(p)
-b^2 - a*b^3 - 2*b^6 + a^7 + a^5*b^2 + O(a, b)^9
```

TESTS:

```
sage: N = PowerSeriesRing(QQ, 'k', num_gens=5); N
Multivariate Power Series Ring in k0, k1, k2, k3, k4 over Rational Field
```

The following behavior of univariate power series ring will eventually be deprecated and then changed to return a multivariate power series ring:

```
sage: N = PowerSeriesRing(QQ, 'k', 5); N
Power Series Ring in k over Rational Field
sage: N.default_prec()
5
sage: L.<m> = PowerSeriesRing(QQ, 5); L
Power Series Ring in m over Rational Field
```



```
sage: L.default_prec()
5
```

By [trac ticket #14084](#), a power series ring belongs to the category of integral domains, if the base ring does:

```
sage: P = ZZ[['x']]
sage: P.category()
Category of integral domains
sage: TestSuite(P).run()
sage: M = ZZ[['x', 'y']]
sage: M.category()
Category of integral domains
sage: TestSuite(M).run()
```

Otherwise, it belongs to the category of commutative rings:

```
sage: P = Integers(15)[['x']]
sage: P.category()
Category of commutative rings
sage: TestSuite(P).run()
sage: M = Integers(15)[['x', 'y']]
sage: M.category()
Category of commutative rings
sage: TestSuite(M).run()
```

See also:

- `sage.misc.defaults.set_series_precision()`

```
class sage.rings.power_series_ring.PowerSeriesRing_domain(base_ring, name=None,
                                                           default_prec=None,
                                                           sparse=False,
                                                           use_lazy_mpoly_ring=False,
                                                           category=None)

Bases: sage.rings.power_series_ring.PowerSeriesRing_generic,
       sage.rings.ring.IntegralDomain
```

Initializes a power series ring.

INPUT:

- `base_ring` - a commutative ring
- `name` - name of the indeterminate
- `default_prec` - the default precision
- `sparse` - whether or not power series are sparse
- `use_lazy_mpoly_ring` - if base ring is a poly ring compute with multivariate polynomials instead of a univariate poly over the base ring. Only use this for dense power series where you won't do too much arithmetic, but the arithmetic you do must be fast. You must explicitly call `f.do_truncation()` on an element for it to truncate away higher order terms (this is called automatically before printing).

EXAMPLES:

This base class inherits from `CommutativeRing`. Since [trac ticket #11900](#), it is also initialised as such, and since [trac ticket #14084](#) it is actually initialised as an integral domain:

```
sage: R.<x> = ZZ[[]]
sage: R.category()
```

```
Category of integral domains
sage: TestSuite(R).run()
```

When the base ring k is a field, the ring $k[[x]]$ is not only a commutative ring, but also a complete discrete valuation ring (CDVR). The appropriate (sub)category is automatically set in this case:

```
sage: k = GF(11)
sage: R.<x> = k[[x]]
sage: R.category()
Category of complete discrete valuation rings
sage: TestSuite(R).run()
```

It is checked that the default precision is non-negative (see [trac ticket #19409](#)):

```
sage: PowerSeriesRing(ZZ, 'x', default_prec=-5)
Traceback (most recent call last):
...
ValueError: default_prec (= -5) must be non-negative
```

```
class sage.rings.power_series_ring.PowerSeriesRing_generic(base_ring, name=None,
                                                            default_prec=None,
                                                            sparse=False,
                                                            use_lazy_mpoly_ring=False,
                                                            category=None)

Bases:
    sage.structure.unique_representation.UniqueRepresentation,
    sage.rings.ring.CommutativeRing, sage.structure.nonexact.Nonexact
```

A power series ring.

Element

alias of `PowerSeries_poly`

base_extend(R)

Return the power series ring over R in the same variable as self, assuming there is a canonical coerce map from the base ring of self to R .

EXAMPLES:

```
sage: R.<T> = GF(7)[[T]]; R
Power Series Ring in T over Finite Field of size 7
sage: R.change_ring(ZZ)
Power Series Ring in T over Integer Ring
sage: R.base_extend(ZZ)
Traceback (most recent call last):
...
TypeError: no base extension defined
```

change_ring(R)

Return the power series ring over R in the same variable as self.

EXAMPLES:

```
sage: R.<T> = QQ[[T]]; R
Power Series Ring in T over Rational Field
sage: R.change_ring(GF(7))
Power Series Ring in T over Finite Field of size 7
sage: R.base_extend(GF(7))
Traceback (most recent call last):
...
TypeError: no base extension defined
```

```
sage: R.base_extend(QuadraticField(3,'a'))
Power Series Ring in T over Number Field in a with defining polynomial x^2 - 3
```

change_var(var)

Return the power series ring in variable var over the same base ring.

EXAMPLES:

```
sage: R.<T> = QQ[[]]; R
Power Series Ring in T over Rational Field
sage: R.change_var('D')
Power Series Ring in D over Rational Field
```

characteristic()

Return the characteristic of this power series ring, which is the same as the characteristic of the base ring of the power series ring.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.characteristic()
0
sage: R.<w> = Integers(2^50)[[]]; R
Power Series Ring in w over Ring of integers modulo 1125899906842624
sage: R.characteristic()
1125899906842624
```

construction()

Return the functorial construction of self, namely, completion of the univariate polynomial ring with respect to the indeterminate (to a given precision).

EXAMPLE:

```
sage: R = PowerSeriesRing(ZZ, 'x')
sage: c, S = R.construction(); S
Univariate Polynomial Ring in x over Integer Ring
sage: R == c(S)
True
```

gen(n=0)

Return the generator of this power series ring.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.gen()
t
sage: R.gen(3)
Traceback (most recent call last):
...
IndexError: generator n>0 not defined
```

is_dense()

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_dense()
True
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_dense()
False
```

is_exact()

Return False since the ring of power series over any ring is not exact.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.is_exact()
False
```

is_field(*proof=True*)

Return False since the ring of power series over any ring is never a field.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.is_field()
False
```

is_finite()

Return False since the ring of power series over any ring is never finite.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.is_finite()
False
```

is_sparse()

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_sparse()
False
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_sparse()
True
```

laurent_series_ring()

If this is the power series ring $R[[t]]$, return the Laurent series ring $R((t))$.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ, default_prec=5)
sage: S = R.laurent_series_ring(); S
Laurent Series Ring in t over Integer Ring
sage: S.default_prec()
5
sage: f = 1+t; g=1/f; g
1 - t + t^2 - t^3 + t^4 + O(t^5)
```

ngens()

Return the number of generators of this power series ring.

This is always 1.

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]]
sage: R.ngens()
1
```

random_element (*prec=None, *args, **kws*)

Return a random power series.

INPUT:

- *prec* - Integer specifying precision of output (default: default precision of self)
- **args, **kws* - Passed on to the `random_element` method for the base ring

OUTPUT:

- Power series with precision *prec* whose coefficients are random elements from the base ring, randomized subject to the arguments **args* and ***kws*

ALGORITHM:

Call the `random_element` method on the underlying polynomial ring.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: R.random_element(5) # random
-4 - 1/2*t^2 - 1/95*t^3 + 1/2*t^4 + O(t^5)
sage: R.random_element(10) # random
-1/2 + 2*t - 2/7*t^2 - 25*t^3 - t^4 + 2*t^5 - 4*t^7 - 1/3*t^8 - t^9 + O(t^10)
```

If given no argument, `random_element` uses default precision of self:

```
sage: T = PowerSeriesRing(ZZ, 't')
sage: T.default_prec()
20
sage: T.random_element() # random
4 + 2*t - t^2 - t^3 + 2*t^4 + t^5 + t^6 - 2*t^7 - t^8 - t^9 + t^11 - 6*t^12 + 2*t^14 + 2*t^15
sage: S = PowerSeriesRing(ZZ, 't', default_prec=4)
sage: S.random_element() # random
2 - t - 5*t^2 + t^3 + O(t^4)
```

Further arguments are passed to the underlying base ring ([trac ticket ##9481](#)):

```
sage: SZ = PowerSeriesRing(ZZ, 'v')
sage: SQ = PowerSeriesRing(QQ, 'v')
sage: SR = PowerSeriesRing(RR, 'v')

sage: SZ.random_element(x=4, y=6) # random
4 + 5*v + 5*v^2 + 5*v^3 + 4*v^4 + 5*v^5 + 5*v^6 + 5*v^7 + 4*v^8 + 5*v^9 + 4*v^10 + 4*v^11 +
sage: SZ.random_element(3, x=4, y=6) # random
5 + 4*v + 5*v^2 + O(v^3)
sage: SQ.random_element(3, num_bound=3, den_bound=100) # random
1/87 - 3/70*v - 3/44*v^2 + O(v^3)
sage: SR.random_element(3, max=10, min=-10) # random
2.85948321262904 - 9.73071330911226*v - 6.60414378519265*v^2 + O(v^3)
```

residue_field()

Return the residue field of this power series ring.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(GF(17))
sage: R.residue_field()
Finite Field of size 17
sage: R.<x> = PowerSeriesRing(Zp(5))
sage: R.residue_field()
Finite Field of size 5
```

uniformizer()

Return a uniformizer of this power series ring if it is a discrete valuation ring (i.e., if the base ring is actually a field). Otherwise, an error is raised.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: R.uniformizer()
t

sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.uniformizer()
Traceback (most recent call last):
...
TypeError: The base ring is not a field
```

variable_names_recursive (*depth=None*)

Return the list of variable names of this and its base rings.

EXAMPLES:

```
sage: R = QQ[['x']][['y']][['z']]
sage: R.variable_names_recursive()
('x', 'y', 'z')
sage: R.variable_names_recursive(2)
('y', 'z')
```

```
class sage.rings.power_series_ring.PowerSeriesRing_over_field(base_ring,
                                                                name=None, de-
                                                                fault_prec=None,
                                                                sparse=False,
                                                                use_lazy_mpoly_ring=False,
                                                                category=None)

Bases: sage.rings.power_series_ring.PowerSeriesRing_domain
```

Initializes a power series ring.

INPUT:

- `base_ring` - a commutative ring
- `name` - name of the indeterminate
- `default_prec` - the default precision
- `sparse` - whether or not power series are sparse
- `use_lazy_mpoly_ring` - if base ring is a poly ring compute with multivariate polynomials instead of a univariate poly over the base ring. Only use this for dense power series where you won't do too much arithmetic, but the arithmetic you do must be fast. You must explicitly call `f.do_truncation()` on an element for it to truncate away higher order terms (this is called automatically before printing).

EXAMPLES:

This base class inherits from `CommutativeRing`. Since [trac ticket #11900](#), it is also initialised as such, and since [trac ticket #14084](#) it is actually initialised as an integral domain:

```
sage: R.<x> = ZZ[[[]]]
sage: R.category()
Category of integral domains
sage: TestSuite(R).run()
```

When the base ring k is a field, the ring $k[[x]]$ is not only a commutative ring, but also a complete discrete valuation ring (CDVR). The appropriate (sub)category is automatically set in this case:

```
sage: k = GF(11)
sage: R.<x> = k[[x]]
sage: R.category()
Category of complete discrete valuation rings
sage: TestSuite(R).run()
```

It is checked that the default precision is non-negative (see [trac ticket #19409](#)):

```
sage: PowerSeriesRing(ZZ, 'x', default_prec=-5)
Traceback (most recent call last):
...
ValueError: default_prec (= -5) must be non-negative
```

`fraction_field()`

Return the fraction field of this power series ring, which is defined since this is over a field.

This fraction field is just the Laurent series ring over the base field.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(GF(7))
sage: R.fraction_field()
Laurent Series Ring in t over Finite Field of size 7
sage: Frac(R)
Laurent Series Ring in t over Finite Field of size 7
```

`sage.rings.power_series_ring.is_PowerSeriesRing(R)`

Return True if this is a *univariate* power series ring. This is in keeping with the behavior of `is_PolynomialRing` versus `is_MPolynomialRing`.

EXAMPLES:

```
sage: from sage.rings.power_series_ring import is_PowerSeriesRing
sage: is_PowerSeriesRing(10)
False
sage: is_PowerSeriesRing(QQ[['x']])
True
```

`sage.rings.power_series_ring.unpickle_power_series_ring_v0(base_ring, name, default_prec, sparse)`

Unpickle (deserialize) a univariate power series ring according to the given inputs.

EXAMPLES:

```
sage: P.<x> = PowerSeriesRing(QQ)
sage: loads(dumps(P)) == P # indirect doctest
True
```


POWER SERIES

Sage provides an implementation of dense and sparse power series over any Sage base ring. This is the base class of the implementations of univariate and multivariate power series ring elements in Sage (see also *Power Series Methods*, *Multivariate Power Series*).

AUTHORS:

- William Stein
- David Harvey (2006-09-11): added `solve_linear_de()` method
- Robert Bradshaw (2007-04): `sqrt`, `rmul`, `lmul`, shifting
- Robert Bradshaw (2007-04): Cython version
- Simon King (2012-08): use category and coercion framework, [trac ticket #13412](#)

EXAMPLE:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: TestSuite(R).run()
sage: R([1, 2, 3])
1 + 2*x + 3*x^2
sage: R([1, 2, 3], 10)
1 + 2*x + 3*x^2 + O(x^10)
sage: f = 1 + 2*x - 3*x^3 + O(x^4); f
1 + 2*x - 3*x^3 + O(x^4)
sage: f^10
1 + 20*x + 180*x^2 + 930*x^3 + O(x^4)
sage: g = 1/f; g
1 - 2*x + 4*x^2 - 5*x^3 + O(x^4)
sage: g * f
1 + O(x^4)
```

In Python (as opposed to Sage) create the power series ring and its generator as follows:

```
sage: R = PowerSeriesRing(ZZ, 'x')
sage: x = R.gen()
sage: parent(x)
Power Series Ring in x over Integer Ring
```

EXAMPLE:

This example illustrates that coercion for power series rings is consistent with coercion for polynomial rings.

```
sage: poly_ring1.<gen1> = PolynomialRing(QQ)
sage: poly_ring2.<gen2> = PolynomialRing(QQ)
sage: huge_ring.<x> = PolynomialRing(poly_ring1)
```

The generator of the first ring gets coerced in as itself, since it is the base ring.

```
sage: huge_ring(gen1)
gen1
```

The generator of the second ring gets mapped via the natural map sending one generator to the other.

```
sage: huge_ring(gen2)
x
```

With power series the behavior is the same.

```
sage: power_ring1.<gen1> = PowerSeriesRing(QQ)
sage: power_ring2.<gen2> = PowerSeriesRing(QQ)
sage: huge_power_ring.<x> = PowerSeriesRing(power_ring1)
sage: huge_power_ring(gen1)
gen1
sage: huge_power_ring(gen2)
x
```

class sage.rings.power_series_ring_element.**PowerSeries**
Bases: sage.structure.element.AlgebraElement

A power series. Base class of univariate and multivariate power series. The following methods are available with both types of objects.

O (*prec*)

Return this series plus $O(x^{\text{prec}})$. Does not change self.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: p = 1 + x^2 + x^10; p
1 + x^2 + x^10
sage: p.O(15)
1 + x^2 + x^10 + O(x^15)
sage: p.O(5)
1 + x^2 + O(x^5)
sage: p.O(-5)
Traceback (most recent call last):
...
ValueError: n must be at least 0
```

V (*n*)

If $f = \sum a_m x^m$, then this function returns $\sum a_m x^{nm}$.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: p = 1 + x^2 + x^10; p
1 + x^2 + x^10
sage: p.V(3)
1 + x^6 + x^30
sage: (p+O(x^20)).V(3)
1 + x^6 + x^30 + O(x^60)
```

add_bigoh (*prec*)

Return the power series of precision at most *prec* got by adding $O(q^{\text{prec}})$ to *f*, where *q* is the variable.

EXAMPLES:

```

sage: R.<A> = RDF[[[]]
sage: f = (1+A+O(A^5))^5; f
1.0 + 5.0*A + 10.0*A^2 + 10.0*A^3 + 5.0*A^4 + O(A^5)
sage: f.add_bigoh(3)
1.0 + 5.0*A + 10.0*A^2 + O(A^3)
sage: f.add_bigoh(5)
1.0 + 5.0*A + 10.0*A^2 + 10.0*A^3 + 5.0*A^4 + O(A^5)

```

base_extend(R)

Return a copy of this power series but with coefficients in R.

The following coercion uses base_extend implicitly:

```

sage: R.<t> = ZZ[['t']]
sage: (t - t^2) * Mod(1, 3)
t + 2*t^2

```

base_ring()

Return the base ring that this power series is defined over.

EXAMPLES:

```

sage: R.<t> = GF(49, 'alpha')[[]]
sage: (t^2 + O(t^3)).base_ring()
Finite Field in alpha of size 7^2

```

change_ring(R)

Change if possible the coefficients of self to lie in R.

EXAMPLES:

```

sage: R.<T> = QQ[[[]]; R
Power Series Ring in T over Rational Field
sage: f = 1 - 1/2*T + 1/3*T^2 + O(T^3)
sage: f.base_extend(GF(5))
Traceback (most recent call last):
...
TypeError: no base extension defined
sage: f.change_ring(GF(5))
1 + 2*T + 2*T^2 + O(T^3)
sage: f.change_ring(GF(3))
Traceback (most recent call last):
...
ZeroDivisionError: Inverse does not exist.

```

We can only change the ring if there is a `__call__` coercion defined. The following succeeds because `ZZ(K(4))` is defined.

```

sage: K.<a> = NumberField(cyclotomic_polynomial(3), 'a')
sage: R.<t> = K[['t']]
sage: (4*t).change_ring(ZZ)
4*t

```

This does not succeed because `ZZ(K(a+1))` is not defined.

```

sage: K.<a> = NumberField(cyclotomic_polynomial(3), 'a')
sage: R.<t> = K[['t']]
sage: ((a+1)*t).change_ring(ZZ)
Traceback (most recent call last):
...
TypeError: Unable to coerce a + 1 to an integer

```

coefficients()

Return the nonzero coefficients of self.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: f = t + t^2 - 10/3*t^3
sage: f.coefficients()
[1, 1, -10/3]
```

common_prec(f)

Return minimum precision of f and self.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)

sage: f = t + t^2 + O(t^3)
sage: g = t + t^3 + t^4 + O(t^4)
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3

sage: f = t + t^2 + O(t^3)
sage: g = t^2
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3

sage: f = t + t^2
sage: f = t^2
sage: f.common_prec(g)
+Infinity
```

degree()

Return the degree of this power series, which is by definition the degree of the underlying polynomial.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: f = t^100000 + O(t^1000000)
sage: f.degree()
100000
```

derivative(*args)

The formal derivative of this power series, with respect to variables supplied in args.

Multiple variables and iteration counts may be supplied; see documentation for the global derivative() function for more details.

See also:

`_derivative()`

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(QQ)
sage: g = -x + x^2/2 - x^4 + O(x^6)
sage: g.derivative()
```

```

-1 + x - 4*x^3 + O(x^5)
sage: g.derivative(x)
-1 + x - 4*x^3 + O(x^5)
sage: g.derivative(x, x)
1 - 12*x^2 + O(x^4)
sage: g.derivative(x, 2)
1 - 12*x^2 + O(x^4)

```

egf (*args, **kws)

Deprecated: Use `ogf_to_egf()` instead. See [trac ticket #15705](#) for details.

egf_to_ogf ()

Returns the ordinary generating function power series, assuming self is an exponential generating function power series.

This function is known as `serlaplace` in PARI/GP.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(QQ)
sage: f = t + t^2/factorial(2) + 2*t^3/factorial(3)
sage: f.egf_to_ogf()
t + t^2 + 2*t^3

```

exp (prec=None)

Return exp of this power series to the indicated precision.

INPUT:

- prec - integer; default is `self.parent().default_prec`

ALGORITHM: See `solve_linear_de()`.

Note:

- Screwy things can happen if the coefficient ring is not a field of characteristic zero. See `solve_linear_de()`.
-

AUTHORS:

- David Harvey (2006-09-08): rewrote to use simplest possible “lazy” algorithm.
- David Harvey (2006-09-10): rewrote to use divide-and-conquer strategy.
- David Harvey (2006-09-11): factored functionality out to `solve_linear_de()`.
- Sourav Sen Gupta, David Harvey (2008-11): handle constant term

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(QQ, default_prec=10)

```

Check that $\exp(t)$ is, well, $\exp(t)$:

```

sage: (t + O(t^10)).exp()
1 + t + 1/2*t^2 + 1/6*t^3 + 1/24*t^4 + 1/120*t^5 + 1/720*t^6 + 1/5040*t^7 + 1/40320*t^8 + 1/362880*t^9 + O(t^10)

```

Check that $\exp(\log(1+t))$ is $1+t$:

```

sage: (sum([(-t)^n/n for n in range(1, 10)]) + O(t^10)).exp()
1 + t + O(t^10)

```

Check that $\exp(2t + t^2 - t^5)$ is whatever it is:

```
sage: (2*t + t^2 - t^5 + O(t^10)).exp()
1 + 2*t + 3*t^2 + 10/3*t^3 + 19/6*t^4 + 8/5*t^5 - 7/90*t^6 - 538/315*t^7 - 425/168*t^8 - 3061/1260*t^9 + O(t^10)
```

Check requesting lower precision:

```
sage: (t + t^2 - t^5 + O(t^10)).exp(5)
1 + t + 3/2*t^2 + 7/6*t^3 + 25/24*t^4 + O(t^5)
```

Can't get more precision than the input:

```
sage: (t + t^2 + O(t^3)).exp(10)
1 + t + 3/2*t^2 + O(t^3)
```

Check some boundary cases:

```
sage: (t + O(t^2)).exp(1)
1 + O(t)
sage: (t + O(t^2)).exp(0)
O(t^0)
```

Handle nonzero constant term (fixes [trac ticket #4477](#)):

```
sage: R.<x> = PowerSeriesRing(RR)
sage: (1 + x + x^2 + O(x^3)).exp()
2.71828182845905 + 2.71828182845905*x + 4.07742274268857*x^2 + O(x^3)
```

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: (1 + x + O(x^2)).exp()
Traceback (most recent call last):
...
```

ArithmeticError: exponential of constant term does not belong to coefficient ring (consider

```
sage: R.<x> = PowerSeriesRing(GF(5))
sage: (1 + x + O(x^2)).exp()
Traceback (most recent call last):
...
```

ArithmeticError: constant term of power series does not support exponentiation

exponents()

Return the exponents appearing in self with nonzero coefficients.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: f = t + t^2 - 10/3*t^3
sage: f.exponents()
[1, 2, 3]
```

inverse()

Return the inverse of self, i.e., self^{-1} .

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: t.inverse()
t^-1
sage: type(_)
<type 'sage.rings.laurent_series_ring_element.LaurentSeries'>
sage: (1-t).inverse()
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + ...
```

is_dense()

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_dense()
True
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_dense()
False
```

is_gen()

Return True if this is the generator (the variable) of the power series ring.

EXAMPLES:

```
sage: R.<t> = QQ[[[]]]
sage: t.is_gen()
True
sage: (1 + 2*t).is_gen()
False
```

Note that this only returns True on the actual generator, not on something that happens to be equal to it.

```
sage: (1*t).is_gen()
False
sage: 1*t == t
True
```

is_monomial()Return True if this element is a monomial. That is, if self is x^n for some non-negative integer n .

EXAMPLES:

```
sage: k.<z> = PowerSeriesRing(QQ, 'z')
sage: z.is_monomial()
True
sage: k(1).is_monomial()
True
sage: (z+1).is_monomial()
False
sage: (z^2909).is_monomial()
True
sage: (3*z^2909).is_monomial()
False
```

is_sparse()

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_sparse()
False
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_sparse()
True
```

is_square()Return True if this function has a square root in this ring, e.g., there is an element y in `self.parent()` such that y^2 equals `self`.

ALGORITHM: If the base ring is a field, this is true whenever the power series has even valuation and the leading coefficient is a perfect square.

For an integral domain, it attempts the square root in the fraction field and tests whether or not the result lies in the original ring.

EXAMPLES:

```
sage: K.<t> = PowerSeriesRing(QQ, 't', 5)
sage: (1+t).is_square()
True
sage: (2+t).is_square()
False
sage: (2+t.change_ring(RR)).is_square()
True
sage: t.is_square()
False
sage: K.<t> = PowerSeriesRing(ZZ, 't', 5)
sage: (1+t).is_square()
False
sage: f = (1+t)^100
sage: f.is_square()
True
```

is_unit()

Return True if this power series is invertible.

A power series is invertible precisely when the constant term is invertible.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: (-1 + t - t^5).is_unit()
True
sage: (3 + t - t^5).is_unit()
False
```

AUTHORS:

•David Harvey (2006-09-03)

laurent_series()

Return the Laurent series associated to this power series, i.e., this series considered as a Laurent series.

EXAMPLES:

```
sage: k.<w> = QQ[[[]]]
sage: f = 1+17*w+15*w^3+O(w^5)
sage: parent(f)
Power Series Ring in w over Rational Field
sage: g = f.laurent_series(); g
1 + 17*w + 15*w^3 + O(w^5)
```

list()

See this method in derived classes:

- `sage.rings.power_series_poly.PowerSeries_poly.list()`,
- `sage.rings.multi_power_series_ring_element.MPowerSeries.list()`

Implementations *MUST* override this in the derived class.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: PowerSeries.list(1+x^2)
Traceback (most recent call last):
```



```
...
NotImplementedError
```

log (*prec=None*)

Return log of this power series to the indicated precision.

This works only if the constant term of the power series is 1.

INPUT:

- *prec* – integer; default is `self.parent().default_prec()`

ALGORITHM: See `solve_linear_de()`.

Warning: Screwy things can happen if the coefficient ring is not a field of characteristic zero. See `solve_linear_de()`.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, default_prec=10)
```

```
sage: (1 + t + O(t^10)).log()
t - 1/2*t^2 + 1/3*t^3 - 1/4*t^4 + 1/5*t^5 - 1/6*t^6 + 1/7*t^7 - 1/8*t^8 + 1/9*t^9 + O(t^10)
```

```
sage: t.exp().log()
t + O(t^10)
```

```
sage: (1+t).log().exp()
1 + t + O(t^10)
```

```
sage: (-1 + t + O(t^10)).log()
```

```
Traceback (most recent call last):
```

```
...
```

```
ArithmeticError: constant term of power series is not 1
```

ogf (**args, **kws*)

Deprecated: Use `egf_to_ogf()` instead. See [trac ticket #15705](#) for details.

ogf_to_egf ()

Returns the exponential generating function power series, assuming self is an ordinary generating function power series.

This can also be computed as `serconvol(f, exp(t))` in PARI/GP.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
```

```
sage: f = t + t^2 + 2*t^3
```

```
sage: f.ogf_to_egf()
t + 1/2*t^2 + 1/3*t^3
```

padded_list (*n=None*)

Return a list of coefficients of self up to (but not including) q^n .

Includes 0's in the list on the right so that the list has length n .

INPUT:

- *n* - (optional) an integer that is at least 0. If *n* is not given, it will be taken to be the precision of self, unless this is `+Infinity`, in which case we just return `self.list()`.

EXAMPLES:

```
sage: R.<q> = PowerSeriesRing(QQ)
sage: f = 1 - 17*q + 13*q^2 + 10*q^4 + O(q^7)
sage: f.list()
[1, -17, 13, 0, 10]
sage: f.padded_list(7)
[1, -17, 13, 0, 10, 0, 0]
sage: f.padded_list(10)
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
sage: f.padded_list(3)
[1, -17, 13]
sage: f.padded_list()
[1, -17, 13, 0, 10, 0, 0]
sage: g = 1 - 17*q + 13*q^2 + 10*q^4
sage: g.list()
[1, -17, 13, 0, 10]
sage: g.padded_list()
[1, -17, 13, 0, 10]
sage: g.padded_list(10)
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
```

polynomial()

See this method in derived classes:

- `sage.rings.power_series_poly.PowerSeries_poly.polynomial()`,
- `sage.rings.multi_power_series_ring_element.MPowerSeries.polynomial()`

Implementations *MUST* override this in the derived class.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: PowerSeries.polynomial(1+x^2)
Traceback (most recent call last):
...
NotImplementedError
```

prec()

The precision of $\dots + O(x^r)$ is by definition r .

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]]
sage: (t^2 + O(t^3)).prec()
3
sage: (1 - t^2 + O(t^100)).prec()
100
```

precision_absolute()

Return the absolute precision of this series.

By definition, the absolute precision of $\dots + O(x^r)$ is r .

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]]
sage: (t^2 + O(t^3)).precision_absolute()
3
sage: (1 - t^2 + O(t^100)).precision_absolute()
100
```

precision_relative()

Return the relative precision of this series, that is the difference between its absolute precision and its valuation.

By convention, the relative precision of 0 (or $O(x^r)$ for any r) is 0.

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]]
sage: (t^2 + O(t^3)).precision_relative()
1
sage: (1 - t^2 + O(t^100)).precision_relative()
100
sage: O(t^4).precision_relative()
0
```

shift(n)

Return this power series multiplied by the power t^n . If n is negative, terms below t^n will be discarded. Does not change this power series.

Note: Despite the fact that higher order terms are printed to the right in a power series, right shifting decreases the powers of t , while left shifting increases them. This is to be consistent with polynomials, integers, etc.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ['y'], 't', 5)
sage: f = ~(1+t); f
1 - t + t^2 - t^3 + t^4 + O(t^5)
sage: f.shift(3)
t^3 - t^4 + t^5 - t^6 + t^7 + O(t^8)
sage: f >> 2
1 - t + t^2 + O(t^3)
sage: f << 10
t^10 - t^11 + t^12 - t^13 + t^14 + O(t^15)
sage: t << 29
t^30
```

AUTHORS:

•Robert Bradshaw (2007-04-18)

solve_linear_de(prec='infinity', b=None, f0=None)

Obtain a power series solution to an inhomogeneous linear differential equation of the form:

$$f'(t) = a(t)f(t) + b(t).$$

INPUT:

- self - the power series $a(t)$
- b - the power series $b(t)$ (default is zero)
- f0 - the constant term of f ("initial condition") (default is 1)
- prec - desired precision of result (this will be reduced if either a or b have less precision available)

OUTPUT: the power series f , to indicated precision

ALGORITHM: A divide-and-conquer strategy; see the source code. Running time is approximately $M(n) \log n$, where $M(n)$ is the time required for a polynomial multiplication of length n over the co-efficient ring. (If you're working over something like \mathbf{Q} , running time analysis can be a little complicated because the coefficients tend to explode.)

Note:

- If the coefficient ring is a field of characteristic zero, then the solution will exist and is unique.
- For other coefficient rings, things are more complicated. A solution may not exist, and if it does it may not be unique. Generally, by the time the n th term has been computed, the algorithm will have attempted divisions by $n!$ in the coefficient ring. So if your coefficient ring has enough ‘precision’, and if your coefficient ring can perform divisions even when the answer is not unique, and if you know in advance that a solution exists, then this function will find a solution (otherwise it will probably crash).

AUTHORS:

- David Harvey (2006-09-11): factored functionality out from `exp()` function, cleaned up precision tests a bit

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, default_prec=10)

sage: a = 2 - 3*t + 4*t^2 + O(t^10)
sage: b = 3 - 4*t^2 + O(t^7)
sage: f = a.solve_linear_de(prec=5, b=b, f0=3/5)
sage: f
3/5 + 21/5*t + 33/10*t^2 - 38/15*t^3 + 11/24*t^4 + O(t^5)
sage: f.derivative() - a*f - b
O(t^4)

sage: a = 2 - 3*t + 4*t^2
sage: b = b = 3 - 4*t^2
sage: f = a.solve_linear_de(b=b, f0=3/5)
Traceback (most recent call last):
...
ValueError: cannot solve differential equation to infinite precision

sage: a.solve_linear_de(prec=5, b=b, f0=3/5)
3/5 + 21/5*t + 33/10*t^2 - 38/15*t^3 + 11/24*t^4 + O(t^5)
```

sqrt (*prec=None, extend=False, all=False, name=None*)

Return a square root of self.

INPUT:

- *prec* - integer (default: None): if not None and the series has infinite precision, truncates series at precision *prec*.
- *extend* - bool (default: False); if True, return a square root in an extension ring, if necessary. Otherwise, raise a `ValueError` if the square root is not in the base power series ring. For example, if *extend* is True the square root of a power series with odd degree leading coefficient is defined as an element of a formal extension ring.
- *name* - string; if *extend* is True, you must also specify the print name of the formal square root.
- *all* - bool (default: False); if True, return all square roots of self, instead of just one.

ALGORITHM: Newton’s method

$$x_{i+1} = \frac{1}{2}(x_i + \text{self}/x_i)$$

EXAMPLES:

```

sage: K.<t> = PowerSeriesRing(QQ, 't', 5)
sage: sqrt(t^2)
t
sage: sqrt(1+t)
1 + 1/2*t - 1/8*t^2 + 1/16*t^3 - 5/128*t^4 + O(t^5)
sage: sqrt(4+t)
2 + 1/4*t - 1/64*t^2 + 1/512*t^3 - 5/16384*t^4 + O(t^5)
sage: u = sqrt(2+t, prec=2, extend=True, name = 'alpha'); u
alpha
sage: u^2
2 + t
sage: u.parent()
Univariate Quotient Polynomial Ring in alpha over Power Series Ring in t over Rational Field
sage: K.<t> = PowerSeriesRing(QQ, 't', 50)
sage: sqrt(1+2*t+t^2)
1 + t
sage: sqrt(t^2 + 2*t^4 + t^6)
t + t^3
sage: sqrt(1 + t + t^2 + 7*t^3)^2
1 + t + t^2 + 7*t^3 + O(t^50)
sage: sqrt(K(0))
0
sage: sqrt(t^2)
t

sage: K.<t> = PowerSeriesRing(CDF, 5)
sage: v = sqrt(-1 + t + t^3, all=True); v
[1.0*I - 0.5*I*t - 0.125*I*t^2 - 0.5625*I*t^3 - 0.2890625*I*t^4 + O(t^5),
 -1.0*I + 0.5*I*t + 0.125*I*t^2 + 0.5625*I*t^3 + 0.2890625*I*t^4 + O(t^5)]
sage: [a^2 for a in v]
[-1.0 + 1.0*t + 0.0*t^2 + 1.0*t^3 + O(t^5), -1.0 + 1.0*t + 0.0*t^2 + 1.0*t^3 + O(t^5)]

```

A formal square root:

```

sage: K.<t> = PowerSeriesRing(QQ, 5)
sage: f = 2*t + t^3 + O(t^4)
sage: s = f.sqrt(extend=True, name='sqrtf'); s
sqrtf
sage: s^2
2*t + t^3 + O(t^4)
sage: parent(s)
Univariate Quotient Polynomial Ring in sqrtf over Power Series Ring in t over Rational Field

```

TESTS:

```

sage: R.<x> = QQ[[[]]]
sage: (x^10/2).sqrt()
Traceback (most recent call last):
...
ValueError: unable to take the square root of 1/2

```

AUTHORS:

- Robert Bradshaw
- William Stein

square_root()

Return the square root of self in this ring. If this cannot be done then an error will be raised.

This function succeeds if and only if `self.is_square()`

EXAMPLES:

```
sage: K.<t> = PowerSeriesRing(QQ, 't', 5)
sage: (1+t).square_root()
1 + 1/2*t - 1/8*t^2 + 1/16*t^3 - 5/128*t^4 + O(t^5)
sage: (2+t).square_root()
Traceback (most recent call last):
...
ValueError: Square root does not live in this ring.
sage: (2+t.change_ring(RR)).square_root()
1.41421356237309 + 0.353553390593274*t - 0.0441941738241592*t^2 + 0.0110485434560398*t^3 - 0.000110485434560398*t^4 + O(t^5)
sage: t.square_root()
Traceback (most recent call last):
...
ValueError: Square root not defined for power series of odd valuation.
sage: K.<t> = PowerSeriesRing(ZZ, 't', 5)
sage: f = (1+t)^20
sage: f.square_root()
1 + 10*t + 45*t^2 + 120*t^3 + 210*t^4 + O(t^5)
sage: f = 1+t
sage: f.square_root()
Traceback (most recent call last):
...
ValueError: Square root does not live in this ring.
```

AUTHORS:

•Robert Bradshaw

truncate (*prec*='infinity')

The polynomial obtained from power series by truncation.

EXAMPLES:

```
sage: R.<I> = GF(2)[[]]
sage: f = 1/(1+I+O(I^8)); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
sage: f.truncate(5)
I^4 + I^3 + I^2 + I + 1
```

valuation()

Return the valuation of this power series.

This is equal to the valuation of the underlying polynomial.

EXAMPLES:

Sparse examples:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: f = t^100000 + O(t^1000000)
sage: f.valuation()
100000
sage: R(0).valuation()
+Infinity
```

Dense examples:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: f = 17*t^100 + O(t^110)
sage: f.valuation()
100
```

```

100
sage: t.valuation()
1

```

valuation_zero_part()

Factor self as $q^n \cdot (a_0 + a_1q + \cdots)$ with a_0 nonzero. Then this function returns $a_0 + a_1q + \cdots$.

Note: This valuation zero part need not be a unit if, e.g., a_0 is not invertible in the base ring.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(QQ)
sage: ((1/3)*t^5*(17-2/3*t^3)).valuation_zero_part()
17/3 - 2/9*t^3

```

In this example the valuation 0 part is not a unit:

```

sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: u = (-2*t^5*(17-t^3)).valuation_zero_part(); u
-34 + 2*t^3
sage: u.is_unit()
False
sage: u.valuation()
0

```

variable()

Return a string with the name of the variable of this power series.

EXAMPLES:

```

sage: R.<x> = PowerSeriesRing(Rationals())
sage: f = x^2 + 3*x^4 + O(x^7)
sage: f.variable()
'x'

```

AUTHORS:

•David Harvey (2006-08-08)

`sage.rings.power_series_ring_element.is_PowerSeries(x)`
 Return True if x is an instance of a univariate or multivariate power series.

EXAMPLES:

```

sage: R.<x> = PowerSeriesRing(ZZ)
sage: from sage.rings.power_series_ring_element import is_PowerSeries
sage: is_PowerSeries(1+x^2)
True
sage: is_PowerSeries(x-x)
True
sage: is_PowerSeries(0)
False
sage: var('x')
x
sage: is_PowerSeries(1+x^2)
False

```

`sage.rings.power_series_ring_element.make_element_from_parent_v0(parent, *args)`

```
sage.rings.power_series_ring_element.make_powerseries_poly_v0(parent, f, prec,  
                                                                is_gen)
```


POWER SERIES METHODS

The class `PowerSeries_poly` provides additional methods for univariate power series.

```
class sage.rings.power_series_poly.PowerSeries_poly
    Bases: sage.rings.power_series_ring_element.PowerSeries
```

EXAMPLES:

```
sage: R.<q> = PowerSeriesRing(CC)
sage: R
Power Series Ring in q over Complex Field with 53 bits of precision
sage: loads(q.dumps()) == q
True

sage: R.<t> = QQ[[[]]
sage: f = 3 - t^3 + O(t^5)
sage: a = f^3; a
27 - 27*t^3 + O(t^5)
sage: b = f^-3; b
1/27 + 1/27*t^3 + O(t^5)
sage: a*b
1 + O(t^5)
```

degree()

Return the degree of the underlying polynomial of self. That is, if self is of the form $f(x) + O(x^n)$, we return the degree of $f(x)$. Note that if $f(x)$ is 0, we return -1, just as with polynomials.

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]
sage: (5 + t^3 + O(t^4)).degree()
3
sage: (5 + O(t^4)).degree()
0
sage: O(t^4).degree()
-1
```

dict()

Return a dictionary of coefficients for self. This is simply a dict for the underlying polynomial, so need not have keys corresponding to every number smaller than `self.prec()`.

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]
sage: f = 1 + t^10 + O(t^12)
sage: f.dict()
{0: 1, 10: 1}
```

integral (*var=None*)

The integral of this power series

By default, the integration variable is the variable of the power series.

Otherwise, the integration variable is the optional parameter *var*

Note: The integral is always chosen so the constant term is 0.

EXAMPLES:

```
sage: k.<w> = QQ[[w]]
sage: (1+17*w+15*w^3+O(w^5)).integral()
w + 17/2*w^2 + 15/4*w^4 + O(w^6)
sage: (w^3 + 4*w^4 + O(w^7)).integral()
1/4*w^4 + 4/5*w^5 + O(w^8)
sage: (3*w^2).integral()
w^3
```

TESTS:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: f = t + 5*t^2 + 21*t^3
sage: g = f.integral(); g
1/2*t^2 + 5/3*t^3 + 21/4*t^4
sage: g.parent()
Power Series Ring in t over Rational Field

sage: R.<x> = QQ[]
sage: t = PowerSeriesRing(R, 't').gen()
sage: f = x*t + 5*t^2
sage: f.integral()
1/2*x*t^2 + 5/3*t^3
sage: f.integral(x)
1/2*x^2*t + 5*x*t^2
```

list ()

Return the list of known coefficients for self. This is just the list of coefficients of the underlying polynomial, so in particular, need not have length equal to self.prec().

EXAMPLES:

```
sage: R.<t> = ZZ[[t]]
sage: f = 1 - 5*t^3 + t^5 + O(t^7)
sage: f.list()
[1, 0, 0, -5, 0, 1]
```

padé (*m, n*)

Returns the Padé approximant of self of index (*m, n*).

The Padé approximant of index (*m, n*) of a formal power series *f* is the quotient *Q/P* of two polynomials *Q* and *P* such that $\deg(Q) \leq m$, $\deg(P) \leq n$ and

$$f(z) - Q(z)/P(z) = O(z^{m+n+1}).$$

The formal power series *f* must be known up to order $n + m + 1$.

See [Wikipedia article Padé approximant](#)

INPUT:

- *m, n* – integers, describing the degrees of the polynomials

OUTPUT:

a ratio of two polynomials

Warning: The current implementation uses a very slow algorithm and is not suitable for high orders.

ALGORITHM:

This method uses the formula as a quotient of two determinants.

See also:

- `sage.matrix.berlekamp_massey`,
- `sage.rings.polynomial.polynomial_zmod_flint.Polynomial_zmod_flint.rational_recor`

EXAMPLES:

```
sage: z = PowerSeriesRing(QQ, 'z').gen()
sage: exp(z).pade(4, 0)
1/24*z^4 + 1/6*z^3 + 1/2*z^2 + z + 1
sage: exp(z).pade(1, 1)
(-z - 2)/(z - 2)
sage: exp(z).pade(3, 3)
(-z^3 - 12*z^2 - 60*z - 120)/(z^3 - 12*z^2 + 60*z - 120)
sage: log(1-z).pade(4, 4)
(25/6*z^4 - 130/3*z^3 + 105*z^2 - 70*z)/(z^4 - 20*z^3 + 90*z^2 - 140*z + 70)
sage: sqrt(1+z).pade(3, 2)
(1/6*z^3 + 3*z^2 + 8*z + 16/3)/(z^2 + 16/3*z + 16/3)
sage: exp(2*z).pade(3, 3)
(-z^3 - 6*z^2 - 15*z - 15)/(z^3 - 6*z^2 + 15*z - 15)
```

TESTS:

With real coefficients:

```
sage: R.<z> = RR[[]]
sage: f = exp(2*z)
sage: f.pade(3, 3) # abs tol 1e-10
(-1.0*z^3 - 6.0*z^2 - 15.0*z - 15.0)/(z^3 - 6.0*z^2 + 15.0*z - 15.0)
```

When precision is too low:

```
sage: f = z + O(z**6)
sage: f.pade(4, 4)
Traceback (most recent call last):
...
ValueError: the precision of the series is not large enough
```

polynomial()

Return the underlying polynomial of self.

EXAMPLE:

```
sage: R.<t> = GF(7)[[]]
sage: f = 3 - t^3 + O(t^5)
sage: f.polynomial()
6*t^3 + 3
```

reverse (*precision=None*)

Return the reverse of f , i.e., the series g such that $g(f(x)) = x$. Given an optional argument `precision`, return the reverse with given precision (note that the reverse can have precision at most `f.prec()`). If f has infinite precision, and the argument `precision` is not given, then the precision of the reverse defaults to the default precision of `f.parent()`.

Note that this is only possible if the valuation of `self` is exactly 1.

ALGORITHM:

We first attempt to pass the computation to `pari`; if this fails, we use Lagrange inversion. Using `sage: set_verbose(1)` will print a message if passing to `pari` fails.

If the base ring has positive characteristic, then we attempt to lift to a characteristic zero ring and perform the reverse there. If this fails, an error is raised.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(QQ)
sage: f = 2*x + 3*x^2 - x^4 + O(x^5)
sage: g = f.reverse()
sage: g
1/2*x - 3/8*x^2 + 9/16*x^3 - 131/128*x^4 + O(x^5)
sage: f(g)
x + O(x^5)
sage: g(f)
x + O(x^5)

sage: A.<t> = PowerSeriesRing(ZZ)
sage: a = t - t^2 - 2*t^4 + t^5 + O(t^6)
sage: b = a.reverse(); b
t + t^2 + 2*t^3 + 7*t^4 + 25*t^5 + O(t^6)
sage: a(b)
t + O(t^6)
sage: b(a)
t + O(t^6)

sage: B.<b,c> = PolynomialRing(ZZ)
sage: A.<t> = PowerSeriesRing(B)
sage: f = t + b*t^2 + c*t^3 + O(t^4)
sage: g = f.reverse(); g
t - b*t^2 + (2*b^2 - c)*t^3 + O(t^4)
sage: f(g)
t + O(t^4)
sage: g(f)
t + O(t^4)

sage: A.<t> = PowerSeriesRing(ZZ)
sage: B.<s> = A[[t]]
sage: f = (1 - 3*t + 4*t^3 + O(t^4))*s + (2 + t + t^2 + O(t^3))*s^2 + O(s^3)
sage: set_verbose(1)
sage: g = f.reverse(); g
verbose 1 (<module>) passing to pari failed; trying Lagrange inversion
(1 + 3*t + 9*t^2 + 23*t^3 + O(t^4))*s + (-2 - 19*t - 118*t^2 + O(t^3))*s^2 + O(s^3)
sage: set_verbose(0)
sage: f(g) == g(f) == s
True
```

If the leading coefficient is not a unit, we pass to its fraction field if possible:

```

sage: A.<t> = PowerSeriesRing(ZZ)
sage: a = 2*t - 4*t^2 + t^4 - t^5 + O(t^6)
sage: a.reverse()
1/2*t + 1/2*t^2 + t^3 + 79/32*t^4 + 437/64*t^5 + O(t^6)

sage: B.<b> = PolynomialRing(ZZ)
sage: A.<t> = PowerSeriesRing(B)
sage: f = 2*b*t + b*t^2 + 3*b^2*t^3 + O(t^4)
sage: g = f.reverse(); g
1/(2*b)*t - 1/(8*b^2)*t^2 + ((-3*b + 1)/(16*b^3))*t^3 + O(t^4)
sage: f(g)
t + O(t^4)
sage: g(f)
t + O(t^4)

```

We can handle some base rings of positive characteristic:

```

sage: A8.<t> = PowerSeriesRing(Zmod(8))
sage: a = t - 15*t^2 - 2*t^4 + t^5 + O(t^6)
sage: b = a.reverse(); b
t + 7*t^2 + 2*t^3 + 5*t^4 + t^5 + O(t^6)
sage: a(b)
t + O(t^6)
sage: b(a)
t + O(t^6)

```

The optional argument `precision` sets the precision of the output:

```

sage: R.<x> = PowerSeriesRing(QQ)
sage: f = 2*x + 3*x^2 - 7*x^3 + x^4 + O(x^5)
sage: g = f.reverse(precision=3); g
1/2*x - 3/8*x^2 + O(x^3)
sage: f(g)
x + O(x^3)
sage: g(f)
x + O(x^3)

```

If the input series has infinite precision, the precision of the output is automatically set to the default precision of the parent ring:

```

sage: R.<x> = PowerSeriesRing(QQ, default_prec=20)
sage: (x - x^2).reverse() # get some Catalan numbers
x + x^2 + 2*x^3 + 5*x^4 + 14*x^5 + 42*x^6 + 132*x^7 + 429*x^8 + 1430*x^9 + 4862*x^10 + 16796*x^11 + O(x^12)
sage: (x - x^2).reverse(precision=3)
x + x^2 + O(x^3)

```

TESTS:

```

sage: R.<x> = PowerSeriesRing(QQ)
sage: f = 1 + 2*x + 3*x^2 - x^4 + O(x^5)
sage: f.reverse()
Traceback (most recent call last):
...
ValueError: Series must have valuation one for reversion.

```

reversion (*args, **kws)

Deprecated: Use `reverse()` instead. See [trac ticket #17724](#) for details.

truncate (prec='infinity')

The polynomial obtained from power series by truncation at precision `prec`.

EXAMPLES:

```
sage: R.<I> = GF(2) [[]]
sage: f = 1/(1+I+O(I^8)); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
sage: f.truncate(5)
I^4 + I^3 + I^2 + I + 1
```

truncate_powerseries (*prec*)

Given input $\text{prec} = n$, returns the power series of degree $< n$ which is equivalent to self modulo x^n .

EXAMPLES:

```
sage: R.<I> = GF(2) [[]]
sage: f = 1/(1+I+O(I^8)); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
sage: f.truncate_powerseries(5)
1 + I + I^2 + I^3 + I^4 + O(I^5)
```

valuation()

Return the valuation of self.

EXAMPLES:

```
sage: R.<t> = QQ [[]]
sage: (5 - t^8 + O(t^11)).valuation()
0
sage: (-t^8 + O(t^11)).valuation()
8
sage: O(t^7).valuation()
7
sage: R(0).valuation()
+Infinity
```

`sage.rings.power_series_poly.make_powerseries_poly_v0` (*parent*, *f*, *prec*, *is_gen*)

Return the power series specified by *f*, *prec*, and *is_gen*.

This function exists for the purposes of pickling. Do not delete this function – if you change the internal representation, instead make a new function and make sure that both kinds of objects correctly unpickle as the new type.

EXAMPLES:

```
sage: R.<t> = QQ [[]]
sage: sage.rings.power_series_poly.make_powerseries_poly_v0(R, t, infinity, True)
t
```

MULTIVARIATE POWER SERIES RINGS

Construct a multivariate power series ring (in finitely many variables) over a given (commutative) base ring.

EXAMPLES:

Construct rings and elements:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: TestSuite(R).run()
sage: p = -t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + R.O(6); p
-t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + O(t, u, v)^6
sage: p in R
True

sage: g = 1 + v + 3*u*t^2 - 2*v^2*t^2; g
1 + v + 3*t^2*u - 2*t^2*v^2
sage: g in R
True
```

Add big O as with single variable power series:

```
sage: g.add_bigoh(3)
1 + v + O(t, u, v)^3
sage: g = g.O(5); g
1 + v + 3*t^2*u - 2*t^2*v^2 + O(t, u, v)^5
```

Sage keeps track of total-degree precision:

```
sage: f = (g-1)^2 - g + 1; f
-v + v^2 - 3*t^2*u + 6*t^2*u*v + 2*t^2*v^2 + O(t, u, v)^5
sage: f in R
True
sage: f.prec()
5
sage: ((g-1-v)^2).prec()
8
```

Construct multivariate power series rings over various base rings.

```
sage: M = PowerSeriesRing(QQ, 4, 'k'); M
Multivariate Power Series Ring in k0, k1, k2, k3 over Rational Field
sage: loads(dumps(M)) is M
True
sage: TestSuite(M).run()

sage: H = PowerSeriesRing(PolynomialRing(ZZ, 3, 'z'), 4, 'f'); H
```

Multivariate Power Series Ring in f_0, f_1, f_2, f_3 over Multivariate Polynomial Ring in z_0, z_1, z_2 over Integer Ring

```
sage: TestSuite(H).run()
```

```
sage: loads(dumps(H)) is H
```

```
True
```

```
sage: z = H.base_ring().gens()
```

```
sage: f = H.gens()
```

```
sage: h = 4*z[1]^2 + 2*z[0]*z[2] + z[1]*z[2] + z[2]^2 \
+ (-z[2]^2 - 2*z[0] + z[2])*f[0]*f[2] \
+ (-22*z[0]^2 + 2*z[1]^2 - z[0]*z[2] + z[2]^2 - 1955*z[2])*f[1]*f[2] \
+ (-z[0]*z[1] - 2*z[1]^2)*f[2]*f[3] \
+ (2*z[0]*z[1] + z[1]*z[2] - z[2]^2 - z[1] + 3*z[2])*f[3]^2 \
+ H.O(3)
```

```
sage: h in H
```

```
True
```

```
sage: h
```

```
4*z1^2 + 2*z0*z2 + z1*z2 + z2^2 + (-z2^2 - 2*z0 + z2)*f0*f2
+ (-22*z0^2 + 2*z1^2 - z0*z2 + z2^2 - 1955*z2)*f1*f2
+ (-z0*z1 - 2*z1^2)*f2*f3 + (2*z0*z1 + z1*z2 - z2^2 - z1 + 3*z2)*f3^2
+ O(f0, f1, f2, f3)^3
```

- Use angle-bracket notation:

```
sage: S.<x,y> = PowerSeriesRing(GF(65537)); S
```

Multivariate Power Series Ring in x, y over Finite Field of size 65537

```
sage: s = -30077*x + 9485*x*y - 6260*y^3 + 12870*x^2*y^2 - 20289*y^4 + S.O(5); s
```

```
-30077*x + 9485*x*y - 6260*y^3 + 12870*x^2*y^2 - 20289*y^4 + O(x, y)^5
```

```
sage: s in S
```

```
True
```

```
sage: TestSuite(S).run()
```

```
sage: loads(dumps(S)) is S
```

```
True
```

- Use double square bracket notation:

```
sage: ZZ[['s,t,u']]
```

Multivariate Power Series Ring in s, t, u over Integer Ring

```
sage: GF(127931)[['x,y']]
```

Multivariate Power Series Ring in x, y over Finite Field of size 127931

Variable ordering determines how series are displayed.

```
sage: T.<a,b> = PowerSeriesRing(ZZ,order='deglex'); T
```

Multivariate Power Series Ring in a, b over Integer Ring

```
sage: TestSuite(T).run()
```

```
sage: loads(dumps(T)) is T
```

```
True
```

```
sage: T.term_order()
```

Degree lexicographic term order

```
sage: p = - 2*b^6 + a^5*b^2 + a^7 - b^2 - a*b^3 + T.O(9); p
```

```
a^7 + a^5*b^2 - 2*b^6 - a*b^3 - b^2 + O(a, b)^9
```

```
sage: U = PowerSeriesRing(ZZ,'a,b',order='negdeglex'); U
```

Multivariate Power Series Ring in a, b over Integer Ring

```
sage: U.term_order()
```

Negative degree lexicographic term order

```
sage: U(p)
```

```
-b^2 - a*b^3 - 2*b^6 + a^7 + a^5*b^2 + O(a, b)^9
```


Change from one base ring to another:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: R.base_extend(RR)
Multivariate Power Series Ring in t, u, v over Real Field with 53
bits of precision
sage: R.change_ring(IntegerModRing(10))
Multivariate Power Series Ring in t, u, v over Ring of integers
modulo 10

sage: S = PowerSeriesRing(GF(65537),2,'x,y'); S
Multivariate Power Series Ring in x, y over Finite Field of size 65537
sage: S.change_ring(GF(5))
Multivariate Power Series Ring in x, y over Finite Field of size 5
```

Coercion from polynomial ring:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: A = PolynomialRing(ZZ,3,'t,u,v')
sage: g = A.gens()
sage: a = 2*g[0]*g[2] - 2*g[0] - 2; a
2*t*v - 2*t - 2
sage: R(a)
-2 - 2*t + 2*t*v
sage: R(a).O(4)
-2 - 2*t + 2*t*v + O(t, u, v)^4
sage: a.parent()
Multivariate Polynomial Ring in t, u, v over Integer Ring
sage: a in R
True
```

Coercion from polynomial ring in subset of variables:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: A = PolynomialRing(QQ,2,'t,v')
sage: g = A.gens()
sage: a = -2*g[0]*g[1] - 1/27*g[1]^2 + g[0] - 1/2*g[1]; a
-2*t*v - 1/27*v^2 + t - 1/2*v
sage: a in R
True
```

Coercion from symbolic ring:

```
sage: x,y = var('x,y')
sage: S = PowerSeriesRing(GF(11),2,'x,y'); S
Multivariate Power Series Ring in x, y over Finite Field of size 11
sage: type(x)
<type 'sage.symbolic.expression.Expression'>
sage: type(S(x))
<class 'sage.rings.multi_power_series_ring_element.MPowerSeriesRing_generic_with_category.element_class'>

sage: f = S(2/7 -100*x^2 + 1/3*x*y + y^2).O(3); f
5 - x^2 + 4*x*y + y^2 + O(x, y)^3
sage: f.parent()
Multivariate Power Series Ring in x, y over Finite Field of size 11
sage: f.parent() == S
```

True

The implementation of the multivariate power series ring uses a combination of multivariate polynomials and univariate power series. Namely, in order to construct the multivariate power series ring $R[[x_1, x_2, \dots, x_n]]$, we consider the univariate power series ring $S[[T]]$ over the multivariate polynomial ring $S := R[x_1, x_2, \dots, x_n]$, and in it we take the subring formed by all power series whose i -th coefficient has degree i for all $i \geq 0$. This subring is isomorphic to $R[[x_1, x_2, \dots, x_n]]$. This is how $R[[x_1, x_2, \dots, x_n]]$ is implemented in this class. The ring S is called the foreground polynomial ring, and the ring $S[[T]]$ is called the background univariate power series ring.

AUTHORS:

- Niles Johnson (2010-07): initial code
- Simon King (2012-08, 2013-02): Use category and coercion framework, [trac ticket #13412](#) and [trac ticket #14084](#)

```
class sage.rings.multi_power_series_ring.MPowerSeriesRing_generic(base_ring,
                                                                    num_gens,
                                                                    name_list, or-
                                                                    der='negdeglex',
                                                                    de-
                                                                    fault_prec=10,
                                                                    sparse=False)

Bases:
    sage.rings.power_series_ring.PowerSeriesRing_generic,
    sage.structure.nonexact.Nonexact
```

A multivariate power series ring. This class is implemented as a single variable power series ring in the variable T over a multivariable polynomial ring in the specified generators. Each generator g of the multivariable polynomial ring (called the “foreground ring”) is mapped to $g \cdot T$ in the single variable power series ring (called the “background ring”). The background power series ring is used to do arithmetic and track total-degree precision. The foreground polynomial ring is used to display elements.

For usage and examples, see above, and `PowerSeriesRing()`.

Element

alias of `MPowerSeries`

`O(prec)`

Return big oh with precision `prec`. This function is an alias for `bigoh`.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2); T
Multivariate Power Series Ring in a, b over Integer Ring
sage: T.O(10)
0 + O(a, b)^10
sage: T.bigoh(10)
0 + O(a, b)^10
```

`bigoh(prec)`

Return big oh with precision `prec`. The function `O` does the same thing.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2); T
Multivariate Power Series Ring in a, b over Integer Ring
sage: T.bigoh(10)
0 + O(a, b)^10
sage: T.O(10)
0 + O(a, b)^10
```

change_ring(*R*)

Returns the power series ring over *R* in the same variable as self. This function ignores the question of whether the base ring of self is or can extend to the base ring of *R*; for the latter, use `base_extend`.

EXAMPLES:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: R.base_extend(RR)
Multivariate Power Series Ring in t, u, v over Real Field with
53 bits of precision
sage: R.change_ring(IntegerModRing(10))
Multivariate Power Series Ring in t, u, v over Ring of integers
modulo 10
sage: R.base_extend(IntegerModRing(10))
Traceback (most recent call last):
...
TypeError: no base extension defined

sage: S = PowerSeriesRing(GF(65537), 2, 'x,y'); S
Multivariate Power Series Ring in x, y over Finite Field of size
65537
sage: S.change_ring(GF(5))
Multivariate Power Series Ring in x, y over Finite Field of size 5
```

characteristic()

Return characteristic of base ring, which is characteristic of self.

EXAMPLES:

```
sage: H = PowerSeriesRing(GF(65537), 4, 'f'); H
Multivariate Power Series Ring in f0, f1, f2, f3 over
Finite Field of size 65537
sage: H.characteristic()
65537
```

construction()

Returns a functor *F* and base ring *R* such that *F*(*R*) == self.

EXAMPLES:

```
sage: M = PowerSeriesRing(QQ, 4, 'f'); M
Multivariate Power Series Ring in f0, f1, f2, f3 over Rational Field

sage: (c,R) = M.construction(); (c,R)
(Completion[('f0', 'f1', 'f2', 'f3')],
Multivariate Polynomial Ring in f0, f1, f2, f3 over Rational Field)
sage: c
Completion[('f0', 'f1', 'f2', 'f3')]
sage: c(R)
Multivariate Power Series Ring in f0, f1, f2, f3 over Rational Field
sage: c(R) == M
True
```

gen(*n=0*)

Return the *n*th generator of self.

EXAMPLES:

```
sage: M = PowerSeriesRing(ZZ, 10, 'v');
sage: M.gen(6)
v6
```

is_dense()

Is self dense? (opposite of sparse)

EXAMPLES:

```
sage: M = PowerSeriesRing(ZZ, 3, 's, t, u'); M
Multivariate Power Series Ring in s, t, u over Integer Ring
sage: M.is_dense()
True
sage: N = PowerSeriesRing(ZZ, 3, 's, t, u', sparse=True); N
Sparse Multivariate Power Series Ring in s, t, u over Integer Ring
sage: N.is_dense()
False
```

is_integral_domain(*proof=False*)

Return True if the base ring is an integral domain; otherwise return False.

EXAMPLES:

```
sage: M = PowerSeriesRing(QQ, 4, 'v'); M
Multivariate Power Series Ring in v0, v1, v2, v3 over Rational Field
sage: M.is_integral_domain()
True
```

is_noetherian(*proof=False*)

Power series over a Noetherian ring are Noetherian.

EXAMPLES:

```
sage: M = PowerSeriesRing(QQ, 4, 'v'); M
Multivariate Power Series Ring in v0, v1, v2, v3 over Rational Field
sage: M.is_noetherian()
True

sage: W = PowerSeriesRing(InfinitePolynomialRing(ZZ, 'a'), 2, 'x, y')
sage: W.is_noetherian()
False
```

is_sparse()

Is self sparse?

EXAMPLES:

```
sage: M = PowerSeriesRing(ZZ, 3, 's, t, u'); M
Multivariate Power Series Ring in s, t, u over Integer Ring
sage: M.is_sparse()
False
sage: N = PowerSeriesRing(ZZ, 3, 's, t, u', sparse=True); N
Sparse Multivariate Power Series Ring in s, t, u over Integer Ring
sage: N.is_sparse()
True
```

laurent_series_ring()

Laurent series not yet implemented for multivariate power series rings

TESTS:

```

sage: M = PowerSeriesRing(ZZ, 3, 'x, y, z');
sage: M.laurent_series_ring()
Traceback (most recent call last):
...
NotImplementedError: Laurent series not implemented for
multivariate power series.

```

ngens()

Return number of generators of self.

EXAMPLES:

```

sage: M = PowerSeriesRing(ZZ, 10, 'v');
sage: M.ngens()
10

```

prec_ideal()

Return the ideal which determines precision; this is the ideal generated by all of the generators of our background polynomial ring.

EXAMPLES:

```

sage: A.<s,t,u> = PowerSeriesRing(ZZ)
sage: A.prec_ideal()
Ideal (s, t, u) of Multivariate Polynomial Ring in s, t, u over
Integer Ring

```

remove_var(*var)

Remove given variable or sequence of variables from self.

EXAMPLES:

```

sage: A.<s,t,u> = PowerSeriesRing(ZZ)
sage: A.remove_var(t)
Multivariate Power Series Ring in s, u over Integer Ring
sage: A.remove_var(s,t)
Power Series Ring in u over Integer Ring

sage: M = PowerSeriesRing(GF(5), 5, 't'); M
Multivariate Power Series Ring in t0, t1, t2, t3, t4 over
Finite Field of size 5
sage: M.remove_var(M.gens()[3])
Multivariate Power Series Ring in t0, t1, t2, t4 over Finite
Field of size 5

```

Removing all variables results in the base ring:

```

sage: M.remove_var(*M.gens())
Finite Field of size 5

```

term_order()

Print term ordering of self. Term orderings are implemented by the TermOrder class.

EXAMPLES:

```

sage: M.<x,y,z> = PowerSeriesRing(ZZ, 3);
sage: M.term_order()
Negative degree lexicographic term order
sage: m = y*z^12 - y^6*z^8 - x^7*y^5*z^2 + x*y^2*z + M.O(15); m
x*y^2*z + y*z^12 - x^7*y^5*z^2 - y^6*z^8 + O(x, y, z)^15

```

```
sage: N = PowerSeriesRing(ZZ, 3, 'x, y, z', order="deglex");
sage: N.term_order()
Degree lexicographic term order
sage: N(m)
-x^7*y^5*z^2 - y^6*z^8 + y*z^12 + x*y^2*z + O(x, y, z)^15
```

`sage.rings.multi_power_series_ring.is_MPowerSeriesRing(x)`

Return true if input is a multivariate power series ring.

TESTS:

```
sage: from sage.rings.power_series_ring import is_PowerSeriesRing
sage: from sage.rings.multi_power_series_ring import is_MPowerSeriesRing
sage: M = PowerSeriesRing(ZZ, 4, 'v');
sage: is_PowerSeriesRing(M)
False
sage: is_MPowerSeriesRing(M)
True
sage: T = PowerSeriesRing(RR, 'v')
sage: is_PowerSeriesRing(T)
True
sage: is_MPowerSeriesRing(T)
False
```

`sage.rings.multi_power_series_ring.unpickle_multi_power_series_ring_v0` (*base_ring*,
num_gens,
names,
or-
der,
de-
fault_prec,
sparse)

Unpickle (deserialize) a multivariate power series ring according to the given inputs.

EXAMPLES:

```
sage: P.<x,y> = PowerSeriesRing(QQ)
sage: loads(dumps(P)) == P # indirect doctest
True
```

MULTIVARIATE POWER SERIES

Construct and manipulate multivariate power series (in finitely many variables) over a given commutative ring. Multivariate power series are implemented with total-degree precision.

EXAMPLES:

Power series arithmetic, tracking precision:

```
sage: R.<s,t> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in s, t over Integer Ring

sage: f = 1 + s + 3*s^2; f
1 + s + 3*s^2
sage: g = t^2*s + 3*t^2*s^2 + R.O(5); g
s*t^2 + 3*s^2*t^2 + O(s, t)^5
sage: g = t^2*s + 3*t^2*s^2 + O(s, t)^5; g
s*t^2 + 3*s^2*t^2 + O(s, t)^5
sage: f = f.O(7); f
1 + s + 3*s^2 + O(s, t)^7
sage: f += s; f
1 + 2*s + 3*s^2 + O(s, t)^7
sage: f*g
s*t^2 + 5*s^2*t^2 + O(s, t)^5
sage: (f-1)*g
2*s^2*t^2 + 9*s^3*t^2 + O(s, t)^6
sage: f*g - g
2*s^2*t^2 + O(s, t)^5

sage: f*=s; f
s + 2*s^2 + 3*s^3 + O(s, t)^8
sage: f%2
s + s^3 + O(s, t)^8
sage: (f%2).parent()
Multivariate Power Series Ring in s, t over Ring of integers modulo 2
```

As with univariate power series, comparison of f and g is done up to the minimum precision of f and g :

```
sage: f = 1 + t + s + s*t + R.O(3); f
1 + s + t + s*t + O(s, t)^3
sage: g = s^2 + 2*s^4 - s^5 + s^2*t^3 + R.O(6); g
s^2 + 2*s^4 - s^5 + s^2*t^3 + O(s, t)^6
sage: f == g
False
sage: g == g.add_bigoh(3)
True
sage: f < g
```

```
False
sage: f > g
True
```

Calling:

```
sage: f = s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + R.O(5); f
s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + O(s, t)^5
sage: f(t,s)
s*t + t^2 + s*t^2 + t^3 + 3*s*t^3 + 3*t^4 + O(s, t)^5
sage: f(t^2,s^2)
s^2*t^2 + t^4 + s^2*t^4 + t^6 + 3*s^2*t^6 + 3*t^8 + O(s, t)^10
```

Substitution is defined only for elements of positive valuation, unless f has infinite precision:

```
sage: f(t^2,s^2+1)
Traceback (most recent call last):
...
TypeError: Substitution defined only for elements of positive valuation,
unless self has infinite precision.

sage: g = f.truncate()
sage: g(t^2,s^2+1)
t^2 + s^2*t^2 + 2*t^4 + s^2*t^4 + 4*t^6 + 3*s^2*t^6 + 3*t^8
sage: g(t^2,(s^2+1).O(3))
t^2 + s^2*t^2 + 2*t^4 + O(s, t)^5
```

0 has valuation +Infinity:

```
sage: f(t^2,0)
t^4 + t^6 + 3*t^8 + O(s, t)^10
sage: f(t^2,s^2+s)
s*t^2 + s^2*t^2 + t^4 + O(s, t)^5
```

Substitution of power series with finite precision works too:

```
sage: f(s.O(2),t)
s^2 + s*t + O(s, t)^3
sage: f(f,f)
2*s^4 + 4*s^3*t + 2*s^2*t^2 + 4*s^5 + 8*s^4*t + 4*s^3*t^2 + 16*s^6 +
34*s^5*t + 20*s^4*t^2 + 2*s^3*t^3 + O(s, t)^7
sage: t(f,f)
s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + O(s, t)^5
sage: t(0,f) == s(f,0)
True
```

The subs syntax works as expected:

```
sage: r0 = -t^2 - s*t^3 - 2*t^6 + s^7 + s^5*t^2 + R.O(10)
sage: r1 = s^4 - s*t^4 + s^6*t - 4*s^2*t^5 - 6*s^3*t^5 + R.O(10)
sage: r2 = 2*s^3*t^2 - 2*s*t^4 - 2*s^3*t^4 + s*t^7 + R.O(10)
sage: r0.subs({t:r2,s:r1})
-4*s^6*t^4 + 8*s^4*t^6 - 4*s^2*t^8 + 8*s^6*t^6 - 8*s^4*t^8 - 4*s^4*t^9
+ 4*s^2*t^11 - 4*s^6*t^8 + O(s, t)^15
sage: r0.subs({t:r2,s:r1}) == r0(r1,r2)
True
```

Construct ring homomorphisms from one power series ring to another:


```
sage: A.<a,b> = PowerSeriesRing(QQ)
sage: X.<x,y> = PowerSeriesRing(QQ)
```

```
sage: phi = Hom(A,X) ([x,2*y]); phi
```

Ring morphism:

```
From: Multivariate Power Series Ring in a, b over Rational Field
To:   Multivariate Power Series Ring in x, y over Rational Field
Defn: a |--> x
      b |--> 2*y
```

```
sage: phi(a+b+3*a*b^2 + A.O(5))
x + 2*y + 12*x*y^2 + O(x, y)^5
```

Multiplicative inversion of power series:

```
sage: h = 1 + s + t + s*t + s^2*t^2 + 3*s^4 + 3*s^3*t + R.O(5);
```

```
sage: k = h^-1; k
```

```
1 - s - t + s^2 + s*t + t^2 - s^3 - s^2*t - s*t^2 - t^3 - 2*s^4 -
2*s^3*t + s*t^3 + t^4 + O(s, t)^5
```

```
sage: h*k
```

```
1 + O(s, t)^5
```

```
sage: f = 1 - 5*s^29 - 5*s^28*t + 4*s^18*t^35 + \
4*s^17*t^36 - s^45*t^25 - s^44*t^26 + s^7*t^83 + \
s^6*t^84 + R.O(101)
```

```
sage: h = ~f; h
```

```
1 + 5*s^29 + 5*s^28*t - 4*s^18*t^35 - 4*s^17*t^36 + 25*s^58 + 50*s^57*t
+ 25*s^56*t^2 + s^45*t^25 + s^44*t^26 - 40*s^47*t^35 - 80*s^46*t^36
- 40*s^45*t^37 + 125*s^87 + 375*s^86*t + 375*s^85*t^2 + 125*s^84*t^3
- s^7*t^83 - s^6*t^84 + 10*s^74*t^25 + 20*s^73*t^26 + 10*s^72*t^27
+ O(s, t)^101
```

```
sage: h*f
```

```
1 + O(s, t)^101
```

AUTHORS:

- Niles Johnson (07/2010): initial code
- Simon King (08/2012): Use category and coercion framework, [trac ticket #13412](#)

```
class sage.rings.multi_power_series_ring_element.MO(x)
```

Bases: object

Object representing a zero element with given precision.

EXAMPLES:

```
sage: R.<u,v> = QQ[[[]]]
```

```
sage: m = O(u, v)
```

```
sage: m^4
```

```
0 + O(u, v)^4
```

```
sage: m^1
```

```
0 + O(u, v)^1
```

```
sage: T.<a,b,c> = PowerSeriesRing(ZZ,3)
```

```
sage: z = O(a, b, c)
```

```
sage: z^1
```

```
0 + O(a, b, c)^1
```

```
sage: 1 + a + z^1
```

```
1 + O(a, b, c)^1
```

```

sage: w = 1 + a + O(a, b, c)^2; w
1 + a + O(a, b, c)^2
sage: w^2
1 + 2*a + O(a, b, c)^2

```

```

class sage.rings.multi_power_series_ring_element.MPowerSeries (parent, x=0,
                                                                prec=+Infinity,
                                                                is_gen=False,
                                                                check=False)

```

Bases: `sage.rings.power_series_ring_element.PowerSeries`

Multivariate power series; these are the elements of Multivariate Power Series Rings.

INPUT:

- `parent` – A multivariate power series.
- `x` – The element (default: 0). This can be another `MPowerSeries` object, or an element of one of the following:
 - the background univariate power series ring
 - the foreground polynomial ring
 - a ring that coerces to one of the above two
- `prec` – (default: infinity) The precision
- `is_gen` – (default: False) Is this element one of the generators?
- `check` – (default: False) Needed by univariate power series class

EXAMPLES:

Construct multivariate power series from generators:

```

sage: S.<s,t> = PowerSeriesRing(ZZ)
sage: f = s + 4*t + 3*s*t
sage: f in S
True
sage: f = f.add_bigoh(4); f
s + 4*t + 3*s*t + O(s, t)^4
sage: g = 1 + s + t - s*t + S.O(5); g
1 + s + t - s*t + O(s, t)^5

```

```

sage: T = PowerSeriesRing(GF(3), 5, 't'); T
Multivariate Power Series Ring in t0, t1, t2, t3, t4 over Finite
Field of size 3
sage: t = T.gens()
sage: w = t[0] - 2*t[1]*t[3] + 5*t[4]^3 - t[0]^3*t[2]^2; w
t0 + t1*t3 - t4^3 - t0^3*t2^2
sage: w = w.add_bigoh(5); w
t0 + t1*t3 - t4^3 + O(t0, t1, t2, t3, t4)^5
sage: w in T
True

```

```

sage: w = t[0] - 2*t[0]*t[2] + 5*t[4]^3 - t[0]^3*t[2]^2 + T.O(6)
sage: w
t0 + t0*t2 - t4^3 - t0^3*t2^2 + O(t0, t1, t2, t3, t4)^6

```

Get random elements:

```

sage: S.random_element(4) # random
-2*t + t^2 - 12*s^3 + O(s, t)^4

sage: T.random_element(10) # random
-t1^2*t3^2*t4^2 + t1^5*t3^3*t4 + O(t0, t1, t2, t3, t4)^10

```

Convert elements from polynomial rings:

```

sage: R = PolynomialRing(ZZ, 5, T.gens())
sage: t = R.gens()
sage: r = -t[2]*t[3] + t[3]^2 + t[4]^2
sage: T(r)
-t2*t3 + t3^2 + t4^2
sage: r.parent()
Multivariate Polynomial Ring in t0, t1, t2, t3, t4 over Integer Ring
sage: r in T
True

```

O(*prec*)

Return a multivariate power series of precision *prec* obtained by truncating *self* at precision *prec*.

This is the same as `add_bigoh()`.

EXAMPLES:

```

sage: B.<x,y> = PowerSeriesRing(QQ); B
Multivariate Power Series Ring in x, y over Rational Field
sage: r = 1 - x*y + x^2
sage: r.O(4)
1 + x^2 - x*y + O(x, y)^4
sage: r.O(2)
1 + O(x, y)^2

```

Note that this does not change *self*:

```

sage: r
1 + x^2 - x*y

```

V(*n*)

If

$$f = \sum a_{m_0, \dots, m_k} x_0^{m_0} \cdots x_k^{m_k},$$

then this function returns

$$\sum a_{m_0, \dots, m_k} x_0^{nm_0} \cdots x_k^{nm_k}.$$

The total-degree precision of the output is *n* times the precision of *self*.

EXAMPLES:

```

sage: H = QQ[['x,y,z']]
sage: (x,y,z) = H.gens()
sage: h = -x*y^4*z^7 - 1/4*y*z^12 + 1/2*x^7*y^5*z^2 \
+ 2/3*y^6*z^8 + H.O(15)
sage: h.V(3)
-x^3*y^12*z^21 - 1/4*y^3*z^36 + 1/2*x^21*y^15*z^6 + 2/3*y^18*z^24 + O(x, y, z)^45

```

add_bigoh(*prec*)

Return a multivariate power series of precision *prec* obtained by truncating *self* at precision *prec*.

This is the same as `O()`.

EXAMPLES:

```
sage: B.<x,y> = PowerSeriesRing(QQ); B
Multivariate Power Series Ring in x, y over Rational Field
sage: r = 1 - x*y + x^2
sage: r.add_bigoh(4)
1 + x^2 - x*y + O(x, y)^4
sage: r.add_bigoh(2)
1 + O(x, y)^2
```

Note that this does not change self:

```
sage: r
1 + x^2 - x*y
```

coefficients()

Return a dict of monomials and coefficients.

EXAMPLES:

```
sage: R.<s,t> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in s, t over Integer Ring
sage: f = 1 + t + s + s*t + R.O(3)
sage: f.coefficients()
{s*t: 1, t: 1, s: 1, 1: 1}
sage: (f^2).coefficients()
{t^2: 1, s*t: 4, s^2: 1, t: 2, s: 2, 1: 1}

sage: g = f^2 + f - 2; g
3*s + 3*t + s^2 + 5*s*t + t^2 + O(s, t)^3
sage: cd = g.coefficients()
sage: g2 = sum(k*v for (k,v) in cd.iteritems()); g2
3*s + 3*t + s^2 + 5*s*t + t^2
sage: g2 == g.truncate()
True
```

constant_coefficient()

Return constant coefficient of self.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b, c over Integer Ring
sage: f = 3 + a + b - a*b - b*c - a*c + R.O(4)
sage: f.constant_coefficient()
3
sage: f.constant_coefficient().parent()
Integer Ring
```

degree()

Return degree of underlying polynomial of self.

EXAMPLES:

```
sage: B.<x,y> = PowerSeriesRing(QQ)
sage: B
Multivariate Power Series Ring in x, y over Rational Field
sage: r = 1 - x*y + x^2
sage: r = r.add_bigoh(4); r
1 + x^2 - x*y + O(x, y)^4
```

```
sage: r.degree()
2
```

derivative (*args)

The formal derivative of this power series, with respect to variables supplied in args.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a^2*b + T.O(5)
sage: f.derivative(a)
1 + 2*a*b + O(a, b)^4
sage: f.derivative(a,2)
2*b + O(a, b)^3
sage: f.derivative(a,a)
2*b + O(a, b)^3
sage: f.derivative([a,a])
2*b + O(a, b)^3
sage: f.derivative(a,5)
0 + O(a, b)^0
sage: f.derivative(a,6)
0 + O(a, b)^0
```

dict ()

Return underlying dictionary with keys the exponents and values the coefficients of this power series.

EXAMPLES:

```
sage: M = PowerSeriesRing(QQ,4,'t',sparse=True); M
Sparse Multivariate Power Series Ring in t0, t1, t2, t3 over
Rational Field

sage: M.inject_variables()
Defining t0, t1, t2, t3

sage: m = 2/3*t0*t1^15*t3^48 - t0^15*t1^21*t2^28*t3^5
sage: m2 = 1/2*t0^12*t1^29*t2^46*t3^6 - 1/4*t0^39*t1^5*t2^23*t3^30 + M.O(100)
sage: s = m + m2
sage: s.dict()
{(1, 15, 0, 48): 2/3,
 (12, 29, 46, 6): 1/2,
 (15, 21, 28, 5): -1,
 (39, 5, 23, 30): -1/4}
```

egf ()

Method from univariate power series not yet implemented

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.egf()
Traceback (most recent call last):
...
NotImplementedError: egf
```

exp (prec=+Infinity)

Exponentiate the formal power series.

INPUT:

•`prec` – Integer or infinity. The degree to truncate the result to.

OUTPUT:

The exponentiated multivariate power series as a new multivariate power series.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(3)
sage: exp(f)
1 + a + b + 1/2*a^2 + 2*a*b + 1/2*b^2 + O(a, b)^3
sage: f.exp()
1 + a + b + 1/2*a^2 + 2*a*b + 1/2*b^2 + O(a, b)^3
sage: f.exp(prec=2)
1 + a + b + O(a, b)^2
sage: log(exp(f)) - f
0 + O(a, b)^3
```

If the power series has a constant coefficient c and $\exp(c)$ is transcendental, then $\exp(f)$ would have to be a power series over the `SymbolicRing`. These are not yet implemented and therefore such cases raise an error:

```
sage: g = 2+f
sage: exp(g)
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for '*': 'Symbolic Ring' and
'Power Series Ring in Tbg over Multivariate Polynomial Ring in a, b
over Rational Field'
```

Another workaround for this limitation is to change base ring to one which is closed under exponentiation, such as \mathbf{R} or \mathbf{C} :

```
sage: exp(g.change_ring(RDF))
7.38905609... + 7.38905609...*a + 7.38905609...*b + 3.69452804...*a^2 +
14.7781121...*a*b + 3.69452804...*b^2 + O(a, b)^3
```

If no precision is specified, the default precision is used:

```
sage: T.default_prec()
12
sage: exp(a)
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + 1/120*a^5 + 1/720*a^6 + 1/5040*a^7 +
1/40320*a^8 + 1/362880*a^9 + 1/3628800*a^10 + 1/39916800*a^11 + O(a, b)^12
sage: a.exp(prec=5)
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + O(a, b)^5
sage: exp(a + T.O(5))
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + O(a, b)^5
```

TESTS:

```
sage: exp(a^2 + T.O(5))
1 + a^2 + 1/2*a^4 + O(a, b)^5
```

exponents()

Return a list of tuples which hold the exponents of each monomial of `self`.

EXAMPLES:

```
sage: H = QQ[['x,y']]
sage: (x,y) = H.gens()
```

```
sage: h = -y^2 - x*y^3 - 6/5*y^6 - x^7 + 2*x^5*y^2 + H.O(10)
sage: h
-y^2 - x*y^3 - 6/5*y^6 - x^7 + 2*x^5*y^2 + O(x, y)^10
sage: h.exponents()
[(0, 2), (1, 3), (0, 6), (7, 0), (5, 2)]
```

integral (*args)

The formal integral of this multivariate power series, with respect to variables supplied in args.

The variable sequence args can contain both variables and counts; for the syntax, see `derivative_parse()`.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(QQ,2)
sage: f = a + b + a^2*b + T.O(5)
sage: f.integral(a, 2)
1/6*a^3 + 1/2*a^2*b + 1/12*a^4*b + O(a, b)^7
sage: f.integral(a, b)
1/2*a^2*b + 1/2*a*b^2 + 1/6*a^3*b^2 + O(a, b)^7
sage: f.integral(a, 5)
1/720*a^6 + 1/120*a^5*b + 1/2520*a^7*b + O(a, b)^10
```

Only integration with respect to variables works:

```
sage: f.integral(a+b)
Traceback (most recent call last):
...
ValueError: a + b is not a variable
```

Warning: Coefficient division.

If the base ring is not a field (e.g. \mathbb{ZZ}), or if it has a non-zero characteristic, (e.g. $\mathbb{ZZ}/3\mathbb{ZZ}$), integration is not always possible while staying with the same base ring. In the first case, Sage will report that it has not been able to coerce some coefficient to the base ring:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + T.O(5)
sage: f.integral(a)
Traceback (most recent call last):
...
TypeError: no conversion of this rational to integer
```

One can get the correct result by changing the base ring first:

```
sage: f.change_ring(QQ).integral(a)
1/2*a^2 + O(a, b)^6
```

However, a correct result is returned even without base change if the denominator cancels:

```
sage: f = 2*b + T.O(5)
sage: f.integral(b)
b^2 + O(a, b)^6
```

In non-zero characteristic, Sage will report that a zero division occurred

```
sage: T.<a,b> = PowerSeriesRing(Zmod(3),2)
sage: (a^3).integral(a)
a^4
sage: (a^2).integral(a)
Traceback (most recent call last):
...
ZeroDivisionError: Inverse does not exist.
```

is_nilpotent()

Return True if self is nilpotent. This occurs if

- self has finite precision and positive valuation, or
- self is constant and nilpotent in base ring.

Otherwise, return False.

Warning: This is so far just a sufficient condition, so don't trust a False output to be legit!

Todo

What should we do about this method? Is nilpotency of a power series even decidable (assuming a nilpotency oracle in the base ring)? And I am not sure that returning True just because the series has finite precision and zero constant term is a good idea.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(Zmod(8)); R
Multivariate Power Series Ring in a, b, c over Ring of integers
modulo 8
sage: f = a + b + c + a^2*c
```



```

sage: f.is_nilpotent()
False
sage: f = f.O(4); f
a + b + c + a^2*c + O(a, b, c)^4
sage: f.is_nilpotent()
True

sage: g = R(2)
sage: g.is_nilpotent()
True
sage: (g.O(4)).is_nilpotent()
True

sage: S = R.change_ring(QQ)
sage: S(g).is_nilpotent()
False
sage: S(g.O(4)).is_nilpotent()
False

```

is_square()

Method from univariate power series not yet implemented.

TESTS:

```

sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.is_square()
Traceback (most recent call last):
...
NotImplementedError: is_square

```

is_unit()

A multivariate power series is a unit if and only if its constant coefficient is a unit.

EXAMPLES:

```

sage: R.<a,b> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b over Integer Ring
sage: f = 2 + a^2 + a*b + a^3 + R.O(9)
sage: f.is_unit()
False
sage: f.base_extend(QQ).is_unit()
True

```

laurent_series()

Not implemented for multivariate power series.

TESTS:

```

sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.laurent_series()
Traceback (most recent call last):
...
NotImplementedError: laurent_series not defined for multivariate power series.

```

list()

Doesn't make sense for multivariate power series. Multivariate polynomials don't have list of coefficients either.

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.list()
Traceback (most recent call last):
...
NotImplementedError: Multivariate power series do not have list
of coefficients; use 'coefficients' to get a dict of coefficients.
```

log (*prec*=+Infinity)

Return the logarithm of the formal power series.

INPUT:

- *prec* – Integer or infinity. The degree to truncate the result to.

OUTPUT:

The logarithm of the multivariate power series as a new multivariate power series.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = 1 + a + b + a*b + T.O(5)
sage: f.log()
a + b - 1/2*a^2 - 1/2*b^2 + 1/3*a^3 + 1/3*b^3 - 1/4*a^4 - 1/4*b^4 + O(a, b)^5
sage: log(f)
a + b - 1/2*a^2 - 1/2*b^2 + 1/3*a^3 + 1/3*b^3 - 1/4*a^4 - 1/4*b^4 + O(a, b)^5
sage: exp(log(f)) - f
0 + O(a, b)^5
```

If the power series has a constant coefficient c and $\exp(c)$ is transcendental, then $\exp(f)$ would have to be a power series over the `SymbolicRing`. These are not yet implemented and therefore such cases raise an error:

```
sage: g = 2+f
sage: log(g)
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for '-': 'Symbolic Ring' and 'Power
Series Ring in Tbg over Multivariate Polynomial Ring in a, b over Rational Field'
```

Another workaround for this limitation is to change base ring to one which is closed under exponentiation, such as **R** or **C**:

```
sage: log(g.change_ring(RDF))
1.09861228... + 0.333333333...*a + 0.333333333...*b - 0.055555555...*a^2
+ 0.222222222...*a*b - 0.055555555...*b^2 + 0.0123456790...*a^3
- 0.0740740740...*a^2*b - 0.0740740740...*a*b^2 + 0.0123456790...*b^3
- 0.00308641975...*a^4 + 0.0246913580...*a^3*b + 0.0246913580...*a*b^3
- 0.00308641975...*b^4 + O(a, b)^5
```

TESTS:

```
sage: (1+a).log(prec=10).exp()
1 + a + O(a, b)^10
sage: a.exp(prec=10).log()
a + O(a, b)^10

sage: log(1+a)
a - 1/2*a^2 + 1/3*a^3 - 1/4*a^4 + 1/5*a^5 - 1/6*a^6 + 1/7*a^7
```

```

- 1/8*a^8 + 1/9*a^9 - 1/10*a^10 + 1/11*a^11 + O(a, b)^12
sage: -log(1-a+T.O(5))
a + 1/2*a^2 + 1/3*a^3 + 1/4*a^4 + O(a, b)^5
sage: a.log(prec=10)
Traceback (most recent call last):
...
ValueError: Can only take formal power series for non-zero constant term.

```

monomials()

Return a list of monomials of self.

These are the keys of the dict returned by `coefficients()`.

EXAMPLES:

```

sage: R.<a,b,c> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b, c over Integer Ring
sage: f = 1 + a + b - a*b - b*c - a*c + R.O(4)
sage: f.monomials()
[1, b*c, b, a, a*c, a*b]
sage: f = 1 + 2*a + 7*b - 2*a*b - 4*b*c - 13*a*c + R.O(4)
sage: f.monomials()
[1, b*c, b, a, a*c, a*b]
sage: f = R.zero()
sage: f.monomials()
[]

```

ogf()

Method from univariate power series not yet implemented

TESTS:

```

sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.ogf()
Traceback (most recent call last):
...
NotImplementedError: ogf

```

padded_list()

Method from univariate power series not yet implemented.

TESTS:

```

sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.padded_list()
Traceback (most recent call last):
...
NotImplementedError: padded_list

```

polynomial()

Return the underlying polynomial of self as an element of the underlying multivariate polynomial ring (the “foreground polynomial ring”).

EXAMPLES:

```

sage: M = PowerSeriesRing(QQ,4,'t'); M
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational
Field
sage: t = M.gens()

```

```

sage: f = 1/2*t[0]^3*t[1]^3*t[2]^2 + 2/3*t[0]*t[2]^6*t[3] - t[0]^3*t[1]^3*t[3]^3
sage: f
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7 + O(t0, t1, t2, t3)^10

sage: f.polynomial()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7

sage: f.polynomial().parent()
Multivariate Polynomial Ring in t0, t1, t2, t3 over Rational Field

```

Contrast with `truncate()`:

```

sage: f.truncate()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3 - 1/4*t0*t1*t2^7
sage: f.truncate().parent()
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field

```

`prec()`

Return precision of `self`.

EXAMPLES:

```

sage: R.<a,b,c> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b, c over Integer Ring
sage: f = 3 + a + b - a*b - b*c - a*c + R.O(4)
sage: f.prec()
4
sage: f.truncate().prec()
+Infinity

```

`quo_rem(other, precision=None)`

Return the pair of quotient and remainder for the increasing power division of `self` by `other`.

If a and b are two elements of a power series ring $R[[x_1, x_2, \dots, x_n]]$ such that the trailing term of b is invertible in R , then the pair of quotient and remainder for the increasing power division of a by b is the unique pair $(u, v) \in R[[x_1, x_2, \dots, x_n]] \times R[[x_1, x_2, \dots, x_n]]$ such that $a = bu + v$ and such that no monomial appearing in v divides the trailing monomial (`trailing_monomial()`) of b . Note that this depends on the order of the variables.

This method returns both quotient and remainder as power series, even though in mathematics, the remainder for the increasing power division of two power series is a polynomial. This is because Sage's power series come with a precision, and that precision is not always sufficient to determine the remainder completely. Disregarding this issue, the `polynomial()` method can be used to recast the remainder as an actual polynomial.

INPUT:

- `other` – an element of the same power series ring as `self` such that the trailing term of `other` is invertible in `self` (this is automatically satisfied if the base ring is a field, unless `other` is zero)
- `precision` – (default: the default precision of the parent of `self`) nonnegative integer, determining the precision to be cast on the resulting quotient and remainder if both `self` and `other` have infinite precision (ignored otherwise); note that the resulting precision might be lower than this integer

EXAMPLES:

```

sage: R.<a,b,c> = PowerSeriesRing(ZZ)
sage: f = 1 + a + b - a*b + R.O(3)

```

```

sage: g = 1 + 2*a - 3*a*b + R.O(3)
sage: q, r = f.quo_rem(g); q, r
(1 - a + b + 2*a^2 + O(a, b, c)^3, 0 + O(a, b, c)^3)
sage: f == q*g+r
True

sage: q, r = (a*f).quo_rem(g); q, r
(a - a^2 + a*b + 2*a^3 + O(a, b, c)^4, 0 + O(a, b, c)^4)
sage: a*f == q*g+r
True

sage: q, r = (a*f).quo_rem(a*g); q, r
(1 - a + b + 2*a^2 + O(a, b, c)^3, 0 + O(a, b, c)^4)
sage: a*f == q*(a*g)+r
True

sage: q, r = (a*f).quo_rem(b*g); q, r
(a - 3*a^2 + O(a, b, c)^3, a + a^2 + O(a, b, c)^4)
sage: a*f == q*(b*g)+r
True

```

Trying to divide two polynomials, we run into the issue that there is no natural setting for the precision of the quotient and remainder (and if we wouldn't set a precision, the algorithm would never terminate). Here, default precision comes to our help:

```

sage: (1+a^3).quo_rem(a+a^2)
(a^2 - a^3 + a^4 - a^5 + a^6 - a^7 + a^8 - a^9 + a^10 + O(a, b, c)^11, 1 + O(a, b, c)^12)

sage: (1+a^3+a*b).quo_rem(b+c)
(a + O(a, b, c)^11, 1 - a*c + a^3 + O(a, b, c)^12)
sage: (1+a^3+a*b).quo_rem(b+c, precision=17)
(a + O(a, b, c)^16, 1 - a*c + a^3 + O(a, b, c)^17)

sage: (a^2+b^2+c^2).quo_rem(a+b+c)
(a - b - c + O(a, b, c)^11, 2*b^2 + 2*b*c + 2*c^2 + O(a, b, c)^12)

sage: (a^2+b^2+c^2).quo_rem(1/(1+a+b+c))
(a^2 + b^2 + c^2 + a^3 + a^2*b + a^2*c + a*b^2 + a*c^2 + b^3 + b^2*c + b*c^2 + c^3 + O(a, b, c)^13, 0)

sage: (a^2+b^2+c^2).quo_rem(a/(1+a+b+c))
(a + a^2 + a*b + a*c + O(a, b, c)^13, b^2 + c^2)

sage: (1+a+a^15).quo_rem(a^2)
(0 + O(a, b, c)^10, 1 + a + O(a, b, c)^12)
sage: (1+a+a^15).quo_rem(a^2, precision=15)
(0 + O(a, b, c)^13, 1 + a + O(a, b, c)^15)
sage: (1+a+a^15).quo_rem(a^2, precision=16)
(a^13 + O(a, b, c)^14, 1 + a + O(a, b, c)^16)

```

Illustrating the dependency on the ordering of variables:

```

sage: (1+a+b).quo_rem(b+c)
(1 + O(a, b, c)^11, 1 + a - c + O(a, b, c)^12)
sage: (1+b+c).quo_rem(c+a)
(0 + O(a, b, c)^11, 1 + b + c + O(a, b, c)^12)
sage: (1+c+a).quo_rem(a+b)
(1 + O(a, b, c)^11, 1 - b + c + O(a, b, c)^12)

```

TESTS:

```
sage: (f).quo_rem(R.zero())
Traceback (most recent call last):
...
ZeroDivisionError

sage: (f).quo_rem(R.zero().add_bigoh(2))
Traceback (most recent call last):
...
ZeroDivisionError
```

Coercion is applied on other:

```
sage: (a+b).quo_rem(1)
(a + b + O(a, b, c)^12, 0 + O(a, b, c)^12)

sage: R.<a,b,c> = PowerSeriesRing(QQ)
sage: R(3).quo_rem(2)
(3/2 + O(a, b, c)^12, 0 + O(a, b, c)^12)
```

shift (*n*)

Doesn't make sense for multivariate power series.

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.shift(3)
Traceback (most recent call last):
...
NotImplementedError: shift not defined for multivariate power series.
```

solve_linear_de (*prec=+Infinity, b=None, f0=None*)

Not implemented for multivariate power series.

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.solve_linear_de()
Traceback (most recent call last):
...
NotImplementedError: solve_linear_de not defined for multivariate power series.
```

sqrt ()

Method from univariate power series not yet implemented. Depends on square root method for multivariate polynomials.

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.square_root()
Traceback (most recent call last):
...
NotImplementedError: square_root
```

square_root ()

Method from univariate power series not yet implemented. Depends on square root method for multivariate polynomials.

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.square_root()
Traceback (most recent call last):
...
NotImplementedError: square_root
```

trailing_monomial()

Return the trailing monomial of *self*.

This is defined here as the lowest term of the underlying polynomial.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(ZZ)
sage: f = 1 + a + b - a*b + R.O(3)
sage: f.trailing_monomial()
1
sage: f = a^2*b^3*f; f
a^2*b^3 + a^3*b^3 + a^2*b^4 - a^3*b^4 + O(a, b, c)^8
sage: f.trailing_monomial()
a^2*b^3
```

TESTS:

```
sage: (f-f).trailing_monomial()
0
```

truncate (*prec*=+Infinity)

Return infinite precision multivariate power series formed by truncating *self* at precision *prec*.

EXAMPLES:

```
sage: M = PowerSeriesRing(QQ,4,'t'); M
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field
sage: t = M.gens()
sage: f = 1/2*t[0]^3*t[1]^3*t[2]^2 + 2/3*t[0]*t[2]^6*t[3] - t[0]^3*t[1]^3*t[3]^3
sage: f
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7 + O(t0, t1, t2, t3)^10

sage: f.truncate()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7
sage: f.truncate().parent()
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field
```

Contrast with polynomial:

```
sage: f.polynomial()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3 - 1/4*t0*t1*t2^7
sage: f.polynomial().parent()
Multivariate Polynomial Ring in t0, t1, t2, t3 over Rational Field
```

valuation()

Return the valuation of *self*.

The valuation of a power series *f* is the highest nonnegative integer *k* less or equal to the precision of *f* and such that the coefficient of *f* before each term of degree < *k* is zero. (If such an integer does not exist, then the valuation is the precision of *f* itself.)

EXAMPLES:

```
sage: R.<a,b> = PowerSeriesRing(GF(4949717)); R
Multivariate Power Series Ring in a, b over Finite Field of
size 4949717
sage: f = a^2 + a*b + a^3 + R.O(9)
sage: f.valuation()
2
sage: g = 1 + a + a^3
sage: g.valuation()
0
sage: R.zero().valuation()
+Infinity
```

valuation_zero_part()

Doesn't make sense for multivariate power series; valuation zero with respect to which variable?

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.valuation_zero_part()
Traceback (most recent call last):
...
NotImplementedError: valuation_zero_part not defined for multivariate
power series; perhaps 'constant_coefficient' is what you want.
```

variable()

Doesn't make sense for multivariate power series.

TESTS:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(5)
sage: f.variable()
Traceback (most recent call last):
...
NotImplementedError: variable not defined for multivariate power
series; use 'variables' instead.
```

variables()

Return tuple of variables occurring in self.

EXAMPLES:

```
sage: T = PowerSeriesRing(GF(3),5,'t'); T
Multivariate Power Series Ring in t0, t1, t2, t3, t4 over
Finite Field of size 3
sage: t = T.gens()
sage: w = t[0] - 2*t[0]*t[2] + 5*t[4]^3 - t[0]^3*t[2]^2 + T.O(6)
sage: w
t0 + t0*t2 - t4^3 - t0^3*t2^2 + O(t0, t1, t2, t3, t4)^6
sage: w.variables()
(t0, t2, t4)
```

```
sage.rings.multi_power_series_ring_element.is_MPowerSeries(f)
```

Return True if f is a multivariate power series.

TESTS:

```
sage: from sage.rings.power_series_ring_element import is_PowerSeries
sage: from sage.rings.multi_power_series_ring_element import is_MPowerSeries
```



```
sage: M = PowerSeriesRing(ZZ, 4, 'v');
sage: is_PowerSeries(M.random_element(10))
True
sage: is_MPowerSeries(M.random_element(10))
True
sage: T.<v> = PowerSeriesRing(RR)
sage: is_MPowerSeries(1 - v + v^2 + O(v^3))
False
sage: is_PowerSeries(1 - v + v^2 + O(v^3))
True
```


LAURENT SERIES RINGS

EXAMPLES:

```

sage: R = LaurentSeriesRing(QQ, "x")
sage: R.base_ring()
Rational Field
sage: S = LaurentSeriesRing(GF(17)['x'], 'y')
sage: S
Laurent Series Ring in y over Univariate Polynomial Ring in x over
Finite Field of size 17
sage: S.base_ring()
Univariate Polynomial Ring in x over Finite Field of size 17

```

See also:

- `sage.misc.defaults.set_series_precision()`

```

sage.rings.laurent_series_ring.LaurentSeriesRing(base_ring,          name=None,
                                                    names=None,      default_prec=None,
                                                    sparse=False)

```

EXAMPLES:

```

sage: R = LaurentSeriesRing(QQ, 'x'); R
Laurent Series Ring in x over Rational Field
sage: x = R.0
sage: g = 1 - x + x^2 - x^4 + O(x^8); g
1 - x + x^2 - x^4 + O(x^8)
sage: g = 10*x^(-3) + 2006 - 19*x + x^2 - x^4 + O(x^8); g
10*x^-3 + 2006 - 19*x + x^2 - x^4 + O(x^8)

```

You can also use more mathematical notation when the base is a field:

```

sage: Frac(QQ[['x']])
Laurent Series Ring in x over Rational Field
sage: Frac(GF(5)['y'])
Fraction Field of Univariate Polynomial Ring in y over Finite Field of size 5

```

Here the fraction field is not just the Laurent series ring, so you can't use the `Frac` notation to make the Laurent series ring.

```

sage: Frac(ZZ[['t']])
Fraction Field of Power Series Ring in t over Integer Ring

```

Laurent series rings are determined by their variable and the base ring, and are globally unique.

```

sage: K = Qp(5, prec = 5)
sage: L = Qp(5, prec = 200)
sage: R.<x> = LaurentSeriesRing(K)

```

```
sage: S.<y> = LaurentSeriesRing(L)
sage: R is S
False
sage: T.<y> = LaurentSeriesRing(Qp(5,prec=200))
sage: S is T
True
sage: W.<y> = LaurentSeriesRing(Qp(5,prec=199))
sage: W is T
False
```

TESTS:

Check if changing global series precision does it right (and that [trac ticket #17955](#) is fixed):

```
sage: set_series_precision(3)
sage: R.<x> = LaurentSeriesRing(ZZ)
sage: 1/(1 - 2*x)
1 + 2*x + 4*x^2 + O(x^3)
sage: set_series_precision(5)
sage: R.<x> = LaurentSeriesRing(ZZ)
sage: 1/(1 - 2*x)
1 + 2*x + 4*x^2 + 8*x^3 + 16*x^4 + O(x^5)
sage: set_series_precision(20)
```

```
class sage.rings.laurent_series_ring.LaurentSeriesRing_domain(base_ring,
                                                                name=None, de-
                                                                fault_prec=None,
                                                                sparse=False)

Bases:
    sage.rings.laurent_series_ring.LaurentSeriesRing_generic,
    sage.rings.ring.IntegralDomain

Initialization

TESTS:
sage: TestSuite(LaurentSeriesRing(ZZ, 't')).run()
```

```
class sage.rings.laurent_series_ring.LaurentSeriesRing_field(base_ring,
                                                             name=None, de-
                                                             fault_prec=None,
                                                             sparse=False)

Bases:
    sage.rings.laurent_series_ring.LaurentSeriesRing_generic,
    sage.rings.ring.Field

Initialization

TESTS:
sage: TestSuite(LaurentSeriesRing(QQ, 't')).run()
```

```
class sage.rings.laurent_series_ring.LaurentSeriesRing_generic(base_ring,
                                                                name=None, de-
                                                                fault_prec=None,
                                                                sparse=False,
                                                                category=None)

Bases: sage.rings.ring.CommutativeRing

Univariate Laurent Series Ring

EXAMPLES:
```

```

sage: K = LaurentSeriesRing(CC, 'q')
sage: K
Laurent Series Ring in q over Complex Field with 53 bits of precision
sage: loads(K.dumps()) == K
True
sage: P = QQ[['x']]
sage: F = Frac(P)
sage: TestSuite(F).run()

```

When the base ring k is a field, the ring $k((x))$ is a CDVF, that is a field equipped with a discrete valuation for which it is complete. The appropriate (sub)category is automatically set in this case:

```

sage: k = GF(11)
sage: R.<x> = k[[[]]]
sage: F = Frac(R)
sage: F.category()
Category of complete discrete valuation fields
sage: TestSuite(F).run()

```

Element

alias of `LaurentSeries`

base_extend(R)

Returns the laurent series ring over R in the same variable as self, assuming there is a canonical coerce map from the base ring of self to R.

EXAMPLES:

```

sage: K.<x> = LaurentSeriesRing(QQ, default_prec=4)
sage: K.base_extend(QQ[['t']])
Laurent Series Ring in x over Univariate Polynomial Ring in t over Rational Field

```

change_ring(R)

EXAMPLES:

```

sage: K.<x> = LaurentSeriesRing(QQ, default_prec=4)
sage: R = K.change_ring(ZZ); R
Laurent Series Ring in x over Integer Ring
sage: R.default_prec()
4

```

characteristic()

EXAMPLES:

```

sage: R.<x> = LaurentSeriesRing(GF(17))
sage: R.characteristic()
17

```

default_prec()

Get the precision to which exact elements are truncated when necessary (most frequently when inverting).

EXAMPLES:

```

sage: R.<x> = LaurentSeriesRing(QQ, default_prec=5)
sage: R.default_prec()
5

```

gen(n=0)

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.gen()
x
```

is_dense()

EXAMPLES:

```
sage: K.<x> = LaurentSeriesRing(QQ, sparse=True)
sage: K.is_dense()
False
```

is_exact()

Laurent series rings are inexact.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.is_exact()
False
```

is_field(*proof=True*)

A Laurent series ring is a field if and only if the base ring is a field.

TESTS:

```
sage: LaurentSeriesRing(QQ, 't').is_field()
True
sage: LaurentSeriesRing(ZZ, 't').is_field()
False
```

is_sparse()

EXAMPLES:

```
sage: K.<x> = LaurentSeriesRing(QQ, sparse=True)
sage: K.is_sparse()
True
```

laurent_polynomial_ring()If this is the Laurent series ring $R((t))$, return the Laurent polynomial ring $R[t, 1/t]$.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.laurent_polynomial_ring()
Univariate Laurent Polynomial Ring in x over Rational Field
```

ngens()

Laurent series rings are univariate.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.ngens()
1
```

polynomial_ring()If this is the Laurent series ring $R((t))$, return the polynomial ring $R[t]$.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.polynomial_ring()
```

Univariate Polynomial Ring in x over Rational Field

power_series_ring()

If this is the Laurent series ring $R((t))$, return the power series ring $R[[t]]$.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.power_series_ring()
Power Series Ring in x over Rational Field
```

residue_field()

Return the residue field of this Laurent series field if it is a complete discrete valuation field (i.e. if the base ring is a field, in which case it is also the residue field).

EXAMPLES:

```
sage: R.<x> = LaurentSeriesRing(GF(17))
sage: R.residue_field()
Finite Field of size 17
```

```
sage: R.<x> = LaurentSeriesRing(ZZ)
sage: R.residue_field()
Traceback (most recent call last):
...
TypeError: The base ring is not a field
```

set_default_prec(n)

Set the default precision.

This method is deprecated.

TESTS:

```
sage: R.<x> = LaurentSeriesRing(QQ)
sage: R.set_default_prec(3)
doctest:...: DeprecationWarning: This method is deprecated.
See http://trac.sagemath.org/16201 for details.
sage: 1/(x^5-x^7)
x^-5 + x^-3 + O(x^-2)
```

uniformizer()

Return a uniformizer of this Laurent series field if it is a discrete valuation field (i.e. if the base ring is actually a field). Otherwise, an error is raised.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: R.uniformizer()
t

sage: R.<t> = LaurentSeriesRing(ZZ)
sage: R.uniformizer()
Traceback (most recent call last):
...
TypeError: The base ring is not a field
```

`sage.rings.laurent_series_ring.is_LaurentSeriesRing(x)`

TESTS:

```
sage: from sage.rings.laurent_series_ring import is_LaurentSeriesRing
sage: K.<q> = LaurentSeriesRing(QQ)
sage: is_LaurentSeriesRing(K)
True
```


LAURENT SERIES

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(GF(7), 't'); R
Laurent Series Ring in t over Finite Field of size 7
sage: f = 1/(1-t+O(t^10)); f
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + t^9 + O(t^10)
```

Laurent series are immutable:

```
sage: f[2]
1
sage: f[2] = 5
Traceback (most recent call last):
...
IndexError: Laurent series are immutable
```

We compute with a Laurent series over the complex mpfr numbers.

```
sage: K.<q> = Frac(CC[['q']])
sage: K
Laurent Series Ring in q over Complex Field with 53 bits of precision
sage: q
1.000000000000000*q
```

Saving and loading.

```
sage: loads(q.dumps()) == q
True
sage: loads(K.dumps()) == K
True
```

IMPLEMENTATION: Laurent series in Sage are represented internally as a power of the variable times the unit part (which need not be a unit - it's a polynomial with nonzero constant term). The zero Laurent series has unit part 0.

AUTHORS:

- William Stein: original version
- David Joyner (2006-01-22): added examples
- Robert Bradshaw (2007-04): optimizations, shifting
- Robert Bradshaw: Cython version

```
class sage.rings.laurent_series_ring_element.LaurentSeries
    Bases: sage.structure.element.AlgebraElement
```

A Laurent Series.

We consider a Laurent series of the form $t^n \cdot f$ where f is a power series.

INPUT:

- `parent` – a Laurent series ring
- `f` – a power series (or something can be coerced to one); note that `f` does *not* have to be a unit
- `n` – (default: 0) integer

add_bigoh(*prec*)

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = t^2 + t^3 + O(t^10); f
t^2 + t^3 + O(t^10)
sage: f.add_bigoh(5)
t^2 + t^3 + O(t^5)
```

change_ring(*R*)

coefficients()

Return the nonzero coefficients of self.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = -5/t^(2) + t + t^2 - 10/3*t^3
sage: f.coefficients()
[-5, 1, 1, -10/3]
```

common_prec(*other*)

Return the minimum precision of self and other.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)

sage: f = t^(-1) + t + t^2 + O(t^3)
sage: g = t + t^3 + t^4 + O(t^4)
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3

sage: f = t + t^2 + O(t^3)
sage: g = t^(-3) + t^2
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3

sage: f = t + t^2
sage: g = t^2
sage: f.common_prec(g)
+Infinity

sage: f = t^(-3) + O(t^(-2))
sage: g = t^(-5) + O(t^(-1))
sage: f.common_prec(g)
-2
```

```

sage: f = O(t^2)
sage: g = O(t^5)
sage: f.common_prec(g)
2

```

common_valuation(*other*)

Return the minimum valuation of *self* and *other*.

EXAMPLES:

```

sage: R.<t> = LaurentSeriesRing(QQ)

```

```

sage: f = t^(-1) + t + t^2 + O(t^3)
sage: g = t + t^3 + t^4 + O(t^4)
sage: f.common_valuation(g)
-1
sage: g.common_valuation(f)
-1

```

```

sage: f = t + t^2 + O(t^3)
sage: g = t^(-3) + t^2
sage: f.common_valuation(g)
-3
sage: g.common_valuation(f)
-3

```

```

sage: f = t + t^2
sage: g = t^2
sage: f.common_valuation(g)
1

```

```

sage: f = t^(-3) + O(t^(-2))
sage: g = t^(-5) + O(t^(-1))
sage: f.common_valuation(g)
-5

```

```

sage: f = O(t^2)
sage: g = O(t^5)
sage: f.common_valuation(g)
+Infinity

```

degree()

Return the degree of a polynomial equivalent to this power series modulo big oh of the precision.

EXAMPLES:

```

sage: x = Frac(QQ[['x']]).0
sage: g = x^2 - x^4 + O(x^8)
sage: g.degree()
4
sage: g = -10/x^5 + x^2 - x^4 + O(x^8)
sage: g.degree()
4
sage: (x^-2 + O(x^0)).degree()
-2

```

derivative(*args)

The formal derivative of this Laurent series, with respect to variables supplied in *args*.

Multiple variables and iteration counts may be supplied; see documentation for the global `derivative()`

function for more details.

See also:

`_derivative()`

EXAMPLES:

```
sage: R.<x> = LaurentSeriesRing(QQ)
sage: g = 1/x^10 - x + x^2 - x^4 + O(x^8)
sage: g.derivative()
-10*x^-11 - 1 + 2*x - 4*x^3 + O(x^7)
sage: g.derivative(x)
-10*x^-11 - 1 + 2*x - 4*x^3 + O(x^7)

sage: R.<t> = PolynomialRing(ZZ)
sage: S.<x> = LaurentSeriesRing(R)
sage: f = 2*t/x + (3*t^2 + 6*t)*x + O(x^2)
sage: f.derivative()
-2*t*x^-2 + (3*t^2 + 6*t) + O(x)
sage: f.derivative(x)
-2*t*x^-2 + (3*t^2 + 6*t) + O(x)
sage: f.derivative(t)
2*x^-1 + (6*t + 6)*x + O(x^2)
```

exponents()

Return the exponents appearing in self with nonzero coefficients.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = -5/t^2 + t + t^2 - 10/3*t^3
sage: f.exponents()
[-2, 1, 2, 3]
```

integral()

The formal integral of this Laurent series with 0 constant term.

EXAMPLES: The integral may or may not be defined if the base ring is not a field.

```
sage: t = LaurentSeriesRing(ZZ, 't').0
sage: f = 2*t^-3 + 3*t^2 + O(t^4)
sage: f.integral()
-t^-2 + t^3 + O(t^5)
```

```
sage: f = t^3
sage: f.integral()
Traceback (most recent call last):
...
ArithmeticError: Coefficients of integral cannot be coerced into the base ring
```

The integral of $1/t$ is $\log(t)$, which is not given by a Laurent series:

```
sage: t = Frac(QQ[['t']]).0
sage: f = -1/t^3 - 31/t + O(t^3)
sage: f.integral()
Traceback (most recent call last):
...
ArithmeticError: The integral of is not a Laurent series, since t^-1 has nonzero coefficient
```

Another example with just one negative coefficient:

```

sage: A.<t> = QQ[[[]]
sage: f = -2*t^(-4) + O(t^8)
sage: f.integral()
2/3*t^-3 + O(t^9)
sage: f.integral().derivative() == f
True

```

inverse()

Return the inverse of self, i.e., self^{-1} .

EXAMPLES:

```

sage: R.<t> = LaurentSeriesRing(ZZ)
sage: t.inverse()
t^-1
sage: (1-t).inverse()
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + ...

```

is_monomial()

Return True if this element is a monomial. That is, if self is x^n for some integer n .

EXAMPLES:

```

sage: k.<z> = LaurentSeriesRing(QQ, 'z')
sage: (30*z).is_monomial()
False
sage: k(1).is_monomial()
True
sage: (z+1).is_monomial()
False
sage: (z^-2909).is_monomial()
True
sage: (3*z^-2909).is_monomial()
False

```

is_unit()

Returns True if this is Laurent series is a unit in this ring.

EXAMPLES:

```

sage: R.<t> = LaurentSeriesRing(QQ)
sage: (2+t).is_unit()
True
sage: f = 2+t^2+O(t^10); f.is_unit()
True
sage: 1/f
1/2 - 1/4*t^2 + 1/8*t^4 - 1/16*t^6 + 1/32*t^8 + O(t^10)
sage: R(0).is_unit()
False
sage: R.<s> = LaurentSeriesRing(ZZ)
sage: f = 2 + s^2 + O(s^10)
sage: f.is_unit()
False
sage: 1/f
Traceback (most recent call last):
...
ArithmeticError: division not defined

```

ALGORITHM: A Laurent series is a unit if and only if its “unit part” is a unit.

is_zero()

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: f = 1/x + x + x^2 + 3*x^4 + O(x^7)
sage: f.is_zero()
0
sage: z = 0*f
sage: z.is_zero()
1
```

laurent_polynomial()

Return the corresponding Laurent polynomial.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = t^-3 + t + 7*t^2 + O(t^5)
sage: g = f.laurent_polynomial(); g
t^-3 + t + 7*t^2
sage: g.parent()
Univariate Laurent Polynomial Ring in t over Rational Field
```

list()

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = -5/t^(2) + t + t^2 - 10/3*t^3
sage: f.list()
[-5, 0, 0, 1, 1, -10/3]
```

power_series()

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(ZZ)
sage: f = 1/(1-t+O(t^10)); f.parent()
Laurent Series Ring in t over Integer Ring
sage: g = f.power_series(); g
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + t^9 + O(t^10)
sage: parent(g)
Power Series Ring in t over Integer Ring
sage: f = 3/t^2 + t^2 + t^3 + O(t^10)
sage: f.power_series()
Traceback (most recent call last):
...
TypeError: self is not a power series
```

TESTS:

Check whether a polynomial over a Laurent series ring is contained in the polynomial ring over the power series ring (see [trac ticket #19459](#)):

```
sage: L.<t> = LaurentSeriesRing(GF(2)) sage: R.<x,y> = PolynomialRing(L) sage: O =
L.power_series_ring() sage: S.<x,y> = PolynomialRing(O) sage: t**(-1)*x*y in S False
```

prec()

This function returns the n so that the Laurent series is of the form $(\text{stuff}) + O(t^n)$. It doesn't matter how many negative powers appear in the expansion. In particular, `prec` could be negative.

EXAMPLES:

```

sage: x = Frac(QQ[['x']]).0
sage: f = x^2 + 3*x^4 + O(x^7)
sage: f.prec()
7
sage: g = 1/x^10 - x + x^2 - x^4 + O(x^8)
sage: g.prec()
8

```

precision_absolute()

Return the absolute precision of this series.

By definition, the absolute precision of $\dots + O(x^r)$ is r .

EXAMPLES:

```

sage: R.<t> = ZZ[[[]]]
sage: (t^2 + O(t^3)).precision_absolute()
3
sage: (1 - t^2 + O(t^100)).precision_absolute()
100

```

precision_relative()

Return the relative precision of this series, that is the difference between its absolute precision and its valuation.

By convention, the relative precision of 0 (or $O(x^r)$ for any r) is 0.

EXAMPLES:

```

sage: R.<t> = ZZ[[[]]]
sage: (t^2 + O(t^3)).precision_relative()
1
sage: (1 - t^2 + O(t^100)).precision_relative()
100
sage: O(t^4).precision_relative()
0

```

residue()

Return the residue of `self`.

Consider the Laurent series

$$f = \sum_{n \in \mathbb{Z}} a_n t^n = \dots + \frac{a_{-2}}{t^2} + \frac{a_{-1}}{t} + a_0 + a_1 t + a_2 t^2 + \dots,$$

then the residue of f is a_{-1} . Alternatively this is the coefficient of $1/t$.

EXAMPLES:

```

sage: t = LaurentSeriesRing(ZZ, 't').gen()
sage: f = 1/t**2 + 2/t + 3 + 4*t
sage: f.residue()
2
sage: f = t + t**2
sage: f.residue()
0
sage: f.residue().parent()
Integer Ring

```

shift(k)

Returns this Laurent series multiplied by the power t^k . Does not change this series.

Note: Despite the fact that higher order terms are printed to the right in a power series, right shifting decreases the powers of t , while left shifting increases them. This is to be consistent with polynomials, integers, etc.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ['y'])
sage: f = (t+t^-1)^4; f
t^-4 + 4*t^-2 + 6 + 4*t^2 + t^4
sage: f.shift(10)
t^6 + 4*t^8 + 6*t^10 + 4*t^12 + t^14
sage: f >> 10
t^-14 + 4*t^-12 + 6*t^-10 + 4*t^-8 + t^-6
sage: t << 4
t^5
sage: t + O(t^3) >> 4
t^-3 + O(t^-1)
```

AUTHORS:

- Robert Bradshaw (2007-04-18)

truncate(n)

Returns the laurent series of degree ' $< n$ ' which is equivalent to self modulo x^n .

EXAMPLES:

```
sage: A.<x> = LaurentSeriesRing(ZZ)
sage: f = 1/(1-x)
sage: f
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + x^10 + x^11 + x^12 + x^13 + x^14 + x^15 + ...
sage: f.truncate(10)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9
```

truncate_laurentseries(n)

Replaces any terms of degree $\geq n$ by big oh

EXAMPLES:

```
sage: A.<x> = LaurentSeriesRing(ZZ)
sage: f = 1/(1-x)
sage: f
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + x^10 + x^11 + x^12 + x^13 + x^14 + x^15 + ...
sage: f.truncate_laurentseries(10)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + O(x^10)
```

truncate_neg(n)

Returns the laurent series equivalent to self except without any degree n terms.

This is equivalent to `'self - self.truncate(n)'`.

valuation()**EXAMPLES:**

```
sage: R.<x> = LaurentSeriesRing(QQ)
sage: f = 1/x + x^2 + 3*x^4 + O(x^7)
sage: g = 1 - x + x^2 - x^4 + O(x^8)
sage: f.valuation()
-1
sage: g.valuation()
0
```


Note that the valuation of an element undistinguishable from zero is infinite:

```
sage: h = f - f; h
O(x^7)
sage: h.valuation()
+Infinity
```

TESTS:

The valuation of the zero element is `+Infinity` (see [trac ticket #15088](#)):

```
sage: zero = R(0)
sage: zero.valuation()
+Infinity
```

valuation_zero_part()

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: f = x + x^2 + 3*x^4 + O(x^7)
sage: f/x
1 + x + 3*x^3 + O(x^6)
sage: f.valuation_zero_part()
1 + x + 3*x^3 + O(x^6)
sage: g = 1/x^7 - x + x^2 - x^4 + O(x^8)
sage: g.valuation_zero_part()
1 - x^8 + x^9 - x^11 + O(x^15)
```

variable()

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: f = 1/x + x^2 + 3*x^4 + O(x^7)
sage: f.variable()
'x'
```

```
sage.rings.laurent_series_ring_element.is_LaurentSeries(x)
```

```
sage.rings.laurent_series_ring_element.make_element_from_parent(parent, *args)
```


INDICES AND TABLES

- Index
- Module Index
- Search Page

r

`sage.rings.laurent_series_ring`, [63](#)
`sage.rings.laurent_series_ring_element`, [69](#)
`sage.rings.multi_power_series_ring`, [35](#)
`sage.rings.multi_power_series_ring_element`, [43](#)
`sage.rings.power_series_poly`, [29](#)
`sage.rings.power_series_ring`, [1](#)
`sage.rings.power_series_ring_element`, [13](#)

A

`add_bigoh()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 70
`add_bigoh()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 47
`add_bigoh()` (sage.rings.power_series_ring_element.PowerSeries method), 14

B

`base_extend()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 65
`base_extend()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 6
`base_extend()` (sage.rings.power_series_ring_element.PowerSeries method), 15
`base_ring()` (sage.rings.power_series_ring_element.PowerSeries method), 15
`bigoh()` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 38

C

`change_ring()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 65
`change_ring()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 70
`change_ring()` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 38
`change_ring()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 6
`change_ring()` (sage.rings.power_series_ring_element.PowerSeries method), 15
`change_var()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 7
`characteristic()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 65
`characteristic()` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 39
`characteristic()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 7
`coefficients()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 70
`coefficients()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 48
`coefficients()` (sage.rings.power_series_ring_element.PowerSeries method), 16
`common_prec()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 70
`common_prec()` (sage.rings.power_series_ring_element.PowerSeries method), 16
`common_valuation()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 71
`constant_coefficient()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 48
`construction()` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 39
`construction()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 7

D

`default_prec()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 65
`degree()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 71
`degree()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 48
`degree()` (sage.rings.power_series_poly.PowerSeries_poly method), 29

`degree()` (sage.rings.power_series_ring_element.PowerSeries method), 16
`derivative()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 71
`derivative()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 49
`derivative()` (sage.rings.power_series_ring_element.PowerSeries method), 16
`dict()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 49
`dict()` (sage.rings.power_series_poly.PowerSeries_poly method), 29

E

`egf()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 49
`egf()` (sage.rings.power_series_ring_element.PowerSeries method), 17
`egf_to_ogf()` (sage.rings.power_series_ring_element.PowerSeries method), 17
`Element` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic attribute), 65
`Element` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic attribute), 38
`Element` (sage.rings.power_series_ring.PowerSeriesRing_generic attribute), 6
`exp()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 49
`exp()` (sage.rings.power_series_ring_element.PowerSeries method), 17
`exponents()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 72
`exponents()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 50
`exponents()` (sage.rings.power_series_ring_element.PowerSeries method), 18

F

`fraction_field()` (sage.rings.power_series_ring.PowerSeriesRing_over_field method), 11

G

`gen()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 65
`gen()` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 39
`gen()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 7

I

`integral()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 72
`integral()` (sage.rings.multi_power_series_ring_element.MPowerSeries method), 51
`integral()` (sage.rings.power_series_poly.PowerSeries_poly method), 29
`inverse()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 73
`inverse()` (sage.rings.power_series_ring_element.PowerSeries method), 18
`is_dense()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 66
`is_dense()` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 40
`is_dense()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 7
`is_dense()` (sage.rings.power_series_ring_element.PowerSeries method), 18
`is_exact()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 66
`is_exact()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 8
`is_field()` (sage.rings.laurent_series_ring.LaurentSeriesRing_generic method), 66
`is_field()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 8
`is_finite()` (sage.rings.power_series_ring.PowerSeriesRing_generic method), 8
`is_gen()` (sage.rings.power_series_ring_element.PowerSeries method), 19
`is_integral_domain()` (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 40
`is_LaurentSeries()` (in module sage.rings.laurent_series_ring_element), 77
`is_LaurentSeriesRing()` (in module sage.rings.laurent_series_ring), 67
`is_monomial()` (sage.rings.laurent_series_ring_element.LaurentSeries method), 73
`is_monomial()` (sage.rings.power_series_ring_element.PowerSeries method), 19
`is_MPowerSeries()` (in module sage.rings.multi_power_series_ring_element), 60

[is_MPowerSeriesRing\(\)](#) (in module `sage.rings.multi_power_series_ring`), 42
[is_nilpotent\(\)](#) (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 52
[is_noetherian\(\)](#) (`sage.rings.multi_power_series_ring.MPowerSeriesRing_generic` method), 40
[is_PowerSeries\(\)](#) (in module `sage.rings.power_series_ring_element`), 27
[is_PowerSeriesRing\(\)](#) (in module `sage.rings.power_series_ring`), 11
[is_sparse\(\)](#) (`sage.rings.laurent_series_ring.LaurentSeriesRing_generic` method), 66
[is_sparse\(\)](#) (`sage.rings.multi_power_series_ring.MPowerSeriesRing_generic` method), 40
[is_sparse\(\)](#) (`sage.rings.power_series_ring.PowerSeriesRing_generic` method), 8
[is_sparse\(\)](#) (`sage.rings.power_series_ring_element.PowerSeries` method), 19
[is_square\(\)](#) (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 53
[is_square\(\)](#) (`sage.rings.power_series_ring_element.PowerSeries` method), 19
[is_unit\(\)](#) (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 73
[is_unit\(\)](#) (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 53
[is_unit\(\)](#) (`sage.rings.power_series_ring_element.PowerSeries` method), 20
[is_zero\(\)](#) (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 73

L

[laurent_polynomial\(\)](#) (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 74
[laurent_polynomial_ring\(\)](#) (`sage.rings.laurent_series_ring.LaurentSeriesRing_generic` method), 66
[laurent_series\(\)](#) (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 53
[laurent_series\(\)](#) (`sage.rings.power_series_ring_element.PowerSeries` method), 20
[laurent_series_ring\(\)](#) (`sage.rings.multi_power_series_ring.MPowerSeriesRing_generic` method), 40
[laurent_series_ring\(\)](#) (`sage.rings.power_series_ring.PowerSeriesRing_generic` method), 8
[LaurentSeries](#) (class in `sage.rings.laurent_series_ring_element`), 69
[LaurentSeriesRing\(\)](#) (in module `sage.rings.laurent_series_ring`), 63
[LaurentSeriesRing_domain](#) (class in `sage.rings.laurent_series_ring`), 64
[LaurentSeriesRing_field](#) (class in `sage.rings.laurent_series_ring`), 64
[LaurentSeriesRing_generic](#) (class in `sage.rings.laurent_series_ring`), 64
[list\(\)](#) (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 74
[list\(\)](#) (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 53
[list\(\)](#) (`sage.rings.power_series_poly.PowerSeries_poly` method), 30
[list\(\)](#) (`sage.rings.power_series_ring_element.PowerSeries` method), 20
[log\(\)](#) (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 54
[log\(\)](#) (`sage.rings.power_series_ring_element.PowerSeries` method), 21

M

[make_element_from_parent\(\)](#) (in module `sage.rings.laurent_series_ring_element`), 77
[make_element_from_parent_v0\(\)](#) (in module `sage.rings.power_series_ring_element`), 27
[make_powerseries_poly_v0\(\)](#) (in module `sage.rings.power_series_poly`), 34
[make_powerseries_poly_v0\(\)](#) (in module `sage.rings.power_series_ring_element`), 27
[MO](#) (class in `sage.rings.multi_power_series_ring_element`), 45
[monomials\(\)](#) (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 55
[MPowerSeries](#) (class in `sage.rings.multi_power_series_ring_element`), 46
[MPowerSeriesRing_generic](#) (class in `sage.rings.multi_power_series_ring`), 38

N

[ngens\(\)](#) (`sage.rings.laurent_series_ring.LaurentSeriesRing_generic` method), 66
[ngens\(\)](#) (`sage.rings.multi_power_series_ring.MPowerSeriesRing_generic` method), 41
[ngens\(\)](#) (`sage.rings.power_series_ring.PowerSeriesRing_generic` method), 8

O

`O()` (`sage.rings.multi_power_series_ring.MPowerSeriesRing_generic` method), 38
`O()` (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 47
`O()` (`sage.rings.power_series_ring_element.PowerSeries` method), 14
`ogf()` (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 55
`ogf()` (`sage.rings.power_series_ring_element.PowerSeries` method), 21
`ogf_to_egf()` (`sage.rings.power_series_ring_element.PowerSeries` method), 21

P

`padded_list()` (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 55
`padded_list()` (`sage.rings.power_series_ring_element.PowerSeries` method), 21
`pade()` (`sage.rings.power_series_poly.PowerSeries_poly` method), 30
`polynomial()` (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 55
`polynomial()` (`sage.rings.power_series_poly.PowerSeries_poly` method), 31
`polynomial()` (`sage.rings.power_series_ring_element.PowerSeries` method), 22
`polynomial_ring()` (`sage.rings.laurent_series_ring.LaurentSeriesRing_generic` method), 66
`power_series()` (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 74
`power_series_ring()` (`sage.rings.laurent_series_ring.LaurentSeriesRing_generic` method), 67
`PowerSeries` (class in `sage.rings.power_series_ring_element`), 14
`PowerSeries_poly` (class in `sage.rings.power_series_poly`), 29
`PowerSeriesRing()` (in module `sage.rings.power_series_ring`), 2
`PowerSeriesRing_domain` (class in `sage.rings.power_series_ring`), 5
`PowerSeriesRing_generic` (class in `sage.rings.power_series_ring`), 6
`PowerSeriesRing_over_field` (class in `sage.rings.power_series_ring`), 10
`prec()` (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 74
`prec()` (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 56
`prec()` (`sage.rings.power_series_ring_element.PowerSeries` method), 22
`prec_ideal()` (`sage.rings.multi_power_series_ring.MPowerSeriesRing_generic` method), 41
`precision_absolute()` (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 75
`precision_absolute()` (`sage.rings.power_series_ring_element.PowerSeries` method), 22
`precision_relative()` (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 75
`precision_relative()` (`sage.rings.power_series_ring_element.PowerSeries` method), 22

Q

`quo_rem()` (`sage.rings.multi_power_series_ring_element.MPowerSeries` method), 56

R

`random_element()` (`sage.rings.power_series_ring.PowerSeriesRing_generic` method), 8
`remove_var()` (`sage.rings.multi_power_series_ring.MPowerSeriesRing_generic` method), 41
`residue()` (`sage.rings.laurent_series_ring_element.LaurentSeries` method), 75
`residue_field()` (`sage.rings.laurent_series_ring.LaurentSeriesRing_generic` method), 67
`residue_field()` (`sage.rings.power_series_ring.PowerSeriesRing_generic` method), 9
`reverse()` (`sage.rings.power_series_poly.PowerSeries_poly` method), 31
`reversion()` (`sage.rings.power_series_poly.PowerSeries_poly` method), 33

S

`sage.rings.laurent_series_ring` (module), 63
`sage.rings.laurent_series_ring_element` (module), 69
`sage.rings.multi_power_series_ring` (module), 35

[sage.rings.multi_power_series_ring_element \(module\)](#), 43
[sage.rings.power_series_poly \(module\)](#), 29
[sage.rings.power_series_ring \(module\)](#), 1
[sage.rings.power_series_ring_element \(module\)](#), 13
[set_default_prec\(\) \(sage.rings.laurent_series_ring.LaurentSeriesRing_generic method\)](#), 67
[shift\(\) \(sage.rings.laurent_series_ring_element.LaurentSeries method\)](#), 75
[shift\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 58
[shift\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 23
[solve_linear_de\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 58
[solve_linear_de\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 23
[sqrt\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 58
[sqrt\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 24
[square_root\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 58
[square_root\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 25

T

[term_order\(\) \(sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method\)](#), 41
[trailing_monomial\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 59
[truncate\(\) \(sage.rings.laurent_series_ring_element.LaurentSeries method\)](#), 76
[truncate\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 59
[truncate\(\) \(sage.rings.power_series_poly.PowerSeries_poly method\)](#), 33
[truncate\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 26
[truncate_laurentseries\(\) \(sage.rings.laurent_series_ring_element.LaurentSeries method\)](#), 76
[truncate_neg\(\) \(sage.rings.laurent_series_ring_element.LaurentSeries method\)](#), 76
[truncate_powerseries\(\) \(sage.rings.power_series_poly.PowerSeries_poly method\)](#), 34

U

[uniformizer\(\) \(sage.rings.laurent_series_ring.LaurentSeriesRing_generic method\)](#), 67
[uniformizer\(\) \(sage.rings.power_series_ring.PowerSeriesRing_generic method\)](#), 9
[unpickle_multi_power_series_ring_v0\(\) \(in module sage.rings.multi_power_series_ring\)](#), 42
[unpickle_power_series_ring_v0\(\) \(in module sage.rings.power_series_ring\)](#), 11

V

[V\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 47
[V\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 14
[valuation\(\) \(sage.rings.laurent_series_ring_element.LaurentSeries method\)](#), 76
[valuation\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 59
[valuation\(\) \(sage.rings.power_series_poly.PowerSeries_poly method\)](#), 34
[valuation\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 26
[valuation_zero_part\(\) \(sage.rings.laurent_series_ring_element.LaurentSeries method\)](#), 77
[valuation_zero_part\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 60
[valuation_zero_part\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 27
[variable\(\) \(sage.rings.laurent_series_ring_element.LaurentSeries method\)](#), 77
[variable\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 60
[variable\(\) \(sage.rings.power_series_ring_element.PowerSeries method\)](#), 27
[variable_names_recursive\(\) \(sage.rings.power_series_ring.PowerSeriesRing_generic method\)](#), 10
[variables\(\) \(sage.rings.multi_power_series_ring_element.MPowerSeries method\)](#), 60