

INSERT THIS SIDE UP, THIS END FIRST. USE BLACK
FELT-TIPPED INK, FILL OVALS COMPLETELY



Pulse/
Serial \$1/\$5
Credit Lines

MDB \$1-20
Credit Lines

RS-232 Always
Enabled

Parallel Hi

Special 1 Special 2

**section
1**

Select
only one
Interface
Type

**section
2**

Pulses
per Dollar
(sum of
selected
values)

64 4

32 2

16 1

8 None

Example:
For 50 ppd, fill
in the ovals for
32, 16, and 2,
(32+16+2 = 50)

Pulse Speed: Slow Fast

Lighted Bezel: Solid On Flashing

**section
3**

**section
4**

Select
Bills to
Enable

Bill 1 (\$1) Bill 2 (\$5)

Bill 3 (\$10) Bill 4 (\$20)

Bill 5 (\$50) Bill 6 (\$100)

Bill 7 Bill 8

Bill 9 Bill 10

Bill 11 Bill 12

Example:
To accept USA
\$1, \$5, and \$10,
fill in the ovals
for Bill 1, Bill 2,
and Bill 3.

Security Level: High Low

Insert Direction: Face up,
Left 1st All 4
Ways

**section
5**

This Configuration Card should be printed on standard
copy paper, measuring 6.0 x 2.6 inches (152 x 66 mm).

If printing from a .PDF file, turn off the "shrink to fit"
option in your printer settings for proper scale.



PYRAMID TECHNOLOGIES, INC.

CURRENCY VALIDATION EXPERTS