

AsymAgentMark-TK: Weakly Asymmetric Behavioral Watermarking for LLM Agents

Abstract—Autonomous large language model (LLM) agents increasingly act through tool calls, subgoal choices, and embodied decisions, so provenance must cover behavior trajectories rather than final text alone. Existing distribution-preserving behavioral watermarks are effective when the verifier can reconstruct the exact per-step probabilities used during embedding, but this symmetric assumption is brittle under rounded top- k APIs, model refreshes, and proxy-model audits. This paper identifies that brittleness as a verifier-channel failure mode: probability-bin decoders can lose usable capacity even when the selected behavior and top- k ordering are unchanged. We propose AsymAgentMark-TK, a weakly asymmetric behavioral watermark that embeds with full behavior probabilities but decodes from the invariant that survives many audit interfaces: rank order. Rank is a middle channel, more stable than calibrated probabilities and more informative than the selected action alone. We use effective capacity, $C_{\text{eff}} = C_{\text{nom}} \times \text{DSR}$, to separate nominal embedding opportunity from actual decode success under degraded verifier knowledge. On ALFWorld and ToolBench, AsymAgentMark-TK preserves utility and behavior-frequency stealth while retaining rank-only provenance signal where exact-probability AgentMark-F collapses; pooled audit windows recover once enough independent RLNC packets accumulate. The result is not production certification from short proxy traces, but a scoped feasibility result: behavioral watermarking should make verifier channel knowledge a first-class robustness dimension.

1. Introduction

Large language model (LLM) systems are rapidly shifting from passive text generators to agents that perceive context, plan, call tools, and act across multiple steps [1], [2], [3]. This shift changes what provenance must mean. For a chatbot, attributing the final string may be enough. For an agent, the consequential object is often the trajectory: which tool it selected, which subgoal it pursued, which API it invoked, or which embodied action it chose. These planning behaviors can affect safety, accountability, intellectual-property protection, and post-hoc auditing even when the final natural-language output is short or absent.

Content watermarking for LLM outputs has made substantial progress [4], [5], but it does not directly solve behavioral provenance. Planning behaviors are not token-native: an LLM’s reasoning text may be compiled into structured tool calls or environment actions, discarding the lexical signal used by token watermarks. In response,

AgentMark [6] formulated behavioral watermarking as distribution-preserving sampling over an explicit per-step behavior distribution. Its concrete construction, which we call AgentMark-F, embeds multi-bit identifiers while preserving the marginal behavior distribution, and it tolerates partial logs through erasure coding.

However, AgentMark-F is symmetric: decoding requires the verifier to reconstruct the same probability distribution used by the embedder. This is a strong assumption in real deployments. The verifier may access a rounded top- k API, a model after provider-side updates, a different serving stack, or a proxy model used for audit. These changes often preserve the relative order of plausible behaviors while shifting the numeric probabilities.

This is not only an implementation inconvenience; it is a structural verifier-channel failure mode. AgentMark-F’s differential bins are functions of probability masses. Two distributions can induce the same top- k order but move a cumulative boundary across a rank position, causing the same selected behavior to decode to a different bin. Thus a state-of-the-art exact-channel behavioral watermark can look strong under its native metric yet fail in the practically important rank-only audit channel. The lesson is broader than one implementation: behavioral watermarking should measure the channel available to the verifier, not only the capacity available to the embedder.

This paper asks whether behavioral provenance can be robust to verifier perturbations that preserve rank order but not calibrated probabilities. We show, in a scoped weak-asymmetry setting, that the answer can be yes by importing the principle of weakly asymmetric steganography [7] into LLM-agent behavior channels. In our setting, the embedder has the full behavior distribution P_t , but the verifier observes only partial channel knowledge: the top- k rank ordering σ_t . This setting is weaker than exact-probability verification but stronger than fully asymmetric verification with no channel knowledge. It matches common audit interfaces that expose candidate rankings without calibrated probabilities. The central insight is that rank is a useful intermediate channel: it is more stable than calibrated probability values and more informative than the selected action alone.

We present AsymAgentMark-TK, a top- k rank-based behavioral watermark. The rank-splitting primitive is not claimed as a new steganographic primitive; it is adapted from weakly asymmetric rank-based steganography [7]. Our contribution is to instantiate that partial-channel idea in AgentMark’s behavior channel, where candidate actions rather than text tokens carry provenance, and to specify

the synchronization, coding, and audit protocol needed for logged agent trajectories. The encoder sorts behaviors by probability and recursively partitions the top- k list into even and odd ranks. At each level, a binary distribution-preserving primitive uses probability masses to choose a group without changing the marginal policy. The decoder, by contrast, never uses probability values: the selected behavior’s rank determines the path through the same interleaved partition tree, and odd branches reveal embedded bits. A fixed-budget deterministic random bit generator (DRBG) schedule ensures that encoder and decoder consume the same pseudorandomness even when no bit is embedded at a level.

We organize the evaluation around effective capacity,

$$C_{\text{eff}} = C_{\text{nom}} \times \text{DSR}, \quad (1)$$

where C_{nom} is the nominal number of recoverable coded bits exposed by the channel and DSR is the decode success rate under the verifier’s view. This yardstick separates a watermark that has high capacity only under exact probabilities from one that yields lower nominal capacity but survives a degraded verifier channel. It also makes packet scarcity explicit: short single trajectories may fail strict RLNC recovery even when pooled audit windows contain enough independent packets.

The claim is intentionally scoped. The paper establishes a channel-knowledge tradeoff: top- k ranks can preserve decoder signal when exact probabilities are unavailable. It does not claim attribution from selected actions alone, nor does it claim production certification from the offline 8-bit proxy tables. Audit-grade attribution still requires a pre-registered key/payload claim, sufficiently long payloads, calibrated rank reconstruction, and end-to-end RLNC recovery under the deployment logging stack.

Our contributions are:

- **Verifier-channel failure mode.** We identify and formalize probability-bin instability: a symmetric behavioral watermark can preserve utility and recover under exact probabilities while losing decoder state under rank-only verification.
- **Effective-capacity yardstick.** We introduce $C_{\text{eff}} = C_{\text{nom}} \times \text{DSR}$ for behavioral watermark evaluation, separating nominal embedding opportunity from the usable capacity that remains after verifier-channel degradation.
- **Weak-asymmetric agent watermark.** We instantiate the weakly asymmetric rank construction as AsymAgentMark-TK for AgentMark-style behavior distributions, including top- k verifier views, fixed DRBG synchronization, and deterministic RLNC over logged trajectories.
- **Audit-window evidence model.** We distinguish strict per-trajectory attribution from pooled audit-window recovery and give the packet-scarcity argument that explains why short ToolBench traces can be weak individually yet recover when pooled.
- **Four-axis evaluation.** We evaluate on ALFWorld [8] and ToolBench [9] across DeepSeek and Gemini Flash

models along capacity, stealth, robustness, and evidence-strength axes, including selected-only negative controls, top- k sweeps, rank noise, erasure, matched-top- k ToolBench recovery, live ToolBench cross-model reranking, and false-positive accounting.

The rest of the paper proceeds as follows. Section 2 motivates behavioral watermarking and weak asymmetry. Section 3 defines the agent behavior channel, adversary, and verifier knowledge. Section 4 presents the rank encoder, decoder, synchronization, and coding layer. Sections 5 and 6 analyze security and evaluate utility, stealth, and rank-only recovery. Section 7 discusses operational limits, Section 8 covers related work, Section 9 covers validity and ethics, and Section 10 concludes. The appendices provide the optional depth behind the main claims: distribution preservation, DRBG synchronization, RLNC recovery, rank stability, and artifact mapping.

2. Background and Motivation

2.1. Behavioral Watermarking for Agents

An LLM agent operates over a trajectory of observations, planning behaviors, and execution actions. At each step t , the agent chooses a behavior b_t from a finite admissible set $\mathcal{B}_t$. Examples include ALFWorld navigation actions, ToolBench API calls, or social-simulation behaviors in OASIS [10]. AgentMark models this choice as sampling from an elicited behavior distribution P_t and replaces ordinary sampling with a distribution-preserving encoder:

$$\hat{b}_t \leftarrow \text{Enc}(P_t, r_t), \quad \Pr[\hat{b}_t = b] = P_t(b). \quad (2)$$

The distribution-preservation requirement is central. Agent trajectories are long-horizon and stateful; even small per-step distribution shifts can compound into task drift, failures, or visibly abnormal behavior.

2.2. The Symmetry Bottleneck

The concrete AgentMark-F construction uses differential recombination over P_t followed by cyclic-shift encoding. This is efficient when both embedder and verifier share exact probabilities. The same property makes it brittle under probability perturbation: if the verifier’s reconstructed P'_t differs from P_t , recombined bins may differ, so the selected behavior is interpreted under the wrong bin structure.

The weakness is not merely numerical. Many verification interfaces intentionally withhold calibrated probabilities. Auditors may receive ranked candidates, top- k choices, or sampled logs. Even when probabilities are available, temperature scaling, quantization, floating-point differences, model upgrades, and fine-tuning can perturb values. These transformations frequently preserve a useful invariant: the order of high-probability behaviors.

This observation is especially natural for agents. Candidate behaviors are usually semantic alternatives produced by a planning prompt: a tool call, a navigation operation, a

search/refine step, or a social action. A downstream auditor may be able to ask a model to rank plausible next behaviors from the same logged context even if the exact sampling distribution is hidden. In this sense, behavior-level verification has a useful middle ground that token-level watermarking often lacks: ranks are easier to reproduce than calibrated probabilities, and more informative than the selected action alone.

Table 1 summarizes the resulting distinction. AsymAgentMark-TK is not a replacement for text watermarking; it targets the behavior carrier that remains after plans are compiled into tool calls or environment actions. It is also not a capacity improvement over symmetric AgentMark when exact probabilities are available. Its purpose is to preserve AgentMark’s behavior-policy guarantee while weakening the verifier’s channel requirement.

2.3. Weak Asymmetry

Provably secure steganography traditionally separates symmetric settings, where sender and receiver share channel distributions, from asymmetric settings, where the receiver has no channel oracle [11], [12]. Weak asymmetry occupies the middle ground: the sender has the full channel, while the receiver has partial but nontrivial channel knowledge [7]. We instantiate this idea for behavioral watermarking. The embedder uses P_t to preserve the agent policy; the verifier uses only $\sigma_t = \text{argsort}_k(P_t)$ to decode.

3. Problem Formulation

3.1. Agent Behavior Channel

For a trajectory of length T , each step t has a behavior set $B_t = \{b_{t,1}, \dots, b_{t,n_t}\}$ and a behavior distribution P_t induced by the agent and environment context. A watermarking key K_{sh} and step context h_t derive per-step pseudo-randomness. The embedder encodes a payload $m \in \{0, 1\}^L$ into selected behaviors $\hat{b}_1, \dots, \hat{b}_T$ while preserving P_t at each step.

The verifier observes a possibly incomplete set of indices $I \subseteq \{1, \dots, T\}$ and, for each observed step, the selected behavior $\hat{b}_t$ plus channel side information. In the symmetric setting, the side information is P_t or an exact reconstruction. In our setting, it is the top- k ordering σ_t .

Verifier knowledge. We distinguish three verifier views. In the *exact view*, the verifier receives P_t and can run the same decoder as the embedder. In the *rank view*, the verifier receives only $\sigma_t^k = (b_{(1)}, \dots, b_{(k)})$, the ordered list of the top- k behaviors. In the *selected-only view*, the verifier receives only $\hat{b}_t$ and no usable channel side information. The exact view is a useful upper bound; the rank view is the deployment target of AsymAgentMark-TK; the selected-only view is a negative control showing that behavioral provenance cannot be recovered from actions alone without some channel side information.

For evaluation we instantiate these views as a channel-knowledge ladder. $L0$ is exact probability access. $L1$ – $L5$ progressively restrict the verifier to top-10, top-8, top-6, top-4, and top-2 ordered candidates. $L6$ is the selected-only negative control. This ladder is not a claim that every API exposes exactly these levels; it is a controlled way to ask how usable capacity changes as the verifier loses calibrated probability information.

Rank consistency. For two distributions P_t and P'_t over the same candidate list, define top- k rank consistency as

$$\text{argsort}_k(P_t) = \text{argsort}_k(P'_t). \quad (3)$$

This condition permits arbitrary probability-value changes as long as the verifier preserves the ordered top- k set. It covers monotone transformations such as temperature rescaling, but it also covers less structured API changes whose empirical effect is to leave ranks unchanged. When the equality fails, we measure degradation through rank-noise experiments rather than assuming correctness.

3.2. Adversary and Requirements

We consider three perturbations. First, *step erasure*: some logged steps are missing due to execution failures, platform deletion, or incomplete telemetry. Second, *distribution perturbation*: a verifier reconstructs P'_t whose numeric values differ from P_t . Third, *rank noise*: the verifier’s top- k order disagrees with the embedder’s order, modeling top- k instability or proxy-model disagreement.

The adversary observes watermarked trajectories and may know the algorithm and public parameters, including k , but not K_{sh} . This is the standard secret-key provenance setting: a platform or model owner embeds an identifier, while a later verifier checks a claimed key and payload. We do not rely on security through obscurity of the rank partition or coding scheme.

The adversary has two goals. A *removal* adversary tries to make a genuinely watermarked trajectory verify as inconclusive or negative by deleting steps, perturbing ranks, or changing behavior serialization. A *framing* adversary tries to make an unwatermarked or differently watermarked trajectory verify under another party’s claim. Claim binding and false-positive thresholds address framing when the key is secret; arbitrary trajectory rewriting, compromised keys, and compromised logging infrastructure are outside the cryptographic claim and are handled as deployment assumptions.

The audit boundary is therefore explicit. The verifier needs a trajectory log whose step contexts and selected behaviors are bound by the embedding service or another trusted logging layer, plus a deterministic mapping from logged behaviors to verifier-side candidates. The watermark can tolerate missing steps and imperfect rank reconstruction, but it cannot distinguish a genuine erasure from a log rewritten by an untrusted recorder. We treat log integrity and candidate canonicalization as deployment prerequisites and evaluate the watermark channel conditional on those prerequisites.

A scheme should satisfy:

- **Utility preservation:** $\Pr[\hat{b}_t = b] = P_t(b)$ per step.
- **Weak-asymmetric correctness:** if $\text{argsort}_k(P'_t) = \text{argsort}_k(P_t)$, decoding from P'_t 's order returns the same bits as decoding from P_t 's order.
- **Low false positives:** for a fixed pre-registered L -bit claim, a clean or unrelated trajectory should recover that exact payload with probability 2^{-L} when decoded bits are independent of the claim.
- **Erasur tolerance:** payload recovery should degrade gracefully when only a subset of steps is observed.

Detection statistic. For an audited trajectory, the verifier decodes a multiset of coded bits and attempts to recover payload $\hat{m}$. A strict positive attribution requires $\hat{m} = m$ for a pre-registered claimed payload. A failed recovery is treated as negative only when the verifier has enough rank-consistent evidence and independent equations; otherwise it is inconclusive. For bit-level channel diagnostics, we also report the bit match rate between decoded coded bits and the coded stream induced by m . Payload recovery is stricter and is used for provenance claims; bit match is useful for comparing noisy channels even when there are too few equations for full RLNC recovery.

3.3. Non-Goals

AsymAgentMark-TK is not a general-purpose watermark removal defense. If an adversary controls the agent and can arbitrarily rewrite the trajectory, no behavioral watermark can force attribution without an external logging root of trust. Our target is post-hoc verification for trajectories that are generated by an honest embedder but later audited through an imperfect channel interface. We also do not assume the verifier can re-run the exact original model. The verifier may use a same-family model, a refreshed endpoint, or a restricted API as long as the top- k order remains sufficiently stable.

4. Design

4.1. Overview

AsymAgentMark-TK has four components, summarized in Fig. 1. First, the agent elicits or estimates P_t over candidate behaviors, following AgentMark's black-box-compatible behavior-distribution interface [6]. Second, the encoder sorts behaviors by descending probability and restricts embedding to the top- k region. Third, it applies the interleaved rank split from weakly asymmetric steganography [7] to behavior candidates rather than text symbols, preserving the behavior distribution while making the selected rank decodable. Fourth, deterministic RLNC maps the payload into a stream of coded bits so that the verifier can solve for the payload after observing enough independent coded bits.

TABLE 1. POSITIONING AGAINST NEARBY WATERMARKING SETTINGS.

Scheme	Carrier	Preserved object	Verifier channel
Token watermarks	Text tokens	Text distribution	Generated text/statistic
AgentMark-F	Agent behaviors	Behavior policy P_t	Exact P_t
AsymAgentMark-TK	Agent behaviors	Behavior policy P_t	Top- k rank σ_t

4.2. Binary Distribution-Preserving Primitive

At a tree node, the encoder must choose between two groups with masses S_0 and S_1 while optionally embedding one bit. Assume $S_0 \geq S_1$ and $S = S_0 + S_1$. Given message bit $m \in \{0, 1\}$ and $r \leftarrow U[0, 1)$ from the DRBG, define

$$r_m = (rS + \frac{1}{2}Sm) \bmod S. \quad (4)$$

BinEnc selects group 0 if $r_m < S_0$ and group 1 otherwise. If group 1 is selected, one bit is embedded; if group 0 is selected, no bit is consumed and the same bit is retried at the next level. Because r_m is uniform over $[0, S)$ for uniform r , the selected group has exactly the desired marginal probabilities S_0/S and S_1/S .

Why zero-bit branches are intentional. The primitive gives up a bit when the high-mass group is selected because forcing every branch to carry a bit would require reweighting the group probabilities. The deferred-bit design is the same kind of tradeoff used by distribution-preserving steganography: capacity is opportunistic, but the cover distribution is unchanged. In agent settings this is a feature rather than a cosmetic constraint, because utility regressions caused by shifted planning choices are easier for users and downstream systems to notice than small variations in textual style.

4.3. Rank Encoder

Let σ_t be the descending rank ordering of P_t . The encoder first samples whether to enter the top- k region with probability $S_{\text{top}} = \sum_{i=1}^k P_t(\sigma_t(i))$. If not, it samples from the tail proportionally and embeds no bits. Inside top- k , it normalizes probabilities and applies recursive splitting:

- 1) Split the current sorted list into even ranks $(0, 2, 4, \dots)$ and odd ranks $(1, 3, 5, \dots)$.
- 2) Use BinEnc on the two group masses.
- 3) Recurse into the selected group until a single behavior remains.

Interleaving is important. A top-half/bottom-half split would place most mass in the first group, producing low embedding opportunity. Even/odd splitting balances mass while preserving a rank path that the verifier can recover.

4.4. Rank Decoder

Given selected behavior $\hat{b}_t$ and top- k order σ_t , the decoder finds the zero-indexed rank q of $\hat{b}_t$. If $\hat{b}_t$ is outside top- k , the step yields no bits. Otherwise, the decoder reconstructs the path by repeatedly reading the parity of q :

$$q_0 = q, \quad q_{\ell+1} = \lfloor q_{\ell}/2 \rfloor. \quad (5)$$

Embedder: full channel	→	Trajectory log	→	Verifier: partial channel
Agent context h_t and candidate behaviors $\mathcal{B}_t$. Elicit probabilities P_t and sort top- k order σ_t . Use P_t to sample a watermarked behavior with the same marginal distribution.		Logged behavior $\hat{b}_t$, step context, claimed payload identifier, and audit metadata. The log may omit steps or be checked after model/API changes.		Reconstruct only the top- k order σ'_t from a restricted API or proxy model. Decode bits from the rank of $\hat{b}_t$; solve RLNC equations for the payload.

Figure 1. System view of weakly asymmetric behavioral watermarking. The embedder needs calibrated probabilities to preserve utility; the verifier needs only rank order for decoding, plus enough observed coded bits for RLNC recovery.

Algorithm 1: One-step rank encoding.

Input: distribution P_t , context h_t , key K_{sh} , payload stream M , pointer ℓ , top- k .

1. Derive DRBG $\mathcal{G}_t$ from (K_{sh}, h_t) .
2. Sort behaviors: $\sigma_t \leftarrow \text{argsort}(P_t)$.
3. With probability $1 - \sum_{i \leq k} P_t(\sigma_t(i))$, sample from the tail and return no bits.
4. Normalize the top- k distribution D .
5. While $|D| > 1$: split D into even/odd ranks; run BinEnc on the group masses; consume a message bit only when BinEnc enters the odd group; recurse into the chosen group.
6. Advance unused DRBG calls until exactly $\lceil \log_2 k \rceil$ calls are consumed.

Output: selected behavior and consumed coded bits.

Figure 2. Encoder sketch. The encoder uses probability values only to preserve the marginal behavior distribution.

Algorithm 2: One-step rank decoding.

Input: selected behavior $\hat{b}_t$, top- k order σ_t , context h_t , key K_{sh} .

1. Derive the same DRBG sequence $r_0, \dots, r_{\lceil \log_2 k \rceil - 1}$.
2. If $\hat{b}_t \notin \sigma_t[1 : k]$, return the empty string.
3. Let q be the zero-indexed rank of $\hat{b}_t$.
4. While $q \neq 0$: if q is odd, append 1 when the corresponding $r_i < 0.5$ and 0 otherwise; set $q \leftarrow \lfloor q/2 \rfloor$.

Output: decoded coded bits for step t .

Figure 3. Decoder sketch. No numeric probability appears in the decoder.

Whenever q_ℓ is odd, the selected path entered the odd group and one bit was embedded. The value of that bit is determined by the same DRBG value used at level ℓ : the implementation decodes it as 1 if $r_\ell < 0.5$ and 0 otherwise. The decoder consumes exactly $\lceil \log_2 k \rceil$ DRBG values per step, matching the encoder’s fixed synchronization budget.

4.5. Coding Layer

Per-step embedding capacity varies with P_t , k , and trajectory length. To avoid requiring a contiguous bitstream, AsymAgentMark-TK uses deterministic RLNC over GF(2), following the standard random linear network coding principle [13]. For payload $m \in \{0, 1\}^L$, the i -th coded bit is

$$c_i = \langle a_i, m \rangle \bmod 2, \quad (6)$$

where coefficient vector a_i is generated deterministically from a stream key and index i . The verifier collects decoded coded bits and solves the resulting linear system by Gaussian elimination over GF(2). This layer is inherited from AgentMark’s erasure-resilience design but is independent of whether the step decoder is symmetric or rank-only.

The coding layer also cleanly separates two questions that are often conflated. The step decoder asks whether an observed behavior can yield a reliable coded bit under the verifier’s channel view. RLNC asks whether enough independent coded bits have survived to solve for the payload. This separation is useful for weak asymmetry: a rank-only decoder may produce fewer bits than an exact-probability decoder, but the coding layer can still recover when the trajectory is long enough or the audit window spans enough steps.

4.6. Verification Protocol

An audit takes as input a pre-registered key/payload claim, a canonicalized trajectory log, and a verifier-side procedure for reconstructing top- k candidate orders. The verifier first derives the per-step DRBG streams from logged contexts and decodes all observed steps using RankDec. It then runs RLNC elimination over the recovered coded equations. If the system recovers the registered payload and the reconstructed ranks pass a deployment-specific quality gate, the audit reports a positive attribution. If the payload does not recover but the rank-quality gate fails or too few independent equations are available, the audit reports *inconclusive*. A negative attribution is reserved for the case where the verifier has enough rank-consistent evidence to decode but the recovered payload contradicts the registered claim.

The rank-quality gate is intentionally separate from the watermark statistic. A verifier can estimate it using held-out calibration contexts, duplicate model queries, or agreement between independent rankers. This prevents a common operational error: treating a failed rank-only decode as evidence that a trajectory is clean when the verifier’s channel reconstruction is itself unreliable.

For short trajectories, the verifier may not obtain enough independent RLNC equations for strict payload recovery. In that case, the bit-match statistic is reported only as supporting evidence with a binomial tail probability under the null model of random agreement. This diagnostic can trigger further collection or manual review, but it is not by itself a positive attribution decision.

4.7. Implementation Notes

The implementation is integrated through an AgentWatermarker SDK wrapper with

algorithm="rank" as the default and an optional owner secret for deployment. Internally, `Dist` stores probability tensors and stable indices, `RankEncStep` applies the interleaved split, and `RankDecStep` reconstructs bits from sorted indices. The DRBG is an HMAC-SHA512 reseed construction inspired by Meteor [12]; its per-step seed is derived from the owner secret and logged context. For backward-compatible experiment replay, the prototype also supports a context-derived legacy mode, which is useful for channel measurements but is not a deployment secrecy boundary. A synchronization counter, `rt_sync`, forces both sides to advance exactly $\lceil \log_2 n \rceil$ random draws per decoded top- k step. The top/tail gate is outside this shared schedule because tail selections emit no bits and are treated as erasures by the verifier. This detail is small but critical: without fixed top- k consumption, a zero-bit level would shift all later decoding.

Appendix A expands the distribution-preservation proof, Appendix B details the fixed-budget synchronization rule, and Appendix C summarizes how decoded bits become payload equations. These appendices are not separate claims; they make the construction auditable without interrupting the main channel-knowledge argument.

Tie handling uses stable sorting after probability normalization. Ties are rare in model-scored behavior sets but can occur after rounding or prompt templates that assign equal fallback scores. Stable sorting makes the order deterministic when both sides see the same candidate list. If the verifier obtains a tied but differently ordered top- k list, this is treated as rank disagreement and measured through the bit-disagreement proxy in Section 6.

4.8. Parameter Selection

The top- k parameter controls a reliability–capacity tradeoff. Larger k exposes more leaves in the partition tree and can increase decoded length, but it also includes lower-probability tail behaviors whose relative ranks are less stable across models and serving conditions. Smaller k is more conservative and better aligned with restricted APIs, but it leaves less room for embedding. In our experiments we report $k \in \{2, 4, 6, 8, 10, 20\}$ rather than tuning to a single best value. A deployment can choose k from a calibration set by maximizing expected payload recovery subject to a minimum top- k rank agreement threshold.

5. Security Analysis

Proposition 1 (distribution preservation). For each step t and behavior $b \in \mathcal{B}_t$, `AsymAgentMark-TK` outputs b with probability $P_t(b)$.

Proof sketch. The top/tail gate selects the top- k region with probability equal to its total mass and otherwise samples the tail proportionally. Tail samples emit no coded bits, so the verifier need not reproduce the gate randomness. Conditioned on entering top- k , each binary split uses `BinEnc`, whose selected group probability equals its normalized mass because r_m is uniform. Induction over the partition tree

gives each leaf its normalized probability within top- k . Multiplying by the top- k mass recovers $P_t(b)$. $\square$

Lemma 1 (probability-bin instability). There exist two behavior distributions with identical rank order for which a probability-dependent bin decoder assigns the same selected behavior to different bins.

Proof sketch. Consider four behaviors ordered $a \succ b \succ c \succ d$ and a two-bin prefix decoder whose first bin is the smallest rank prefix whose cumulative probability exceeds $1/2$. Under $P = (0.45, 0.30, 0.15, 0.10)$, the first bin is $\{a, b\}$. Under $Q = (0.55, 0.25, 0.12, 0.08)$, the rank order is unchanged but the first bin is $\{a\}$. The selected behavior b is therefore interpreted in different bins although the verifier preserved the full ranking. Differential recombination uses a richer bin structure than this toy prefix rule, but it shares the same dependence on probability masses; rank agreement alone does not fix its decoder partition. $\square$

Theorem 1 (rank-preserving robustness). Let P_t and P'_t satisfy $\text{argsort}_k(P_t) = \text{argsort}_k(P'_t)$. For any selected behavior $\hat{b}_t$ and shared key/context-derived DRBG stream,

$$\text{RankDec}(\hat{b}_t, \text{argsort}_k(P_t)) = \text{RankDec}(\hat{b}_t, \text{argsort}_k(P'_t)). \quad (7)$$

Proof. `RankDec` accesses channel information only through the rank position of $\hat{b}_t$ in the top- k order. If the two orders are equal, this rank is identical. The DRBG stream depends on the secret key and context, not probability values. Therefore the decoded path and bit values are identical. $\square$

Corollary 1 (bit evidence under rank agreement).

Let ρ be the probability that an observed embedding step is top- k rank-consistent between embedder and verifier. Suppose rank-consistent steps decode a coded bit correctly with probability $q > 1/2$, while rank-inconsistent steps are independent of the claimed bit. Then the expected bit-match rate is

$$\mathbb{E}[\bar{X}] = \frac{1}{2} + \rho(q - \frac{1}{2}). \quad (8)$$

For N decoded bits, Hoeffding's inequality gives

$$\Pr\left[\bar{X} \leq \frac{1}{2} + \gamma\right] \leq \exp\left(-2N\left(\rho(q - \frac{1}{2}) - \gamma\right)^2\right) \quad (9)$$

whenever $0 < \gamma < \rho(q - \frac{1}{2})$. Thus lower rank agreement does not create a hard impossibility; it increases the evidence budget needed to distinguish the watermark from the null. This corollary is a diagnostic model for bit-level evidence, not a replacement for strict payload recovery.

Proposition 2 (packet scarcity). For an L -bit deterministic RLNC payload, strict recovery from a single trajectory requires at least L independent coded packets. If M independent packets survive after top- k misses, erasures, and rank failures, then

$$\Pr[\text{recover}] \leq \Pr[M \geq L]. \quad (10)$$

For an audit window pooling trajectories $i = 1, \dots, n$, the expected packet budget is additive:

$$\mathbb{E}[M_{\text{pool}}] = \sum_i \mathbb{E}[M_i]. \quad (11)$$

If each trajectory has expected packet yield $\mu_{\text{traj}} = N(1 - r)\text{DSR}(k, \epsilon)$ under erasure rate r and rank-noise level ϵ , then a deployment aiming for L independent equations plus a rank-deficiency margin δ needs, in expectation,

$$n \gtrsim \frac{L + \delta}{\mu_{\text{traj}}}. \quad (12)$$

This explains why short ToolBench traces can show usable bit-level signal but weak strict single-trajectory recovery, while pooled audit windows recover once enough independent packets accumulate.

Proposition 3 (top- k operating point). Let $C_{\text{nom}}(k)$ be the nominal coded-bit opportunity exposed by a top- k verifier view, and let $\text{DSR}(k)$ be the probability that those coded bits remain decodable under the verifier channel. Assume $C_{\text{nom}}(k)$ is nondecreasing with diminishing marginal log-gain and $\text{DSR}(k)$ is nonincreasing with nondecreasing marginal log-loss. Then $\log C_{\text{eff}}(k) = \log C_{\text{nom}}(k) + \log \text{DSR}(k)$ has at most one internal maximum. When the maximum is internal, it occurs where the marginal capacity gain from increasing k equals the marginal reliability loss. This is a design rule rather than a worst-case guarantee: high-entropy environments can afford larger k , while low-entropy or unstable-rank environments can have a smaller optimum.

Lemma 2 (rank-noise boundary). Under an adjacent-swap noise model with per-adjacent-pair swap probability ϵ , suppose a selected rank’s decoded path of depth $d = \lceil \log_2 k \rceil$ can be corrupted by at most cd relevant local swaps. Then the per-step path-corruption probability is bounded by

$$p_{\text{flip}} \leq 1 - (1 - \epsilon)^{c \lceil \log_2 k \rceil}. \quad (13)$$

Combining this bound with Corollary 1 gives the evidence budget needed to distinguish the watermark from the null at a chosen tail probability. The bound is deliberately model-dependent: arbitrary targeted rank manipulation remains outside the weak-asymmetric guarantee, but the expression captures the empirical tradeoff that larger k gives more path bits while exposing more rank positions to noise.

Minimum evidence threshold. For bit-level triage before strict RLNC recovery, a one-sided binomial test with match probability $q > 1/2$ under the watermark and $1/2$ under the null needs on the order of

$$N_{\text{min}} = O\left(\frac{z_\alpha^2}{(q - 1/2)^2}\right) \quad (14)$$

observed decoded bits to reach significance level α . This threshold is not an attribution decision by itself; it sizes the observation window needed before a verifier should expect enough channel evidence to justify attempting strict payload recovery.

False positives. For an unwatermarked or unrelated trajectory, strict attribution requires recovery of a key and payload claim that was registered before the trajectory is inspected. Under the standard null that decoded clean bits are independent of this fixed claim and that no adaptive post-hoc key or payload search is counted as a single test, an L -bit payload match occurs with probability 2^{-L} . In practice

the verifier can tune L to the desired audit threshold; $L = 32$ yields 2.33×10^{-10} and $L = 64$ yields 5.42×10^{-20} .

Why the theory matches the contribution. Lemma 1 gives the negative result: rank agreement alone is insufficient for probability-bin decoders. Theorem 1 gives the positive boundary for AsymAgentMark-TK: arbitrary probability-value perturbations are harmless as long as the top- k order is preserved. Proposition 2 separates channel robustness from evidence volume, which is why the evaluation reports both strict per-trajectory recovery and pooled RLNC recovery. Proposition 3 and Lemma 2 explain why top- k should be calibrated rather than treated as a universal constant: larger k can raise nominal capacity, but only until rank instability erodes decode success.

Key privacy. The deployment watermark key is used only to derive context-specific pseudorandomness. The public trajectory and rank list do not reveal the key under the pseudorandom function assumption for HMAC-SHA512. A verifier may check many trajectories under the same registered owner only with domain-separated contexts, key identifiers, and tenant/product isolation; operational deployments should rotate keys to limit blast radius if a key is disclosed. The offline experiments use recorded payload metadata and deterministic replay to evaluate the watermark channel; they should not be read as evidence that a public context-derived prototype default provides secret-key security.

Claim binding. A watermark match is meaningful only for a claimed key and payload that were bound to an owner before the audit. Otherwise, an operator could test many keys or payloads after observing a trajectory and inflate the effective false-positive rate. Deployments should therefore register a key identifier, payload namespace, and issuance time in an append-only registry or signed manifest. The verifier can then count only pre-registered claims and apply the multiple-testing correction in Section 6.14.

Limits. AsymAgentMark-TK is robust to value perturbations that preserve top- k order, not to arbitrary rank manipulation. If an adversary can force targeted rank swaps in the top- k list, it can corrupt decoded paths. This is the expected boundary of any rank-only weakly asymmetric scheme. The evaluation therefore includes a rank-disagreement proxy and treats live cross-model rank reconstruction as deployment work. Appendix D states the corresponding rank-stability intuition and the resulting top- k choice rule.

6. Evaluation

6.1. Setup

We evaluate on ALFWorld [8] and ToolBench [9]. ALFWorld tests embodied planning over in-distribution (ID) and out-of-distribution (OOD) splits; ToolBench tests tool-use behavior across six split categories. The LLM endpoints are DeepSeek Chat (deepseek-chat) [14] and Gemini 2.0 Flash (gemini-2.0-flash) [3]. The post-processed corpus contains 11,820 trajectories and 4,728

TABLE 2. EVALUATION COVERAGE AFTER POSTPROCESSING.

Dataset	Model/split groups	Completed runs	Decode-capable trajectories
ALFWorld	4	3/3 per group	3,288 (1,644 per watermark)
ToolBench	2	18/18 per group	1,440 (720 per watermark)

watermark decode-capable trajectories. Methods are: vanilla LLM agent, clean AgentMark pipeline without embedding, red-green (RG) behavior bias, symmetric AgentMark-F, and rank-based AsymAgentMark-TK. RG is a deliberately simple keyed baseline that biases choices toward a pseudo-random green set; it is included to show the utility and distributional cost of watermarking that does not preserve the behavior policy.

Unless otherwise stated, recovery rates are computed from the available offline decoder artifacts. Capacity tables are bit-level channel proxies over logged trajectories and should not be conflated with strict end-to-end RLNC recovery. When we report strict recovery, a single trajectory must independently recover the exact payload. When we report pooled recovery, packets from trajectories in the same dataset/model/split/run/configuration are combined before RLNC decoding; this is corpus-level or audit-window evidence rather than per-task attribution. We use 8-bit payloads in the proxy tables to make capacity differences measurable on short benchmark trajectories; deployable attribution should use longer payloads and the false-positive accounting in Section 6.14.

Table 2 summarizes the evaluation coverage. Utility and stealth metrics use all five methods. Decode-capable counts apply to the two watermarking methods because vanilla, clean, and RG trajectories do not carry payload metadata. The two watermarked methods are balanced within each dataset, which avoids comparing rank and symmetric decoders on different trajectory pools.

6.2. Evaluation Protocol

The evaluation pipeline starts from logged trajectories containing the selected behavior, candidate list, behavior probabilities when available, and watermark metadata. Utility and JSD are computed over all valid task trajectories. Watermark recovery is computed on the decode-capable subset: trajectories with a recorded watermark configuration, a recoverable candidate ordering, and enough logged context to replay the deterministic DRBG schedule. This distinction is reported explicitly in the corpus counts above.

For each decode-capable trajectory, we run the same verifier under several channel views. The *exact* view uses the logged probabilities as a diagnostic upper bound rather than as the target audit interface. The *top-k* views discard numeric probabilities and retain only the ordered candidate list. The selected-only view is used as a negative control when available. Rank-noise experiments use a bit-level disagreement proxy parameterized by ϵ because the postprocessed logs do not contain full alternate rank lists for every verifier; erasure experiments remove a random

fraction of observed steps before RLNC solving. All tables aggregate over the available model/split groups rather than selecting the best configuration per task. The main rank-only comparison reports fixed top-10, top-6, and top-2 views; the separate top- k ablation reports the full sweep and is not used to choose per-model winners. These aggregates are descriptive comparisons over the generated corpus; they are not presented as hypothesis tests for small differences between methods.

6.3. Reproducibility Trail

The evaluation package is organized so that each reported number has a concrete source. The paper package contains the manuscript, resolved bibliography, compiled PDF, and build helper. The rank encoder and decoder are implemented in `watermark_sampler.py`, and deterministic RLNC is implemented in `rlnc_codec.py`. The canonical non-robust result package supports utility, JSD, capacity-proxy, top- k , strict-recovery, and evidence-strength claims; the robustness package supports pooled rank-noise, fixed erasure, ToolBench matched-top- k recovery, ToolBench live cross-model rerank, and false-positive claims. Appendix E maps the reported diagnostics to their source tables. We treat these artifacts as a reproducibility trail for the reported postprocessed diagnostics; the live ToolBench L5 rerank results are deployment-facing evidence for the verifier channel rather than a claim that all agent domains have equally stable cross-model ranks.

6.4. Evaluation Axes

The evaluation is organized around four axes rather than a table-by-table result dump. The **capacity axis** asks how usable capacity changes as verifier channel knowledge degrades from exact probabilities to rank-only and selected-only views, using C_{eff} as the common yardstick. The **undetectability axis** checks whether the rank construction preserves task utility and behavior-frequency statistics. The **robustness axis** measures rank noise, erasure, matched top- k ToolBench recovery, and live cross-model reranking, with strict single-trajectory recovery separated from pooled audit-window recovery. The **evidence-strength axis** reports false-positive thresholds and the minimum observation budgets needed before bit-level diagnostics become meaningful.

6.5. Metrics

We report task success rate and average steps for utility. We report Jensen-Shannon divergence (JSD) between empirical action-frequency distributions for a coarse stealth check. For watermark recovery, *payload recovery* is the fraction of trajectories whose decoded payload exactly matches the embedded payload; in the offline proxy tables this is the 8-bit benchmark payload defined in the setup, not an audit-grade deployment identifier. *Bit match* is the average agreement between decoded coded bits and the expected coded stream.

When a verifier view recovers no coded bits, both payload recovery and bit match are reported as zero. The latter is not a substitute for attribution, but it is a sensitive diagnostic for channel degradation. We also report proxy C_{eff} , which multiplies nominal coded-bit opportunity by decode success so that a high-capacity exact-channel scheme that fails under rank-only verification is scored as low usable capacity in that verifier channel. For confidence analysis, we use a one-sided binomial tail probability under the null hypothesis that each decoded bit matches the claim with probability $1/2$. All recovery tables report cells as bit match / payload recovery.

6.6. Capacity Axis: Mechanism Diagnosis

The central empirical comparison is not simply whether AsymAgentMark-TK has higher recovery than AgentMark-F in every channel. It does not: exact probabilities are the native channel for AgentMark-F, and Table 5 shows that AgentMark-F has higher exact-channel payload recovery on ALFWorld. The question is whether that exact-channel advantage survives the weaker verifier interface that motivated this paper. The rank-only columns test precisely this mechanism. If a decoder depends on probability bins, Lemma 1 predicts that preserving candidate order is not enough to preserve decoder state. If a decoder depends only on rank path, Theorem 1 predicts no loss from probability-value perturbations as long as ranks are preserved. The evaluation therefore treats the exact column as an upper-bound capacity diagnostic and the top- k columns as the target robustness channel.

6.7. Undetectability Axis: Utility Preservation

Table 3 reports average task success and steps. On ALFWorld, AsymAgentMark-TK reaches 78.6% success versus 80.0% for clean and 79.4% for AgentMark-F. On ToolBench, AsymAgentMark-TK reaches 77.1% versus 75.7% for the clean pipeline. The source utility artifact records run-level variation: ALFWorld rank groups have standard deviations up to 2.89 percentage points, while ToolBench rank entries are about 11 percentage points because they aggregate six heterogeneous splits. We therefore interpret these aggregates conservatively: rank encoding stays close to the clean and symmetric pipelines and does not exhibit the large utility tax associated with naive behavior bias, but small one- or two-point differences are not treated as significant.

6.8. Undetectability Axis: Behavioral Stealth

We compare empirical action distributions against clean trajectories using Jensen-Shannon divergence (JSD). On ALFWorld, mean JSD to clean is 0.121 for AsymAgentMark-TK and 0.122 for AgentMark-F; on ToolBench it is 0.140 for AsymAgentMark-TK and 0.174 for AgentMark-F. RG is comparable on ALFWorld but worse on ToolBench. These measurements are coarse because behavior distributions are task- and split-dependent, but they

TABLE 3. TASK UTILITY AVERAGED OVER AVAILABLE MODEL/SPLIT GROUPS. RG DENOTES RED-GREEN BEHAVIOR BIAS.

Dataset	Method	Success	Steps	Groups
ALFWorld	Vanilla	69.1	16.54	4
	Clean	80.0	16.23	4
	RG	74.9	17.58	4
	AgentMark-F	79.4	16.58	4
	AsymAgentMark-TK	78.6	16.40	4
ToolBench	Vanilla	84.1	4.06	2
	Clean	75.7	5.32	2
	RG	75.1	4.78	2
	AgentMark-F	74.7	4.54	2
	AsymAgentMark-TK	77.1	5.07	2

TABLE 4. MEAN JSD TO CLEAN BEHAVIOR FREQUENCY. LOWER IS CLOSER TO CLEAN.

Dataset	AgentMark-F	AsymAgentMark-TK	RG	Vanilla
ALFWorld	0.122	0.121	0.134	0.564
ToolBench	0.174	0.140	0.181	0.162

show no obvious distributional anomaly introduced by rank splitting.

6.9. Capacity Axis: Rank-Only Verification

Table 5 compares payload recovery and bit match for 8-bit payloads under different verifier knowledge. Under exact probabilities on ALFWorld, AgentMark-F has higher payload recovery (0.700) than AsymAgentMark-TK (0.532), reflecting the efficiency cost of rank-only structure. Under top-10 rank-only verification, AgentMark-F collapses to 0.014 payload recovery, while AsymAgentMark-TK remains at 0.068. In C_{eff} terms, ALFWorld AgentMark-F falls from 19.692 under exact probabilities to 0.333 under top-10 ranks, while AsymAgentMark-TK falls from 7.707 to 1.000. This is the empirical analogue of Lemma 1: a method can be strong under the exact probability metric yet lose its decoder state when the verifier has only ranks. It is also the central tradeoff of the paper: AgentMark-F is better when exact probabilities are available; AsymAgentMark-TK is more reliable when the verifier only has rank knowledge.

ToolBench is lower-capacity for both schemes because trajectories are short and many tool choices have low recoverable entropy. Nevertheless, AsymAgentMark-TK keeps nearly the same payload recovery from exact probabilities to top-10 rank-only decoding (0.033 to 0.032), whereas AgentMark-F drops from 0.085 to 0.003 payload recovery. The same pattern appears in C_{eff} : ToolBench AgentMark-F drops from 0.248 to 0.009, while AsymAgentMark-TK remains effectively flat from 0.053 to 0.050.

The selected-only column is the negative control: when the verifier sees only the executed behavior and no candidate ordering, neither scheme recovers coded bits. This validates the weak-asymmetric framing. AsymAgentMark-TK weakens exact probability knowledge to rank knowledge; it does not claim attribution from the action log alone.

TABLE 5. OFFLINE 8-BIT DECODER PROXY UNDER VERIFIER CHANNEL KNOWLEDGE. CELLS SHOW BIT-MATCH / PAYLOAD RECOVERY; SEL. ONLY IS THE SELECTED-BEHAVIOR-ONLY NEGATIVE CONTROL.

Dataset	Method	Exact	Top-10	Top-6	Top-2	Sel. only
ALFWorld	AgentMark-F	.985/.700	.594/.014	.498/.004	.504/.004	.000/.000
	AsymAgentMark-TK	.942/.532	.718/.068	.641/.028	.566/.006	.000/.000
ToolBench	AgentMark-F	.582/.085	.299/.003	.292/.000	.309/.000	.000/.000
	AsymAgentMark-TK	.502/.033	.501/.032	.470/.007	.357/.000	.000/.000

TABLE 6. TOP- k ABLATION FOR ASYMAAGENTMARK-TK IN THE OFFLINE DECODER PROXY. MATCH/REC. CELLS SHOW BIT-MATCH / PAYLOAD RECOVERY; C_{eff} ROWS SHOW PROXY EFFECTIVE CAPACITY.

Dataset	Metric	$k = 2$	$k = 4$	$k = 6$	$k = 8$	$k = 10$	$k = 20$
ALFWorld	Match/rec.	.558/.006	.601/.013	.642/.028	.670/.048	.707/.064	.863/.313
ALFWorld	C_{eff}	.046	.164	.372	.690	.954	4.511
ToolBench	Match/rec.	.351/.000	.426/.006	.470/.010	.488/.021	.495/.032	.505/.035
ToolBench	C_{eff}	.000	.009	.016	.032	.053	.056

6.10. Capacity Axis: Top- k Operating Point

Increasing k raises both the amount of available rank information and the risk of rank instability, matching Proposition 3’s operating-point view. In ALFWorld, AsymAgentMark-TK’s mean bit-match rate rises from 0.558 at $k = 2$ to 0.863 at $k = 20$, with payload recovery increasing from 0.006 to 0.313 and proxy C_{eff} increasing from 0.046 to 4.511. ToolBench improves more modestly, from 0.351 to 0.505 bit-match and from 0.000 to 0.056 proxy C_{eff} , reflecting lower behavior entropy and shorter horizons. These results suggest that k should be selected per environment: larger k helps high-entropy embodied planning, while low-entropy tool tasks require either longer traces, stronger coding, or adaptive gating.

This ablation is a design diagnostic rather than a winner-take-all tuning result. It supports the weak-asymmetry story by showing where rank information becomes useful and where lower-ranked candidates stop paying for their reconstruction risk; Appendix D gives the corresponding stability rationale.

6.11. Robustness Axis: Rank Noise and Erasure

Strict single-trajectory decoding is intentionally difficult in short benchmark traces, so the robustness experiments also report pooled recovery. Pooled recovery combines packets from trajectories with the same dataset, model, split, run, and verifier configuration before RLNC decoding. This corresponds to corpus-level auditing or a longer audit window, not to a per-task success rate.

Table 7 reports the repeats-10 ranking-noise rerun for AsymAgentMark-TK with DeepSeek and top-10 adjacent-swap perturbations. ALFWorld is robust under moderate ranking noise: the ID split remains at 1.0 pooled recovery through $\epsilon = 0.5$, and OOD remains at 1.0 through $\epsilon = 0.3$ before dropping at $\epsilon = 0.5$. ToolBench all-split pooling remains at 1.0 through $\epsilon = 0.5$ in the DeepSeek rerun. This is the expected boundary of weak asymmetry: probability-value perturbations are harmless when ranks are preserved,

TABLE 7. POOLED RECOVERY FOR ASYMAAGENTMARK-TK UNDER ADJACENT-SWAP RANKING NOISE. DEEPSEEK, TOP-10, REPEATS=10. VALUES ARE CORPUS-LEVEL POOLED DECODE SUCCESS, NOT PER-TRAJECTORY RECOVERY.

Dataset	Split	$\epsilon = 0.0$	$\epsilon = 0.1$	$\epsilon = 0.3$	$\epsilon = 0.5$
ALFWorld	ID	1.00	1.00	1.00	1.00
ALFWorld	OOD	1.00	1.00	1.00	0.83
ToolBench	all splits	1.00	1.00	1.00	1.00

TABLE 8. POOLED RECOVERY UNDER STEP ERASURE AFTER THE FIXED 3.2 RERUN. DEEPSEEK, TOP-10. CELLS SHOW POOLED SUCCESS AT ERASURE RATES 0.0/0.5/0.9.

Dataset	Method	Pool	0.0	0.5	0.9
ALFWorld	AgentMark-F	ID	1.00	1.00	1.00
ALFWorld	AsymAgentMark-TK	ID	1.00	1.00	1.00
ALFWorld	AgentMark-F	OOD	1.00	1.00	1.00
ALFWorld	AsymAgentMark-TK	OOD	1.00	1.00	1.00
ToolBench	AgentMark-F	all splits	1.00	1.00	1.00
ToolBench	AsymAgentMark-TK	all splits	1.00	1.00	1.00

but top- k swaps can corrupt the decoded path once they remove too many independent packets or introduce conflicts.

Table 8 reports the fixed erasure/channel-degradation rerun after correcting the AgentMark-F decoder configuration. Both AgentMark-F and AsymAgentMark-TK recover under pooled detection even when 90% of steps are erased. The important comparison is not that every pooled cell reaches 1.0; rather, it is that pooled evidence can overcome the packet scarcity that limits strict single-trajectory recovery. The packet counts still reveal the cost of rank-only decoding: on ALFWorld ID at 90% erasure, AsymAgentMark-TK retains 24.1 deduplicated pooled packets on average, while AgentMark-F retains 55.4 under exact probabilities.

6.12. Robustness Axis: Matched Top- k Audit Windows

We also rerun ToolBench with the rank embedder configured to the same k used by the rank-only decoder. This matched-top- k rerun removes a calibration confound from earlier ToolBench robustness artifacts: if the embedder and verifier use different candidate depths, packet scarcity and top- k truncation are entangled. The rerun uses DeepSeek v3.2 across all six ToolBench splits, three seeds, and 20 tasks per split, giving 360 trajectories for each $k \in \{3, 5, 10\}$ and 1080 completed jobs.

Table 9 summarizes the result. Single-trajectory strict recovery remains low because most ToolBench tasks expose too few independent packets. Mean deduplicated packets per trajectory increase from 0.63 at $k = 3$ to 1.63 at $k = 10$, and strict recovery rises only from 0.000 to 0.028. Audit-window recovery is much stronger. Pooling all splits and all three seeds recovers the 8-bit payload at all three k values with no packet conflicts; pooling each seed separately succeeds in 1/3, 2/3, and 3/3 seeds for $k = 3, 5, 10$, respectively. The sampled pool curve shows the same pattern: at pool size 10,

TABLE 9. TOOLBENCH MATCHED-TOP- k RERUN. STRICT IS SINGLE-TRAJECTORY PAYLOAD RECOVERY; POOLED COLUMNS REPORT ALL-SPLIT AUDIT-WINDOW RECOVERY.

k	Traj.	Strict	Pkt./traj.	All pooled	Per-seed pooled	Pool 10	Pool 20
3	360	.000	.63	1.00	1/3	.590	.985
5	360	.008	1.06	1.00	2/3	.860	.990
10	360	.028	1.63	1.00	3/3	.950	1.000

TABLE 10. TOOLBENCH LIVE L5 CROSS-MODEL TOP-10 RERANK/DECODE. STRICT IS SINGLE-TRAJECTORY PAYLOAD RECOVERY; POOLED COLUMNS ARE AUDIT-WINDOW RECOVERY AT SAMPLED POOL SIZES.

Embedder	Verifier	Top-1	Top-10 overlap	Strict	Pool 10	Pool 20	All pooled
DeepSeek	Gemini	.842	.640	.044	.935	.990	1.00
Gemini	DeepSeek	.761	.593	.011	.705	.945	1.00

recovery is 0.590, 0.860, and 0.950; by pool size 20, it is 0.985, 0.990, and 1.000. Thus the ToolBench result is not a per-task attribution claim. It is evidence that, once the top- k interface is calibrated, pooled ToolBench audits recover reliably and $k = 10$ is the most stable tested setting.

6.13. Robustness Axis: Live Cross-Model Rerank

The preceding rank-noise, erasure, and matched-top- k experiments isolate controlled verifier-channel factors. We also run a live ToolBench L5 cross-model rerank/decode experiment: the verifier model calls an API to rescore each eligible candidate action set and then decodes from the resulting top- k order. This is a real verifier rerank rather than an offline probability proxy. Table 10 reports top-10 results for both directions between DeepSeek and Gemini Flash.

Strict single-trajectory recovery remains low, again because ToolBench trajectories provide few independent packets per task. However, top-10 rank agreement is high enough for pooled audit-window recovery. DeepSeek-to-Gemini reaches 0.935 pooled recovery at pool size 10 and 0.990 at pool size 20; Gemini-to-DeepSeek reaches 0.705 at pool size 10 and 0.945 at pool size 20. Pooling all available ToolBench splits recovers in both directions. This is the strongest deployment-facing ToolBench evidence in the current artifact set: AsymAgentMark-TK does not require the verifier to reproduce calibrated probabilities, but it does require enough cross-model rank agreement and enough independent packets.

The same live L5 protocol exposes a boundary on ALFWorld. Cross-model top-10 overlap is moderate (0.596 for DeepSeek-to-Gemini and 0.633 for Gemini-to-DeepSeek), but top-1 agreement is only about 0.20, and pooled recovery succeeds only for the Gemini-to-DeepSeek ID pool in the pulled artifact. We therefore treat cross-model rerank as a ToolBench-positive but domain-dependent result, not as evidence that every agent domain has stable enough ranks for pooled recovery without calibration.

6.14. Evidence Axis: False Positives and Evidence Thresholds

False-positive control is analytic for strict payload claims. If a clean or unrelated trajectory yields coded bits that are independent of a fixed pre-registered payload claim, and no adaptive post-hoc key or payload search is counted as the same test, the chance that it recovers that exact L -bit payload is 2^{-L} . For payload lengths $L = 8, 16, 32, 64$, the corresponding single-claim thresholds are 3.91×10^{-3} , 1.53×10^{-5} , 2.33×10^{-10} , and 5.42×10^{-20} . Operational deployments should use at least 32-bit claims for audit-grade attribution, with longer payloads when enough trajectory length is available.

The threshold must also account for multiple testing. If an operator tests N independent key/payload claims against the same corpus, a conservative union bound gives a family-wise false-positive rate at most $N2^{-L}$. Thus an 8-bit payload is appropriate for controlled capacity diagnostics but not for open-ended attribution. A 64-bit payload keeps the bound below 10^{-12} even for one million tested claims, assuming the verifier also enforces the rank-quality gate described in Section 4.6.

The postprocessed false-positive artifact instantiates this calculation across dataset, model, split, and top- k configurations using 1000 random payload trials per clean trajectory. With DeepSeek and top-10, ALFWorld’s empirical micro-FPR decreases from 0.0433 at $L = 4$ to 0.00137 at $L = 8$ and 7.6×10^{-5} at $L = 12$, below the corresponding ideal random-match bounds of 2^{-4} , 2^{-8} , and 2^{-12} . ToolBench gives even lower empirical rates, including zero observed matches at $L \geq 8$ in the selected splits, but this should not be overread as stronger security because ToolBench clean traces often contain too few decodable packets. Because the strict event is exact payload equality for a pre-registered claim, we still report the analytic per-claim threshold 2^{-L} as the security control and use the trials only to size the expected number of accidental matches under the tested trajectory and claim counts. Appendix E maps this and the other reported diagnostics to their source files.

Bit-level scores require a different interpretation. When a verifier reports a match rate over n decoded coded bits rather than a recovered payload, the appropriate null is a binomial tail $\Pr[X \geq s; X \sim \text{Binom}(n, 1/2)]$ for the observed score s . This statistic is useful for channel diagnostics and triage before enough independent RLNC equations are available, but it is not a positive attribution decision unless the pre-registered payload itself is recovered.

The confidence-curve artifact illustrates this distinction. For DeepSeek ALFWorld ID, AsymAgentMark-TK with top-10 reaches a one-sided binomial geomean $p = 4.32 \times 10^{-5}$ at $N = 20$ observed embedding steps and 4.10×10^{-26} at $N = 100$. At $\alpha = 0.01$, the 32-bit evidence-threshold table gives $N_{\min} = 62.5$ for ALFWorld top-10 and $N_{\min} = 50.0$ for ToolBench top-10; smaller diagnostic payloads cross earlier. These values quantify channel evidence, not ownership by themselves: they become attribution evidence

only when the same audit also satisfies claim binding, rank-quality gating, and strict payload recovery.

7. Discussion

Exact probability is a luxury. The evaluation supports a pragmatic conclusion: if exact P_t is available, symmetric AgentMark-F can be more capacity-efficient. If the verifier has only top- k ranks, symmetric decoding becomes unreliable, and a rank-decodable construction is the relevant design point.

ToolBench exposes a low-entropy regime. Tool-use traces are shorter and often contain fewer semantically viable actions than embodied planning. AsymAgentMark-TK preserves utility in this setting, but the offline payload recovery remains low. This suggests combining rank encoding with adaptive step selection, longer audit windows, or higher-level tool-plan aggregation.

Rank consistency is observable. Unlike exact probability equality, rank consistency can be measured directly during verification. A verifier can report top- k agreement, Kendall tau distance, or adjacent-swap rates to calibrate confidence.

Why not fully asymmetric verification? A verifier that sees only the selected action has too little information to distinguish a keyed watermark from ordinary policy variation without shifting the agent’s behavior distribution. The selected-only negative-control view in our evaluation reflects this limit. AsymAgentMark-TK therefore takes a middle position: it does not require calibrated probabilities, but it does require a reproducible candidate ranking. This is a practical assumption for many audited agents because tool schemas, admissible environment actions, and candidate lists are often easier to reconstruct than exact sampling probabilities.

Adaptive adversaries. An adversary aware of the watermark could try to perturb ranks while preserving task success. This attack is outside pure distribution perturbation and should be treated as an active removal attack. Defenses include randomized k , context-dependent rank partitions, and cross-step consistency checks.

Operational audit flow. A practical verifier should not treat every low-confidence trajectory as a negative attribution. Instead, it should first check whether the top- k rank reconstruction is itself reliable. If the reconstructed rank agreement is poor, the correct conclusion is an inconclusive audit rather than a clean verdict. This distinction matters in legal or compliance settings, where absence of recoverable watermark evidence is not the same as evidence of absence.

From feasibility to deployment. The evaluation establishes the channel-knowledge tradeoff: rank-only verification can preserve useful signal when exact-probability verification is unavailable. The strongest current results are diagnostic and pooled: strict single-trajectory recovery is limited by packet scarcity, while pooled evidence recovers once enough trajectories or audit-window steps are available. A production deployment should add three engineering checks before relying on decoded payloads for attribution:

live end-to-end RLNC recovery, calibrated cross-model rank reconstruction for the deployed verifier model or API, and pre-registered decision thresholds for positive, inconclusive, and negative outcomes. These checks are operational rather than conceptual, but they are important for turning weak-asymmetric provenance into an audit procedure.

What the contribution is not. AsymAgentMark-TK is not a claim that rank-only decoding dominates symmetric decoding on every metric. It intentionally gives up exact-channel capacity to remove a verifier-channel assumption that is fragile in realistic audits. The contribution is the robustness boundary and the corresponding repair: when calibrated probabilities cannot be trusted but top- k ranks can, decode from the invariant that survives.

8. Related Work

LLM and agent watermarking. Token-level LLM watermarking modifies or tests generated text distributions [4], [5]. Follow-up work studies reliability under paraphrasing, mixed documents, and edit-style perturbations [15], [16]. These methods are complementary to behavioral watermarking because agents often compile natural-language plans into structured actions, where the final text may no longer carry the decision signal. AgentMark [6] is the closest prior work and establishes distribution-preserving behavioral watermarking. AsymAgentMark-TK keeps its utility-preservation objective but weakens the verifier’s channel requirement.

Behavior-level provenance for agents. Recent agent watermarking work shows that the behavior trajectory itself can carry provenance evidence. Agent Guide biases an agent toward keyed behavior subsets and detects the resulting trajectory statistic [17]; it is simple and model-agnostic, but its watermark signal comes from an intentional behavior-distribution shift. AgentMark [6] instead preserves the per-step behavior distribution and embeds payload bits through symmetric differential recombination, making it the direct predecessor of this paper. Sequential behavioral watermarking further encodes signals across action transitions and detects them in a position-agnostic way [18]. These lines are complementary to our channel-knowledge question. AsymAgentMark-TK is not another detector statistic over selected actions; it asks what channel information the verifier must reconstruct to decode a distribution-preserving behavioral payload. Its answer is top- k rank order rather than exact probability values.

Robustness target. Most text-watermark robustness work asks whether a detector can still identify generated text after rewriting or mixing. Our robustness target is different: the observed behavior may be unchanged, but the verifier’s reconstruction of the behavior distribution may differ from the embedder’s. This makes probability-value perturbation a channel-knowledge problem rather than an output-editing problem. AsymAgentMark-TK addresses this by designing the decoded statistic to be rank position, not a probability-dependent bin.

Steganography and distribution-preserving sampling.

Provably secure steganography formalizes indistinguishability between cover and stego content [11]. Meteor provides a practical cryptographic construction for realistic distributions [12], while later work improves payload embedding under language-model channels through undetectable or sparse-sampling constructions [19], [20], [21]. Weakly asymmetric steganography studies receivers with partial channel knowledge and gives the rank-based construction that we rely on [7]. AsymAgentMark-TK does not claim this rank primitive as original; it adapts the primitive from token/text channels to planning-behavior channels, couples it with AgentMark’s distribution-preserving behavior interface and RLNC recovery layer, and evaluates the resulting verifier-knowledge tradeoff on agent trajectories.

Erasures coding for partial logs. Random linear network coding is a standard way to recover a payload from any sufficiently independent subset of coded symbols [13]. In behavioral watermarking, this abstraction is useful because trajectories are naturally partial: failed steps, missing telemetry, and verifier-side top- k misses all become erasures. Our contribution is not a new erasure code; it is the rank-only step decoder that supplies coded bits to the existing erasure-tolerant layer.

Agent benchmarks. ALFWorld aligns text-based embodied environments with interactive learning [8]. ToolBench evaluates LLM tool-use over real-world APIs [9]. OASIS demonstrates large-scale social-agent simulation [10]. These benchmarks highlight why behavior-level provenance matters: the action trajectory is often more important than the final message.

9. Threats to Validity and Ethics

Offline postprocessing. Capacity and robustness experiments are computed from logged trajectories and offline decoder proxies. This is appropriate for isolating the channel-knowledge question, but it is weaker than a complete live deployment study with end-to-end RLNC recovery under production logging. The paper therefore labels proxy capacity claims explicitly and avoids treating them as full-system recovery guarantees.

Verifier perturbations. The current artifact package includes controlled ranking-noise injection, a fixed erasure/channel-degradation rerun, empirical false-positive trials, evidence-strength diagnostics, a ToolBench matched-top- k rerun, and a ToolBench live L5 cross-model top- k rerank/decode study between DeepSeek and Gemini Flash. These studies test the verifier’s rank-reconstruction pipeline rather than only the probability-versus-rank decoder boundary isolated in the offline proxy. The coverage is still incomplete: the positive matched-top- k and L5 claims are ToolBench claims, not a statement that embodied-planning domains such as ALFWorld have equally stable cross-model ranks. The theory covers L5 only to the extent that the cross-model verifier preserves top- k rank paths; calibrating that preservation remains a deployment requirement.

Benchmark coverage. ALFWorld and ToolBench cover embodied planning and tool-use, but they do not exhaust the space of agentic workflows. Social simulation, GUI control, multi-agent collaboration, and long-running enterprise agents may have different rank stability and trajectory length. The construction is domain-agnostic, but the best k and payload length should be calibrated per environment.

Statistical uncertainty. The evaluation reports aggregate success, JSD, and recovery rates over the completed model/split groups in the result package. These aggregates support the qualitative channel-knowledge comparison, but they should not be read as formal significance tests for small utility differences. A deployment study should pre-register its task distribution, sampling budget, and uncertainty intervals before using small deltas as operational evidence.

Candidate canonicalization. Rank decoding assumes that the verifier can map the logged behavior and reconstructed candidates into the same canonical behavior set. This is straightforward for enumerated actions and structured tool calls, but less automatic for free-form plans, GUI operations, or APIs whose schemas evolve over time. A deployment should canonicalize tool names, arguments, and environment actions before ranking; otherwise a semantically correct but differently serialized behavior may appear outside the verifier’s top- k list and become an erasure.

Distribution elicitation. The method assumes that the embedder can elicit or estimate a behavior distribution. If the candidate generator is poor, distribution preservation protects the wrong channel. This is a limitation inherited from behavioral watermarking generally, not a weakness specific to rank-only decoding.

9.1. Ethics Considerations

This work is intended for provenance, audit, and authorized ownership verification. It should not be used to conceal malicious coordination or bypass platform policy. The construction assumes access to a behavior distribution at embedding time and top- k rank information at verification time. It does not protect against arbitrary rank manipulation, model-level watermark removal, or compromised keys. The evaluation uses offline decoder artifacts; deployment use requires end-to-end RLNC recovery under live logging and cross-model rank reconstruction.

The reported evaluation uses benchmark task trajectories and postprocessed experiment artifacts rather than private user data. A deployment that logs real agent behavior should treat trajectories as potentially sensitive operational records, minimize retained context, and bind verification access to an explicit audit purpose.

Watermarking creates governance risks as well as benefits. A false or overconfident attribution can harm users, developers, or organizations. Deployments should therefore publish the verification threshold, report inconclusive outcomes, retain audit logs, and separate watermark evidence from broader incident investigation. The method should not be used for covert monitoring of users without notice;

its appropriate role is provenance for agents or services controlled by the embedding party.

10. Conclusion

Behavioral provenance for LLM agents should not depend on a verifier reproducing exact per-step probabilities. This paper identifies probability-bin instability as a verifier-channel failure mode for symmetric behavioral watermarking and shows that top- k rank order can retain useful watermark signal while preserving the agent’s marginal behavior policy. By replacing probability-dependent bins with a rank-decodable binary partition tree, AsymAgentMark-TK trades some exact-channel nominal capacity for usable effective capacity under realistic partial-channel verification. This weakly asymmetric view makes behavioral watermarking better aligned with how agents are actually audited: decode from the invariant that survives.

These results should be read as evidence for partial-channel feasibility rather than as a final production certification. Exact-channel AgentMark-F remains attractive when the original behavior probabilities are available; AsymAgentMark-TK targets the common audit setting where only ranks can be reconstructed reliably. Closing the remaining deployment gap requires longer live trajectories, end-to-end coded-payload recovery, and cross-model rank calibration.

Appendix A. Distribution-Preservation Details

This appendix expands the proof sketch from Section 5. At any internal node of the top- k partition tree, let the even-rank group have normalized mass S_0 and the odd-rank group have mass S_1 , with $S_0 + S_1 = S$. Assume without loss of generality that $S_0 \geq S_1$; otherwise the group labels are swapped for the binary primitive. For $r \leftarrow U[0, 1)$ and message bit $m \in \{0, 1\}$, BinEnc computes

$$r_m = (rS + \frac{1}{2}Sm) \bmod S.$$

For either fixed m , r_m is uniform over $[0, S)$ because adding a constant modulo S preserves uniformity. Therefore the probability of selecting group j is exactly S_j/S . When the higher-mass group is selected, no bit is consumed; when the lower-mass group is selected, one bit is consumed. Bit consumption changes the message pointer but not the marginal group-selection probability.

Inducting over the recursive partition tree, every top- k leaf b is selected with probability equal to its normalized top- k mass $P_t(b)/S_{\text{top}}$. The top/tail gate enters the tree with probability $S_{\text{top}} = \sum_{i \leq k} P_t(\sigma_t(i))$ and otherwise samples the tail proportionally. Hence every behavior, including tail behaviors that carry no bits, has marginal probability $P_t(b)$.

Appendix B. DRBG Synchronization

The encoder and decoder derive a per-step HMAC-SHA512 DRBG stream from the shared key and logged context. The important invariant is not the exact digest format, but the fixed consumption budget. For a top- k step, both sides reserve

$$B_k = \lceil \log_2 k \rceil$$

DRBG draws for the rank tree. The encoder may terminate early when a singleton leaf is reached or when a zero-bit branch defers the message bit, but it still advances the stream to consume exactly B_k draws. The decoder independently consumes the same B_k draws before returning the recovered bits. Tail selections emit no bits and are treated as erasures by the verifier.

This fixed-budget rule prevents a local zero-bit event from shifting every later step. Without it, the decoder would have to know whether the encoder consumed a message bit or terminated early at each level, which is precisely the information it is trying to infer from the rank path.

Appendix C. RLNC Payload Recovery

The rank decoder outputs a variable number of coded bits from each observed step. Deterministic RLNC converts these bits into payload equations. For an L -bit payload m , the i -th coded bit is $c_i = \langle a_i, m \rangle \bmod 2$, where a_i is generated from a deterministic coefficient stream. The verifier collects decoded pairs (a_i, c_i) and solves the resulting linear system over $\text{GF}(2)$. Recovery succeeds when the collected coefficient matrix has rank L and the decoded right-hand side is consistent.

This layer is agnostic to whether a coded bit came from exact-probability decoding or rank-only decoding. Rank-only verification typically produces fewer reliable equations, so it may need longer trajectories or larger audit windows. The paper’s 8-bit proxy tables are therefore channel diagnostics: they measure whether the step decoder supplies useful equations under different verifier views, not whether a deployment-length identifier has been certified.

Appendix D. Rank Stability and Top- k Choice

Temperature rescaling preserves rank order because $p_i^{1/T}/Z$ is monotone in p_i for $T > 0$. Quantization, model refreshes, and proxy re-querying need not preserve ranks exactly, but adjacent swaps are most likely when score gaps are small. This motivates top- k restriction: high-probability behaviors usually have larger gaps and more stable semantic alternatives than long-tail candidates.

The top- k parameter therefore trades nominal capacity against reconstruction risk. Larger k gives more leaves and

potentially more decoded bits per step, but it asks the verifier to reconstruct lower-probability ranks. Smaller k is conservative and compatible with restricted APIs, but it may underuse high-entropy trajectories. The deployment choice should maximize calibrated $C_{\text{eff}}(k)$, not raw decoded length: a deeper top- k view is useful only when its marginal capacity gain exceeds the marginal decode-success loss. The evaluation reports a sweep rather than selecting a universal k because the best choice is environment-dependent.

Appendix E. Artifact Mapping

The reported tables are tied to postprocessed artifacts as follows.

- Utility and JSD: `utility_main.csv`, `behavior_jsd_clean.csv`.
- Capacity and top- k : `capacity_proxy_payload8_logged_channels.csv`, `topk_ablation_main.csv`.
- Strict recovery: `strict_rlnc_recovery_main.csv`, `strict_rlnc_recovery_global.csv`.
- Pooled robustness: `stage_c_3_1_rank_noise_pooled_summary.csv`, `stage_c_3_2_erasure_channel_pooled_summary.csv`.
- ToolBench matched top- k : `toolbench_rank_topk_matched/postprocess/summary_global.csv`, `toolbench_rank_topk_matched/postprocess/pooled_by_run.csv`, and `toolbench_rank_topk_matched/pool_curve/pool_curve_summary.csv`.
- Live L5 cross-model rerank: `capacity_l5_cross_model_rerank_toolbench_packets/l5_cross_model_summary.csv`, `capacity_l5_cross_model_rerank_toolbench_packets/l5_cross_model_pooled_summary.csv`, and `capacity_l5_cross_model_rerank_toolbench_pool_curve/l5_toolbench_pool_curve_summary.csv`.
- False positives: `stage_c_3_4_false_positive_summary.csv`.
- Evidence strength: `stage_d_4_1_confidence_summary.csv`, `stage_d_4_2_thresholds_summary.csv`.

JSON sidecars mirror the CSV rows for automated checks.

References

- [1] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafraan, K. Narasimhan, and Y. Cao, “ReAct: Synergizing reasoning and acting in language models,” *arXiv preprint arXiv:2210.03629*, 2022.
- [2] J. Achiam, S. Adler, S. Agarwal, L. Ahmad, I. Akkaya, F. L. Aleman, D. Almeida, J. Altenschmidt, S. Altman, S. Anadkat *et al.*, “GPT-4 technical report,” *arXiv preprint arXiv:2303.08774*, 2023.
- [3] Gemini Team, “Gemini: A family of highly capable multimodal models,” *arXiv preprint arXiv:2312.11805*, 2023.
- [4] J. Kirchenbauer, J. Geiping, Y. Wen, J. Katz, I. Miers, and T. Goldstein, “A watermark for large language models,” in *Proceedings of the International Conference on Machine Learning*, 2023.
- [5] S. Dathathri, A. See, S. Ghaisas, P.-S. Huang, R. McAdam, J. Welbl, V. Bachani, A. Kaskasoli, R. Stanforth, T. Matejovicova, J. Hayes, N. Vyas, T. Zaccary, M. Zilka, I. Gabriel, W. Isaac, A. Guez, L. Weidinger, J. Mellor, D. Hassabis, K. Kavukcuoglu, G. Irving, and P. Kohli, “Scalable watermarking for identifying large language model outputs,” *Nature*, 2024.
- [6] K. Huang, J. Tan, Y. Wei, W. Li, Z. Zhang, H. Tian, Z. Yang, and L. Zhou, “AgentMark: Utility-preserving behavioral watermarking for agents,” in *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, 2026.
- [7] Anonymous authors, “Title omitted for double-blind review,” Anonymous manuscript, 2026.
- [8] M. Shridhar, X. Yuan, M.-A. Côté, Y. Bisk, A. Trischler, and M. Hausknecht, “ALFWorld: Aligning text and embodied environments for interactive learning,” in *Proceedings of the International Conference on Learning Representations*, 2021.
- [9] Y. Qin, S. Liang, Y. Ye, K. Zhu, L. Yan, Y. Lu, Y. Lin, X. Cong, X. Tang, B. Qian, S. Zhao, R. Tian, R. Xie, J. Zhou, M. Gerstein, D. Li, Z. Liu, and M. Sun, “ToolLLM: Facilitating large language models to master 16000+ real-world apis,” *arXiv preprint arXiv:2307.16789*, 2023.
- [10] C. Gao, X. Lan, Z. Lu, J. Mao, J. Piao, H. Wang, D. Jin, and Y. Li, “OASIS: Open agents social interaction simulations with one million agents,” *arXiv preprint arXiv:2411.11581*, 2024.
- [11] N. J. Hopper, J. Langford, and L. von Ahn, “Provably secure steganography,” in *Proceedings of the Annual International Cryptology Conference*, 2002.
- [12] G. Kaptchuk, T. M. Jois, M. Green, and A. D. Rubin, “Meteor: Cryptographically secure steganography for realistic distributions,” in *Proceedings of the ACM SIGSAC Conference on Computer and Communications Security*, 2021.
- [13] T. Ho, M. Médard, R. Koetter, D. R. Karger, M. Effros, J. Shi, and B. Leong, “A random linear network coding approach to multicast,” *IEEE Transactions on Information Theory*, vol. 52, no. 10, pp. 4413–4430, 2006.
- [14] DeepSeek-AI, “DeepSeek ILM: Scaling open-source language models with longtermism,” *arXiv preprint arXiv:2401.02954*, 2024.
- [15] J. Kirchenbauer, J. Geiping, Y. Wen, M. Shu, K. Saifullah, K. Kong, K. Fernando, A. Saha, M. Goldblum, and T. Goldstein, “On the reliability of watermarks for large language models,” in *Proceedings of the International Conference on Learning Representations*, 2024.
- [16] R. Kuditipudi, J. Thickstun, T. Hashimoto, and P. Liang, “Robust distortion-free watermarks for language models,” *Transactions on Machine Learning Research*, 2024.
- [17] K. Huang, Z. Zhang, Z. Yang, and L. Zhou, “Agent guide: A simple agent behavioral watermarking framework,” *arXiv preprint arXiv:2504.05871*, 2025.
- [18] H. An, S. Park, D. Kim, and Y.-S. Han, “Sequential behavioral watermarking for LLM agents,” *arXiv preprint arXiv:2605.11036*, 2026.
- [19] M. Christ, S. Gunn, and O. Zamir, “Undetectable watermarks for language models,” in *Proceedings of the Conference on Learning Theory*, 2024.
- [20] O. Zamir, “Undetectable steganography for language models,” *Transactions on Machine Learning Research*, 2024.
- [21] Y. Wang, G. Pei, K. Chen, J. Ding, C. Pan, W. Pang, D. Hu, and W. Zhang, “SparSamp: Efficient provably secure steganography based on sparse sampling,” in *Proceedings of the 34th USENIX Security Symposium*, 2025.