Kapılar • doors Kepenkler • shutters Pencereler • windows Cepheler · curtain walling Yapı Donanımları • building hardware

15.10.2020

Letter of Result / 2020-01-0640-B2

Initial type testing (ITT) of performance characteristics in accordance with EN 14351-1 :2006 + A2 : 2016 "Windows and doors - Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets"

Applicant Gürmen PVC Plastik İnş. San.ve Tic. Anonim.Şti Merkez Mah. 89.Sk.No:2 Sasalı – Çiğli / İzmir

Type Inward opening tilt and turn single casement window (double glazing)

System Proline 81mm Series

Total outside dimensions (W x H) Dimension max. 1180 mm x 1180 mm

Cesement (W x H) max. 1097 mm x 1097 mm

Test Date 09.10.2020

Results	EN 1026 A	Air Permeability	EN 12207	Class 4
resures	EN 1027 V	Water tightness	EN 12208	Class 9A
	EN 12211 R	Resistance to wind load	EN 12210	Class C5/B5
	EN 12046-1 C	Operating force	EN 13115	Class 0
	EN 14351-1 L	Load bearing of safety devices	EN 14351-1	complied
	EN 14351-1 S	Sound Insulation	EN 14351-1	•

Size of Specimen	Double glazing	4 - (12-16) - 4
Area $\leq 2.7 \text{ m}^2$	R _w (C;Ctr) dB	32 (-1;-5)
$2,7 \text{ m}^2 \le \text{Area} \le 3,6 \text{ m}^2$	R _w (C;Ctr) dB	31 (-1;-5)
$3.6 \text{ m}^2 \le \text{Area} \le 4.6 \text{ m}^2$	R _w (C;Ctr) dB	30 (-1;-5)
Area $> 4.6 \text{ m}^2$	R _w (C;Ctr) dB	29 (-1;-5)

*This document is not a report or a certificate. This document shows the test results. This document is not a certificate for CE-marking. Real reports will be prepared.

> Nedret Sürmeli General Managerp

Prüfzentrum Für Bauelement Yapı Elemanlan Test Merkezi San. ve Tig. Ltd. Şti. 10045 Sokak No: 7 A.O.S'B. Çiğli / İZMİR Tel: (0.232) 328 10 44

Çiğli Vergi Dalı si - 729 050 7072