



# 102553 Harness SA PV A



Wiring Chart			
P1	P2	Colour	Signal
3	1	White	Anode
4	2	Black	Cathode
5	3	Black	Anode
6	4	Green	Cathode

Table			
Var.	IFS P/N	CL1 [mm]	TL1 [mm]
1	<b>102553</b>	N/A	134 -0+8

General tolerance:  $\pm 0.1$  mm,  $\pm 1^\circ$

Item	Quantity	Manufacturer P/N	Manufacturer	Comments	IFS ID
A	2	MSAP106SB	Axon Cables S.A.S	Microstrip 6-pin, female	103359
B	1	KT2419^G	Axon Cables S.A.S	24 AWG FEP Green	103391
C	2	KT2419^B	Axon Cables S.A.S	24 AWG FEP Black	103382
D	1	KT2419^L	Axon Cables S.A.S	24 AWG FEP White	103381
E	3	To come	To come	Braided Polyester Lacing Tape, Type II	

Confidential - DO NOT DISTRIBUTE  
Copyright © 2018 by GomSpace A/S  
Langagervej 6  
9220 Aalborg East  
Denmark

ALL ARTICLES TO BE PRODUCED IN ACCORDANCE WITH:	
- IPC/WHMA-A-620C CLASS III	
- MANUFACTURER SPECIFIC RECOMMENDATIONS AND DESCRIPTIONS UNLESS OTHERWISE SPECIFIED	
<b>102553 Harness SA PV A</b>	
IFS document nr.:	1008455
Revision:	01
Project:	gs-hn-NanoHarness-SA_PV_A.PrjPcb
Engineer:	SRYT
Date:	30-05-2018
State of drawing:	PRELIMINARY

GOMSPACE