GomSpace A/S
Langagervej 6
9220 Aalborg East
Denmark
Phone: +45 71741741

CHECKED IN

Date:	22-03-2018
Program & PCB Name:	NanoPower BP8 Heater
Part Number:	?
Revision:	1
PCB Designer:	Mogens Groth Nicolaisen
PCB Specifications:	
Base Specification:	IPC-6013-D class 2+ (Class 3 regarding requirements for Annular ring breakout, Surface and copper plating, and Copper wrap plating)
Material:	Flexible Metal-Clad Dielectrics IPC-4204A Dupont Pyralux
Construction:	Two layer flex
Layer count:	2
Stackup detailes:	See Stack-up sheet
Tolerances:	Thickness: +/- 10%, Outline: +/- 10%, Cluster dimensions: +/- 10%

Special requirements:		
☐	Notation Top	White low-outgassing epoxy
☐	Notation Bottom	White low-outgassing epoxy
☐	Nickel/Hard Gold edge plating:	See Gold plated mechanical layer in files included below.
☐	Vias in pad has to be filled and capped	All drilled vias
☐	All Microvia has to be with copper filling.	Unless otherwise agreed
☐	Surface finish:	Hot Oil reflow SnPb - unless otherwise agreed
☐	Nickel/Hard gold contacts:	See Gold plated mechanical layer in files included below.
☐	Panelization	Use Gomspace standard cluster template - Choose Cluster 1 or Cluster 2
☑	Minimum isolation distance:	200um
☐	Countersunk holes	All 2.5 mm holes countersunk by 90 degrees to 5.5mm opening from the buttom layer.
☑	PCB manufacturer logo - **Not allowed**	unless otherwise agreed
☐	PCB Manufacturer serial number	See specified area in mechanical layer 7
☐	Stencil data required	Stencil data shall be based on compensated production files
☑	Electrically test to be done.	In accordance with IPC-9552, test level B
☐	Peelable Solder Mask:	
☑	Impedance controlled nets	Top layer 150 ohm +/- 3%
☐	Tolerances	Thickness: +/- 10%, Outline: +/- 10%, Cluster dimensions: +/- 10%

Files included in data package

	File Description	File Name	Format	Comments
☑	Read-Me File	ReadMe.pdf	ACROBAT	This Document
☑	Outline (Mechanical 4)	GND_breaker_default.GM4	OBD++	Board Outline
☐	CID+LOGO (Mechanical 6)	GND_breaker_default.GM6	ODB++	Notation Top - white low-outgassing epoxy
☑	Top Paste	GND_breaker_default.GTP	OBD++	Top Paste
☑	Top side flex	GND_breaker_default.GTL	ODB++	L1 in stackup
☑	Bottom side flex	GND_breaker_default.GBL	OBD++	L2 in stackup
☑	Bottom Paste	GND_breaker_default.GBP	OBD++	Bottom Paste
☑	ODB++	GND_breaker_default.zip	ODB	Netlist etc.
☑	Stackup details	Stack-up.pdf	ACROBAT	
☐	ID-text (Mechanical 7)	GND_breaker_default.GM7	ODB++	Manufacturer serial no. notation Bottom - white low-outgassing epoxy
☐				
☐				
☐				

All files are in millimeters and showed from top view.
Format: 4:3
Any changes/production optimizations shall be approved by GomSpace.