

SAFETY DATA SHEET

Safety Data Sheet - Mobil DTE 25

Hydraulic oil (ISO VG 32)

This is sample documentation generated for an Atlas CMMS demonstration environment. It mirrors the structure of a real OEM document but does not contain proprietary manufacturer content.

1. Identification

Product name: Mobil DTE 25

Manufacturer: ExxonMobil

Recommended use: metalworking / machine lubrication.

Emergency phone (CHEMTREC): 1-800-424-9300.

2. Hazards Identification

Classification: not classified as hazardous under OSHA HCS (sample data).

- Prolonged skin contact may cause mild irritation.
- Avoid contact with eyes; use in well-ventilated areas.

3. First-Aid Measures

Skin: wash with soap and water. Eyes: flush 15 minutes with water.

Inhalation: move to fresh air. Ingestion: do NOT induce vomiting; seek advice.

4. Handling & Storage

Store in a cool, dry, well-ventilated area away from oxidizers.

- Keep containers closed; avoid mist generation.

5. Disposal

Dispose of in accordance with local, state, and federal regulations.