Hands-On Activity 8 | Visualizing Variability

Name : Carl Andrei D. Torres

Course Code and Title : CPE-031 Visualizations and Data Analysis

Date Submitted : September 19, 2026

Instructor : Engr. Jimlord Quejado

---

1. Objectives:

This activity aims to develop students' ability to visualize deviations in data, and analyze variability with sample statistics and estimates.

2. Intended Learning Outcomes (ILOs):

By the end of this module the students should be able to:
1. Analyze how charts display represent categorical and quantitative data distribution.

2. Evaluate feature distribution and statistical measures of location and variability.

3. Create clear and coherent visualizations of sample statistics and prediction estimates.

3. Discussions:

Deviations in data values can appear within a single variable, such as the ages of Olympic gymnasts. It explains different chart types for showing how a variable's values are distributed. The choice of visualization depends on factors like whether the data is categorical or quantitative, the dataset size, and the number of variables being compared. To better interpret these visualizations, the chapter introduces basic statistical measures of central tendency and variability. It concludes with methods for visually representing variability in sample statistics and prediction estimates.

4. Procedures:

Creating Distributions from Data

In data analysis, understanding how variables vary is essential for making informed decisions. Distributions help engineers and analysts identify patterns, detect anomalies, and model real-world systems. A random variable represents a quantity whose values are uncertain, while realizations are the past observed values collected through sampling. Since it is rarely practical to analyze an entire population, analysts work with representative samples to generalize findings. Visualization techniques like histograms, frequency polygons, and relative frequency plots are critical tools for revealing the structure and variability of data.

Core Concepts

1. Random Variables and Variation
- Random variables represent uncertain values affected by external factors.
- Variation occurs when a variable's values differ across observations, such as over time or across customers.
- Descriptive analytics uses data visualization to understand these variations and their impact.
2. Types of Data
-.Categorical Data: Consists of labels or names that cannot be mathematically manipulated (e.g., beverage types, product categories).
- Quantitative Data: Numeric values that can be mathematically analyzed (e.g., sales numbers, temperatures).
3. Frequency Distributions
- Show how often specific values or ranges of values occur.
- Categorical Example: Soft drink sales distribution to compare popularity.
- Quantitative Example: Age distribution using ranges (bins) to capture continuous data.
4. Relative and Percent Frequency
- Relative frequency expresses counts as proportions of the total.
- Percent frequency provides percentages, useful for estimating probabilities.
- Example: Using purchase data to predict required stock for a concert.
5. Benford's Law
- Observes that in many natural datasets, lower digits (like 1) appear more frequently as the first digit.
- Used in fraud detection and anomaly detection, especially in financial datasets.

Visualization Techniques

1. Histograms
- Best for quantitative data.
- Columns without spaces represent continuous ranges of values.
- The number of bins and bin width strongly affect clarity:
- Too many bins make data noisy.

- Too few bins oversimplify patterns.
2. Frequency Polygons
- Use lines instead of bars, allowing easier comparison between multiple variables.
- Example: Comparing age distributions of male and female individuals.
3. Skewness
- Left-skewed: Most values are high, few are low (e.g., exam scores).
- Right-skewed: Most values are low, few are high (e.g., income data).
- Symmetric: Balanced distribution, like heights or standardized test scores.

Key Steps for Building Distributions
1. Define Bins: Decide the number and range of bins (typically 5–20).
2. Calculate Frequencies: Use software functions like COUNTIF or FREQUENCY in Excel.
3. Visualize:
- Clustered column charts for categorical data.
- Histograms or frequency polygons for quantitative data.
4. Interpret Patterns: Identify trends, anomalies, or potential risks.

Coding Procedure

In [ ]:
```
#Import libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# Seed for reproducibility
np.random.seed(42)
```

In [24]:

```
# Setup
# ========================================
# Generate sample quantitative data
# ========================================
# Simulated data: 200 random ages between 15 and 70
ages = np.random.randint(15, 70, 200)

# Define bin ranges for age groups
bins = [15, 25, 35, 45, 55, 65, 75]

# ========================================
# Part 1: Core Concepts
# ========================================
# Calculate frequency and relative frequency
frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

# Create a frequency table
distribution_df = pd.DataFrame({
    "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in
range(len(bins)-1)],
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("=== Part 1: Core Concepts ===")
print("Frequency and Relative Frequency Table:")
print(distribution_df)

# ========================================
# Part 2: Visualization Techniques
# ========================================
# Calculate midpoints for the frequency polygon
midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])

plt.figure(figsize=(10, 5))

# Histogram
plt.hist(ages, bins=bins, color='skyblue', edgecolor='black', alpha=0.7,
label='Histogram')

# Frequency Polygon
plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2,
label='Frequency Polygon')

print("=== Part 2: Visualization Techniques ===")
plt.title("Part 2: Visualization Techniques - Age Distribution")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
```

```
plt.show()

# ========================================
# Part 3: Key Steps for Building Distributions
# ========================================

print("\n=== Part 3: Key Steps for Building Distributions ===")

# Step 1: Define bins
print(f"Step 1: Bins defined as {bins}")

# Step 2: Calculate frequency and relative frequency
frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

step2_df = pd.DataFrame({
    "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in
range(len(bins)-1)],
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("\nStep 2: Frequency Table")
print(step2_df)

# Step 3: Visualize the data
plt.figure(figsize=(10, 5))
plt.hist(ages, bins=bins, color='lightgreen', edgecolor='black',
alpha=0.7, label='Histogram')
plt.plot(midpoints, frequency, color='blue', marker='o', linewidth=2,
label='Frequency Polygon')

plt.title("Step 3: Visualization of Age Distribution")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.show()


# Step 4: Interpret Patterns
max_freq_index = np.argmax(frequency)
most_common_range = step2_df.iloc[max_freq_index]["Age Range"]

print("\nStep 4: Interpretation")
print(f"- The most common age range is {most_common_range} with
{frequency[max_freq_index]} individuals.")

# Check skewness
lower_half = sum(frequency[:len(frequency)//2])
upper_half = sum(frequency[len(frequency)//2:])
```


```
if lower_half < upper_half:
    print("- The data is LEFT-SKEWED (more older individuals).")
elif lower_half > upper_half:
    print("- The data is RIGHT-SKEWED (more younger individuals).")
else:
    print("- The data is approximately symmetric.")
```


```
=== Part 1: Core Concepts ===
Frequency and Relative Frequency Table:
  Age Range  Frequency  Relative Frequency
0     15-24         28               0.140
1     25-34         44               0.220
2     35-44         39               0.195
3     45-54         34               0.170
4     55-64         36               0.180
5     65-74         19               0.095
=== Part 2: Visualization Techniques ===
```




```
=== Part 3: Key Steps for Building Distributions ===
Step 1: Bins defined as [15, 25, 35, 45, 55, 65, 75]

Step 2: Frequency Table
  Age Range  Frequency  Relative Frequency
0     15-24         28               0.140
1     25-34         44               0.220
2     35-44         39               0.195
3     45-54         34               0.170
4     55-64         36               0.180
5     65-74         19               0.095
```






```
Step 4: Interpretation
- The most common age range is 25-34 with 44 individuals.
- The data is RIGHT-SKEWED (more younger individuals).
```

Task 1: Creating Distributions from Data

Modify the provided code to see how **bin size** affects the shape of the distribution.

Instructions:

1. Update the `bins` variable to use **different bin groupings**, such as:

* `[15, 30, 45, 60, 75]`
* `[15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75]` (many narrow bins)

2. Run the code after each change and observe how the **histogram** and **frequency polygon** change.
3. Add labels or a note in the print statements describing which bin setting is being used.

In [1]:
```
#Import libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# Seed for reproducibility
np.random.seed(42)
```

In [29]:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# Setup
# ========================================
# Generate sample quantitative data
# ========================================
np.random.seed(42)  # Set seed for reproducible results
ages = np.random.randint(15, 70, 200)

# Define bin ranges for age groups
short = [15, 30, 45, 60, 75]
long = [15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75]

# ========================================
# Part 1: Core Concepts (Wide Bins: 'short')
# ========================================
# Calculate frequency and relative frequency using wide bins
frequency_short, bin_edges_short = np.histogram(ages, bins=short)
relative_frequency_short = frequency_short / len(ages)

# Create a frequency table
distribution_df_short = pd.DataFrame({
    "Age Range": [f"{short[i]}-{short[i+1]-1}" for i in
range(len(short)-1)],
    "Frequency": frequency_short,
    "Relative Frequency": relative_frequency_short.round(3)
})

print("=== Part 1: Core Concepts ===")
print("Frequency and Relative Frequency Table (Wide Bins):")
print(distribution_df_short)

# ========================================
# Part 2: Visualization Techniques (Wide Bins: 'short')
# ========================================
# Calculate midpoints specifically for short bins
midpoints_short = 0.5 * (bin_edges_short[1:] + bin_edges_short[:-1])

plt.figure(figsize=(10, 5))

# Histogram
plt.hist(ages, bins=short, color='skyblue', edgecolor='black',
alpha=0.7, label='Histogram')

# Frequency Polygon
plt.plot(midpoints_short, frequency_short, color='red', marker='o',
linewidth=2, label='Frequency Polygon')

print("\n=== Part 2: Visualization Techniques ===")
plt.title("Part 2: Visualization Techniques - Wide Bin Distribution (15-
```

```
Year Steps)")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(short)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.tight_layout()
plt.show()

# ========================================
# Part 3: Key Steps for Building Distributions (Narrow Bins: 'long')
# ========================================

print("\n=== Part 3: Key Steps for Building Distributions ===")

# Step 1: Define bins
print(f"Step 1: Bins defined as {long}")

# Step 2: Calculate frequency and relative frequency using narrow bins
frequency_long, bin_edges_long = np.histogram(ages, bins=long)
relative_frequency_long = frequency_long / len(ages)

step2_df = pd.DataFrame({
    "Age Range": [f"{long[i]}-{long[i+1]-1}" for i in
range(len(long)-1)],
    "Frequency": frequency_long,
    "Relative Frequency": relative_frequency_long.round(3)
})

print("\nStep 2: Frequency Table (Granular Bins)")
print(step2_df)

# Step 3: Visualize the data using long bin midpoints
midpoints_long = 0.5 * (bin_edges_long[1:] + bin_edges_long[:-1])

plt.figure(figsize=(10, 5))
plt.hist(ages, bins=long, color='lightgreen', edgecolor='black',
alpha=0.7, label='Histogram')
plt.plot(midpoints_long, frequency_long, color='blue', marker='o',
linewidth=2, label='Frequency Polygon')

plt.title("Step 3: Visualization of Age Distribution (5-Year Steps)")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(long)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.tight_layout()
plt.show()

# Step 4: Interpret Patterns
max_freq_index = np.argmax(frequency_long)
```

```
most_common_range = step2_df.iloc[max_freq_index]["Age Range"]


print("\nStep 4: Interpretation")
print(f"- The most common age range is {most_common_range} with
{frequency_long[max_freq_index]} individuals.")

# Check skewness on narrow bins
lower_half = sum(frequency_long[:len(frequency_long)//2])
upper_half = sum(frequency_long[len(frequency_long)//2:])

if lower_half < upper_half:
    print("- The data is LEFT-SKEWED (more older individuals).")
elif lower_half > upper_half:
    print("- The data is RIGHT-SKEWED (more younger individuals).")
else:
    print("- The data is approximately symmetric.")
```

```
=== Part 1: Core Concepts ===
Frequency and Relative Frequency Table (Wide Bins):
  Age Range  Frequency  Relative Frequency
0     15-29         58                0.29
1     30-44         54                0.27
2     45-59         58                0.29
3     60-74         30                0.15


=== Part 2: Visualization Techniques ===
```




```
=== Part 3: Key Steps for Building Distributions ===
Step 1: Bins defined as [15, 20, 25, 30, 35, 40, 45, 50, 55, 60,
65, 70, 75]

Step 2: Frequency Table (Granular Bins)
   Age Range  Frequency  Relative Frequency
0      15-19         18               0.090
1      20-24         19               0.095
2      25-29         21               0.105
```

```
3       30-34          10              0.050
4       35-39          23              0.115
5       40-44          21              0.105
6       45-49          15              0.075
7       50-54          20              0.100
8       55-59          23              0.115
9       60-64          11              0.055
10      65-69          19              0.095
11      70-74           0              0.000
```




```
Step 4: Interpretation
- The most common age range is 35-39 with 23 individuals.
- The data is RIGHT-SKEWED (more younger individuals).
```

QUESTION: How does increasing the number of bins affect the smoothness or detail of the visualization?

The increasing of the number of bins makes the bins in a narrow shape but it still manages to interpret the data which the most common range is 35-39 with 23 individuals but it complicates the skewness because of the large value of bins.

Statistical Analysis of Distributions of Quantitative Variables

Understanding data distributions is essential for engineers and analysts working with real-world datasets. Statistical measures and visualization techniques help summarize, analyze, and interpret data patterns effectively. This section focuses on methods for identifying central tendencies, variability, and outliers in quantitative variables. These concepts are foundational for data-driven decision-making, predictive modeling, and system optimization in computer engineering applications.

Measures of Location (Central Tendency):
- Identify the "center" of a dataset, which represents a typical value.
- Mean (Average):
- Sensitive to extreme values or outliers.
- Useful when data is evenly distributed.
- Median (Middle Value):
- Preferred when data contains extreme values or is skewed.
- More robust than the mean for smaller datasets.
- Mode (Most Frequent Value):
- Best for datasets with a limited range of distinct values.
- In continuous data, represents the range with the highest frequency in a histogram.

Measures of Variability (Dispersion):
- Quantify how spread out the data values are.
- Range:
- Simple to compute but overly affected by outliers.
- Standard Deviation:
- Indicates average deviation from the mean.
- Best for symmetric, bell-shaped distributions.
- Percentiles and Interquartile Range (IQR):
- Describe data spread without being distorted by extreme values.
- Useful for skewed datasets.
- IQR highlights the middle 50% of data values.

Visualization Techniques: Box-and-Whisker Plots
- Combine statistical measures into a clear visual summary.
- Show median, quartiles, range, and potential outliers.
- Useful for comparing multiple datasets, such as performance metrics across different systems.
- Outliers are easily identifiable, helping engineers detect anomalies in system behavior or sensor data.

Applications in Engineering

- Identifying network latency anomalies using skewness and outlier detection.
- Analyzing processor performance data through measures of variability.
- Monitoring sensor outputs in IoT systems with box plots for quality control.
- Selecting appropriate summary measures for predictive models and machine learning pipelines.

Statistical analysis of quantitative data involves understanding central tendency, variability, and outlier behavior. Combining numerical measures with effective visualizations like box plots enables engineers to interpret data more accurately. By applying these concepts, computer engineers can improve decision-making in areas such as performance optimization, anomaly detection, and predictive analytics.

In [ ]:

```
# ================================================
# Statistical Analysis of Distributions of Quantitative Variables
# ================================================

import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# Generate sample quantitative data: 200 random ages between 15 and 70
ages = np.random.randint(15, 70, 200)

# ------------------------------------------------
# PART 1: CORE CONCEPTS - Measures of Central Tendency and Variability
# ------------------------------------------------

print("=== PART 1: CORE CONCEPTS ===")

# Calculate measures of central tendency
mean_age = np.mean(ages)
median_age = np.median(ages)
mode_age = pd.Series(ages).mode()[0]  # mode() returns a Series

# Calculate measures of variability
range_age = np.max(ages) - np.min(ages)
std_dev_age = np.std(ages)
q1 = np.percentile(ages, 25)
q3 = np.percentile(ages, 75)
iqr = q3 - q1

# Display results
print(f"Mean Age: {mean_age:.2f}")
print(f"Median Age: {median_age}")
print(f"Mode Age: {mode_age}")
print(f"Range: {range_age}")
print(f"Standard Deviation: {std_dev_age:.2f}")
print(f"Interquartile Range (IQR): {iqr}")

# Interpretation example
if std_dev_age > 10:
    print("- The data has high variability.")
else:
    print("- The data has low variability.")

# ------------------------------------------------
# PART 2: VISUALIZATION TECHNIQUES - Box Plot and Histogram
# ------------------------------------------------

print("\n=== PART 2: VISUALIZATION TECHNIQUES ===")

plt.figure(figsize=(12, 5))

# Box plot to visualize spread and outliers
```

```
plt.subplot(1, 2, 1)
plt.boxplot(ages, vert=True, patch_artist=True,
boxprops=dict(facecolor='lightblue'))
plt.title("Box-and-Whisker Plot of Ages")
plt.ylabel("Age")

# Histogram to show frequency distribution
plt.subplot(1, 2, 2)
plt.hist(ages, bins=10, color='skyblue', edgecolor='black')
plt.title("Histogram of Ages")
plt.xlabel("Age")
plt.ylabel("Frequency")

plt.tight_layout()
plt.show()

# ------------------------------------------------
# PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS
# ------------------------------------------------

print("\n=== PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS ===")

# Step 1: Define bins for age ranges
bins = [15, 25, 35, 45, 55, 65, 75]

# Step 2: Calculate frequencies and relative frequencies
frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

# Step 3: Create a frequency table
distribution_df = pd.DataFrame({
    "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in
range(len(bins)-1)],
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("Frequency Distribution Table:")
print(distribution_df)

# Step 4: Visualize frequency polygon with histogram
midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])

plt.figure(figsize=(8, 5))
plt.hist(ages, bins=bins, color='lightgray', edgecolor='black',
alpha=0.7, label='Histogram')
plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2,
label='Frequency Polygon')
plt.title("Age Distribution with Frequency Polygon")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins)
```


```
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.show()

# Interpretation: Skewness
lower_half = np.sum(ages < median_age)
upper_half = np.sum(ages > median_age)


print("\nSkewness Interpretation:")
if lower_half < upper_half:
    print("- The data is LEFT-SKEWED (more older individuals, tail on
the left).")
elif lower_half > upper_half:
    print("- The data is RIGHT-SKEWED (more younger individuals, tail on
the right).")
else:
    print("- The data is approximately symmetric.")
```

```
=== PART 1: CORE CONCEPTS ===
Mean Age: 41.88
Median Age: 42.0
Mode Age: 58
Range: 54
Standard Deviation: 15.77
Interquartile Range (IQR): 28.0
- The data has high variability.

=== PART 2: VISUALIZATION TECHNIQUES ===
```




```
=== PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS ===
Frequency Distribution Table:
  Age Range  Frequency  Relative Frequency
0     15-24         37               0.185
1     25-34         31               0.155
2     35-44         44               0.220
3     45-54         35               0.175
4     55-64         34               0.170
5     65-74         19               0.095
```




```
Skewness Interpretation:
- The data is RIGHT-SKEWED (more younger individuals, tail on the
right).
```

Task 2: Statistical Analysis of Distributions of Quantitative Variables

Modify the provided code to explore how data distribution and visualization methods affect interpretation.

Part 1 (Core Concepts):

- Change the randomly generated data to simulate different scenarios, such as network latency or response times.

- Compare how the mean and median behave when outliers are introduced.

- Add at least one extreme value manually (e.g., very high age or latency).

Part 2 (Visualization Techniques):

- Adjust the box plot color scheme to make outliers more visible.

- Experiment with the number of bins in the histogram (try 5, 10, and 15) and observe how it changes the view of the data.

Part 3 (Building Distributions):

- Modify the bin ranges to group values differently, then observe how the frequency table and frequency polygon are affected.

- Add a title and axis labels that match the new dataset you created.

In [38]:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# Seed for reproducibility
np.random.seed(42)

response_times = np.random.exponential(scale=50, size=200)

# Add extreme outliers manually to test their impact on central tendency
response_times = np.append(response_times, [850.0, 1200.0])

# PART 1: CORE CONCEPTS - Outliers & Central Tendency

print("PART 1: CORE CONCEPTS (Network Latency)")

mean_rt = np.mean(response_times)
median_rt = np.median(response_times)
mode_rt = pd.Series(response_times).mode()[0]

range_rt = np.max(response_times) - np.min(response_times)
std_dev_rt = np.std(response_times)
q1 = np.percentile(response_times, 25)
q3 = np.percentile(response_times, 75)
iqr_rt = q3 - q1

print(f"Mean Response Time: {mean_rt:.2f} ms")
print(f"Median Response Time: {median_rt:.2f} ms")
print(f"Mode Response Time: {mode_rt:.2f} ms")
print(f"Range: {range_rt:.2f} ms")
print(f"Standard Deviation: {std_dev_rt:.2f} ms")
print(f"Interquartile Range (IQR): {iqr_rt:.2f} ms")

# PART 2: VISUALIZATION TECHNIQUES - Box Plot & Multi-Bin Histograms

print("\n=== PART 2: VISUALIZATION TECHNIQUES ===")

plt.figure(figsize=(16, 5))

# 1. Box plot with high-contrast outlier formatting (red markers)
plt.subplot(1, 4, 1)
plt.boxplot(
    response_times, vert=True, patch_artist=True,
            boxprops=dict(facecolor='green', color='black'),
            flierprops=dict(marker='o', color='red',
markerfacecolor='red', markersize=8))
plt.title("Box Plot of Latency (Outliers)")
plt.ylabel("Response Time (ms)")
plt.grid(axis='y', alpha=0.3)

# 2, 3, 4. Histograms experimenting with different bin counts (5, 10,
15)
```

```
bin_options = [5, 10, 15]
for i, b_count in enumerate(bin_options, start=2):
    plt.subplot(1, 4, i)
    plt.hist(response_times, bins=b_count, color='pink',
edgecolor='black')
    plt.title(f"Histogram (Bins = {b_count})")
    plt.xlabel("Response Time (ms)")
    plt.ylabel("Frequency")
    plt.grid(axis='y', alpha=0.3)

plt.tight_layout()
plt.show()


# PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS

print("\nPART 3: KEY STEPS FOR BUILDING DISTRIBUTION")

# Step 1: Define new bins tailored to latency ranges (0 to 1250 ms)
bins = [0, 100, 200, 300, 400, 500, 750, 1000, 1250]

# Step 2: Calculate frequencies and relative frequencies
frequency, bin_edges = np.histogram(response_times, bins=bins)
relative_frequency = frequency / len(response_times)

# Step 3: Create frequency table
distribution_df = pd.DataFrame({
    "Latency Range (ms)": [f"{bins[i]}-{bins[i+1]}" for i in
range(len(bins)-1)],
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("Network Latency Frequency Distribution Table:")
print(distribution_df)

# Step 4: Visualize frequency polygon with histogram
midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])


plt.figure(figsize=(10, 5))
plt.hist(response_times, bins=bins, color='yellow', edgecolor='black',
alpha=0.7, label='Histogram')
plt.plot(midpoints, frequency, color='black', marker='o', linewidth=2,
label='Frequency Polygon')
plt.title("Network Latency Distribution & Frequency Polygon")
plt.xlabel("Response Time Range (ms)")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.show()
```

```
# Skewness Interpretation based on Median (Fixed Logic)
lower_half = np.sum(response_times < median_rt)
upper_half = np.sum(response_times > median_rt)


print("\nSkewness Interpretation:")
if mean_rt > median_rt:
    print(">>The data is RIGHT-SKEWED")
elif mean_rt < median_rt:
    print(">>The data is LEFT-SKEWED.")
else:
    print(">>The data is near SYMMETRIC.")
```


```
PART 1: CORE CONCEPTS (Network Latency)
Mean Response Time: 56.95 ms
Median Response Time: 34.28 ms
Mode Response Time: 0.28 ms
Range: 1199.72 ms
Standard Deviation: 108.28 ms
Interquartile Range (IQR): 58.52 ms

=== PART 2: VISUALIZATION TECHNIQUES ===
```




```
PART 3: KEY STEPS FOR BUILDING DISTRIBUTION
Network Latency Frequency Distribution Table:
  Latency Range (ms)  Frequency  Relative Frequency
0              0-100        171               0.847
1            100-200         27               0.134
2            200-300          2               0.010
3            300-400          0               0.000
4            400-500          0               0.000
5            500-750          0               0.000
6           750-1000          1               0.005
7          1000-1250          1               0.005
```






```
Skewness Interpretation:
>>The data is RIGHT-SKEWED
```

QUESTION: How did adding outliers affect the mean and median?

It makes the histogram and the frequency polygon complicated in its form because of the arrangements of the figures.

Uncertainty in Sample Statistics

In data analysis, we often rely on samples to estimate characteristics of a larger population. However, because a sample is only a subset of the entire population, there is always uncertainty in how accurately sample results reflect the true population values. This uncertainty must be clearly communicated through statistical measures and visualizations to avoid misleading conclusions. By using tools like confidence intervals and visual aids such as error bars, analysts can provide a clearer picture of the reliability of their findings. These techniques are essential for engineers and data scientists when making decisions based on limited data, such as system monitoring, user behavior analysis, or predictive modeling.

Statistical Inference and Sampling
- Statistical inference is the process of using a sample to draw conclusions about a population.
- Uncertainty arises because samples are incomplete representations of the population.
- Common real-world applications include political polling, market research, and quality control.

Confidence Intervals (CIs)
- A confidence interval shows a range of values that likely contains the population parameter. It can be showed in two variations:
- Formula:
- Mean: sample mean ± margin of error
- Proportion: sample proportion ± margin of error
- Influencing factors:
- Sample size: Larger samples reduce uncertainty and narrow the interval.
- Data variability: Greater variability increases uncertainty and widens the interval.
- Confidence level: Higher confidence levels (e.g., 95% or 99%) require wider intervals.

Visualization Techniques
- Error Bars: Visually represent the margin of error around a point estimate.
- Box-and-Whisker Plots: Highlight variability, median, and outliers.
- Violin Plots: Combine box plots with density plots for a richer understanding of distribution shape.
- Starting the vertical axis at zero prevents misleading visuals unless comparing small differences.

Practical Examples
- Political Polling: Estimating the proportion of voters supporting a candidate.
- Market Research: Estimating average customer spending.
- Health Analytics: Comparing average lifespans between male and female groups.

- Engineering Context: Detecting network performance issues or system failures through error margins.

In [ ]:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from scipy import stats

# ================================
# PART 1: Statistical Inference and Sampling
# ================================
print("=== Part 1: Statistical Inference and Sampling ===")

# Population data: Simulate a population of 10,000 network latency
values (in ms)
population = np.random.normal(loc=100, scale=15, size=10000)  #
mean=100ms, std=15ms

# Draw a random sample of 50
sample_size = 50
sample = np.random.choice(population, sample_size, replace=False)

# Calculate population and sample means
population_mean = np.mean(population)
sample_mean = np.mean(sample)

print(f"Population Mean (True): {population_mean:.2f} ms")
print(f"Sample Mean (Estimate): {sample_mean:.2f} ms")
print(f"Sample Size: {sample_size}", end="\n\n")

# ================================
# PART 2: Confidence Intervals
# ================================
print("=== Part 2: Confidence Intervals ===")

# Calculate 95% confidence interval for the sample mean
confidence_level = 0.95
std_error = np.std(sample, ddof=1) / np.sqrt(sample_size)
margin_of_error = stats.t.ppf((1 + confidence_level) / 2,
df=sample_size-1) * std_error

ci_lower = sample_mean - margin_of_error
ci_upper = sample_mean + margin_of_error

print(f"95% Confidence Interval: [{ci_lower:.2f}, {ci_upper:.2f}] ms")

# ================================
# PART 3: Visualization Techniques
# ================================


# Create a dataframe for plotting
population_subset = np.random.choice(population, 200, replace=False)  #
200 for visualization

# Boxplot directly from separate arrays
```

```
plt.figure(figsize=(8, 5))
plt.boxplot(
    [population_subset, sample],
    tick_labels=['Population (Subset of 200)', 'Sample (50)'],
    patch_artist=True,
    boxprops=dict(facecolor='lightblue')
)
plt.title("Population vs Sample Variability")
plt.ylabel("Latency (ms)")
plt.show()
```

```
=== Part 1: Statistical Inference and Sampling ===
Population Mean (True): 99.99 ms
Sample Mean (Estimate): 105.76 ms
Sample Size: 50

=== Part 2: Confidence Intervals ===
95% Confidence Interval: [101.64, 109.87] ms
```



Task 3: Uncertainty in Sample Statistics

Modify the provided code to explore how sampling decisions and visualization methods affect uncertainty in statistical analysis.

Part 1: Sampling
- Change the sample size from 50 to 30 and 100.
- Compare how the sample mean differs from the population mean for each sample size.
- Print all sample means alongside the true population mean.

Part 2: Confidence Intervals
- Compute and print the 95% confidence intervals for each sample size.
- Observe how the width of the interval changes when the sample size increases or decreases.
- Highlight which sample size provides the most reliable estimate.

Part 3: Visualization
- Adjust the boxplot to include all three sample sets side by side along with the population subset.
- Add a clear title and proper axis labels.

In [31]:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from scipy import stats

# Set random seed for reproducible results
np.random.seed(42)

# ================================
# PART 1: Statistical Inference and Sampling
# ================================
print("=== Part 1: Statistical Inference and Sampling ===")

# Population data: Simulate a population of 10,000 network latency
values (in ms)
population = np.random.normal(loc=100, scale=15, size=10000)  #
mean=100ms, std=15ms

# Define sample sizes
sample_size_1 = 30
sample_size_2 = 50
sample_size_3 = 100

# Draw random samples from the population
sample_1 = np.random.choice(population, sample_size_1, replace=False)
sample_2 = np.random.choice(population, sample_size_2, replace=False)
sample_3 = np.random.choice(population, sample_size_3, replace=False)

# Calculate population and sample means
population_mean = np.mean(population)
mean_1 = np.mean(sample_1)
mean_2 = np.mean(sample_2)
mean_3 = np.mean(sample_3)

print(f"Population Mean (True): {population_mean:.2f} ms\n")
print(f"Sample Size {sample_size_1} Mean: {mean_1:.2f} ms")
print(f"Sample Size {sample_size_2} Mean: {mean_2:.2f} ms")
print(f"Sample Size {sample_size_3} Mean: {mean_3:.2f} ms\n")


# ================================
# PART 2: Confidence Intervals
# ================================
print("=== Part 2: Confidence Intervals ===")

# Function to calculate confidence interval
def calculate_ci(sample, confidence=0.95):
    n = len(sample)
    s_mean = np.mean(sample)
    std_err = np.std(sample, ddof=1) / np.sqrt(n)
    margin = stats.t.ppf((1 + confidence) / 2, df=n - 1) * std_err
    return s_mean - margin, s_mean + margin
```

```
ci_1 = calculate_ci(sample_1)
ci_2 = calculate_ci(sample_2)
ci_3 = calculate_ci(sample_3)

print(f"Sample (n={sample_size_1}) 95% CI: [{ci_1[0]:.2f},
{ci_1[1]:.2f}] ms")
print(f"Sample (n={sample_size_2}) 95% CI: [{ci_2[0]:.2f},
{ci_2[1]:.2f}] ms")
print(f"Sample (n={sample_size_3}) 95% CI: [{ci_3[0]:.2f},
{ci_3[1]:.2f}] ms\n")


# ================================
# PART 3: Visualization Techniques
# ================================

# Create a subset of 200 for the population visualization
population_subset = np.random.choice(population, 200, replace=False)


# Boxplot comparing population subset against all drawn samples
plt.figure(figsize=(10, 6))
plt.boxplot(
    [population_subset, sample_1, sample_2, sample_3],
    tick_labels=['Pop (Subset 200)', 'Sample (n=30)', 'Sample (n=50)',
'Sample (n=100)'],
    patch_artist=True,
    boxprops=dict(facecolor='lightblue')
)
plt.title("Population vs Sample Variability Across Sample Sizes (30, 50,
100)")
plt.ylabel("Latency (ms)")
plt.grid(axis='y', alpha=0.3)
plt.tight_layout()
plt.show()
```

```
=== Part 1: Statistical Inference and Sampling ===
Population Mean (True): 99.97 ms

Sample Size 30 Mean: 101.10 ms
Sample Size 50 Mean: 98.88 ms
Sample Size 100 Mean: 100.18 ms

=== Part 2: Confidence Intervals ===
Sample (n=30) 95% CI: [95.12, 107.08] ms
Sample (n=50) 95% CI: [94.96, 102.81] ms
Sample (n=100) 95% CI: [97.46, 102.90] ms
```





QUESTION: How did the sample size affect the accuracy of the sample mean compared to the population mean?

The sample size affects the accuracy of the sample because larger samples reduce the impact of random noise and outliers, causing the sample average to converge closely on the true population mean.

Uncertainty in Predictive Models

Predictive analytics uses past data to create models that forecast future outcomes. These models are widely applied in engineering and business, such as predicting network latency, product sales, or travel times. However, predictions are never exact, and uncertainty must be considered. Visualization of this uncertainty helps engineers and decision-makers understand the reliability of forecasts, improving real-world decision-making.

Predictive Models and Point Estimates
- Predictive models generate point estimates, which are single predicted values for future observations.
- These estimates contain error because real-world systems involve randomness and variability.

Prediction Intervals
- A prediction interval gives a range where future outcomes are likely to occur with a certain confidence level (e.g., 95%).
- Similar to confidence intervals used in statistical inference, but focused on predicting individual future observations rather than population parameters.

Simple Linear Regression Example
- Linear regression models relationships between two variables:
- Independent variable (x): factor used for prediction (e.g., number of requests in a delivery route).
- Dependent variable (y): outcome being predicted (e.g., travel time).
- Visualization includes:
- Historical data points.
- Regression line showing predicted values.
- Upper and lower dashed lines showing prediction interval boundaries.
- Key observation: intervals are narrower near the average values of the independent variable and wider at extremes, indicating higher uncertainty for unusual cases.

Time Series Models Example
- Used for data measured sequentially over time (e.g., quarterly sales).
- Predictions account for patterns like seasonality or trends.
- Visualization shows:
- Past data as a continuous line.
- Future point predictions as a lighter line.
- Prediction intervals widening as the forecast extends further into the future.
- Important insight: uncertainty grows over time because long-term predictions are inherently less reliable.

In [ ]:

```
# ============================================
# Uncertainty in Predictive Models
# ============================================
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import statsmodels.api as sm
from sklearn.linear_model import LinearRegression

# ============================================
# PART 1: Predictive Models and Point Estimates
# ============================================
print("=== Part 1: Predictive Models and Point Estimates ===")

# Generate random data: relationship between requests and travel time
num_requests = np.random.randint(1, 10, size=10)  # independent variable
(random integers 1–9)
travel_time = np.random.normal(loc=3, scale=0.5, size=10)  # dependent
variable with random noise

# Fit a simple linear regression model
X = num_requests.reshape(-1, 1)
y = travel_time
model = LinearRegression().fit(X, y)

# Predict point estimates
predictions = model.predict(X)

print("Regression Model Summary:")
print(f"Intercept: {model.intercept_:.3f}, Slope:
{model.coef_[0]:.3f}\n")

print("Sample of Predictions:")
for i, p in zip(num_requests, predictions):
    print(f"Requests: {i}, Predicted Travel Time: {p:.2f} hours")

# ============================================
# PART 2: Prediction Intervals
# ============================================
print("\n=== Part 2: Prediction Intervals ===")

# Use statsmodels to compute prediction intervals
X_with_const = sm.add_constant(X)  # statsmodels requires intercept
column
ols_model = sm.OLS(y, X_with_const).fit()

# Generate prediction intervals
pred_summary =
ols_model.get_prediction(X_with_const).summary_frame(alpha=0.05)  # 95%
PI
lower_bounds = pred_summary["obs_ci_lower"]
upper_bounds = pred_summary["obs_ci_upper"]
```

```
# Display prediction intervals
print(pred_summary[["mean", "obs_ci_lower", "obs_ci_upper"]])

# ================================================
# PART 3: Visualization for Linear Regression
# ================================================
print("\n=== Part 3: Visualization for Linear Regression ===")

# Sort data for a cleaner plot
sorted_indices = np.argsort(num_requests)
sorted_requests = num_requests[sorted_indices]
sorted_predictions = predictions[sorted_indices]
sorted_lower = lower_bounds[sorted_indices]
sorted_upper = upper_bounds[sorted_indices]
sorted_actual = travel_time[sorted_indices]

plt.figure(figsize=(8, 6))
plt.scatter(sorted_requests, sorted_actual, color='blue',
label='Observed Data')
plt.plot(sorted_requests, sorted_predictions, color='orange',
label='Regression Line')
plt.fill_between(sorted_requests, sorted_lower, sorted_upper,
                 color='orange', alpha=0.3, label='95% Prediction
Interval')
plt.xlabel("Number of Requests")
plt.ylabel("Travel Time (hours)")
plt.title("Linear Regression with Prediction Intervals")
plt.legend()
plt.show()

# ================================================
# PART 4: Time Series Forecasting with Prediction Intervals
# ================================================
print("\n=== Part 4: Time Series Forecasting ===")

# Generate random time series data for quarterly sales
time_periods = 17
quarters = np.arange(1, time_periods + 1)
sales = np.random.normal(loc=150, scale=20, size=time_periods)  # random
sales data

# Create dataframe
df_sales = pd.DataFrame({"Quarter": quarters, "Sales": sales})

# Simulate future predictions
future_periods = 8
future_quarters = np.arange(time_periods + 1, time_periods +
future_periods + 1)

# Random predictions with added seasonality-like variation
future_sales_pred = np.random.normal(loc=150, scale=15,
```

```
size=future_periods)

# Add growing uncertainty to future predictions
future_uncertainty = np.linspace(10, 30, future_periods)
lower_future = future_sales_pred - future_uncertainty
upper_future = future_sales_pred + future_uncertainty

# Combine into dataframe
forecast_df = pd.DataFrame({
    "Quarter": future_quarters,
    "Predicted_Sales": future_sales_pred,
    "Lower_PI": lower_future,
    "Upper_PI": upper_future
})

# ================================================
# Visualization for Time Series
# ================================================
plt.figure(figsize=(10, 6))
plt.plot(df_sales["Quarter"], df_sales["Sales"], color='darkblue',
label='Historical Sales')
plt.plot(forecast_df["Quarter"], forecast_df["Predicted_Sales"],
color='lightblue', label='Forecast')
plt.fill_between(forecast_df["Quarter"], forecast_df["Lower_PI"],
forecast_df["Upper_PI"],
                 color='lightblue', alpha=0.3, label='95% Prediction
Interval')
plt.xlabel("Quarter")
plt.ylabel("Sales ($1000s)")
plt.title("Time Series Forecast with Prediction Intervals")
plt.legend()
plt.show()
```


```
=== Part 1: Predictive Models and Point Estimates ===
Regression Model Summary:
Intercept: 2.989, Slope: 0.034

Sample of Predictions:
Requests: 1, Predicted Travel Time: 3.02 hours
Requests: 8, Predicted Travel Time: 3.26 hours
Requests: 2, Predicted Travel Time: 3.06 hours
Requests: 8, Predicted Travel Time: 3.26 hours
Requests: 7, Predicted Travel Time: 3.23 hours
Requests: 2, Predicted Travel Time: 3.06 hours
Requests: 6, Predicted Travel Time: 3.19 hours
Requests: 6, Predicted Travel Time: 3.19 hours
Requests: 3, Predicted Travel Time: 3.09 hours
Requests: 2, Predicted Travel Time: 3.06 hours


=== Part 2: Prediction Intervals ===
       mean  obs_ci_lower  obs_ci_upper
0  3.022463      1.918040      4.126885
```

```
1  3.259269      2.154847      4.363692
2  3.056292      1.990363      4.122221
3  3.259269      2.154847      4.363692
4  3.225440      2.159511      4.291369
5  3.056292      1.990363      4.122221
6  3.191610      2.152135      4.231085
7  3.191610      2.152135      4.231085
8  3.090122      2.050647      4.129597
9  3.056292      1.990363      4.122221

=== Part 3: Visualization for Linear Regression ===
```




```
=== Part 4: Time Series Forecasting ===
```





Task 4: Uncertainty in Predictive Models

Modify the provided code to explore how uncertainty changes under different scenarios. Complete the following steps:

Part 1: Predictive Models and Point Estimates
- Increase the sample size of the random data by generating 30 data points instead of 10.
- Observe how the regression model changes with more data.

Part 2: Prediction Intervals
- Change the confidence level from 95% to 80% when generating prediction intervals.
- Compare how the width of the intervals changes.

Part 3: Visualization
- Change the scatter plot color for observed data to green.
- Increase the transparency (alpha) of the shaded prediction interval region to 0.5 for better visibility.
- Modify the plot title to: "Effect of Sample Size and Confidence Level on Prediction Intervals".

In [35]:

```
# ================================================
# Uncertainty in Predictive Models
# ================================================
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import statsmodels.api as sm
from sklearn.linear_model import LinearRegression

# Set random seed for consistent results
np.random.seed(42)

# ================================================
# PART 1: Predictive Models and Point Estimates
# ================================================
print("=== Part 1: Predictive Models and Point Estimates ===")

# Increased sample size from 10 to 30 data points
num_requests = np.random.randint(1, 10, size=30)  # independent variable
travel_time = np.random.normal(loc=3, scale=0.5, size=30)  # dependent
variable

# Fit a simple linear regression model
X = num_requests.reshape(-1, 1)
y = travel_time
model = LinearRegression().fit(X, y)

# Predict point estimates
predictions = model.predict(X)

print("Regression Model Summary (n=30):")
print(f"Intercept: {model.intercept_:.3f}, Slope:
{model.coef_[0]:.3f}\n")

print("Sample of Predictions (First 5):")
for i, p in zip(num_requests[:5], predictions[:5]):
    print(f"Requests: {i}, Predicted Travel Time: {p:.2f} hours")

# ================================================
# PART 2: Prediction Intervals
# ================================================
print("\n=== Part 2: Prediction Intervals ===")

# Use statsmodels to compute prediction intervals
X_with_const = sm.add_constant(X)
ols_model = sm.OLS(y, X_with_const).fit()

# Changed alpha to 0.20 to calculate an 80% Prediction Interval (1 -
0.20 = 0.80)
pred_summary =
ols_model.get_prediction(X_with_const).summary_frame(alpha=0.20)
lower_bounds = pred_summary["obs_ci_lower"]
```

```
upper_bounds = pred_summary["obs_ci_upper"]

print("80% Prediction Interval Summary (First 5 rows):")
print(pred_summary[["mean", "obs_ci_lower", "obs_ci_upper"]].head())

# ================================================
# PART 3: Visualization for Linear Regression
# ================================================
print("\n=== Part 3: Visualization for Linear Regression ===")

# Sort data for a cleaner plot
sorted_indices = np.argsort(num_requests)
sorted_requests = num_requests[sorted_indices]
sorted_predictions = predictions[sorted_indices]
sorted_lower = lower_bounds[sorted_indices]
sorted_upper = upper_bounds[sorted_indices]
sorted_actual = travel_time[sorted_indices]

plt.figure(figsize=(8, 6))

# Changed scatter plot color to green
plt.scatter(sorted_requests, sorted_actual, color='green',
label='Observed Data')

# Regression line
plt.plot(sorted_requests, sorted_predictions, color='orange',
label='Regression Line')

# Increased alpha transparency to 0.5 for the shaded prediction interval
plt.fill_between(sorted_requests, sorted_lower, sorted_upper,
                 color='orange', alpha=0.5, label='80% Prediction
Interval')

plt.xlabel("Number of Requests")
plt.ylabel("Travel Time (hours)")

# Updated Title
plt.title("Effect of Sample Size and Confidence Level on Prediction
Intervals")
plt.legend()
plt.tight_layout()
plt.show()

# ================================================
# PART 4: Time Series Forecasting with Prediction Intervals
# ================================================
print("\n=== Part 4: Time Series Forecasting ===")

# Generate random time series data for quarterly sales
time_periods = 17
quarters = np.arange(1, time_periods + 1)
sales = np.random.normal(loc=150, scale=20, size=time_periods)
```

```
df_sales = pd.DataFrame({"Quarter": quarters, "Sales": sales})

future_periods = 8
future_quarters = np.arange(time_periods + 1, time_periods +
future_periods + 1)
future_sales_pred = np.random.normal(loc=150, scale=15,
size=future_periods)

future_uncertainty = np.linspace(10, 30, future_periods)
lower_future = future_sales_pred - future_uncertainty
upper_future = future_sales_pred + future_uncertainty

forecast_df = pd.DataFrame({
    "Quarter": future_quarters,
    "Predicted_Sales": future_sales_pred,
    "Lower_PI": lower_future,
    "Upper_PI": upper_future
})

plt.figure(figsize=(10, 6))
plt.plot(df_sales["Quarter"], df_sales["Sales"], color='darkblue',
label='Historical Sales')
plt.plot(forecast_df["Quarter"], forecast_df["Predicted_Sales"],
color='lightblue', label='Forecast')
plt.fill_between(forecast_df["Quarter"], forecast_df["Lower_PI"],
forecast_df["Upper_PI"],
                 color='lightblue', alpha=0.3, label='95% Prediction
Interval')
plt.xlabel("Quarter")
plt.ylabel("Sales ($1000s)")
plt.title("Time Series Forecast with Prediction Intervals")
plt.legend()
plt.tight_layout()
plt.show()
```


```
=== Part 1: Predictive Models and Point Estimates ===
Regression Model Summary (n=30):
Intercept: 2.874, Slope: 0.007

Sample of Predictions (First 5):
Requests: 7, Predicted Travel Time: 2.92 hours
Requests: 4, Predicted Travel Time: 2.90 hours
Requests: 8, Predicted Travel Time: 2.93 hours
Requests: 5, Predicted Travel Time: 2.91 hours
Requests: 7, Predicted Travel Time: 2.92 hours


=== Part 2: Prediction Intervals ===
80% Prediction Interval Summary (First 5 rows):
       mean  obs_ci_lower  obs_ci_upper
0  2.920063      2.289262      3.550865
1  2.900514      2.271935      3.529093
```

```
2  2.926580      2.287695      3.565464
3  2.907030      2.281427      3.532634
4  2.920063      2.289262      3.550865

=== Part 3: Visualization for Linear Regression ===
```




```
=== Part 4: Time Series Forecasting ===
```



---

5. Supplementary Activity:

Demonstrate the key steps for building, analyzing, and visualizing data distributions.

1. Create a synthetic dataset
- Generate one dataset of 200 random ages between 15 and 70. This dataset will be used throughout all steps.

2. Core Concepts: Frequency and Relative Frequency
- Build a frequency table showing:
- Age ranges divided into bins of 10 years (15-24, 25-34, etc.).
- The frequency and relative frequency of each bin.
- *Reference the frequency table example shown in earlier parts.*

3. Visualization Techniques
- Create a histogram to display the age distribution.
- Overlay a frequency polygon on the same plot.
- *Refer to the visualization section in Part 2 of earlier codes.*

4. Statistical Measures
- Compute and print:
- Mean, Median, Mode.
- Range, Standard Deviation, and Interquartile Range (IQR).
- *Use the approach shown in the Measures of Central Tendency and Variability example.*

5. Box Plot and Histogram Comparison
- Create a box-and-whisker plot to visualize spread and detect outliers.
- Create a separate histogram for frequency distribution.
- *See Part 2 of the Statistical Analysis example for reference.*

6. Prediction and Uncertainty Visualization
- Using the same dataset, simulate a simple linear regression where:
- x is a random subset of 10 values from ages.
- y is a random dependent variable with noise.
- Fit the regression and plot:
- Observed data.
- Regression line.
- 95% prediction intervals shaded on the plot.
- *Reference the Predictive Models example from earlier codes.*

In [37]:

```
# ======================================================
# Supplementary Activity: Exploring Data Visualization
# ======================================================

import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import statsmodels.api as sm
from scipy import stats
from sklearn.linear_model import LinearRegression

# Set random seed for reproducible results
np.random.seed(42)

# ======================================================
# Step 1: Create synthetic dataset
# ======================================================
# Generate a dataset of 200 random ages between 15 and 70
ages = np.random.randint(15, 70, 200)

# ======================================================
# Step 2: Frequency and Relative Frequency Table
# ======================================================

# Define bin ranges for age groups
bins_1 = [15, 25, 35, 45, 55, 65, 75]
bins_2 = [5, 10, 15, 20, 25]

# Calculate frequency and relative frequency using bins_1
frequency_short, bin_edges_short = np.histogram(ages, bins=bins_1)
relative_frequency_short = frequency_short / len(ages)

# Create a DataFrame for the frequency table
distribution_df_short = pd.DataFrame({
    "Age Range": [f"{bins_1[i]}-{bins_1[i+1]-1}" for i in
range(len(bins_1)-1)],
    "Frequency": frequency_short,
    "Relative Frequency": relative_frequency_short.round(3)
})

# Print frequency table
print("=== Part 1: Core Concepts ===")
print("Frequency and Relative Frequency Table (Bins_1):")
print(distribution_df_short)

# ======================================================
# Step 3: Visualization Techniques
# ======================================================

# Calculate midpoints for frequency polygon
midpoints = 0.5 * (bin_edges_short[1:] + bin_edges_short[:-1])
```

```
plt.figure(figsize=(10, 5))

# Create histogram of ages
plt.hist(ages, bins=bins_1, color='skyblue', edgecolor='black',
alpha=0.7, label='Histogram')

# Overlay frequency polygon on top of histogram
plt.plot(midpoints, frequency_short, color='red', marker='o',
linewidth=2, label='Frequency Polygon')

plt.title("Age Distribution with Frequency Polygon")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins_1)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.tight_layout()
plt.show()


# ======================================================
# Step 4: Statistical Measures
# ======================================================

# Calculate mean, median, and mode
mean_age = np.mean(ages)
median_age = np.median(ages)
mode_age = pd.Series(ages).mode()[0]

# Calculate range, standard deviation, and IQR
range_age = np.max(ages) - np.min(ages)
std_dev_age = np.std(ages)
q1 = np.percentile(ages, 25)
q3 = np.percentile(ages, 75)
iqr = q3 - q1

# Print results with interpretations
print("\n=== Statistical Measures ===")
print(f"Mean Age: {mean_age:.2f}")
print(f"Median Age: {median_age:.2f}")
print(f"Mode Age: {mode_age}")
print(f"Range: {range_age}")
print(f"Standard Deviation: {std_dev_age:.2f}")
print(f"Interquartile Range (IQR): {iqr:.2f}")


# ======================================================
# Step 5: Box Plot and Histogram
# ======================================================

plt.figure(figsize=(12, 5))
```

```
# Create box plot of ages
plt.subplot(1, 2, 1)
plt.boxplot(ages, vert=True, patch_artist=True,
boxprops=dict(facecolor='lightblue'))
plt.title("Box Plot of Ages")
plt.ylabel("Age")

# Create histogram of ages (separate subplot)
plt.subplot(1, 2, 2)
plt.hist(ages, bins=10, color='skyblue', edgecolor='black')
plt.title("Histogram of Ages (10 Bins)")
plt.xlabel("Age")
plt.ylabel("Frequency")

plt.tight_layout()
plt.show()


# ======================================================
# Step 6: Prediction and Uncertainty Visualization
# ======================================================

# Randomly select 10 age values as x
x = np.random.choice(ages, 10, replace=False)

# Create y values with random noise
y = 0.5 * x + np.random.normal(loc=5, scale=3, size=10)

# Fit linear regression model
X = x.reshape(-1, 1)
model = LinearRegression().fit(X, y)

# Generate predictions
predictions = model.predict(X)

# Prepare data for statsmodels
X_with_const = sm.add_constant(X)

# Fit OLS model
ols_model = sm.OLS(y, X_with_const).fit()

# Get prediction summary with intervals (95% PI)
pred_summary =
ols_model.get_prediction(X_with_const).summary_frame(alpha=0.05)

# Extract lower and upper bounds
lower_bounds = pred_summary["obs_ci_lower"]
upper_bounds = pred_summary["obs_ci_upper"]

# Sort values for a smooth visualization line
sort_idx = np.argsort(x)
x_sorted = x[sort_idx]
```

```
pred_sorted = predictions[sort_idx]
lower_sorted = lower_bounds.iloc[sort_idx]
upper_sorted = upper_bounds.iloc[sort_idx]

# Visualization
plt.figure(figsize=(8, 6))

# Scatter plot of observed data
plt.scatter(x, y, color='blue', label='Observed Data')

# Plot regression line
plt.plot(x_sorted, pred_sorted, color='orange', label='Regression Line')

# Shade prediction interval region
plt.fill_between(x_sorted, lower_sorted, upper_sorted, color='orange',
alpha=0.3, label='95% Prediction Interval')

plt.xlabel("Number of Requests (simulated x)")
plt.ylabel("Simulated Outcome (y)")
plt.title("Linear Regression with Prediction Intervals")
plt.legend()
plt.grid(alpha=0.3)
plt.tight_layout()
plt.show()


# ======================================================
# Step 7: Interpretation and Reflection
# ======================================================

# Identify most common age range
max_freq_index = np.argmax(frequency_short)
most_common_range = distribution_df_short.iloc[max_freq_index]["Age
Range"]


print("\n=== Part 7: Interpretation and Reflection ===")
print(f"- The most common age range is {most_common_range}.")

# Determine skewness based on Mean vs. Median comparison
if mean_age > median_age + 1:
    print("- The distribution is RIGHT-SKEWED.")
elif mean_age < median_age - 1:
    print("- The distribution is LEFT-SKEWED.")
else:
    print("- The distribution is approximately SYMMETRIC.")


# Reflection prompt outputs
print("\nReflection Responses:")
print("1. How does the histogram compare to the box plot in showing
variability?")
print("The histogram shows detailed shape, bin frequencies, and modes,
while the box plot summarizes spread, median, quartiles, and outliers
```


```
each.")
print("2. What does the width of the prediction interval tell us about
uncertainty?")
print("A wider interval indicates higher variance and uncertainty in
individual predictions. However a narrower band signifies greater model
precision.")
print("3. How would you use this information in a real-world decision-
making process?")
print("Prediction intervals allow the decision-makers to assess best-
case and worst-case scenarios rather than relying on a single point
estimate only.")
```


```
=== Part 1: Core Concepts ===
Frequency and Relative Frequency Table (Bins_1):
  Age Range  Frequency  Relative Frequency
0     15-24         37               0.185
1     25-34         31               0.155
2     35-44         44               0.220
3     45-54         35               0.175
4     55-64         34               0.170
5     65-74         19               0.095
```




```
=== Statistical Measures ===
Mean Age: 41.88
Median Age: 42.00
Mode Age: 58
Range: 54
Standard Deviation: 15.77
Interquartile Range (IQR): 28.00
```








```
=== Part 7: Interpretation and Reflection ===
- The most common age range is 35-44.
- The distribution is approximately SYMMETRIC.

Reflection Responses:
1. How does the histogram compare to the box plot in showing
variability?
The histogram shows detailed shape, bin frequencies, and modes,
while the box plot summarizes spread, median, quartiles, and
outliers each.
2. What does the width of the prediction interval tell us about
uncertainty?
A wider interval indicates higher variance and uncertainty in
individual predictions. However a narrower band signifies greater
model precision.
3. How would you use this information in a real-world decision-
making process?
Prediction intervals allow the decision-makers to assess best-case
and worst-case scenarios rather than relying on a single point
estimate only.
```

6. Conclusion/Learnings/Analysis:

Using this activity, I've learned how to demonstrate that simply presenting data is not always sufficient in any case to be able to allow the users or the viewers to comprehend the data easier, so that we must combine statistical analysis, and other multi-method visualizations like histograms, frequency polygons, and the skewness of the histograms in order to transform messy data into reliable, and concrete or coherent data, and be able to present it to the viewers.

Exported with runcell — convert notebooks to HTML or PDF anytime at runcell.dev.