

What new will bring us Java 9?

Dominik Przybysz



@alien11689



<http://przybyszd.blogspot.com>



<https://github.com/alien11689>



Short history of Java part 1

1995 - JDK Alpha and Beta

1996/01 - JDK 1.0 - *Oak*

1997/02 - JDK 1.1 (RMI, JDBC, JIT)

1998/12 - J2SE 1.2

1999/12 - J2EE 1.2

2000/05 - J2SE 1.3

2001/09 - J2EE 1.3



Short history of Java part 2

2002/02 - J2SE 1.4

2003/11 - J2EE 1.4

2004/09 - J2SE 1.5

2006/05 - Java EE 5

2006/12 - Java SE 6

2009/04 - Oracle buys Sun

2009/12 - Java EE 6



Short history of Java part 3

2011/07 - Java SE 7

2013/06 - Java EE 7

2014/03 - Java SE 8

2016/09 - Java SE 9 / Java EE 8

2018 - Java 10



Java 9

2015/12/10 - Feature Complete

2016/02/04 - All Tests Run

2016/02/25 - Rampdown Start

2016/04/21 - Zero Bug Bounce

2016/06/16 - Rampdown Phase 2

2016/07/21 - Final Release Candidate

2016/09/22 - General Availability



Modularization



Modularization

- improvements to performance
- improvements to security
- reduce system complexity
- fix classpath/jar hell




Compact profiles (Java 8)

- compiled for embedded systems
- compact1 - 14 MB
- compact2 - 18 MB
- compact3 - 21 MB
- Full - 45 MB



Project Jigsaw

- JEP 200: The Modular JDK
- JEP 201: Modular Source Code
- JEP 220: Modular Run-Time Images
- JSR 376: Java Platform Module System



What will change?

- no sun.* and *.internal.* packages
- no rt.jar
- improve SecurityManager.checkPackageAccess
- new linker - jlink
- no endorsed lib
- no extension mechanism
- no jre - building images



No sun.misc.Unsafe!
(maybe...)



sun.misc.Unsafe

Do we need to get rid of Unsafe, Yes! Do we need to keep Unsafe? Yes. How do we reconcile these seemingly conflicting positions? Well, we need to plan a migration path to move the stuff that we now know how it should be implemented out of Unsafe and into the JDK proper.

<https://jaxenter.com/java-9-without-sun-misc-unsafe-119026.html>



JEP 260: Encapsulate Most Internal APIs

Critical internal APIs for which replacements are introduced in JDK 9 will be deprecated in JDK 9 and either encapsulated or removed in JDK 10.

<http://openjdk.java.net/jeps/260>



New URL schema

`ClassLoader.getResource(String name)`

old url → *jar:file:<path-to-jar>!<path-to-file-in-jar>*

new url → *jrt:/<module-name>/<path-to-file-in-module>*




Problems?

	rt	com.oracle.*	com.sun.*	java.*	javax.*	org.ietf.jgss	org.jcp.xml.dsig.internal.*	org.omg.*	org.w3c.dom.*	org.xml.sax.*	sun.*	sunw.*
rt												
com.oracle.*												
com.sun.*												
java.*												
javax.*												
org.ietf.jgss												
org.jcp.xml.dsig.internal.*												
org.omg.*												
org.w3c.dom.*												
org.xml.sax.*												
sun.*												
sunw.*												
jfr												
jce												
jsse												

	rt	com.oracle.*	com.sun.*	java.*	javax.*	org.ietf.jgss	org.jcp.xml.dsig.internal.*	org.omg.*	org.w3c.dom.*	org.xml.sax.*	sun.*	sunw.*
rt												
com.oracle.*												
com.sun.*												
java.*												
javax.*												
org.ietf.jgss												
org.jcp.xml.dsig.internal.*												
org.omg.*												
org.w3c.dom.*												
org.xml.sax.*												
sun.*												
sunw.*												
jfr												
jce												
jsse												

Modules



modules.xml

```
<modules>
  <module>
    <name>java.activation</name>
    <depend>java.base</depend>
    <depend re-exports="true">java.datatransfer</depend>
    <depend>java.desktop</depend>
    <depend>java.logging</depend>
    <export>
      <name>javax.activation</name>
    </export>
  </module>
  ...
```



jdeps (java 8) - part 1

```
$ jdeps -cp ... \  
pl/touk/mockserver/server/HttpMockServer.class  
HttpMockServer.class -> .../groovy-all-2.4.3.jar  
HttpMockServer.class -> java.base  
HttpMockServer.class -> jdk.httpserver  
HttpMockServer.class -> .../slf4j-api-1.7.9.jar  
...
```



jdeps (java 8) - part 2

```
pl.touk.mockserver.server (HttpMockServer.class)
```

```
-> com.sun.net.httpserver
```

```
-> groovy.lang groovy-all-2.4.3.jar
```

```
-> groovy.util.slurpersupport groovy-all-2.4.3.jar
```

```
-> groovy.xml groovy-all-2.4.3.jar
```

```
-> java.io
```

```
-> java.lang
```

```
-> java.lang.ref
```

```
-> java.util
```

```
-> java.util.concurrent
```

...



Example: Tree

src/dpr.api/com/dpr/api/Hello.java

src/dpr.api/module-info.java

src/dpr.impl/com/dpr/impl/Hello.java

src/dpr.impl/module-info.java

src/dpr.runner/com/dpr/runner/Main.java

src/dpr.runner/module-info.java



dpr.api

```
module dpr.api {  
    requires java.base;  
    exports com.dpr.api;  
}
```



dpr.impl

```
module dpr.impl {  
    requires dpr.api;  
    provides com.dpr.api.IHello  
        with com.dpr.impl.Hello;  
}
```



dpr.runner

```
module dpr.runner {  
    requires dpr.api;  
    uses com.dpr.api.IHello;  
}
```



Compilation

```
$ javac \  
    -d modules  
    -modulesourcepath src  
    `find src -name '*.java'`
```



jmod

- like **jar** command
- creating modules
- printing modules descriptors
- listing modules content



jmod example

```
$ jmod -c --module-version=1.0.0 \  
    --class-path modules/dpr.api/ \  
modules/dpr.api.jmod
```



jdeps (java 9) - part 1

```
$ ./bin/jdeps -genmoduleinfo . \  
~/.
```

```
m2/repository/pl/touk/mockserver/mockserver/  
2.1.1/mockserver-2.1.1.jar
```



jdeps (java 9) - part 2

```
$ cat mockserver/module-info.java
```

```
module mockserver {  
  
    requires java.xml;  
  
    requires java.xml.bind;  
  
    requires public jdk.httpserver;  
  
    requires public NOT_FOUND;  
  
    exports pl.touk.mockserver.server;  
  
}
```



OSGi?

- execution environment
- module
- life-cycle
- service registry



com.dpr.api bundle

Manifest-Version: 1.0

Bundle-ManifestVersion: 2

Bundle-Name: DPR API

Bundle-SymbolicName: com.dpr.api

Bundle-Version: 1.0.0

Exports: com.dpr.api;version=1.0.0



com.dpr.impl bundle

Manifest-Version: 1.0

Bundle-ManifestVersion: 2

Bundle-Name: DPR IMPL

Bundle-SymbolicName: com.dpr.impl

Bundle-Version: 1.0.1

Imports: com.dpr.api;version=[1.0,2)

Bundle-RequiredExecutionEnvironment: JavaSE-
1.8



com.dpr.runner bundle

Manifest-Version: 1.0

Bundle-ManifestVersion: 2

Bundle-Name: DPR RUNNER

Bundle-SymbolicName: com.dpr.runner


Bundle-Version: 1.0.0

Bundle-Activator: com.dpr.runner.Main

Imports: com.dpr.api;version=1.0.0



OSGI vs Jigsaw



We are still waiting...

“A shorter release cycle would be great.

And for Jigsaw, just drop the idea, you are really loosing your time. OSGI is good enough, it's already working, and it's working well.”


<http://mreinhold.org/blog/late-for-the-train>



Money and Currency API

1.2626		EURO	1.0395
1.6888		USA	1.3947
12.7315		SOUTH AFRICA	9.9772
13.2175		HONG KONG	10.7869
162.29		JAPAN	130.37
1.8646		AUSTRALIA	1.5058
1.7278		CANADA	1.3924
1.8228		NEW ZEALAND	1.3924

Money and Currency API



Money and Currency API

Advice from Effective Java:

- do not use:
 - float
 - double
- use:
 - BigDecimal
 - Integer (int)
 - Long (long)



Money today

```
public class Money {  
    private String currency;  
    private BigDecimal amount;  
    // ...  
}
```



What for will it be?

- currency for each country
- exchange rate
- find rates
- standard ISO 4217

ISO 4217

```
<CcyNtry>  
  <CtryNm>POLAND</CtryNm>  
  <CcyNm>Zloty</CcyNm>  
  <Ccy>PLN</Ccy>  
  <CcyNbr>985</CcyNbr>  
  <CcyMnrUnits>2</CcyMnrUnits>  
</CcyNtry>
```



JSR 354 & Reference implementation

```
<dependency>  
  <groupId>org.javamoney</groupId>  
  <artifactId>moneta</artifactId>  
  <version>1.0</version>  
</dependency>
```

<http://javamoney.github.io/ri.html>



CurrencyUnit

```
CurrencyUnit pln =  
    Monetary.getCurrency("PLN");
```

```
CurrencyUnit usd =  
    Monetary.getCurrency(Locale.US);
```



Creating Money

```
MonetaryAmount normal = Money.of(new  
    BigDecimal("1.5"), usd);
```

```
MonetaryAmount fast = FastMoney.of(new  
    BigDecimal("1.5"), usd);
```

```
assertEquals("USD 1.5", normal.toString());  
assertEquals("USD 1.50000",  
    fast.toString());
```



Formatting Money

```
MonetaryAmountFormat format =  
    MonetaryFormats.getAmountFormat(new  
        Locale("pl_PL")) ;  
  
assertEquals("USD 1.50",  
    format.format(money)) ;
```



Money operations

```
MonetaryAmount m1 = Money.of(1, usd);
```

```
MonetaryAmount m2 = Money.of(2, usd);
```

```
MonetaryAmount m3 = Money.of(3, usd);
```

```
assertEquals(m3, m1.add(m2));
```

```
assertEquals(m2, m1.multiply(2));
```

```
assertTrue(m1.isLessThan(m2));
```



Money functions

```
Arrays.asList(m1, m2, m3)
    .stream()
    .filter(MonetaryFunctions
        .isCurrency(usd))
    .reduce(MonetaryFunctions.sum()) );
```



ExchangeRate

```
ExchangeRateProvider ecbRateProvider =  
    MonetaryConversions.getExchangeRateProvider(  
        "ECB");  
  
ExchangeRate exchangeRate =  
    ecbRateProvider.getExchangeRate(  
        "PLN", "USD");  
  
NumberValue factor = exchangeRate.getFactor();  
// 0.27369381044951642996
```



CurrencyConversion

```
CurrencyConversion currencyConversion =  
    ecbRateProvider.getCurrencyConversion(usd);  
Money m = Money.of(5, pln)  
    .with(currencyConversion);  
  
// Money.of(new  
    BigDecimal("1.3684690522475821498"), usd)
```



Rounding

```
MonetaryRounding rounding = Monetary  
    .getRounding(RoundingQueryBuilder.of()  
        .setCurrency(usd).build());
```

```
assertEquals(Money.of(  
    new BigDecimal("1.37"), usd),  
    rounding.apply(Money.of(  
        new BigDecimal("1.3684690522475821498"),  
        usd)));
```



JSON API



JSON API

- Parsing and generation of JSON without external libraries like Jackson.
- Navigation over JSON tree like in DOM or SAX for XML.
- Builder API for JSON.
- JSON tree transformation.



Road to JSON support

- JSR 353: Java API for JSON Processing - Java EE 7
- Nashorn in Java 8 - `JSON.parse()` and `JSON.stringify()`
- JEP 198: Light-Weight JSON API - Java 9



Nashorn

```
ScriptEngineManager m =  
    new ScriptEngineManager();  
ScriptEngine e =  
    m.getEngineByName("nashorn");  
try {  
    e.eval("print('Hello World!');");  
} catch (ScriptException se) {  
    // ...  
}
```



Nashorn

```
jjs> var me = JSON.parse('{ "name": "John",  
    "details": { "dob": "1976-05-21", "gender": "  
    Male" } }');
```

```
jjs> print(me.name);
```

John

```
jjs> print(JSON.stringify(me));  
    { "name": "John",  
      "details": { "dob": "1976-05-21",  
        "gender": "Male" } }
```



Nashorn

```
ScriptObjectMirror o =  
    (ScriptObjectMirror) e.eval(  
        "JSON.parse ( ' { \"name\" : \"John\" } ' ) ;"  
    ) ;  
  
assertEquals ( "John", o.getMember ( "name" ) ) ;
```



Producing JSON

```
@GET
@Path("/{name}")
@Produces(MediaType.APPLICATION_JSON)
public Project get(@PathParam("name") String
name) {
    return projects.get(name);
}
```



Consuming JSON

```
@POST
```

```
@Consumes (MediaType.APPLICATION_JSON)
```

```
public void create (Project p) {  
    projects.put (p.getName (), p);  
}
```



HTTP2 client



Old HTTP client

- URLConnection class does not implement the AutoCloseable interface
- Blocking API
- Only support HTTP 1.0



HTTP2 client

JEP 110 will define and implement a new HTTP client for Java that will replace HttpURLConnection and also implement HTTP 2.0 and websockets.



GET

```
HttpResponse response = HttpRequest  
    .create(new URI("http://www.foo.com"))  
    .headers("Foo", "foovalue", "Bar", "barvalue")  
    .GET()  
    .response();  
  
int statusCode = response.statusCode();  
  
String responseBody = response.body(asString());
```



POST

```
HttpResponse response = HttpRequest  
    .create(new URI("http://www.foo.com"))  
    .body(fromString("param1=foo,param2=bar"))  
    .POST()  
    .response();
```



Collections factories



JEP 269: Convenience Factory Methods for Collections

*“Provide **static factory methods** on the **collection interfaces** that will **create compact, unmodifiable collection instances**. Provide static factory methods for creating the **most common concrete collections** classes.”*

<http://openjdk.java.net/jeps/269>



Factories for interfaces

```
List.of(1, 2, 3);
```

```
Set.of("a", "b");
```

```
Map.of(5, "test", 6, "test2")
```

```
Map.fromEntries(  
    entry(5, "test"),  
    entry(6, "test2"));
```



Factories for concrete classes

```
ArrayList.of(1, 2, 3);
```

```
HashSet.of("a", "b");
```

```
HashMap.of(5, "test", 6, "test2")
```

```
HashMap.fromEntries(  
    entry(5, "test"),  
    entry(6, "test2"));
```



Smart Java compilation



Smart Java compilation - phase 1

JEP 139: Enhance javac to Improve Build Speed in Java 8
by:

- javac use all cores
- reuse javac in a server process
- javac build incrementally
- internal wrapper of javac - sjavac



Smart Java compilation - phase 2

JEP 199: Smart Java Compilation, Phase Two in Java 9:

- expose sjavac in the JDK tool chain
- fix stability
- fix portability
- improve the quality of sjavac



Improved contended locking



Improved contended locking

JEP 143: Improve Contended Locking

Improve the overall performance of contended Java object monitors as measured by many tests.

For example volcano29:

- a chat server with huge thread counts and client connections
- trying to access the same resources
- simulate a heavy duty real world application



What will be improved

- Field reordering and cache line alignment
- Speed up PlatformEvent::unpark()
- Fast Java monitor enter operations
- Fast Java monitor exit operations
- Fast Java monitor notify/notifyAll operations



Segmented code cache

Segmented Code Cache

JEP 197: Segmented Code Cache

- divide the code cache into distinct segments
- each segment contains compiled code of a particular type
- to improve performance and enable future extensions.

Example: the method sweeper will work faster because it could skip non-method code



Segmented Code Cache

3 segments:

- code that will stay in the cache forever (JVM internal / non-method code)
- short lifetime (Profiled code, specific to a certain set of conditions)
- potentially long lifetime (Non-profiled code)



Process API Improvements



Process API Improvements

JEP 102: Process API Updates

- get PID of current JVM process or processes created by it
- get and set name of JVM process or processes created by it
- enumerate JVMs processes and processes on system
- working with process tree, e. g. destroy process tree
- working with hundreds of subprocess, e. g. one output stream and error stream for many processes, not one thread per subprocess



REPL



Java REPL - project KULLA

- JEP 222: jshell: The Java Shell (Read-Eval-Print Loop)
- evaluate declarations, statements, and expressions
- `jshell` command line tool



Unified JVM Logging



Unified JVM Logging

- JEP 158: Unified JVM Logging
- only infrastructure for logging
- multiple tags per log e. g. *gc, compiler, etc.*
- standard error levels
- redirecting log to console or file
- dynamic configuration via MBeans or jcmd
- decorators on demand - uptime, tags, level
- multiline print



Compiler Control



Compiler Control

- JEP 165: Compiler Control
- fine-grained and method-context dependent control of the JVM compilers
- change the JVM compiler control options in run time
- no performance degradation
- directives for compilation in file



New Version-String Scheme



JEP 223: New Version-String Scheme

- easier to parse and read versions
- compatible with Semantic Versioning (MAJOR.MINOR.PATCH)
- each version part encode only one information
- simple API for version-string parsing, validation, and comparison



Old versioning

Release type	Existing long	Existing short
Early Access	1.9.0-ea-b19	9-ea
Major	1.9.0-b100	9
Security #1	1.9.0_5-b20	9u5
Security #2	1.9.0_11-b12	9u11
Minor #1	1.9.0_20-b62	9u20
Security #3	1.9.0_25-b15	9u25
Minor #2	1.9.0_40-b45	9u40



Old versioning

Release type	Existing long	Existing short
Early Access	9.0.0-ea+19	9-ea
Major	9.0.0+100	9
Security #1	9.0.1+20	9.0.1
Security #2	9.0.2+12	9.0.2
Minor #1	9.1.2+62	9.1.2
Security #3	9.1.3+15	9.1.3
Minor #2	9.2.4+45	9.2.4



Version API

```
public class Version implements
Comparable<Version>, Serializable {
    public static Version parse(String);
    public static Version current();
    public int major();
    public int minor();
    public int security();
    // ...
}
```



Version API

```
// ...
```

```
public List<Integer> version();
```

```
public Optional<String> pre();
```

```
public Optional<Integer> build();
```

```
public Optional<String> optional();
```

```
public int compareTo(Version o);
```

```
}
```



Remove GC Combinations Deprecated in JDK 8



JEP 214: Remove GC Combinations Deprecated in JDK 8

- flags were deprecated with JEP 173: Retire Some Rarely-Used GC Combinations
- these options add very little value to the users
- these options add extra complexity to the GC code base
- in Java 8 there was a warning
- in Java 9 JVM will not start with such combinations



JEP 214: Remove GC Combinations Deprecated in JDK 8

DefNew + CMS : -XX:-UseParNewGC
-XX:+UseConcMarkSweepGC

ParNew + SerialOld : -XX:+UseParNewGC

ParNew + iCMS : -Xincgc

ParNew + iCMS : -XX:+CMSIncrementalMode
-XX:+UseConcMarkSweepGC



JEP 214: Remove GC Combinations Deprecated in JDK 8

DefNew + iCMS : -XX:+CMSIncrementalMode

-XX:+UseConcMarkSweepGC

-XX:-UseParNewGC

CMS foreground : -XX:+UseCMSCompactAtFullCollection

CMS foreground : -XX:+CMSFullGCsBeforeCompaction

CMS foreground : -XX:+UseCMSCollectionPassing



Default GC



G1 will be default GC

- JEP 248: Make G1 the Default Garbage Collector
- current default GC is Parallel GC
- low-pause
- limiting GC pause



Milling Project Coin



JEP 213: Milling Project Coin

- JSR 334: Small Enhancements to the Java Programming Language in Java 7
- underscore will be not allowed as identifier
- interfaces with private methods
- allow @SafeVargs on private instance methods - nowadays it is allowed only on static and final methods
- final variable could be used in try-with-resources



Try-with-resources in Java 7/8

```
final BufferedReader reader =  
    new BufferedReader(  
        new InputStreamReader(System.in)) ;  
try (BufferedReader r = reader) {  
    // ...  
} catch (IOException ex) {  
    // ...  
}
```



Try-with-resources in Java 9

```
final BufferedReader reader =  
    new BufferedReader(  
        new InputStreamReader(System.in) );  
try (reader) {  
    // ...  
} catch (IOException ex) {  
    // ...  
}
```



Now and future



What we could try now?

- early access Oracle Java 9
- docker compiling the latest OpenJDK 9
- Money API and RI on github
- working jigsaw examples



Java 10

- in 2018
- change typing system
- Project Valhalla
 - value types
 - generics in generated classes names:
 - `ArrayList${T=String}.class`
 - `List<int>`



Summary

Adoption of Java 9 will slow to a crawl due to this, which would effect the entire Java ecosystem. The situation will be analogous to Python 2 and 3.

<https://jaxenter.com/java-9-without-sun-misc-unsafe-119026.html>



Q & A



References

- <http://blog.codefx.org/java/dev/how-java-9-and-project-jigsaw-may-break-your-code/>
- <http://blog.takipi.com/java-9-the-ultimate-feature-list/>
- <http://comments.gmane.org/gmane.comp.java.openjdk.macosx-port.devel/6900>
- <http://docs.oracle.com/javase/8/embedded/develop-apps-platforms/jrecreate.htm#JEMAG270>
- <http://javadepend.files.wordpress.com/2012/10/jigsaw1.png?w=595>
- <http://javamoney.github.io/ri.html>
- <http://jaxenter.com/behind-scenes-java-9-new-features-come-113124.html>
- <http://jaxenter.com/java-9-release-date-announced-116945.html>
- <http://jaxenter.com/json-api-dropped-java-9-113028.html>
- <http://jaxenter.com/new-java-9-features-announced-112654.html>
- <http://mreinhold.org/blog/late-for-the-train>
- <http://openjdk.java.net/jeps/102>
- <http://openjdk.java.net/jeps/110>
- <http://openjdk.java.net/jeps/143>
- <http://openjdk.java.net/jeps/158>
- <http://openjdk.java.net/jeps/165>
- <http://openjdk.java.net/jeps/197>



References

- <http://openjdk.java.net/jeps/199>
- <http://openjdk.java.net/jeps/214>
- <http://openjdk.java.net/jeps/220>
- <http://openjdk.java.net/jeps/222>
- <http://openjdk.java.net/jeps/223>
- <http://openjdk.java.net/jeps/231>
- <http://openjdk.java.net/jeps/260>
- <http://openjdk.java.net/jeps/269>
- <http://openjdk.java.net/projects/jdk9/>
- <http://openjdk.java.net/projects/jigsaw/>
- <http://openjdk.java.net/projects/jigsaw/doc/lang-vm.html#jigsaw-1>
- <http://openjdk.java.net/projects/jigsaw/doc/ModulesAndJavac.pdf>
- <http://openjdk.java.net/projects/jigsaw/doc/quickstart.html>
- <http://radar.oreilly.com/2014/09/what-every-java-developer-needs-to-know-about-java-9.html>
- https://blogs.oracle.com/jtc/entry/a_first_look_at_compact
- <https://docs.oracle.com/javase/8/docs/technotes/guides/compactprofiles/compactprofiles.html>
- <https://github.com/JavaMoney/javamoney-examples>



References

- <https://github.com/neomatrix369/BuildHelpers>
- <https://jdk9.java.net/jigsaw/>
- <https://github.com/AdoptOpenJDK/jdk9-jigsaw>
- <https://msdn.microsoft.com/en-us/library/ms179882.aspx>
- <http://stackoverflow.com/questions/26424759/what-is-sjavac-who-is-it-for-and-how-do-i-use-it>
- <http://stackoverflow.com/questions/29366265/how-to-use-jigsaw-with-java-9>
- <https://weblogs.java.net/blog/otaviojava/archive/2014/08/25/java-9-coming-money-api>
- <https://www.eclipsecon.org/na2015/sites/default/files/slides/reinhold-eclipsecon-2015.pdf>
- <https://www.voxxed.com/blog/2015/01/new-try-resources-improvement-jdk-9/>
- <https://www.voxxed.com/blog/presentation/presentation-java-9-make-way-for-modules/>
- <http://www.baeldung.com/java-9>
- <http://www.codergears.com/Blog/?p=310>
- <http://www.codergears.com/Blog/wp-content/uploads/jigsaw1.png>
- <http://www.dobreprogramy.pl/Java-9-bedzie-lekka-oszczedna-i-modulowa-jak-LEGO,News,62108.html>
- http://www.dzone.com/links/r/java_9_could_mess_with_your_code_new_early_access.html
- http://www.dzone.com/links/r/why_not_build_openjdk_9_using_docker_.html



References

- <http://www.jarchitect.com/img/DocMatrix/img3.png>
- <http://www.javaworld.com/article/2878952/java-platform/modularity-in-java-9.html>
- <http://www.postgresql.org/docs/9.1/static/datatype-money.html>
- <http://www.slideshare.net/mfrancis/java-8-modules-jigsaw-and-osgi-neil-bartlett>
- <http://openjdk.java.net/projects/jigsaw/spec/reqs/02>
- <http://openjdk.java.net/projects/jigsaw/j1/>
- <https://github.com/sandermaak/jigsaw-firstlook/blob/master/src/module1/com/test/TestClassModule1.java>
- <http://www.slideshare.net/delabassee/delabassee-http2>
- <https://neomatrix369.wordpress.com/2015/06/04/why-not-build-openjdk-9-using-docker/>
- <http://www.slideshare.net/SimoneBordet/http2-and-java-current-status>
- <http://cr.openjdk.java.net/~michaelm/8087112/>
- <http://hg.openjdk.java.net/jdk9>
- <https://vimeo.com/138736736>
- <http://www.infoq.com/articles/Java9-New-HTTP-2-and-REPL>
- <http://mail.openjdk.java.net/pipermail/core-libs-dev/2015-October/035743.html>
- <http://njbartlett.name/2015/11/13/osgi-jigsaw.html>



Images

- <http://www.clipartlord.com/wp-content/uploads/2014/11/puzzle4.png>
- <http://i537.photobucket.com/albums/ff332/Kento231/jigsaw.jpg>
- <http://www.codergears.com/Blog/wp-content/uploads/jigsaw1.png>
- <http://javadepend.files.wordpress.com/2012/10/jisgaw1.png?w=595>
- <http://www.osgi.org/wiki/uploads/Main/logo1.jpg>
- http://i.telegraph.co.uk/multimedia/archive/02576/currency_2576865b.jpg
- <http://media.techtarget.com/TheServerSideCOM/images/ModularDependants5.png>



Thank you

