# **XCONFIGURE**

XCONFIGURE is a collection of configure wrapper scripts for various HPC applications. The purpose of the scripts is to configure the application in question to make use of Intel's software development tools (Intel Compiler, Intel MPI, Intel MKL). XCONFIGURE helps to rely on a "build recipe", which is known to expose the highest performance or to reliably complete the build process.

Contributions are very welcome!

Each application (or library) is hosted in a separate directory. To configure (and ultimately build) an application, one can rely on a single script which then downloads a specific wrapper into the current working directory (of the desired application).

```
wget --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure-get.sh
chmod +x configure-get.sh
echo "EXAMPLE: recipe for Quantum Espresso"
./configure-get.sh qe hsw
```

On systems without access to the Internet, one can download (or clone) the entire collection upfront. To configure an application, please open the config folder directly or use the documentation and then follow the build recipe of the desired application or library.

### **Documentation**

- **ReadtheDocs**: online documentation with full text search: CP2K, ELPA, LIBINT, LIBXC, LIBXSMM, QE, and TF.
- PDF: a single documentation file.

# **Related Projects**

- Spack Package Manager: [http://computation.llnl.gov/projects/spack-hpc-package-manager%5D(http://computation.llnl.gov/projects/spack-hpc-package-manager)
- EasyBuild / EasyConfig (University of Gent): [https://github.com/easybuilders%5D(https://github.com/easybuilders)

Please note that XCONFIGURE has a narrower scope when compared to the above package managers.

# **Applications**

# CP2K

This document describes building CP2K with several (optional) libraries, which may be beneficial in terms of functionality and performance.

- Intel Math Kernel Library (also per Linux' distro's package manager) acts as:
  - LAPACK/BLAS and ScaLAPACK library
  - FFTw library
- LIBXSMM (replaces LIBSMM)
- LIBINT (depends on CP2K version)
- PLUMED (version 2.x)
- LIBXC (version 4.x)
- ELPA (depends on CP2K version)

The ELPA library eventually improves the performance (must be currently enabled for each input file even if CP2K was built with ELPA). There is also the option to auto-tune additional routines in CP2K (integrate/collocate) and to collect the generated code into an archive referred as LIBGRID.

For high performance, LIBXSMM (see also [https://libxsmm.readthedocs.io%5D(https://libxsmm.readthedocs.io)) has been incorporated since CP2K 3.0. When CP2K is built with LIBXSMM, CP2K's "libsmm" library is not used and hence libsmm does not need to be built and linked with CP2K.

# **Getting Started**

There are no configuration wrapper scripts provided for CP2K since a configure-step is usually not required, and the application can be built right away. CP2K's install\_cp2k\_toolchain.sh (under tools/toolchain) is out of scope in this document (it builds the entire tool chain from source including the compiler).

Although there are no configuration wrapper scripts for CP2K, below command delivers, e.g., an info-script and a script for planning CP2K execution:

```
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh cp2k
```

Of course, the scripts can be also download manually:

```
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/config/cp
chmod +x info.sh
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/config/cp
chmod +x plan.sh
```

## Step-by-step Guide

This step-by-step guide aims to build an MPI/OpenMP-hybrid version of the official release of CP2K by using the GNU Compiler Collection, Intel MPI, Intel MKL, LIBXSMM, ELPA, LIBXC, and LIBINT. Internet connectivity is assumed on the build-system. Please note that such limitations can be worked around or avoided with additional steps. However, this simple step-by-step guide aims to make some reasonable assumptions.

There are step-by-step guides for the current release (v7.1) and the previous release (v6.1).

**Current Release** This step-by-step guide uses (a) GNU Fortran (version 8.x, or 9.x, 9.1 is not recommended), or (b) Intel Compiler (version 19.1 "2020"). In any case, Intel MKL (2018, 2019, 2020 recommended) and Intel MPI (2018, 2020 recommended) need to be sourced. The following components are used:

- Intel Math Kernel Library (also per Linux' distro's package manager) acts as:
  - LAPACK/BLAS and ScaLAPACK library
  - FFTw library
- LIBXSMM (replaces LIBSMM)
- LIBINT (2.x from CP2K.org!)
- PLUMED (version 2.x)
- LIBXC (version 4.x, not 5.x)
- ELPA (version 2020.05.001 or 2020.11.001)

To install Intel Math Kernel Library and Intel MPI from a public repository depends on the Linux distribution's package manager (mixing and matching recommended Intel components is possible). For newer distributions, Intel MKL and Intel MPI libraries are likely part of the official repositories. Otherwise a suitable repository must be added to the package manager (not subject of this document).

```
source / opt/intel/compilers\_and\_libraries\_2020.4.304/linux/mpi/intel64/bin/mpivars.sh source / opt/intel/compilers\_and\_libraries\_2020.4.304/linux/mkl/bin/mklvars.sh intel64/bin/mpivars.sh intel64/bin/mpi
```

If Intel Compiler is used, the following (or similar) makes the compiler and all necessary libraries available.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

Please note, the ARCH file (used later/below to build CP2K) attempts to find Intel MKL even if the MKLROOT environment variable is not present. The MPI library is implicitly known when using compiler wrapper scripts (no need for I\_MPI\_ROOT). Installing the proper software stack and drivers for an HPC fabric to be used by MPI is out of scope in this document. If below check fails (GNU GCC only), the MPI's bin-folder must be added to the path.

```
$ mpif90 --version
  GNU Fortran (GCC) 8.3.0
  Copyright (C) 2018 Free Software Foundation, Inc.
  This is free software; see the source for copying conditions.
                                                                     There is NO
  warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
1) The first step builds ELPA. Please rely on ELPA 2020.
echo "wget --content-disposition --no-check-certificate https://elpa.mpcdf.mpg.de/software/tarball-arc
wget --content-disposition --no-check-certificate https://www.cp2k.org/static/downloads/elpa-2020.11.0
tar xvf elpa-2020.11.001.tar.gz
cd elpa-2020.11.001
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh elpa
a) GNU GCC
./configure-elpa-skx-gnu-omp.sh
b) Intel Compiler
./configure-elpa-skx-omp.sh
Build and install ELPA:
make -j
make install
make clean
2) The second step builds LIBINT (preconfigured for CP2K).
cd $HOME
curl -s https://api.github.com/repos/cp2k/libint-cp2k/releases/latest \
| grep "browser_download_url" | grep "lmax-6" \
 sed "s/..*: \"\(..*[^\"]\)\".*/url \1/" \
| curl -LOK-
{\tt tar xvf libint-v2.6.0-cp2k-lmax-6.tgz}
Note: A rate limit applies to GitHub API requests of the same origin. If the download fails, it can be worth trying an
authenticated request by using a GitHub account (-u "user:password").
cd libint-v2.6.0-cp2k-lmax-6
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh libint
Note: There are spurious issues about specific target flags requiring a build-system able to execute compiled binaries.
To avoid cross-compilation (not supported here), please rely on a build system that matches the target system.
a) GNU GCC
./configure-libint-skx-gnu.sh
```

Build and install LIBINT:

./configure-libint-skx.sh

make -j
make install
make distclean

b) Intel Compiler

**3**) The third step builds LIBXC.

```
wget --content-disposition --no-check-certificate https://gitlab.com/libxc/libxc/-/archive/4.3.4/libxc
tar xvf libxc-4.3.4.tar.bz2
cd libxc-4.3.4
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh libxc
Note: LIBXC 5.x is not supported. Please also disregard messages during configuration suggesting libtoolize --force.
a) GNU GCC
./configure-libxc-skx-gnu.sh
b) Intel Compiler
./configure-libxc-skx.sh
Build and install LIBXC:
make -j
make install
make distclean
4) The fourth step builds Plumed 2.
cd $HOME
wget --content-disposition --no-check-certificate https://github.com/plumed/plumed2/archive/v2.6.1.tar
tar xvf v2.6.1.tar.gz
cd plumed2-2.6.1
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh plumed
a) GNU GCC
./configure-plumed-skx-gnu.sh
b) Intel Compiler
./configure-plumed-skx.sh
Build and install Plumed2:
make -i
make install
make distclean
5) The fifth step makes LIBXSMM available, which is compiled as part of the last step.
cd $HOME
wget --content-disposition --no-check-certificate https://github.com/libxsmm/libxsmm/archive/1.16.1.ta
tar xvf 1.16.1.tar.gz
6) This last step builds the PSMP-variant of CP2K. Please re-download the ARCH-files from GitHub as mentioned
below (avoid reusing older/outdated files). If Intel MKL is not found, the key MKLROOT=/path/to/mkl can be added to
Make's command line. To select a different MPI implementation one can try, e.g., MKL_MPIRTL=openmpi.
cd $HOME
wget https://github.com/cp2k/cp2k/releases/download/v7.1.0/cp2k-7.1.tar.bz2
tar xvf cp2k-7.1.tar.bz2
Note: Do not download the package v7.1.0.tar.gz from [https://github.com/cp2k/cp2k/releases%5D(https:
//github.com/cp2k/cp2k/releases) which was automatically generated by GitHub (it misses the source code from
Git-submodules).
cd cp2k-7.1
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh cp2k
```

cd \$HOME

It is possible to supply LIBXSMMMROOT, LIBINTROOT, LIBXCROOT, and ELPAROOT (see below). However, the ARCH-file attempts to auto-detect these libraries.

```
a) GNU GCC

rm -rf exe lib obj

make ARCH=Linux-x86-64-intelx VERSION=psmp AVX=3 GNU=1 \
    LIBINTROOT=$HOME/libint/gnu-skx \
    LIBXCROOT=$HOME/libxc/gnu-skx \
    ELPAROOT=$HOME/elpa/gnu-skx-omp -j

b) Intel Compiler

rm -rf exe lib obj

make ARCH=Linux-x86-64-intelx VERSION=psmp AVX=3 \
    LIBINTROOT=$HOME/libint/intel-skx \
    LIBXCROOT=$HOME/libxc/intel-skx \
    ELPAROOT=$HOME/libxc/intel-skx \
    ELPAROOT=$HOME/elpa/intel-skx-omp -j
```

The above mentioned auto-detection of libraries goes further: GCC is used automatically if no Intel Compiler was sourced. Also, if cross-compilation is not necessary (make ARCH=Linux-x86-64-intelx VERSION=psmp AVX=3), AVX can be dropped as well from Make's command line (make ARCH=Linux-x86-64-intelx VERSION=psmp). The initial output of the build looks like:

Once the build completed, the CP2K executable should be ready (exe/Linux-x86-64-intelx/cp2k.psmp):

```
$ LIBXSMM_VERBOSE=1 exe/Linux-x86-64-intelx/cp2k.psmp
[...]
LIBXSMM_VERSION: release-1.16.1
LIBXSMM_TARGET: clx
```

Have a look at Running CP2K to learn more about pinning MPI processes (and OpenMP threads), and to try a first workload.

**Previous Release** As the step-by-step guide uses GNU Fortran (version 7.x, 8.x, or 9.x, 9.1 is not recommended), only Intel MKL (2019.x recommended) and Intel MPI (2018.x recommended) need to be sourced (sourcing all Intel development tools of course does not harm). The following components are used:

- Intel Math Kernel Library (also per Linux' distro's package manager) acts as:
  - LAPACK/BLAS and ScaLAPACK library
  - FFTw library
- LIBXSMM (replaces LIBSMM)
- LIBINT (version 1.1.5 or 1.1.6)
- PLUMED (version 2.x)
- LIBXC (version 4.x)
- ELPA (version 2017.11.001)

Note: GNU GCC version 7.x, 8.x, or 9.x is recommended (CP2K built with GCC 9.1 may not pass regression tests).

```
source / opt/intel/compilers\_and\_libraries\_2018.5.274/linux/mpi/intel64/bin/mpivars.sh source / opt/intel/compilers\_and\_libraries\_2019.3.199/linux/mkl/bin/mklvars.sh intel64/bin/mpivars.sh intel64/bin/mpi
```

To install Intel Math Kernel Library and Intel MPI from a public repository depends on the Linux distribution's package manager. For newer distributions, both libraries are likely part of the official repositories. Otherwise a suitable repository must be added to the package manager (not subject of this document). For example, installing with yum looks like:

```
sudo yum install intel-mkl-2019.4-070.x86_64 sudo yum install intel-mpi-2018.3-051.x86_64
```

Please note, the ARCH file (used later/below to build CP2K) attempts to find Intel MKL even if the MKLROOT environment variable is not present. The MPI library is implicitly known when using compiler wrapper scripts (no need for I\_MPI\_ROOT). Installing the proper software stack and drivers for an HPC fabric to be used by MPI is out of scope in this document. If below check fails, the MPI's bin-folder must be added to the path.

```
$ mpif90 --version
  GNU Fortran (GCC) 8.3.0
  Copyright (C) 2018 Free Software Foundation, Inc.
  This is free software; see the source for copying conditions.
                                                                     There is NO
  warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
The first step builds ELPA. Do not use an ELPA-version newer than 2017.11.001.
cd $HOME
wget https://elpa.mpcdf.mpg.de/software/tarball-archive/Releases/2017.11.001/elpa-2017.11.001.tar.gz
tar xvf elpa-2017.11.001.tar.gz
cd elpa-2017.11.001
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh elpa
./configure-elpa-skx-gnu-omp.sh
make -i
make install
make clean
The second step builds LIBINT (1.1.6 recommended, newer version cannot be used). This library does not compile on
an architecture with less CPU-features than the target (e.g., configure-libint-skx-gnu.sh implies to build on "Skylake"
or "Cascadelake" server).
cd $HOME
wget --content-disposition --no-check-certificate https://github.com/evaleev/libint/archive/release-1-
tar xvf release-1-1-6.tar.gz
cd libint-release-1-1-6
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./ \verb|configure-get.sh| | \verb|libint| |
./configure-libint-skx-gnu.sh
make -j
make install
make distclean
The third step builds LIBXC.
```

```
cd $HOME
wget --content-disposition --no-check-certificate https://gitlab.com/libxc/libxc/-/archive/4.3.4/libxc
tar xvf libxc-4.3.4
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh libxc
./configure-libxc-skx-gnu.sh
make -j
make install
make distclean
```

The fourth step builds Plumed2.

```
wget --content-disposition --no-check-certificate https://github.com/plumed/plumed2/archive/v2.6.1.tar
tar xvf v2.6.1.tar.gz

cd plumed2-2.6.1
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
```

```
chmod +x configure-get.sh
./configure-get.sh plumed
./configure-plumed-skx.sh
```

Build and install Plumed2:

```
make -j
make install
make distclean
```

The fifth step makes LIBXSMM available, which is compiled as part of the last step.

```
wget --content-disposition --no-check-certificate https://github.com/libxsmm/libxsmm/archive/1.16.1.tar xvf 1.16.1.tar.gz
```

This last step builds the PSMP-variant of CP2K. Please re-download the ARCH-files from GitHub as mentioned below (avoid reusing older/outdated files). If Intel MKL is not found, the key MKLROOT=/path/to/mkl can be added to Make's command line. To select a different MPI implementation one can try, e.g., MKL\_MPIRTL=openmpi.

```
cd $HOME
wget https://github.com/cp2k/cp2k/archive/v6.1.0.tar.gz
tar xvf v6.1.0.tar.gz

cd cp2k-6.1.0
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh cp2k

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/config/cp
patch -p0 src/mpiwrap/message_passing.F mpi-wrapper.diff
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/config/cp
patch -p0 src/pw/fft/fftw3_lib.F intel-mkl.diff
```

It is possible to supply LIBXSMMROOT, LIBINTROOT, LIBXCROOT, and ELPAROOT (see below). However, the ARCH-file attempts to auto-detect these libraries.

```
rm -rf exe lib obj
cd makefiles
make ARCH=Linux-x86-64-intelx VERSION=psmp AVX=3 GNU=1 \
   LIBINTROOT=$HOME/libint/gnu-skx \
   LIBXCROOT=$HOME/libxc/gnu-skx \
   ELPAROOT=$HOME/elpa/gnu-skx-omp -j
```

The above mentioned auto-detection of libraries goes further: GCC is used automatically if no Intel Compiler was sourced. Also, if cross-compilation is not necessary (make ARCH=Linux-x86-64-intelx VERSION=psmp AVX=3), AVX can be dropped as well from Make's command line (make ARCH=Linux-x86-64-intelx VERSION=psmp). The initial output of the build looks like:

```
Discovering programs ...

Using the following libraries:

LIBXSMMROOT=/path/to/libxsmm

LIBINTROOT=/path/to/libint/gnu-skx

LIBXCROOT=/path/to/libxc/gnu-skx

ELPAROOT=/path/to/elpa/gnu-skx-omp

LIBXSMM release-1.16.1 (Linux)
```

Once the build completed, the CP2K executable should be ready (exe/Linux-x86-64-intelx/cp2k.psmp):

```
$ LIBXSMM_VERBOSE=1 exe/Linux-x86-64-intelx/cp2k.psmp
[...]
LIBXSMM_VERSION: release-1.16.1
LIBXSMM_TARGET: clx
```

Have a look at Running CP2K to learn more about pinning MPI processes (and OpenMP threads), and to try a first workload.

## **Intel Compiler**

Below are the releases of the Intel Compiler, which are known to reproduce correct results according to the regression tests. It is also possible to mix and match different component versions by sourcing from different Intel suites.

- Intel Compiler 2017 (u0, u1, u2, u3), and the initial release of MKL 2017 (u0)
- Intel Compiler 2017 Update 4, and any later update of the 2017 suite (u4, u5, u6, u7)
  - source /opt/intel/compilers\_and\_libraries\_2017.[u4-u7]/linux/bin/compilervars.sh intel64
- Intel Compiler 2018 (u3, u4, u5): only with CP2K/development (not with CP2K 6.1 or earlier)
  - source /opt/intel/compilers\_and\_libraries\_2018.3.222/linux/bin/compilervars.sh intel64
  - source /opt/intel/compilers\_and\_libraries\_2018.5.274/linux/bin/compilervars.sh intel64
- Intel Compiler 2019 and 2020: only suitable for CP2K 7.1 (and later)
  - source /opt/intel/compilers\_and\_libraries\_2020.4.304/linux/bin/compilervars.sh intel64
  - Avoid 2019u1, 2019u2, 2019u3
- Intel MPI; usually any version is fine: Intel MPI 2018 and 2020 are recommended

Note: Intel Compiler 2019 (and likely later) is not recommended for CP2K 6.1 (and earlier).

### Intel ARCH File

CP2K 6.1 includes Linux-x86-64-intel.\* (arch directory) as a starting point for writing an own ARCH-file (note: Linux-x86-64-intel.\* vs. Linux-x86-64-intelx.\*). Remember, performance critical code is often located in libraries (hence -02 optimizations for CP2K's source code are enough in almost all cases), more important for performance are target-flags such as -march=native (-xHost) or -mavx2 -mfma. Prior to Intel Compiler 2018, the flag -fp-model source (FORTRAN) and -fp-model precise (C/C++) were key for passing CP2K's regression tests. If an own ARCH file is used or prepared, all libraries including LIBXSMM need to be built separately and referred in the link-line of the ARCH-file. In addition, CP2K may need to be informed and certain preprocessor symbols need to be given during compilation (-D compile flag). For further information, please follow the official guide and consider the CP2K Forum in case of trouble.

The purpose of the Intel ARCH files is to avoid writing an own ARCH-file even when GNU Compiler is used. Taking the Intel ARCH files that are part of the CP2K/Intel fork automatically picks up the correct paths for Intel libraries. These paths are determined by using the environment variables setup when the Intel tools are source'd. Similarly, LIBXSMMMROOT, LIBINTROOT, LIBXCROOT, and ELPAROOT (which can be supplied on Make's command line) are discovered automatically if it is in the user's home directory, or when it is in parallel to the CP2K directory. The Intel ARCH files not only work with CP2K/Intel fork but even if an official release of CP2K is built (which is also encouraged). Of course, one can download the afore mentioned Intel ARCH files manually:

```
cd cp2k-6.1.0/arch  
wget https://github.com/cp2k/cp2k/raw/master/arch/Linux-x86-64-intelx.arch  
wget https://github.com/cp2k/cp2k/raw/master/arch/Linux-x86-64-intelx.popt  
wget https://github.com/cp2k/cp2k/raw/master/arch/Linux-x86-64-intelx.psmp  
wget https://github.com/cp2k/cp2k/raw/master/arch/Linux-x86-64-intelx.sopt  
wget https://github.com/cp2k/cp2k/raw/master/arch/Linux-x86-64-intelx.ssmp
```

## **Running CP2K**

Running CP2K may go beyond a single node, and pinning processes and threads becomes even more important. There are several schemes available. As a rule of thumb, a high rank-count for lower node-counts may yield best results unless the workload is very memory intensive. In the latter case, lowering the number of MPI-ranks per node is effective especially if a larger amount of memory is replicated rather than partitioned by the rank-count. In contrast (communication bound), a lower rank count for multi-node computations may be desired.

Most important, in most cases CP2K prefers a total rank-count to be a square-number which leads to some complexity when aiming for rank/thread combinations that exhibit good performance properties. Please refer to the documentation of the script for planning MPI/OpenMP-hybrid (plan.sh), which illustrates running CP2K's PSMP-binary on an HT-enabled dual-socket system with 24 cores per processor/socket (96 hardware threads). The single-node execution with 16 ranks and 6 threads per rank looks like (lx16x6):

```
mpirun -np 16 \
  -genv I_MPI_PIN_DOMAIN=auto -genv I_MPI_PIN_ORDER=bunch \
  -genv OMP_PLACES=threads -genv OMP_PROC_BIND=SPREAD \
  -genv OMP_NUM_THREADS=6 \
  exe/Linux-x86-64-intelx/cp2k.psmp workload.inp
```

For an MPI command line targeting 8 nodes, plan.sh was used to setup 8 ranks per node with 12 threads per rank (8x8x12):

```
mpirun -perhost 8 -host node1,node2,node3,node4,node5,node6,node7,node8 \
    -genv I_MPI_PIN_DOMAIN=auto -genv I_MPI_PIN_ORDER=bunch \
    -genv OMP_PLACES=threads -genv OMP_PROC_BIND=SPREAD \
    -genv OMP_NUM_THREADS=12 -genv I_MPI_DEBUG=4 \
    exe/Linux-x86-64-intelx/cp2k.psmp workload.inp
```

**Note**: the documentation of plan.sh also motivates and explains the MPI environment variables as shown in above MPI command lines.

#### CP2K on GPUs

This section shows how to build CP2K with DBCSR's OpenCL backend (USE\_ACCEL=openc1 like USE\_ACCEL=openc1 for CUDA). Any other dependencies like LIBINT, LIBXC, and others are auto-detected and can be made available using XCONFIGURE as well. LIBXSMM is a prerequisite and building it, is managed by using the ARCH-file as fetched below (configure-get.sh cp2k).

```
git clone -b main https://github.com/libxsmm/libxsmm.git
git clone https://github.com/cp2k/cp2k.git

cd cp2k
git submodule update --init --recursive
cd exts/dbcsr
git fetch
git checkout develop
cd ../..
wget --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure-get.sh
chmod +x configure-get.sh
./configure-get.sh cp2k

rm -rf exe lib obj
echo "Intel MPI, Intel MKL, and GNU Fortran are made available"
make ARCH=Linux-x86-64-intelx VERSION=psmp NDEBUG=2 USE_ACCEL=opencl -j
```

DBCSR can be built stand-alone and used to exercise and test GPU accleration as well, which is not subject of XCONFIGURE. Further, within DBCSR some driver code exists to exercise GPU performance in a stand-alone fashion as well. The latter is not even subject to DBCSR's build system and simply required GNU Make (see DBCSR ACCelerator Interface). The mentioned SMM driver can be used to auto-tune or bulk-tune kernels for the OpenCL backend.

Note: if the GNU Fortran compiler rejects Intel MPI because of an incompatible MPI module, a build-key gnuver is automatically determined (by default), or can be specified with make. Please list the content of the directory \${I\_MPI\_ROOT}/include/mpi/gfortran (or \${I\_MPI\_ROOT}/include/gfortran) and select the closest version matching the version of the GNU Fortran compiler, e.g., make ARCH=Linux-x86-64-intelx VERSION=psmp GNUVER=11.1.0 for GNU Fortran 12.2. To rely on the GNU Compiler even when Intel Compiler was source'd, use GNU=1.

```
make ARCH=Linux-x86-64-intelx VERSION=psmp USE_ACCEL=opencl GNU=1 cp2k
```

**Note**: for more comprehensive builds of CP2K, please refer to CP2K's Toolchain, e.g., it is possible to blend the OpenCL backend with other GPU-enabled code written in CUDA.

The OpenCL backend provides pretuned kernels and comprehensive runtime-control by the means of environment variables. This can be used to assign OpenCL devices, to aggregate sub-devices (devices are split into sub-devices by default), to extract kernel shapes used by a specific workload, and to subsequently tune specific kernels.

#### **Performance**

The script for planning MPI-execution (plan.sh) is highly recommend along with reading the section about how to run CP2K. For CP2K, the MPI-communication patterns can be tuned in most MPI-implementations. For Intel MPI, the following setting can be beneficial:

```
export I_MPI_COLL_INTRANODE=pt2pt
export I_MPI_ADJUST_REDUCE=1
export I_MPI_ADJUST_BCAST=1
```

For large-scale runs, the startup can be tuned, but typically this is not necessary. However, the following may be useful (and does not harm):

```
export I_MPI_DYNAMIC_CONNECTION=1
```

Intel MPI usually nicely determines the fabric settings for both Omnipath and InfiniBand, and no adjustment is needed. However, people often prefer explicit settings even if it does not differ from what is determined automatically. For example, InfiniBand with RDMA can be set explicitly by using mpirun -rdma which can be also achieved with environment variables:

```
echo "'mpirun -rdma' and/or environment variables for InfiniBand" export I_MPI_FABRICS=shm:dapl
```

As soon as several experiments are finished, it becomes handy to summarize the log-output. For this case, an info-script (info.sh) is available attempting to present a table (summary of all results), which is generated from log files (use tee, or rely on the output of the job scheduler). There are only certain file extensions supported (.txt, .log). If no file matches, then all files (independent of the file extension) are attempted to be parsed (which will go wrong eventually). If for some reason the command to launch CP2K is not part of the log and the run-arguments cannot be determined otherwise, the number of nodes is eventually parsed by using the filename of the log itself (e.g., first occurrence of a number along with an optional "n" is treated as the number of nodes used for execution).

```
./run-cp2k.sh | tee cp2k-h2o64-2x32x2.txt
ls -1 *.txt
cp2k-h2o64-2x32x2.txt
cp2k-h2o64-4x16x2.txt

./info.sh [-best] /path/to/logs-or-cwd
H2O-64 Nodes R/N T/R Cases/d Seconds
cp2k-h2o64-2x32x2 2 32 4 807 107.237
cp2k-h2o64-4x16x2 4 16 8 872 99.962
```

Please note that the "Cases/d" metric is calculated with integer arithmetic and hence represents fully completed cases per day (based on 86400 seconds per day). The number of seconds (as shown) is end-to-end (wall time), i.e., total time to solution including any (sequential) phase (initialization, etc.). Performance is higher if the workload requires more iterations (some publications present a metric based on iteration time).

### Sanity Check

There is nothing that can replace the full regression test suite. However, to quickly check whether a build is sane or not, one can run for instance tests/QS/benchmark/H2O-64.inp and check if the SCF iteration prints like the following:

Step		Update	method	Time	Convergence	Total energy	Change
1	OT	DIIS	0.15E+00	0.5	0.01337191	-1059.6804814927	-1.06E+03
2	OT	DIIS	0.15E+00	0.3	0.00866338	-1073.3635678409	-1.37E+01
3	OT	DIIS	0.15E+00	0.3	0.00615351	-1082.2282197787	-8.86E+00
4	OT	DIIS	0.15E+00	0.3	0.00431587	-1088.6720379505	-6.44E+00
5	OT	DIIS	0.15E+00	0.3	0.00329037	-1092.3459788564	-3.67E+00
6	OT	DIIS	0.15E+00	0.3	0.00250764	-1095.1407783214	-2.79E+00
7	OT	DIIS	0.15E+00	0.3	0.00187043	-1097.2047924571	-2.06E+00
8	OT	DIIS	0.15E+00	0.3	0.00144439	-1098.4309205383	-1.23E+00
9	OT	DIIS	0.15E+00	0.3	0.00112474	-1099.2105625375	-7.80E-01
10	OT	DIIS	0.15E+00	0.3	0.00101434	-1099.5709299131	-3.60E-01
[	.]						

The column called "Convergence" must monotonically converge towards zero.

```
[https://nholmber.github.io/2017/04/cp2k-build-cray-xc40/\%5D(https://nholmber.github.io/2017/04/cp2k-build-cray-xc40/)\\ [https://xconfigure.readthedocs.io/cp2k/plan/\%5D(https://xconfigure.readthedocs.io/cp2k/plan/)\\ [https://www.cp2k.org/static/downloads\%5D(https://www.cp2k.org/static/downloads)\\ [https://www.cp2k.org/howto:compile%5D(https://www.cp2k.org/howto:compile)
```

### **ELPA**

#### **Build Instructions**

**ELPA 2021** Download and unpack ELPA and make the configure wrapper scripts available in ELPA's root folder. Consider CP2K's download area (cache) as an alternative source for downloading ELPA.

```
echo "wget --content-disposition --no-check-certificate https://www.cp2k.org/static/downloads/elpa-202 wget --content-disposition --no-check-certificate https://elpa.mpcdf.mpg.de/software/tarball-archive/Rtar xvf elpa-2021.11.002.tar.gz cd elpa-2021.11.002

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure chmod +x configure-get.sh ./configure-get.sh elpa
```

Please make the Intel Compiler and Intel MKL available on the command line. This depends on the environment. For instance, many HPC centers rely on module load.

```
\verb|source|/opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh| intel 64.304/linux/bin/compilervars.sh| in
```

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make clean
./configure-elpa-skx-omp.sh
make -j ; make install

make clean
./configure-elpa-skx.sh
make -j ; make install
```

Even if ELPA was just unpacked (and never built before), make clean is recommended in advance of building ELPA ("unknown module file format"). After building and installing the desired configuration(s), one may have a look at the installation:

```
[user@system elpa-2021.11.002] $ ls ../elpa
intel-skx
intel-skx-omp
```

For different targets (instruction set extensions) or for different versions of the Intel Compiler, the configure scripts support an additional argument ("default" is the default tagname):

```
./configure-elpa-skx-omp.sh tagname
```

./configure-get.sh elpa

As shown above, an arbitrary "tagname" can be given (without editing the script). This might be used to build multiple variants of the ELPA library.

**ELPA 2020** Download and unpack ELPA and make the configure wrapper scripts available in ELPA's root folder. Consider CP2K's download area (cache) as an alternative source for downloading ELPA.

```
echo "wget --content-disposition --no-check-certificate https://elpa.mpcdf.mpg.de/software/tarball-arc wget --content-disposition --no-check-certificate https://www.cp2k.org/static/downloads/elpa-2020.11.0 tar xvf elpa-2020.11.001.tar.gz cd elpa-2020.11.001

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure chmod +x configure-get.sh
```

Please make the Intel Compiler and Intel MKL available on the command line. This depends on the environment. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make clean
./configure-elpa-skx-omp.sh
make -j ; make install

make clean
./configure-elpa-skx.sh
make -j ; make install
```

Even if ELPA was just unpacked (and never built before), make clean is recommended in advance of building ELPA ("unknown module file format"). After building and installing the desired configuration(s), one may have a look at the installation:

```
[user@system elpa-2020.11.001] $ ls ../elpa
intel-skx
intel-skx-omp
```

**ELPA 2019** Download and unpack ELPA and make the configure wrapper scripts available in ELPA's root folder.

```
wget --content-disposition --no-check-certificate https://elpa.mpcdf.mpg.de/software/tarball-archive/R
tar xvf elpa-2019.11.001.tar.gz
cd elpa-2019.11.001

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
```

Please make the Intel Compiler and Intel MKL available on the command line. This depends on the environment. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make clean
./configure-elpa-skx-omp.sh
make -j ; make install

make clean
./configure-elpa-skx.sh
make -j ; make install
```

./configure-get.sh elpa

Even if ELPA was just unpacked (and never built before), make clean is recommended in advance of building ELPA ("unknown module file format"). After building and installing the desired configuration(s), one may have a look at the installation:

```
[user@system elpa-2019.11.001] $ ls ../elpa
intel-skx
intel-skx-omp
```

**ELPA 2018** Please use ELPA 2017.11.001 for CP2K 6.1. For CP2K 7.1, please rely on ELPA 2019. ELPA 2018 fails or crashes in several regression tests in CP2K (certain rank-counts produce an incorrect decomposition), and hence ELPA 2018 should be avoided in production.

**ELPA 2017** Download and unpack ELPA and make the configure wrapper scripts available in ELPA's root folder. It is recommended to package the state (Tarball or similar), which is achieved after downloading the wrapper scripts.

Note: In Quantum Espresso, the \_\_\_ELPA\_2018 interface must be used for ELPA 2017.11 (-D\_\_ELPA\_2018). The \_\_ELPA\_2017 preprocessor definition triggers the ELPA1 legacy interface (get\_elpa\_row\_col\_comms, etc.), which was removed in ELPA 2017.11. This is already considered when using XCONFIGURE's wrapper scripts.

```
wget --content-disposition --no-check-certificate https://elpa.mpcdf.mpg.de/software/tarball-archive/R
tar xvf elpa-2017.11.001.tar.gz
cd elpa-2017.11.001
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
```

Please make the Intel Compiler and Intel MKL available on the command line. This depends on the environment. For instance, many HPC centers rely on module load.

source /opt/intel/compilers\_and\_libraries\_2020.4.304/linux/bin/compilervars.sh intel64

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make clean
./configure-elpa-skx-omp.sh
make -j ; make install

make clean
./configure-elpa-skx.sh
make -j ; make install
```

chmod +x configure-get.sh
./configure-get.sh elpa

Even if ELPA was just unpacked (and never built before), make clean is recommended in advance of building ELPA ("unknown module file format").

### References

[https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2l-elpa-optional-improved-performance-for-diagonalization%5D(https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2l-elpa-optional-improved-performance-for-diagonalization)

[https://elpa.mpcdf.mpg.de/software/tarball-archive/ELPA\_TARBALL\_ARCHIVE.html%5D(https://elpa.mpcdf.mpg.de/software/tarball-archive/ELPA\_TARBALL\_ARCHIVE.html)

[https://www.cp2k.org/static/downloads%5D(https://www.cp2k.org/static/downloads)

## HDF5

To download, configure, build, and install HDF5, one may proceed as shown below.

```
wget --content-disposition --no-check-certificate https://support.hdfgroup.org/ftp/HDF5/releases/hdf5-
tar xvf hdf5-1.12.1.tar.bz2
cd hdf5-1.12.1

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh hdf5
```

Please make the intended compiler available on the command line. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make distclean
./configure-hdf5-skx.sh
make -j; make install
```

 $[https://support.hdfgroup.org/ftp/HDF5/releases/\%5D(https://support.hdfgroup.org/ftp/HDF5/releases/)\\[https://hdfgroup.org/\%5D(https://hdfgroup.org/)$ 

### LIBINT

#### Overview

For CP2K 6.1 (and earlier), LIBINT 1.1.x is required (1.2.x, 2.x, or any later version cannot be used). For CP2K 7.x and onwards, LIBINT 2.5 (or later) is needed.

Please make the Intel Compiler available on the command line. This depends on the environment. For instance, many HPC centers rely on module load.

**Note**: CP2K 6.1 (and earlier) depends on LIBINT 1.1.x and a newer version of LIBINT cannot be used! CP2K 7.x (and later) rely on LIBINT 2.5 (or later) and cannot use the preconfigured library as provided on LIBINT's home page.

## Version 2.5 (and later)

LIBINT generates code according to a configuration and an extent that is often specific to the application. The downloads from LIBINT's home page are not configured for CP2K and hence cannot be used. Please download (take "lmax-6" if unsure), unpack LIBINT, and make the configure wrapper scripts available in LIBINT's root folder.

To just determine the download-URL of the latest version (a suitable variant can be "lmax-6"):

```
curl -s https://api.github.com/repos/cp2k/libint-cp2k/releases/latest \
| grep "browser_download_url" | grep "lmax-6" \
| sed "s/..*: \"\(..*[^\"]\)\".*/\1/"
```

To download the lmax6-version right away, run the following command:

```
curl -s https://api.github.com/repos/cp2k/libint-cp2k/releases/latest \
    grep "browser_download_url" | grep "lmax-6" \
    sed "s/..*: \"\(..*[^\"]\)\".*/url \1/" \
    curl -LOK-
```

**Note**: A rate limit applies to GitHub API requests of the same origin. If the download fails, it can be worth trying an authenticated request by using a GitHub account (-u "user:password").

To unpack the archive and to download the configure wrapper (lmax6-version is assumed):

```
tar xvf libint-v2.6.0-cp2k-lmax-6.tgz
cd libint-v2.6.0-cp2k-lmax-6
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh libint
```

There are spurious issues about specific target flags requiring a build-system able to execute compiled binaries. To avoid cross-compilation (not supported here), please rely on a build system that matches the target system. For example, to configure and make for an Intel Xeon Scalable processor such as "Cascadelake" or "Skylake" server ("SKX"):

```
make distclean
./configure-libint-skx.sh
make -j; make install
```

Make sure to run make distclean before reconfiguring a different variant, e.g., GNU and Intel variant. Further, for different targets (instruction set extensions) or different compilers, the configure-wrapper scripts support an additional argument ("default" is the default tagname):

```
./{\tt configure\,-libint\,-hsw.sh}\ {\tt tagname}
```

As shown above, an arbitrary "tagname" can be given (without editing the script). This might be used to build multiple variants of the LIBINT library.

#### Version 1.x

Download and unpack LIBINT and make the configure wrapper scripts available in LIBINT's root folder. Please note that the "automake" package is a prerequisite.

```
wget --content-disposition --no-check-certificate https://github.com/evaleev/libint/archive/release-1-
tar xvf release-1-1-6.tar.gz
cd libint-release-1-1-6

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh libint
```

For example, to configure and make for an Intel Xeon E5v4 processor (formerly codenamed "Broadwell"):

```
make distclean
./configure-libint-hsw.sh
make -j; make install
```

The version 1.x line of LIBINT does not support to cross-compile for an architecture. If cross-compilation is necessary, one can rely on the Intel Software Development Emulator (Intel SDE) to compile LIBINT for targets, which cannot execute on the compile-host.

```
/software/intel/sde/sde -knl -- make
```

To speed-up compilation, "make" might be carried out in phases: after "printing the code" (c-files), the make execution continues with building the object-file where no SDE needed. The latter phase can be sped up by interrupting "make" and executing it without SDE. The root cause of the entire problem is that the driver printing the c-code is (needlessly) compiled using the architecture-flags that are not supported on the host.

### References

[https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2g-libint-optional-enables-methods-including-hf-exchange%5D(https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2g-libint-optional-enables-methods-including-hf-exchange)

[https://github.com/evaleev/libint/releases/tag/release-1-1-6%5D(https://github.com/evaleev/libint/release-1-1-6%5D(https://github.com/evaleev/libint/release-1-1-6%5D(https://github.com/ev

[https://github.com/cp2k/libint-cp2k/releases/latest%5D(https://github.com/cp2k/libint-cp2k/releases/latest)

## Med File Library (libmed)

To download, configure, build, and install libmed, one may proceed as shown below.

```
wget --content-disposition --no-check-certificate https://files.salome-platform.org/Salome/other/med-4
tar xvf med-4.1.0.tar.gz
cd med-4.1.0

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh libmed
```

Please make the intended compiler available on the command line. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

Note: Please make the "hdf5-tools" command available, or pay attention to the console output after configuring libmed. In general, an HDF5 development package is necessary to pass the default configuration as implemented by XCONFIGURE. One can adjust the configure wrapper script for custom-built HDF5 by pointing to an (non-default) installation location.

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make distclean
./configure-med-skx.sh
make -j; make install
```

```
[https://salome-platform.org/downloads/%5D(https://salome-platform.org/downloads/) [http://wiki.opentelemac.org/doku.php?id=installation_linux_med%5D(http://wiki.opentelemac.org/doku.php?id=installation_linux_med) [http://opentelemac.org/%5D(http://opentelemac.org/)
```

### **LIBXC**

To download, configure, build, and install LIBXC 2.x, 3.x (CP2K 5.1 and earlier is only compatible with LIBXC 3.0 or earlier), 4.x (CP2K 7.1 and earlier is only compatible with LIBXC 4.x), or 5.x (CP2K 8.1 and later require LIBXC 5.x), one may proceed as shown below. For CP2K, see also How to compile the CP2K code). In general, only the latest major release of LIBXC (by the time of the CP2K-release) is supported.

```
wget --content-disposition --no-check-certificate https://www.tddft.org/programs/libxc/down.php?file=6
tar xvf libxc-6.2.2.tar.gz
cd libxc-6.2.2

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh libxc
```

Please make the Intel Compiler available on the command line. This depends on the environment. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make distclean
./configure-libxc-skx.sh
make -j; make install
```

./configure-get.sh metis

Note: Please disregard messages during configuration suggesting libtoolize --force.

### References

[https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals%5D (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals)] (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals) (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals) (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals) (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals) (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals) (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functionals) (https://github.com/cp2k/cp2k/blob/master/INSTALL.md#2k-libxc-optional-wider-choice-of-xc-functional-wider-choice-of-xc-functional-wider-choice-of-xc-functional-wider-choice-of-

## **LIBXSMM**

LIBXSMM is a library targeting Intel Architecture (x86) for small, dense or sparse matrix multiplications, and small convolutions. The build instructions can be found at [https://github.com/hfp/libxsmm%5D(https://libxsmm.readth edocs.io/#build-instructions) (PDF).

## **METIS**

To download, configure, build, and install METIS, one may proceed as shown below.

```
wget --content-disposition --no-check-certificate http://glaros.dtc.umn.edu/gkhome/fetch/sw/metis/meti
tar xvf metis-5.1.0.tar.gz
cd metis-5.1.0

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
```

Please make the intended compiler available on the command line. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make distclean
./configure-metis-skx.sh
make -j; make install
```

#### References

[http://glaros.dtc.umn.edu/gkhome/metis/metis/download%5D(http://glaros.dtc.umn.edu/gkhome/metis/metis/download)

[http://glaros.dtc.umn.edu/gkhome/views/metis%5D(http://glaros.dtc.umn.edu/gkhome/views/metis)

## **Plumed**

To download, configure, build, and install Plumed 2.x (CP2K requires Plumed2), one may proceed as shown below. See also How to compile CP2K with Plumed.

```
wget --content-disposition --no-check-certificate https://github.com/plumed/plumed2/archive/v2.8.0.tar
tar xvf plumed2-2.8.0.tar.gz
cd plumed2-2.8.0

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh plumed
```

Please make the intended compiler available on the command line. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

Note: Please make the "python" command available, which may point to Python2 or Python3. For example, create a bin directory at \$HOME (mkdir -p \${HOME}/bin), and create a symbolic link to either Python2 or Python3 (e.g., ln -s /usr/bin/python3 \${HOME}/bin/python).

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make distclean
./configure-plumed-skx.sh
make -j; make install
```

## References

 $[https://github.com/plumed/plumed2/releases/latest\%5D(https://github.com/plumed/plumed2/releases/latest)\\ [https://github.com/cp2k/cp2k/blob/master/INSTALL.md\#2o-plumed-optional-enables-various-enhanced-sampling-methods\%5D(https://github.com/cp2k/cp2k/blob/master/INSTALL.md\#2o-plumed-optional-enables-various-enhanced-sampling-methods)$ 

 $[https://www.cp2k.org/howto:install\_with\_plumed\%5D(https://www.cp2k.org/howto:install\_with\_plumed)\\ [https://www.plumed.org/\%5D(https://www.plumed.org/)$ 

### **QE**

### **Build Instructions**

Download, unpack Quantum Espresso and make the configure wrapper scripts available in QE's root folder. Please note that the configure wrapper scripts support QE 6.x (prior support for 5.x is dropped). Before building QE, one needs to complete the recipe for ELPA.

Note: the ELPA configuration must correspond to the desired QE configuration, e.g., configure-elpa-skx-omp.sh and configure-qe-skx-omp.sh ("omp").

```
wget https://gitlab.com/QEF/q-e/-/archive/qe-6.6/q-e-qe-6.6.tar.bz2
tar xvf q-e-qe-6.6.tar.bz2
cd q-e-qe-6.6

wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
./configure-get.sh qe
```

Please make the Intel Compiler available on the command line, which may vary with the computing environment. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

For example, configure for an Intel Xeon Scalable Processor (applicable to CPUs previously codenamed "Skylake" and "Cascadelake" server), and build the desired application(s), e.g., "pw", "cp", or "all".

```
./configure-qe-skx-omp.sh make pw -j \,
```

Building "all" (or make without target argument) requires repeating make all until no compilation error occurs. This is because of some incorrect build dependencies (build order issue which might have been introduced by the configure wrapper scripts). In case of starting over, one can run make distclean, reconfigure the application, and build it again. For different targets (instruction set extensions) or different versions of the Intel Compiler, the configure scripts support an additional argument ("default" is the default tagname):

```
./configure-qe-skx-omp.sh tagname
```

As shown above, an arbitrary "tagname" can be given (without editing the script). This might be used to build multiple variants of QE. Please note: this tagname also selects the corresponding ELPA library (or should match the tagname used to build ELPA). Make sure to save your current QE build before building an additional variant!

#### Run Instructions

To run Quantum Espresso in an optimal fashion depends on the workload and on the "parallelization levels", which can be exploited by the workload in question. These parallelization levels apply to execution phases (or major algorithms) rather than staying in a hierarchical relationship (levels). It is recommended to read some of the primary references explaining these parallelization levels (a number of them can be found in the Internet including some presentation slides). Time to solution may *vary by factors* depending on whether these levels are orchestrated or not. To specify these levels, one uses command line arguments along with the QE executable(s):

- -npool: try to maximize the number of pools. The number depends on the workload, e.g., if the number of k-points can be distributed among independent pools. Indeed, per trial-and-error it is rather quick to check if a workload fails to pass the initialization phase. One may use prime numbers: 2, 3, 5, etc. (default is 1). For example, when npool=2 worked it might be worth trying npool=4. On the other hand, increasing the number pools duplicates the memory consumption accordingly (larger numbers are increasingly unlikely to work).
- -ndiag: this number determines the number of ranks per pool used for dense linear algebra operations (DGEMM and ZGEMM). For example, if 64 ranks are used in total per node and npool=2, then put ndiag=32 (QE selects the next square number which is less equal than the given number, e.g., ndiaq=25 in the previous example).
- -ntg: specifies the number of tasks groups per pool being used for, e.g., FFTs. One can start with NTG=\$((NUMNODES\*NRANKS/(NPOOL\*2))). If NTG becomes zero, NTG=\${NRANKS} should be used (number of ranks per node). Please note the given formula is only a rule of thumb, and the number of task groups also depends on the number of ranks as the workload is scaled out.

To run QE, below command line can be a starting point ("numbers" are presented as Shell variables to better understand the inner mechanics). Important for hybrid builds (MPI and OpenMP together) are the given environment variables. The kmp\_affinity assumes Hyperthreading (SMT) is enabled (granularity=fine), and the "scatter" policy allows to easily run less than the maximum number of Hyperthreads per core. As a rule of thumb, OpenMP adds only little overhead (often not worth a pure MPI application) but allows to scale further out when compared to pure MPI builds.

```
mpirun -bootstrap ssh -genvall \
  -np $((NRANKS_PER_NODE*NUMNODES)) -perhost ${NRANKS} \
  -genv I_MPI_PIN_DOMAIN=auto -genv I_MPI_PIN_ORDER=bunch \
  -genv KMP_AFFINITY=compact,granularity=fine,1 \
  -genv OMP_NUM_THREADS=${NTHREADS_PER_RANK} \
  /path/to/pw.x \<command-line-arguments\>
```

#### **Performance**

An info-script (info.sh) is available attempting to present a table (summary of all results), which is generated from log files (use tee, or rely on the output of the job scheduler). There are only certain file extensions supported (.txt, .log). If no file matches, then all files (independent of the file extension) are attempted to be parsed (which will go wrong eventually). For legacy reasons (run command is not part of the log, etc.), certain schemes for the filename are eventually parsed and translated as well.

```
./run-qe.sh | tee qe-asrf112-4x16x1.txt
ls -1 *.txt
qe-asrf112-2x32x1.txt
qe-asrf112-4x16x1.txt
./info.sh [-best] /path/to/logs-or-cwd
AUSURF112
                  Nodes R/N T/R Cases/d Seconds NPOOL NDIAG NTG
qe-asrf112-2x32x1 2
                          32
                               2
                                     533
                                          162.35
                                                      2
                                                            25
qe-asrf112-4x16x1 4
                          16
                               4
                                     714
                                           121.82
                                                      2
                                                            25
                                                                32
```

Please note that the number of cases per day (Cases/d) are currently calculated with integer arithmetic and eventually lower than just rounding down (based on 86400 seconds per day). The number of seconds taken are end-to-end (wall time), i.e., total time to solution including any (sequential) phase (initialization, etc.). Performance is higher if the workload requires more iterations (some publications present a metric based on iteration time).

### References

 $[https://software.intel.com/en-us/articles/quantum-espresso-for-the-intel-xeon-phi-processor\%5D(https://software.intel.com/en-us/articles/quantum-espresso-for-the-intel-xeon-phi-processor)\\ [https://www.quantum-espresso.org/Doc/user_guide/node1.html\%5D(https://www.quantum-espresso.org/Doc/user_guide/node1.html)$ 

### TensorFlow™ with LIBXSMM

There is a recipe available for TensorFlow with LIBXSMM (PDF). However, the recipe also contains information about building TensorFlow with Intel MKL and MKL-DNN (see section about Performance Tuning).

## **TensorFlow Serving**

./configure-get.sh vc

For experimentation, there is a recipe available for TensorFlow Serving with LIBXSMM. Please note this recipe is likely outdated and not intended for production use.

# Vc: SIMD Vector Classes for C++

To download, configure, build, and install Vc, one may proceed as shown below.

```
wget --content-disposition --no-check-certificate https://github.com/VcDevel/Vc/archive/refs/tags/1.4.
tar xvf Vc-1.4.2.tar.gz
cd Vc-1.4.2
wget --content-disposition --no-check-certificate https://github.com/hfp/xconfigure/raw/main/configure
chmod +x configure-get.sh
```

Please make the intended compiler available on the command line. For instance, many HPC centers rely on module load.

```
source /opt/intel/compilers_and_libraries_2020.4.304/linux/bin/compilervars.sh intel64
```

For example, to configure and make for an Intel Xeon Scalable processor ("SKX"):

```
make distclean
./configure-vc.sh
cd build; make -j; make install
```

[https://github.com/VcDevel/Vc/releases%5D(https://github.com/VcDevel/Vc/releases) [https://github.com/VcDevel/Vc%5D(https://github.com/VcDevel/Vc)

# **Appendix**

# CP2K MPI/OpenMP-hybrid Execution (PSMP)

## **Overview**

CP2K's grid-based calculation as well as DBCSR's block sparse matrix multiplication (Cannon algorithm) prefer a square-number for the total rank-count (2d communication pattern). This is not to be obfuscated with a Power-of-Two (POT) rank-count that usually leads to trivial work distribution (MPI).

It can be more efficient to leave CPU-cores unused in order to achieve this square-number property rather than using all cores with a "non-preferred" total rank-count (sometimes a frequency upside over an "all-core turbo" emphasizes this property further). Counter-intuitively, even an unbalanced rank-count per node i.e., different rank-counts per socket can be an advantage. Pinning MPI processes and placing threads requires extra care to be taken on a per-node basis to load a dual-socket system in a balanced fashion or to setup space between ranks for the OpenMP threads.

Because of the above-mentioned complexity, a script for planning MPI/OpenMP-hybrid execution (plan.sh) is available. Here is a first example for running the PSMP-binary on an SMP-enabled (Hyperthreads) dual-socket system with 24 cores per processor/socket (96 hardware threads in total). At first, a run with 48 ranks and 2 threads per core comes to the mind (48x2). However, for instance 16 ranks with 6 threads per rank can be better for performance (16x6). To easily place the ranks, Intel MPI is used:

```
mpirun -np 16 \
  -genv I_MPI_PIN_DOMAIN=auto -genv I_MPI_PIN_ORDER=bunch \
  -genv OMP_PLACES=threads -genv OMP_PROC_BIND=SPREAD \
  -genv OMP_NUM_THREADS=6 \
  exe/Linux-x86-64-intelx/cp2k.psmp workload.inp
```

Note: For hybrid codes, I\_MPI\_PIN\_DOMAIN=auto is recommended as it spaces the ranks according to the number of OpenMP threads (OMP\_NUM\_THREADS). It is not necessary and not recommended to build a rather complicated I\_MPI\_PIN\_PROCESSOR\_LIST for hybrid codes (MPI plus OpenMP). To display and to log the pinning and thread affinization at the startup of an application, I\_MPI\_DEBUG=4 can be used with no performance penalty. The recommended I\_MPI\_PIN\_ORDER=bunch ensures that ranks per node are split as even as possible with respect to sockets (e.g., 36 ranks on a 2x20-core system are put in 2x18 ranks instead of 20+16 ranks).

To achieve a similar placement with OpenMPI, ranks are mapped to "execution slots" (--map-by slot) along with specifying the number of processing elements (PE). By default, execution slots are counted in number of physical cores which yields --map-by slot:PE=3 for the same system (mentioned above).

```
mpirun -np 16 --map-by slot:PE=3 \
  -x OMP_PLACES=threads -x OMP_PROC_BIND=SPREAD \
  -x OMP_NUM_THREADS=6 \
  exe/Linux-x86-64-intelx/cp2k.psmp workload.inp
```

Note: Intel MPI's I\_MPI\_PIN\_ORDER=bunch to balance the number of ranks between sockets (see above) appears hard to achieve with OpenMPI therefore an undersubscribed system may not be recommended. To display and to log the pinning and thread affinization at the startup of an application, mpirum --report-bindings can be used.

The end of the next section continues with our example and extends execution to multiple nodes of the above-mentioned system.

## Plan Script

To configure the plan-script, the metric of the compute nodes can be given for future invocations so that only the node-count is required as an argument. The script's help output (-h or --help) initially shows the "system metric" of the computer the script is invoked on. For a system with 48 cores (two sockets, SMP/HT enabled), setting up the "system metric" looks like (plan.sh <num-nodes> <ncores-per-node> <nthreads-per-core> <nsockets-per-node>):

```
./plan.sh 1 48 2 2
```

The script is storing the arguments (except for the node-count) as default values for the next plan (file: \$HOME/.xconfigure-cp2k-plan). This allows to supply the system-type once, and to plan with varying node-counts in a convenient fashion. Planning for 8 nodes of the above kind yields the following output (plan.sh 8):

```
384 cores: 8 node(s) with 2x24 core(s) per node and 2 thread(s) per core

[48x2]: 48 ranks per node with 2 thread(s) per rank (14% penalty)

[24x4]: 24 ranks per node with 4 thread(s) per rank (14% penalty)

[12x8]: 12 ranks per node with 8 thread(s) per rank (33% penalty)

[32x3]: 32 ranks per node with 3 thread(s) per rank (34% penalty) -> 16x16

[18x5]: 18 ranks per node with 5 thread(s) per rank (25% penalty) -> 12x12

[8x12]: 8 ranks per node with 12 thread(s) per rank (0% penalty) -> 8x8

[2x48]: 2 ranks per node with 48 thread(s) per rank (0% penalty) -> 4x4
```

The first group of the output displays POT-style (trivial) MPI/OpenMP configurations (penalty denotes potential communication overhead), however the second group (if present) shows rank/thread combinations with the total rank-count hitting a square number (penalty denotes waste of compute due to not filling each node). For the given example, 8 ranks per node with 12 threads per rank is chosen (8x12) and MPI-executed:

```
mpirun -perhost 8 -host node1, node2, node3, node4, node5, node6, node7, node8 \
   -genv I_MPI_PIN_DOMAIN=auto -genv I_MPI_PIN_ORDER=bunch -genv I_MPI_DEBUG=4 \
   -genv OMP_PLACES=threads -genv OMP_PROC_BIND=SPREAD -genv OMP_NUM_THREADS=12 \
   exe/Linux-x86-64-intelx/cp2k.psmp workload.inp
```

Note: For Intel MPI as well as OpenMPI, mpirun's host-list (mpirun -host) is setup with unique node-names, and this is the only style that is explained in this article. There is a competing style where nodes names are duplicated for the sake of enumerating available ranks (or "execution slots" in case of OpenMPI), which is not exercised in this article.

For OpenMPI, the quantity (per node) of the previously mentioned "execution slots" (measured in number of physical cores) are sometimes not known to OpenMPI (depends on cluster/scheduler setup). For instance, mpirun may be complaining about an attempt to use too many execution slots simply because OpenMPI believes all systems represent a single such slot (instead of 2x24 cores it only "sees" a single core per system). In such case, it is not recommended to "oversubscribe" the system because rank/thread affinity will likely be wrong (mpirun --oversubscribe). Instead, the list of unique nodes names (-host) may be augmented with the number of physical cores on each of the nodes (e.g., ":48" in our case).

```
mpirun -npernode 8 -host node1:48,node2:48,node3:48,node4:48,node5:48,node6:48,node7:48,node8:48 \
    --map-by slot:PE=6 --report-bindings \
    -x OMP_PLACES=threads -x OMP_PROC_BIND=SPREAD -x OMP_NUM_THREADS=12 \
    exe/Linux-x86-64-intelx/cp2k.psmp workload.inp
```

Note: It can be still insufficient to augment the nodes with the expected number of slots (:48). If OpenMPI's mpirun is still complaining, it might be caused and solved by the job scheduler. For example, qsub (PBS) may be instructed with -1 select=8:mpiprocs=48 in the above case (mpirum in this job can use less than 48 ranks per node).

The plan-script also suggests close-by configurations (lower and higher node-counts) that can hit the square-property ("Try also the following node counts"). The example (as exercised above) was to illustrate how the script works, however it can be very helpful when running jobs especially on CPUs with not many prime factors in the core-count. Remember, the latter can be also the case for virtualized environments that reserve some of the cores to run the Hypervisor i.e., reporting less cores to the Operating System (guest OS) when compared to the physical core-count.

[https://github.com/hfp/xconfigure/raw/main/config/cp2k/plan.sh%5D(https://github.com/hfp/xconfigure/raw/main/config/cp2k/plan.sh)

[https://xconfigure.readthedocs.io/cp2k/%5D(https://xconfigure.readthedocs.io/cp2k/)]

[https://software.intel.com/content/www/us/en/develop/articles/pinning-simulator-for-intel-mpi-library.html%5 D(https://software.intel.com/content/www/us/en/develop/articles/pinning-simulator-for-intel-mpi-library.html)