

Moniepoint FT Integration — Full Configuration & Security Guide

This guide documents all required configuration for the Moniepoint / TeamApt FT integration, including:

- PGP configuration
 - RSA configuration (legacy/optional)
 - Environment-variable secret management
 - appsettings.json structure
 - Docker deployment examples
 - Security hardening recommendations
-

1. Recommended appsettings.json

```
{
  "Logging": {
    "LogLevel": {
      "Default": "Information",
      "Microsoft.AspNetCore": "Warning"
    }
  },
  "AllowedHosts": "*",
  "HttpClient": {
    "TimeoutSeconds": 40
  },
  "Credentials": {
    "BaseUrl":
      "https://aptpay-account-transfer.switch-staging.teamapt.com/eft/v1",
    "ApiKey": "",
    "UniqueReferencePrefix": "APT00015",
    "UseWwwRootKeys": false,
    "TimeoutSeconds": 30,
    "ReQueryDelaySeconds": 10,
    "MaxReQueryAttempts": 36,
    "GLAccountName": "Simulator",
    "GLAccountNumber": "11111111111",
    "GLKycLevel": "1",

    // =====
    // PGP CONFIGURATION
    // =====

    "PgpTeamAptPublicKeyPath":
      "MONIEPOINT_PGP_PUBLIC_KEY",

    "PgpInstitutionPrivateKeyPath":
      "MONIEPOINT_PGP_PRIVATE_KEY",

    "PgpInstitutionPrivateKeyPassphrase": "",

    // =====
    // RSA CONFIGURATION (OPTIONAL / LEGACY)
    // =====
  }
}
```

```

    "RsaTeamAptPublicKeyPath":
        "MONIEPOINT_RSA_PUBLIC_KEY",

    "RsaInstitutionPrivateKeyPath":
        "MONIEPOINT_RSA_PRIVATE_KEY",

    "RsaInstitutionPrivateKeyPassphrase": ""
}
}

```

2. Environment Variables

```

# =====
# API KEY
# =====

Credentials__ApiKey=xxxxxxxxxxxxxxxxx

# =====
# PGP KEYS
# =====

MONIEPOINT_PGP_PUBLIC_KEY=-----BEGIN PGP PUBLIC KEY BLOCK-----
...
-----END PGP PUBLIC KEY BLOCK-----

MONIEPOINT_PGP_PRIVATE_KEY=-----BEGIN PGP PRIVATE KEY BLOCK-----
...
-----END PGP PRIVATE KEY BLOCK-----

Credentials__PgpInstitutionPrivateKeyPassphrase=xxxxxxx

# =====
# RSA KEYS (OPTIONAL / LEGACY)
# =====

MONIEPOINT_RSA_PUBLIC_KEY=-----BEGIN PUBLIC KEY-----
...
-----END PUBLIC KEY-----

MONIEPOINT_RSA_PRIVATE_KEY=-----BEGIN ENCRYPTED PRIVATE KEY-----
...
-----END ENCRYPTED PRIVATE KEY-----

Credentials__RsaInstitutionPrivateKeyPassphrase=xxxxxxx

```

3. Configuration Explanation

Setting	Purpose
UseWwwRootKeys	false = read keys from environment variables
PgpTeamAptPublicKeyPath	Environment variable name holding TeamApt PGP public key
PgpInstitutionPrivateKeyPath	Environment variable name holding institution PGP private key
RsaTeamAptPublicKeyPath	Environment variable name holding TeamApt RSA public key
RsaInstitutionPrivateKeyPath	Environment variable name holding institution RSA private key
TimeoutSeconds	HTTP timeout for TeamApt requests
ReQueryDelaySeconds	Delay between status polls
MaxReQueryAttempts	36 attempts × 10 seconds = 6-minute SLA
UniqueReferencePrefix	Transaction reference prefix

ApiKey	TeamApt API authentication key
--------	--------------------------------

4. Docker Deployment Example

```
docker run -d \
-e Credentials__ApiKey="xxxxxxx" \
-e MONIEPOINT_PGP_PUBLIC_KEY="$(cat pgp-public.asc)" \
-e MONIEPOINT_PGP_PRIVATE_KEY="$(cat pgp-private.asc)" \
-e Credentials__PgpInstitutionPrivateKeyPassphrase="xxxxxxx" \
-e MONIEPOINT_RSA_PUBLIC_KEY="$(cat rsa-public.pem)" \
-e MONIEPOINT_RSA_PRIVATE_KEY="$(cat rsa-private.pem)" \
-e Credentials__RsaInstitutionPrivateKeyPassphrase="xxxxxxx" \
moniepoint-ftintegration
```

5. Security Recommendations

Issue	Recommendation
Keys in wwwroot	Do not store keys under wwwroot or static folders
Secrets in appsettings.json	Use environment variables or a secrets manager
Retries on transfers	Disable retries for /ft to avoid duplicate debits
PII logging	Never log full account numbers or decrypted payloads
Time handling	Use DateTime.UtcNow instead of DateTime.Now
Random jitter	Use RandomNumberGenerator instead of Random.Shared