


```
network:
  version: 2
  renderer: networkd
  ethernets:
    enp0s3:
      dhcp4: no
      addresses:
        - 192.168.1.2/24
      routes:
        - to: default
          via: 192.168.1.254
      nameservers:
        addresses: [192.168.1.1]
        search: [vizsgaremek.local]
```

```
~$ sudo chmod 600 /etc/netplan/01-netcfg.yaml
~$ sudo mv /etc/netplan/50-cloud-init.yaml /etc/netplan/50-cloud-init.yaml.old
~$ sudo netplan apply
~$
```

```
GNU nano 7.2 /etc/dh
# dhcpd.conf
#
# Sample configuration file for ISC dhcpd
#
# Attention: If /etc/ltsp/dhcpd.conf exists, that will be used as
# configuration file instead of this file.
#
# option definitions common to all supported networks...
option domain-name "vizsgaremek.local";
option domain-name-servers 192.168.1.1;
#
default-lease-time 600;
max-lease-time 7200;

# The ddns-update-style parameter controls whether or not the server will
# attempt to do a DNS update when a lease is confirmed. We default to the
# behavior of the version 2 packages ('none', since DHCP v2 didn't
# have support for DDNS.)
ddns-update-style none;

# If this DHCP server is the official DHCP server for the local
# network, the authoritative directive should be uncommented.
#authoritative;

# Use this to send dhcp log messages to a different log file (you also
# have to hack syslog.conf to complete the redirection).
#log-facility local7;

# No service will be given on this subnet, but declaring it helps the
# DHCP server to understand the network topology.

#subnet 10.152.187.0 netmask 255.255.255.0 {
#}
```


