

Jobs History
Analyzers
Responders
Organization
CortexTheHive/user

Organization: CortexTheHive

Users
Analyzers Config
Analyzers
Responders Config
Responders

Available analyzers (246)
Refresh analyzers

v
virusotal

Analyzer	Max TLP	Max PAP	Rate Limit	Cache
VirusTotal_DownloadSample_3_1 Version: 3.1 Author: LDO-CERT License: AGPL-V3 Type: Docker, Kubernetes Use VirusTotal to download the original file for an hash.				+ Enable
VirusTotal_GetReport_3_1 Version: 3.1 Author: CERT-BDF, StrangeBee License: AGPL-V3 Type: Docker, Kubernetes Get the latest VirusTotal report for a file, hash, domain or an IP address.				+ Enable
VirusTotal_Rescan_3_1 Version: 3.1 Author: CERT-LDO License: AGPL-V3 Type: Docker, Kubernetes Use VirusTotal to run new analysis on hash.				+ Enable
VirusTotal_Scan_3_1 Version: 3.1 Author: CERT-BDF, StrangeBee License: AGPL-V3 Type: Docker, Kubernetes Use VirusTotal to scan a file or URL.				+ Enable

Activate Windows
Go to Settings to activate Windows.

5 new notification

API QUOTA ALLOWANCES FOR YOUR USER

You own a standard free end-user account. It is not tied to any corporate group and so it does not ha access to Premium services. You are subjected to the following limitations:

Access level	⚠ Limited , standard free public API Upgrade to premium
Usage	Must not be used in business workflows, commercial products or services.
Request rate	4 lookups / min —
Daily quota	500 lookups / day
Monthly quota	15.5 K lookups / month

Gratuites :

🔍 **VirusTotal_GetReport** : C'est l'option la plus importante pour toi. Elle permet de récupérer le dernier rapport d'analyse existant pour un hash, une IP ou une URL sans rien "consommer" de spécial.

🔍 **VirusTotal_Scan** : À utiliser si le rapport n'existe pas encore. Cela envoie l'élément à analyser.

Enable analyzer VirusTotal_GetReport_3_1

Base details

Name VirusTotal_GetReport_3_1

Configuration

[Apply defaults](#)

key * [REDACTED]

API key for Virustotal

polling_interval 60

Define time interval between two requests attempts for the report

rescan_hash_older_than 30

Rescan hash observable if report is older than selected days

highlighted_antivirus

[Add option](#)

1. [REDACTED] ✕

Add taxonomy if selected AV don't recognize observable

download_sample

☒ True ☐ False

Download automatically sample as observable when looking for hash

download_sample_if_high ☒ True ☐ False

[Activate V](#)
[Go to Settings](#)

Rate Limiting

4

Minute



Define the maximum number of requests and the associated unit if applicable.

VirusTotal_GetReport_3_1

Version: 3.1 **Author:** CERT-BDF,
StrangeBee **License:** AGPL-V3 **Type:**
Docker, Kubernetes

TLP:AMBER

PAP:AMBER

4 per Minute

10 Minutes

[Edit](#)

Get the latest VirusTotal report for a file,
hash, domain or an IP address.

Pareil pour :

Enable analyzer VirusTotal_Scan_3_1

Base details

Name

VirusTotal_Scan_3_1

VirusTotal_Scan_3_1

Version: 3.1 **Author:** CERT-BDF,
StrangeBee **License:** AGPL-V3
Type: Docker, Kubernetes

TLP:AMBER

PAP:AMBER

4 per Minute

10 Minutes

[Edit](#)

[Disable](#)

Use VirusTotal to scan a file or
URL.

Q shodan

AnalyzerMax TLPMax PAPRate LimitCache

Shodan_DNSResolve_1_0

Version: 1.0 Author: ANSSI License: AGPL-V3 Type: Docker, Kubernetes

Retrieve domain resolutions on Shodan.

+ Enable

Shodan_Host_1_0

Version: 1.0 Author: Sebastien Larinier @Sebdraven License: AGPL-V3 Type: Docker, Kubernetes

Retrieve key Shodan information on an IP address.

+ Enable

Shodan_Host_History_1_0

Version: 1.0 Author: ANSSI License: AGPL-V3 Type: Docker, Kubernetes

Retrieve Shodan history scan results for an IP address.

+ Enable

Shodan_InfoDomain_1_0

Version: 1.0 Author: ANSSI License: AGPL-V3 Type: Docker, Kubernetes

Retrieve key Shodan information on a domain.

+ Enable

Shodan_ReverseDNS_1_0

Version: 1.0 Author: ANSSI License: AGPL-V3 Type: Docker, Kubernetes

Retrieve ip reverse DNS resolutions on Shodan.

+ Enable

Shodan_Search_2_0

Version: 2.0 Author: Sebastien Larinier @Sebdraven License: AGPL-V3 Type: Docker, Kubernetes

Search query on Shodan

+ Enable

Activate Windows
Go to Settings to activate Windows

Le choix principal : Shodan_Host_1_0

C'est l'analyseur le plus utile pour un compte gratuit.

- **Action :** Cliquez sur **Enable** pour celui-ci.
- **Utilité :** Il récupère toutes les informations connues sur une adresse IP (ports ouverts, services, localisation).
- **Avantage Gratuit :** Les "IP lookups" (recherche par IP directe) ne consomment généralement pas de crédits de recherche sur Shodan, contrairement aux recherches par mots-clés ou filtres.

Enable analyzer Shodan_Host_1_0

Base details

Name

Shodan_Host_1_0

Rate Limiting

1

Second

Define the maximum number of requests and the associated unit if applicable.

Shodan_Host_1_0

Version: 1.0 Author: Sebastien

Larinier @Sebdraven License:

AGPL-V3 Type: Docker,
Kubernetes

TLP:AMBER

PAP:AMBER

1 per Second

10 Minutes

Edit

Disable

Retrieve key Shodan
information on an IP address.

Users

Analizers Config

Analizers

Responders Config

Responders

Available analyzers (246)

Refresh analyzers

Q

abuseip

Analyzer

Max TLP

Max PAP

Rate Limit

Cache

AbuseIPDB_1_1

Version: 1.1 Author: Matteo Lodi; Fabien Bloume, StrangeBee License: AGPL-v3 Type: Docker, Kubernetes

+ Enable

Checks an IP against AbuseIPDB for abuse score, categories, and recent reports.

Enable analyzer AbuseIPDB_1_1

Base details

Name

AbuseIPDB_1_1

Configuration

[Apply defaults](#)

key *

97cd5da29129abc08d9856f6ad721533cb53a4fc3e5f51e3l

API key for AbuseIPDB

days

30

Check for IP Reports in the last X days

Extract
observables

True

False

Set to True to enable automatic observables extraction from analysis reports.

Rate Limiting

1000

Day



Define the maximum number of requests and the associated unit if applicable.

1. Check for IP reports in the last X days

- **Valeur recommandée : 30 ou 90.**
- **Pourquoi ?** Ce paramètre définit la "fraîcheur" des données. Si vous mettez **30**, l'analyseur ne vous montrera que les signalements d'abus ayant eu lieu durant le dernier mois. Pour un usage de sécurité classique, **30 jours** est un bon équilibre pour éviter les faux positifs (une IP peut avoir été malveillante il y a 6 mois mais être saine aujourd'hui).

2. Extract Observables

- **Réglage : False.**
- **Pourquoi ?** Dans le cadre d'un analyzer comme AbuseIPDB, mettre sur True n'apporte pas grand-chose et peut ralentir le traitement. Cette option sert à ce que Cortex essaie de trouver *d'autres* indicateurs (comme des URLs ou des fichiers) à l'intérieur du rapport

renvoyé par AbuseIPDB. Comme AbuseIPDB renvoie principalement des scores et des catégories, il n'y a rien d'utile à extraire. Laissez-le sur **False**.

3. Rate Limiting

- **Valeur recommandée : 1000 par jour (si l'unité est disponible) ou 1 par seconde.**
- **Détails du quota gratuit :** AbuseIPDB est très généreux : vous avez droit à **1 000 vérifications par jour** gratuitement.
- **Configuration :**
 - Si Cortex vous demande un nombre par seconde : mettez **1**.
 - Si vous voulez être sûr de ne jamais dépasser votre quota journalier, vous pouvez mettre **1000** dans la case et sélectionner **day** (jour) si l'option est présente dans le menu déroulant.

AbuseIPDB_1_1
Version: 1.1 Author: Matteo Lodi;
Fabien Bloume, StrangeBee
License: AGPL-v3 Type: Docker,
Kubernetes
Checks an IP against AbuseIPDB
for abuse score, categories, and
recent reports.

TLP:AMBERPAP:AMBER1000 per Day10 Minutes

EditDisable

Organization: CortexTheHive

UsersAnalyzers ConfigAnalyzersResponders ConfigResponders

Available analyzers (246) Refresh analyzers

Q greyno

Analyzer	Max TLP	Max PAP	Rate Limit	Cache
GreyNoise_3_2 Version: 3.2 Author: GreyNoise License: APLv2 Type: Docker, Kubernetes Determine whether an IP has known scanning activity using GreyNoise.				

+ Enable

Enable analyzer GreyNoise_3_2

Base details

Name

GreyNoise_3_2

Extract observables

☐ True ☒ False

Set to True to enable automatic observables extraction from analysis reports.

Rate Limiting

1

Second

Define the maximum number of requests and the associated unit if applicable.

GreyNoise_3_2

Version: 3.2 **Author:** GreyNoise
License: APLv2 **Type:** Docker, Kubernetes

TLP:AMBER

PAP:AMBER

1 per Second

10 Minutes

[Edit](#)

[Disable](#)

Determine whether an IP has known scanning activity using GreyNoise.

← ↻ ⚠ Not secure 192.168.20.4:9002/index.html#/analYZers 🔍 ☆ ⚙ Update ... 🌐 C

Data Types (6)

Select ▼

Analyzer

Search for analyzer description

Search ✖ Clear

Page size

50 / page ▼

AbuseIPDB_1_1 **Version:** 1.1 **Author:** Matteo Lodi; Fabien Bloume, StrangeBee **License:** AGPL-v3

Checks an IP against AbuseIPDB for abuse score, categories, and recent reports.

▶ Run

Applies to:

ip

GreyNoise_3_2 **Version:** 3.2 **Author:** GreyNoise **License:** APLv2

Determine whether an IP has known scanning activity using GreyNoise.

▶ Run

Applies to:

ip

Shodan_Host_1_0 **Version:** 1.0 **Author:** Sebastien Larinier @Sebdraven **License:** AGPL-V3

Retrieve key Shodan information on an IP address.

▶ Run

Applies to:

ip

VirusTotal_GetReport_3_1 **Version:** 3.1 **Author:** CERT-BDF, StrangeBee **License:** AGPL-V3

Get the latest VirusTotal report for a file, hash, domain or an IP address.

▶ Run

Applies to:

file hash domain fqdn ip url

VirusTotal_Scan_3_1 **Version:** 3.1 **Author:** CERT-BDF, StrangeBee **License:** AGPL-V3

Use VirusTotal to scan a file or URL.

▶ Run

Applies to:

file url

Activate Windows

Go to Settings to activate Windows.

On peut effectuer des tests de bon fonctionnement :

Run analysis

TLP *

AMBER



PAP *

AMBER



Data Type



ip



Data *

8.8.8.8

Analyzers



☒ AbuseIPDB_1_1

Cancel

* Required field

Start

Failure

ago

Hide error

Worker cannot be run

```
root@irplatform:/home/templatedebian# getent group cortex
cortex:x:994:
```

```
root@irplatform:/home/templatedebian# usermod -aG docker cortex
```

systemctl restart cortex

Plus de problème :

```
root@irplatform:/home/templatedebian# tail -f /var/log/cortex/application.log
```

```
2026-01-24 19:52:05,810 [INFO] from org.thp.cortex.util.docker.DockerClient in application-analyzer-17 - about to start container a9d380daf898ed9283f02e682d7ee1fd1fd1518cb719368cb88bf796f546716
timeout: 30 minutes
image : ghcr.io/thehive-project/abuseipdb:1
volumes : /tmp/cortex-job-UqtY8Zs8JCsmZ3lWxxL-14612351969736232688
```

[url] example[.]com						
Success	Analyzer: VirusTotal_Scan	Date: a minute ago	User: CortexTheHive/user	TLP:AMBER	PAP:AMBER	View Delete
[url] google[.]com						
Success	Analyzer: VirusTotal_GetReport	Date: 1 minute ago	User: CortexTheHive/user	TLP:AMBER	PAP:AMBER	View Delete
[ip] 8[.]8[.]8[.]8						
Success	Analyzer: Shodan_Host_1	Date: 2 minutes ago	User: CortexTheHive/user	TLP:AMBER	PAP:AMBER	View Delete
[ip] 8[.]8[.]8[.]8						
Success	Analyzer: GreyNoise_3_2	Date: 2 minutes ago	User: CortexTheHive/user	TLP:AMBER	PAP:AMBER	View Delete
[ip] 8[.]8[.]8[.]8						
Success	Analyzer: AbuseIPDB_1_1	Date: 5 minutes ago	User: CortexTheHive/user	TLP:AMBER	PAP:AMBER	View Delete

Par exemple pour virus total on a 1/95 produit qui a classé example.com comme malveillant :

Job details

⚙️ VirusTotal_Scan_3_1

Artifact

[URL] example[.]com

Date

2 minutes ago

TLP

TLP:AMBER

PAP

PAP:AMBER

Status

Success

Report summary

VT:Scan="1/95"

Greynoise nomme 8.8.8.8 comme Google Public DNS

Job details

⚙️ GreyNoise_3_2

Artifact

[IP] 8[.]8[.]8[.]8

Date

4 minutes ago

TLP

TLP:AMBER

PAP

PAP:AMBER

Status

Success

Report summary

GreyNoise:classification="unknown"

GreyNoise:Name="Google Public DNS"

GreyNoise:Type="public_dns"

Pour AbuseIPDB :

Report summary

AbuseIPDB:Is Whitelist="True"

AbuseIPDB:Usage Type="Content Delivery Network"

AbuseIPDB:Abuse Confidence Score="0"

AbuseIPDB:Records="14"