

The format pattern is used as a template to format the message and is copied character by character except for the following special characters, which are replaced by the corresponding value.

%s - message source

%t - message text

%l - message priority level (1 .. 7)

%p - message priority (Fatal, Critical, Error, Warning, Notice, Information, Debug, Trace)

%q - abbreviated message priority (F, C, E, W, N, I, D, T)

%I - message thread identifier (numeric)

%N - node or host name

%U - message source file path (empty string if not set)

%u - message source line number (0 if not set)

%w - message date/time abbreviated weekday (Mon, Tue, ...)

%W - message date/time full weekday (Monday, Tuesday, ...)

%b - message date/time abbreviated month (Jan, Feb, ...)

%B - message date/time full month (January, February, ...)

%d - message date/time zero-padded day of month (01 .. 31)

%e - message date/time day of month (1 .. 31)

%f - message date/time space-padded day of month (1 .. 31)

%m - message date/time zero-padded month (01 .. 12)

%n - message date/time month (1 .. 12)

%o - message date/time space-padded month (1 .. 12)

%y - message date/time year without century (70)

%Y - message date/time year with century (1970)

%H - message date/time hour (00 .. 23)

%h - message date/time hour (00 .. 12)

%a - message date/time am/pm

%A - message date/time AM/PM

%M - message date/time minute (00 .. 59)

%S - message date/time second (00 .. 59)

%i - message date/time millisecond (000 .. 999)

%c - message date/time centisecond (0 .. 9)

%F - message date/time fractional seconds/microseconds (000000 - 999999)

%L - convert time to local time (must be specified before any date/time specifier; does not itself output anything)

%U - convert time to UTC time (must be specified before any date/time specifier; does not itself output anything)

%E - epoch time (UTC, seconds since midnight, January 1, 1970)

%% - percent sign