

Expand view







Accessibility



Best Practices



SEO



Performance

Values are estimated and may vary. The <u>performance</u> score is calculated directly from these metrics. See calculator.

0 - 49



50-89



90-100



METRICS

First Contentful Paint

0.3 s

Total Blocking Time

10 ms

Speed Index

0.4 s

Largest Contentful Paint


0.6 s

Cumulative Layout Shift


0

View Treemap





Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. Learn how to use modern JavaScript FCP LCP




○ Initial server response time was short — Root document took 0 ms


Keep the server response time for the main document short because all other requests depend on it. <u>Learn more about the Time to First Byte metric</u>. [FCP] [LCP]



O Avoids enormous network payloads — Total size was 277 KiB

Large network payloads cost users real money and are highly correlated with long load times. <u>Learn how to reduce payload sizes</u>.






Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn how to minimize main-thread work TBT</u>

Category	Time Spent
Script Evaluation	120 ms
Other	80 ms
Style & Layout	76 ms
Script Parsing & Compilation	14 ms
Parse HTML & CSS	13 ms
Garbage Collection	4 ms
Rendering	2 ms

○ Largest Contentful Paint element − 560 ms

This is the largest contentful element painted within the viewport. <u>Learn more about the Largest Contentful Paint element [LCP]</u>



Phase	% of LCP	Timing
TTFB	23%	130 ms
Load Delay	0%	0 ms
Load Time	0%	0 ms
Render Delay	77%	430 ms


O Avoid long main-thread tasks — 1 long task found


Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay.

Learn how to avoid long main-thread tasks TBT

URL	Start Time	Duration
localhost 1st Party		60 ms
js/main.67c209b5.js (localhost)	582 ms	60 ms

More information about the performance of your application. These numbers don't directly affect the Performance score.





(12.1.0). The latest version is 12.2.1.


O Preload Largest Contentful Paint image
If the LCP element is dynamically added to the page, you should preload the image in order to improve LCP. <u>Learn more about preloading LCP elements</u> . <u>LCP</u>
O User Timing marks and measures
Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. <u>Learn more about User Timing marks</u> .
All text remains visible during webfont loads
Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. <u>Learn more about font-display</u> .
O Minimize third-party usage
Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. Learn how to minimize third-party impact . TBT
Lazy load third-party resources with facades
Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. Learn how to defer third-parties with a facade. TBT
Largest Contentful Paint image was not lazily loaded ^
Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. <u>Learn more about optimal lazy loading</u> . <u>LCP</u>
O Avoid large layout shifts
These are the largest layout shifts observed on the page. Each table item represents a single layout shift, and shows the element that shifted the most. Below each item are possible root causes that led to the layout shift. Some of these layout shifts may not be included in the CLS metric value due to windowing. Learn how to improve CLS CLS

Consider marking your touch and wheel event listeners as passive to improve your page's scroll performance. Learn more about adopting passive event listeners. Avoids document.write() For users on slow connections, external scripts dynamically injected via document.write() can delay page load by tens of seconds. Learn how to avoid document.write(). Avoid non-composited animations Animations which are not composited can be janky and increase CLS. Learn how to avoid noncomposited animations CLS Image elements have explicit width and height Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn how to set image dimensions (CLS) Has a <meta name="viewport"> tag with width or initial-scale A <meta name="viewport"> not only optimizes your app for mobile screen sizes, but also prevents a 300 millisecond delay to user input. Learn more about using the viewport meta tag. Page didn't prevent back/forward cache restoration Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. Learn more about the **bfcache**



These checks highlight opportunities to <u>improve the accessibility of your web app</u>. Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so <u>manual testing</u> is also encouraged.


ARIA



These are opportunities to improve the usage of ARIA in your application which may enhance the experience for users of assistive technology, like a screen reader.

NAMES AND LABELS

(12.1.0). The latest version is 12.2.1.



Failing Elements



<input class="margin-bottom p-inputtext p-component"
name="lastName" required="" data-pc-name="inputtext" datapc-section="root" value="">



form > div.input-container > span.margin-bottom > input.p-inputtext
 <input class="p-inputtext p-component p-inputtext p component" name="dateOfBirth" type="text" role="combobox"
 autocomplete="off" aria-expanded="false" aria autocomplete="none" aria-haspopup="dialog" aria-</pre>

controls="pr_id_5_panel" inputmode="none" data-pc-name="inputtext" data-pcsection="root">




form > div.input-container > span.margin-bottom > input.p-inputtext
 <input class="p-inputtext p-component p-inputtext p component" name="startDate" type="text" role="combobox"
 autocomplete="off" aria-expanded="false" aria autocomplete="none" aria-haspopup="dialog" aria-</pre>


controls="pr_id_6_panel" inputmode="none" data-pc-name="inputtext" data-pcsection="root">



form > fieldset.mb-2 > div.input-container > input.margin-bottom
 <input class="margin-bottom p-inputtext p-component"
 name="street" required="" data-pc-name="inputtext" data-pc-section="root" value="">



div.input-container > div.margin-bottom > div.p-hidden-accessible > input
<input type="text" readonly="" aria-haspopup="listbox" tabindex="0" data-pcsection="input" value="Alabama">



fieldset.mb-2 > div.input-container > span.margin-bottom > input.p-inputnumber-input

<input class="p-inputnumber-input p-inputtext p-component"
role="spinbutton" type="text" inputmode="numeric"
required="" name="zipCode" data-pc-name="inputtext" data-</pre>

pc-section="root" value="">

div.input-container > div.margin-bottom > div.p-hidden-accessible > input
<input type="text" readonly="" aria-haspopup="listbox" tabindex="0" data-pcsection="input" value="Sales">

O Interactive controls are keyboard focusable
Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn how to make custom controls focusable</u> .
O Interactive elements indicate their purpose and state
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn how to decorate interactive elements with affordance hints.</u>
O The page has a logical tab order
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more about logical tab ordering</u> .
O Visual order on the page follows DOM order
DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> <u>about DOM and visual ordering</u> .
O User focus is not accidentally trapped in a region
A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn</u> how to avoid focus traps.
O The user's focus is directed to new content added to the page
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn how</u> to direct focus to new content.
O HTML5 landmark elements are used to improve navigation
Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more about landmark elements.</nav></main>
O Offscreen content is hidden from assistive technology
Offscreen content is hidden with display: none or aria-hidden=true. <u>Learn how to properly hide</u> <u>offscreen content</u> .
O Custom controls have associated labels

Custom controls have ARIA roles
 Custom interactive controls have appropriate ARIA roles. <u>Learn how to add roles to custom controls</u>.

These items address areas which an automated testing tool cannot cover. Learn more in our guide on <u>conducting an accessibility review</u>.

PASSED AUDITS (21) Hide

[aria-*] attributes match their roles

Each ARIA role supports a specific subset of aria—* attributes. Mismatching these invalidates the aria—* attributes. Learn how to match ARIA attributes to their roles.

[aria-hidden="true"] is not present on the document <body>

Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. Learn how aria-hidden affects the document body.

[role]s have all required [aria-*] attributes

Some ARIA roles have required attributes that describe the state of the element to screen readers. <u>Learn more about roles and required attributes</u>.

[aria-*] attributes have valid values

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <u>Learn</u> more about valid values for ARIA attributes.

● [aria-*] attributes are valid and not misspelled

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <u>Learn</u> more about valid ARIA attributes.

[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximumscale1 attribute is not less than 5. Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more about the viewport meta tag. ARIA attributes are used as specified for the element's role Some ARIA attributes are only allowed on an element under certain conditions. Learn more about conditional ARIA attributes. [aria-hidden="true"] elements do not contain focusable descendents Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn how aria-hidden affects focusable elements. Elements use only permitted ARIA attributes Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. Learn more about prohibited ARIA roles. [role] values are valid ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more about valid ARIA roles. Background and foreground colors have a sufficient contrast ratio Low-contrast text is difficult or impossible for many users to read. Learn how to provide sufficient color contrast. Document has a <title> element Warning: Results may not display properly. Report was created with an earlier version of Lighthouse (12.1.0). The latest version is 12.2.1.

<html> element has a [lang] attribute If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute. <html> element has a valid value for its [lang] attribute Specifying a valid <u>BCP 47 language</u> helps screen readers announce text properly. <u>Learn how to use</u> the lang attribute. Links have a discernible name Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn how to make links accessible. No element has a [tabindex] value greater than 0 A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more about the tabindex attribute. Touch targets have sufficient size and spacing. Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. Learn more about touch targets. Heading elements appear in a sequentially-descending order Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more about

Warning: Results may not display properly. Report was created with an earlier version of Lighthouse (12.1.0). The latest version is 12.2.1.

heading order.

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. <u>Learn more about ARIA roles</u>.

Deprecated ARIA roles were not used

Deprecated ARIA roles may not be processed correctly by assistive technology. <u>Learn more about deprecated ARIA roles</u>.

NOT APPLICABLE (34)
Hide

[accesskey] values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. <u>Learn more about access keys</u>.

O Elements with role="dialog" or role="alertdialog" have accessible names.

ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. <u>Learn how to make ARIA dialog elements more accessible</u>.

ARIA input fields have accessible names

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more about input field labels</u>.

ARIA meter elements have accessible names

When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn how to name meter</u> <u>elements</u>.

ARIA progressbar elements have accessible names

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn how to label progressbar elements</u>.

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. <u>Learn more about roles and required children elements</u> .	
[role]s are contained by their required parent element	
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. <u>Learn more about ARIA roles and required parent element</u> .	
Elements with the role=text attribute do not have focusable descendents.	,
Adding role=text around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the role=text attribute.	
ARIA toggle fields have accessible names	
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more about toggle fields</u> .	
 ARIA tooltip elements have accessible names 	
When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn how to name tooltip elements</u> .	
 ARIA treeitem elements have accessible names 	
When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about labeling treeitem elements.	
The page contains a heading, skip link, or landmark region	,
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. <u>Learn more about bypass blocks</u> .	
<pre><dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements.</pre></td><td>,</td></tr><tr><td>When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn how to structure definition lists correctly.</td><td></td></tr><tr><td>Warning: Results may not display properly. Report was created with an earlier version of Lighthouse</td><td></td></tr></tbody></table></script></dd></dt></dl></pre>	

Definition list items (<dt> and <dd>) must be wrapped in a parent <dl> element to ensure that screen readers can properly announce them. Learn how to structure definition lists correctly.</dl></dd></dt>
O ARIA IDs are unique
The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. <u>Learn how to fix duplicate ARIA IDs</u> .
O No form fields have multiple labels
Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <u>Learn how to use form labels</u> .
O <frame/> or <iframe> elements have a title</iframe>
Screen reader users rely on frame titles to describe the contents of frames. <u>Learn more about</u> <u>frame titles</u> .
<pre><html> element has an [xml:lang] attribute with the same base language as the [lang] attribute.</html></pre>
If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. <u>Learn more about the lang attribute</u> .
O Image elements have [alt] attributes
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more about the alt attribute</u> .
O Image elements do not have [alt] attributes that are redundant text.
Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. Learn more about the alt attribute.
O Input buttons have discernible text.
Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. <u>Learn more about input buttons</u> .
<pre> <input type="image"/> elements have [alt] text</pre>

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. Learn how to make links distinguishable.
Lists contain only elements and script supporting elements (<script> and <template>).</td></tr><tr><td>Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more about proper list structure.</td></tr><tr><td>List items () are contained within , or <menu> parent elements</td></tr><tr><td>Screen readers require list items () to be contained within a parent , or <menu> to be announced properly. Learn more about proper list structure.</td></tr><tr><td>The document does not use <meta http-equiv="refresh"></td></tr><tr><td>Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more about the refresh meta tag</u>.</td></tr><tr><td>O sobjects alemente have alternate toyt</td></tr><tr><td>O <object> elements have alternate text</td></tr><tr><td>Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps screen readers convey meaning to users. Learn more about alt text for object elements.</td></tr><tr><td>Screen readers cannot translate non-text content. Adding alternate text to <object> elements</td></tr><tr><td>Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps screen readers convey meaning to users. Learn more about alt text for object elements.</td></tr><tr><td>Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps screen readers convey meaning to users. Learn more about alt text for object elements. O Select elements have associated label elements.</td></tr><tr><td>Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps screen readers convey meaning to users. Learn more about alt text for object elements. O Select elements have associated label elements. A Form elements without effective labels can create frustrating experiences for screen reader users. Learn more about the select element.</td></tr><tr><td>Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps screen readers convey meaning to users. Learn more about alt text for object elements. Select elements have associated label elements. Form elements without effective labels can create frustrating experiences for screen reader users. Learn more about the select element. Skip links are focusable. All links are focusable.</td></tr></tbody></table></script>

Screen readers have features to make navigating tables easier. Ensuring cells using the [headers] attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more about the headers attribute.

elements and elements with [role="columnheader"/"rowheader"] have data cells they
describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more about table headers</u>.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn how to use the lang attribute</u>.

<video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. <u>Learn more about video captions</u>.



Best Practices


TRUST AND SAFETY

Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. <u>Learn how to use a CSP to prevent XSS</u>

Description	Directive	Severity
No CSP found in enforcement mode		High

GENERAL



PASSED AUDITS (14)

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u>, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. <u>Learn more about HTTPS</u>.

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. Learn more about deprecated APIs.

Avoids third-party cookies

Support for third-party cookies will be removed in a future version of Chrome. <u>Learn more about phasing out third-party cookies</u>.

Allows users to paste into input fields

Preventing input pasting is a bad practice for the UX, and weakens security by blocking password

Avoids requesting the geolocation permission on page load Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn how to provide responsive images. Has a <meta name="viewport"> tag with width or initial-scale A <meta name="viewport"> not only optimizes your app for mobile screen sizes, but also prevents a 300 millisecond delay to user input. Learn more about using the viewport meta tag. Page has the HTML doctype Specifying a doctype prevents the browser from switching to quirks-mode. Learn more about the doctype declaration. Properly defines charset A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more about declaring the character encoding. Warning: Results may not display properly. Report was created with an earlier version of Lighthouse

(12.1.0). The latest version is 12.2.1.

failures and other browser concerns. Learn more about this errors in console diagnostic audit

No issues in the Issues panel in Chrome Devtools

Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. Learn more about source maps.

URL Map URL

localhost 1st Party

...js/main.67c209b5.js (localhost) ...js/main.67c209b5.js.map (localhost)

NOT APPLICABLE (2)

O Redirects HTTP traffic to HTTPS

Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u>.

your users. <u>cean more</u>.

Document uses legible font sizes

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. <u>Learn more about legible font sizes</u>.

SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on Core Web Vitals. Learn more about Google Search Essentials.

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

Structured data is valid

^

Run the <u>Structured Data Testing Tool</u> and the <u>Structured Data Linter</u> to validate structured data. Learn more about Structured Data.

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (8)

Page isn't blocked from indexing

Search engines are unable to include your pages in search results if they don't have permission to crawl them. <u>Learn more about crawler directives</u>.

Document has a <title> element

^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more about document titles</u>.

Document has a meta description

^

Meta descriptions may be included in search results to concisely summarize page content. <u>Learn</u> more about the meta description.

Page has successful HTTP status code

.

Pages with unsuccessful HTTP status codes may not be indexed properly. <u>Learn more about HTTP status codes</u>.

Links are crawlable

Search engines may use h ref attributes on links to crawl websites. Ensure that the h ref attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. Learn how to make links crawlable

robots.txt is valid

robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. Learn more about robots.txt.

Document has a valid hreflang

hreflang links tell search engines what version of a page they should list in search results for a given language or region. Learn more about hreflang.

O Image elements have [alt] attributes
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the alt attribute.

O Document has a valid rel=canonical
Canonical links suggest which URL to show in search results. Learn more about canonical links.

Captured at Oct 9, 2024, 10:08 AM Emulated Desktop with Lighthouse Single page session

GMT+2 12.1.0

Initial page load Custom throttling Using Chromium 128.0.0.0 with