COMPUTER NETWORKS · COURSE PROJECT REPORT

Mini-Meet

A two-to-four-party video conferencing application written in C: our own signalling server and protocol, STUN-based NAT traversal, raw UDP media with jitter buffer and loss repair, congestion-aware rate control and end-to-end encryption, evaluated under emulated network impairment.

Team: Suvansh Choudhary (25BAI0252) · Priyam Sharma (25BAI0159) · Avika Agarwal (25BBS0057)

Project 16: Video Conferencing Application (Mini-Meet) · Group B · CO4, CO5 · Modules 4 and 5

Platforms: Windows (MinGW-w64) and Linux · Language: C11 · Tools: raw UDP + codecs (VP8, Opus), STUN, Python, tc netem, Git

Source code and data: https://github.com/TowVansh/mini-meet · November 2026

Abstract

Mini-Meet is a 2–4 person audio/video calling application implemented from the socket level up in C. A TCP signalling server written by us introduces the participants. Each client discovers its public address with STUN and traverses NAT with UDP hole punching. VP8 video and Opus audio then flow directly between peers in our own RTP-style framing layer over UDP, encrypted end to end with X25519 key agreement and ChaCha20-Poly1305. The receiver uses an adaptive, timestamp-driven jitter buffer, and repairs or conceals losses with NACK retransmission, keyframe requests and Opus FEC/PLC. RTCP receiver reports drive an AIMD rate controller with slow start, a delay-based congestion signal and feedback-starvation detection.

We evaluated the system in 28 runs over Linux network namespaces with per-direction `tc netem` impairment, plus a jitter-buffer on/off experiment, a single call through changing bandwidth, a 4-person mesh test and a real call between two different networks. Random loss up to 5 % is invisible to the user. Without rate control, a 1 Mbit/s bottleneck drives RTT above 10 s (bufferbloat). With it the call stays at 20 fps with a 3 ms RTT. The jitter buffer reduces audio concealment under ±30 ms jitter from 88 % to 0.1 %, at the cost of about 140 ms of added delay. The real cross-network call connected peer-to-peer through both NATs (`srflx↔srflx`).

Contents

1. Introduction and objectives
2. System architecture
3. Signalling protocol
4. Media framing layer
5. NAT traversal
6. Jitter buffer and loss repair
7. Feedback and rate control
8. Security
9. Implementation and testing
10. Evaluation
11. Discussion
12. Limitations and future work
13. Conclusion

Appendix A. Syllabus coverage
Appendix B. How to build and run
References

1. Introduction and Objectives

Video calls combine two very different kinds of traffic. Call setup needs a few hundred bytes that must arrive reliably and in order. Media needs a continuous stream of time-critical packets, where a late packet is as useless as a lost one. The project builds both halves ourselves and measures how a real-time stream behaves when the network loses, delays, reorders or throttles packets.

1.1 Expected outcome mapping

Each expected outcome of the brief, mapped to what was delivered. All code, data and documents are at https://github.com/TowVansh/mini-meet.

Brief asks for	Delivered
Working multi-party call with audio and video	2–4 participants, full mesh, VP8 640×480 at 20 fps + Opus 32 kbps; Windows and Linux
Custom signalling server and documented protocol	`mm-server`, a line-based TCP protocol (Section 3; `docs/PROTOCOL.md`)
NAT traversal across separate networks (STUN)	Own STUN client and server, UDP hole punching; Wi-Fi ↔ mobile hotspot connected `srflx↔srflx`
Call quality under loss, jitter and bandwidth limits: how the system degrades and adapts	28 netem runs with rate control off/on, a jitter-buffer on/off experiment, and one call through changing bandwidth (Section 10)
Architecture: media path vs signalling path	Section 2; `docs/ARCHITECTURE.md`
Beyond the brief	End-to-end media encryption, adaptive jitter buffer, live dashboard, recorded-file streaming, 72 unit-test checks, prebuilt Windows release

1.2 Milestones

Milestone	Result
1. Signalling server and two-party media path	`mm-server` + RTP-style VP8/Opus over UDP (Sections 3, 4)
2. NAT traversal and multi-party topology	STUN + hole punching (Section 5); full mesh of up to 4, all 12 streams verified (Section 10.6)
3. Quality instrumentation and adaptation behaviour	Per-second RTCP-based statistics; jitter buffer, loss repair and AIMD rate control (Sections 6, 7)
4. Impairment evaluation, report and viva	`tc netem` evaluation (Section 10), this report

Required tools: raw UDP + codecs (our framing over UDP with VP8 and Opus), STUN (own client and server), Python (evaluation analysis; a first Node.js/WebRTC prototype was used for comparison), `tc netem`, and Git.

2. System Architecture

The system consists of three programs: `mm-server` (signalling), `mm-stun` (an optional STUN server) and `mm` (the call client). All networking is our own code on plain sockets. Libraries are used only for capture and decoding of camera and file input (FFmpeg), the codecs (libvpx, libopus), the window and speakers (SDL2), and the cryptographic primitives (libsodium).




Figure 1. Signalling goes through the server over TCP. Media goes directly between peers over UDP.

	Signalling path	Media path
Purpose	Find peers, exchange network candidates and public keys	Carry audio and video
Endpoints	client ↔ `mm-server`	client ↔ client (full mesh)
Transport	TCP, newline-delimited text	UDP: RTP + RTCP + STUN on one port
Volume	A few hundred bytes per call setup	0.1–1.2 Mbit/s per stream, continuous
Reliability need	Every line in order, so TCP fits	Late = useless, so UDP with selective repair
If the server dies	New joins fail	Running calls continue

Client threads. *main* runs the SDL window and events. *net* runs one `select()` loop over the TCP and UDP sockets plus all timers (ICE checks, jitter-buffer playout, RTCP, NACK, statistics). *video-in* and *audio-in* capture and encode. One mutex protects the peer table and the sender state.

3. Signalling Protocol

TCP is a byte stream, so a single `recv()` may return half a message or several. Every message is therefore one ASCII line ending in `\n`, at most 512 bytes, made of space-separated tokens. The receiver buffers bytes until a newline completes a line. Because the protocol is plain text, it can be driven by hand with `telnet`.

Client → server	Meaning
`JOIN <room> <name>`	Enter a room (max 4)
`CAND <to> <type> <ip> <port>`	Send a network candidate
`KEY <to> <64 hex>`	X25519 public key
`LEAVE` · `PING`	Leave · keep-alive (5 s)

Server → client	Meaning
`JOINED <id> <room> [id:name…]`	Accepted, who is present
`PEER_JOINED` · `PEER_LEFT`	Membership changes
`CAND` · `KEY` `<from> …`	Relayed, `to` → `from`
`PONG` · `ERROR <code> <text>`	Reply · rejection


```
PC3 (newcomer)            mm-server                       PC1
|-- JOIN demo pc3 ------------>|                            |
|<- JOINED c1 demo a1:pc1 -----|-- PEER_JOINED c1 pc3 -------->|
|-- CAND a1 host/srflx ...  -->|-- CAND c1 host/srflx ... ---->|
|-- KEY a1 3f9a...c41d ------->|-- KEY c1 3f9a...c41d ------->|
|<- CAND/KEY a1 ... -----------|<- CAND/KEY c1 ... ------------|
|==== STUN checks to every candidate, both directions (hole punching) ====|
|==== RTP/RTCP media, encrypted, peer-to-peer over UDP ==================|
```

Validation. The server rejects lines over 512 bytes (and closes the connection), names outside `[A-Za-z0-9_-]{1,32}`, malformed candidates and keys, and relaying to a peer outside the sender's room. It runs as a single thread with one `select()` loop (no locks), with `FD_SETSIZE` raised on Windows.

Liveness. The server drops a connection that has been silent for 20 s, and its peers receive `PEER_LEFT`. Testing showed that under heavy bufferbloat a client's PINGs can be stuck in the same queue as its media, so the server times it out while the call is still working. A client therefore keeps a peer for as long as that peer's media keeps arriving (it is removed 3 s after its packets stop), and it removes any peer silent for 30 s on its own, without the server.

4. Media Framing Layer

STUN, RTP and RTCP share one UDP socket and are demultiplexed by their first byte (RFC 7983). STUN starts with 0–3 and carries the magic cookie `0x2112A442`. RTP and RTCP start with 128–191, and RTCP is recognised by packet type 200–206 in the second byte (RFC 5761). The source address then identifies the peer, and the payload type identifies the stream.



PT	Payload	Clock	Rules
96	VP8	90 kHz	1-byte descriptor: `S` = first packet of a frame, `K` = keyframe. Marker bit `M` = last packet of the frame. Payload ≤ 1160 bytes, so IP packets stay around 1200 bytes, under the MTU.
97	VP8 retransmission	90 kHz	Same bytes and sequence number as the original. The separate PT keeps repairs out of the loss statistics.
111	Opus	48 kHz	One 20 ms mono frame per packet, 32 kbps, in-band FEC. The timestamp advances by 960 per packet.

- **Sequence number**: random start, +1 per packet per stream, wraps at 65535. Wrap-aware comparison is `(int16_t)(a - b) > 0`.
- **Timestamp**: media (capture) time, not send time. All packets of a video frame share it. This is what lets the receiver restore the sender's timing.
- **SSRC**: random per stream at start-up.
- **RTCP**: Sender Report every second with one report block per received stream; Generic NACK (205/1); PLI (206/1).

5. NAT Traversal

A NAT rewrites the source address of outgoing packets and admits incoming packets only if they match a mapping it created. Two peers behind NAT therefore cannot simply send to each other. Mini-Meet uses a simplified ICE (RFC 8445):

1. **Gather**: the *host* candidate is the LAN address. The *server-reflexive* (srflx) candidate is the public IP:port that a STUN Binding request reports in `XOR-MAPPED-ADDRESS`. The address is XORed with the magic cookie so that NAT helpers do not rewrite it.
2. **Exchange**: candidates are sent as `CAND` lines through the signalling server.
3. **Check (hole punching)**: both peers send STUN Binding requests to every candidate of the other every 100 ms, with `USERNAME = "<their-id>:<my-id>"`. Each outgoing packet opens a mapping in the sender's own NAT, so the other side's packets can come back in. A request from an unknown address becomes a *peer-reflexive* candidate.
4. **Select and keep alive**: the first candidate that answers carries the media. A Binding request every 2.5 s keeps the NAT mappings from expiring.

Hole punching fails when both sides (or one symmetric side and one port-restricted side) are behind a **symmetric NAT**, which assigns a new public port per destination. The client detects this after 15 s and reports that a TURN relay would be needed.

Live test	Candidates	Selected pair	Result
Laptop on college Wi-Fi (private 172.16.x, public 36.255.16.51) ↔ laptop on a mobile hotspot (private 10.129.x, public 152.57.86.31)	host + srflx on both	**srflx→srflx**, all 1404 samples	Connected 3 times (ICE 99–752 ms); about 9 minutes of calls

6. Jitter Buffer and Loss Repair

6.1 Playout clock (jitter buffer)

Packets leave at even intervals (20 ms audio frames, 50 ms video frames) but arrive unevenly. Playing them on arrival gives choppy output. For every arriving packet the receiver records

$$\textit{offset} = \text{arrival time} - \text{media time (the RTP timestamp in µs)}, \quad \text{and plays media time } T \text{ at } \quad T + \mathrm{P95}(\text{last 64 offsets}).$$

About 95 % of packets are therefore already present when their turn comes, and playout follows the sender's pace rather than the network's. The delay adapts by itself: a few milliseconds on a clean link, about 140 ms under ±30 ms jitter and about 220 ms under ±60 ms. Using the 95th percentile instead of the maximum trades ~5 % late packets (which concealment hides) for much lower latency. A video frame is decoded only when it is complete **and** due. Audio adds a 25 ms margin so that the next packet, which carries the FEC copy, is usually present. A late packet is dropped but still updates the clock, which is how the buffer learns to grow.

6.2 Loss repair and concealment

Mechanism	How it works
Gap → NACK	A sequence gap puts the missing numbers on a list. After a reordering wait of about 2 × jitter (5–80 ms) they are requested with RTCP Generic NACK (packet ID + 16-bit bitmask, up to 17 losses per entry), resent every 1.5 × RTT, at most 4 tries.
Retransmission	The sender keeps the last 1024 video packets and resends them as PT 97: selective-repeat ARQ with a deadline.
Skip + PLI	A frame not repaired within max(120 ms, 1.5 × RTT + 40 ms) is skipped. Later frames reference it, so the receiver waits for a keyframe and requests one with PLI (rate-limited to at least 1.5 × RTT apart). The visible effect is a freeze.
Opus FEC / PLC	A missing audio frame is rebuilt from the in-band FEC copy in the next packet if that has arrived, otherwise packet loss concealment extrapolates it. The encoder is told the measured loss rate so it can size the FEC.
Metrics	Per second: `playout_sd_ms` (standard deviation of shown-frame intervals), `jb_delay_ms`, freezes (a gap longer than max(3 × average, average + 150 ms)), audio concealment %.

7. Feedback and Rate Control

7.1 Receiver feedback (RTCP, RFC 3550)

- **Loss**: expected = extended highest sequence − base + 1; lost = expected − received; fraction lost = $(\text{lost}_{\text{interval}} \times 256) / \text{expected}_{\text{interval}}$.
- **Interarrival jitter**: $D = (R_j - R_i) - (S_j - S_i)$; $J \leftarrow J + (|D| - J)/16$, in timestamp units.
- **Round-trip time**: RTT = A − LSR − DLSR, where A is the time a report arrives, LSR is our Sender Report time that it echoes, and DLSR is how long the peer held it. Both A and LSR come from our own clock, so no clock synchronisation is needed. Example: SR sent at 10.000 s, held 0.050 s, report arrives at 10.130 s, so RTT = 80 ms.

7.2 AIMD controller

Level	0	1	2	3 (start)	4	5
Video bitrate	1200 kbps	800	500	300	180	100
Resolution	640×480	640×480	480×360	320×240	320×240	160×120

- **Congestion** (loss > 8 % or queuing delay > 120 ms): drop two levels (multiplicative decrease). **Clean** (loss < 2 % and queuing delay < 40 ms) three reports in a row: climb one level (additive increase), giving the TCP-Reno sawtooth.
- **Queuing delay** = smoothed RTT − minimum smoothed RTT of the last 10 s, capped at 250 ms above the best RTT ever seen. This is the delay-based idea of TCP Vegas, BBR and WebRTC GCC: back off when a queue starts to fill, before packets are dropped. The window lets a longer path become the new baseline, and the cap stops a standing queue from becoming "normal".
- **Slow start**: begin at 300 kbps and climb one level per clean report until the first congestion signal.
- **Feedback starvation**: reports normally arrive every second. If none arrive for 2.5 s they are probably stuck in the same queue as the media, so the silence itself is treated as congestion.
- Bitrate changes are applied live (`vpx_codec_enc_config_set`). A resolution change restarts the encoder with a keyframe. In a mesh the encoder serves the worst receiver.

8. Security

- **End-to-end media encryption.** Each client creates a fresh X25519 key pair and sends its public key through signalling. `crypto_kx` derives the same two 256-bit session keys (one per direction) on both peers. The server only ever sees public keys, so it cannot decrypt media. Every RTP payload is sealed with ChaCha20-Poly1305 (AEAD). The 12-byte header stays readable, because demultiplexing and sequence numbers need it, but it is authenticated. The nonce is SSRC || seq || PT || timestamp, which is unique per packet. RTCP is encrypted the same way with an index. A tampered packet fails the tag check and is dropped.
- **Man-in-the-middle.** A malicious server could substitute keys, so both screens show a short **safety code** (a hash of both public keys) for the users to compare. Key pairs are never stored, which gives forward secrecy across calls.
- **Server hardening.** Line-length limit (DoS), name and candidate validation, relaying only within a room, 4-person cap, idle timeout. STUN checks carry peer IDs in `USERNAME`.
- **Not covered.** No TLS on the signalling channel (keys are protected by the safety code instead), no replay window on media, and no message integrity on STUN checks.

9. Implementation and Testing

Module	Files	Role
Portable sockets	`src/common/net.c`	One API over Winsock and BSD sockets (`WSAStartup`/`closesocket`/`ioctlsocket` vs `close`/`fcntl`), TCP/UDP helpers, `SIO_UDP_CONNRESET` fix
Signalling	`proto.c`, `mm_server.c`, `sig.c`	Line framing, rooms, relay, heartbeat, client side
STUN / ICE	`stun.c`, `mm_stun.c`, `ice.c`	RFC 5389 encode/decode, STUN server, candidates, checks
RTP / RTCP	`rtp.c`	Headers, SR/NACK/PLI, RFC 3550 statistics, playout clock
Send side	`media_in.c`	FFmpeg capture or file (paced), VP8/Opus encoding, packetisation, retransmission history
Receive side	`media_out.c`	Jitter buffers, NACK/PLI, decoding, freeze detection, SDL window, audio mixing
Control / security	`cc.c`, `crypto.c`, `netloop.c`	AIMD controller, encryption, packet dispatch, statistics

About **3,900 lines of C11**, built with one Makefile on Linux (gcc) and Windows (MSYS2 MinGW-w64). A prebuilt Windows release with all DLLs runs without installation. `make test` runs **72 unit-test checks** covering line framing, STUN encoding (including XOR mapping), RTP headers and sequence wrap-around, RTCP round trips (SR, NACK bitmask, PLI, 24-bit sign extension), RFC 3550 loss and jitter arithmetic, the playout clock, the AIMD controller (slow start, windowed baseline, standing queue), encryption, and tamper detection. System-level tests: 2- and 4-party calls on Windows and Linux, webcam and microphone, recorded-file streaming, and the cross-network call.

10. Evaluation

10.1 Method

Two Linux network namespaces (`mmA` 10.10.0.1, `mmB` 10.10.0.2) are joined by a veth pair and behave like two separate hosts. `tc netem` runs on both veth ends, so each direction is impaired separately, like a real access link. Clients send a built-in test pattern (VP8, up to 640×480, 20 fps) and a tone (Opus), so every run has identical input. Each run is 10 s clean, then the profile applied mid-call, then 45 s recorded, for 14 profiles × adaptation off (fixed 1200 kbps) / on. Values are steady-state medians (means for loss and concealment). Freezes are summed over both receivers.

Profile	netem (per direction)	Profile	netem (per direction)
loss1/5/10/20	`loss N%`	jitter30/60	`delay 100ms ±30/60ms`, normal
burst5	Gilbert-Elliott bursty loss	rate2m/1m/500k/250k	`rate N`, 1000-packet FIFO
delay100	`delay 100ms`	combo	80 ms ±20 ms, 3 % loss, 1 Mbit/s

10.2 Results

Table 1. Steady-state results (t ≥ 15 s). "adapt" = rate controller off (fixed 1200 kbps) or on. Highlighted rows: bandwidth-limited cases where rate control decides the outcome.

profile	adapt	video kbps	fps	height	loss %	jitter ms	RTT ms	freezes	audio conc. %	playout sd ms	audio buffer ms
baseline	off	1205	20	480	0.0	0.1	0.2	0	0.0	1.4	27
baseline	on	1202	20	480	0.0	0.1	0.7	0	0.0	1.5	27
loss1	off	1212	20	480	1.0	0.1	0.3	0	0.0	2.2	27
loss1	on	1211	20	480	0.9	0.1	0.2	0	0.0	1.9	27
loss5	off	1224	20	480	4.9	0.1	0.3	0	0.2	16.2	27
loss5	on	685	20	360	5.1	0.2	0.3	0	0.4	16.3	26
loss10	off	1218	20	480	9.9	0.1	0.9	2	1.3	23.2	27
loss10	on	106	20	120	9.2	0.3	0.3	0	1.1	23.4	26
loss20	off	1222	19	480	19.8	0.1	0.2	23	4.0	38.0	27
loss20	on	104	20	120	20.8	0.2	0.3	15	3.2	40.8	26
burst5	off	1188	20	480	2.5	0.1	4.6	0	0.7	3.8	27
burst5	on	1224	20	480	2.1	0.1	4.0	0	0.5	2.3	26
delay100	off	1218	20	480	0.0	0.1	200	0	0.0	1.4	27
delay100	on	580	20	360	0.0	0.2	200	0	0.0	1.0	26
jitter30	off	1372	20	480	1.0	33.5	187	1	0.1	12.4	140
jitter30	on	278	20	240	0.8	33.8	200	0	0.1	4.7	143
jitter60	off	1634	20	480	1.7	65.7	194	4	0.2	22.7	222
jitter60	on	213	20	240	1.5	70.5	211	3	0.1	8.1	220
rate2m	off	1228	20	480	0.0	7.8	47	0	0.0	1.3	56
rate2m	on	1226	20	480	0.0	7.6	39	0	0.0	1.5	56
rate1m	off	923	15	480	13.6	13.6	10513	0	34.1	2.1	387
rate1m	on	198	20	240	0.0	3.4	2.8	0	2.7	1.2	28
rate500k	off	446	0	480	39.6	22.9	19414	2	49.0	5.8	476
rate500k	on	188	20	120	0.0	3.2	9.8	0	11.7	2.5	38
rate250k	off	229	4	480	24.7	31.6	17373	2	74.5	7.0	5073
rate250k	on	164	9	120	1.0	18.8	11707	6	34.8	5.2	476
combo	off	924	0	480	13.8	13.9	10054	9	33.0	2437	349
combo	on	231	20	240	2.7	14.0	199	64	0.3	41.6	82

10.3 Bandwidth limits: bufferbloat vs rate control




Figure 2. A 1 Mbit/s cap applied at 9 s. Fixed rate (blue): the 1000-packet queue fills, RTT climbs steadily past 10 s, and once the queue is full loss sets in and video stops. Adaptive (green in the top panel, orange below): the controller backs off within a few seconds (RTT briefly peaks around 1.4 s), then probes back up in a sawtooth with RTT in milliseconds.

10.4 Jitter buffer: playout smoothness under induced jitter

The jitter profiles were repeated with the jitter buffer turned off (`--no-jb`: playout follows the fastest packet with only a 25 ms margin).

Jitter (each way)	Rate control	Buffer	Audio concealed	Video playout sd	Freezes	Buffer delay
±30 ms	off	off	87.9 %	25.2 ms	1	25 ms
±30 ms	off	**on**	**0.1 %**	**12.4 ms**	1	140 ms
±60 ms	off	off	83.6 %	40.7 ms	13	25 ms
±60 ms	off	**on**	**0.2 %**	**22.7 ms**	4	222 ms
±60 ms	on	off	84.2 %	53.0 ms	32	25 ms
±60 ms	on	**on**	**0.1 %**	**8.1 ms**	3	220 ms

Without a buffer most audio frames arrive after their 20 ms slot and must be concealed, and video frames are shown as unevenly as they arrive. The adaptive buffer brings concealment to about 0 %, at least halves the playout spread and cuts freezes (32 → 3 in the worst case). It pays for this with 140–220 ms of added delay, the fundamental smoothness-versus-latency trade-off of a jitter buffer.

10.5 Bitrate adaptation across changing network conditions




Figure 3. One call through clean → 2 Mbit/s → 1 Mbit/s → 500 kbit/s → 1 Mbit/s → clean (phase lines marked). The adaptive sender follows every change: it cuts within ~5 s of each drop, probes upward in a sawtooth, and returns to 1200 kbps ~17 s after the network clears. RTT peaks at about 1 s right after each drop. The fixed-rate sender reaches a 14 s RTT and 0–15 fps, and only recovers when the network is clean again.

10.6 Further results

- **4-person mesh** (Windows, release build): all 12 directed streams received at 640×480, 20 fps, ~1190–1220 kbps each, playout spread ~2 ms. Each client uploads three copies (~3.6 Mbit/s).
- **Real cross-network call**: `srflx→srflx`, median RTT 85 ms, loss < 0.6 %. The mobile hotspot's uplink buffered in bursts (RTT spikes to 1.15 s), and the controller followed them down and back up.
- **Recorded media** (`--file`, H.264 + AAC, looped): streamed in real time on Linux and Windows; the viewer received 640×480 at 20 fps with 0 % concealment.




Figure 4. Audio concealment by impairment profile, rate control off vs on. Bandwidth caps without rate control are the only conditions that ruin audio. Random loss and jitter are absorbed by FEC/PLC and the jitter buffer.

10.7 Output screenshots and dashboard

Real output from a call between two clients (PC1, PC2) on one laptop with the built-in test source. The live review demo uses the webcam and two laptops.





Figure 5. Client window on PC2: its own view (left) and PC1 (right), with the live overlay: candidate pair, safety code, RTT, loss, jitter, freezes.

```
$ mm-server 9640
[server] Mini-Meet signalling server listening on TCP 9640 (protocol v1)
[room] join room=demo id=ae2ea3fb name=PC1 from=127.0.0.1:64698 (1/4)
[room] join room=demo id=306e24b3 name=PC2 from=127.0.0.1:64700 (2/4)

$ mm --server 127.0.0.1:9640 --room demo --name PC2 --test
[sig] joined room demo as PC2 (id 306e24b3), 1 already here
[ice] PC1: remote host candidate 172.16.242.48:63029
[crypto] PC1: end-to-end keys ready, safety code 0789-0177 (compare on both screens)
[ice] PC1: CONNECTED via host->host, media to 172.16.242.48:63029 (2 ms)
[stats] PC1 host->host rtt 5ms | in v 1325kbps 20fps 640x480 loss 0.0% jit 0ms frz 0
        | a conceal 0.0% | out 1192kbps lvl 0 | jb v 5ms a 27ms playout-sd 2.7ms

$ make test
72 checks, 0 failed
```

Dashboard. `analysis/dashboard.py` (Python standard library) serves a local web page. It shows the running call's statistics, refreshed every second from the client's `--csv` file, along with the evaluation table and the timeline graph of any run.



Profile	Rate control	Video kbps	fps	Loss %	Jitter ms	RTT ms	Freezes	Audio concealed %	Playout spread ms
baseline	off	1205.2	20.0	0.0	0.1	0.2	0.0	0.0	1.4
baseline	on	1201.9	20.0	0.0	0.1	0.7	0.0	0.0	1.5
loss1	off	1211.8	20.0	1.0	0.1	0.3	0.0	0.0	2.2
loss1	on	1210.6	20.0	0.9	0.1	0.2	0.0	0.0	1.9
loss5	off	1223.8	20.0	4.9	0.1	0.3	0.0	0.2	16.2
loss5	on	684.5	20.0	5.1	0.2	0.3	0.0	0.4	16.3
loss10	off	1218.0	20.0	9.9	0.1	0.9	2.0	1.3	23.3
loss10	on	105.5	20.0	9.2	0.3	0.3	0.0	1.1	23.4
loss20	off	1222.3	19.0	19.8	0.1	0.2	23.0	4.0	38.0
loss20	on	103.8	20.0	20.8	0.2	0.3	15.0	3.2	40.8
burst5	off	1188.0	20.0	2.5	0.1	4.6	0.0	0.7	3.8
burst5	on	1224.0	20.0	2.1	0.1	4.0	0.0	0.5	2.3
delay100	off	1217.8	20.0	0.0	0.1	200.4	0.0	0.0	1.4
delay100	on	580.0	20.0	0.0	0.2	200.3	0.0	0.0	1.0
jitter30	off	1371.9	20.0	1.0	33.5	186.7	1.0	0.1	12.4
jitter30	on	277.8	20.0	0.8	33.8	200.3	0.0	0.1	4.7
jitter60	off	1633.6	20.0	1.7	65.7	193.6	4.0	0.2	22.7
jitter60	on	213.1	20.0	1.5	70.5	211.1	3.0	0.1	8.1
rate2m	off	1228.0	20.0	0.0	7.8	46.8	0.0	0.0	1.3
rate2m	on	1225.5	20.0	0.0	7.6	38.7	0.0	0.0	1.5
rate1m	off	923.0	15.0	13.6	13.6	10513.1	0.0	34.1	2.1
rate1m	on	197.7	20.0	0.0	3.4	2.8	0.0	2.7	1.2
rate500k	off	446.4	0.0	39.6	22.9	19413.9	2.0	49.0	5.8
rate500k	on	188.1	20.0	0.0	3.2	9.8	0.0	11.7	2.5
rate250k	off	228.8	4.0	24.7	31.6	17373.2	2.0	74.5	7.0
rate250k	on	164.2	9.0	1.0	18.8	11706.7	6.0	34.8	5.2
combo	off	923.7	0.0	13.8	13.9	10054.2	9.0	33.0	2437.0

Figure 6. Dashboard during the same call: live numbers and graphs for the peer, above the evaluation results.

11. Discussion

- **Random loss up to 5 % is invisible.** NACK retransmission repairs video before the frame deadline, and Opus FEC keeps audio concealment ≤ 0.4 %. At 10–20 % loss a packet and its retransmission are sometimes both lost. The frame is skipped and a keyframe is awaited, which shows as freezes (23 at 20 %). Rate control reduces this to 15, because smaller frames have fewer packets that can be lost.
- **Constant delay is harmless.** At 200 ms RTT the quality equals baseline. The windowed baseline keeps the controller from treating a longer path as congestion; a first version without it stayed at the lowest level permanently, and this test caught the bug.
- **Bandwidth limits need rate control.** A fixed 1200 kbps stream into a 1 Mbit/s link fills netem's 1000-packet FIFO (bufferbloat): RTT 10.5 s, 14 % loss, 34 % audio concealed. At 500 kbit/s the video stops. The adaptive sender keeps RTT at 3–10 ms with 0 % loss at 20 fps. In the combined profile the fixed-rate call stalls entirely, while the adaptive call keeps 20 fps at 199 ms RTT.

- **Known weaknesses**, all textbook ones:
  - Random (wireless-style) loss and jitter are misread as congestion, so the controller lowers quality unnecessarily (5 % loss → 690 kbps).
  - At 250 kbit/s, feedback-starvation detection backs off within 2.5 s, but the first seconds at full rate have already filled the queue. Even the lowest level plus audio drains it only slowly, so RTT stays high. A "pause video" level, or AQM such as CoDel in the network, would fix it.
  - A larger jitter buffer means more latency.
- **Comparison with a WebRTC prototype** built first (browser + Node.js): Chrome's GCC handled the same 1 Mbit/s cap by settling around 50 kbps. Both systems were stuck behind netem's buffer at 250 kbit/s. Our implementation makes every mechanism visible and measurable.

12. Limitations and Future Work

- No TURN relay: two symmetric NATs cannot connect.
- Mesh topology limits calls to about 4 people. An SFU with simulcast or SVC would scale, and would let each receiver get the quality its link supports.
- Signalling over plain TCP: add TLS and STUN message integrity, and a replay window for media.
- Controller: distinguish random loss from congestion (for example using delay trends), and add a pause-video level for very thin links.
- IPv4 only. One 45 s run per profile; repeated runs would give confidence intervals.

13. Conclusion

Mini-Meet delivers working 2–4 person audio/video calls written in C on raw sockets, covering signalling, NAT traversal, framing, jitter buffering, loss repair, rate control and encryption. It runs on Windows and Linux and has been verified across two different real networks. The evaluation shows both halves of the real-time loop at work. The receiver-side jitter buffer turns uneven arrivals back into smooth playout (88 % → 0.1 % concealed audio under ±30 ms jitter). The sender-side rate controller, driven by receiver feedback, keeps a call usable on bandwidth-limited links where a fixed-rate stream collapses into seconds of delay. The remaining limitations are well-understood trade-offs of the design.

Appendix A. Syllabus Coverage

Module	Topic → where in Mini-Meet
1 Foundations	Layering/encapsulation (VP8/Opus → RTP → UDP → IP); sockets API (`net.c`, Winsock/POSIX); throughput, delay, jitter, latency (measured per second); network byte order
2 Direct links	Framing (frames split at MTU, S/M bits; newline framing on TCP); error detection (sequence gaps); error correction (Opus FEC); reliable transmission (NACK = selective repeat with deadline)
3 Internetworking	NAT, private vs public addresses, STUN, hole punching; MTU and fragmentation; why IP multicast is not used (application-level fan-out: mesh/SFU)
4 End-to-end	UDP vs TCP; demultiplexing on one port; connection setup/teardown and record boundaries; adaptive retransmission timers from RTT; RTCP feedback; AIMD and delay-based congestion control; FIFO queues and bufferbloat; QoS metrics
5 Security/apps	Threats and server hardening; end-to-end encryption (X25519, ChaCha20-Poly1305, safety code) vs IPsec; firewall traversal; Telnet-style text protocol; DNS resolution of the STUN server
6 Contemporary	Per-second streaming telemetry (CSV) vs SNMP polling

Appendix B. How to Build and Run

```
# Windows (MSYS2 MinGW64 shell) or Linux: build and test
make && make test

# a call (up to 4 people per room)
bin/mm-server                                          # signalling server, TCP 9000
bin/mm --server 127.0.0.1 --room demo --name PC1         # webcam + microphone
bin/mm --server 127.0.0.1 --room demo --name PC2 --test    # test pattern + tone
bin/mm --server 127.0.0.1 --room demo --name PC3 --file media/sample.mp4    # recorded media

# across networks: expose the server with a TCP tunnel, then join with --server bore.pub:PORT
bore local 9000 --to bore.pub

# dashboard for a running call (start the client with --csv results/live-pc1.csv)
python3 analysis/dashboard.py --csv results/live-pc1.csv    # http://localhost:8090

# evaluation (inside WSL/Linux as root), then the graphs
bash bench/run-matrix.sh
SCHEDULE="baseline:15 rate2m:20 rate1m:20 rate500k:20 rate1m:20 baseline:20" bash bench/run-matrix.sh
python3 analysis/plot.py results/eval_*.csv
```

Window keys: M mute, V camera, S statistics, F mirror, Q quit. Options: `--no-adapt`, `--no-jb`, `--no-encrypt`, `--csv FILE`, `--list-devices`.

References

1. RFC 3550: RTP, A Transport Protocol for Real-Time Applications (2003).
2. RFC 4585: Extended RTP Profile for RTCP-Based Feedback (NACK, PLI) (2006).
3. RFC 5389: Session Traversal Utilities for NAT (STUN) (2008).
4. RFC 8445: Interactive Connectivity Establishment (ICE) (2018).
5. RFC 7983 and RFC 5761: multiplexing STUN, RTP and RTCP on a single port.
6. RFC 6716: Opus audio codec; RFC 6386: VP8 data format.
7. RFC 7748: X25519 elliptic-curve Diffie-Hellman; RFC 8439: ChaCha20-Poly1305 AEAD.
8. Jacobson, V. "Congestion Avoidance and Control", SIGCOMM 1988 (AIMD).
9. Carlucci et al. "Analysis and Design of the Google Congestion Control for WebRTC", MMSys 2016.
10. Nichols, K. and Jacobson, V. "Controlling Queue Delay" (CoDel), ACM Queue 2012.
11. Peterson, L. and Davie, B. *Computer Networks: A Systems Approach* (course textbook).