



SMS

Last updated July 17th, 2026

Overview

The **Hubtel SMS API** allows businesses to integrate SMS functionality into their applications. With this API, you can send:

1. Send Simple/Batch Messages to individuals or groups of people (batch).
2. Send Personalized Messages to individuals or groups of people (batch).

Hubtel also provides an **SMPP (Short Message Peer-to-Peer)** route for sending SMS, which allows high-throughput message delivery suitable for large-scale applications.

The reference provides an overview of the Hubtel SMS API endpoints for interacting programmatically within your application and a guide to help you integrate with Hubtel's SMS SMPP route effectively.

SMPP

The SMPP route is designed for enterprises requiring reliable and efficient SMS delivery. It supports standard SMPP protocol features and ensures availability and scalability.

SMPP Connection

To connect to Hubtel's SMPP server, use the following details:

- Host: **smpp.hubtel.com**
- Port: **2775**
- **ClientID**
- **ClientSecret**



Note



LET'S CHAT



Supported Operations

Hubtel's SMPP route supports the following operations:

- **Bind Transmitter (TX):** To send SMS messages.
- **Bind Receiver (RX):** To receive delivery receipts.
- **Bind Transceiver (TRX):** To send and receive messages and receipts.
- **Submit_SM:** To submit a single SMS message.
- **Deliver_SM:** To receive delivery receipts.
- **Unbind:** To close the SMPP session.

Please refer to the detailed SMPP documentation provided [here](#) for further understanding.

SMS API

The **Hubtel SMS API** allows you to integrate multiple SMS functionalities into your applications. This document focuses on:

- Simple Messaging: send messages to individuals using **POST** and **GET**.
- Batch Simple Messaging: send simple messages to a group of people.
- Batch Personalized Messaging: Send personalized messages to a group of people.
- Message Status Check: Check the status of a message with **messageId** or **batchId**.

API Reference

Simple SEND SMS GET

This endpoint allows you to send a simple message using **GET** method. You will need to pass **clientId** and **clientSecret** in the request.



LET'S CHAT

Request Type	GET
--------------	-----

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
clientid	String	Mandatory	ClientId needed to authenticate SMS request. You can find your clientid here .
clientsecret	String	Mandatory	Clientsecret needed to authenticate SMS request. You can find your clientsecret here .
from	String	Mandatory	Sender ID or Name recipients will see. Maximum characters for this value is 11.
to	String	Mandatory	Mobile number of recipient



LET'S CHAT

content	String	Mandatory	Content of the simple message
---------	--------	-----------	-------------------------------

SAMPLE REQUEST

HTTP	cURL	PHP	Python
------	------	-----	--------

JavaScript - Fetch

Copy

```
const requestOptions = {
  method: "GET",
  redirect: "follow"
};

fetch("https://sms.hubtel.com/v1/messages/send?clientsecret=sgornei
.then((response) => response.text())
.then((result) => console.log(result))
.catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
rate	Float	Cost per sms
messageld	String	Unique identifier of messages
status	Int	Status code of the request

networkId	String	networkId of message
clientReference	String	ClientReference of message. Can be null
statusDescription	String	Brief description of request status

SAMPLE RESPONSE

201 Created

Copy

```
{
  "rate": 0.0309,
  "messageId": "9c5f3edc-529e-4182-959b-aeb17b9ddad4",
  "status": 0,
  "networkId": "62001",
  "clientReference": null,
  "statusDescription": "request submitted successfully"
}
```

Simple SEND SMS POST

This endpoint allows you to send a simple message using **POST** method. Send an HTTP **POST** request to the below URL and authenticate your request with **Basic Auth** using your SMS API credentials.

API Endpoint	https://sms.hubtel.com/v1/messages/send
Request Type	POST
Content Type	JSON



LET'S CHAT



Parameter	Type	Requirement	Description
From	String	Mandatory	SenderId or Name recipients will see. Maximum characters for this value is 11.
To	String	Mandatory	Mobile number of recipient.
Content	String	Mandatory	Content of the message.

SAMPLE REQUEST

HTTP

cURL

PHP

Python

JavaScript - Fetch

Copy

```
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic cW92Y7c2dyb3JuaWU=");

const raw = JSON.stringify({
  "From": "AbrantieLai",
  "To": "233546335113",
  "Content": "This is a test. Kindly ignore."
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
```



LET'S CHAT

```
return( https://sms.hubtel.com/v1/messages/send , requestOptions)
    .then((response) => response.text())
    .then((result) => console.log(result))
    .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
rate	Float	Cost per sms
messageId	String	Unique identifier of messages
status	Int	Status code of the request
networkId	String	networkId of message
clientReference	String	ClientReference of message. Can be null
statusDescription	String	Brief description of request status

SAMPLE RESPONSE

201 Created

Copy

```
{
  "rate": 0.0246,
  "messageId": "fab43849-6c5b-4334-a88b-d06520b1ace8",
  "status": 0,
```



LET'S CHAT



Batch Simple Messaging

This endpoint allows you to send messages to a group of people. Send an HTTP **POST** request to the below URL and authenticate your request with **Basic Auth** using your SMS API credentials.

API Endpoint	https://sms.hubtel.com/v1/messages/batch/simple
Request Type	POST
Content Type	JSON

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
From	String	Mandatory	SenderId or Name recipients will see. Maximum characters for this value is 11.
Recipients	Array	Mandatory	MSISDNs to receive of message
Content	String	Mandatory	Content of the simple message

[LET'S CHAT](#)



HTTP

cURL

PHP

Python

JavaScript - Fetch

Copy

```
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic cW92Y6c2dyb3Juam=");

const raw = JSON.stringify({
  "From": "AbrantieLai",
  "Recipients": [
    "233546335113",
    "233501431586"
  ],
  "Content": "Welcome to the first ever bulk SMS via API in Ghana"
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
  redirect: "follow"
};

fetch("https://sms.hubtel.com/v1/messages/batch/simple/send", requestOptions)
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
batchId	String	The ID of the batch of messages
status	Int	Status code of request returned



LET'S CHAT

Request Body (JSON)			By SMS API
data	ArrayOfObjects	This contains other objects	
recipient	String	MSISDNs to receive message	
content	String	Content of the simple message	
messageId	String	Unique identifier of message	

SAMPLE RESPONSE

200 OK

Copy

```
{
  "batchId": "165949ee-431b-4bf8-9eca-108058a8bc32",
  "status": 0,
  "data": [
    {
      "recipient": "233546335113",
      "content": "Welcome to the first ever bulk SMS via API in Ghana",
      "messageId": "e80133f9-e822-457c-98fb-d217bc4a1f83"
    },
    {
      "recipient": "233501431586",
      "content": "Welcome to the first ever bulk SMS via API in Ghana",
      "messageId": "ebc7948a-7c81-4396-9104-9c99fc921069"
    }
  ]
}
```

Batch Personalized Messaging



API Endpoint	https://sms.hubtel.com/v1/messages/batch/personalized
Request Type	POST
Content Type	JSON

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
From	String	Mandatory	SenderId Name recipients will see. Maximum characters for this value is 11.
personalizedRecipients	ArrayOfObjects	Mandatory	Contains object of recipients and content.
To	String	Mandatory	MSISDNs receive message
Content	String	Mandatory	Content of the simple message

SAMPLE REQUEST





JavaScript - Fetch

[Copy](#)

```
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic cW92Y6c2dyb3Juam=");

const raw = JSON.stringify({
  "From": "AbrantieCo",
  "personalizedRecipients": [
    {
      "To": "233501431586",
      "Content": "Hi Pheezy, thank you for all you do for this busi"
    },
    {
      "To": "233501431586",
      "Content": "Hi Joe, thank you for all you do for this busines:"
    }
  ]
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
  redirect: "follow"
};

fetch("https://sms.hubtel.com/v1/messages/batch/personalized/send",
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
batchId	String	The ID of the batch of messages

[LET'S CHAT](#)

status	Int	Status code of the request returned by SMS API
data	ArrayOfObjects	This contains other objects
recipient	String	MSISDNs to receive message
content	String	Content of the simple message
messageId	String	Unique identifier of message

SAMPLE RESPONSE

200 OK

Copy

```
{
  "batchId": "18ee6a2a-29ac-41c6-b70f-de809b040584",
  "status": 0,
  "data": [
    {
      "recipient": "233501431586",
      "content": "Hi Pheezy, thank you for all you do for this busin",
      "messageId": "350fd34d-dce1-4694-a4c9-d9b97d1f4593"
    },
    {
      "recipient": "233546335113",
      "content": "Hi Joe, thank you for all you do for this business",
      "messageId": "f58e7f2a-203a-4079-a518-7f6647099b5e"
    }
  ]
}
```



Status Check with MessageID

A query to this endpoint returns the status of a single message.

Note

Replace the **messageID** in the below endpoint with the messageID of your messages.

API Endpoint	https://sms.hubtel.com/v1/messages/{messageid}
Request Type	GET

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
messageID	String	Mandatory	An ID of one of the sent messages

SAMPLE REQUEST (Message ID)

[HTTP](#)[cURL](#)[PHP](#)[Python](#)[JavaScript - Fetch](#)[Copy](#)

```
const requestOptions = {
  method: "GET",
  redirect: "follow"
};
```

[LET'S CHAT](#)

```
.catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
rate	Float	Cost per sms
batchId	String	Unique identifier of batch message.
messageId	String	Unique identifier of individual message.
content	String	Content of the simple message.
status	String	Current status of message based on DeliveryReceipt (DLR) by Telco.
updateTime	String	DLR update time.
time	String	The time SMS was sent.
to	String	MSISDN to receive message.
from	String	SenderId or name recipient will see



LET'S CHAT



200 OK

Copy

```
{
  "rate": 0.0309,
  "batchId": null,
  "messageId": "eadbfcd0-94d1-438f-ad32-0013f34042c2",
  "content": "The Job is the JOB", "status": "Delivered",
  "status": "Delivered",
  "updateTime": "2023-05-30T16:43:15",
  "time": "2023-05-30T16:43:13.7208383Z",
  "to": "233546335113",
  "from": "AbrantieCo"
}
```

Status Check with BatchID

A query to this endpoint returns the status of a batch of messages.

Note

Replace the **batchID** in the below endpoint with the batchID of your messages.

API Endpoint	https://sms.hubtel.com/v1/messages/{batchId}
Request Type	GET

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
batchId	String	Mandatory	An ID of one of the sent messages



LET'S CHAT

HTTP

cURL

PHP

Python

JavaScript - Fetch

Copy

```
const requestOptions = {
  method: "GET",
  redirect: "follow"
};

fetch("https://sms.hubtel.com/v1/messages/batch/eadbfc0-94d1-438f-;
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
batchId	String	Unique identifier of batch message.
data	ArrayOfObjects	This contains other objects.
rate	Float	Cost per sms.
messageId	String	Unique identifier of individual message.
content	String	Content of the simple message.
status	String	Current status of message based on



LET'S CHAT

		Delivery Receipt (DLR) by Telco.
updateTime	String	DLR update time.
time	String	The time SMS was sent.
to	String	MSISDN to receive message.
from	String	SenderId or name recipient will see.

SAMPLE RESPONSE

200 OK

Copy

```
{
  "batchId": "eadbfcd0-94d1-438f-ad32-0013f34042c2",
  "data": [
    {
      "rate": 0.0309,
      "messageId": "f58e7f2a-203a-4079-a518-7f6647099b5e",
      "content": "Hi Joe, thank you for all you do for this business",
      "status": "Delivered",
      "updateTime": "2023-03-21T12:54:43",
      "time": "2023-03-21T12:50:27.893495Z",
      "to": "233546335113",
      "from": "AbrantieCo"
    },
    {
      "rate": 0.0309,
      "messageId": "350fd34d-dce1-4694-a4c9-d9b97d1f4593",
      "content": "Hi Pheezy, thank you for all you do for this busin",
      "status": "Delivered",
      "updateTime": "2023-03-21T12:50:34",
      "time": "2023-03-21T12:50:27.893495Z",
      "to": "233501431586",
      "from": "AbrantieCo"
    }
  ]
}
```

 LET'S CHAT



SMS Statuses

Below are SMS statuses based on DeliveryReceipts (DLR)s by Telco.

- **Delivered:** These messages have been reliably and successfully dispatched to the recipient's phone. This constitutes the ultimate Delivery Receipt (DLR) status provided by a telco.
- **Sent:** Sent messages encompass messages that have been forwarded by Hubtel to the recipient's network operator for eventual delivery. These messages are currently in a state of pending delivery by the telcos. To ascertain their ultimate status, you can utilize the status check API at a later time.
- **Pending:** Pending messages are those in a queue, awaiting discharge by Hubtel to the recipient's network operator for the purpose of delivery.
- **Blacklisted:** Blacklisted numbers correspond to individuals who have explicitly communicated with telcos to abstain from receiving unsolicited bulk messages on their mobile devices. As a result, the telco designates these numbers for blacklist inclusion. It's important to emphasize that the network operator is responsible for delivering messages to the handset. Hubtel solely receives the ultimate message status from the mobile network operator.
- **Undeliverable/Failed, Unrouteable/Error, Rejected:** Occurrences of messages like these could arise from various factors, such as the customer's phone being powered off, inaccessible, or experiencing network unavailability. Additionally, issues could stem from the recipient being situated outside network coverage during the moment the message was dispatched to their device. These various statuses are dependent on the various Telcos.
- **NACK/0x0000000b/Invalid Destination Address:** These statuses mean that the recipient number may be inaccurate or inadequately formatted.
- **NACK/0x0000000a/Invalid Source Address:** These statuses mean that the value for the "From" key in your request may have exceeded the maximum limit of 11.

Response Codes



LET'S CHAT

response body, which contains information about the error.

Http Code	Status	Description
200	0	The request was successful and the message has been sent for onward delivery
201	0	The request was successful and the message has been sent for onward delivery
201	100	General invalid request. Returned when no data is sent or a malformed request is received
201	1	Invalid Destination address received. The recipient's phone number is not a valid phone number
201	2	Invalid Source address was sent. You need to be aware of the sender address restrictions



LET'S CHAT



400	3	The message body was too long.
400	4	The message is not routable on Hubtel gateway
400	5	The delivery time specified was not a valid time.
	6	The message content was rejected or is invalid.
	7	One or more parameters are not allowed in the message. Details will be provided as part of the response.
	8	One or more parameters are not valid for the message. Details will be provided as part of the response.
	12	Payment required on account; Kindly fund your account
401		The request authorization f



LET'S CHAT



402	Your account does not have enough messaging credit to send the message.
403	Forbidden. This means that the recipient has not given his/her approval to receive messages
404	The specified message was not found.
500	The request failed on the server
502	Bad Gateway. The server could not find any appropriate gateway for the request.



LET'S CHAT