คำสั่งที่สำคัญ

Show MAC static

```
SW1#show mac address-table static
          Mac Address Table
-------------------------------------------

Vlan    Mac Address       Type        Ports
----    -----------       --------    -----
 All    0012.7f2b.32c0    STATIC      CPU
 All    0100.0ccc.cccc    STATIC      CPU
 All    0100.0ccc.cccd    STATIC      CPU
 All    0100.0cdd.dddd    STATIC      CPU
   1    e0be.0371.dbc5    STATIC      Fa0/1
Total Mac Addresses for this criterion: 5
SW1#
```

Show MAC Dynamic

```
SW1#show mac address-table dynamic
          Mac Address Table
-------------------------------------------

Vlan    Mac Address       Type        Ports
----    -----------       --------    -----
   1    0019.555c.6118    DYNAMIC     Fa0/24
   1    2216.d73b.b472    DYNAMIC     Fa0/24
   1    e0be.0371.bdd6    DYNAMIC     Fa0/2
Total Mac Addresses for this criterion: 3
SW1#
```

Show MAC aging time

```
SW1#show mac address-table aging-time
Vlan    Aging Time
----    ----------
   1     300
  10     300
  20     300
  30     300
SW1#
```

Protect

```
SW1#show port-security interface fastEthernet 0/1
Port Security              : Enabled
Port Status                : Secure-down
Violation Mode             : Protect
Aging Time                 : 0 mins
Aging Type                 : Absolute
SecureStatic Address Aging : Disabled
Maximum MAC Addresses      : 2
Total MAC Addresses        : 0
Configured MAC Addresses   : 0
Sticky MAC Addresses       : 0
Last Source Address        : 0000.0000.0000
Security Violation Count   : 0
```

Restrict

```
SW1#show port-security interface fastEthernet 0/2
Port Security              : Enabled
Port Status                : Secure-up
Violation Mode             : Restrict
Aging Time                 : 0 mins
Aging Type                 : Absolute
SecureStatic Address Aging : Disabled
Maximum MAC Addresses      : 2
Total MAC Addresses        : 0
Configured MAC Addresses   : 0
Sticky MAC Addresses       : 0
Last Source Address        : 0000.0000.0000
Security Violation Count   : 0
```

Shutdown

```
SW1#show port-security interface fastEthernet 0/3
Port Security              : Enabled
Port Status                : Secure-up
Violation Mode             : Shutdown
Aging Time                 : 0 mins
Aging Type                 : Absolute
SecureStatic Address Aging : Disabled
Maximum MAC Addresses      : 2
Total MAC Addresses        : 1
Configured MAC Addresses   : 0
Sticky MAC Addresses       : 1
Last Source Address        : 3203.14bd.772f
Security Violation Count   : 0
```

Show running config sw1

```
!
interface Vlan1
 ip address 192.168.1.2 255.255.255.0
 no ip route-cache
!
ip default-gateway 192.168.1.1
ip http server
!
line con 0
 exec-timeout 5 0
 password cisco
 login
line vty 0 4
 password cisco
 login
line vty 5 15
 login
!
mac-address-table static e0be.0371.dbc5 vlan 1 interface FastEthernet0/1
!
end

SW1#
```

Show running config sw2

```
interface Vlan1
 ip address 192.168.1.3 255.255.255.0
 no ip route-cache
!
ip default-gateway 192.168.1.1
ip http server
!
line con 0
 exec-timeout 5 0
 password cisco
 login
line vty 0 4
 password cisco
 login
line vty 5 15
 password cisco
 login
!
!
end
```

```
Current configuration : 2063 bytes
!
version 12.1
no service pad
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
!
hostname SW2
!
enable secret 5 $1$V.yg$Pza8oB47tZWnd.C6F43Bj.
enable password cisco
!
ip subnet-zero
!
!
spanning-tree mode pvst
no spanning-tree optimize bpdu transmission
spanning-tree extend system-id
!
!
!
interface FastEthernet0/1
 switchport mode access
 switchport port-security
 switchport port-security maximum 2
 switchport port-security violation protect
 switchport port-security mac-address sticky
 switchport port-security mac-address sticky 2216.d73b.b472
 switchport port-security mac-address sticky 98ee.cba8.18da
!
interface FastEthernet0/2
 switchport mode access
 switchport port-security
 switchport port-security maximum 2
 switchport port-security violation restrict
 switchport port-security mac-address sticky
 switchport port-security mac-address sticky 3a09.2390.fed6
!
interface FastEthernet0/3
 switchport mode access
 switchport port-security
 switchport port-security maximum 2
 switchport port-security mac-address sticky
 switchport port-security mac-address sticky 6a59.8328.ae99
 switchport port-security mac-address sticky ee43.d556.feb5
!
```

COM4 - PuTTY

```
!
interface FastEthernet0/6
!
interface FastEthernet0/7
!
interface FastEthernet0/8
!
interface FastEthernet0/9
!
interface FastEthernet0/10
!
interface FastEthernet0/11
!
interface FastEthernet0/12
!
interface FastEthernet0/13
!
interface FastEthernet0/14
!
interface FastEthernet0/15
!
interface FastEthernet0/16
!
interface FastEthernet0/17
!
interface FastEthernet0/18
!
interface FastEthernet0/19
!
interface FastEthernet0/20
!
interface FastEthernet0/21
!
interface FastEthernet0/22
!
interface FastEthernet0/23
!
interface FastEthernet0/24
!
interface Vlan1
 ip address 192.168.1.2 255.255.255.0
 no ip route-cache
!
ip default-gateway 192.168.1.1
ip http server
!
line con 0
 exec-timeout 5 0
 password cisco
 login
line vty 0 4
 password cisco
 login
line vty 5 15
 login
```