




Dalhousie University
Faculty of Computer Science

CSCI 3132 – Object Orientation and Generic Programming


Week 6, 7 – Inheritance and
Polymorphism

Types and Subtypes

- A class defines a type, or a set of objects
- Subtypes are types within a type
 - Teacher and Student are subtypes of People




Type Hierarchy




- What do people have in common?
 - Characteristics
 - Name, address, ID
 - Behaviours
 - Display profile, update address

Type Hierarchy



- What things are specific to students?
 - Characteristics
 - Program, courses, semester, grade
 - Behaviours
 - Add/drop course, add/remove classes, update grades

Type Hierarchy



- What things are specific to teachers?
 - Characteristics
 - Courses taught, classes taken, research projects
 - Behaviours
 - Add a class, add a course, add/update project

Inheritance

- A subtype inherits characteristics and behaviours of its base type
- Student has:
 - Characteristics
 - Name, address, id, program, courses, semester, grade
 - Behaviours
 - Display profile, update address, update program, add/drop course, update grade

Base Class – People

```
Class People {
```

```
protected:
```

```
    int id;
```

```
    string name;
```

```
    string address;
```

//Access control

```
Public:
```

```
    People (int id, string name, string address);
```

```
    void DisplayProfile();
```

```
    void UpdateAddress(string newAddr);
```

```
};
```

Access Control

- Private
 - No one from outside of the class can access it.
 - Even the subclasses cannot access it
- Protected
 - Only the class itself and all its subclasses can access it
- Public
 - Anyone can access it
- Friend
 - Friend class or function can access private members of the class it in which it is declared friend

Derived Class – Student

```
#include "People.h"  
class Student : public People {  
protected:
```

```
    int program;  
    int semester;  
    float grade;
```

```
Public:
```

```
    Student (int id, string name, string address,  
            int program, int semester, float grade);  
    void DisplayProfile();  
    void UpdateGrade(float grade);
```

```
};
```

Constructing the Student Subclass

```
//in implementation of the derived class Student
Student::Student(int id, string name, string address,
                int program, int semester, float grade) :
    People(id, name, address){
    this->program = program;
    this->semester = semester;
    this->grade = grade;
}

//in implementation of the base class People
People::People(int id, string name, string address);
    this->id = id;
    this->name = name;
    this->address = address;
}
```

Overriding a Base Class Method

```
class People {  
protected:  
    int id;  
    string name;  
    string address;  
public:  
    People (int id, string name, string address);  
    void DisplayProfile() ;  
    void UpdateAddress(string newAddr);  
};
```

```
#include "People.h"  
class Student : public People {  
protected:  
    int program;  
    int semester;  
    float grade;  
public:  
    Student (int id, string name, string address, int program, int semester,  
float grade);  
    void DisplayProfile() ;  
    void UpdateGrade(float grade);  
};
```

Overriding a Base Class Method

```
void People::DisplayProfile() {  
    cout <<"ID: "<<id<<"", Name: "<<name<<endl;  
    cout <<"Addr: "<<address<<endl;  
}
```

```
void Student::DisplayProfile() {  
    cout <<"ID: "<<id<<"", Name: "<<name<<endl;  
    cout <<"Addr: "<<address<<endl;  
    cout <<"Program: "<<program;  
    cout <<"", Semester: "<<semester<<endl;  
    cout <<"GPA: "<<grade<<endl;  
    cout<<endl;  
}
```

Overriding a Base Class Method

```
People* john = new People(5542, "John Snow",  
    "Somewhere on the wall");  
Student* bran = new Student(7944, "Brandon Stark",  
    "Somewhere beyond the wall", 62255, 6, 3.98);
```

```
john->DisplayProfile();
```

```
ID: 5542, Name: John Snow  
Addr: Somewhere on the wall
```

```
bran->DisplayProfile();  
ID: 7944, Name: Brandon Stark  
Addr: Somewhere beyond the wall  
Program: 62255, Semester: 6  
GPA: 3.98
```



POLYMORPHISM

Polymorphism

Poly → Many Morph → Forms

- Ability of a type X to appear and be used like another type Y
 - Example: Student object can be used in place of a People object
- Bjarne Stroustrup, creator of C++ defines polymorphism as:
 - Providing a single interface to entities of different types. Virtual functions provide dynamic (run-time) polymorphism through an interface provided by a base class. Overloaded functions and templates provide static (compile-time) polymorphism. TC++PL 12.2.6, 13.6.1, D&E 2.9.

Actual versus Declared Type

- At compile-time
 - Variables have declared types
- At runtime
 - Variable may refer to an object with an actual type
 - Actual type may be the same or a subclass of the declared type

```
People* john = new People(5542, "John Snow",  
    "Somewhere on the wall");  
Student* bran = new Student(7944, "Brandon Stark",  
    "Somewhere beyond the wall", 62255, 6, 3.98);
```

- What are the declared and actual types of john and bran?

Calling an Overriden Function

```
People* bran = new Student(7944, "Brandon Stark",  
    "Somewhere beyond the wall", 62255, 6, 3.98);  
  
bran->DisplayProfile();
```

ID: 7944, Name: Brandon Stark

Addr: Somewhere beyond the wall

Why other details for the Student are not shown?

– Where are the program, semester and GPA?

Virtual Functions

- In base class
 - Declare overridden methods as virtual

```
Class People {  
protected:  
    int id;  
    string name;  
    string address;  
Public:  
    People (int id, string name, string address);  
    virtual void DisplayProfile();  
    virtual void UpdateAddress(string newAddr);  
};
```

Calling a Virtual Function

```
People* bran = new Student(7944, "Brandon Stark",  
    "Somewhere beyond the wall", 62255, 6, 3.98);  
  
bran->DisplayProfile();
```

```
ID: 7944, Name: Brandon Stark  
Addr: Somewhere beyond the wall  
Program: 62255, Semester: 6  
GPA: 3.98  
Courses Taken:
```

Why the details for the Student are now shown?

Early versus Late Binding

- Without using virtual, we get early binding
 - Also known as static (or compile-time) binding
 - Which implementation of the method should be called is decided at compile time
 - Based on the type of the pointer used to make the call
- Using virtual, we get late binding
 - Also known as dynamic (or runtime) binding
 - Which implementation of the method should be called is decided at runtime
 - Based on the type of the pointed-to object

Early versus Late Binding

```
People* bran = new Student(7944, "Brandon Stark",  
    "Somewhere beyond the wall", 62255, 6, 3.98);  
  
bran->DisplayProfile();
```

ID: 7944, Name: Brandon Stark

Addr: Somewhere beyond the wall

Program: 62255, Semester: 6

GPA: 3.98

- Example of late binding.
 - bran gets bound to the type of pointed-to object i.e. Student

What goes on Behind the Scenes

- When a class contains virtual functions or overrides virtual functions from a parent class
 - The compiler builds a vtable for that class
 - vtable stores pointers to all virtual functions
 - One virtual table created for each class
 - Lookup performed during the function call
 - All objects of the same class share the same vtable
 - Virtual tables are not constructed for every class
 - Only classes with virtual functions or overriding functions

Virtual Pointers


- vpointers associated with every vtable
 - Used to access functions inside the vtable
- For every class with a vtable
 - Compiler adds hidden code to the constructor of that class to initialize the vpointers of its objects to the address of the corresponding vtable
- How does the program know which function to invoke?

Example

```
#include <iostream>
using namespace std;
class shape{
public:
    virtual float CalcArea(float r) {return 0;}
    virtual float CalcPerim(float r) {return 0;}
};
class circle : public shape{
public:
    float CalcArea(float r) { return (3.14159*r*r); }
};
int main() {
    shape *s1 = new circle;
    cout<<s1->CalcArea(2);
}
```

//behind the scenes, s1 uses vpointer to the vtable of the circle class to access the correct CalcArea() function of circle class. i.e. s1 ---> vpointer ---> CalcArea() method for circle

Virtual Tables and Pointers



Virtual Destructor

- Destructors are called when an object is destroyed
 - Compiler generated public member if not specified
 - Automatically called
 - Used to free up resources acquired by the object
 - Syntax: `~ClassName();`
- Base class destructors should be virtual
 - This ensures that correct destructor is called through late binding

Virtual Destructor – Example

```
#include <iostream>
using namespace std;

class shape{
public:
    virtual ~shape(){cout<<"Shape Destructor\n";}
};

class circle : public shape{
public:
    ~circle(){cout<<"Circle Destructor\n";}
};

int main(){
    shape *s1 = new shape; //s1 points to base class object
    shape *s2 = new circle; //s2 points to derived class object
    delete s1;              //base class destructor called
    delete s2;              //derived class, then base class destructor called
}
```

Shape Destructor
Circle Destructor
Shape Destructor

Pure Virtual Functions and Abstract Classes

- A virtual function may be declared as a pure virtual function by adding =0 to its declaration
 - Providing the implementation is not required
 - Derived class MUST implement provide an implementation of the pure virtual function
 - Pure virtual function makes a class Abstract
- Abstract classes cannot be instantiated
 - Not implementing all pure virtual functions in a derived class makes that class Abstract too

Abstract class – Example

```
#include <iostream>
using namespace std;

class shape{
public:
    virtual float CalcArea(float r) = 0;    //pure virtual function
};

class circle : public shape{
public:
    float CalcArea(float r){ return (3.14159*r*r); }
};

int main(){
    //shape sh;                //error - Cannot initialize Abstract class
    //shape *sh = new shape;    //error - Cannot initialize Abstract class
    shape *s1 = new circle;    //valid
    cout<<s1->CalcArea(2)<<"\n"; //calls derived class' CalcArea()
}
```