1. Các lệnh đã thực hiện trên máy attacker

```
^C
ubuntu@attacker:~$ history
    1 ifconfig
    2 sudo hping3 -c 10 -i u1 10.10.0.10
    3 apt install nmap
    4 sudo apt install nmap
    5 nmap -sn 10.10.0.0/24
    6 nmap -p 80 -oN scan_result.nmap 10.10.0.10
    7 ls
    8 cat scan_result.nmap
    9 sudo hping3 -c 10000 -d 120 -S -w 64 -p 80 10.10.0.10
    10 history
ubuntu@attacker:~$
```

## Cụ thể

```
ubuntu@attacker:~$ nmap -sn 10.10.0.0/24
Starting Nmap 7.80 ( https://nmap.org ) at 2024-09-18 09:44 UTC
Nmap scan report for 10.10.0.1
Host is up (0.0011s latency).
Nmap scan report for ptit-hping3.victim.student.some_network (10.10.0.10)
Host is up (0.00039s latency).
Nmap scan report for attacker (10.10.0.20)
Host is up (0.00086s latency).
Nmap done: 256 IP addresses (3 hosts up) scanned in 2.69 seconds
ubuntu@attacker:~S nman -n 80 -oN scan result.nman 10.10.0.10
ubuntu@attacker:~$ nmap -p 80 -oN scan result.nmap 10.10.0.10
Starting Nmap 7.80 ( https://nmap.org ) at 2024-09-18 09:44 UTC
Nmap scan report for ptit-hping3.victim.student.some network (10.10.0.10)
Host is up (0.00033s latency).
       STATE SERVICE
80/tcp open http
```

```
# Nmap done at Wed Sep 18 09:44:59 2024 -- 1 IP address (1 host up) scanned i
ubuntu@attacker:~$ sudo hping3 -c 10000 -d 120 -S -w 64 -p 80 10.10.0.10
HPING 10.10.0.10 (eth0 10.10.0.10): S set, 40 headers + 120 data bytes
```

2. Các lệnh đã thực hiện trên máy victim

```
ubuntu@victim:~$ history

1 ifconfig
2 nmap -sn 10.10.0.0/24
3 uname -a
4 cat /proc/version
5 wireshark
6 sudo wireshark
7 ls
8 tshack syn.pcap
9 sudo apt install tshark
10 tshack syn.pcap
11 tshark -r syn.pcap -Y "tcp.flags.syn == 1" | wc -l
12 history
ubuntu@victim:~$ ls
```

## Cụ thể

```
12 history
ubuntu@victim:~$ ls
syn.pcapng
```

```
ubuntu@victim:~$ tshark -r syn.pcap -Y "tcp.flags.syn == 1" | wc -l
```

```
ubuntu@victim:~$ sudo wireshark
[1]+ Killed wireshark
QStandardPaths: XDG_RUNTIME_DIR not set, defaulting to '/tmp/runtime-root'
```

## 3. Checkwork