

Getting Started

Gary Allan Howard

June 1, 2018

Abstract

Getting Started guide covers how to install [tlc-article](#) both globally and locally, describes the general use case, how to customize your [tlc-article](#) environment, describes the commands [tlc-article](#) implements, and reveals the packages [tlc-article](#) depends upon.

Contents

1	Installation	2
1.1	Prerequisites	2
1.2	Local installation	2
1.3	Global installation	3
2	General Use Case	4
2.1	Document Layout	4
2.2	documentclass tlc-article	4
2.3	Title, Author & Abstract	4
2.4	Table of Contents	5
2.5	Header & Footer	5
3	Customization	6
3.1	data/additional-layout.tex	6
3.2	data/header-footer.tex	6
3.3	data/version.csv	7
3.4	data/logo.png	7
4	Definitions & Commands	8
4.1	tlcBeginLandscape	8
4.2	tlcEndLandScape	8
4.3	tlcDarkblue	8
4.4	tlcTitlePageAndTableOfContents	8
4.5	newcolumn type: L, C & R	8
4.6	data/additional-layout.tex	8
4.7	data/header-footer.tex	8
4.8	data/version.csv	9
4.9	data/logo.png	9
5	Required Packages	10

1 Installation

This section describes how to install `tlc-article` either globally to make it available to your L^AT_EX environment or locally to the document you are authoring. And, this section identifies the prerequisites you must meet in order to clone a repository from GitHub.com and install software on your computer.

1.1 Prerequisites

The following prerequisites are needed.

Administrative privilege

You will need administrative privileges to install `tlc-article` globally because ‘sudo’ is used.

SSH key

You will need your private key to access GitHub.com. Please refer to <http://help.github.com/articles/generating-an-ssh-key> for instructions on ‘Generating an SSH key’.

Enable your SSH key

The following instructions enable your SSH key so you do not have to enter the passphrase for each git command.

1. `eval $(ssh-agent -s)`
2. `ssh-add ~/.ssh/your-private-key`
3. enter your passphrase

1.2 Local installation

A local installation is done by installing `tlc-article` into `/the/path/to/your/document`. Assuming your document is located at `$HOME/mydoc` the following shell commands will make `tlc-article` available to your document.

1. `cd $HOME`
2. `git clone git@GitHub.com:Traap/tlc-article.git`
3. `cd tlc-article`
4. `mkdir $HOME/mydoc`
5. `cp -v tlc-article.cls $HOME/mydoc/.`

1.3 Global installation

A global installation is done by installing [tlc-article](#) into your `/path/to/your/texmf` directory. Assuming a TeXLive installation exists at `$(kpsewhich -var-value TEXMFLOCAL)` the following shell commands will make [tlc-article](#) available to your L^AT_EX environment.

1. `cd $HOME`
2. `git clone git@GitHub.com:Traap/tlc-article.git`
3. `cd tlc-article`
4. `sudo mkdir -p $(kpsewhich -var-value TEXMFLOCAL)/tex/latex/tlc-article`
5. `sudo mv -v tlc-article.cls $(kpsewhich -var-value TEXMFLOCAL)/tex/latex/tlc-article/.`
6. `sudo mktexlsr $(kpsewhich -var-value TEXMFLOCAL)`

Note You may remove your local installation by removing [tlc-article](#).

2 General Use Case

The goal of `tlc-article` is to simplify document layout. `tlc-article` orchestrates a logical arrangement for document header, footer, author, abstract, table of contents, and margins. The following sections outline the default implementation for each part `tlc-article` organizes.

Note This document was typeset using the instructions provided throughout this section.

2.1 Document Layout



Figure 1: Document Layout

2.2 documentclass `tlc-article`

`tlc-article` extends the article document class. `tlc-article` provide options directly to the article document class. As an example, the Author can specify the font as follows:

```
1 \documentclass[12pt]{tlc-article}
```

2.3 Title, Author & Abstract

`tlc-article` has a macro `tlcTitlePageAndTableOfContents` that can be used to set the document title, document author, document abstract, and establish the Table of Contents. The sample below reveals how to use `tlcTitlePageAndTableOfContents`.

```
1 \tlcTitlePageAndTableOfContents
2 {Document Title}
3 {Document Article}
4 {Document Abstract}
```

2.4 Table of Contents

The Table of Contents immediately follows the document abstract on page 1, uses dark blue for content, dots separate table of contents sections and page number, and uses roman numerals.

2.5 Header & Footer

fancyhdr is used to render the header and footer. The Author can override the `tlc-article` by providing an implementation in `data/header-footer.tex` or augment `tlc-article` application by providing `data/version.csv`. The sections below show the placement `tlc-article` uses when writing objects, and where the objects are defined.

Note `tlc-article` ignores `data/version.csv` when `data/header-footer.tex` is defined.

Header

lhead When `data/logo.png` is found, logo.

chead Document Title

rhead When `data/version.csv` is present, status, date, and version columns.

Footer

lfoot When `data/version.csv` is present, instatution column.

cfoot When `data/version.csv` is present, permission column.

rfoot Page 1 of N.

Rule width

A 0.1pt rule width is placed below the document header and above the document footer.

3 Customization

This section describes how `tlc-article` can be customized by using the file-hooks `tlc-article` check for. `tlc-article` default implementation will be used when the file-hooks are now found.

3.1 `data/additional-layout.tex`

`tlc-article` will use whatever L^AT_EX definitions are found in `data/additional-layout.tex` when it exists. The file-check is shown below:

```
1 \IfFileExists{docstyle/additional-layout.tex}
2 {\input{docstyle/additional-layout.tex}}
3 {}
```

3.2 `data/header-footer.tex`

In the absence of `data/additional-layout.tex` `tlc-article` has a builtin header and footer strategy that is base on *fancyhdr*, *titling*, and *lastpage* L^AT_EX packages. The default implementation is show below:

```
1 \IfFileExists{\tlc@logoFile}
2 { % Typeset the logo in the left side of the document header.
3   \lhead{\includegraphics[width=3cm,height=1cm]{\tlc@logoFile}}
4 }
5 {% Else: no operation because tlc@logoFile does not exist.
6 }
7 % Typeset the title in the center of the document header.
8 \chead{\large{\thetitle}}
9 % Typeset version information in the right side of the document header.
10 \IfFileExists{\tlc@versionFile}
11 {
12   % document status, document date and document version.
13   \rhead{\tiny \tlc@status \tlc@date \tlc@version}
14   % document owner. This maybe a person or company name.
15   \lfoot{\tiny \tlc@instatution}
16   % document license. This maybe a license or word like confidential.
17   \cfoot{\tiny \tlc@permission}
18 }
19 {% Else: no operation because tlc@versionFile does not exist.
20 }
21 \renewcommand{\headrulewidth}{0.1pt}
22 % eliminate head height too small warning, which is occurring because
23 % we are using multiple lines in our header.
24 \setlength\headheight{52pt}
25 % % footer applied to all pages.
26 \rfoot{\tiny{page \thepage~of~\pageref{LastPage}}}
27 \renewcommand{\footrulewidth}{0.1pt}
28 % we want our header and footer to remain consistent with a table of
29 % contents that span multiple pages.
30 \AtBeginDocument{\addtocontents{toc}{\protect\thispagestyle{fancy}}}
```

The default implementation can be overridden by defining `data/header-footer.tex`.

Note When `data/header-footer.tex` exists and is empty, your document will be typeset with the defaults from document-class `article`.

3.3 data/version.csv

`tlc-article` will populate the builtin header and footer with information extracted from `data/version.csv` when it is present. `data/version.csv` is a comma-separated-variable file that uses the pipe character as the field delimiter. `data/version.csv` uses the following column names:

version

The version value is typeset in the rhead area. This field is used to convey the version the document was at the date it reached its current state.

date

The date value is typeset in the rhead area. This field is used to communicate when the document transitioned into its current state.

status

The status value is typeset in the rhead area. This field is used to convey the document state such as Approved, Draft, Effective, or Obsolete.

instatution

The institution value is typeset in the lfoot area. This field is used to tell the reader the author name or company name.

permission

The permission value is typeset in the cfoot area. This field is used to identify confidentiality or a particular license.

The extaction methods are shown below.

```

1 % Extract document status, document date and document version from
2 % \tlc@versionFile.
3 % Argument:
4 % 1 - the column name to extract from the data file.
5 \newcommand{\tlcVersionPart}[1]{
6   \csvreader[separator=pipe]
7   {\tlc@versionFile}{
8     1=\version,
9     2=\date,
10    3=\status,
11    4=\instatution,
12    5=\permission
13  }{#1}
14 }%
15
16 % Define extractions macros when \tlc@versionFile exists.
17 \IfFileExists{\tlc@versionFile}
18 {
19   \def\tlc@version{\tlcVersionPart{\version}}
20   \def\tlc@date{\tlcVersionPart{\date}}
21   \def\tlc@status{\tlcVersionPart{\status}}
22   \def\tlc@instatution{\tlcVersionPart{\instatution}}
23   \def\tlc@permission{\tlcVersionPart{\permission}}
24 }
25 {% Else: no operation because tlc@versionFile does not exist.
26 }
```

3.4 data/logo.png

`tlc-article` will typeset the lhead area with `data/logo.png` when it is present. Make sure your logo's height is not larger than 34pt to avoid 'Package Fancyhdr Warning: headheight is to small' warning.

4 Definitions & Commands

4.1 `tlcBeginLandscape`

Page layout is rotated 90° clockwise resulting in a landscape page orientation. Landscape orientation remains active until `tlcEndLandScape`.

4.2 `tlcEndLandScape`

Page layout is returned to portrait orientation when `tlcEndLandScape` is reached.

4.3 `tlcDarkblue`

`tlcDarkblue` is used throughout this document to render text using `rgb{0,0,0.5}`. `tlcDarkblue` is safe to use within your document.

4.4 `tlcTitlePageAndTableOfContents`

`tlcTitlePageAndTableOfContents` creates the document layout shown in Figure 1. Section 2.3 shows an example implementation.

4.5 newcolumn type: **L**, **C** & **R**

New newcolumn type: **L**, **C** & **R** are Left, Center, and Right, respectively are designed to use with `longtable`. Data is wrapped within a table cell. The parameter defines the column width. As an example, `L2cm` yields a Left aligned, ragged right, wrapped text within a 2cm wide cell.

```
1 \newcolumntype{L}[1]{>{\raggedright\let\newline\\\arraybackslash}p{#1}}
2 \newcolumntype{C}[1]{>{\centering\let\newline\\\arraybackslash}p{#1}}
3 \newcolumntype{R}[1]{>{\raggedleft\let\newline\\\arraybackslash}p{#1}}
```

4.6 `data/additional-layout.tex`

`data/additional-layout.tex` is an architectural hook the Author should use when it becomes necessary to use packages not provided by `tlc-article` and to design commands that are specific to your document.

4.7 `data/header-footer.tex`

`data/header-footer.tex` is an architectural hook the Author should use to completely override the document layout `tlc-article` implements.

4.8 data/version.csv

data/version.csv is by used [tlc-article](#) to populate the document header & footer. Refer to section 3.3 for [data/version.csv](#) definitions. [data/version.csv](#) is not used by [tlc-article](#) when [data/header-footer.tex](#) is define. However, you might want to use the version hook by defining [data/version.csv](#) and using the commands below to extract data from [data/version.csv](#) in your [data/header-footer.tex](#).

1. [tlc@version](#)
2. [tlc@date](#)
3. [tlc@status](#)
4. [tlc@instatution](#)
5. [tlc@permission](#)

4.9 data/logo.png

[data/logo.png](#) is used to place your logo in the header created by [tlc-article](#).

5 Required Packages

This section documents the dependencies of the required package `tlc-article` has. Package names are listed in alphabetical order. A complete description of each package is found at <http://www.ctan.org/>. At this writing, you can type in the package name and press the search button to learn more about each package.

Name	Description
<code>appendix</code>	The <code>appendix</code> package provides various ways of formatting the titles of appendices. Also (sub)appendices environments are provided that can be used, for example, for per chapter/section appendices.
<code>array</code>	An extended implementation of the <code>array</code> and <code>tabular</code> environments which extends the options for column formats, and provides ‘programmable’ format specifications.
<code>csvsimple</code>	The package provides a simple \LaTeX interface for the processing of files with comma separated values (CSV); it relies on the key value syntax supported by <code>pgfkeys</code> to simplify usage.
<code>enumitem</code>	This package provides user control over the layout of the three basic list environments: <code>enumerate</code> , <code>itemize</code> and <code>description</code> .
<code>fancyhdr</code>	The package provides extensive facilities, both for constructing headers and footers, and for controlling their use (for example, at times when \LaTeX would automatically change the heading style in use).
<code>fontenc</code>	The package allows the user to select font encodings, and for each encoding provides an interface to ‘font-encoding specific’ commands for each font.
<code>geometry</code>	The package provides an easy and flexible user interface to customize page layout, implementing autocentering and auto-balancing mechanisms so that the users have only to give the least description for the page layout.
<code>graphicx</code>	The package builds upon the <code>graphics</code> package, providing a key-value interface for optional arguments to the ‘ <code>includegraphics</code> ’ command. This interface provides facilities that go far beyond what the <code>graphics</code> package offers on its own.
<code>hyperref</code>	The <code>hyperref</code> package is used to handle cross-referencing commands in \LaTeX to produce hypertext links in the document.
<code>lastpage</code>	Reference the number of pages in your \LaTeX document through the introduction of a new label which can be referenced like ‘ <code>gpagerefLastPage</code> ’ to give a reference to the last page of a document.
<code>listings</code>	The package enables the user to typeset programs (programming code) within \LaTeX ; the source code is read directly by \TeX – no frontend processor is needed.
<code>lmodern</code>	Latin modern fonts
<code>longtable</code>	<code>Longtable</code> allows you to write tables that continue to the next page. You can write captions within the table (typically at the start of the table), and headers and trailers for pages of table.

Name	Description
makecell	This package supports common layouts for tabular column heads in whole documents, based on one-column tabular environment.
multicol	Multicol defines a multcols environment which typesets text in multiple columns (up to a maximum of 10), and (by default) balances the end of each column at the end of the environment.
parskip	Simply changing ‘gparskip’ and ‘parindent’ leaves a layout that is untidy; this package (though it is no substitute for a properly-designed class) helps alleviate this untidiness.
pdfscape	The package adds PDF support to the landscape environment of package lscape, by setting the PDF /Rotate page attribute.
pdfpages	This package simplifies the inclusion of external multipage PDF documents in L ^A T _E X documents.
spverbatim	The spverbatim package provides an ‘gspverb’ macro that is analogous to ‘verb’ and an spverbatim environment that is analogous to verbatim with the difference being that ‘spverb’ and spverbatim allow L ^A T _E X to break lines at space characters.
tabularx	The package defines an environment tabularx, an extension of tabular which has an additional column designator, X, which creates a paragraph-like column whose width automatically expands so that the declared width of the environment is filled.
textcomp	The package supports the Text Companion fonts, which provide many text symbols (such as baht, bullet, copyright, musicalnote, onequarter, section, and yen), in the TS1 encoding.
titling	The titling package provides control over the typesetting of the ‘gmaketitle’ command and ‘thanks’ commands, and makes the ‘title’, ‘author’ and ‘date’ information permanently available.
tocloft	Provides control over the typography of the Table of Contents, List of Figures and List of Tables, and the ability to create new ‘List of ...’. The ToC ‘gparskip’ may be changed.
xcolor	The package starts from the basic facilities of the color package, and provides easy driver-independent access to several kinds of color tints, shades, tones, and mixes of arbitrary colors.