

BornAgain Python API

Gennady Pospelov
Jülich Centre for Neutron Science at MLZ

GISAXS2019, BornAgain training session
Hamburg, November 2019

Outline

Introduction to Python API	talking	pyapi01_introduction.pdf
Minimal simulation example	demo	pyapi02_minimal_example.py pyapi02_jupyter_example.ipynb
Simulating lamellar structure	demo	pyapi03_lamellar.py
Modifying lamellar example	task	pyapi04_lamellar_vertical_solution1.py pyapi04_lamellar_vertical_solution2.py

BornAgain Python API

Application Programming Interface (API) can be used to build and run simulations.

Advantages

- Complex sample construction
- Access to features non existing in GUI
- Possibility to reuse code in other projects
- Less back-compatibility problems
- Git based workflow

Minimal simulation example

```
from bornagain import *

# --- sample ---

air = Layer(HomogeneousMaterial("Air", 0.0, 0.0))
substrate = Layer(HomogeneousMaterial("Substrate", 6e-6, 2e-8))


multi_layer = MultiLayer()
multi_layer.addLayer(air)
multi_layer.addLayer(substrate)

# --- simulation ---

simulation = GISASSimulation()
simulation.setDetectorParameters(100, -2.0*deg, 2.0*deg, 100, 0.0*deg, 2.0*deg)
simulation.setBeamParameters(1.0*angstrom, 0.2*deg, 0.0*deg)
simulation.setSample(multi_layer)

# --- run and plot ---

simulation.runSimulation()
plot_simulation_result(simulation.result())
```



GUI equivalent

Minimal simulation example

```
from bornagain import *

# --- sample ---

air = Layer(HomogeneousMaterial("Air", 0.0, 0.0))
substrate = Layer(HomogeneousMaterial("Substrate", 6e-6, 2e-8))


multi_layer = MultiLayer()
multi_layer.addLayer(air)
multi_layer.addLayer(substrate)

# --- simulation ---


simulation = GISASSimulation()
simulation.setDetectorParameters(100, -2.0*deg, 2.0*deg, 100, 0.0*deg, 2.0*deg)
simulation.setBeamParameters(1.0*angstrom, 0.2*deg, 0.0*deg)
simulation.setSample(multi_layer)

# --- run and plot ---

simulation.runSimulation()
plot_simulation_result(simulation.result())
```



GUI equivalent



```
$ python pyapi02_minimal_example.py
```

Demo

Running trivial simulations

```
pyapi02_minimal_example.py  
pyapi02_jupyter_example.ipynb
```

Structuring the code

```
import bornagain as ba


def get_sample():
    multi_layer = ba.MultiLayer()
    ...
    return multi_layer

def get_simulation():
    simulation = ba.GISASSimulation()
    ...
    sample = get_sample()
    simulation.setSample(sample)
    return simulation

def run_simulation():
    simulation = get_simulation()
    simulation.runSimulation()
    return simulation.result()

if __name__ == '__main__':
    result = run_simulation()
    ba.plot_simulation_result(result)
```

Example on sample construction



```
import bornagain as ba
```


```
def get_sample():  
    # defining materials  
    air = ba.HomogeneousMaterial("Air", 0.0, 0.0)  
    substrate = ba.HomogeneousMaterial("Substrate", 6e-6, 2e-8)  
    gold = ba.HomogeneousMaterial("Gold", 6e-4, 2e-8)  
  
    # creating particles  
    cylinder_ff = ba.FormFactorCylinder(5*nm, 5*nm)  
    cylinder = ba.Particle(gold, cylinder_ff)  
  
    layout = ba.ParticleLayout()  
    layout.addParticle(cylinder, 1.0)  
  
    air_layer = ba.Layer(air)  
    air_layer.addLayout(layout)  
    substrate_layer = ba.Layer(substrate)  
  
    multi_layer = ba.MultiLayer()  
    multi_layer.addLayer(air_layer)  
    multi_layer.addLayer(substrate_layer)  
    return multi_layer
```

Material definition

Particle collection

MultiLayer construction

Example on sample construction



```
import bornagain as ba
```

```
def get_materials():  
    # defining materials  
    air = ba.HomogeneousMaterial("Air", 0.0, 0.0)  
    substrate = ba.HomogeneousMaterial("Substrate", 6e-6, 2e-8)  
    gold = ba.HomogeneousMaterial("Gold", 6e-4, 2e-8)  
    return air, substrate, gold
```

Material definition

```
def get_sample():  
    air, substrate, gold = get_materials()  
  
    # creating particles  
    cylinder_ff = ba.FormFactorCylinder(5*nm, 5*nm)  
    cylinder = ba.Particle(gold, cylinder_ff)
```

```
    layout = ba.ParticleLayout()  
    layout.addParticle(cylinder, 1.0)
```

```
    air_layer = ba.Layer(air)  
    air_layer.addLayout(layout)  
    substrate_layer = ba.Layer(substrate)
```

```
    multi_layer = ba.MultiLayer()  
    multi_layer.addLayer(air_layer)  
    multi_layer.addLayer(substrate_layer)  
    return multi_layer
```

Particle collection

MultiLayer construction

Where to start

Python viewer embedded in GUI

The screenshot displays a software interface titled "*Untitled" with a menu bar (File, Settings, Help) and a toolbar (Remove item, Zoom 100%, Material Editor, 3D Viewer). The interface is divided into several panels:

- Left Panel:** A sidebar with icons for Welcome, Instrument, Sample, Import, Simulation, and Jobs. Below these are lists of objects: Prism3, Prism6, Pyramid, Ripple1, Ripple2, Tetrahedron, Truncated cube, Truncated sphere, Truncated spheroid, Transformations (Rotation), Particle assemblies (Core shell particle, Particle Composition, Meso Crystal, Distributed particle), and Standard samples (Cylinder and prisms, Interference 1D paracrystal, Interference 2D paracrystal, Core shell particles).
- Center Panel:** A 3D visualization area showing a particle assembly. It includes two particle objects (Particle0 and Particle1) connected to a central "Particle Layout" object. The layout is a cylinder with a blue and orange gradient. The particles are connected via "transformation" and "interference" nodes.
- Right Panel:** A "Name" panel showing a hierarchical tree structure: example01 > Layer0 > ParticleLayout > Particle0. Below this is a table with "Name" and "Value" columns.


The Python script in the bottom panel defines the sample function:

```
def get_sample():  
    # Defining Materials  
    material_1 = ba.HomogeneousMaterial("example01_Air", 0.0, 0.0)  
    material_2 = ba.HomogeneousMaterial("example01_Particle", 0.0006, 2e-08)  
    material_3 = ba.HomogeneousMaterial("example01_Substrate", 6e-06, 2e-08)  
  
    # Defining Layers  
    layer_1 = ba.Layer(material_1)  
    layer_2 = ba.Layer(material_3)  
  
    # Defining Form Factors  
    formFactor_1 = ba.FormFactorCylinder(5.0*nm, 5.0*nm)  
    formFactor_2 = ba.FormFactorPrism3(10.0*nm, 5.0*nm)  
  
    # Defining Particles  
    particle_1 = ba.Particle(material_2, formFactor_1)  
    particle_2 = ba.Particle(material_2, formFactor_2)  
  
    # Defining Particle Layouts and adding Particles  
    layout_1 = ba.ParticleLayout()
```

Name	Value
Particle0	
Form Fact...	Cylinder
Radius	5.000
Height	5.000
Material	example01_Par...
Abundance	0.500
Position ...	(0, 0, 0)
X	0.000
Y	0.000
Z	0.000

Where to start

Sample model reference on website




Rotated Pyramids


Scattering from a monodisperse distribution of rotated pyramids.

This example illustrates how the in-plane rotation of non-radially symmetric particles influences the scattering pattern.

- The sample is made of pyramids deposited on a substrate.
- Each pyramid is characterized by a squared-base side length of 10 nm, a height of 5 nm, and a base angle α equal to 54.73° .
- These particles are rotated in the (x, y) plane by 45° .
- There is no interference between the scattered waves.
- The wavelength is equal to 1 Å.
- The incident angles are $\alpha_i = 0.2^\circ$ and $\phi_i = 0^\circ$.



Real-space model




Intensity image

```
1  """
2  Rotated pyramids on top of substrate
3  """
4  import bornagain as ba
5  from bornagain import deg, angstrom, nm
6
7
8  def get_sample():
    .....
```


- [-] Documentation
 - [+] Introduction
 - [+] Getting started
 - [+] Using Graphical User Interface
 - [+] Working with Python scripts
 - [-] Sample model reference
 - [-] Embedded particles
 - Cylinders in Born Approximation
 - Cylinders in Distorted Wave Born Approximation
 - Cylinders with size distribution
 - Two types of cylinders with size distribution
 - Rotated Pyramids
 - Cylinders and Prisms
 - All available form factors
 - [+] Layered structures
 - [+] Interference functions
 - [+] Complex shapes
 - [+] Beam and detector
 - [+] Reflectometry
 - [+] Fitting
 - [+] Miscellaneous
 - [+] Getting help
 - [+] Developer's corner

Where to code

- Editor of your choice, Python interpreter
- Integrated development environment (IDE)
 - MS Visual Studio Code, PyCharm
 - Syntax and error highlighting, debug, code navigation
- Jupyter notebooks
 - Quick prototyping




VS Code



PyCharm


Python API technicalities

BornAgain Python API is automatically generated from C++ code



Python API technicalities

BornAgain Python API is automatically generated from C++ code



Python API technicalities


BornAgain Python API is automatically generated from C++ code


*Python API internals
looks unhuman*

```
26223 class Particle(IParticle):
26224     """
26225
26226
26227     A particle with a form factor and refractive index.
26228
26229     C++ includes: Particle.h
26230
26231     """
26232
26233     __swig_setmethods__ = {}
26234     for _s in [IParticle]:
26235         __swig_setmethods__.update(getattr(_s, '__swig_setmethods__', {}))
26236     __setattr__ = lambda self, name, value: __swig_setattr(self, Particle, name, value)
26237     __swig_getmethods__ = {}
26238     for _s in [IParticle]:
26239         __swig_getmethods__.update(getattr(_s, '__swig_getmethods__', {}))
26240     __getattr__ = lambda self, name: __swig_getattr(self, Particle, name)
26241     __repr__ = __swig_repr
26242
26243     def __init__(self, *args):
26244         """
26245         __init__(Particle self) -> Particle
26246         __init__(Particle self, Material material) -> Particle
26247         __init__(Particle self, Material material, IFormFactor form_factor) -> Particle
26248         __init__(Particle self, Material material, IFormFactor form_factor, IRotation rota
26249
26250         Particle::Particle(Material material, const IFormFactor &form_factor, const IRotat
26251
26252         """
26253         this = _libBornAgainCore.new_Particle(*args)
26254         try:
26255             self.this.append(this)
26256         except __builtin__.Exception:
26257             self.this = this
26258
```

Documentation on Python API

C++ API documentation sometimes might help ...

 BornAgain

Home Gallery Download News Documentation Contact About 

Home > Documentation > [Working with Python scripts](#) > Python API

Python API

Simulation scripts interact with the BornAgain core library through an Application Programmer Interface (API). This API consists of numerous classes and their member functions. The primary API is written in the programming language C++. All important classes and their member functions are also available through a Python API.


The [BornAgain C++ User API Reference](#), and the [Comprehensive BornAgain C++ API Reference](#) are always up to date, since they are automatically extracted from the source code (which contains comment lines in the special **Doxygen** format in order to enable this self documentation).

For the moment, we do not dispose of a similarly efficient documentation generator for Python. Therefore, Python users need to refer to the C++ API. Even though Python and C++ have different syntax, it is usually straightforward to infer from the C++ API how the corresponding Python method call will look like.

[<](#) [>](#)

Documentation

- ⊕ Introduction
- ⊕ Getting started
- ⊕ Using Graphical User Interface
- ⊖ Working with Python scripts
 - Setup of a PyCharm project
 - ⊕ Basic simulation tutorial
 - Material types
 - ⊕ Detector types
 - Accessing simulation results
 - Particle positioning
 - Particle rotation
 - Particle composition
 - ⊕ Interference functions
 - Magnetic particles
 - [Python API](#)
 - ⊕ Fitting
- ⊕ Sample model reference
- ⊕ Getting help
- ⊕ Developer's corner



BornAgain C++ API

Simulate and fit neutron and x-ray scattering at grazing incidence

Main Page

User API

Full C++ API

File List

Class List

Class Index

Class Hierarchy

BornAgain

User API

Full C++ API

Class List

Class Index

Class Hierarchy

File List

Search

Class Index

A | B | C | D | E | F | G | H | I | K | L | M | N | O | P | R | S | T | U | V | W | Z

A

AnisoPyramid

AsymRippleBuilder

AttLimits

Attributes

AxesUnitsWrap

UnitConverterSimple::AxisData

AxisInfo

B

BaseMaterialImpl

Basic2DLatticeBuilder

Basic2DParaCrystalBuilder

BasicLattice

BasicVector3D

Beam

Bin1D

Bin1DCVector

Bin1DKVector

BiPyramid

Box

BoxCompositionBuilder

BoxCompositionRotateXBuilder

BoxCompositionRotateYBuilder

BoxCompositionRotateZandYBuilder

BoxCompositionRotateZBuilder

BoxesSquareLatticeBuilder

BoxStackCompositionBuilder

C

IntegratorReal::CallbackHolder

IntegratorMCMiser::CallbackHolder

FitStatus

FixedBinAxis

FootprintFactorGaussian

FootprintFactorSquare

FormatErrorException (Exceptions)

FormFactorAnisoPyramid

FormFactorBox

FormFactorCoherentPart

FormFactorCoherentSum

FormFactorComponents

FormFactorCone

FormFactorCone6

FormFactorCoreShell

FormFactorCrystal

FormFactorCuboctahedron

FormFactorCylinder

FormFactorDebyeBueche

FormFactorDecoratorDebyeWaller

FormFactorDecoratorMaterial

FormFactorDecoratorPositionFactor

FormFactorDecoratorRotation

FormFactorDodecahedron

FormFactorDot

FormFactorDWBA

FormFactorDWBAPol

FormFactorEllipsoidalCylinder

FormFactorFullSphere

FormFactorFullSpheroid

FormFactorGauss

FormFactorHemiEllipsoid

FormFactorIcosahedron

FormFactorLongBox

FormFactorLongBoxGauss

I

IClusteredParticles

IComputation

Icosahedron

IdentityRotation

IDetector

IDetector2D

IDetectorResolution

IDistribution1D

IDistribution1DSampler

IDistribution2DSampler

IFactory

IFootprintFactor

IFormFactor

IFormFactorBorn

IFormFactorDecorator

IFresnelMap

IFTDecayFunction1D

IFTDecayFunction2D

IFTDistribution1D

IFTDistribution2D

IFunctionAdapter (Fit)

IHistogram

IIntensityFunction

IIntensityNormalizer

IInterferenceFunction

IInterferenceFunctionStrategy

ILatticeOrientation

ILayerRTCoefficients

ILayout

IMinimizer

IMultiLayerBuilder

INamed

InfinitePlane

M

MagneticCylindersBuilder

MagneticMaterialImpl

MagneticParticleZeroFieldBuilder

MagneticRotationBuilder

MagneticSpheresBuilder

MagneticSubstrateZeroFieldBuilder

Material

MaterialBySLDImpl

PlainMultiLayerBySLDBuilder::MaterialData

MatrixFresnelMap

MatrixRTCoefficients

MesoCrystal

MesoCrystalBuilder

MillerIndex

MillerIndexOrientation

Minimizer (Fit)

MinimizerCatalogue

MinimizerFactory

MinimizerInfo

MinimizerOptions

MinimizerResult (Fit)

Minuit2Minimizer

MPSimulation

MultiLayer

MultilayerInfo

MultiLayerWithRoughnessBuilder

MultiOption

MultipleLayoutBuilder

BornAgain C++ API

FormFactorBox Class Reference

Hard particles

Description

A rectangular prism (parallelepiped).

Definition at line 23 of file [FormFactorBox.h](#).

► Inheritance diagram for FormFactorBox:

Public Member Functions

	FormFactorBox (double length, double width, double height) Constructor of a rectangular cuboid. More...
FormFactorBox *	clone () const overridefinal Returns a clone of this ISample object.
void	accept (INodeVisitor *visitor) const overridefinal Calls the INodeVisitor 's visit method.
double	getLength () const
double	getHeight () const
double	getWidth () const
double	radialExtension () const overridefinal Returns the (approximate in some cases) radial size of the particle of this form factor's shape. More...
complex_t	evaluate_for_q (cvector_t q) const overridefinal Returns scattering amplitude for complex scattering wavevector $q=k_i-k_f$. More...

BornAgain C++ API

FormFactorBox.cpp

[Go to the documentation of this file.](#)

```
1  // ***** //  
2  //  
3  // BornAgain: simulate and fit scattering at grazing incidence  
4  //  
5  ///! @file      Core/HardParticle/FormFactorBox.cpp  
6  ///! @brief      Implements class FormFactorBox.  
7  ///!  
8  ///! @homepage   http://www.bornagainproject.org  
9  ///! @license     GNU General Public License v3 or higher (see COPYING)  
10 ///! @copyright   Forschungszentrum Jülich GmbH 2018  
11 ///! @authors     Scientific Computing Group at MLZ (see CITATION, AUTHORS)  
12 //  
13 // ***** //  
14 //  
15 #include "FormFactorBox.h"  
16 #include "BornAgainNamespace.h"  
17 #include "Box.h"  
18 #include "MathFunctions.h"  
19 #include "RealParameter.h"  
20 //  
21 ///! Constructor of a rectangular cuboid.  
22 ///! @param length: length of the base in nanometers  
23 ///! @param width: width of the base in nanometers  
24 ///! @param height: height of the box in nanometers  
25 FormFactorBox::FormFactorBox(double length, double width, double height)  
26     : m_length(length), m_width(width), m_height(height)  
27 {  
28     setName(BornAgain::FFBoxType);  
29     registerParameter(BornAgain::Length, &m_length).setUnit(BornAgain::UnitsNm).setNonnegative();  
30     registerParameter(BornAgain::Width, &m_width).setUnit(BornAgain::UnitsNm).setNonnegative();  
31     registerParameter(BornAgain::Height, &m_height).setUnit(BornAgain::UnitsNm).setNonnegative();  
32     onChange();  
33 }  
34 //  
35 complex_t FormFactorBox::evaluate_for_q(cvector_t q) const  
36 {  
37     complex_t qzHdiv2 = m_height/2*q.z();  
38     return m_height*m_length*m_width *  
39         MathFunctions::sinc(m_length/2*q.x()) * MathFunctions::sinc(m_width/2*q.y()) *  
40         MathFunctions::sinc(qzHdiv2) * exp_I(qzHdiv2);  
41 }  
42
```

Features available only in Python

Simulation

- Simulation with distributed parameters
- Some exotic interference functions

Fitting

- Fitting multiple data sets
- Fit along slices
- Third party minimizers
- Custom objective functions

Complex workflows


Demo

Simulating lamellar structure


`pyapi04_lamellar.py`

Simulating lamellar structures

- Represents one of ordered phase of block copolymers during self-assembly
- Alternating layers of different materials in the form of lamellae



<https://wiki.anton-paar.com/>






The resulting GISAS pattern depends on the size and arrangement of lamellar structure

Simulating lamellar structures

Steps to simulate vertically oriented lamellae in BornAgain using PythonAPI

- Define two materials
 - `HomogeneousMaterial`
- Define two boxes
 - `FormFactorBox`
- Define lamellar structure as stack of boxes
 - `ParticleComposition`
- Add rotation around Z
 - `RotationZ`
- Apply rotation angle distribution 0-180
 - `ParticleDistribution`



Simulating lamellar structures

11.1.2 Box (cuboid)

Real-space geometry





Figure 11.5: A rectangular cuboid.

Syntax and parameters


```
FormFactorBox(double length, double width, double height)
```

```
def get_horizontal_lamellar():
    mat_a = ba.HomogeneousMaterial("PTFE", 5.20508729E-6, 1.96944292E-8)
    mat_b = ba.HomogeneousMaterial("HMDSO", 2.0888308E-6, 1.32605651E-8)
    length = 30*nm
    width_a = 4*nm
    width_b = 8*nm
    height = 30*nm
    nstack = 5
    stack = ba.ParticleComposition()
    for i in range(0, nstack):
        box_a = ba.Particle(mat_a, ba.FormFactorBox(length, width_a, height))
        box_b = ba.Particle(mat_b, ba.FormFactorBox(length, width_b, height))
        stack.addParticle(box_a, ba.kvector_t(0.0, i*(width_a+width_b), 0.0))
        stack.addParticle(box_b, ba.kvector_t(0.0, (width_a + width_b)/2. + i*(width_a+width_b), 0.0))
```



Simulating lamellar structures

Results




$$2 \cdot \pi / dx = 12.0 \text{ nm}$$

the value coincide with lamellar period
which was defined in simulation script

Simulating lamellar structures

If we would have to do it in GUI ...



Task

Modifying lamellar example

`pyapi04_lamellar_vertical_solution1.py`

`pyapi04_lamellar_vertical_solution2.py`

Modifying lamellar example

Task: make lamellar parallel to surface

