

NP Friend List2 Dialog Overview

© 2014 Sony Computer Entertainment Inc.
All Rights Reserved.
SCE Confidential

Table of Contents

1 Library Overview.....	3
Purpose and Features.....	3
Main Features	3
Embedding into a Program	3
Sample Program	3
Reference Material	3
2 Using the Library	4
Conditions for Use.....	4
Libraries to be Loaded and Initialized Beforehand.....	4
Basic Usage Procedure	4
3 Reference Information.....	7
Display of the Friends List.....	7
Info Bar, Background Color and Dimmer	7
4 Notes	8
Limitations	8

1 Library Overview

Purpose and Features

The NP Friend List2 Dialog library displays a friends list of maximum 2000 players and obtains the NP ID of a player selected by the user.

The NP Friend List2 Dialog library is one feature of the Common Dialog library and encapsulates GUI display and the handling of user operation.

Main Features

The following are the main features provided by the NP Friend List2 Dialog library.

- Features to display a maximum of 2000 friends and to obtain the NP ID of a player selected by the user

Embedding into a Program

Include `np_friendlist2_dialog.h` in the source program.

The PRX module need not be loaded.

Upon building the program, link `libSceCommonDialog_stub.a`.

Sample Program

A sample program that uses the NP Friend List2 Dialog library is provided as follows.

`sample_code/system/api_np_friendlist2_dialog/`

This sample calls the NP Friend List2 dialog and displays the profile of the player selected by the user in the NP Profile dialog.

Reference Material

For common limitations, specifications, etc., of the Common Dialog library, refer to the following document.

- Common Dialog Overview

2 Using the Library

Conditions for Use

To use the NP Friend List2 Dialog library, the service state of the NP library must be set to the signed-in state in advance using the Network Check dialog. Also note that a network connection environment is necessary.

To display the online state of a friend, the Network Check dialog must be started in the PSNSM online mode and the service state of the NP library must be set to the online state.

For details, refer to the "Network Overview" document.

Moreover, when calling the NP Friend List2 dialog, the available spaces in the memory pools of libssl and libhttp must at least be the required sizes. These actually required sizes are indicated by the following macros of `sdk/target/include/np_friendlist2_dialog.h`.

- `SCE_NP_FRIENDLIST2_DIALOG_LEAST_SSL_POOL_SIZE`
Size required for the memory pool of libssl
- `SCE_NP_FRIENDLIST2_DIALOG_LEAST_HTTP_POOL_SIZE`
Size required for the memory pool of libhttp

There are cases when the available memory pool spaces of libssl and libhttp differ before and after the NP Friend List2 dialog operation; this is not a problem.

Libraries to be Loaded and Initialized Beforehand

To use the NP Friend List2 Dialog library, the PRX module must be loaded in advance by calling the following APIs.

- `sceSysmoduleLoadModule(SCE_SYSMODULE_HTTPS)`
- `sceSysmoduleLoadModule(SCE_SYSMODULE_NP_UTILITY)`


Moreover, the following initializing APIs of libssl, libhttp, and the NP library must be called in advance.

- `sceSslInit()`
- `sceHttpInit()`
- `sceNpInit()`

Basic Usage Procedure

The basic procedure to call the NP Friend List2 dialog is described below. The processing flow is outlined as follows.

- (1) Set parameters to the variables of the `SceNpFriendList2DialogParam` type
- (2) Display the dialog
- (3) Monitor the dialog state
- (4) Obtain the call result
- (5) Terminate the dialog

Figure 1 Basic Processing Procedure**(1) Set parameters**

Prepare a variable of the `SceNpFriendList2DialogParam` type. After initializing with `sceNpFriendList2DialogParamInit()`, set the calling mode (*mode*) and the default sort method (*defaultSort*).

(2) Display the dialog

Call the NP Friend List2 dialog feature with `sceNpFriendList2DialogInit()`. Specify the `SceNpFriendList2DialogParam` type variable set beforehand as the argument. When the call succeeds, the friends list will be displayed onscreen and the operation status will transition to SCE_COMMON_DIALOG_STATUS_RUNNING.

(3) Wait for a response from the dialog

Call `sceNpFriendList2DialogGetStatus()` to poll the operation status of the NP Friend List2 dialog in each frame.

Note

While the operation status is SCE_COMMON_DIALOG_STATUS_RUNNING, `sceCommonDialogUpdate()` must be called at every frame. For details, refer to the "Common Dialog Overview" document.

(4) Obtain the call result

When the NP Friend List2 dialog is closed, the operation status will transition to `SCE_COMMON_DIALOG_STATUS_FINISHED`.

When the operation status changes to `SCE_COMMON_DIALOG_STATUS_FINISHED`, the call result can be obtained with `sceNpFriendList2DialogGetResult()`. The result that can be obtained includes the selected result (whether the user made a selection or canceled operation), and the NP ID of the selected player. The NP ID of the selected player will be stored in `npId` of `SceNpFriendList2DialogResult`.

(5) Terminate the dialog

When the operation status becomes `SCE_COMMON_DIALOG_STATUS_FINISHED`, call `sceNpFriendList2DialogTerm()` to terminate processing. As a result, the resources allocated upon calling the NP Friend List2 dialog feature will be released and the operation status will transition to `SCE_COMMON_DIALOG_STATUS_NONE`.

Aborting Processing

When aborting the display of the NP Friend List2 dialog from the application side (when terminating the application, for example), call `sceNpFriendList2DialogAbort()`. Processing to abort display will be started and the operation status will change to `SCE_COMMON_DIALOG_STATUS_FINISHED` upon completion of the abort processing. In this case, too, the call result can be obtained with `sceNpFriendList2DialogGetResult()`. `SCE_COMMON_DIALOG_RESULT_ABORTED` is returned as the call result.

Main APIs Used for Basic Processing


API	Description
<code>SceNpFriendList2DialogParam</code>	NP Friend List2 dialog call parameters
<code>sceNpFriendList2DialogParamInit()</code>	Macro to initialize call parameters
<code>sceNpFriendList2DialogInit()</code>	Calls the NP Friend List2 dialog
<code>sceNpFriendList2DialogGetStatus()</code>	Obtains operation status of the NP Friend List2 dialog
<code>SceNpFriendList2DialogResult</code>	Structure for storing the NP Friend List2 dialog call result
<code>sceNpFriendList2DialogGetResult()</code>	Obtains call result of the NP Friend List2 dialog
<code>sceNpFriendList2DialogTerm()</code>	Terminates the call of the NP Friend List2 dialog
<code>sceNpFriendList2DialogAbort()</code>	Aborts the call of the NP Friend List2 dialog

3 Reference Information

Display of the Friends List

When the call of the NP Friend List2 dialog feature succeeds, the friends list will be displayed as follows.

Figure 2 Friends List



Info Bar, Background Color and Dimmer

In the NP Friend List2 Dialog library, an info bar is displayed to inform the user that communication is in progress. This info bar is displayed regardless of the value specified to the *commonParam.infobarParam* argument relating to the info bar of the *ScenpFriendList2DialogParam* structure.

Also, the background color and dimmer of the NP Friend List2 dialog can be specified using the common parameters for the Common dialogs. If no value is specified, the system default value (recommended) will be applied. For details, refer to the "Common Dialog Reference" document.

SCE CONFIDENTIAL

4 Notes

Limitations

Common dialog limitations apply.

000004892117