Hybrid Mode Integration Guide

API Contract & Optimization Process

Traigent SDK v1.0

February 10, 2026

Confidential — for integration partners only

Contents

1 Overview **2**
- 1.1 What you implement . . . 2
- 1.2 What Traigent provides . . . 2

2 Optimization Process **2**

3 Privacy-Preserving Mode **2**

4 Authentication (Optional) **3**

5 Endpoints **3**
- 5.1 GET /capabilities *(required)* . . . 3
  - 5.1.1 Response (200) . . . 3
- 5.2 GET /config-space *(required)* . . . 3
  - 5.2.1 Response (200) . . . 3
  - 5.2.2 Tunable Definition . . . 4
  - 5.2.3 Tunable Types . . . 4
- 5.3 POST /execute *(required)* . . . 4
  - 5.3.1 Request . . . 4
  - 5.3.2 Response (200) . . . 5
  - 5.3.3 Operational Metrics . . . 6
- 5.4 POST /evaluate *(optional)* . . . 6
  - 5.4.1 Request . . . 6
  - 5.4.2 Response (200) . . . 7
- 5.5 GET /health *(optional)* . . . 7
- 5.6 POST /keep-alive *(optional)* . . . 8

6 Error Responses **8**

7 Idempotency **8**

8 Accompanying Specifications **8**
- 8.1 Generating client stubs . . . 8

9 Quick Reference **9**

Overview

Traigent Hybrid Mode enables zero-code optimization of external agentic services. Your service exposes a lightweight REST API; Traigent's optimizer discovers tunable parameters, explores configurations, and converges on an optimal setting—all without accessing your underlying data.

What you implement

A REST service with the prefix `/traigent/v1/` exposing the endpoints listed in Section 5. Three endpoints are required; two are optional.

What Traigent provides

- Automatic parameter-space exploration (NSGA-II, Bayesian, grid).
- Multi-objective optimization (accuracy, cost, latency, or any custom metric).
- Budget controls (max trials, max spend, wall-clock limits).
- Statistical promotion via ε-Pareto dominance testing.

Optimization Process

The optimization loop follows four phases, repeated until a budget or convergence criterion is met.

1. **Discover** — Traigent calls `GET /capabilities` and `GET /config-space` to learn which parameters are tunable, their domains, and declared objectives.
2. **Execute** — For each trial, Traigent posts a candidate configuration and a batch of inputs to `POST /execute`. Your service runs the agent with those settings and returns per-input outputs plus operational metrics (cost, latency, tokens).
3. **Evaluate** — If a separate evaluation endpoint is available, Traigent posts output–target pairs to `POST /evaluate`. Your service scores outputs and returns quality metrics (accuracy, relevance, etc.).
4. **Optimize** — Traigent aggregates metrics, updates its surrogate model, and selects the next configuration to try. After all trials complete, the optimizer ranks configurations by ε-Pareto dominance and reports the best.

Phase	Direction	Endpoint
Discover	Traigent → Service	`GET /capabilities`, `GET /config-space`
Execute	Traigent → Service	`POST /execute`
Evaluate	Traigent → Service	`POST /evaluate`
Optimize	Internal	(no API call)

Privacy-Preserving Mode

Privacy is the default. Only configuration values and numeric metrics are observed by Traigent. Input data, output content, and evaluation targets are **never** transmitted.

Data	Observed by Traigent
Tunable definitions (config-space)	Yes
Configuration values per trial	Yes
Operational metrics (cost, latency, tokens)	Yes
Quality metrics (accuracy, relevance, etc.)	Yes
Input data content	**No** (only IDs)
Output data content	**No** (only IDs)
Target / expected output content	**No** (only IDs)

Your service stores data locally and uses opaque identifiers (`input_id`, `output_id`, `target_id`) in API exchanges. If privacy is not a concern, you may include full content in `data`, `output`, and `target` fields. Both modes can be mixed.

Authentication (Optional)

If your service requires authentication, accept a standard `Authorization` header (e.g. bearer token). Configure the Traigent SDK client with:

```
hybrid_api_auth_header = "Bearer <token>"
```

All endpoints must consistently enforce the same authentication policy.

Endpoints

All paths are prefixed with `/traigent/v1/`.

GET /capabilities *(required)*

Returns service capabilities for the initial handshake.

Response (200)

```
{
  "version": "1.0",
  "supports_evaluate": true ,
  "supports_keep_alive": false ,
  "supports_streaming": false ,
  "max_batch_size": 100,
  "max_payload_bytes": null
}
```

Field	Type	Req.	Description
`version`	string	**Yes**	API version (currently `"1.0"`)
`supports_evaluate`	boolean	**No**	Separate `/evaluate` endpoint available (default: `true`)
`supports_keep_alive`	boolean	**No**	Session heartbeat supported
`supports_streaming`	boolean	**No**	Streaming responses supported
`max_batch_size`	integer	**No**	Max inputs per execute request (default: 100)
`max_payload_bytes`	integer	**No**	Max request payload size (`null` = unlimited)

GET /config-space *(required)*

Returns tunable variable definitions. Traigent uses these to build the parameter search space.

Response (200)

```
{
  "schema_version": "0.9",
  "capability_id": "my_agent",
  "tunables": [
    {
      "name": "model",
      "type": "enum",
      "domain": {"values": ["gpt-4o", "claude-3-sonnet", "llama-70b"]},
```

```
      "default": "gpt-4o"
    },
    {
      "name": "temperature",
      "type": "float",
      "domain": {"range": [0.0, 2.0], "resolution": 0.1},
      "default": 0.7
    }
  ],
  "objectives": [
    {"name": "accuracy", "direction": "maximize", "weight": 2.0},
    {"name": "cost",     "direction": "minimize", "weight": 1.0}
  ]
}
```

Field	Type	Req.	Description
`schema_version`	string	**Yes**	TVL schema version (currently `"0.9"`)
`capability_id`	string	**Yes**	Unique identifier for this capability
`tunables`	array	**Yes**	List of tunable definitions (see below)
`constraints`	object	**No**	Structural / behavioral constraints
`objectives`	array	**No**	Objective definitions (name, direction, weight)
`exploration`	object	**No**	Strategy, budgets, and convergence criteria
`promotion_policy`	object	**No**	ε-Pareto promotion policy
`defaults`	object	**No**	Default configuration values
`measures`	array	**No**	Declared metric names produced by the service

Tunable Definition

Each element of the `tunables` array describes one parameter:

Field	Type	Req.	Description
`name`	string	**Yes**	Variable name (valid Python identifier)
`type`	string	**Yes**	One of: `enum`, `float`, `int`, `bool`, `str`
`domain`	object	Conditional	Domain specification (required for all types except `bool`)
`default`	any	**No**	Default value
`agent`	string	**No**	Agent name for multi-agent grouping

Tunable Types

Type	Domain format	Example
`enum`	`{"values": [...]}`	`["gpt-4o", "claude-3-sonnet"]`
`float`	`{"range": [min, max], "resolution": step}`	`[0.0, 2.0]`, step 0.1
`int`	`{"range": [min, max]}`	`[100, 4096]`
`bool`	N/A	`true` / `false`
`str`	`{"values": [...]}`	`["concise", "detailed"]`

POST /execute *(required)*

Execute the agent with a specific configuration on a batch of inputs.

Request

```
{
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "capability_id": "my_agent",
```

```
  "config": {
    "model": "gpt-4o",
    "temperature": 0.5,
    "max_tokens": 1024
  },
  "inputs": [
    {"input_id": "ex_001", "data": {"query": "What is machine learning?
        "}},
    {"input_id": "ex_002", "data": {"query": "Explain neural networks"
        }}
  ],
  "timeout_ms": 30000
}
```

Field	Type	Req.	Description
`request_id`	string (UUID)	**No**	Idempotency key (auto-generated if omitted)
`capability_id`	string	**Yes**	Capability to invoke
`config`	object	**Yes**	Configuration parameters (tunable values)
`inputs`	array	**Yes**	Input examples to process
`session_id`	string	**No**	Session ID for stateful agents
`batch_options`	object	**No**	Parallelism, fail-fast, per-item timeout
`timeout_ms`	integer	**No**	Request timeout in ms (default: 30 000)

Each **Input Item** contains:

`input_id`	string	**Yes**	Unique identifier for this input
`data`	object	**No**	Input data (omit in privacy-preserving mode)

Response (200)

```
{
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "execution_id": "exec_123456",
  "status": "completed",
  "outputs": [
    {
      "input_id": "ex_001",
      "output": {"response": "Machine learning is a subset of AI..."},
      "cost_usd": 0.002,
      "latency_ms": 150
    }
  ],
  "operational_metrics": {
    "total_cost_usd": 0.005,
    "latency_ms": 330,
    "tokens_used": 450
  }
}
```

Field	Type	Req.	Description
`request_id`	string	**Yes**	Echoed request ID for correlation
`execution_id`	string	**Yes**	Unique execution ID (referenced by `/evaluate`)
`status`	string	**Yes**	`"completed"`, `"partial"`, or `"failed"`
`outputs`	array	**Yes**	Per-input results (see Output Item below)
`operational_metrics`	object	**Yes**	Aggregate operational metrics
`quality_metrics`	object	**No**	Quality metrics (combined execute+evaluate mode)
`session_id`	string	**No**	Session ID for stateful agents
`error`	object	**No**	Error details if `status` is `"failed"` or `"partial"`

Each **Output Item** contains:

`input_id`	string	**Yes**	Matching input identifier
`output`	object	**No**	Agent output (omit in privacy-preserving mode)
`output_id`	string	**No**	Output identifier (privacy-preserving mode)
`cost_usd`	number	**No**	Cost for this input
`latency_ms`	number	**No**	Latency for this input
`metrics`	object	**No**	Per-input quality metrics (combined mode)
`error`	string	**No**	Error message for partial failures

Operational Metrics

`total_cost_usd` is the only required field. Additional recommended and custom metrics may be included:

Field	Type	Description
`total_cost_usd`	number	**Required.** Total cost in USD
`latency_ms`	number	Recommended. Total latency in milliseconds
`tokens_input`	integer	Input token count
`tokens_output`	integer	Output token count
`cache_hit_rate`	number	Cache hit ratio (0.0–1.0)
`retry_count`	integer	Number of retries

Any additional numeric, string, or boolean fields are accepted.

POST /evaluate *(optional)*

Evaluate outputs against expected targets. Only required when `supports_evaluate` is `true` in capabilities.

Request

```
{
  "request_id": "660e8400-e29b-41d4-a716-446655440001",
  "capability_id": "my_agent",
  "execution_id": "exec_123456",
  "evaluations": [
    {
      "input_id": "ex_001",
      "output": {"response": "Machine learning is a subset of AI..."},
      "target": {"expected": "Machine learning is a branch of AI..."}
    }
  ]
}
```

Field	Type	Req.	Description
`request_id`	string (UUID)	**No**	Idempotency key
`capability_id`	string	**Yes**	Evaluation capability identifier
`execution_id`	string	**No**	Reference to previous execute
`evaluations`	array	**No**	Output–target pairs
`config`	object	**No**	Evaluation parameters
`session_id`	string	**No**	Session ID for stateful agents

Each **Evaluation Item** contains:

`input_id`	string	**Yes**	Matching input identifier
`output`	object	**No**	Agent output (or use `output_id`)
`output_id`	string	**No**	Output reference (privacy-preserving mode)
`target`	object	**No**	Expected output (or use `target_id`)
`target_id`	string	**No**	Target reference (privacy-preserving mode)

Response (200)

```
{
  "request_id": "660e8400-e29b-41d4-a716-446655440001",
  "status": "completed",
  "results": [
    {
      "input_id": "ex_001",
      "metrics": {"accuracy": 0.92, "relevance": 0.88, "fluency": 0.95}
    }
  ],
  "aggregate_metrics": {
    "accuracy":  {"mean": 0.92, "std": 0.05, "n": 100},
    "relevance": {"mean": 0.88, "std": 0.03, "n": 100}
  }
}
```

Field	Type	Req.	Description
`request_id`	string	**Yes**	Echoed request ID
`status`	string	**Yes**	`"completed"`, `"partial"`, or `"failed"`
`results`	array	**Yes**	Per-example evaluation results
`aggregate_metrics`	object	**Yes**	Aggregated statistics per metric
`error`	object	**No**	Error details for partial/failed evaluations

Each **Result Item**: `input_id` (required), `metrics` (required object of numeric quality scores), `error` (optional string).

Each **Aggregate Metric**: `mean` (number), `std` (number), `n` (integer).

GET /health *(optional)*

Health check for monitoring and load-balancer probes.

Field	Type	Req.	Description
`status`	string	**Yes**	`"healthy"`, `"degraded"`, or `"unhealthy"`
`version`	string	**No**	Service version
`uptime_seconds`	number	**No**	Uptime in seconds
`details`	object	**No**	Additional health details

POST /keep-alive *(optional)*

Session heartbeat for stateful agents. Only implement if `supports_keep_alive` is `true` in capabilities.

Request: `{"session_id": "session_abc123"}`

200 Response: `{"status": "alive", "session_id": "session_abc123"}`

404 Response: `{"error": {"code": "SESSION_NOT_FOUND", "message": "..."}}`

Error Responses

All endpoints must return structured errors with appropriate HTTP status codes.

Status	Description
200	Success
400	Bad Request (invalid input, capability mismatch)
401	Unauthorized
404	Not Found (unknown route or session)
429	Too Many Requests (rate limited)
500	Internal Server Error
503	Service Unavailable

Error body format:

```
{
  "error": {
    "code": "INVALID_CONFIG",
    "message": "Unknown tunable: invalid_param",
    "details": {"invalid_params": ["invalid_param"]}
  }
}
```

Idempotency

All `POST` requests accept a `request_id` field (UUID). If the same `request_id` is received again, the service may return the cached response. This enables safe retries without duplicate processing.

Accompanying Specifications

The following machine-readable files are provided alongside this document and constitute the normative contract:

File	Format	Usage
`hybrid-mode-openapi.yaml`	OpenAPI 3.0.3	Client/server codegen, request/response validation, Swagger UI
`hybrid-mode-schemas.json`	JSON Schema (Draft 2020-12)	Standalone DTO validation
`hybrid-mode-api-contract.md`	Markdown	Full endpoint reference with examples
`hybrid-mode-client-guide.md`	Markdown	Implementation patterns, code samples, troubleshooting

Generating client stubs

```
// Python
openapi-generator generate -i hybrid-mode-openapi.yaml -g python -o client/

// TypeScript
openapi-generator generate -i hybrid-mode-openapi.yaml -g typescript-fetch -o
    client/
```

Quick Reference

Method	Path	Req.	Purpose
GET	/traigent/v1/capabilities	**Yes**	Service handshake
GET	/traigent/v1/config-space	**Yes**	Tunable definitions
POST	/traigent/v1/execute	**Yes**	Run agent with config
POST	/traigent/v1/evaluate	**No**	Score outputs vs. targets
GET	/traigent/v1/health	**No**	Health check
POST	/traigent/v1/keep-alive	**No**	Session heartbeat